



US008979746B2

(12) **United States Patent**
Kim

(10) **Patent No.:** **US 8,979,746 B2**
(45) **Date of Patent:** **Mar. 17, 2015**

(54) **RETRACTION DEVICE FOR LAPAROSCOPY**

(56) **References Cited**

(75) Inventor: **Jae-Hwang Kim**, Daegu (KR)

U.S. PATENT DOCUMENTS

(73) Assignees: **Jae-Hwang Kim**, Daegu (KR); **Dalim Corporation**, Seoul (KR)

5,312,422 A * 5/1994 Trott 606/144
2011/0082347 A1 * 4/2011 Okoniewski 600/227
2013/0066155 A1 * 3/2013 Keating et al. 600/204

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 713 days.

FOREIGN PATENT DOCUMENTS

KR 10-2011-0120767 A 11/2011
WO WO 2011022787 A1 * 3/2011

* cited by examiner

Primary Examiner — Jerry Cumberledge

Assistant Examiner — Nicholas Plionis

(74) *Attorney, Agent, or Firm* — Novick, Kim & Lee, PLLC;
Jae Youn Kim

(21) Appl. No.: **13/158,938**

(22) Filed: **Jun. 13, 2011**

(65) **Prior Publication Data**

US 2012/0316593 A1 Dec. 13, 2012

(51) **Int. Cl.**

A61B 1/32 (2006.01)

A61B 17/02 (2006.01)

A61B 17/04 (2006.01)

A61B 17/28 (2006.01)

A61B 17/00 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/0218** (2013.01); **A61B 17/0487**
(2013.01); **A61B 17/2812** (2013.01); **A61B**
2017/00349 (2013.01); **A61B 2017/0225**
(2013.01); **A61B 2017/0454** (2013.01)

USPC **600/204**; **600/208**

(58) **Field of Classification Search**

USPC **600/204**, **208**
See application file for complete search history.

ABSTRACT

Disclosed herein is a retraction device for laparoscopy in which a trocar needle including latching grooves formed at the side of the lower end thereof is inserted into a trocar tube, both ends of which are opened, to form a laparoscopic platform, the laparoscopic platform pierces an abdominal wall and the trocar needle is pushed into an abdominal cavity so that the latching grooves are exposed to the outside of the trocar tube, sutures connected to tissue retractors retracting tissues are hung on the latching grooves, and then the trocar needle of the laparoscopic platform is drawn upwards so that the latching grooves are inserted back into the trocar tube to fix the tissue retractors to the laparoscopic platform. The retraction device for laparoscopy prevents the tissues from being unnecessarily damaged due to retraction and facilitates convenient retraction of the tissues without the help of assistant's two hands.

7 Claims, 11 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



RETRACTION DEVICE FOR LAPAROSCOPY**BACKGROUND OF THE INVENTION****1. Field of the Invention**

The present invention relates to a retraction device for laparoscopy which retracts tissues without the help of assistant's hands during laparoscopy.

2. Description of the Related Art

Recently, laparoscopy, which is performed within the abdomen using a subminiature video camera and various surgical tools inserted into the abdomen through plural small incisions of usually 0.5-1.5 cm, is being applied to a wide variety of diseases affecting organs in the abdominal cavity.

Such laparoscopy uses a small incision size as compared to traditional laparotomy, thus having advantages, such as reduced surgical pain, rapid recovery and minimal or no scarring.

The above laparoscopy requires retraction of a tissue so as to assist in surgery. As one example, laparoscopic anterior resection of a patient suffering lesion of the rectum and colon requires retraction of the rectum when dissection of the rectum is performed after dissection of the sigmoid colon.

Dissection of the rectum which is generally performed is achieved by a method in which an assistant draws the intestinal tract or the mesentery with laparoscopic clamps, or binds and draws the rectum with a thin string.

However, such a method requires assistant's one hand or two hands to draw the rectum and thus has a drawback in that the assistant cannot help a main operator. Particularly, when an experienced doctor grants a right as a main operator to a beginning surgeon and the experienced doctor serves as an assistant, drawing of the rectum with assistant's two hands may cause a dangerous situation.

As another example, laparoscopic low anterior resection of a female patient suffering rectal cancer requires retraction of the uterus to the abdominal wall. In this case, a method in which a needle connected to a suture is inserted into the abdominal cavity through the abdominal wall from the outside, passes through the uterus, exits the abdominal cavity through the abdominal wall, and is then ligated is mainly used.

However, such a method requires penetration of the abdominal wall twice and easily causes tearing of the uterus due to the pressure of the suture, thereby increasing a possibility of uterine hemorrhage.

Therefore, a retraction device which facilitates convenient retraction of tissues without damage to the tissues and frees assistant's two hands during surgery so as to enable the assistant to more actively assist in surgery is necessary.

SUMMARY OF THE INVENTION

Therefore, the present invention has been made in view of the above problems, and it is an object of the present invention to provide a retraction device which prevents tissues from being unnecessarily damaged due to retraction, facilitates convenient retraction of the tissues without the help of assistant's two hands, enables an assistant to more actively assist in surgery, and assures a wide field of surgical vision.

In accordance with an aspect of the present invention, the above and other objects can be accomplished by the provision of a retraction device for laparoscopy in which a trocar needle including latching grooves formed at the side of the lower end thereof is inserted into a trocar tube, both ends of which are opened, to form a laparoscopic platform, the laparoscopic platform pierces an abdominal wall and the trocar needle is

pushed into an abdominal cavity so that the latching grooves are exposed to the outside of the trocar tube, sutures connected to tissue retractors retracting tissues are hung on the latching grooves, and then the trocar needle of the laparoscopic platform is drawn upwards so that the latching grooves are inserted back into the trocar tube to fix the tissue retractors to the laparoscopic platform.

In accordance with another aspect of the present invention, there is provided a retraction device for laparoscopy in which a pair of clamps provided with interface surfaces having prominence and depression shapes corresponding to each other is formed at left and right forceps parts to form fixing forceps, a tap is attached to the end of a suture provided with a needle to form a tap type retractor, the needle of the tap type retractor penetrates one side of a tissue so that the tap is supported by the outer wall of the tissue, the needle having penetrated the tissue passes through an abdominal wall and exits an abdominal cavity, the suture of the tap type retractor is inserted between the interface surfaces of the clamps of the fixing forceps located on the upper surface of the abdominal wall, and then the clamps are moved towards each other to firmly fix the tap type retractor.

In accordance with yet another aspect of the present invention, there is provided a retraction device for laparoscopy in which a pair of clamps provided with interface surfaces having prominence and depression shapes corresponding to each other is formed at left and right forceps parts to form fixing forceps, a toothed part with latching protrusions arranged in a line and an insertion hole into which one of the latching protrusions is inserted are formed at one end and the other end of a band-shaped main body to form a band type retractor, a suture provided with a needle is connected to the frontmost latching protrusion of the toothed part of the band type retractor, the band type retractor surrounds the outer surface of a tissue, one of the latching protrusions is inserted into the insertion hole, and the needle connected to the band type retractor passes through an abdominal wall and exits an abdominal cavity, the suture of the band type retractor is inserted between the interface surfaces of the clamps of the fixing forceps located on the upper surface of the abdominal wall, and then the clamps are moved towards each other to firmly fix the band type retractor.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects, features and other advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIG. 1 is a perspective view of a retraction device in accordance with one embodiment of the present invention;

FIG. 2 is a perspective view of a laparoscopic platform in accordance with the embodiment of the present invention;

FIG. 3 is a perspective view of a band type retractor in accordance with the embodiment of the present invention;

FIG. 4 is a perspective view of a tap type retractor in accordance with the embodiment of the present invention;

FIGS. 5(a) to 7(c) are views illustrating various states of tissues retracted using the retraction device in accordance with the embodiment of the present invention;

FIGS. 8(a) and 8(b) are perspective views of fixing forceps in accordance with another embodiment of the present invention;

FIGS. 9(a) to 9(c) are perspective views illustrating states of a tap type retractor fixed to the fixing forceps in accordance with the embodiment of the present invention;

FIGS. 10(a) to 10(c) are perspective views illustrating states of a band type retractor fixed to the fixing forceps in accordance with the embodiment of the present invention; and

FIGS. 11(a) to 11(c) are perspective views illustrating change of the retracting direction of a tissue using the retraction devices in accordance with the embodiments of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Now, preferred embodiments of the present invention will be described in detail with reference to the annexed drawings.

The present invention provides a retraction device for laparoscopy in which a laparoscopic platform fixed to an abdominal wall is installed within an abdominal cavity or fixing forceps are installed at the outside of the abdominal cavity, a band type retractor or a tap type retractor simply retracts a tissue, and then such a retractor is fixed to the laparoscopic platform or the fixing forceps so as to facilitate convenient retraction of the tissue without the help of assistant's two hands during surgery and minimize unnecessary damage to the tissue during retraction.

FIG. 1 is a perspective view of a retraction device in accordance with one embodiment of the present invention, FIG. 2 is a perspective view of a laparoscopic platform in accordance with the embodiment of the present invention, FIG. 3 is a perspective view of a band type retractor in accordance with the embodiment of the present invention, FIG. 4 is a perspective view of a tap type retractor in accordance with the embodiment of the present invention, FIGS. 5(a) to 7(c) are views illustrating various states of tissues retracted using the retraction device in accordance with the embodiment of the present invention, FIGS. 8(a) and 8(b) are perspective views of fixing forceps in accordance with another embodiment of the present invention, FIGS. 9(a) to 9(c) are perspective views illustrating states of a tap type retractor fixed to the fixing forceps in accordance with the embodiment of the present invention, FIGS. 10(a) to 10(c) are perspective views illustrating states of a band type retractor fixed to the fixing forceps in accordance with the embodiment of the present invention, and FIGS. 11(a) to 11(c) are perspective views illustrating change of the retracting direction of a tissue using the retraction devices in accordance with the embodiments of the present invention.

A retraction device 8 for laparoscopy in accordance with one embodiment of the present invention is used to fix tissue retractors 20 and 30 retracting tissues 5 and 6 within an abdominal cavity 4.

The retraction device 8 for laparoscopy in accordance with the embodiment of the present invention shown in FIG. 1 includes a laparoscopic platform 10 penetrating an abdominal wall 2, and the tissue retractors 20 and 30 retracting the tissues 5 and 6 and fixed to the laparoscopic platform 10.

As shown in FIG. 2, the laparoscopic platform 10 in accordance with the embodiment of the present invention is configured such that a trocar needle 12 provided with latching grooves 16 formed thereon is inserted into a trocar tube 14 provided with both opened ends. The tip of the trocar needle 12 of the laparoscopic platform 10 is sharp, and the plural latching grooves 16 are formed on the side wall of the lower end of the trocar needle 12. The trocar needle 12 has a larger length than the trocar tube 14 such that, when the trocar needle 12 is inserted into the trocar tube 14, the latching grooves 16 may protrude from the trocar tube 14. The latching grooves 16 of the trocar needle 12 may be arranged in a line on the side wall of the lower end of the trocar needle 12.

Sutures 26 and 40 connected to the tissue retractors 20 and 30 retracting the tissues 5 and 6 are hung on the latching grooves 16 of the trocar needle 12.

The trocar tube 14 of the laparoscopic platform 10 has a diameter such that the trocar needle 12 may be inserted into the trocar tube 14, and both ends of the trocar tube 14 are opened. The lower end of the trocar tube 14 is level so as not to cause tissue damage.

Head parts 17 and 18 having larger diameters than the body parts of the trocar needle 12 and the trocar tube 14 are respectively formed at the upper ends of the trocar needle 12 and the trocar tube 14. The diameter of the head part 18 of the trocar tube 14 is larger than the diameter of the head part 17 of the trocar needle 12. The head part 18 of the trocar tube 14 supports the head part 17 of the trocar needle 12, thus serving as a latching protrusion of the trocar needle 12. Further, the head part 17 of the trocar needle 12 serves as a handle, thus facilitating pushing or drawing of the trocar needle 12.

After the laparoscopic platform 10 pierces the abdominal wall 2, the trocar needle 12 is pushed into the abdominal cavity 4 so that the latching grooves 16 formed at the lower end of the trocar needle 12 are exposed to the outside of the trocar tube 14, the sutures 26 and 40 of the tissue retractors 20 and 30 retracting the tissues 5 and 6 are respectively hung on the latching grooves 16, and the trocar needle 12 is drawn upwards and inserted back into the trocar tube 14 so that the sutures 26 and 40 are fixed so as not to be easily separated from the latching grooves 16.

Here, the trocar tube 14 located at the outside of the abdominal wall 2 may be fixed by a fixture 60 formed of an elastic material, such as rubber or a synthetic resin. The fixture 60 which is formed in a flange shape surrounds the outer circumferential surface of the trocar tube 14 and prevents the trocar tube 14 from being drawn into the abdominal wall 2. Further, a fixing ring formed of rubber or a synthetic resin is installed on the outer circumferential surface of the trocar needle 12 adjacent to the head part 18 of the trocar tube 14, thus preventing the trocar needle 12 from being drawn into the abdominal wall 2.

The tissue retractors 20 and 30 hung on and fixed to the latching grooves 16 of the laparoscopic platform 10 include a tap type retractor 20 in which a tap 22 is attached to the end of the suture 26 provided with a needle 24, and a band type retractor 30 including a toothed part 32 with latching protrusions 36 arranged in a line and an insertion hole 34 into which one of the latching protrusions 36 is inserted. Either the tap type retractor 20 or the band type retractor 30, or both the tap type retractor 20 and the band type retractor 30 may be fixed to the laparoscopic platform 10.

The tap type retractor 20 may be used in, for example, retraction of an uterus 6 to the abdominal wall when laparoscopic low anterior resection of a female patient suffering rectal cancer is performed, and the band type retractor 30 may be used in, for example, retraction of a rectum 50 when dissection of the rectum 5 is performed after dissection of the sigmoid colon in laparoscopic anterior resection of a patient suffering lesion of the rectum 5 and colon.

From among the tissue retractors 20 and 30, the tap type retractor 20 has the tap 22 attached to the end of the suture 26 provided with the needle 24, as shown in FIG. 4. The tap type retractor 20 is configured such that the needle 24 penetrates one side of the tissue 6 and the tap 22 is supported by the outer wall of the tissue 6 so as to retract the tissue 6. The tap 22 attached to the tap type retractor 20 serves to widely disperse pressure of the suture 26 applied to the tissue 6 and thus to prevent the tissue 6 from being damaged.

5

The tap **22** preferably has a generally circular shape so as not to damage the tissue **6**, and the surface of the tap **22** supported by the outer wall of the tissue **6** is preferably flat so as to widely support the tissue **6** to the maximum extent possible. Further, the tap **22** may be formed of a soft material, such as elastic rubber, silicon or plastic.

In the embodiment of the present invention, the surface of the tap **22** supported by the outer wall of the tissue **6** has a circular shape, and a hemostatic agent can be applied to the surface of the tap **22** so as to reduce hemorrhage due to damage to the tissue **6**.

From among the tissue retractors **20** and **30**, the band type retractor **30** is formed in a flexible band shape and is rolled up so as to surround the outer surface of the tissue **5**, as shown in FIG. **3**. In this case, a main body **31** of the band type retractor **30** preferably maintains a round-shaped bending band shape at all times.

The toothed part **32** with the latching protrusions **36** is formed at one end of the bending band-shaped main body **31**, and the insertion hole **34** into which one of the latching protrusions **36** is inserted is formed at the other end of the bending band-shaped main body **31**.

The toothed part **32** formed at one end of the main body **31** of the band type retractor **30** is provided with the latching protrusions **36** having a rectangular shape, which are arranged in a line. The frontmost latching protrusion **36** of the toothed part **32** has a protruding end, and the suture **40** provided with the needle **42** may be connected to the protruding end of the frontmost latching protrusion **36**.

Instead of the suture **40** provided with the needle **42**, the tap type retractor **20** may be connected to the band type retractor **30**. Connection holes **38** to which the tap type retractor **20** is connected are respectively formed on the latching protrusions **36** of the band type retractor **30**. The connection holes **38** of the latching protrusions **36** have a sufficient size to pass the needle **42** and the suture **40** of the tap type retractor **20**. The tap type retractor **20** is connected to the band type retractor **30** by allowing the needle **24** of the tap type retractor **20** to pass through the connection hole **38** of one latching protrusion **36** and then the tap **22** to be supported by the outer surface of the latching protrusion **36**.

The insertion hole **34** formed at the other end of the main body **31** of the band type retractor **30** has a T shape so that one of the rectangular latching protrusions **36** of the toothed part **32** is inserted into the insertion hole **34**.

Now, with reference to FIGS. **5(a)** to **7(c)**, an operating process of the retraction device **8** for laparoscopy in accordance with the embodiment of the present invention will be described.

First, a user inserts the laparoscopic platform **10** into the abdominal wall **2** so that one end of the laparoscopic platform **10** is introduced into the abdominal cavity **4**. Then, the user pushes the trocar needle **12** into the abdominal cavity **4** using the head part **17** so that the latching grooves **16** are exposed to the outside of the trocar tube **14**.

Thereafter, as shown in FIGS. **6(a)** to **6(c)**, the needle **24** of the tap type retractor **20** penetrates one side of the tissue **6**, such as the uterus, so that the tap **22** is supported by the outer wall of the tissue **6**, and the needle **24** having penetrated the tissue **6** passes through one latching groove **16** of the trocar needle **12** so that the suture **26** of the tap type retractor **20** is hung on the latching groove **16** of the laparoscopic platform **10**.

Further, as shown in FIGS. **5(a)** to **5(c)**, after the band type retractor **30** surrounds the outer surface of the tissue **5**, such as the rectum, one of the latching protrusions **36** is inserted into the insertion hole **34**, and the needle **42** connected to the band

6

type retractor **30** passes through one latching groove **16** of the trocar needle **12** so that the suture connected to the band type retractor **30** is hung on the latching groove **16**.

In this case, instead of the suture **40** provided with the needle **42**, the tap type retractor **20** may be connected to the band type retractor **30**. If the tap type retractor **20** is connected to the band type retractor **30**, as shown in FIGS. **7(a)** to **7(c)**, the band type retractor **30** surrounds the outer surface of the tissue **5** and then one of the latching protrusions **36** is inserted into the insertion hole **34**. Then, the needle **24** of the tap type retractor **20** passes through the connection hole **38** of one latching protrusion **36** and the suture **26** is drawn so that the tap **22** is supported by the outer surface of the latching protrusion **36**. Thereafter, the needle **24** of the tap type retractor **20** connected to the band type retractor **30** is hung on one latching groove **16** of the laparoscopic platform **10**.

After the sutures **26** and **40** of the above-described tissue retractors **20** and **30** are hung on the latching grooves **16** of the laparoscopic platform **10**, the user draws the head part **17** of the trocar needle **12** of the laparoscopic platform **10** upwards so that the trocar needle **12** is inserted back into the trocar tube **14**. Here, in order to prevent downward movement of the trocar needle **12**, a fixing ring or a fixing clip provided with an insertion hole, one side part of which is opened, may be inserted between the head part **17** of the trocar needle **12** and the head part **18** of the trocar tube **14** so as to fix the trocar needle **12**.

By means of the insertion of the trocar needle **12** of the laparoscopic platform **10** back into the trocar tube **14**, the tissue retractors **20** and **30** may be firmly fixed to the laparoscopic platform **10** so as not to separate the sutures **26** and **40** connected to the tissue retractors **20** and **30** from the latching grooves **16**.

Hereinafter, a retraction device **8a** for laparoscopy in accordance with another embodiment of the present invention will be described. Some parts of the retraction device **8a** for laparoscopy in accordance with this embodiment are substantially the same as those of the retraction device **8** for laparoscopy in accordance with the earlier embodiment, and a detailed description thereof will thus be omitted because it is considered to be unnecessary.

The retraction device **8a** for laparoscopy in accordance with this embodiment of the present invention may be used to fix tissue retractors **20** and **30** retracting tissues **5** and **6** at the outside of an abdominal cavity **4**.

The retraction device **8a** for laparoscopy in accordance with this embodiment of the present invention, as shown in FIGS. **9(a)** to **10(c)**, includes fixing forceps **50** including left and right forceps parts **54a** and **54b** to which a pair of clamps **56a** and **56b** is attached, and the tissue retractors **20** and **30** retracting the tissues **5** and **6** and configured such that sutures **26** and **40** are clamped by the fixing forceps **50**.

The fixing forceps **50** installed at the outside of an abdominal wall **2**, as shown in FIG. **8**, include the left and right forceps parts **54a** and **54b** provided with the pair of clamps **56a** and **56b** formed at the front end of the fixing forceps **50**, and left and right handle parts **52a** and **52b** formed at the rear end of the fixing forceps **50**. The fixing forceps **50** are configured such that the clamps **56a** and **56b** attached to the left and right forceps parts **54a** and **54b** are moved towards or away from each other using the left and right handle parts **52a** and **52b** so as to clamp the sutures **26** and **40** of the tissue retractors **20** and **30**.

The pair of clamps **56a** and **56b** attached to the left and right forceps parts **54a** and **54b** may be rectangular elastic

members. For example, the clamps **56a** and **56b** may be elastic members formed of rubber, silicon or plastic which is harmless to the human body.

Interface surfaces **58a** and **58b** of the clamps **56a** and **56b** have prominence and depression shapes corresponding to each other. For example, if one of the interface surfaces **58a** and **58b** of the pair of clamps **56a** and **56b** has a depression shape, the other of the interface surfaces **58a** and **58b** of the pair of clamps **56a** and **56b** has a prominence shape so as to be engaged with the one of the interface surfaces **58a** and **58b**.

The interface surfaces **58a** and **58b** of the pair of clamps **56a** and **56b** having the prominence and depression shapes serve to firmly clamp the sutures **26** and **40** connected to the tissue retractors **20** and **30**.

The tissue retractors **20** and **30** in accordance with this embodiment of the present invention include a tap type retractor **20** in which a tap **22** is attached to the end of the suture **26** provided with a needle **24**, and a band type retractor **30** including a toothed part **32** with latching protrusions **36** arranged in a line and an insertion hole **34** into which one of the latching protrusions **36** is inserted.

The band type retractor **30** may be used under the condition that the suture **40** provided with a needle **42** is connected to the frontmost latching protrusion **36** of the toothed part **32** or the tap type retractor **20** is connected to a connection hole **38** of one latching protrusion **36** of the toothed part **32**.

Now, with reference to FIGS. **9(a)** to **10(c)**, an operating process of the retraction device **8a** for laparoscopy in accordance with this embodiment of the present invention will be described.

In order to retract the tissue **6**, such as an uterus, as shown FIGS. **9(a)** to **9(c)**, the needle **24** of the tap type retractor **20** penetrates one side of the tissue **6** so that the tap **22** is supported by the outer wall of the tissue **6**, and the needle **24** having penetrated the tissue **6** passes through the abdominal wall **2** and exits the abdominal cavity **4**. Then, the suture **26** connected to the needle **24** is inserted between the interface surfaces **58a** and **58b** of the clamps **56a** and **56b** of the fixing forceps **50** located on the upper surface of the abdominal wall **2**. Thereafter, the clamps **56a** and **56b** of the left and right forceps parts **54a** and **54b** are moved towards each other using the left and right handle parts **52a** and **52b** of the fixing forceps **50**, thereby firmly fixing the suture **26** of the tap type retractor **20**.

Further, in order to retract the tissue **5**, such as a rectum, as shown FIGS. **10(a)** to **10(c)**, after the band type retractor **30** surrounds the outer surface of the tissue **5**, one of the latching protrusions **36** is inserted into the insertion hole **34**, and the needle **42** connected to the band type retractor **30** passes through the abdominal wall **2** and exits the abdominal cavity **4**. Then, the suture **40** connected to the needle **42** is inserted between the interface surfaces **58a** and **58b** of the clamps **56a** and **56b** of the fixing forceps **50** located on the upper surface of the abdominal wall **2**. Thereafter, the clamps **56a** and **56b** of the left and right forceps parts **54a** and **54b** are moved towards each other using the left and right handle parts **52a** and **52b** of the fixing forceps **50**, thereby firmly fixing the suture **40** of the band type retractor **30**.

Instead of the suture **40** provided with the needle **42**, the tap type retractor **20** may be connected to the band type retractor **30**. The band type retractor **30** to which the tap type retractor **20** is connected may be usefully applied when a user desires to change the retracting direction of the tissue **5**.

In more detail, when the user desires to change the retracting direction of the tissue **5**, as shown in FIGS. **11(a)** to **11(c)**, the suture **40** of the band type retractor **30** fixed to the laparoscopic platform **10** in accordance with one embodiment of the

present invention is cut using scissors. Then, the tap type retractor **20** is connected to the band type retractor **20** by allowing the needle **24** of the tap type retractor **20** to pass through the connection hole **38** of one latching protrusion **36** of the band type retractor **30** so that the tap **22** is supported by the latching protrusion **36**. Thereafter, the needle **24** of the tap type retractor **20** passes through the abdominal wall **2** in a direction desired by the user, the suture **26** connected to the needle **24** is inserted between the interface surfaces **58a** and **58b** of the clamps **56a** and **56b** of the fixing forceps **50** located on the upper surface of the abdominal wall **2**, and the clamps **56a** and **56b** are moved towards each other so as to firmly fix the suture **26**.

Through the above-described configurations, the retraction devices **8** and **8a** for laparoscopy in accordance with the embodiments of the present invention prevent unnecessary damage to the tissues **5** and **6** due to retraction and simply retract the tissues **5** and **6** without the help of assistant's two hands. Further, the retraction devices **8** and **8a** for laparoscopy assure a wide field of surgical vision and enable an assistant to more actively assist in surgery so as to successfully achieve the surgery.

As apparent from the above description, the present invention provides a retraction device which prevents unnecessary damage to tissues due to retraction, such as penetration of the tissues by a needle twice or more, facilitates convenient retraction of the tissues without the help of assistant's two hands, enables an assistant to more actively assist in surgery, and assures a wide field of surgical vision.

Although the preferred embodiments of the present invention have been disclosed for illustrative purposes, those skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.

What is claimed is:

1. A retraction device for laparoscopy comprising:

a trocar needle including latching grooves formed at a side of a lower end thereof and configured to be inserted into a trocar tube, wherein both ends of the trocar tube are opened to form a laparoscopic platform, the laparoscopic platform is configured to pierce an abdominal wall, the trocar needle is configured to be pushed into an abdominal cavity, and the latching grooves are exposed to the outside of the trocar tube; and

at least one suture provided with a needle connected to at least one tissue retractor configured for retracting tissues and configured to be hung on the latching grooves, wherein the trocar needle is configured to be drawn upwards so that the latching grooves are configured to be inserted back into the trocar tube to fix the tissue retractors to the laparoscopic platform,

wherein the at least one tissue retractor includes:

a tap type retractor in which a tap is attached to one end of the at least one suture provided with a needle; and
a band type retractor including a toothed part with latching protrusions arranged in a line and formed at one end of a band-shaped main body, and an insertion hole formed at another end of the band-shaped main body,

wherein each of the latching protrusions is configured to be inserted into the insertion hole,

wherein the band type retractor further includes connection holes respectively formed on the latching protrusions of the toothed part so that the tap type retractor is configured to be connected to the connection holes, and the tap type retractor is configured to be connected to the band type retractor by allowing the needle of the tap type

9

retractor to pass through one of the connection holes and the tap to be supported by an outer surface of one of the latching protrusions.

2. The retraction device for laparoscopy according to claim 1, wherein the band type retractor is configured such that another at least one suture provided with a needle is connected to the frontmost latching protrusion of the toothed part.

3. A retraction device for laparoscopy comprising:

a trocar needle including latching grooves formed at a side of a lower end thereof and inserted into a trocar tube, wherein both ends of the trocar tube are opened to form a laparoscopic platform, the laparoscopic platform is configured to pierce an abdominal wall, the trocar needle is configured to be pushed into an abdominal cavity, and the latching grooves are exposed to the outside of the trocar tube; and

a tap attached to one end of a suture provided with a needle to form a tap type retractor, the tap having a top flat circular surface configured to support a tissue, a side circumferential surface connected to the top circular surface, and a cone shaped bottom surface connected to the side surface,

wherein the needle of the tap type retractor is configured to penetrate one side of the tissue so that the tap is configured to be supported by the outer surface of the tissue, wherein the needle having penetrated the tissue is configured to pass through one latching groove of the trocar needle so that the suture is configured to be hung on one of the latching grooves, and

wherein the trocar needle of the laparoscopic platform is configured to be drawn upwards so that the latching grooves are configured to be inserted back into the trocar tube to fix the tap type retractor to the laparoscopic platform.

4. A retraction device for laparoscopy comprising:

a trocar needle including latching grooves formed at a side of a lower end thereof and inserted into a trocar tube, wherein both ends of the trocar tube are opened to form a laparoscopic platform, the laparoscopic platform is configured to pierce an abdominal wall, the trocar needle is configured to be pushed into an abdominal cavity, and the latching grooves are exposed to the outside of the trocar tube;

a flexible band type retractor having a band-shaped main body including a toothed part with latching protrusions, the toothed part being arranged in a line and formed at

10

one end of the band-shaped main body and the main body having an insertion hole into which one of the latching protrusions is configured to be inserted, wherein the insertion hole is formed at another end of the band-shaped main body; and

a suture provided with a needle, the suture being connected to a frontmost latching protrusion of the latching protrusions of the toothed part of the band type retractor, each of the latching protrusions having an upper tooth and a lower tooth and being configured to be locked in the insertion hole, thereby forming a circular shaped band, wherein the band type retractor is configured to surround an outer surface of a tissue,

wherein the needle connected to the band type retractor is configured to pass through one latching groove of the latching grooves of the trocar needle so that the suture connected to the band type retractor is configured to be hung on the one latching groove, and

wherein the trocar needle of the laparoscopic platform is configured to be drawn upwards so that the latching grooves are configured to be inserted back into the trocar tube to fix the band type retractor to the laparoscopic platform.

5. A retraction device for laparoscopy comprising:

a band type retractor including:

a band-shaped main body;

a toothed part with latching protrusions arranged in a line formed at one end of the band-shaped main body; and an insertion hole into which one of the latching protrusions is inserted, formed at another end of the band-shaped main body, and wherein the band type retractor is configured for retracting a tissue by surrounding the outer surface of the tissue and then inserting the one of the latching protrusions into the insertion hole,

wherein connection holes are respectively formed on the latching protrusions of the toothed part formed at the one end of the band-shaped main body, and a tap type retractor in which a tap is attached to one end of a suture provided with a needle that is connected to one of the connection holes.

6. The retraction device for laparoscopy according to claim 5, wherein the suture is connected to the frontmost latching protrusion of the toothed part.

7. The retraction device for laparoscopy according to claim 5, wherein the main body of the band type retractor is formed in a bending band shape.

* * * * *

专利名称(译)	用于腹腔镜检查的牵开装置		
公开(公告)号	US8979746	公开(公告)日	2015-03-17
申请号	US13/158938	申请日	2011-06-13
[标]申请(专利权)人(译)	此外, Dalim CORP 金载晃		
申请(专利权)人(译)	此外, Dalim CORPORATION KIM, JAE-HWANG		
当前申请(专利权)人(译)	KIM, JAE-HWANG 此外, Dalim CORPORATION		
[标]发明人	KIM JAE HWANG		
发明人	KIM, JAE-HWANG		
IPC分类号	A61B1/32 A61B17/00 A61B17/02 A61B17/04 A61B17/28		
CPC分类号	A61B17/0218 A61B17/0487 A61B2017/0454 A61B2017/00349 A61B2017/0225 A61B17/2812 A61B17/28		
代理人(译)	KIM, JAE YOUN		
其他公开文献	US20120316593A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明公开了一种用于腹腔镜检查的收缩装置，其中包括形成在其下端侧的锁定槽的套管针插入到套管针中，所述套管针的两端都是敞开的，以形成腹腔镜平台，所述腹腔镜平台刺穿所述套管针平台。腹壁和套管针被推入腹腔，使得锁定槽暴露于套管针管的外侧，连接组织牵开器的缝合线将组织牵开器悬挂在闭锁槽上，然后悬挂在腹腔镜平台的套管针上向上拉动，使得锁定槽插回到套管针管中，以将组织牵开器固定到腹腔镜平台。用于腹腔镜检查的收缩装置防止组织由于收缩而不必要地损坏，并且在没有助手的双手帮助的情况下便于组织的收缩。

