



US008357153B2

(12) **United States Patent**  
**Habib**

(10) **Patent No.:** **US 8,357,153 B2**  
(45) **Date of Patent:** **Jan. 22, 2013**

(54) **APPARATUS FOR ADMINISTERING THERAPY AT A REMOTE LOCATION IN THE BODY**

(75) Inventor: **Nagy Habib**, London (GB)  
(73) Assignee: **Emcision Ltd.**, London (GB)  
(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 662 days.

(21) Appl. No.: **12/522,721**  
(22) PCT Filed: **Jan. 11, 2008**  
(86) PCT No.: **PCT/GB2008/000084**  
§ 371 (c)(1),  
(2), (4) Date: **Dec. 9, 2009**

(87) PCT Pub. No.: **WO2008/084239**  
PCT Pub. Date: **Jul. 17, 2008**

(65) **Prior Publication Data**  
US 2010/0106149 A1 Apr. 29, 2010

(30) **Foreign Application Priority Data**  
Jan. 11, 2007 (GB) ..... 0700553.1  
Apr. 13, 2007 (GB) ..... 0707370.3  
Dec. 13, 2007 (GB) ..... 0724347.0

(51) **Int. Cl.**  
**A61B 18/14** (2006.01)  
(52) **U.S. Cl.** ..... **606/41; 607/101; 607/116**  
(58) **Field of Classification Search** ..... **606/41, 606/45-50; 607/101, 102, 115, 116**  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,122,136	A *	6/1992	Guglielmi et al.	606/32
5,234,437	A *	8/1993	Sepetka	606/108
5,250,071	A *	10/1993	Palermo	606/198
5,281,217	A *	1/1994	Edwards et al.	606/41
5,709,224	A *	1/1998	Behl et al.	128/898
5,851,206	A *	12/1998	Guglielmi et al.	606/28
5,972,026	A *	10/1999	Laufer et al.	607/96
6,179,832	B1 *	1/2001	Jones et al.	606/32
6,190,353	B1	2/2001	Makower et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

WO 94/03213 A 2/1994

(Continued)

OTHER PUBLICATIONS


International Search Report for International Application No. PCT/GB2008/000084.

*Primary Examiner* — Michael Peffley  
(74) *Attorney, Agent, or Firm* — Caesar, Rivise, Bernstein, Cohen & Pokotilow, Ltd.

(57) **ABSTRACT**

Devices suitable for insertion into a hollow anatomical structure within a patient for the purpose of ablating tissue within or surrounding the hollow structure so as to induce occlusion of the hollow structure are provided. The devices are in the form of guidewires with functional tips, that comprise at least one heating module, at their distal ends. The devices of the invention are suitable for occluding hollow anatomical structures selected from vasculature or from non-vascular ducts and tubes, via percutaneous, laparoscopic or endoscopic routes of access. Methods of using the devices in the treatment of patients are also described.

**3 Claims, 16 Drawing Sheets**



# US 8,357,153 B2

Page 2

---

## U.S. PATENT DOCUMENTS

6,726,677	B1	4/2004	Flaherty et al.	
6,979,330	B2 *	12/2005	Kelly et al. ....	606/41
7,674,262	B2 *	3/2010	Sugita et al. ....	606/45
2002/0151886	A1	10/2002	Wood	
2004/0181215	A1	9/2004	Kelly et al.	
2005/0043727	A1	2/2005	Swanson et al.	

## FOREIGN PATENT DOCUMENTS

WO	99/56812	A	11/1999
WO	00/72909	A	12/2000
WO	02/32333	A	4/2002
WO	2006/062873	A	6/2006

\* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 4





FIGURE 4 (cont'd)






FIGURE 5

FIGURE 6





FIGURE 7







FIGURE 8

FIGURE 9






FIGURE 9  
(cont'd)





FIGURE 9  
(cont'd)

FIGURE 10






FIGURE 11

FIGURE 12





FIGURE 13



**APPARATUS FOR ADMINISTERING  
THERAPY AT A REMOTE LOCATION IN THE  
BODY**

CROSS-REFERENCE TO RELATED  
APPLICATIONS

This national stage application claims the benefit under 35 U.S.C. §371 of International Application No. PCT/GB2008/000084 filed on Jan. 11, 2008, entitled APPARATUS FOR ADMINISTERING THERAPY AT A REMOTE LOCATION IN THE BODY, which in turn takes its priority from Great Britain Application No. 0700553.1 filed on Jan. 11, 2007, Great Britain Application No. 0707370.3 filed on Apr. 13, 2007, and Great Britain Application No. 0724347.0 filed on Dec. 13, 2007, and all of whose entire disclosures are incorporated by reference herein.

BACKGROUND OF THE INVENTION

1. Field of Invention

The invention relates to apparatus and methods for performing endoscopic, laparoscopic and percutaneous interventional surgery.

2. Description of Related Art

This invention is in the surgical therapies for the treatment of disease by blocking, or occluding, hollow anatomical structures within the body of a patient. The invention also relates to surgical therapies for the treatment of the surface of a hollow anatomical structure, wherein such treatments do not necessarily result in occlusion of the structure.

In many medical conditions such as arterio-venous vascular malformations and varicose veins, it is advantageous to block a blood vessel. In treating liver disease it is possible to induce liver regeneration by directing blood supply from one area to another, for example by blockage of portal blood to the right liver to induce hypertrophy of the left liver. Blocking blood flow can also be used in the field of oncology, specifically in the field of treating solid tumours. One method of treating tumours is to interrupt the blood supply to the tumour. In many tumours there are a small number of discrete vessels supplying blood to the tumour. Interrupting the blood supply to these vessels will cease the flow of nutrients to the tumour causing the tumour cells to die. Blood vessels that supply tumours can also be used to introduce an ablation device into the tumour.

Occlusion of non-blood vessels can also be desirable. Hollow anatomical structures include, for example, the fallopian tubes, small and large intestine, bronchi, bronchioles, biliary duct, urethra, ureters and vas deferens. In certain circumstances it may be desirable to occlude (fully or partially) a hollow anatomical structure. For example; ligation of the fallopian tubes is a well known means for achieving female sterilization. In other circumstances it may be desirable to treat the lumen-facing surface of the hollow structure so as to administer therapy to a lesion that is located on that surface.

Prior methods of inducing closure or occlusion of a hollow anatomical structure include injecting a sealing compound into the structure, or positioning a plug or obstructive stent into the structure. These have the disadvantage that these blocking structures may move over time. For instance, where a blood vessel that leads to a tumour has been occluded loss or displacement of the occluding structure can permit resumption of blood flow through the tumour supplying vessel. In some cases the structure may move to another vessel and cause an embolism.

Thermal ablation of hollow anatomical structures has been utilised in the percutaneous treatment of venous disorders such as varicose veins as well as in endoscopic tubal ligation for achieving female sterilization. Hollow anatomical structures, such as blood vessels, are treated in this way by local heating. This heating may be applied by exposing the tissue in the tube or vessel to locally applied electro-magnetic or ultrasound energy. The electro-magnetic energy may be at radio-frequencies, or micro-wave radiation. The effect of the heating on the treated tissue is two-fold. First, hollow structures will be sealed, and permanent occlusion of the structure achieved. Second, the surrounding tissue that is heated will be coagulated, causing cell death and shrinkage.

Conventional methods for administering thermal ablation to hollow anatomical structures, such as the vasculature or various ducts in the body, are typically based on the use of one or more therapeutic catheters that are slidably mounted over a prepositioned guidewire. The disadvantage of this system is that the arrangement sets functional limitations upon the minimum lumen diameter of the anatomical structure that can be treated due to the combined diameter of guidewire and catheter. Hence, for oncology, paediatric/neonatal, neurovascular, cerebrovascular or cardiovascular applications, where the lumen diameters can be very small, such percutaneous or endoscopic thermal ablation techniques can be unsuitable.

Hence there is a need for improved apparatus and methods for managing occlusion of hollow anatomical structures and thermally ablating tissues. In particular, there is a need for methods and apparatus that can be directed to blockage of blood vessels at remote sites within the body that are inaccessible to conventional surgical techniques, such as the brain and the smaller vessels of the heart. There is further need for methods and apparatus for occluding or treating hollow anatomical structures within the body that are not comprised within the vasculature via endoscopic or laparoscopic routes.

BRIEF SUMMARY OF THE INVENTION

In its primary aspect the invention provides a device suitable for insertion into a hollow anatomical structure within a patient for the purpose of ablating tissue within or surrounding the hollow structure so as to induce occlusion of the hollow structure, the device comprising:

a body having a distal end and a proximal end, the body comprising a central core which extends along the length of the body, the central core comprising a plurality of steering members and at least one conductor, the at least one conductor having a connection to an external energy source; and

a tip located at the distal end of the body, wherein the tip comprises a heating module, and wherein the heating module is in contact with the at least one conductor;

wherein, in use, when the tip is located within the hollow structure the external energy source is activated, thereby inducing activation of the heating module and facilitating ablation of said structure and/or the surrounding tissue.

Typically the heating module comprises at least one electrode that is capable of expansion outwardly from the tip so as to achieve improved physical contact with the walls of the surrounding hollow anatomical structure. The body, suitably, has mean diameter along its length of between about 0.1 mm and about 3 mm, and as such the body may be in the form of what is conventionally termed a 'guidewire'.

Optionally, the device comprises means for permitting in situ detachment of the tip following activation of the ablating

module. Further, the device can suitably comprise a plurality of sequentially detachable tips located at the distal end of the body.

The means for connecting the at least one conductor to an external energy source may suitably comprise a housing that is slidably mounted on the body, the housing including an actuator means for controlling electrical contact between the at least one conductor and the external energy source. Optionally, the external energy source is an RF generator.

A further aspect of the invention provides a guidewire device suitable for insertion into a hollow anatomical structure within a patient via a percutaneous, laparoscopic or endoscopic route for the purpose of ablating tissue within or surrounding the hollow structure so as to induce occlusion of the hollow structure, the device comprising:

a body having a distal end and a proximal end, the body comprising a central core which extends along the length of the body, the central core comprising a plurality of steering members and at least one conductor, the at least one conductor having a connection to an external energy source; and

a tip located at the distal end of the body, wherein the tip comprises at least one expandable heating module capable of heating the walls of the hollow structure to a temperature that causes endoluminal closure of the hollow structure, and wherein the heating module is in contact with the at least one conductor;

wherein, in use, when the tip is located within the hollow structure the heating module is expanded so as to contact the surface of the hollow structure, and the external energy source is activated, thereby causing endoluminal closure of the hollow structure.

A further aspect of the invention provides for a device suitable for insertion into a hollow anatomical structure within a patient via a percutaneous, laparoscopic or endoscopic route for the purpose of ablating tissue within or surrounding the hollow structure so as to induce occlusion of the hollow structure, the device comprising:

a guidewire having a distal end and a proximal end, the guidewire comprising a central core which extends along the length of the body, the central core comprising at least one conductor and a plurality of steering members, a tip located at the distal end of the guidewire wherein the tip comprises a heating module and means for connecting the at least one conductor to an external energy source, said means being located at the proximal end of the guidewire; and

a catheter having an elongate body including a lumen extending along at least a portion of the elongate body, wherein the lumen is adapted to facilitate slidable mounting of the catheter on the guidewire, an aperture positioned in the side wall of the catheter proximally to the distal end of the catheter, the aperture being sealable via a pivotally mounted door;

wherein, in use, the guidewire can be withdrawn proximally until the distal tip of the guidewire is located within the lumen of the catheter at a point that is adjacent to the aperture which permits the door to be opened inwardly, such that upon subsequent advancement of the guidewire the tip is deflected outwardly from the lumen of the catheter through the aperture and into the surrounding hollow anatomical structure where the heating module can be activated so as to induce ablation of the tissue.

In specific embodiments the devices of the invention are suitable for transluminal use in hollow anatomical structures including but not limited to a vein; an artery; an arteriole; a fallopian tube; a biliary duct; a ureter; a urethra; a bronchiole;

and a vas deferens. The invention is also suitably used for administering treatment to ducts, vessels or tubes within the body that can be accessed endoscopically, laparoscopically or percutaneously.

In an aspect of the invention there is provided a method of treating a patient requiring endoluminal closure of a hollow anatomical structure, comprising locating a device as described herein within a hollow anatomical structure within the body of the patient, ablating tissue within or surrounding the hollow structure so as to induce occlusion of the hollow structure and withdrawing the device from the body of the patient. In one embodiment of the invention the patient is suffering from cancer and the hollow structure is located adjacent to or within a solid tumour. In a specific embodiment of the invention the hollow structure is a fallopian tube and the patient requires tubal ligation. In a further specific embodiment of the invention the hollow anatomical structure is a blood vessel (e.g. vein, artery, or arteriole) located within the cerebrovasculature, typically the brain, of the patient.

#### BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWINGS

FIG. 1 shows a diagrammatic view of an embodiment of a guidewire of the invention in use in a patient.

FIG. 2 shows a cut away side view of the distal end tip of a guidewire of the invention demonstrating the location of the electrode tip.

FIG. 3 shows two embodiments of the distal end tip of FIG. 2, (a) shows a cut away side view of the distal end tip which also includes an outer sleeve, (b) shows an oblique view of an embodiment where the outer sleeve is adjustable and can be retracted to expose or shroud the electrode tip, sliding movement is along the longitudinal axis of the guidewire as denoted by arrow D; (c) shows an embodiment where the sleeve is static.

FIG. 4 (a) shows an oblique view of the distal tip of an embodiment of the guidewire of the invention which comprises an expandable spring electrode in the undeployed state. (b) shows the spring electrode in the deployed or expanded state. (c) Shows an axial view along line C in FIG. 4 (b). (d) shows an axial view along line B in FIG. 4 (a). (e) shows a side view of the guidewire with the spring electrode in the expanded state, in an additional embodiment a helical outer sleeve is provided that surrounds the exterior surface of the guidewire. (f) shows a side view of the guidewire with the spring electrode in the unexpanded state.

FIG. 5 shows an oblique view of the distal tip of an alternate embodiment of the guidewire of the invention in which the guidewire further comprises an expandable structure that takes the form of a bipolar double helix coil spring electrode.

FIG. 6 shows a side view of the distal tip of an alternate embodiment of the guidewire of the invention in which the guidewire includes an expandable electrode structure that is shown in the process of deploying in (a) to (c). (d) shows the expanded structure within a hollow anatomical structure, demonstrating the increased contact between the flexible electrode arms and the walls of the hollow structure.

FIG. 7 shows a side view of the distal tip of the embodiment of the guidewire of the invention as shown in FIG. 6, (a) displays the further inclusion of additional radial electrode wires that retractably extend across the span between the expanded flexible electrode arms thereby providing additional contact area with the surface of the surrounding hollow structure walls. (b) shows an additional embodiment of the invention in which a resilient member is located at the proximal end of the expandable structure and allows for a con-

trolled level of movement of the hub, thereby improving the ability to maintain contact between the pliable electrode arms and the walls during movement of the guidewire within the hollow anatomical structure.

FIG. 8 shows a schematic cross sectional view of an embodiment of the guidewire of the invention showing an arrangement of six steering wires surrounding a central conductor core, the arrangement is enclosed within an outer insulating coating.

FIG. 9 shows cut away side views of the distal tip of embodiments of the invention in which the distal tip is detachable from the body of the guidewire in use, (a) shows an embodiment wherein the distal tip is joined to the body via a weld of joining material, (b) shows an embodiment where the joining is mediated via a threaded, joint and where a threaded connecting post is retractable into the body of the guidewire thereby releasing the tip from the guidewire body, (c) shows an embodiment where the detachable tip engages with the body of the guidewire via a post and socket arrangement and is secured via a removable tether that passes through an aperture formed in the post, (d) shows an embodiment where the distal tip is joined to the body of the guidewire via a magnetic linkage, (e) shows an embodiment in which the distal tip is linked to the body of the guidewire via a releasable latching mechanism, (f) shows a similar embodiment to (e) but wherein the latching arms are released from engagement with the distal tip by retraction of the adjustable outer coating which can be slidably displaced along the axis shown by line y.

FIG. 10 shows a cut away side view of the proximal end of an embodiment of the device of the invention which provides the user interface in the form of a handle grip, (a) shows the configuration of the grip in which the plug and socket means are engaged to allow electrical connection. (b) shows the configuration of the grip in which the plug and socket means are separated so that no electrical connection is made.

FIG. 11 shows an alternative embodiment of the invention which provides the user interface and electrical connector in the form of a slidably removable housing. (a) shows a perspective view of the housing with the slidable switch apparent, (b) shows the reverse view along line R of FIG. 8 (a) where the entry point of the electrical cable into the housing is apparent.

FIG. 12 shows a top-down cut away view of the user interface shown in FIG. 11 (a) shows an embodiment wherein the electrical cable enters the housing via a side port (as in FIG. 11 (a)), (b) shows an alternative embodiment wherein the electrical cable enters via a port located in the rearward face of the housing.

FIG. 13 shows a diagrammatic side view of an embodiment of the invention in which (a) a catheter is loaded onto the guidewire of the invention and is tracked to the site requiring therapy within the patient's body. (b) the catheter comprises a side port with a hinged gate that can open inwardly, along arrow P, into the central lumen of the catheter when the guidewire is withdrawn proximally, and act as a deflector to direct the reinserted guidewire outwardly so that it will penetrate the wall of the surrounding hollow anatomical structure.

#### DETAILED DESCRIPTION OF THE INVENTION

In the embodiments described herein the term 'guidewire' is used to describe the elongate filament-like device of the invention which is utilised to administer therapy within the body via a percutaneous surgical technique. The devices of the invention are typically of composite manufacture and

comprise thermal ablation functionality at or near their distal tips. Hence, the devices of the invention are described as 'guidewires' largely because of their resemblance to conventional wires that are used to guide catheters slidably mounted thereon, and because they can continue to function as conventional guidewires if the need arises. However, it is envisaged that for many embodiments the devices described according to the present invention are stand-alone devices that do not rely on a separate catheter for functionality.

FIG. 1 shows a typical embodiment of a device of the present invention where a lesion 6 such as a tumour or haemorrhage is located at an inoperable site in the body of a patient 2 and requires treatment. A guidewire 10 is inserted via a percutaneous route, such as a femoral artery access, and tracked up the vascular system to the tumour site 6. In the present instance the target site may be in the brain or another part of the body. The guidewire 10 has a distal tip 13 which may comprise, or be located adjacent to, an electrode 14 (see FIG. 2). The distal tip 13 may also comprise a radio-opaque material to facilitate navigation of the device to the tumour site 6. The guidewire is conducting and can conduct an applied RF signal from a connector 3 at the proximal end to the distal tip 13. The proximal connector mates with a matching connector on a lead 7 that is connected to one polarity of an RF generator 5. The other polarity of the RF generator is connected to an electrode pad 4 that is placed in contact with the patient's body 2.

In RF configuration the electrode 14 located at the distal tip 13 comprises a single electrode and so it is said that the that the RF is applied in monopolar mode. The RF current is preferably at a frequency between 100 kHz and 5 MHz. The device can be used in two different modes. The device can be inserted into one or more blood vessels that provide a blood supply to a solid tumour, so the distal end is positioned at any point in the vessel close to but upstream to the tumour (i.e. in an artery or arteriole). RF energy is then applied causing heating of the surrounding tissue, including collagen and other extracellular matrix components in the vessel wall, which causes the vessel to collapse and prevent blood flow into the tumour. In another mode the device can be inserted into a vessel in the centre of the tumour and the RF energy is applied to also heat the surrounding tissue beyond the vessel wall. This embodiment of the invention is particularly suitable where the surrounding tissue is a tumour. Alternative arrangements are possible when other energy sources are used such as microwave or ultrasound. Likewise, alternative embodiments include use of the device in non-vascular hollow anatomical structures.

Typically the guidewires of the invention are operated according to three main phases of therapy: an insertion phase, a therapy phase and a removal phase. The insertion phase includes the percutaneous insertion of the guidewire and the location of the guidewire to the site where therapy is to be administered. The therapy phase includes the steps of deploying the electrode and administering thermal ablation to the walls of the hollow anatomical structure, and optionally the surrounding tissue. The removal phase includes the withdrawal of the guidewire from the site of ablation, usually back along the initial insertion path. Optionally, the therapy phase and withdrawal phase can overlap such that ablation is applied along a portion of the hollow anatomical structure rather than simply at a single site.

FIG. 2 shows details of the construction of the distal region of the guidewire 10. The guidewire 10 suitably possesses a number of properties relating to electrical conductivity, flexibility, steerability and pushability. For this combination a composite construction is desirable, as one single material

component typically cannot simultaneously provide the required electrical conductivity, and required steerability. A conducting core **22**, suitably constructed from a high conductivity material, such as copper, silver or gold wire, provides the conductivity, and a plurality of steering members **21**, suitably steel or nitinol wires, provide the mechanical properties including pushability. The steering members **21** can be arrayed about the central conducting core **22** as shown in FIG. **8**. In embodiments of the invention the central core is enclosed with an insulating material, such as a polyimide sheath. An insulating coating **11** made from a low friction material such as a fluoropolymer (e.g. PTFE) suitably covers and encapsulates the assembly, to provide a low-friction surface and electrical insulation. The coating **11** typically stops short of the distal tip **13** to allow the electrode **14** to be exposed to the surrounding tissue when in use. The outer diameter of the guidewire assembly is typically in the range of about 0.1 mm to about 3 mm (about 0.005 inches to about 0.14 inches). Where a monopolar RF configuration is desired the guidewire device of the invention comprises a single central conducting core **22**. In embodiments of the invention where a bipolar RF configuration is desired (i.e. wherein the guidewire distal tip **13** comprises two electrodes of opposing polarity) the central core **22** will contain two conductor wires (one for each polarity) each enclosed within a separate insulating sheath.

FIG. **3** shows details of the tip. The core **20** comprises the conducting core **22** and the steering members **21** and is positioned at the centre of the assembly and lies along the whole length of the guidewire **10**, thereby defining the longitudinal axis of the device. The coating **11**, and the steering members **21** terminate a short distance from the distal tip **13**. The remaining length will have a series of short conducting wires connecting to the conductor **22**. These wires act as the outer contact surface of the tip, forming an electrode **14**, and enable electrical contact to be made with the surrounding tissues. A smooth, conical or hemi-spherical cap may be attached to the tip **13** of the assembly to ease insertion into the hollow anatomical structure. In a specific embodiment of the invention an outer sheath **12** is retractably located in the distal region of the guidewire **10** (see FIG. **3** (b)) allowing the amount of electrode **14** exposed to the surrounding tissue to be adjusted. Alternatively, the sheath **12** can be static and serves as an additional layer of insulation in the tip region (see FIG. **3** (c)).

The configuration of the electrode **14**, represents a particular embodiment of the present invention. In FIG. **4** one configuration of the guidewire electrode **142** is shown which comprises an expandable structure both allowing for improved contact between the surface of the electrode and walls of the surrounding structure as well as anchoring the guidewire in its location. FIG. **4** (a) shows a guidewire electrode **142** comprising an expandable basket arrangement, referred to as a spring electrode that includes deformable splines secured at either end to a static tip **13** and a slidable collar **143**. When deployment of the electrode is required the collar **143** is able to be moved slidably in the direction shown by arrow A in order to reduce the longitudinal distance between the collar **143** and the tip **13** causing the deformable splines of the electrode **142** to bow radially outward, as shown in FIG. **4** (b). Views along the longitudinal axis of the guidewire are shown in FIGS. **4** (c-d) further showing the radial expansion of the spring electrode **142**. In a specific embodiment of the invention an additional spring sheath **122** in the form of a spiralled shaft is applied to at least a portion of the exterior of the insulating coating **11** at the location of the collar **143**, which accommodates the need for expansion of the insulation when the collar **143** is slid towards the tip **13**

(see FIGS. **4** (e-f)). The expanded spring electrode is retracted following administration of therapy by initiating sliding of the collar **143** in the reverse direction to that to arrow A (FIG. **4** (a)).

The expandable electrode **142** need not be limited to the configuration described above and shown in FIG. **4**. In FIG. **5** an alternative arrangement is shown in which the expandable structure is in the form of a helical or coil spring. Operation of the expansion/retraction of the electrode is substantially similar to that described previously. However, one advantage of the helical coil spring configuration is that it is possible to provide a bipolar RF electrode configuration solely on the guidewire by adopting a double helical structure wherein each strand of the helix provides the opposite polarity. In this embodiment, a separate electrode pad **4** is not required. Such an arrangement may be suitable in hollow anatomical structures (e.g. blood vessels) that are particularly small, for instance, where the diameter of the lumen is less than 2 mm, or even less than 1 mm.

A further embodiment of the invention includes an alternative conformation for an expandable electrode located on the distal tip of the guidewire. FIG. **6** (a-c) shows an expandable 'umbrella' electrode configuration. The guidewire **90** is provided with a tip **91** located at the distal (i.e. forward) end of a central flexible shaft **96**. An annular collar **93** is slidably mounted on the shaft **96** proximally (i.e. to the rear) of the tip **91**. A statically mounted hub **94** is located at a position proximally to the collar **93**. Elongated flexible electrode arms **92** have an end pivotally anchored to the hub **94** and a free end **92a** that extends in a distal direction. Each electrode arm **92** is either fixedly or pivotally connected to the first end of a strut **95** at an interim location **97** on the arm **92** between the hub **94** anchor point and the free end **92a**. The second end of the strut **95** is pivotally anchored to the collar **93**. In use, the guidewire **90** is inserted into the hollow anatomical structure and directed to the site where therapy is to be directed. During the insertion phase the umbrella electrode is kept in a retracted state with the electrode arms **92** held parallel to the longitudinal axis of the shaft **96**, this being achieved by maximising the distance between the slidable collar **93** and the hub **94**. In this configuration the free ends **92a** of the arms **92** are housed within notches **98** formed in the proximally facing portion of the tip **91**. When expansion of the electrode arms **92** is required, the collar **93** is drawn towards the hub **94** reducing the distance there-between and enabling the struts **95** to bear on the arms **92** causing the free ends **92a** to extend outwardly from guidewire **90** towards the surrounding walls **159** (see FIG. **6**(d)). In this manner the expansion of the electrode broadly mimics the opening of an umbrella.

As with the other embodiments of the invention flexible electrode arms **92** are suitably manufactured from a resilient and conductive material, for instance, stainless steel or a shape memory alloy such as nitinol. The pliability of the arms **92** is advantageous as it allows for improved contact with the walls **159** of the hollow anatomical structure and which can match the sometimes-complex surface topography over an extended area. This is particularly of advantage, for example, if the electrode is expanded for use within a varicose vein or within a tortuous oviduct.

The pivotal connections between the electrode arm **92** and the hub **94**, the strut **95** and the collar **93**, and optionally the strut **95** and the arm **92**, can suitably be in the form of an articulated joint or hinge. In a further embodiment of the invention a resilient member **94b** can be located proximal to semi-fixed hub **94a** (see FIG. **7**(b)), this allows for the hub **94a** to be displaced proximally by a certain amount in response to compression exerted on the flexible arms **92** by the contract-

ing vessel walls during the thermal ablation step. By allowing a certain amount of free longitudinal movement of the hub **94** the contact between the arms **92** and the walls of the hollow anatomical structure can be maintained, particularly if the expanded electrode is in the process of being withdrawn from the hollow anatomical structure whilst the ablation is occurring (as indicated by directional arrow D in FIG. 7(b)). The resilient member **94b** is suitably tensioned to provide an appropriate biasing force against the hub **94a**. The resilient member **94b** may comprise a resilient or elastic polymeric material or a spring.

Contact between the expanded umbrella electrode and the walls can be increased by inclusion of additional electrode cross wires **92b** that extend across the span between adjacent expanded flexible electrode arms **92** so as to be arrayed circumferentially about the longitudinal axis of the shaft **96** (see FIG. 7(a)). The combination of the flexible arms **92** together with the spanning cross wires **92b** effectively converts the expandable electrode into an expandable web-like structure. The additional cross wires **92b** are suitably manufactured from similar materials to those used to make the flexible arms **92**. It should be noted that the inclusion of additional cross wires is not limited to the expandable umbrella electrode embodiment of the invention, but can also extend to the other expandable electrode configurations described above.

In a specific embodiment of the invention it is desirable to provide a device comprising a detachable distal end tip, which end tip comprises the electrode. Typically, the end tip will be detached following the therapy phase after thermal ablation of the hollow anatomical structure has occurred. This may be necessary in situations where there is tissue adhesion to the electrode surface as a result of heating and there exists a risk of haemorrhage or damage to peripheral healthy tissue if the electrode were to be withdrawn. In such an embodiment of the invention, one or more detachment mechanisms can be employed that facilitate release of the distal end tip and, thus, removal of the guidewire device following the therapy phase. The detached end tip remains in the body of the patient following treatment and can serve as an additional occluding structure to assist in maintenance of the integrity of the occlusion.

A number of suitable detachment mechanisms are provided by the invention for facilitating the release of the distal end tip in situ following the therapy phase and are shown in FIG. 9(a-f). It should be noted that the detachment mechanisms described are suitable for use with any or all of the aforementioned expandable electrode configurations.

FIG. 9(a) shows an embodiment comprising a detachable tip. A central conductor core **221** is affixed to the central conductor **22** of the guidewire **10** with a disc of joining material **23**. Electrode contacts **141** are attached to the central conductor core **221** and provide an ablation surface that contacts the surrounding tissue when in use. The joining material **23** comprises a material that will dissolve or melt during or shortly after thermal ablation, permitting the tip assembly to detach. In one embodiment the material is made of a suitable electrolytically erodeable metal, such as stainless steel. The electrode contacts **141** are suitably made of a material which is less electrolytically erodeable, such as platinum. In use, when a DC current is passed from the distal tip to a nearby electrode such as the patient electrode pad **4** or a needle inserted into nearby tissue, the joining material **23** will be eroded by electrolytic action. When the joining disc is eroded sufficiently, the tip will detach, allowing the main guidewire body **10** to be withdrawn. In another embodiment of the invention the joining material **23** comprises a material with a low melting point, such as wax, or polypropylene. When the

tissue surrounding the tip is heated by the application of RF energy, the temperature of this joining disc will be raised to a value when the material of the disc begins to soften, and no longer joins the tip to the main guidewire body.

Another embodiment of the invention comprising a detachable tip is shown in FIG. 9(b), in which the terminus of the main guidewire body **10** comprises a retaining member **25** that includes a threaded joining member **24**. The joining member **24** is able to engage with a matching threaded cavity formed in the proximally facing portion of the central conducting core **221** in the distal tip. The distal tip is detached from the guidewire body **10** by rotating the main guidewire about its longitudinal axis so as to unscrew the guide wire body **10** from the distal tip. It will be appreciated that the distal tip will be anchored into the tissue following the thermal ablation due to adhesion between the ablated tissue and the electrode contacts **221**.

FIG. 9(c) shows a further embodiment of the invention comprising a detachable tip. The central conductor core **22** of the main guidewire body **10** comprises a socket **28** formed in the distally facing terminus of the core **22**. The central conductor core **221** of the distal tip is of a dimension that allows it to be received within the socket so as to enable a male/female engagement. The engagement is secured via a tether **261**, suitably a wire, fine cable or thread (e.g. nylon thread), which passes along the length of the guidewire body **10** via channels **26** located adjacent to the steering members **21**, and passes through an aperture **27** formed in the central conductor core **221**. Typically the tether channels **26** will be defined by an insulated conduit that allows free movement of the tether along the channel. In use, the tether forms a loop through the aperture **27** and anchors the detachable tip to the body of the guidewire **10**. The ends of the tether **262** exit from the proximal end of the guidewire outside of the patient's body **2**. To detach the distal tip the tether can simply be withdrawn from the device by pulling on one of the ends **262** in direction B. Alternatively, the tether can be cut at position A, and one of the ends **262**, is pulled to remove the loop of wire from the guidewire **10**, again in direction B.

A further embodiment of the detachable tip is shown in FIG. 9(d) in which a magnetic release mechanism is utilised. The central conductor core **22** of the main guidewire body **10** is attached to a permanent magnet **30**. The magnet suitably comprises a material based on Neodymium-Boron, or a similar high coercivity and high remanence material. The material is modified to have a Curie temperature in the range of the thermal ablation temperature. The central conductor core **221** of the detachable distal tip is attached to a ferromagnetic yoke **31** located at the proximally facing side of the detachable distal tip. In use, the yoke **31** engages the magnet **30** via magnetic attraction. During thermal ablation, the distal tip region is heated to the ablation temperature, at which point the magnet **30** loses its magnetic properties, and the tip becomes detached from the guidewire body **10**, thereby permitting removal of the guidewire device.

Another embodiment of the detachable tip assembly is shown in FIG. 9(e). Extending distally from the distal terminus of the steering members **21** of the main guidewire body **10** are two or more deformable latching arms **35**. At the distal end of each arm **35** there is located a locking member **34**, suitably a lug, which is capable of engaging with a recess **33** formed in the surface of the distal end tip. The recess **33** may be in the form of a depression, or as a groove that extends around the circumference of the distal end tip and which is defined by a space between the proximal end portion of the electrode contacts **141** and an annular retaining ring **32**. In use, when the arms **35** are in the extended positions and the locking

members **34** engaged with the recess **33**, the distal tip is secured to the main guidewire body **10**. The arms **35** are suitably made of a material that changes shape with temperature. The arms **35** may comprise a bimetallic strip, made of a laminate of two materials of different thermal expansion coefficients such as bronze and steel. Alternatively the arms **35** can comprise nitinol used in shape memory mode, with the transition temperature suitably arranged to coincide with the thermal ablation temperature. When the distal tip is heated, during the therapy phase, the arms **35** will deform outwardly (as shown by deformed arm **35'**) so that the locking member **34** no longer engages with the recess **33**. When the arms **35'** are deformed the distal tip is no longer anchored to the guidewire body **10** and can be detached. Although the figures show the deformable latching arms **35** as separate components from the steering members **21**, in an embodiment of the invention the arms **35** are simply integral distal extensions of the steering members.

A similar embodiment to that described above is shown in FIG. **9** (f). Located at the distal terminus of the steering members **21** of the main guidewire body **10** are two or more deformable latching arms **35** in a configuration akin to that described previously. The deformable arms comprise an elastic material which is configured such that so that the arms **35** are splayed outwardly when unconstrained so that the locking members **34** are disengaged from the recess **33**. The elastic material may suitably comprise spring steel, or nitinol in super-elastic mode. A slideable mounted sleeve **111** enshrouds at least the distal portion of the guidewire body **10** and is capable of reciprocal movement along the longitudinal axis of the device as shown by arrow **y**. When the sleeve **111** is moved distally the arms **35** will be urged into a configuration that is parallel to the guidewire axis, so that the locking members **34** engage with the recess **33** and the distal tip is attached to the guidewire body. When the sleeve **111** is moved proximally, the arms **35** will splay outwardly and the locking members **34** disengage from the recess **33** and the distal tip will detach from the main guidewire body **10**.

In both the embodiments described above, the latching arms **35** can serve to provide an electrical connection between the core conductor **22** of the guidewire body **10** and the central core **221** of the distal tip.

In specific embodiments of the invention, the device may contain more than one detachable distal tips. For example, a plurality of detachable tips can be 'stacked' at the distal end region of the device and sequentially released either in a single location or at multiple discrete locations within the patient's body. In this way, the invention permits use of the device in a single-entry-multiple-treatment format. This arrangement is particularly suited to clinical indications where several lesions, tumours or metastases are present within or proximate to the hollow anatomical structure and all require ablation during a single surgical procedure. One or more of the above described tip detachment mechanisms can be combined into a single device if necessary in embodiments of the invention relating to the multiple detachable tip arrangement.

By way of example, methods of the invention using the device comprising a detachable tip can typically include the following steps.

- i) Insertion of the guidewire device into the patient through a suitable endoscopic, laparoscopic or vascular access port.
- ii) Manoeuvre of the guidewire so that the distal tip is located in an appropriate hollow anatomical structure,

this may be a blood vessel supplying a lesion, inside the lesion, inside an arterio-venous malformation or within a tube or duct.

- iii) Connection of the proximal end of the guidewire assembly to a radiofrequency (RF) generator.
- iv) Application of RF power to the electrode tip via the central conductor core, using a patient electrode pad as the return electrode (monopolar configuration).
- v) Cessation of application of power when the hollow anatomical structure is sealed or the surrounding tissue is ablated.
- vi) If not already achieved during (v), activation of the tip detachment mechanism, and separation of the distal tip from the main body of the guidewire.
- vii) Withdrawal of the main body of the guidewire device from the patient.

In embodiments of the invention where multiple detachable distal tips are used, steps (ii) to (vi) are repeated as necessary prior to withdrawal of the device from the patient's body.

Whilst devices of the invention comprise the distal portion which is inserted into the body and which applies the therapy to the required location, the proximal portion of the device may suitably comprise the user interface and energy connection functions. The proximal end of the device of the invention is located outside of the patient's body when in use and provides a user interface, typically in the form of a handle grip or hub **50** as well as a means for connecting the guidewire **10** to an energy source. The energy connection may be in the form of a direct connection to an energy source, such as an RF generator. In this arrangement the application of energy to the electrode(s) at the distal tip is achieved by activating the energy source.

Alternatively, an embodiment of the invention is shown in FIGS. **10** (a) and (b) which shows a hub **80** comprising a plug and socket arrangement **83,84** that can be slidably mounted over a guidewire which passes through central channel **85** defined by the housing **86** and a barrel **81**. The plug **86** is connected to an RF source via a lead **87**, and can engage the socket **83** through the action of the user pushing the attached slider **82** in a distal (i.e. forward) direction. The guidewire is in electrical contact with the socket **83** and thus when the plug **84** and socket **83** are engaged the RF source can be activated to apply RF energy at the therapy site via the guidewire or the electrode(s) located at the distal tip of the guidewire. The arrangement also allows for ease of connection to the remote energy source after the guidewire **10** has been positioned correctly.

In a specific embodiment of the invention shown in FIGS. **11** and **12**, a slidably mounted electrical interface hub **40** is provided. The hub **40** comprises a body **44** upon which is located a sliding actuator or switch **41**, and a barrel **42** which defines a bore **43** (see FIG. **11** (a)). The barrel **42** extends through the central portion of the body **44** and allows for slidably mounting of the hub **40** on a guidewire **10** which passes through the bore **43**. A lead **45** to the RF energy source is connected to the body **44** (see FIG. **11** (b)).

In FIG. **12** (a) the internal features of a first embodiment of the invention are shown. The guidewire **10** is inserted into the hub **40** via the barrel **42** along the direction shown by arrow **T**. A portion of the central core **20** of the guidewire **10** is exposed at the proximal end so as to permit electrical connection between the central conducting core **22** and the external energy source. Within the body **44** of the hub **40** the exposed portion of the central core **20** is located between a contact pad **47** and an angled foot **46**. The contact pad **47** is in electrical contact with the remote energy source via the lead **45** which

enters the hub via port 49. The foot 46 is attached to the sliding actuator 41, which is slidable along the longitudinal axis of the guidewire 10 from a released position to a locking position, as shown by arrow S (see FIG. 12 (b)). In the released position the foot 46 does not contact the central core 20 and there is free movement of the guidewire 10 within the hub 40. When the sliding actuator is moved to the locking position the angled foot 46 is brought to bear upon the central core 20 thereby urging it into contact with the contact pad 47, establishing an electrical contact between the central conducting core 22 of the guidewire 10 and the remote energy source. An alternative arrangement is shown in FIG. 12 (b) in which the lead 45 enters the hub via a proximally directed port 491. In this embodiment of the invention the contact pad 47 does not serve as the source of the electrical connection but cooperates with the angled foot 46 to lock the guidewire 10 into position such that electrical connection with contacts at the terminus of the lead 45 can be established.

In an embodiment of the invention the device is able to cooperate with a catheter loaded thereupon either via a mono-rail or over-the-wire mounting. In this configuration, the catheter comprises an elongate body including a lumen, through which the guidewire device of the invention is located. As shown in FIG. 13, a catheter 150 is slidably mounted over a guidewire 155. Optionally, the catheter 150 may comprise an RF electrode 151 located at the distal tip. An aperture 152 is positioned in the side wall of the catheter proximally to the distal end of the catheter. The aperture is sealed via a pivotally mounted door 153. In use, the catheter 150 is slidably mounted onto the prepositioned guidewire 155 and located to the position in the body where therapy is required. The guidewire 155 is then withdrawn proximally until the distal tip of the guidewire 157 is withdrawn into the central lumen 158 of the catheter 150 to a point that is proximal relative to the location of the aperture 152. Optionally the guidewire 155 can be withdrawn completely and substituted with a therapeutic guidewire according to the present invention and substantially as described in any of the preceding embodiments. Retraction of the guidewire proximally causes the door 153 to open inwardly (along arrow P in FIG. 13(b)) via a user induced release mechanism (not shown) or simply by biasing the door 153 to spring open when the guidewire 155 is withdrawn. The guidewire 155 is then advanced proximally and is deflected out of the body of the catheter 150 through the aperture 152 and into the wall 159 of the surrounding hollow anatomical structure. In the bipolar configuration the RF electrode 156 on the guidewire 155 can cooperate with the RF electrode 151 on the catheter. In an alternative embodiment of the invention, the catheter 150 does not comprise an electrode 151 and so the guidewire operates in a monopolar configuration.

Optionally, the guidewire 155 can be configured to adopt a helical conformation once it has exited the aperture 152. This can be achieved by manufacturing at least the distal portion of the guidewire 155 from a shape memory alloy, for example. Hence, once the distal tip of the guidewire 155 has exited the aperture 152 it is able to spiral about the longitudinal axis of the catheter body in a distal direction through the tissue surrounding the hollow anatomical structure. In this embodiment, it is possible to configure the guidewire 155 to exert additional contraction force upon the hollow structure during the thermal phase by configuring the initial diameter of the helix prior to thermal ablation such that it is greater than the diameter assumed following transition. In a specific embodiment of the invention, suitably but not exclusively adapted to an endoscopic procedure for fallopian tubal ligation, the distal tip of the guidewire 155 is preformed from a shape

memory alloy such that on emergence from the aperture 152 in the side wall of the catheter 150 it penetrates through the wall of the fallopian tube, into the underlying muscular or serous tissue, and coils around the perimeter of the tube. On heating above the austenitic finish temperature (Af) the guidewire 155 reverts to the austenitic state which is arranged to be in the form of tighter helical coil (as described above) thereby facilitating occlusion of the tube. Optionally, the distal tip of the guidewire 155 may be detached and allowed to remain in situ by utilising one of the detachment mechanisms described in previous embodiments of the present invention (see above).

The guidewire devices of the invention can suitably be manufactured from materials that include stainless steel, platinum, gold, silver, titanium, a metal alloy or, when required, a shape memory alloy such as nitinol.

Although particular embodiments of the invention have been disclosed herein in detail, this has been done by way of example and for the purposes of illustration only. The aforementioned embodiments can be utilised alone or in combination and are not intended to be limiting with respect to the scope of the appended claims, which follow. It is contemplated by the inventors that various substitutions, alterations, and modifications may be made to the invention without departing from the spirit and scope of the invention as defined by the claims.

The invention claimed is:

1. A device suitable for insertion into a hollow anatomical structure within a patient via a percutaneous, laparoscopic or endoscopic route for the purpose of ablating tissue within or surrounding the hollow structure so as to induce occlusion of the hollow structure, the device comprising:

a guidewire having a distal end and a proximal end, the guidewire comprising a central core which extends along the length of the body, the central core comprising at least one conductor and a plurality of steering members, a tip located at the distal end of the guidewire wherein the tip comprises at least one heating module and means for connecting the at least one conductor to an external energy source, said means being located at the proximal end of the guidewire;

a catheter having an elongate body including a lumen extending along at least a portion of the elongate body, wherein the lumen is adapted to facilitate slidably mounting of the catheter on the guidewire, an aperture positioned in the side wall of the catheter proximally to the distal end of the catheter, the aperture being sealable via a pivotally mounted door; and

wherein, in use, the guidewire can be withdrawn proximally until the distal tip of the guidewire is located within the lumen of the catheter at a point that is adjacent to the aperture which permits the door to be opened inwardly, such that upon subsequent advancement of the guidewire the tip is deflected outwardly from the lumen of the catheter through the aperture and into the surrounding hollow anatomical structure where the at least one heating module can be activated so as to induce ablation of the tissue.

2. The device of claim 1, wherein the device comprises a mechanism for permitting in situ detachment of the distal tip following activation of the at least one heating module.

3. The device of claim 1 wherein the hollow structure is selected from the group consisting of: a vein; an artery; an arteriole; a fallopian tube; a biliary duct; a ureter; a urethra; a bronchiole; and a vas deferens.

\* \* \* \* \*

专利名称(译)	用于在身体的远程位置进行治疗的装置		
公开(公告)号	<a href="#">US8357153</a>	公开(公告)日	2013-01-22
申请号	US12/522721	申请日	2008-01-11
[标]申请(专利权)人(译)	哈比卜医疗		
申请(专利权)人(译)	哈比卜医药有限		
当前申请(专利权)人(译)	emcision公司		
[标]发明人	HABIB NAGY		
发明人	HABIB, NAGY		
IPC分类号	A61B18/14		
CPC分类号	A61B18/1492 A61B18/082 A61B2017/00867 A61B2018/00214 A61B2018/00267 A61B2018/1435 A61B2018/1467 A61B2018/1495 C08L2201/12		
优先权	2007024347 2007-12-13 GB 2007007370 2007-04-13 GB 2007000553 2007-01-11 GB		
其他公开文献	US20100106149A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

提供了适于插入患者体内的中空解剖结构中的装置，其目的是消融中空结构内或周围的组织，从而引起中空结构的闭塞。所述装置为具有功能尖端的导丝形式，所述功能尖端在其远端包括至少一个加热模块。本发明的装置适用于通过经皮，腹腔镜或内窥镜通路进入阻塞选自脉管系统或非血管和管的中空解剖结构。还描述了在患者的治疗中使用该装置的方法。

