



US008647265B2

(12) **United States Patent**  
**Brustad et al.**

(10) **Patent No.:** **US 8,647,265 B2**  
(45) **Date of Patent:** **Feb. 11, 2014**

(54) **HAND ACCESS LAPAROSCOPIC DEVICE**

(75) Inventors: **John R. Brustad**, Dana Point, CA (US);  
**Jeremy J. Albrecht**, Rancho Santa  
Margarita, CA (US); **Nabil Hilal**,  
Laguna Nigul, CA (US); **Gary M.**  
**Johnson**, Mission Viejo, CA (US);  
**Charles C. Hart**, Summerville, SC (US)

(73) Assignee: **Applied Medical Resources**  
**Corporation**, Rancho Santa Margarita,  
CA (US)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 398 days.

(21) Appl. No.: **13/006,727**

(22) Filed: **Jan. 14, 2011**

(65) **Prior Publication Data**

US 2011/0112374 A1 May 12, 2011

**Related U.S. Application Data**

(60) Continuation of application No. 12/815,986, filed on  
Jun. 15, 2010, now Pat. No. 7,878,974, which is a  
division of application No. 11/548,955, filed on Oct.  
12, 2006, now Pat. No. 7,736,306.

(60) Provisional application No. 60/745,730, filed on Apr.  
26, 2006, provisional application No. 60/803,346,  
filed on May 26, 2006, provisional application No.  
60/803,965, filed on Jun. 5, 2006, provisional  
application No. 60/828,089, filed on Oct. 4, 2006,  
provisional application No. 60/726,826, filed on Oct.  
14, 2005.

(51) **Int. Cl.**  
**A61B 1/32** (2006.01)

(52) **U.S. Cl.**  
USPC ..... 600/208; 600/201

(58) **Field of Classification Search**

USPC ..... 600/201-246  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

558,364 A	4/1896	Doolittle
1,157,202 A	10/1915	Bates et al.
1,598,284 A	8/1926	Kinney
1,690,995 A	11/1928	Pratt
1,180,466 A	6/1931	Deutsch
1,810,466 A	6/1931	Deutsch

(Continued)

**FOREIGN PATENT DOCUMENTS**

DE	26 05 148 A1	8/1977
DE	33 36 279 C2	1/1986

(Continued)

**OTHER PUBLICATIONS**

U.S. Appl. No. 10/902,756, filed Jul. 29, 2004; Title: Hand Access  
Port Device, now abandoned.

(Continued)

*Primary Examiner* — Mary Hoffman


*Assistant Examiner* — Christina Negrelli-rodriguez

(74) *Attorney, Agent, or Firm* — Patrick Y. Ikehara

(57) **ABSTRACT**

The invention relates to a hand access laparoscopy device having a gelcap, a retainer, a sleeve and a retention ring. The gelcap includes gel that is bonded to a cap. The cap includes an inner cylindrical wall to which the gel is bonded, thereby providing a sealing area between the device and the wound in a body wall. By securing the gel to the inner cylindrical wall, the thickness of the gel and corresponding cap is minimized along with the overall footprint of the device. With the gel thickness reduced and able to be substantially flush, the “doming” phenomenon produced by insufflation of a patient’s abdomen is reduced.

**15 Claims, 16 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

2,219,564 A	10/1940	Reyniers	4,338,937 A	7/1982	Lerman
2,305,289 A	12/1942	Coburg	4,367,728 A	1/1983	Mutke
2,478,586 A	8/1949	Krapp	4,369,284 A	1/1983	Chen
2,669,991 A	2/1954	Curutchet	4,399,816 A	8/1983	Spangler
2,695,608 A	11/1954	Gibbon	4,402,683 A	9/1983	Kopman
2,812,758 A	11/1957	Blumenschein	4,411,659 A	10/1983	Jensen et al.
2,835,253 A	5/1958	Borgeson	4,421,296 A	12/1983	Stephens
2,853,075 A	9/1958	Hoffman et al.	4,424,833 A	1/1984	Spector et al.
3,039,468 A	6/1962	Price	4,428,364 A	1/1984	Bartolo
3,057,350 A	10/1962	Cowley	4,430,081 A	2/1984	Timmermans
3,111,943 A	11/1963	Orndorff	4,434,791 A	3/1984	Darnell
3,195,934 A	7/1965	Parrish	4,436,519 A	3/1984	O'Neill
3,244,169 A	4/1966	Baxter	4,454,873 A	6/1984	Laufenberg et al.
3,253,594 A	5/1966	Matthews et al.	4,473,067 A	9/1984	Schiff
3,313,299 A	4/1967	Spademan	4,475,548 A	10/1984	Muto
3,329,390 A	7/1967	Hulsey	4,485,490 A	12/1984	Akers et al.
3,332,417 A	7/1967	Blanford et al.	4,488,877 A	12/1984	Klein
3,347,226 A	10/1967	Harrower	4,543,088 A	9/1985	Bootman et al.
3,347,227 A	10/1967	Harrower	4,550,713 A	11/1985	Hyman
3,397,692 A	8/1968	Creager, Jr. et al.	4,553,537 A	11/1985	Rosenberg
3,402,710 A	9/1968	Paleschuck	4,555,242 A	11/1985	Saudagar
3,416,520 A	12/1968	Creager, Jr.	4,556,996 A	12/1985	Wallace
3,447,533 A	6/1969	Spicer	4,601,710 A	7/1986	Moll
3,522,800 A	8/1970	Lesser	4,610,665 A	9/1986	Matsumoto et al.
3,523,534 A	8/1970	Nolan	4,626,245 A	12/1986	Weinstein
3,570,475 A	3/1971	Weinstein	4,634,424 A	1/1987	O'Boyle
3,656,485 A	4/1972	Robertson	4,634,432 A	1/1987	Kocak
3,685,786 A	8/1972	Woodson	4,644,951 A	2/1987	Bays
3,717,151 A	2/1973	Collett	4,649,904 A	3/1987	Krauter
3,717,883 A	2/1973	Mosher	4,653,476 A	3/1987	Bonnet
3,729,006 A	4/1973	Wilder et al.	4,654,030 A	3/1987	Moll et al.
3,782,370 A	1/1974	McDonald	4,655,752 A	4/1987	Honkanen et al.
3,797,478 A	3/1974	Walsh et al.	4,673,393 A	6/1987	Suzuki et al.
3,799,166 A	3/1974	Marsan	4,673,394 A	6/1987	Fenton
3,807,393 A	4/1974	McDonald	4,691,942 A	9/1987	Ford
3,828,764 A	8/1974	Jones	4,714,749 A	12/1987	Hughes et al.
3,831,583 A	8/1974	Edmunds et al.	4,738,666 A	4/1988	Fuqua
3,841,332 A	10/1974	Treacle	4,755,170 A	7/1988	Golden
3,850,172 A	11/1974	Cazalis	4,760,933 A	8/1988	Christner et al.
3,853,126 A	12/1974	Schulte	4,776,843 A	10/1988	Martinez et al.
3,853,127 A	12/1974	Spademan	4,777,943 A	10/1988	Chvapil
3,856,021 A	12/1974	McIntosh	4,784,646 A	11/1988	Feingold
3,860,274 A	1/1975	Ledstrom et al.	4,796,629 A	1/1989	Grayzel
3,861,416 A	1/1975	Wichterle	4,798,594 A	1/1989	Hillstead
3,907,389 A	9/1975	Cox et al.	4,802,694 A	2/1989	Vargo
3,915,171 A	10/1975	Shermeta	4,808,168 A	2/1989	Warring
3,965,890 A	6/1976	Gauthier	4,809,679 A	3/1989	Shimonaka et al.
3,970,089 A	7/1976	Saice	4,828,554 A	5/1989	Griffin
3,996,623 A	12/1976	Kaster	4,842,931 A	6/1989	Zook
4,000,739 A	1/1977	Stevens	4,848,575 A	7/1989	Nakamura et al.
4,016,884 A	4/1977	Kwan-Gett	4,856,502 A	8/1989	Ersfeld et al.
4,024,872 A	5/1977	Muldoon	4,863,430 A	9/1989	Klyce et al.
4,030,500 A	6/1977	Ronnquist	4,863,438 A	9/1989	Gauderer et al.
4,043,328 A	8/1977	Cawood, Jr. et al.	4,889,107 A	12/1989	Kaufman
4,069,913 A	1/1978	Harrigan	4,895,565 A	1/1990	Hillstead
4,082,005 A	4/1978	Erdley	4,897,081 A	1/1990	Poirier
4,083,370 A	4/1978	Taylor	4,903,710 A	2/1990	Jessamine et al.
4,096,853 A	6/1978	Weigand	4,911,974 A	3/1990	Shimizu et al.
4,112,932 A	9/1978	Chiulli	4,915,132 A	4/1990	Hodge et al.
4,130,113 A	12/1978	Graham	4,926,882 A	5/1990	Lawrence
4,177,814 A	12/1979	Knepshild et al.	4,929,235 A	5/1990	Merry et al.
4,183,357 A	1/1980	Bentley et al.	4,944,732 A	7/1990	Russo
4,187,849 A	2/1980	Stim	4,950,222 A	8/1990	Scott et al.
4,188,945 A	2/1980	Wenander	4,950,223 A	8/1990	Silvanov
4,217,664 A	8/1980	Faso	4,984,564 A	1/1991	Yuen
4,222,126 A	9/1980	Boretos et al.	4,991,593 A	2/1991	LeVahn
4,228,792 A	10/1980	Rhys-Davies	4,998,538 A	3/1991	Charowsky et al.
4,239,036 A	12/1980	Krieger	5,000,745 A	3/1991	Guest et al.
4,240,411 A	12/1980	Hosono	5,009,224 A	4/1991	Cole
4,253,201 A	3/1981	Ross et al.	5,015,228 A	5/1991	Columbus et al.
4,254,973 A	3/1981	Benjamin	5,019,101 A	5/1991	Purkait et al.
4,306,562 A	12/1981	Osborne	5,026,366 A	6/1991	Leckrone
4,321,915 A	3/1982	Leighton	5,037,379 A	8/1991	Clayman et al.
4,331,138 A	5/1982	Jessen	5,041,095 A	8/1991	Littrell
4,338,934 A	7/1982	Spademan	5,045,070 A	9/1991	Grodecki et al.
			D320,658 S	10/1991	Quigley et al.
			5,071,411 A	12/1991	Hillstead
			5,073,169 A	12/1991	Raiken
			5,074,878 A	12/1991	Bark et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,082,005 A	1/1992	Kaldany	5,342,385 A	8/1994	Norelli et al.
5,086,763 A	2/1992	Hathman	5,350,364 A	9/1994	Stephens et al.
5,092,846 A	3/1992	Nishijima et al.	5,353,786 A	10/1994	Wilk
5,104,389 A	4/1992	Deem	5,354,280 A	10/1994	Haber et al.
5,125,396 A	6/1992	Ray	5,360,417 A	11/1994	Gravener et al.
5,125,897 A	6/1992	Quinn et al.	5,364,345 A	11/1994	Lowery et al.
5,127,626 A	7/1992	Hilal et al.	5,364,372 A	11/1994	Danks et al.
5,129,885 A	7/1992	Green et al.	5,366,446 A	11/1994	Tal et al.
5,141,498 A	8/1992	Christian	5,366,478 A	11/1994	Brinkerhoff et al.
5,149,327 A	9/1992	Oshiyama	5,368,545 A	11/1994	Schaller et al.
5,156,617 A	10/1992	Reid	5,375,588 A	12/1994	Yoon
5,158,553 A	10/1992	Berry et al.	5,380,288 A	1/1995	Hart et al.
5,159,921 A	11/1992	Hoover	5,383,861 A	1/1995	Hempel et al.
5,161,773 A	11/1992	Tower	5,385,552 A	1/1995	Haber et al.
5,167,636 A	12/1992	Clement	5,385,553 A	1/1995	Hart et al.
5,167,637 A	12/1992	Okada et al.	5,385,560 A	1/1995	Wulf
5,176,648 A	1/1993	Holmes et al.	5,389,080 A	2/1995	Yoon
5,176,662 A	1/1993	Bartholomew et al.	5,389,081 A	2/1995	Castro
5,176,697 A	1/1993	Hasson et al.	5,391,153 A	2/1995	Haber et al.
5,178,162 A	1/1993	Bose	5,391,156 A	2/1995	Hildwein et al.
5,180,365 A	1/1993	Ensminger et al.	5,395,367 A	3/1995	Wilk
5,183,471 A	2/1993	Wilk	5,403,264 A	4/1995	Wohlens et al.
5,188,595 A	2/1993	Jacobi	5,403,336 A	4/1995	Kieturakis et al.
5,188,607 A	2/1993	Wu	5,407,433 A	4/1995	Loomas
5,192,301 A	3/1993	Kamiya et al.	5,411,483 A	5/1995	Loomas
5,197,955 A	3/1993	Stephens et al.	5,413,571 A	5/1995	Katsaros et al.
5,201,714 A	4/1993	Gentelia et al.	5,423,848 A	6/1995	Washizuka et al.
5,207,656 A	5/1993	Kranys	5,429,609 A	7/1995	Yoon
5,209,737 A	5/1993	Rirchart et al.	5,431,676 A	7/1995	Dubrul et al.
5,211,370 A	5/1993	Powers	5,435,943 A	7/1995	Adams et al.
5,211,633 A	5/1993	Stouder, Jr.	5,437,683 A	8/1995	Neumann et al.
5,213,114 A	5/1993	Bailey, Jr.	5,439,455 A	8/1995	Kieturakis et al.
5,226,890 A	7/1993	Ianniruberto et al.	5,441,486 A	8/1995	Yoon
5,234,455 A	8/1993	Mulhollan	5,443,452 A	8/1995	Hart et al.
5,241,968 A	9/1993	Slater	5,456,284 A	10/1995	Ryan et al.
5,242,400 A	9/1993	Blake, III et al.	5,460,170 A	10/1995	Hammerslag
5,242,409 A	9/1993	Buelna	5,460,616 A	10/1995	Weinstein et al.
5,242,412 A	9/1993	Blake, III	5,468,248 A	11/1995	Chin et al.
5,242,415 A	9/1993	Kantrowitz et al.	5,476,475 A	12/1995	Gadberry
5,248,304 A	9/1993	Vigdorchik et al.	5,480,410 A	1/1996	Cuschieri et al.
5,256,150 A	10/1993	Quiachon et al.	5,486,426 A	1/1996	McGee et al.
5,257,973 A	11/1993	Villasuso	5,490,843 A	2/1996	Hildwein et al.
5,257,975 A	11/1993	Foshee	5,492,304 A	2/1996	Smith et al.
5,259,366 A	11/1993	Reydel et al.	5,496,280 A	3/1996	Vandenbroek et al.
5,261,883 A	11/1993	Hood et al.	5,503,112 A	4/1996	Luhman et al.
5,262,468 A	11/1993	Chen	5,507,758 A	4/1996	Thomason et al.
5,263,922 A	11/1993	Sova et al.	5,508,334 A	4/1996	Chen
5,269,763 A	12/1993	Boehmer et al.	5,511,564 A	4/1996	Wilk
5,269,772 A	12/1993	Wilk	5,514,109 A	5/1996	Mollenauer et al.
5,273,449 A	12/1993	Mattis et al.	5,514,133 A	5/1996	Golub et al.
5,273,545 A	12/1993	Hunt et al.	5,514,153 A	5/1996	Bonutti
D343,236 S	1/1994	Quigley et al.	5,518,278 A	5/1996	Sampson
5,279,575 A	1/1994	Sugarbaker	5,520,632 A	5/1996	Leveen
5,290,310 A	3/1994	Makower et al.	5,522,791 A	6/1996	Leyva
D346,022 S	4/1994	Quigley et al.	5,522,824 A	6/1996	Ashby
5,299,582 A	4/1994	Potts	5,524,644 A	6/1996	Crook
5,300,034 A	4/1994	Behnke	5,526,536 A	6/1996	Cartmill
5,300,035 A	4/1994	Clement	5,531,758 A	7/1996	Uschold et al.
5,300,036 A	4/1994	Mueller et al.	5,538,509 A	7/1996	Dunlap et al.
5,308,336 A	5/1994	Hart et al.	5,540,648 A	7/1996	Yoon
5,309,896 A	5/1994	Moll et al.	5,540,711 A	7/1996	Kieturakis et al.
5,312,391 A	5/1994	Wilk	5,545,150 A	8/1996	Danks et al.
5,314,417 A	5/1994	Stephens et al.	5,545,179 A	8/1996	Williamson, IV
5,316,541 A	5/1994	Fischer	5,549,563 A	8/1996	Kronner
5,320,611 A	6/1994	Bonutti et al.	5,549,637 A	8/1996	Crainich
5,330,437 A	7/1994	Durman	5,554,124 A	9/1996	Alvarado
5,330,486 A	7/1994	Wilk	5,562,632 A	10/1996	Davila et al.
5,330,497 A	7/1994	Freitas et al.	5,562,677 A	10/1996	Hildwein et al.
5,331,975 A	7/1994	Bonutti	5,562,688 A	10/1996	Riza
5,334,143 A	8/1994	Carroll	5,571,115 A	11/1996	Nicholas
5,334,646 A	8/1994	Chen	5,571,137 A	11/1996	Marlow et al.
5,336,192 A	8/1994	Palestrant	5,575,799 A	11/1996	Bolanos et al.
5,336,708 A	8/1994	Chen	5,577,993 A	11/1996	Zhu et al.
5,338,313 A	8/1994	Mollenauer et al.	5,578,048 A	11/1996	Pasqualucci et al.
5,342,315 A	8/1994	Rowe et al.	5,580,344 A	12/1996	Hasson
			5,584,850 A	12/1996	Hart et al.
			5,601,579 A	2/1997	Semertzides
			5,601,581 A	2/1997	Fogarty et al.
			5,603,702 A	2/1997	Smith et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,607,443 A	3/1997	Kieturakis et al.	5,871,474 A	2/1999	Hermann et al.
5,620,415 A	4/1997	Lucey et al.	5,876,413 A	3/1999	Fogarty et al.
5,620,420 A	4/1997	Kriesel	5,879,368 A	3/1999	Hoskin et al.
5,628,732 A	5/1997	Antoon, Jr. et al.	5,882,344 A	3/1999	Stouder, Jr.
5,632,284 A	5/1997	Graether	5,884,639 A	3/1999	Chen
5,632,979 A	5/1997	Goldberg et al.	5,894,843 A	4/1999	Benetti et al.
5,634,911 A	6/1997	Hermann et al.	5,895,377 A	4/1999	Smith et al.
5,634,936 A	6/1997	Linden et al.	5,899,208 A	5/1999	Bonadio
5,634,937 A	6/1997	Mollenauer et al.	5,899,913 A	5/1999	Fogarty et al.
5,636,645 A	6/1997	Ou	5,904,703 A	5/1999	Gilson
5,640,977 A	6/1997	Leahy et al.	5,906,577 A	5/1999	Beane et al.
5,643,301 A	7/1997	Mollenauer	5,913,847 A	6/1999	Yoon
5,649,550 A	7/1997	Crook	5,916,198 A	6/1999	Dillow
5,651,771 A	7/1997	Tangherlini et al.	5,916,232 A	6/1999	Hart
5,653,705 A	8/1997	de la Torre et al.	5,919,476 A	7/1999	Fischer et al.
5,657,963 A	8/1997	Hinchliffe et al.	5,931,832 A	8/1999	Jensen
5,658,272 A	8/1997	Hasson	5,947,922 A	9/1999	MacLeod
5,658,306 A	8/1997	Kieturakis	5,951,467 A	9/1999	Picha et al.
5,662,615 A	9/1997	Blake, III	5,951,588 A	9/1999	Moenning
5,672,168 A	9/1997	de la Torre et al.	5,957,888 A	9/1999	Hinchliffe et al.
5,681,341 A	10/1997	Lunsford et al.	5,957,913 A	9/1999	de la Torre et al.
5,683,378 A	11/1997	Christy	5,962,572 A	10/1999	Chen
5,685,854 A	11/1997	Green et al.	5,964,781 A	10/1999	Mollenauer et al.
5,685,857 A	11/1997	Negus et al.	5,976,174 A	11/1999	Ruiz
5,697,914 A	12/1997	Brimhall	5,980,806 A	11/1999	Ohmi et al.
5,707,703 A	1/1998	Rothrum et al.	5,989,232 A	11/1999	Yoon
5,709,664 A	1/1998	Vandenbroek et al.	5,989,233 A	11/1999	Yoon
5,713,858 A	2/1998	Heruth et al.	5,989,266 A	11/1999	Foster
5,713,869 A	2/1998	Morejon	5,993,471 A	11/1999	Riza et al.
5,720,730 A	2/1998	Blake, III	5,993,485 A	11/1999	Beckers
5,725,536 A	3/1998	Oberlin et al.	5,994,450 A	11/1999	Pearce
5,728,103 A	3/1998	Picha et al.	5,997,515 A	12/1999	de la Torre et al.
5,730,748 A	3/1998	Fogarty et al.	6,004,303 A	12/1999	Peterson
5,735,791 A	4/1998	Alexander et al.	6,010,494 A	1/2000	Schafer et al.
5,738,628 A	4/1998	Sierocuk et al.	6,017,355 A	1/2000	Hessel et al.
5,741,234 A	4/1998	Aboul-Hosn	6,018,094 A	1/2000	Fox
5,741,298 A	4/1998	MacLeod	6,024,736 A	2/2000	de la Torre et al.
5,743,884 A	4/1998	Hasson et al.	6,025,067 A	2/2000	Fay
5,749,882 A	5/1998	Hart et al.	6,033,426 A	3/2000	Kaji
5,753,150 A	5/1998	Martin et al.	6,033,428 A	3/2000	Sardella
5,755,660 A	5/1998	Tyagi	6,035,559 A	3/2000	Freed et al.
5,760,117 A	6/1998	Chen	6,042,573 A	3/2000	Lucey
5,769,783 A	6/1998	Fowler	6,045,535 A	4/2000	Ben Nun
5,782,812 A	7/1998	Hart et al.	6,048,309 A	4/2000	Flom et al.
5,782,817 A	7/1998	Franzel et al.	6,050,871 A	4/2000	Chen
5,782,859 A	7/1998	Nicholas et al.	6,053,934 A	4/2000	Andrews et al.
5,788,676 A	8/1998	Yoon	6,059,806 A	5/2000	Hoegerle
5,792,119 A	8/1998	Marx	6,066,117 A	5/2000	Fox et al.
5,795,290 A	8/1998	Bridges	6,068,639 A	5/2000	Fogarty et al.
5,803,919 A	9/1998	Hart et al.	6,077,288 A	6/2000	Shimomura
5,803,921 A	9/1998	Bonadio	6,086,603 A	7/2000	Termin et al.
5,803,923 A	9/1998	Singh-Derewa et al.	6,090,043 A	7/2000	Austin et al.
5,807,350 A	9/1998	Diaz	6,093,358 A	7/2000	Schiewe et al.
5,810,712 A	9/1998	Dunn	6,099,506 A	8/2000	Macoviak et al.
5,810,721 A	9/1998	Mueller et al.	6,110,154 A	8/2000	Shimomura et al.
5,813,409 A	9/1998	Leahy et al.	6,123,689 A	9/2000	To et al.
5,814,026 A	9/1998	Yoon	6,142,935 A	11/2000	Flom et al.
5,817,062 A	10/1998	Flom et al.	6,142,936 A	11/2000	Beane et al.
5,819,375 A	10/1998	Kastner	6,149,642 A	11/2000	Gerhart et al.
5,820,555 A	10/1998	Watkins, III et al.	6,150,608 A	11/2000	Wambeke et al.
5,820,600 A	10/1998	Carlson et al.	6,159,182 A	12/2000	Davis
5,830,191 A	11/1998	Hildwein et al.	6,162,172 A	12/2000	Cosgrove et al.
5,832,925 A	11/1998	Rothrum	6,162,196 A	12/2000	Hart et al.
5,836,871 A	11/1998	Wallace et al.	6,162,206 A	12/2000	Bindokas
5,841,298 A	11/1998	Huang	6,163,949 A	12/2000	Neuenschwander
5,842,971 A	12/1998	Yoon	6,164,279 A	12/2000	Tweedle
5,848,992 A	12/1998	Hart et al.	6,171,282 B1	1/2001	Ragsdale
5,853,395 A	12/1998	Crook et al.	6,183,486 B1	2/2001	Snow et al.
5,853,417 A	12/1998	Fogarty et al.	6,197,002 B1	3/2001	Peterson
5,857,461 A	1/1999	Levitsky et al.	6,217,555 B1	4/2001	Hart et al.
5,860,995 A	1/1999	Berkelaar	6,217,590 B1	4/2001	Levinson
5,865,728 A	2/1999	Moll et al.	6,224,612 B1	5/2001	Bates et al.
5,865,729 A	2/1999	Meehan et al.	6,228,063 B1	5/2001	Aboul-Hosn
5,865,807 A	2/1999	Blake, III	6,238,373 B1	5/2001	de la Torre et al.
5,865,817 A	2/1999	Moenning et al.	6,241,768 B1	6/2001	Agarwal et al.
			6,254,533 B1	7/2001	Fadem et al.
			6,254,534 B1	7/2001	Butler et al.
			6,258,065 B1	7/2001	Dennis et al.
			6,264,604 B1	7/2001	Kieturakis et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,267,751	B1	7/2001	Mangosong	6,860,463	B2	3/2005	Hartley
6,276,661	B1	8/2001	Laird	6,863,674	B2	3/2005	Kasahara et al.
6,287,280	B1	9/2001	Lampropoulos et al.	6,866,861	B1	3/2005	Luhman
6,315,770	B1	11/2001	de la Torre et al.	6,867,253	B1	3/2005	Chen
6,319,246	B1	11/2001	de la Torre et al.	6,869,393	B2	3/2005	Butler
6,322,541	B2	11/2001	West	6,878,110	B2	4/2005	Yang et al.
6,325,384	B1	12/2001	Berry, Sr. et al.	6,884,253	B1	4/2005	McFarlane
6,346,074	B1	2/2002	Roth	6,890,295	B2	5/2005	Michels et al.
6,371,968	B1	4/2002	Kogasaka et al.	6,895,965	B2	5/2005	Scarberry et al.
6,375,877	B2	4/2002	Lauf et al.	6,902,541	B2	6/2005	McNally et al.
6,382,211	B1	5/2002	Crook	6,902,569	B2	6/2005	Parmer et al.
6,383,162	B1	5/2002	Sugarbaker	6,908,430	B2	6/2005	Caldwell et al.
6,391,043	B1	5/2002	Moll et al.	6,909,220	B2	6/2005	Chen
6,406,499	B1	6/2002	Kania	6,913,609	B2	7/2005	Yencho et al.
6,413,244	B1	7/2002	Bestetti et al.	6,916,310	B2	7/2005	Sommerich
6,413,458	B1	7/2002	Pearce	6,916,331	B2	7/2005	Mollenauer et al.
6,420,475	B1	7/2002	Chen	6,929,637	B2	8/2005	Gonzalez et al.
6,423,036	B1	7/2002	Van Huizen	6,936,037	B2	8/2005	Bubb et al.
6,440,061	B1	8/2002	Wenner et al.	6,939,296	B2	9/2005	Ewers et al.
6,440,063	B1	8/2002	Beane et al.	6,945,932	B1	9/2005	Caldwell et al.
6,443,957	B1	9/2002	Addis	6,949,893	B2	9/2005	Higuchi
6,447,489	B1	9/2002	Peterson	6,958,037	B2	10/2005	Ewers et al.
6,450,983	B1	9/2002	Rambo	6,972,026	B1	12/2005	Caldwell et al.
6,454,783	B1	9/2002	Piskun	6,979,324	B2	12/2005	Bybordi et al.
6,464,686	B1	10/2002	O'Hara et al.	6,991,602	B2	1/2006	Nakazawa et al.
6,468,292	B1	10/2002	Mollenauer et al.	6,997,909	B2	2/2006	Goldberg
6,482,181	B1	11/2002	Racenet et al.	7,001,397	B2	2/2006	Davison et al.
6,485,435	B1	11/2002	Bakal	7,008,377	B2	3/2006	Beane et al.
6,485,467	B1	11/2002	Crook et al.	7,014,628	B2	3/2006	Bousquet
6,488,620	B1	12/2002	Segermark et al.	7,033,319	B2	4/2006	Pulford et al.
6,488,692	B1	12/2002	Spence et al.	7,052,454	B2	5/2006	Taylor
6,494,893	B2	12/2002	Dubrul et al.	7,056,304	B2	6/2006	Bacher et al.
6,527,787	B1	3/2003	Fogarty et al.	7,056,321	B2	6/2006	Pagliuca et al.
6,533,734	B1	3/2003	Corley, III et al.	7,067,583	B2	6/2006	Chen
6,551,270	B1	4/2003	Bimbo et al.	7,077,852	B2	7/2006	Fogarty et al.
6,551,276	B1	4/2003	Mann et al.	7,081,089	B2	7/2006	Bonadio et al.
6,551,344	B2	4/2003	Thill	7,083,626	B2	8/2006	Hart et al.
6,552,109	B1	4/2003	Chen	7,093,599	B2	8/2006	Chen
6,554,793	B1	4/2003	Pauker et al.	7,100,614	B2	9/2006	Stevens et al.
6,558,371	B2	5/2003	Dorn	7,101,353	B2	9/2006	Lui et al.
6,569,120	B1	5/2003	Green	7,105,009	B2	9/2006	Johnson et al.
6,578,577	B2	6/2003	Bonadio et al.	7,105,607	B2	9/2006	Chen
6,579,281	B2	6/2003	Palmer et al.	7,108,009	B2	9/2006	Ishida
6,582,364	B2	6/2003	Butler et al.	7,112,185	B2	9/2006	Hart et al.
6,589,167	B1	7/2003	Shimomura et al.	7,118,528	B1	10/2006	Piskun
6,589,211	B1	7/2003	MacLeod	7,134,929	B2	11/2006	Chen
6,607,504	B2	8/2003	Haarala et al.	7,153,261	B2	12/2006	Wenchell
6,613,952	B2	9/2003	Rambo	7,163,510	B2	1/2007	Kahle et al.
6,623,426	B2	9/2003	Bonadio et al.	7,192,436	B2	3/2007	Sing et al.
6,627,275	B1	9/2003	Chen	7,193,002	B2	3/2007	Chen
6,663,598	B1	12/2003	Carrillo et al.	7,195,590	B2	3/2007	Butler et al.
6,669,674	B1	12/2003	Macoviak et al.	7,214,185	B1	5/2007	Rosney et al.
6,676,639	B1	1/2004	Ternström	7,217,277	B2	5/2007	Parihar et al.
6,702,787	B2	3/2004	Pasqualucci et al.	7,222,380	B2	5/2007	Chen
6,705,989	B2	3/2004	Cuschieri et al.	7,223,257	B2	5/2007	Shubayev et al.
6,706,050	B1	3/2004	Giannadakis	7,223,278	B2	5/2007	Davison et al.
6,714,298	B2	3/2004	Ryer	7,226,484	B2	6/2007	Chen
6,716,201	B2	4/2004	Blanco	7,235,062	B2	6/2007	Brustad
6,723,044	B2	4/2004	Pulford et al.	7,235,084	B2	6/2007	Skakoon et al.
6,723,088	B2	4/2004	Gaskill, III et al.	7,238,154	B2	7/2007	Ewers et al.
6,725,080	B2	4/2004	Melkent et al.	7,244,244	B2	7/2007	Racenet et al.
6,793,621	B2	9/2004	Butler et al.	7,276,075	B1	10/2007	Callas et al.
6,794,440	B2	9/2004	Chen	7,290,367	B2	11/2007	Chen
6,796,940	B2	9/2004	Bonadio et al.	7,294,103	B2	11/2007	Bertolero et al.
6,797,765	B2	9/2004	Pearce	7,297,106	B2	11/2007	Yamada et al.
6,800,084	B2	10/2004	Davison et al.	7,300,399	B2	11/2007	Bonadio et al.
6,811,546	B1	11/2004	Callas et al.	7,316,699	B2	1/2008	McFarlane
6,814,078	B2	11/2004	Crook	7,331,940	B2	2/2008	Sommerich
6,814,700	B1	11/2004	Mueller et al.	7,338,473	B2	3/2008	Campbell et al.
6,817,974	B2	11/2004	Cooper et al.	7,344,547	B2	3/2008	Piskun
6,830,578	B2	12/2004	O'Heeron et al.	7,344,568	B2	3/2008	Chen
6,837,893	B2	1/2005	Miller	7,377,898	B2	5/2008	Ewers et al.
6,840,946	B2	1/2005	Fogarty et al.	7,390,317	B2	6/2008	Taylor et al.
6,840,951	B2	1/2005	de la Torre et al.	7,393,322	B2	7/2008	Wenchell
6,846,287	B2	1/2005	Bonadio et al.	7,412,977	B2	8/2008	Fields et al.
				7,445,597	B2	11/2008	Butler et al.
				7,473,221	B2	1/2009	Ewers et al.
				7,481,765	B2	1/2009	Ewers et al.
				7,537,564	B2	5/2009	Bonadio et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

7,540,839	B2	6/2009	Butler et al.	2004/0243144	A1	12/2004	Bonadio et al.
7,559,893	B2	7/2009	Bonadio et al.	2004/0249248	A1	12/2004	Bonadio et al.
7,578,832	B2	8/2009	Johnson	2004/0254426	A1 *	12/2004	Wenchell ..... 600/207
7,645,232	B2	1/2010	Shluzas	2004/0260244	A1	12/2004	Piechowicz et al.
7,650,887	B2	1/2010	Nguyen et al.	2004/0267096	A1	12/2004	Caldwell et al.
7,661,164	B2	2/2010	Chen	2005/0020884	A1	1/2005	Hart et al.
7,704,207	B2	4/2010	Albrecht et al.	2005/0033246	A1	2/2005	Ahlberg et al.
7,717,847	B2	5/2010	Smith	2005/0059865	A1	3/2005	Kahle et al.
7,727,146	B2	6/2010	Albrecht et al.	2005/0065475	A1	3/2005	Hart et al.
7,727,255	B2	6/2010	Taylor et al.	2005/0065543	A1	3/2005	Kahle et al.
7,736,306	B2	6/2010	Brustad et al.	2005/0080319	A1	4/2005	Dinkler, II et al.
7,749,415	B2	7/2010	Brustad et al.	2005/0090713	A1	4/2005	Gozales et al.
7,753,901	B2	7/2010	Piskun et al.	2005/0090716	A1	4/2005	Bonadio et al.
7,758,500	B2	7/2010	Boyd et al.	2005/0090717	A1	4/2005	Bonadio et al.
7,766,824	B2	8/2010	Jensen et al.	2005/0096695	A1	5/2005	Olich
7,811,251	B2	10/2010	Wenchell et al.	2005/0131349	A1	6/2005	Albrecht et al.
7,815,567	B2	10/2010	Albrecht et al.	2005/0148823	A1	7/2005	Vaugh et al.
7,837,612	B2	11/2010	Gill et al.	2005/0155611	A1	7/2005	Vaugh et al.
7,841,765	B2	11/2010	Keller	2005/0159647	A1	7/2005	Hart et al.
7,850,667	B2	12/2010	Gresham	2005/0192483	A1	9/2005	Bonadio et al.
7,867,164	B2	1/2011	Butler et al.	2005/0192598	A1	9/2005	Johnson et al.
7,878,974	B2	2/2011	Brustad et al.	2005/0197537	A1	9/2005	Bonadio et al.
7,883,461	B2	2/2011	Albrecht et al.	2005/0203346	A1	9/2005	Bonadio et al.
7,892,172	B2	2/2011	Albrecht et al.	2005/0209510	A1	9/2005	Bonadio et al.
7,896,889	B2	3/2011	Mazzocchi et al.	2005/0222582	A1	10/2005	Wenchell
7,909,760	B2	3/2011	Albrecht et al.	2005/0240082	A1	10/2005	Bonadio et al.
7,913,697	B2	3/2011	Nguyen et al.	2005/0241647	A1	11/2005	Nguyen
7,930,782	B2	4/2011	Chen	2005/0251124	A1	11/2005	Zvuloni et al.
2001/0037053	A1	11/2001	Bonadio et al.	2005/0261720	A1	11/2005	Caldwell et al.
2001/0047188	A1	11/2001	Bonadio et al.	2005/0267419	A1	12/2005	Smith
2002/0002324	A1	1/2002	McManus	2005/0277946	A1	12/2005	Greenhalgh
2002/0010388	A1	1/2002	Taylor et al.	2005/0283050	A1	12/2005	Gundlapalli et al.
2002/0010389	A1	1/2002	Butler et al.	2005/0288558	A1	12/2005	Ewers et al.
2002/0013542	A1	1/2002	Bonadio et al.	2005/0288634	A1	12/2005	O'Heeron et al.
2002/0016607	A1	2/2002	Bonadio et al.	2006/0020164	A1	1/2006	Butler et al.
2002/0026230	A1	2/2002	Moll et al.	2006/0020241	A1	1/2006	Piskun et al.
2002/0038077	A1	3/2002	de la Torre et al.	2006/0030755	A1	2/2006	Ewers et al.
2002/0072762	A1	6/2002	Bonadio et al.	2006/0041270	A1	2/2006	Lenker
2002/0111536	A1	8/2002	Cuschieri et al.	2006/0047284	A1	3/2006	Gresham
2003/0004253	A1	1/2003	Chen	2006/0047293	A1	3/2006	Haberland et al.
2003/0014076	A1	1/2003	Mollenauer et al.	2006/0052669	A1	3/2006	Hart
2003/0028179	A1	2/2003	Piskun	2006/0084842	A1	4/2006	Hart et al.
2003/0040711	A1	2/2003	Racenet et al.	2006/0106402	A1	5/2006	McLucas
2003/0078478	A1	4/2003	Bonadio et al.	2006/0129165	A1	6/2006	Edoga et al.
2003/0139756	A1	7/2003	Brustad	2006/0149137	A1	7/2006	Pingleton et al.
2003/0167040	A1	9/2003	Bacher et al.	2006/0149306	A1	7/2006	Hart et al.
2003/0187376	A1	10/2003	Rambo	2006/0161049	A1	7/2006	Beane et al.
2003/0192553	A1	10/2003	Rambo	2006/0161050	A1	7/2006	Butler et al.
2003/0225392	A1	12/2003	McMichael et al.	2006/0241651	A1	10/2006	Wilk
2003/0236505	A1	12/2003	Bonadio et al.	2006/0247498	A1	11/2006	Bonadio et al.
2003/0236549	A1	12/2003	Bonadio et al.	2006/0247499	A1	11/2006	Butler et al.
2004/0015185	A1	1/2004	Ewers et al.	2006/0247500	A1	11/2006	Voegel et al.
2004/0024363	A1	2/2004	Goldberg	2006/0247516	A1	11/2006	Hess et al.
2004/0049099	A1	3/2004	Ewers et al.	2006/0247586	A1	11/2006	Voegel et al.
2004/0049100	A1	3/2004	Butler	2006/0247673	A1	11/2006	Voegel et al.
2004/0054353	A1	3/2004	Taylor	2006/0247678	A1	11/2006	Weisenburgh, II et al.
2004/0063833	A1	4/2004	Chen	2006/0258899	A1	11/2006	Gill et al.
2004/0068232	A1	4/2004	Hart et al.	2006/0264706	A1	11/2006	Piskun
2004/0070187	A1	4/2004	Chen	2006/0270911	A1	11/2006	Voegel et al.
2004/0072942	A1	4/2004	Chen	2007/0004968	A1	1/2007	Bonadio et al.
2004/0073090	A1	4/2004	Butler	2007/0049966	A1	3/2007	Bonadio et al.
2004/0092795	A1	5/2004	Bonadio et al.	2007/0088202	A1	4/2007	Albrecht
2004/0092796	A1	5/2004	Butler et al.	2007/0093695	A1	4/2007	Bonadio et al.
2004/0093018	A1	5/2004	Johnson	2007/0118175	A1	5/2007	Butler et al.
2004/0097793	A1	5/2004	Butler et al.	2007/0151566	A1	7/2007	Kahle et al.
2004/0106942	A1	6/2004	Taylor	2007/0156023	A1	7/2007	Frasier et al.
2004/0111061	A1	6/2004	Curran	2007/0203398	A1	8/2007	Bonadio et al.
2004/0127772	A1	7/2004	Ewers et al.	2007/0208312	A1	9/2007	Norton et al.
2004/0138529	A1	7/2004	Wiltshire et al.	2007/0255219	A1	11/2007	Vaugh et al.
2004/0143158	A1	7/2004	Hart et al.	2007/0299387	A1	12/2007	Williams et al.
2004/0154624	A1	8/2004	Bonadio et al.	2008/0027476	A1	1/2008	Piskun
2004/0167559	A1	8/2004	Taylor et al.	2008/0048011	A1	2/2008	Weller
2004/0173218	A1	9/2004	Yamada et al.	2008/0097162	A1	4/2008	Bonadio et al.
2004/0215063	A1	10/2004	Bonadio et al.	2008/0097163	A1	4/2008	Butler et al.
2004/0230161	A1	11/2004	Zeiner	2008/0200767	A1	8/2008	Ewers et al.
				2008/0255519	A1	10/2008	Piskun et al.
				2008/0281161	A1	11/2008	Albrecht et al.
				2008/0281162	A1	11/2008	Albrecht et al.
				2009/0012477	A1	1/2009	Norton et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2009/0036745 A1 2/2009 Bonadio et al.  
 2009/0069837 A1 3/2009 Bonadio et al.  
 2009/0093683 A1 4/2009 Richard et al.  
 2009/0093752 A1 4/2009 Richard et al.  
 2009/0131754 A1 5/2009 Ewers et al.  
 2009/0137879 A1 5/2009 Ewers et al.  
 2009/0149714 A1 6/2009 Bonadio  
 2009/0182279 A1 7/2009 Wenchell et al.  
 2009/0187079 A1 7/2009 Albrecht et al.  
 2009/0227843 A1 9/2009 Smith et al.  
 2009/0292176 A1 11/2009 Bonadio et al.  
 2009/0326330 A1 12/2009 Bonadio et al.  
 2010/0063362 A1 3/2010 Bonadio et al.  
 2010/0063364 A1 3/2010 Bonadio et al.  
 2010/0081880 A1 4/2010 Widenhouse et al.  
 2010/0081881 A1 4/2010 Murray et al.  
 2010/0081995 A1 4/2010 Widenhouse et al.  
 2010/0100043 A1 4/2010 Racenet  
 2010/0113882 A1 5/2010 Widenhouse et al.  
 2010/0217087 A1 8/2010 Bonadio et al.  
 2010/0228091 A1 9/2010 Widenhouse et al.  
 2010/0228092 A1 9/2010 Ortiz et al.  
 2010/0228094 A1 9/2010 Ortiz et al.  
 2010/0240960 A1 9/2010 Richard  
 2010/0249523 A1 9/2010 Spiegel et al.  
 2010/0249524 A1 9/2010 Ransden et al.  
 2010/0249525 A1 9/2010 Shelton, IV et al.  
 2010/0249694 A1 9/2010 Choi et al.  
 2010/0261972 A1 10/2010 Widenhouse et al.  
 2010/0261975 A1 10/2010 Huey et al.  
 2010/0286484 A1 11/2010 Stellan et al.  
 2010/0298646 A1 11/2010 Stellan et al.  
 2011/0021877 A1 1/2011 Fortier et al.  
 2011/0028891 A1 2/2011 Okoniewski  
 2011/0034935 A1 2/2011 Kleyman  
 2011/0034946 A1 2/2011 Kleyman  
 2011/0034947 A1 2/2011 Kleyman  
 2011/0071462 A1 3/2011 Ewers et al.  
 2011/0071463 A1 3/2011 Ewers et al.

## FOREIGN PATENT DOCUMENTS

DE 37 39 532 12/1988  
 DE 37 37 121 5/1989  
 DE 296 00 939 6/1996  
 DE 19828009 12/1999  
 EP 0113520 7/1984  
 EP 0142262 5/1985  
 EP 0 517 248 12/1992  
 EP 0537768 4/1993  
 EP 0 807 416 11/1997  
 EP 0 849 517 6/1998  
 EP 0950376 10/1999  
 EP 1118657 7/2001  
 EP 1 125 552 8/2001  
 EP 1312318 5/2003  
 EP 1 407 715 4/2004  
 EP 2044889 4/2009  
 EP 2 340 792 7/2011  
 FR 1456623 9/1966  
 GB 1151993 5/1969  
 GB 1355611 6/1974  
 GB 1372491 10/1974  
 GB 1379772 1/1975  
 GB 1400808 7/1975  
 GB 1407023 9/1975  
 GB 1482857 8/1977  
 GB 1496696 12/1977  
 GB 2071502 9/1981  
 GB 2255019 10/1992  
 GB 2275420 8/1994  
 GB 2298906 9/1996  
 IE 930650 9/1963  
 IE 930649 9/1993

IE 930650 9/1993  
 IE S940150 2/1994  
 IE S940613 8/1994  
 IE S940960 12/1994  
 IE S950055 1/1995  
 IE S950266 4/1995  
 IE S75368 8/1997  
 IE S960196 8/1997  
 IE S970810 11/1997  
 IE 991010 7/2000  
 IE 990218 11/2000  
 IE 990219 11/2000  
 IE 990220 11/2000  
 IE 990660 2/2001  
 IE 990795 3/2001  
 JP 10-108868 4/1998  
 JP 11-290327 10/1999  
 JP 2001-61850 3/2001  
 JP 2002-28163 1/2002  
 JP 02003 235879 A 8/2003  
 JP 2004-195037 7/2004  
 SU 1342485 1/1997  
 WO WO 86/06272 11/1986  
 WO WO 86/06316 11/1986  
 WO WO 92/11880 7/1992  
 WO WO 92/21292 12/1992  
 WO WO 93/05740 4/1993  
 WO WO 93/14801 8/1993  
 WO WO 94/04067 3/1994  
 WO WO 94/22357 10/1994  
 WO WO 95/05207 2/1995  
 WO WO95/07056 3/1995  
 WO WO 95/07056 3/1995  
 WO WO95/22289 8/1995  
 WO WO 95/22289 8/1995  
 WO WO 95/24864 9/1995  
 WO WO 95/27445 10/1995  
 WO WO 95/27468 10/1995  
 WO WO 96/36283 11/1996  
 WO WO 97/11642 4/1997  
 WO WO 97/32514 9/1997  
 WO WO 97/32515 9/1997  
 WO WO 97/42889 11/1997  
 WO WO 98/19853 5/1998  
 WO WO 98/35614 8/1998  
 WO WO 98/48724 11/1998  
 WO WO 99/03416 1/1999  
 WO WO 99/15068 4/1999  
 WO WO 99/16368 4/1999  
 WO WO 99/22804 5/1999  
 WO WO 99/25268 5/1999  
 WO WO 99/29250 6/1999  
 WO WO00/32116 6/2000  
 WO WO 00/32116 6/2000  
 WO WO 00/32119 6/2000  
 WO WO 00/32120 6/2000  
 WO WO 00/35356 6/2000  
 WO WO 00/321176 6/2000  
 WO WO 00/54675 9/2000  
 WO WO00/54675 9/2000  
 WO WO00/54676 9/2000  
 WO WO 00/54676 9/2000  
 WO WO 00/54677 9/2000  
 WO WO00/54677 9/2000  
 WO WO 01/08563 2/2001  
 WO WO01/08581 2/2001  
 WO WO 01/08581 2/2001  
 WO WO 01/26558 4/2001  
 WO WO 01/26559 4/2001  
 WO WO 01/45568 6/2001  
 WO WO 01/49363 7/2001  
 WO WO 01/91652 12/2001  
 WO WO 02/07611 1/2002  
 WO WO 02/17800 3/2002  
 WO WO02/34108 5/2002  
 WO WO 02/34108 5/2002  
 WO WO 03/011153 2/2003  
 WO WO 03/011551 2/2003  
 WO WO 03/026512 4/2003

(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

WO	WO 03/032819	4/2003
WO	WO03/032819	4/2003
WO	WO03/034908	5/2003
WO	WO 03/034908	5/2003
WO	WO03/061480	7/2003
WO	WO 03/061480	7/2003
WO	WO 03/077726	9/2003
WO	WO 03/103548	12/2003
WO	WO 2004/026153	4/2004
WO	WO 2004/030547	4/2004
WO	WO 2004/075730	9/2004
WO	WO 2004/075741	9/2004
WO	WO 2004/075930	9/2004
WO	WO 2005/009257	2/2005
WO	WO 2005/034766	4/2005
WO	WO 2005/089661	9/2005
WO	WO 2006/040748	4/2006
WO	WO 2006/059318	6/2006
WO	WO 2006/100658	9/2006
WO	WO 2007/044849	4/2007
WO	WO 2008/015566	2/2008
WO	WO 2008/093313	8/2008
WO	WO 2008/121294	10/2008
WO	WO 2010/082722	7/2010
WO	WO 2010/104259	9/2010

## OTHER PUBLICATIONS

U.S. Appl. No. 10/802,125, filed Mar. 15, 2004; Title: Surgical Guide Valve, now abandoned.

U.S. Appl. No. 10/927,551, filed Aug. 25, 2004; Title: Surgical Access System, now abandoned.

U.S. Appl. No. 10/695,295, filed Oct. 28, 2003; Title: Surgical Gel Seal.

U.S. Appl. No. 11/132,741, filed May 18, 2005; Title: Gas-Tight Seal Accommodating Surgical Instruments with a Wide Range of Diameters.

U.S. Appl. No. 11/245,709, filed Oct. 7, 2005; Title: Surgical Access System.

U.S. Appl. No. 11/330,661, filed Jan. 12, 2006; Title: Sealed Surgical Access Device.

U.S. Appl. No. 11/564,409, filed Nov. 29, 2006; Title: Surgical Instrument Access Device.

U.S. Appl. No. 12/108,400, filed Apr. 23, 2008; Title: Wound Retraction Apparatus and Method.

U.S. Appl. No. 12/119,371, filed May 12, 2008; Title: Surgical Retractor With Gel Pad.

U.S. Appl. No. 12/119,414, filed May 12, 2008; Title: Surgical Retractor.

U.S. Appl. No. 12/358,080, filed Jan. 22, 2009; Title: Surgical Instrument Access Device.

U.S. Appl. No. 12/360,634, filed Jan. 27, 2009; Title: Surgical Access Apparatus and Method.

U.S. Appl. No. 12/360,710, filed Jan. 27, 2009; Title: Surgical Access Apparatus and Method.

U.S. Appl. No. 12/578,422, filed Oct. 13, 2009; Title: Single Port Access System.

U.S. Appl. No. 12/905,932, filed Oct. 15, 2010; Title: Split Hoop Wound Retractor.

U.S. Appl. No. 12/960,449, filed Dec. 3, 2010; Title: Surgical Access Apparatus and Method.

U.S. Appl. No. 12/960,458, filed Dec. 3, 2010; Title: Surgical Access Apparatus and Method.

U.S. Appl. No. 13/006,727, filed Jan. 14, 2011.

U.S. Appl. No. 13/008,728, filed Jan. 18, 2011.

U.S. Appl. No. 13/023,334, filed Feb. 8, 2011.

U.S. Appl. No. 13/031,892, filed Feb. 22, 2011.

U.S. Appl. No. 13/050,042, filed Mar. 17, 2011.

U.S. Appl. No. 10/446,365, filed May 28, 2003; Title: Screw-Type Seal With Inflatable Membrane.

U.S. Appl. No. 12/004,439, filed Dec. 20, 2007; Title: Skin Seal.

U.S. Appl. No. 12/004,441, filed Dec. 20, 2007; Title: Screw-Type Skin Seal With Inflatable Membrane.

U.S. Appl. No. 12/607,667, filed Oct. 28, 2009; Title: Screw-Type Skin Seal With Inflatable Membrane.

U.S. Appl. No. 10/965,217, filed Oct. 15, 2004; Title: Surgical Sealing Device.

U.S. Appl. No. 10/981,730, filed Nov. 5, 2004; Title: Surgical Sealing Device.

U.S. Appl. No. 11/246,909, filed Oct. 11, 2005; Title: Instrument Access Device.

U.S. Appl. No. 11/291,089, filed Dec. 1, 2005; Title: A Surgical Sealing Device.

U.S. Appl. No. 11/486,383, filed Jul. 14, 2006; Title: Wound Retractor.

U.S. Appl. No. 11/785,752, filed Apr. 19, 2007; Title: Instrument Access Device.

U.S. Appl. No. 12/244,024, filed Oct. 2, 2008; Title: Seal Anchor for Use in Surgical Procedures.

U.S. Appl. No. 12/578,832, filed Oct. 14, 2009; Title: Flexible Access Device for Use in Surgical Procedure.

U.S. Appl. No. 12/706,043, filed Feb. 16, 2010; Title: Flexible Port Seal.

U.S. Appl. No. 12/719,341, filed Mar. 8, 2010; Title: Foam Port and Introducer Assembly.

U.S. Appl. No. 10/895,546, filed Jul. 21, 2004; Title: Laparoscopic Instrument and Cannula Assembly and Related Surgical Method.

U.S. Appl. No. 10/913,565, filed Aug. 5, 2004; Title: Surgical Device With Tack-Free Gel and Method of Manufacture.

Dexterity Protractor Instruction Manual by Dexterity Surgical, Inc.

European Patent Office, European Search Report for European Application No. EP 10 18 4681, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".

European Patent Office, European Search Report for European Application No. EP 10 18 4608, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".

European Patent Office, European Search Report for European Application No. EP 10 18 4648, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".

European Patent Office, European Search Report for European Application No. EP 10 18 4731, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".

European Patent Office, European Search Report for European Application No. EP 10 18 4661, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".

European Patent Office, European Search Report for European Application No. EP 10 18 4677, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".

European Patent Office, European Search Report for European Application No. EP 10 18 9325, dated Dec. 14, 2010, entitled "Split Hoop Wound Retractor".

European Patent Office, European Search Report for European Application No. EP 10 18 9327, dated Dec. 14, 2010, entitled "Split Hoop Wound Retractor".

European Patent Office, European Search Report for European Application No. EP 10 18 9328, dated Dec. 15, 2010, entitled "Split Hoop Wound Retractor".

European Patent Office, European Search Report for European Application No. EP 04 00 2888, dated Sep. 10, 2004, entitled "Hand Access Port Device".

European Patent Office, European Search Report for European Application No. EP 04 00 2889, dated Sep. 13, 2004, entitled "Hand Access Port Device".

European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040154, mailed Jan. 30, 2007.

European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040073, mailed Jan. 26, 2007.

European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039905, mailed Jan. 17, 2007.



(56)

## References Cited

## OTHER PUBLICATIONS

European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039883, mailed Jan. 31, 2007.

European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039800, mailed Apr. 16, 2007.

European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039799, mailed Mar. 27, 2007.

European Search Report for corresponding EP 08253236 date of mailing is Feb. 10, 2009 (6 pages).

Horigame, et al., Silicone Rumen Cannula with a Soft Cylindrical Part and a Hard Flange, *Journal of Dairy Science*, Nov. 1989, vol. 72, No. 11, pp. 3230-3232.

Horigame, et al., Technical Note: Development of Duodenal Cannula for Sheep, *Journal of Animal Science*, Apr. 1992, vol. 70, Issue 4, pp. 1216-1219.

International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US04/05484.

International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US01/29682.

McSweeney, Cannulation of the Rumen in Cattle and Buffaloes, *Australian Veterinary Journal*, Aug. 1989, vol. 66, No. 8, pp. 266-268.

Neil Sheehan, Supplemental Expert Report of Neil Sheehan, Re: U.S. Patent No. 5,741,298, United States District Court for the Central District of California, Civil Action No. SACV 03-1322 JVS, Aug. 9, 2005.

Office Action in co-pending U.S. Appl. No. 12/360,634, dated Jan. 24, 2011 in 12 pages.

Office Action in co-pending U.S. Appl. No. 12/360,710, dated Jan. 24, 2011 in 12 pages.

Technical Note: Development of Duodenal Cannula for Sheep, Faculty of Agriculture and School of Medicine Tohoku University, Sendai 981, Japan.

The International Bureau of WIPO, International Preliminary Report on Patentability, dated Aug. 29, 2006, for International Application No. PCT/US2004/028250.

The International Bureau of WIPO, International Preliminary Report on Patentability, dated Apr. 16, 2008, for International Application No. PCT/US2006/039799.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2006/039800 dated Apr. 16, 2008.

Yamazaki, et al., Diurnal Changes in the Composition of Abomasal Digesta in Fasted and Fed Sheep, *The Tohoku Journal of Agricultural Research*, Mar. 1987, vol. 37, No. 3-4, pp. 49-58.

Kagaya, Laparoscopic cholecystectomy via two ports, using the "Twin-Port" system, *J. Hepatobiliary Pancreat Surg* (2001) 8:76-80. International Search Report and Written Opinion in PCT/IE2005/000113 mailed on Feb. 22, 2006.

International Search Report and Written Opinion in PCT/IE2007/000050 mailed on Aug. 13, 2007.

Declaration of John R. Brustad dated Dec. 10, 2009, submitted in U.S. Appl. No. 11/548,955, including Appendices A-D regarding product sales brochures and production drawings from 2001 and 2005.

The International Searching Authority, The International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US08/63445, mailed Sep. 29, 2008.

The International Searching Authority, The International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US08/063463 mailed Sep. 10, 2008.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2008/063463, dated Nov. 17, 2009, entitled "Surgical Retractor".

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US08/63445, issued Nov. 17, 2009, entitled "Surgical Retractor with Gel Pad".

International Searching Authority-US, International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US04/25511, mailed Nov. 7, 2007.

International Bureau of WIPO, International Report on Patentability for International Application No. PCT/US04/25511, mailed Dec. 6, 2007.

Horigame, et al., Technical Note: Development of a Duodenal Cannula for Sheep, *Journal of Animal Science*, Apr. 1992, vol. 70, Issue 4, pp. 1216-1219.

Horigame, et al., Silicone Rumen Cannula with a Soft Cylindrical Part and a Hard Flange, *Journal of Dairy Science*, Nov. 1989, vol. 72, No. 11, pp. 3230-3232.

McSweeney, Cannulation of the Rumen in Cattle and Buffaloes, *Australian Veterinary Journal*, Aug. 1989, vol. 66, No. 8, pp. 266-268.

Yamazaki et al., Diurnal Changes in the Composition of Abomasal Digesta in Fasted and Fed Sheep, *The Tohoku Journal of Agricultural Research*, Mar. 1987, vol. 37, No. 3-4, pp. 49-58.

European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040154, mailed.

European Patent Office, International Search Report and The Written Opinion of the International Searching Authority for PCT Application No. PCT/US2006/039800 mailed Apr. 16.

Co-Pending U.S. Appl. No. 10/381,220, filed Mar. 20, 2003; Title: Surgical Access Apparatus and Method.

Co-Pending U.S. Appl. No. 10/516,198, filed Nov. 30, 2004; Title: Wound Retractor.

Co-Pending U.S. Appl. No. 10/927,551, filed Aug. 25, 2004; Title: Surgical Access System.

Co-Pending U.S. Appl. No. 11/244,647, filed Oct. 5, 2005; Title: Surgical Access Apparatus and Method.

Co-Pending U.S. Appl. No. 11/245,709, filed Oct. 7, 2005; Title: Surgical Access System.

Co-Pending U.S. Appl. No. 11/330,661, filed Jan. 12, 2006; Title: Sealed Surgical Access Device.

Co-Pending U.S. Appl. No. 11/548,746, filed Oct. 12, 2006; Title: Method of Making a Hand Access Laparoscopic Device.

Co-Pending U.S. Appl. No. 11/548,758, filed Oct. 12, 2006; Title: Split Hoop Wound Retractor With Gel Pad.

Co-Pending U.S. Appl. No. 11/548,765, filed Oct. 12, 2006; Title: Split Hoop Wound Retractor.

Co-Pending U.S. Appl. No. 11/548,767, filed Oct. 12, 2006; Title: Circular Surgical Retractor.

Co-Pending U.S. Appl. No. 11/548,781, filed Oct. 12, 2006; Title: Wound Retractor With Gel Cap.

Co-Pending U.S. Appl. No. 11/755,305, filed May 30, 2007; Title: Wound Retraction Apparatus and Method.

Co-Pending U.S. Appl. No. 11/564,409, filed Nov. 29, 2006; Title: Surgical Instrument Access Device.

Declaration of John R. Brustad Under 37 C.F.R. 1.132, dated Dec. 10, 2009.

"Applied GelPort™ Advanced Access Device" product sales brochure dated 2001.

"Cap Ring" production drawing dated Jan. 19, 2001.

"Gelport® Laparoscopic Hand Access System" product sales brochure dated 2005.

"Cap Ring Medium" production drawing dated Aug. 16, 2005.

European Patent Office, European Search Report for European Patent No. 12151288, dated Feb. 10, 2012.



European Patent Office, Supplementary European Search Report for European Patent Application No. 08755322, dated Apr. 18, 2012.


European Patent Office, Supplementary European Search Report for European Patent Application No. 08755336, dated Jun. 15, 2012.



European Patent Office, European Search Report for European Patent No. 11172709.5, dated Aug. 16, 2011.

European Patent Office, European Search Report for European Patent No. 11172706.1, dated Aug. 16, 2011.

\* cited by examiner



**FIG. 3**



**FIG. 5**

FIG. 6











FIG. 7










**FIG. 13**













FIG. 15

**FIG. 16**










FIG. 23






FIG. 24





## CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 12/815,986, filed Jun. 15, 2010, which is a divisional of U.S. application Ser. No. 11/548,955, filed Oct. 12, 2006, now U.S. Pat. No. 7,736,306, which claims the benefit of U.S. Provisional Application No. 60/726,826, filed Oct. 14, 2005; U.S. Provisional Application No. 60/745,730, filed on Apr. 26, 2006; U.S. Provisional Application No. 60/803,346, filed on May 26, 2006; U.S. Provisional Application No. 60/803,965, filed on Jun. 5, 2006; and U.S. Provisional Application No. 60/828,089, filed Oct. 4, 2006, the entire disclosures of which are incorporated herein by reference.

## BACKGROUND OF THE INVENTION

This invention relates substantially to devices and other apparatuses facilitating sealed access with surgical instruments, such as a surgeon's hand, across a body wall and into a body cavity.

In several areas of surgery there exists a need to have mechanisms or devices that can seal a body cavity or space, and yet permit the introduction of surgical instruments such as guidewires, endoscopes, and even the hand of a surgeon. Typical of these areas of surgery is laparoscopic surgery that relies on surgical instruments inserted through the abdominal wall to reach an operative site within the abdominal cavity. In order to increase space around the operative site within the cavity, insufflation gases are typically introduced to inflate the cavity and elevate the abdominal wall. This pressurizing of the abdominal cavity is referred to as pneumoperitoneum. In this context, the need to seal the body cavity or space arises from the need to maintain the pneumoperitoneum even when instruments are present.

Trocars have been commonly used to provide instrument access in laparoscopic surgeries. These trocars have included elaborate seal structures having zero seals that prevent escape of the gases in the absence of instruments, and instrument seals that prevent escape of the gases in the presence of instruments. Unfortunately, the instrument seals have been able to accommodate only a narrow range of instrument diameters. Multiple seal pairs had to be provided where wider ranges were desired.

Some instruments, such as the hand of the surgeon, have been too large for trocar access. Under these circumstances, hand-assisted laparoscopic seals have been provided. Such devices have been large, cumbersome, and largely ineffective in providing the required sealing mechanism. Other access devices, such as Touhy-Borst seals, have been used, but only for very small diameter access such as that required by a guidewire.

Each of the prior devices suffers from drawbacks that make the device difficult or cumbersome to use. For example, a Touhy-Borst seal requires two hands to use and does not form a seal when a guidewire or other device is about to be introduced. Present trocar seals and hand-assisted seals require two valves, one forming an instrument seal in the presence of the instrument, and the other forming a zero seal in the absence of the instrument. For example, in hand-assisted devices, elaborate mechanisms have been required to seal around the surgeon's arm. When the arm is removed, a separate zero seal has been required to prevent the escape of blood or insufflation gases.

The invention is directed to a surgical access device that is adapted for disposition relative to an incision in a body wall.

5 The access device facilitates insertion of an instrument there-through as well as maintenance of a sealing relationship with the instrument. The surgical access device includes a cap that is substantially annular and has an opening therethrough. The surgical access device also includes a gel pad that is coupled to the cap and adapted for insertion of the instrument there-through. The gel pad covers and seals the entire opening of the cap. The surgical access device further includes a retainer that is substantially annular and adapted for placement against the body wall. Additionally, the surgical access device includes 10 coupling means that are adapted for coupling the cap and the retainer together. The retainer is configured to be coupled to a proximal portion of an elongate sleeve that is adapted to extend through the incision. The retainer is also adapted, together with the elongate sleeve, to retract the incision.

20 In one aspect, the cap includes at least one gap along the annular perimeter of the cap. The at least one gap creates at least one first end and at least one second end of the cap. The at least one gap facilitates a transition in the cap from a first, larger periphery to a second, smaller periphery. In another aspect, the surgical access device also includes means for maintaining the periphery of the cap at the second, smaller periphery. In another aspect, when the cap is at the first, larger periphery, the retainer may be inserted into or removed from the opening of the cap, and the retainer may be fixedly coupled to the cap by first, transitioning the perimeter of the cap to the second, smaller periphery with the retainer positioned within the opening of the cap, and second, maintaining the periphery of the cap at the second, smaller periphery with the maintaining means. In one aspect, the maintaining means 35 includes a squeeze release buckle fitting configured to couple the at least one first end of the cap to the at least one second end of the cap. The squeeze release buckle fitting includes a first, barbed portion that extends from the at least one first end of the cap and a second, receiver portion that extends from the at least one second end of the cap. The barbed portion and the receiver portion of the squeeze release buckle fitting are configured to engage each other in a mating relationship. In another aspect, the barbed portion of the squeeze release buckle fitting includes a plurality of arms, two of which are resilient and have projections extending therefrom. The receiver portion of the squeeze release buckle fitting has corresponding sidewalls for engaging the projections of the barbed portion, thereby causing the two arms that have the projections to flex toward each other as the arms slide into a channel defined by the receiver and to flex away from each other as the projections clear the ends of the sidewalls and into a fully engaged state. In another aspect, the cap includes at least a first gap and a second gap. The first and second gaps create first and second arc portions of the annular cap, each of which includes first and second ends. The first end of the first arc portion corresponds with the second end of the second arc portion and the second end of the first arc portion corresponds with the first end of the second arc portion. The first end of each of the first and second arc portions has a barbed portion of the squeeze release buckle fitting extending therefrom and the second end of each of the first and second arc portions has a corresponding receiver portion of the squeeze release buckle fitting extending therefrom. In another aspect, the maintaining means includes a latch that is pivotally coupled proximate the first end of the cap and a latch receiver that is positioned proximate the second end of the cap. In another aspect, the latch receiver includes a channel that is defined by

substantially parallel channel walls. The channel is configured to releasably receive the latch. In another aspect, the latch includes a shaft that has an enlarged head positioned at the non-hinged end of the latch. The perimeter of the enlarged head is larger than the perimeter of the shaft. The head of the latch is configured to engage the channel and to be held in the channel. The width of the channel is smaller than the head of the latch. The channel walls are resilient such that the walls flex away from each other during receipt of the head of the latch. In another aspect, the coupling means include at least one latch that is pivotally coupled to the retainer. The at least one latch is configured to engage the cap. The at least one latch includes a projection that extends substantially orthogonally from the at least one latch and is configured to engage the cap. The cap includes at least one engagement portion for receiving the projection on the at least one latch. In another aspect, the at least one latch is coupled to the retainer with a live hinge. In another aspect, the at least one latch includes a plurality of latches that are spaced along the periphery of the retainer. In another aspect, in a first position the at least one latch extends substantially laterally from the periphery of the retainer in a substantially planar relationship with the retainer. After placing the cap on the retainer, the at least one latch is rotated toward the cap to a second position in which the latch engages the cap to couple the retainer to the cap. In another aspect, the retainer includes at least one resilient snap for releasably coupling the retainer to the cap. The at least one snap extends from the outer periphery of the retainer in a substantially perpendicular direction from a substantially planar, annular surface of the retainer. Each of the at least one snaps has a projection extending substantially perpendicular and radially inwardly from the snap. The at least one snap is configured to deflect radially outwardly to slide over a corresponding lip portion of the cap when the cap and retainer are brought together in a mating relationship. The at least one snap is configured to return toward a neutral position after the projection on the at least one snap passes the lip portion of the cap such that the projection of the at least one snap engages a receiver portion of the cap. In another aspect, the planar, annular surface of the retainer is configured to secure the sleeve to the retainer. In another aspect, the retainer includes a sidewall portion adjacent to each of the at least one snaps and on either side of each of the at least one snaps. The cap includes openings disposed along the edges of the cap for receiving the sidewall portions of the retainer. In another aspect, the cap includes at least one snap for releasably coupling the cap to the retainer. The at least one snap extends perpendicularly from the periphery of the cap. The at least one snap is configured to engage with a corresponding lip portion of the retainer. Each of the at least one snaps has a projection extending substantially perpendicular and radially inward from the snap. The at least one snap is configured to deflect radially outwardly such that the projection on the at least one snap slides over the corresponding lip portion of the retainer when the cap and retainer are brought together in a mating relationship. The at least one snap is configured to return toward a neutral position after the projection on the at least one snap passes the lip portion of the retainer such that the projection of the at least one snap engages a lip portion of the retainer. In another aspect, the cap includes an inner cylindrical wall and the gel pad being coupled to the inner cylindrical wall. In another aspect, the gel pad is bonded to the inner cylindrical wall. In another aspect, the gel pad is molded to the cap. In another aspect, the surgical access device also includes a resilient fabric integrated on a surface of the gel pad and coupled to the periphery of the cap. In another aspect, the surgical access device also includes a first fabric integrated on

a first surface of the gel pad and coupled to the periphery of the cap, and a second fabric integrated on a second, opposite surface of the gel pad and coupled to the cap. In another aspect, the surgical access device also includes a first fabric coupled to the periphery of the cap and a second fabric coupled to the cap a distance from the first fabric. The space between the first fabric and the second fabric defines a cavity. The gel pad is positioned within the cavity between the first and second fabric. In another aspect, the gel pad includes multi-cusped lobes. Adjacent lobes are configured to seal upon one another. In another aspect, the gel pad includes at least two concentric regions of differing resiliency. The at least two concentric regions include a first, central region having first resiliency and a second, outer region having less resiliency than the first region. In another aspect, the gel pad has more than two concentric regions having differing resiliency with the resiliency of each region decreasing in relation to the increase in distance from the first, central region. In another aspect, the gel pad includes gas-filled pockets arranged substantially around the center of the gel pad. In another aspect, the gel pad includes gas-filled pockets dispersed randomly throughout a region beyond the center of the gel pad.

These and other features of the invention will become more apparent with a discussion of the various embodiments in reference to the associated drawings.

#### DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a top perspective view of a hand access laparoscopic device of the present invention;

FIG. 2 depicts a bottom perspective view of the hand access laparoscopic device of FIG. 1;

FIG. 3 depicts a plan view of a gelcap with a gel pad having regions of varying firmness;

FIG. 4 depicts a side view of a gelcap with gel having gas-filled pockets disbursed therein;

FIG. 5 depicts a plan view of a gelcap with gel having gas-filled pockets disbursed therein;

FIG. 6 depicts a plan view of a gelcap with gel having gas-filled pockets disbursed therein;

FIG. 7 depicts a side view of a hand access laparoscopic device including a gelcap with gel having gas-filled pockets disbursed therein;

FIG. 8 depicts a top perspective view of a multiple-piece cap having squeeze release buckle connectors molded into the ends of the pieces forming the cap;

FIG. 9 depicts a top perspective view of one of the pieces of the cap having a male squeeze release buckle connector fitting at one end and a female squeeze release buckle connector fitting at the other end;

FIG. 10 depicts a top perspective view of a cap having a gap with a latch pivotally coupled on one side of the gap and a groove for accepting the latch on the other side of the gap;

FIG. 11 depicts a top perspective view of a cap having latches for releasable coupling the cap to a retainer;

FIG. 12 depicts a side view of the cap of FIG. 11;

FIG. 13 depicts a top perspective view of a hand access laparoscopic device of the present invention including a cap and a retainer, the retainer having a plurality of snaps for releasably coupling the retainer to the cap;

FIG. 14 depicts a top perspective view of the cap of FIG. 13;

FIG. 15 depicts a top perspective view of the retainer of FIG. 13;

FIG. 16 depicts a section view depicting the interaction between the cap and the retainer of FIG. 13;

FIG. 17 depicts a top perspective view of a hand access laparoscopic device of the present invention including a cap and a retainer, the cap having a plurality of snaps for releasably coupling the cap to the retainer;

FIG. 18 depicts a top perspective view of the cap of FIG. 17;

FIG. 19 depicts a top perspective view of the retainer of FIG. 17;

FIG. 20 depicts a section view depicting the interaction between the cap and the retainer of FIG. 17;

FIG. 21 depicts a side view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, with a plurality of stabilizers in the form of strings or tethers extending from the retention ring to the gelcap;

FIG. 22 depicts a side view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, with a plurality of stabilizers in the form of gussets or webs extending from the retention ring to the gelcap;

FIG. 23 depicts a top perspective view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, with a fabric integrated on the surface of the gel pad;

FIG. 24 depicts a partial side view of the hand access laparoscopic device of FIG. 23;

FIG. 25 depicts a top perspective view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, the gelcap having a cavity defined by fabric with the gel pad housed within the cavity; and

FIG. 26 depicts a bottom perspective view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, with the gel pad having multi-cusped lobes that seal upon one another.

## DESCRIPTION

In FIGS. 1 and 2, a surgical hand access device 50 according to one aspect of the present invention is shown. The device includes a retainer 52 and a cap 54. The cap 54 and the retainer 52 are both substantially annular and both include an opening therethrough. The retainer 52 is adapted to be placed against a body wall. The retainer 52, in one aspect, is rigid and is associated with and/or capable of being coupled to an elongate sleeve 56. The surgical hand access device 50 is adapted for disposition relative to an incision in a body wall. The surgical hand access device 50 also facilitates insertion of an instrument through the access device and maintenance of a sealing relationship with the instrument.

In one aspect, the elongate sleeve 56 extends through an incision to a point where an attached retention ring 58 contacts the interior portions of the body cavity and provides tension between the retainer 52 outside the body cavity and the retention ring. The retainer 52 in one aspect also supports or otherwise enables a portion of the elongate sleeve 56 to remain outside of the body cavity. Additionally, the retainer 52, retention ring 58 and elongate sleeve 56 together allow the incision to be retracted and isolated during a surgical procedure. In one aspect, the elongate sleeve 56 and aspects thereof is a wound retractor type device such as described in U.S. patent application Ser. No. 10/516,198, filed Nov. 30, 2004, the disclosure of which is hereby incorporated by reference as if set forth in full herein.

As shown, the retainer 52 and retention ring 58 are circular, but as one skilled in the art would appreciate, they may be of different shapes and sizes. The retainer 52 in one aspect may be either rigid, flexible or a combination of both. The retention ring 58 may be flexible to facilitate insertion into the body cavity. As will be described in more detail, the access

device 50 includes coupling means that are adapted for coupling the cap 54 and the retainer 52 together.

A gel pad 60 may be coupled to, attached to, formed or integrated with the cap 54 so that a gas-tight conduit is formed between the cap and the sleeve 56. The gel pad 60 covers and seals the entire opening in the cap 54. In one aspect, the gel pad includes a plurality of intersecting dead-end slits 62, 64 that form an access portion or passage through the gel pad 60. Unlike foam rubber or other similar types of elastic materials, the gel pad 60 provides a gas tight seal around a variety of shapes and sizes of hands or instruments inserted there-through.

In one aspect, the gel material from which the gel pad 60 is made is an elastomeric gel. Some such gels have been described in U.S. patent application Ser. No. 10/381,220, filed Mar. 20, 2003, the disclosure of which is hereby incorporated by reference as if set forth in full herein. The gel can be prepared by mixing a triblock copolymer with a solvent for the midblocks. The endblocks are typically thermoplastic materials such as styrene and the midblocks are thermoset elastomers such as isoprene or butadiene, e.g., Styrene-Ethylene-Butylene-Styrene (SEBS). In one aspect, the solvent used is mineral oil. Upon heating this mixture or slurry, the midblocks are dissolved into the mineral oil and a network of the insoluble endblocks forms. The resulting network has enhanced elastomeric properties over the parent copolymer. In one aspect, the triblock copolymer used is KRATON G1651, which has a styrene to rubber ratio of 33/67. Once formed, the gel is substantially permanent and, by the nature of the endblocks, processable as thermoplastic elastomers henceforward. The mixture or slurry has a minimum temperature at which it becomes a gel, i.e., the minimum gelling temperature (MGT). This temperature, in one aspect, corresponds to the glass transition temperature of the thermoplastic endblock plus a few degrees. For example, the MGT for the mixture of KRATON G1651 and mineral oil is about 120° C. When the slurry reaches the MGT and the transformation to a gel state takes place, the gel becomes more transparent, thereby providing means for visually confirming when the transformation of the slurry to the gel state is substantially complete and that the gel may be cooled. In addition to triblocks, there are also diblock versions of the materials that may be used where Styrene is present at only one end of the formula, for example, Styrene-Ethylene/Butylene (SEB).

For a given mass of slurry to form into a complete gel, the entire mass of the slurry is heated to the MGT and remains heated at the MGT for sufficient time for the end blocks to form a matrix of interconnections. The slurry will continue to form into gel at temperatures above the MGT until the slurry/gel reaches temperatures at which the components within the slurry/gel begin to decompose or oxidize. For example, when the slurry/gel is heated at temperatures above 250° C., the mineral oil in the slurry/gel will begin to be volatile and oxidize. Oxidizing may cause the gel to turn brown and become oily.

The speed at which a given volume of slurry forms a gel is dependant on the speed with which the entire mass of slurry reaches the MGT. Also, with the application of temperatures higher than the MGT, this speed is further enhanced as the end block networks distribute and form more rapidly.

The various base formulas may also be alloyed with one another to achieve a variety of intermediate properties. For example, KRATON G1701X is a 70% SEB 30% SEBS mixture with an overall Styrene to rubber ratio of 28/72. It can be appreciated that an almost infinite number of combinations, alloys, and Styrene to rubber ratios can be formulated, each capable of providing advantages to a particular embodiment

of the invention. These advantages will typically include low durometer, high elongation, and good tear strength.

It is contemplated that the gel material may also include silicone, soft urethanes and even harder plastics that might provide the desired sealing qualities with the addition of a foaming agent. The silicone material may be of the types currently used for electronic encapsulation. The harder plastics may include PVC, Isoprene, KRATON neat, and other KRATON/oil mixtures. In the KRATON/oil mixture, oils such as vegetable oils, petroleum oils and silicone oils may be substituted for the mineral oil.

Any of the gel materials contemplated could be modified to achieve different properties such as enhanced lubricity, appearance, and wound protection. Additives may be incorporated directly into the gel or applied as a surface treatment. Other compounds may be added to the gel to modify its physical properties or to assist in subsequent modification of the surface by providing bonding sites or a surface charge. Additionally, oil based colorants may be added to the slurry to create gels of different colors.

In one aspect, the mixture/slurry used with the various embodiments of the caps that are described herein are composed of about 90% by weight of mineral oil and about 10% by weight of KRATON G1651. From a thermodynamic standpoint, this mixture behaves similar to mineral oil. Mineral oil has a considerable heat capacity and, therefore, at about 130° C. it can take 3 or 4 hours to heat a pound of the slurry sufficiently to form a homogeneous gel. Once formed, the gel can be cooled as quickly as practical with no apparent deleterious effects on the gel. This cooling, in one aspect, is accomplished with cold-water immersion. In another aspect, the gel may be air-cooled. Those familiar with the art will recognize that other cooling techniques that are well known in the art may be employed and are contemplated as within the scope of the present invention.

Many of the properties of the KRATON/oil mixture will vary with adjustments in the weight ratio of the components. In general, the greater the percentage of mineral oil the less firm the mixture; the greater the percentage of KRATON, the more firm the mixture. If the resultant gel is too soft it can lead to excessive tenting or doming of the gelcap during surgery when a patient's abdominal cavity is insufflated. Excessive tenting or doming may cause the slits 62, 64 to open, providing a leak path. Additionally, if the gel is too soft it might not provide an adequate seal. However, the gel should be sufficiently soft to be comfortable for the surgeon while simultaneously providing good sealing both in the presence of an instrument and in the absence of an instrument.

If the slurry is permitted to sit for a prolonged period of time, the copolymer, such as KRATON, and the solvent, such as mineral oil, may separate. The slurry may be mixed, such as with high shear blades, to make the slurry more homogeneous. However, mixing the slurry may introduce or add air to the slurry. To remove air from the slurry, the slurry may be degassed. In one aspect, the slurry may be degassed in a vacuum, such as within a vacuum chamber. In one aspect, the applied vacuum may be 0.79 meters (29.9 inches) of mercury, or about 1.0 atmosphere. The slurry may be stirred while the slurry is under vacuum to facilitate removal of the air. During degassing within a vacuum, the slurry typically expands, then bubbles, and then reduces in volume. The vacuum may be discontinued when the bubbling substantially ceases. Degassing the slurry in a vacuum chamber reduces the volume of the slurry by about 10%. Degassing the slurry helps reduce the potential of the finished gel to oxidize.

Degassing the slurry tends to make the resultant gel firmer. A degassed slurry composed of about 91.6% by weight of

mineral oil and about 8.4% by weight of KRATON G1651, an eleven-to-one ratio, results in a gel having about the same firmness as a gel made from a slurry that is not degassed and that is composed of about 90% by weight of mineral oil and about 10% by weight of KRATON G1651, a nine-to-one ratio.

Mineral oil is of a lighter density than KRATON and the two components will separate after mixing, with the lighter mineral oil rising to the top of the container. This separation may occur when attempting to form static slurry into gel over a period of several hours. The separation can cause the resulting gel to have a higher concentration of mineral oil at the top and a lower concentration at the bottom, e.g., a non-homogeneous gel. The speed of separation is a function of the depth or head height of the slurry being heated. The mass of slurry combined with the head height, the temperature at which the gel sets and the speed with which the energy can be transferred to the gel, factor into the determination or result of homogeneous gel versus a non-homogeneous gel.

One aspect of a cap 70 in accordance with the present invention is illustrated in FIG. 3 with a gel pad 72 that differs in texture in specific regions 74-80. For example, in one aspect, the gel pad 72 has a soft occlusive first, central sealing region 74, a second region 76 less resilient than the first region, a third region 78 less resilient than the second region, a fourth region 80 less resilient than the third region, and so-on. More particularly, the gel pad 72 may include more than two concentric regions having differing resiliency with the resiliency of each region decreasing in relation to the increase in distance from the first, central region 74. The progressively less resilient or pliable regions allow positive attachment of the gel pad 72 to a support structure, such as the cap 70, while preserving the desirable occlusive properties of a softer more resilient material at, or about, the central portion of the gel pad.

In one aspect, the gel pad 72 has gradient concentric portions 74-80 in which the gel pad is centrifugally molded or formed. During gel formation, the slurry is mixed in a centrifuge. By rotating the slurry while forming the gel pad 72, density separation is created in which denser triblocks of the slurry migrate towards the circumference of the container holding the spinning slurry and the mineral oil increases in concentration towards the center. In this manner, a firmer gel is formed on the exterior of the finished part and a softer gel is formed in the central portion of the finished part, which is useful in hand access seals for laparoscopic surgery.

In one aspect, a long flat rectangular part is used instead of a thin circular part. There are three conventional axes of rotation associated with the rectangular part. The first axis is through the center of the part normal to the long and short axes of the part. Rotation about the first axis induces a higher density gel at the ends of the part as will rotating the gel about the short midpoint of the rectangle. However, rotation about the long axis of the rectangle creates higher density gel along the long edges of the rectangle. The rotation can be altered during processing, as in the case of rotational molding, in which the part is rotated about multiple axes during processing. The axis of rotation does not have to intersect a centroid of the part or even be within the part itself.

A reverse texture layout of the gel pad 70 can be achieved by selecting lighter density triblocks and higher density mineral oils. Other components can be added as well, based on the desired effect, including additives such as colorants, inert filler material, different oils, different triblock or diblock copolymers, polymers, plasticizers, decorative items, etc.

In one aspect, heavy plastic components 82 are provided with the gel pad 72 or slurry and gravitate toward outer

regions of the gel away from the center, leaving the central region **74** with a particular proportion of plastic material and oil. The outer regions **76-80** of the gel pad **72** are denser and contain more heavy plastic material than the central region **74**. When the particular gradient proportions for the gel pad **72** are achieved, rotation is slowed and the gel pad is allowed to cool.

In one aspect, a non-homogenous gel pad with soft gel on one side and a firmer gel on the other is accomplished with density separation over time commensurate with the timing of the energy input into the gel which can vary with the direction of gravity.

In FIGS. **4-7**, a cap **90** includes a gel pad **92** with a plurality of gas-filled pockets **94**. The pockets **94** may be formed by the presence of lightweight foam or balloons, or by casting or molding the gel around spheres or solid objects of other shapes that are removed after the gel pad **92** has cured. The foam, balloons, spheres or other shapes may be inserted into the mold cavity either prior to or after filling the mold cavity with the slurry. In one aspect, the arrangement of gas-pockets **94** substantially around the center of the gel pad **92** reduces the weight of the gel pad and resistance to the passage of a surgeon's hand or instruments while retaining occlusive properties. An alternative aspect of the gel pad **92** contemplates a more random dispersion of gas pockets **94** throughout the region beyond the center of the gel pad, which reduces the overall weight of the gel pad.

The gel pad or gelcap in various aspects of the present invention may be gamma sterilized. The relative or comparative simplicity of qualifying the sterilization process, for example of gamma versus ethylene oxide, of the gel pad and the device with the gel pad is desirable. However, under gamma sterilization large bubbles can form in the gel pad causing potential cosmetic or aesthetic issues in the sterilized devices. The bubbles are more than 99% room air, so removal of the dissolved air in the slurry is performed prior to forming the slurry into gel. For example, the slurry may be degassed via vacuum, as described above, and turned into gel by heat. Bubbles may still form in the gel during gamma sterilization but disappear in a period of about 24 to 72 hours. In one aspect, the percentage of dissolved gas in the mineral oil at room temperature is about 10%. The removal of the air in the gel has an additional effect of making the gel firmer. This however is counterbalanced by the softening effect on the gel caused by gamma radiation during gamma sterilization.

If the gel pad is to be gamma sterilized, the gel may include about 90% mineral oil by weight and about 10% KRATON by weight. As stated above, degassing the slurry has the effect of making the gel firmer. However, the gamma radiation softens the gel to substantially the same firmness as a gel having about 90% mineral oil by weight and about 10% KRATON by weight that is not degassed and gamma sterilized.

In one aspect, cyanoacrylate, e.g., SUPERGLUE or KRAZY GLUE, may be used to bond or otherwise couple or attach the gel pad **60** to the cap **54**. The glue may attach to either the rubber or styrene component of the tri-block and the bond is frequently stronger than the gel material itself. In another aspect, a solvent may be used to dissolve the plastics in the cap and the polystyrene in the gel. The solution of solvent is applied to the gel pad and cap in either a spray or dip form. In effect, the solution melts both the plastic of the cap as well as the polystyrene in the gel pad to allow a chemical bond to form between the two, which remains when the solvent evaporates.

Polyethylene can be dissolved in mineral oil and then applied to the gel pad. The mineral oil will not evaporate but

will over time absorb into the gel pad and impart a polyethylene layer on the gel pad that may have some beneficial properties.

In one aspect, the gel pad **60** is cast into a DYNAFLEX or KRATON polymer support structure, e.g., the cap **54**. By using KRATON polymer or a similar material in the cap, ring adhesion between the gel pad **60** and the cap **54** can be achieved. The polystyrene in the gel is identified as achieving adhesion with polyphenylene oxide (PPO), polystyrene and other polymers.

In the casting process the gel pad **60** and the cap **54** are heated to a temperature above about 130° C. and held at that temperature for several hours, e.g., about 3 to 4 hours. The temperature used is not sufficient to deform the cap **54**.

The cap **54**, in one aspect, includes a polymer, e.g., polyethylene (PE). In one aspect, the polyethylene is a low density polyethylene (LDPE) or high density polyethylene (HDPE), or ultra high molecular weight polyethylene (UHMWPE). In one aspect, the cap **54** may be made of a polymer, such as polycarbonate and may be fabricated by methods including injection molding.

The gel includes mineral oil. PE has a higher molecular weight than mineral oil. PE is dissolved by mineral oil at high temperatures. As such, as the PE and the mineral oil in the gel pad **60** intermix as both are heated to and held at temperatures above about 130° C., a bond between the PE and gel pad is formed.

In one aspect, the cap **54** includes polycarbonate. The polycarbonate of the cap **54** does not form bonds with the gel pad **60** at 130° C. However, by raising the temperature to about 150° C. for a few minutes during casting, bonding occurs between the gel pad **60** and the cap **54**. As such, heating the gel pad **60** and cap **54** to temperatures at which both the polystyrene of the gel and the polycarbonate are simultaneously beyond their melt points allow bonds to form between the gel pad and the cap. Alternatively, the gel pad **60** and cap **54** may be heated to near or at the glass transition temperature of the polycarbonate cap to form the bond between the gel pad and the cap.

Referring to FIGS. **8-10**, the cap **100**, **130** includes at least one gap **101**, **132** along the annular perimeter of the cap. The at least one gap **101**, **132** creates at least one first end **103**, **134** and at least one second end **105**, **138** of the cap **100**, **130**. The gap **101**, **132** facilitates a transition in the cap from a first, larger periphery to a second, smaller periphery. As will be discussed in more detail below, the cap **100**, **130** includes means for maintaining the cap at the second, smaller periphery. When the cap **100**, **130** is set at the first, larger periphery, the retainer **52** (FIG. **1**) may be inserted into or removed from the opening of the cap. The retainer **52** (FIG. **1**) may be fixedly coupled to the cap **100**, **130** by transitioning the perimeter of the cap to the second, smaller periphery while the retainer is positioned within the opening of the cap, and maintaining the periphery of the cap at the second, smaller periphery with the maintaining means.

Referring to FIGS. **8-9**, the cap **100** incorporates squeeze release buckles **102** molded into or otherwise coupled to the cap. The cap **100** includes a first arc **108** and a second arc **110**, the first and second arcs being separated by first and second gaps **101**. The first arc **108** has a first barbed portion **112** extending from a first end and adapted to be inserted in a snap fit mating relationship with a second, receiver portion **114** extending from a second end of the second arc **110**, thereby coupling the at least one first end **103** of the cap **100** to the at least one second end **105** of the cap. Another barbed portion **112** may extend from the first end of the second arc **110**, which is operationally inserted in a snap fit mating relation-

ship with another receiver portion 114 extending from the second end 105 of the first arc 108. In another aspect, the first arc 108 has a barbed portion 112 on each end of the arc with the second arc 110 having corresponding receiver portions 114 on each end of the second arc.

With the first and second arcs 108, 110 placed adjacent to each other, such that the first end 103 of the first arc corresponds with the second end 105 of the second arc and the second end 105 of the first arc corresponds with the first end 103 of the second arc, and prior to being snapped together, the arcs define a first, larger periphery to allow placement of a retainer 52 (FIG. 1) between the two arcs. The barbed portions 112 engage with corresponding receivers 114 coupling the arcs together. Each barbed portion has a plurality of resilient arms 122, two of which have projections 124 extending therefrom. Each receiver 114 has corresponding sidewalls 126 for engaging projections 124 from the barbed portion, which causes the arms 122 to flex towards each other as the arms slide into a channel 128 defined by the receiver. As the projections 124 clear the ends of the sidewalls 126, the arms 122 are allowed to flex away from each other. Engagement or contact between the edges of the projections 124 with edges of the end of the sidewall 126 prevents the arcs 108, 110 from being detached from each other. By coupling the two arcs 108, 110 together, the delimited circumference is reduced to a second, smaller periphery to capture or hold the retainer 52 (FIG. 1). Flexing the arms 122 toward each other allows the barbed portions 112 to disengage from the sidewalls of the corresponding receiver 114 and to slide out from the receiver, thereby allowing the arcs 108, 110 to separate and detach from the retainer 52 (FIG. 1).

Although not shown, additional barbed portions and receiver snap engagements may be included in each arc to assist in the coupling between the cap 100 and the retainer 52 (FIG. 1) or allow for other size and shape configurations of the cap and/or retainer. In one aspect, the cap 100 includes a single gap 101 and a single barbed portion 112 and receiver portion 114 is provided. In one aspect the cap 100 having the single barbed portion 112 and receiver portion 114 may be provided with a hinge or pivot on another portion of the arc.

Referring now to FIG. 10, a cap 130 has a gap or opening 132 along a portion of the periphery of the cap. A latch 136 is hinged or pivotally coupled to the cap proximate a first end 134 of the opening 132 of the cap 130. Proximate a second, opposite end 138 of the opening 132, a latch receiver, such as an aperture or channel 140 defined by substantially parallel channel walls 142, 144, is configured to releasably receive the latch 136. The latch 136 has a shaft 146 coupled to the cap 130 on one end and an enlarged or bulbous head 148 having a perimeter or diameter larger than the perimeter or diameter of the shaft on the non-hinged end of the latch. The head 148 of the latch 136 is configured to be graspable and the latch swung so that the head may engage and be held in the channel 140 defined by the channel walls 142, 144. The width of the channel 140 is smaller than the diameter of the head 148 of the latch 136 and the channel walls 142, 144 are resilient such that the walls flex away from each other during receipt of the head of the latch. Alternatively, or additionally, portions of the head 148 may compress so that the head may be received and held in the channel 140. In one aspect, one or more projections extend from one or both channel walls 142, 144 and engage notches in the head 148, or vice versa, to secure the latch 136 to the channel 140.

In this manner, with the latch 136 open or not engaged with the channel 140, the initial periphery of the cap 130 allows simple placement of the retainer 52 (FIG. 1) within the periphery of the cap. Actuating the latch 136 closes the cap

130 and reduces the size of the periphery delimited by the cap, thereby securing the cap to the retainer 52 (FIG. 1).

Referring back to FIGS. 8-10, with the cap 100, 130 being separable or otherwise disjointed, placement of the respective retainer 52 (FIG. 1) within the inner periphery of the cap is eased. Subsequent joining or recoupling of the cap together secures the retainer and cap to each other. As such, one skilled in the art would recognize that other types of couplings or engagements may be used to couple or join separate portions of the cap and/or the retainer together to close or delimit a periphery to encase or otherwise secure the cap and the retainer together and vice versa. In one aspect, the retainer, or both the retainer and the cap, are separable, having couplings and/or engagements to recouple the separate portions together to secure the cap and retainer to each other.

In FIGS. 11-12, the retainer 150 has one or more latches 152 to releasably couple the retainer to a cap 54 (FIGS. 1 and 2). In one aspect, a plurality of latches 152 is spaced along the periphery of the retainer 150. The latches 152 are hinged or pivotally coupled to the retainer 150 and are spaced along the periphery of the retainer. In one aspect, each of the latches is coupled to the retainer 150 with a live hinge. In a first position, the latches 152 extend laterally from the periphery of the retainer 150 in a substantially planar relationship with the retainer. Each latch 152 has a projection 156 extending substantially orthogonally from the latch. After placing or fitting the cap 54 on the retainer 150 and/or vice versa, the latches 152 are actuated to couple the cap and retainer together. In particular, the latches 152 are rotated toward the cap to a second position in which the latches engage a portion or edge of the cap 54 to couple the retainer to the cap. In one aspect, the engagement portion of the cap 54 is an opening, aperture, notch, step, projection or other similar type of receiver or engagement to secure the projection of the latch 152 to the cap.

In one aspect, one or more of the latches 152 has notches or openings for receiving corresponding projections or protrusions extending laterally from the cap 54 to couple the retainer 150 to the cap. Additionally or alternatively, although not shown, the cap may have one or more latches hinged along the periphery of the cap for engagement with portions or edges of the retainer to releasably couple the cap and retainer together.

Referring now to FIGS. 13-16, the retainer 160 has one or more resilient snaps 162 for releasably coupling the retainer and a cap 164 together. The snaps 162 extend from the outer periphery or edge of the retainer 160 in a substantially perpendicular direction from a substantially planar, annular surface 166 of the retainer. The planar, annular surface 166 of the retainer 160 secures the sleeve 56 (FIGS. 1 and 2) to the retainer. In one aspect, the surface 166 has projections or hooks to catch and secure the sleeve 56 to the retainer 160 under tension. The edge of the retainer 160 is also slightly raised to assist in the holding of the sleeve 56 and the handling of the retainer.

Multiple snaps 162 may be spaced along the periphery of the retainer 160. In one aspect, portions of the edge of the retainer 160 adjacent to each snap are elevated, thereby forming sidewall portions 167 on either side of each snap. The sidewall portions 167 protect the snaps 162 and strengthen or bolster the coupling between the retainer 160 and the cap 164 once coupled together. Additionally, the sidewall portions 167 facilitate handling and coupling the retainer 160 to the cap 164. Corresponding openings or cutouts 169 are disposed along the edges of the cap 164 to receive the sidewall portions 167 of the retainer 160.

Each snap **162** also has a projection **168** extending substantially perpendicular and radially inwardly from the snap. After placing or fitting a cap **164** on the retainer **160** and/or vice versa, both are squeezed together. The snaps **162** are configured to flex or deflect radially outwardly to slide over a corresponding receiver portion **170**, such as a lip portion or an edge, of the cap **164** when the cap and retainer are brought together in a mating relationship. The snaps **162** are also configured to return toward a neutral position after the projection **168** on the snaps pass the receiver portion **170** of the cap **164** such that the projection of the snaps engages the receiver portion **170** of the cap. The receiver portion **170** in one aspect has an opening, aperture, notch, step, projection or other similar type of receiver or engagement means to secure the projection **168** of the snap **162** to the cap **164**. Alternatively, one or more of the snaps **162** have notches or openings (not shown) for receiving corresponding projections or protrusions (not shown) extending from the cap to secure the snaps of the retainer **160** to the cap **164**. The cap **164** and retainer **160** may each be made via injection molding. Additionally, the cap **164** and retainer **160** may each be made of a polycarbonate material.

In one aspect, as shown in FIGS. **17-20**, a cap **180** has one or more snaps **182** for releasably coupling the cap to a retainer **184**. The snaps **182** extend perpendicularly from the periphery of the cap **180** for engagement with portions **188**, such as corresponding lip portions, and/or edges of the retainer **184**. Each snap **182** has a projection **186** extending substantially perpendicular and radially inwardly from the snap. After placing or fitting the cap **180** on the retainer **184**, both are squeezed together. The snaps **182** flex or deflect radially outwardly to slide over the lip or edge **188** of the retainer **184** when the cap **180** and retainer are brought together in a mating relationship, thereby securing the cap, retainer and sleeve **56** disposed therebetween. Each snap **182** is configured to return toward a neutral position after the projection **186** on the snap passes the lip portion **188** of the retainer **184** such that the projection of the snap engages the lip portion of the retainer.

Referring now to FIGS. **1-20**, the retainers and caps previously described in one aspect are rigid, thereby providing manufacturing benefits as well as easing the assembly of the device. In one aspect, the caps **54, 70, 90, 100, 130, 164, 180** also incorporate an inner cylindrical wall **172** (see FIG. **14**) to which the gel pad **60** is bonded or otherwise coupled or attached to the cap. In this manner, the gel pad **60** attaches to a "skeleton" inside the sleeve **56** and provides a sealing area between the device and the wound, incision and/or body cavity. The coupling or intersection of the sleeve, cap and retainer together also provides another sealing area between the device and the body.

By securing the gel pad **60** to the inner cylindrical wall **172**, the thickness of the gel pad and corresponding cap **54, 70, 90, 100, 130, 164, 180** is minimized along with the overall footprint of the device. A reduced thickness and overall size of the device provides a lighter device and allows for easier hand exchanges. With the gel pad thickness reduced and the gel pad being able to be substantially flush or recessed in the cap, the "doming" phenomena produced by gas pressure exerted on the body and device during insufflation is also reduced.

In various aspects (FIGS. **11-20**) in accordance with the present invention, the retainer **150, 160** has a raised edge **158, 174** disposed around the outer periphery of the retainer. A raised edge **159, 190**, in one aspect, is also disposed around the inner periphery of the retainer **150, 184**. The inner periphery defines an opening **157, 192** through which the sleeve extends. The outer raised edge **158, 174** assists in maintaining

or securing the releasable coupling between the cap and the retainer. In one aspect, a groove **129** (FIG. **8**) extends along the circumference of the cap for receiving the outer raised edge to further enhance the coupling between the cap and retainer. Similarly, the inner raised edge assists in maintaining or securing the releasable coupling between the retainer and the sleeve. The inner raised edge also facilitates the seal between the inner cylindrical wall and/or gel pad, the sleeve and the retainer. In one aspect, notches or spaced valleys or openings **155** (FIG. **11**) are disposed along the inner raised edge **159**, which facilitates the engagement of the inner cylindrical wall and/or gel pad with the retainer by reducing binding between the components.

Several of the above-described attachments could be modified to integrate the retainer or a retainer like component directly into a sleeve to which the cap is releasably coupled. Similarly, the cap may be integrated directly into the retainer and/or sleeve creating a non-releasable coupling between the components.

In one aspect, casting the gel pad **60** into the cap **54** to form a gelcap **66** includes placing the cap into a mold cavity of a casting mold. The mold cavity may include support for the annular walls of the cap **54**. The mold may be made of aluminum, copper, brass, or other mold material having good heat dissipation properties. However, those familiar with the art will recognize that other mold materials having lower heat dissipation properties will produce acceptable parts and these are contemplated as within the scope of the present invention as well.

The mold cavity having the cap **54** is filled with the slurry such that the slurry is in contact with the cap. To facilitate filling voids in the mold cavity with the slurry, the slurry may be preheated, for example, to about 52° C. (125° F.). Preheating the slurry to a temperature below the MGT reduces the viscosity of the slurry and allows the slurry to flow more easily. As stated above, the slurry may have been degassed in a vacuum. The slurry may be degassed again within the mold after the mold cavity is filled to remove air that may have been introduced during the filling of the mold cavity and to facilitate flow of the slurry into voids in the mold. Heat is applied to the mold having the cap **54** and the slurry, such as in an oven, until the slurry attains a temperature of about 150° C. As stated above, the slurry turns into gel at about 120° C., however, at about 150° C., the gel can bond to a polycarbonate cap **54**. Depending on the material used to fabricate the cap **54**, bonding may take place at temperatures other than about 150° C. If the cap **54** is fabricated of a material having a lower melting point than 120° C., then the gel pad **60**, such as a gel slug **60**, may be molded separately and then bonded to the cap. The slits **62, 64** may be molded into the gel pad **60** through the use of an insert in the form of the slit in the mold.

Once the temperature of the gel pad **60** reaches about 150° C., the gelcap **66** may be cooled, such as by air-cooling, cold-water immersion, or other cooling means that are well known in the art. At 150° C. the gel pad is soft and if it were distorted during cooling it would set with the distortion included. To reduce the likelihood of distorting the gel pad **60**, the gelcap **66** may be cooled within the mold. Cooling times may vary based on parameters including size and configuration of the mold, quantity of gel, temperature and quantity of cooling medium, cooling medium properties and the mold material. As an example, the cooling time may be about two (2) hours if cooling in air and about fifteen (15) minutes if cooling in water. Whether cooling with air or water, the final properties of the gel are substantially the same. The gelcap **66** is typically cooled to about ambient room temperature, but may be cooled to lower temperatures. If the gelcap **66** is



15

cooled to the freezing point of the gel, about 0° C., then the gel will freeze and become hard. This may be beneficial for other means of coupling the gel pad 60 to the cap 54, such as with a secondary operation. The gelcap 66 may be removed from the mold at any time after the gel has set.

When removed from the mold, the gel pad 60 typically has a tacky surface. The gelcap 66 may be coated with a powder, such as cornstarch, to substantially reduce or eliminate the tackiness of the cured gel pad 60.

As stated above, in another aspect, the gel pad 60 may be molded separately from the cap 54 and coupled to the cap 54 by a secondary operation, such as by bonding. In one aspect, the gel pad 60 may be molded into a gel slug 60 having an outer perimeter smaller than the inner cylindrical wall of the cap 54 and to a height higher than the height of the cap. Since the gel pad 60 is being molded separate from the cap 54, the slurry only needs to be heated until it reaches about 120° C. and completes the transformation from slurry into gel and the gel becomes substantially transparent. The gel slug 60 may then be placed within the inner cylindrical wall of the cap 54. The gel slug 60 may be cooled and/or frozen prior to placing it within the inner cylindrical wall of the cap 54. The gel slug 60 may be coupled to the cap 54 through compression molding with the gel slug being compressed longitudinally so that the outer perimeter of the gel slug expands and compresses against the inner cylindrical wall of the cap. The gel slug 60 and cap 54 are heated to a sufficient temperature for the polystyrene of the gel and the polymer of the cap to form bonds between the gel and the cap. Molding the gel slug 60 separately from the cap 54 and heat bonding the gel slug to the cap at a later time is especially useful when the cap is made of a material that has a lower melting temperature than the MGT. In such situations, the gel slug 60 can be molded first and heat bonded to the cap 54 without melting the cap.

In reference to FIGS. 21-22, a cap 54 has the gel pad 60 attached, formed or integrated with the cap and is capable of being coupled to the retainer 52 which is capable of being coupled to the sleeve 56. In one aspect, the elongate sleeve 56 extends through an incision and is attached to a retention ring 58 that contacts the interior portions of the body cavity and provides tension between the retainer 52 outside the body cavity and the deformable retention ring. A plurality of stabilizers 200-206 extends from the retention ring 58 to the gel pad 60.

In one aspect, the stabilizers 200-206 are sized and configured to prevent excessive bulging of the gel pad 60 in response to the elevated body-cavity pressure. The stabilizers 200, 202, in one aspect, include a plurality of strings or tethers that extend from the retention ring 58 and subsequently through or into the gel pad 60. The stabilizers 204, 206 include a plurality of contiguous gel based gussets or webs that extend between the retention ring 58 and the gel pad 60.

With reference to FIGS. 23-24, a cap 54 has a woven or knitted fabric 210 that is stretchable and/or resilient. The fabric 210 is integrated into or attached onto the surface 211 of the gel pad 60 and coupled to the periphery of the cap 54. The fabric 210 provides support to counteract the "doming" or "bowing" of the gel pad 60 or cap 54 under the influence of the internal inflation gas pressure associated with the inflation of the body cavity. In one aspect, a first fabric 212 can be integrated on a first surface 214 of the gel pad 60 and coupled to the periphery of the cap 54 and a second fabric 216 can be integrated on a second, opposite surface 218 and coupled to the cap. In this manner, counteracting support is provided in both directions to minimize uncontrolled deformation of the gel pad as a hand or instrument is placed through or withdrawn.

16

In FIG. 25, a first fabric 220 is coupled to the periphery of the cap 54 and a second fabric 222 is coupled to the cap a distance from the first fabric. A cavity 224 is defined by the space between the first fabric 220 and the second fabric 222.

The gel pad 60 may be inserted into the cavity 224 or otherwise held within the cavity. The gel pad 60 may be processed alone and formed to a preferred shape and size and firmness prior to coupling to the cap 54. The temperatures commonly required to process SEBS may substantially deform associated plastic structures. Therefore, separate processing and subsequent assembly may be useful for constructing a cap with the gel pad.

Referring to FIG. 26, the gel pad 60 has multi-cusped lobes 230 that seal upon one another. The channel 232 through which a surgeon's hand or instruments may be inserted through is formed between individual lobes of the gel pad 60.

Accordingly, the present invention provides a hand access device and methods thereof. Although this invention has been described in certain specific embodiments, many additional modifications and variations would be apparent to those skilled in the art. It is therefore to be understood that this invention may be practiced otherwise than specifically described, including various changes in the size, shape and materials, without departing from the scope and spirit of the present invention. Thus, embodiments of the present invention should be considered in all respects as illustrative and not restrictive. The scope of the present invention is to be determined by the appended claims and their equivalents rather than the foregoing description.

What is claimed is:

1. A surgical access device adapted for disposition outside a body wall, the access device facilitating insertion of an instrument therethrough and maintenance of a sealing relationship with the instrument, comprising:

a cap ring defining a central opening;

a gel pad coupled to the cap ring and sealing the central opening in the cap ring and forming an instrument seal in the presence of an instrument inserted therethrough and a zero seal in the absence of an instrument inserted therethrough, the gel pad including at least two regions of differing resiliency including a first region having a first resiliency and a second region having less resiliency than the first region;

a first fabric coupled to the cap ring; and

a second fabric coupled to the cap ring a distance from the first fabric, the space between the first fabric and the second fabric defining a cavity, wherein the gel pad is positioned within the cavity between the first and second fabric.

2. The surgical access device of claim 1 wherein the gel pad including gas-filled pockets dispersed throughout the second region.

3. The surgical access device of claim 1 wherein the first region of the gel pad is surrounded by the second region.

4. The surgical access device of claim 1 wherein the gel pad has a third and fourth region with differing resiliency and the resiliency of the third and fourth regions decrease in relation to an increase in distance from the first region.

5. The surgical access device of claim 1 further comprising a fabric integrated with the gel pad.

6. The surgical access device of claim 1 further comprising a resilient fabric integrated on a surface of the gel pad and coupled to the cap ring.

7. The surgical access device of claim 1 wherein the first fabric is integrated onto a first surface of the gel pad.

17

8. The surgical access device of claim 7 further comprising the second fabric is integrated onto a second surface of the gel pad opposite of the first surface of the gel pad.

9. The surgical access device of claim 1 wherein the gel pad including multi-cusped lobes, adjacent lobes being configured to seal upon one another. 5

10. The surgical access device of claim 1 further comprising a retractor comprising a proximal end; a distal end; a retention ring at the distal end of the retractor, wherein the retention ring is deformably insertable through an opening into a body cavity; and an elongate sleeve extending proximally from the retention ring, the cap ring being removably coupled to the proximal end of the retractor. 10

11. A surgical access device adapted for disposition outside a body wall, the access device facilitating insertion of an instrument therethrough and maintenance of a sealing relationship with the instrument, comprising: 15

a cap ring defining a central opening;

a gel pad coupled to the cap ring and sealing the central opening in the cap ring and forming an instrument seal in the presence of an instrument inserted therethrough and a zero seal in the absence of an instrument inserted therethrough, the gel pad including at least two regions of differing resiliency including a first region having a first resiliency and a second region having less resiliency than the first region; 20

wherein the cap ring includes at least one gap along the cap ring, the at least one gap creating at least one first end and at least one second end of the cap ring in which the gel pad couples to the at least one first end of the cap ring to the at least one second end of the cap ring and the cap ring further comprises a buckle fitting arranged to couple the at least one first end of the cap ring to the at least one second end of the cap ring closing the at least one gap. 25

12. The surgical access device of claim 11 wherein the buckle fitting includes a barbed portion extending from the at least one first end of the cap and a receiver portion extending from the at least one second end of the cap, the barbed portion and the receiver portion of the buckle fitting arranged to engage each other in a mating relationship. 30

13. The surgical access device of claim 12 wherein:

the barbed portion of the buckle fitting includes a plurality of arms with at least two of the plurality of arms being resilient and having projections extending therefrom; 35

and the receiver portion of the buckle fitting having corresponding sidewalls defining a channel for engaging the projections of the barbed portion, thereby causing the at least two of the plurality of arms having the projections

18

to flex toward each other as the at least two of the plurality of arms slide into the channel defined by the receiver portion and to flex away from each other as the projections clear the ends of the sidewalls and into a fully engaged state.

14. A surgical access device adapted for disposition outside a body wall, the access device facilitating insertion of an instrument therethrough and maintenance of a sealing relationship with the instrument, comprising: 10

a cap ring defining a central opening;

a gel pad coupled to the cap ring and sealing the central opening in the cap ring and forming an instrument seal in the presence of an instrument inserted therethrough and a zero seal in the absence of an instrument inserted therethrough, the gel pad including at least two regions of differing resiliency including a first region having a first resiliency and a second region having less resiliency than the first region; 15

wherein the cap ring has a first state defining a first annular perimeter and a second state defining a second annular perimeter smaller than the first annular perimeter of the cap ring, the gel pad being relaxed in the first state and compressed by the cap ring in the second state.

15. A surgical access device adapted for disposition outside a body wall, the access device facilitating insertion of an instrument therethrough and maintenance of a sealing relationship with the instrument, comprising: 20

a cap ring defining a central opening;

a gel pad coupled to the cap ring and sealing the central opening in the cap ring and forming an instrument seal in the presence of an instrument inserted therethrough and a zero seal in the absence of an instrument inserted therethrough, the gel pad including at least two regions of differing resiliency including a first region having a first resiliency and a second region having less resiliency than the first region; 25

wherein the cap ring includes at least one gap along the cap ring, the at least one gap creating at least one first end and at least one second end of the cap ring in which the gel pad couples to the at least one first end of the cap ring to the at least one second end of the cap ring and the at least one gap in the first state of the cap ring defining a first distance and the at least one first end and the at least one second end of the cap ring being distal from each other and the at least one gap in the second state of the cap ring defining a second distance being smaller than the first distance and the at least one first end and the at least one second end of the cap ring being proximate to each other. 30

\* \* \* \* \*

专利名称(译)	手进入腹腔镜装置		
公开(公告)号	<a href="#">US8647265</a>	公开(公告)日	2014-02-11
申请号	US13/006727	申请日	2011-01-14
[标]申请(专利权)人(译)	应用医疗资源		
申请(专利权)人(译)	应用医疗资源CORPORATION		
当前申请(专利权)人(译)	应用医疗资源CORPORATION		
[标]发明人	BRUSTAD JOHN R ALBRECHT JEREMY J HILAL NABIL JOHNSON GARY M HART CHARLES C		
发明人	BRUSTAD, JOHN R. ALBRECHT, JEREMY J. HILAL, NABIL JOHNSON, GARY M. HART, CHARLES C.		
IPC分类号	A61B1/32		
CPC分类号	A61B17/3496 A61B2017/00477 A61B2019/0202 A61B17/3439 A61B2017/00526 A61B2019/0203 A61B17/0293 A61B17/02 A61B19/38 A61B17/3498 A61B17/3423 A61B17/3431 A61B17/3462 A61B2017/3419 A61B17/0218 A61B2017/347 A61B90/40 A61B2017/0225 A61B2017/0287 A61B2050 /005 A61B2050/0051		
优先权	60/726826 2005-10-14 US 60/803965 2006-06-05 US 60/745730 2006-04-26 US 60/828089 2006-10-04 US 60/803346 2006-05-26 US		
其他公开文献	US20110112374A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

本发明涉及一种手动进入腹腔镜检查装置，其具有软胶囊，保持器，套管和保持环。gelcap包括与帽结合的凝胶。帽包括内圆柱形壁，凝胶结合到该内圆柱形壁上，从而在装置和体壁中的伤口之间提供密封区域。通过将凝胶固定到内圆柱壁上，凝胶和相应帽的厚度随着装置的整体占地面积而最小化。随着凝胶厚度减小并且能够基本上齐平，通过吹入患者腹部产生的“隆起”现象减少。

