



US008695865B2

(12) **United States Patent**
Smith et al.

(10) **Patent No.:** **US 8,695,865 B2**
 (45) **Date of Patent:** ***Apr. 15, 2014**

(54) **SURGICAL STAPLING AND CUTTING
 DEVICE**

(75) Inventors: **Kevin W. Smith**, Coral Gables, FL (US);
Matthew A. Palmer, Miami, FL (US);
Korey R. Kline, Miami, FL (US); **Derek
 Dee Deville**, Coral Gables, FL (US)

(73) Assignee: **Ethicon Endo-Surgery, Inc.**, Cincinnati,
 OH (US)

(*) Notice: Subject to any disclaimer, the term of this
 patent is extended or adjusted under 35
 U.S.C. 154(b) by 0 days.
 This patent is subject to a terminal dis-
 claimer.

(21) Appl. No.: **13/547,968**

(22) Filed: **Jul. 12, 2012**

(65) **Prior Publication Data**

US 2012/0286020 A1 Nov. 15, 2012

Related U.S. Application Data

(62) Division of application No. 11/491,626, filed on Jul.
 24, 2006, now Pat. No. 8,579,176, and a division of
 application No. 11/540,255, filed on Sep. 29, 2006,
 now Pat. No. 7,404,508, and a division of application
 No. 11/541,105, filed on Sep. 29, 2006, and a division
 of application No. 11/844,406, filed on Aug. 24, 2007,
 now Pat. No. 7,419,080, and a division of application
 No. 12/139,142, filed on Jun. 13, 2008, now Pat. No.
 8,245,898, and a division of application No.
 12/633,292, filed on Dec. 8, 2009, now Pat. No.
 8,034,077, and a division of application No.
 13/228,933, filed on Sep. 9, 2011.

(60) Provisional application No. 60/702,643, filed on Jul.
 26, 2005, provisional application No. 60/760,000,
 filed on Jan. 18, 2006, provisional application No.
 60/811,950, filed on Jun. 8, 2006.

(51) **Int. Cl.**
A61B 17/068 (2006.01)

(52) **U.S. Cl.**
 USPC **227/175.1**; 227/19; 227/175.2; 227/180.1;
 606/139; 606/219

(58) **Field of Classification Search**
 USPC 227/19, 176.1, 175.1, 178.1, 180.1,
 227/175.2; 606/139, 151, 153, 219
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,488,523 A 12/1984 Shichman
 4,566,620 A 1/1986 Green et al.
 (Continued)

FOREIGN PATENT DOCUMENTS

EP 0 216 532 4/1987
 EP 0 674 876 3/1995

(Continued)

OTHER PUBLICATIONS

European Search Report of European App. No. 10 00 7212 dated
 Nov. 30, 2012.

(Continued)


Primary Examiner — Scott A. Smith

(74) *Attorney, Agent, or Firm* — Mayback & Hoffman, P.A.;
 Gregory L. Mayback; Rebecca A. Tie

(57) **ABSTRACT**

A medical device, comprising a pistol-shaped handle, a lap-
 aroscopic shaft extending from the handle having a distal end
 and defining a shaft axis, a surgical end effector connected to
 the distal end of the shaft, a surgical procedure actuator oper-
 able to carry out a surgical procedure on tissue at the end
 effector, and a rotating knob at the handle that is rotatable with
 respect to the shaft about the shaft axis and is operable to
 actuate the surgical procedure actuator and effect the surgical
 procedure.

16 Claims, 66 Drawing Sheets



(56)

References Cited**U.S. PATENT DOCUMENTS**

4,608,981 A * 9/1986 Rothfuss et al. 227/180.1
 4,873,977 A * 10/1989 Avant et al. 227/180.1
 5,020,933 A 6/1991 Salvestro
 5,020,993 A 6/1991 Levandoski
 5,139,513 A 8/1992 Segato
 5,219,111 A 6/1993 Bilotti
 5,271,543 A 12/1993 Grant et al.
 5,271,544 A * 12/1993 Fox et al. 227/180.1
 5,348,259 A 9/1994 Blanco et al.
 5,355,897 A * 10/1994 Pietrafitta et al. 128/898
 5,417,203 A 5/1995 Tovey et al.
 5,439,156 A 8/1995 Grant
 5,465,895 A 11/1995 Knodel et al.
 5,507,426 A * 4/1996 Young et al. 227/180.1
 5,609,285 A * 3/1997 Grant et al. 227/179.1
 5,645,209 A * 7/1997 Green et al. 227/175.2
 5,673,840 A 10/1997 Schulze et al.
 5,732,871 A * 3/1998 Clark et al. 227/175.1
 5,743,456 A 4/1998 Jones et al.
 5,759,151 A 6/1998 Sturges
 5,797,537 A 8/1998 Oberlin et al.
 5,862,972 A 1/1999 Green et al.
 5,901,895 A 5/1999 Heaton et al.
 5,984,864 A 11/1999 Fox et al.
 6,193,129 B1 * 2/2001 Bittner et al. 227/180.1
 6,250,532 B1 6/2001 Green et al.
 6,330,965 B1 12/2001 Milliman et al.
 6,644,532 B2 11/2003 Green et al.
 6,767,153 B1 7/2004 Holbrook
 6,830,174 B2 12/2004 Hillstead
 6,945,444 B2 * 9/2005 Gresham et al. 227/175.1
 6,964,363 B2 11/2005 Wales et al.
 6,981,628 B2 1/2006 Wales
 7,055,731 B2 6/2006 Shelton et al.

7,059,508 B2 6/2006 Shelton, IV et al.
 7,097,650 B2 8/2006 Weller et al.
 7,111,769 B2 9/2006 Wales et al.
 7,210,609 B2 * 5/2007 Leiboff et 227/180.1
 7,213,736 B2 5/2007 Wales et al.
 7,328,828 B2 2/2008 Ortiz et al.
 7,404,508 B2 * 7/2008 Smith et al. 227/175.1
 7,419,080 B2 * 9/2008 Smith et al. 227/175.1
 8,034,077 B2 * 10/2011 Smith et al. 606/219
 8,245,898 B2 * 8/2012 Smith et al. 227/175.2
 8,579,176 B2 * 11/2013 Smith et al. 227/175.1
 2004/0059338 A1 3/2004 Ebner
 2006/0212069 A1 9/2006 Shelton, IV
 2007/0027469 A1 2/2007 Smith et al.
 2007/0073341 A1 3/2007 Smith et al.
 2007/0221701 A1 9/2007 Ortiz


FOREIGN PATENT DOCUMENTS

EP 1 359 851 9/2010
 JP 10-507384 7/1998
 JP 11-192225 7/1999
 JP 2001-190563 7/2001
 JP 2003-175056 6/2003
 WO 02/39909 5/2002
 WO 03/005698 1/2003
 WO 2004019710 3/2004
 WO 2004112618 12/2004
 WO 2007142625 A2 12/2007

OTHER PUBLICATIONS

European Search Report of European App. No. 12 00 3870 dated Dec. 4, 2012.
 European Search Report of European App. No. 12 00 3924 dated Dec. 4, 2012.

* cited by examiner



٧٠




FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12






FIG. 13









FIG. 16






FIG. 18







FIG. 19








FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29





FIG. 30








FIG. 32








FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39





FIG. 40






FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50






FIG. 51





53
G.
F.




FIG. 54




FIG. 55





FIG. 56






FIG. 58




FIG. 59




FIG. 60





FIG. 61







FIG. 63







FIG. 65






FIG. 67




FIG. 68




FIG. 69




FIG. 70

SURGICAL STAPLING AND CUTTING DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is:

a divisional of U.S. patent application Ser. No. 11/491,626, filed on Jul. 24, 2006, now U.S. Pat. No. 8,579,176 (which application claims the priority, under 35 U.S.C. §119, of U.S. Provisional Patent Application No. 60/702,643, filed on Jul. 26, 2005, U.S. Provisional Patent Application No. 60/760,000, filed on Jan. 18, 2006, and U.S. Provisional Patent Application No. 60/811,950, filed on Jun. 8, 2006);
a divisional of U.S. patent application Ser. No. 11/540,255, filed on Sep. 29, 2006, now U.S. Pat. No. 7,404,508;
a divisional of U.S. patent application Ser. No. 11/541,105, filed on Sep. 29, 2006;
a divisional of U.S. patent application Ser. No. 11/844,406, filed on Aug. 24, 2007, now U.S. Pat. No. 7,419,080;
a divisional of U.S. patent application Ser. No. 12/139,142, filed on Jun. 13, 2008 now U.S. Pat. No. 8,245,898;
a divisional of U.S. patent application Ser. No. 12/633,292, filed on Dec. 8, 2009 now U.S. Pat. No. 8,034,077; and
a divisional of U.S. patent application Ser. No. 13/228,933, filed on Sep. 9, 2011, the entire disclosures of which are hereby incorporated herein by reference in their entireties.

FIELD OF INVENTION

The present invention lies in the field of medical devices, in particular, in the field of surgical stapling instruments and methods for use thereof that are capable of applying lines of staples to tissue while cutting the tissue between those staple lines and, more particularly, to improvements relating to stapler instruments and improvements in processes for forming various components of such stapler instruments that include an articulating shaft. The device and methods can be used, particularly, for stapling and cutting tissue during endoscopic or laparoscopic surgical procedures.

BACKGROUND OF THE INVENTION

Endoscopic surgical instruments are often preferred over traditional open surgical devices because a smaller incision tends to reduce the post-operative recovery time and complications. Consequently, significant development has gone into a range of endoscopic surgical instruments that are suitable for precise placement of a distal end effector at a desired surgical site through a cannula of a trocar. These distal end effectors engage the tissue in a number of ways to achieve a diagnostic or therapeutic effect (e.g., endocutter, grasper, cutter, staplers, clip applier, access device, drug/gene therapy delivery device, and energy device using ultrasound, RF, laser, etc.).

Positioning the end effector is constrained by the trocar. Generally, these endoscopic surgical instruments include a long shaft between the end effector and a handle portion manipulated by the clinician. This long shaft enables insertion to a desired depth and rotation about the longitudinal axis of the shaft, thereby positioning the end effector to a degree. With judicious placement of the trocar and use of graspers, for instance, through another trocar, often this amount of positioning is sufficient. Surgical stapling and severing instruments, such as described in U.S. Pat. No. 5,465,895 to Knodel

et al., are an example of an endoscopic surgical instrument that successfully positions an end effector by insertion and rotation.

One stapler manufactured by United States Surgical Corporation and described in U.S. Pat. Nos. 6,644,532 and 6,250,532 to Green et al. have an end effector that pivotally moves along a single plane in steps dependent upon activation of a lever that correspondingly moves along a single plane in similar steps. See FIGS. 31 and 32 therein. The U.S. Surgical Corp. stapler, however, is limited by the predetermined angles that it can achieve and by the limited side to side pivoting (−45 degrees to +45 degrees) that requires two hands for operation.

Depending upon the nature of the operation, it may be desirable to further adjust the positioning of the end effector of an endoscopic surgical instrument rather than being limited to insertion and rotation. In particular, it is often desirable to orient the end effector at an axis transverse to the longitudinal axis of the shaft of the instrument. The transverse movement of the end effector relative to the instrument shaft is conventionally referred to as “articulation.” This articulated positioning permits the clinician to more easily engage tissue in some instances. In addition, articulated positioning advantageously allows an endoscope to be positioned behind the end effector without being blocked by the instrument shaft.

While the aforementioned non-articulating stapling and severing instruments have great utility and may be successfully employed in many surgical procedures, it is desirable to enhance their operation with the ability to articulate the end effector, thereby giving greater clinical flexibility in their use. Articulating surgical instruments generally use one or more firing bars that move longitudinally within the instrument shaft and through the articulation joint to fire the staples from the cartridge and to cut the tissue between the innermost staple lines. One common problem with these surgical instruments is control of the firing bar through the articulation joint. At the articulation joint, the end effector is longitudinally spaced away from the shaft so that the edges of the shaft and end effector do not collide during articulation. This gap must be filled with support material or structure to prevent the firing bar from buckling out of the joint when the single or multiple firing bars is subjected to longitudinal firing loads. What is needed is a support structure that guides and supports the single or multiple firing bars through the articulation joint and bends or curves as the end effector is articulated.

U.S. Pat. No. 5,673,840 to Schulze et al. describes a flexible articulation joint that is formed from an elastomeric or plastic material that bends at the flexible joint or “flex neck.” The firing bars are supported and guided through a hollow tube within the flex neck. The flex neck is a portion of the jaw closure mechanism and moves longitudinally relative to the end effector, shaft, and firing bars when the jaws are closed on tissue. The firing bars then move longitudinally within the flex neck as the staples are fired and tissue is cut.

U.S. Pat. No. 5,797,537 to Oberlin et al. (owned by Richard-Allan Medical Industries, Inc.) describes an articulation joint that pivots around a pin, rather than bends around a flex joint. In this instrument, firing bars are supported between a pair of spaced support plates connected at one end to the shaft and at another end to the end effector. At least one of those connections is a slidable connection. The support plates extend through the articulation joint adjacent to the flexible drive member in the plane of articulation such that the support plates bend through the gap in the plane of articulation and the flexible firing bar bends against the support when the tip is articulated in one direction from its aligned position. U.S. Pat. No. 6,330,965 to Milliman et al. from U.S. Surgical teaches

3

the use of support plates that are fixedly attached to the shaft and slidably attached to the end effector.

Although these known support plates guide a firing bar through an articulation joint, it is believed that performance may be enhanced. For instance, it is often desirable for the firing bar to be rapidly accelerated during firing to ensure sufficient momentum for severing tissue effectively. Rigidly attached support plates may tend to dislodge in response, allowing the firing bar to blow out from the articulation joint. As a further example, it is desirable for the instrument to operate in the same manner whether articulated or not. Increased friction when articulated would be inconvenient and distracting to the clinician if required to exert a varying amount of firing force.

Consequently, a significant need exists for an improved articulation mechanism for a surgical instrument mechanism that provides enhanced support to a firing bar through the articulation joint.

As mentioned above, as used in the art and as used herein, transverse movement of a medical end effector relative to an instrument shaft is conventionally referred to as "articulation." In prior art medical devices having articulation control, the articulation movement is directed actively from the device handle. This active control can be mechanical and/or electrical. For example, some prior art devices have levers at the top of the control handle and, when pivoted left the end effector articulates left and when pivoted right the end effector articulates right. Some operate with opposite movement. To effect this articulation, it is very difficult for the operator to use only one hand. Thus, often, the operator must hold the handle with one hand and pivot the articulation lever with the other hand. As is known, the trend for laparoscopic and other similar medical devices is to make them operable with a single hand because surgeons often lose control of the device held in the second hand when it is necessary to remove their second hand from that device in order to operate the articulation lever. Loss of device control is undesirable and extends the surgical procedure if the device falls outside the view of the operating surgeon. One prior art device uses electrical measures to actively control articulation. In U.S. Pat. No. 7,213,736 to Wales et al., electrical power is supplied to an electrically actuated polymer to articulate the end effector actively in the desired direction. These prior art devices can be characterized by referring to them as "active articulation" devices, in which an articulation control device is present on the handle and extends through the articulation joint to force the articulation in either articulation direction. In other words, the forces required to perform articulation are generated internally in the device.

Thus, a significant need also exists for an improved articulation mechanism for a surgical instrument mechanism that is operable with only a single hand. The articulation assembly of the present invention has no mechanical control device in the handle to effect direct control of articulating movement of the end effector. There is no articulation control device present on the handle that extends through the articulation joint to force the end effector to articulate in a direction. Instead, articulation of the end effector is dependent upon pressure between a surface of the environment in which the end effector exists and an exterior surface of the end effector, for example, at a location distal of the articulation joint. A torque to pivot the inventive end effector about the articulation axis arises from forces external to the device. One force is present by the user holding the handle. The other force acts distal of the articulation joint and imparted by the environment in which the end effector is present and against which the end effector is being held. In other words, the forces

4

required to perform articulation are external to the device. This motion can be referred to herein as "passive articulation" and the "articulation joint" of the present invention operates with passive articulation—it requires a torque external to the device to articulate the end effector about the axis of the passive articulation joint.

BRIEF SUMMARY OF THE INVENTION

It is accordingly an object of the invention to provide a surgical stapling and cutting device that overcomes the hereinafore-mentioned disadvantages of the heretofore-known devices of this general type.

With the foregoing and other objects in view, there is provided, in accordance with the invention, a medical device, comprising a pistol-shaped handle, a laparoscopic shaft extending from the handle having a distal end and defining a shaft axis, a surgical end effector connected to the distal end of the shaft, a surgical procedure actuator operable to carry out a surgical procedure on tissue at the end effector, and a rotating knob at the handle that is rotatable with respect to the shaft about the shaft axis and is operable to actuate the surgical procedure actuator and effect the surgical procedure.

In accordance with a further mode of the invention, the rotating knob is operable to actuate the surgical procedure actuator and effect the surgical procedure when moved in a direction towards the handle.

In accordance with an added mode of the invention, the end effector is connected to the distal end of the shaft with a passive articulating connection.

In accordance with an additional mode of the invention, the end effector is connected to the distal end of the shaft with a passive articulating connection, the surgical procedure actuator is a locking device of the passive articulating connection, and actuation of the surgical procedure actuator by movement of the rotating knob towards the handle unlocks the passive articulating connection.

In accordance with yet another mode of the invention, the pistol-shaped handle has a stapler-closing device, and the end effector is a surgical stapling end effector having a pair of opposing stapling surfaces, whereby at least one of the stapling surfaces is operable to move with respect to the other of the stapling surfaces upon actuation of the stapler-closing device to apply a compressive force to tissue therebetween.

In accordance with yet a further mode of the invention, the end effector further comprises a knife assembly disposed to cut tissue at the end effector.

In accordance with yet an added mode of the invention, the end effector comprises one of a circular surgical staple head and a linear surgical staple head.

In accordance with yet an additional mode of the invention, the end effector is rotationally fixedly connected to the shaft with the passive articulating connection, and the rotating knob is operable to correspondingly rotate the shaft and the end effector when rotated about the shaft axis.

In accordance with again another mode of the invention, the end effector is rotationally fixedly connected to the shaft, and the rotating knob is operable to correspondingly rotate the shaft and the end effector when rotated about the shaft axis.

In accordance with again a further mode of the invention, the rotating knob is operable to correspondingly rotate the shaft and the end effector when rotated about the shaft axis and simultaneously actuate the surgical procedure actuator.

In accordance with again an added mode of the invention, the surgical procedure actuator has an unactuated state and an actuated state, the passive articulating connection has a

5

locked articulation state and an unlocked articulation state, and the surgical procedure actuator changes the passive articulating connection from the locked articulation state to the unlocked articulation state when the rotating knob is moved towards the handle and changes the passive articulating connection from the unlocked articulation state to the locked articulation state when the rotating knob is released after movement towards the handle has occurred.

In accordance with again an additional mode of the invention, the end effector articulates after the surgical procedure actuator is actuated by movement of the rotating knob towards the handle, and thereafter, an external force is applied to the end effector.

In accordance with still another mode of the invention, when the surgical procedure actuator is actuated by movement of the rotating knob towards the handle, the end effector freely articulates dependent upon external forces acting upon the end effector.

In accordance with still a further mode of the invention, the end effector is a surgical stapling end effector having a stapling device with staples and a cutting device with a blade, the handle has a stapler closing actuator closing the stapling device when actuated and a firing actuator that, when actuated staples with the stapling device and cuts with the cutting device, and the stapler closing actuator and the staple firing actuator are different from the rotating knob.

In accordance with a concomitant mode of the invention, the shaft has a first longitudinal axis, the end effector has a second longitudinal axis, at least one of the shaft, the end effector, and the passive articulating connection has an alignment device, and the alignment device is operable to bias the end effector to substantially align the first and second longitudinal axes when the surgical procedure actuator is actuated by movement of the rotating knob towards the handle.

In accordance with a further concomitant mode of the invention, the alignment device is a center-biasing device.

With the foregoing and other objects in view, there is also provided, in accordance with the invention, a medical device, comprising a pistol-shaped handle, a laparoscopic shaft extending from the handle having a distal end and defining a shaft axis, a surgical end effector connected to the distal end of the shaft, a surgical procedure actuator operable to carry out a surgical procedure on tissue at the end effector, and a rotating knob at the handle that is rotatable with respect to the shaft about the shaft axis and is operable to actuate the surgical procedure actuator and effect the surgical procedure when moved in a direction towards the handle.

Additional advantages and other features characteristic of the present invention will be set forth in the detailed description which follows and may be apparent from the detailed description or may be learned by practice of exemplary embodiments of the present invention. Still other advantages of the present invention may be realized by any of the instrumentalities, methods, or combinations particularly pointed out in the claims.

Although the invention is illustrated and described herein as embodied in a surgical stapling and cutting device and methods of use thereof, it is, nevertheless, not intended to be limited to the details shown because various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims. Additionally, well-known elements of exemplary embodiments of the invention will not be described in detail or will be omitted so as not to obscure the relevant details of the invention.

Other features that are considered as characteristic for the present invention are set forth in the appended claims. As

6

required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention, which can be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one of ordinary skill in the art to variously employ the present invention in virtually any appropriately detailed structure. Further, the terms and phrases used herein are not intended to be limiting, but rather, to provide an understandable description of the invention. While the specification concludes with claims defining the features of the invention that are regarded as novel, it is believed that the present invention will be better understood from a consideration of the following description in conjunction with the drawing figures, in which like reference numerals are carried forward.

BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of embodiments the present invention will be apparent from the following detailed description of the preferred embodiments thereof, which description should be considered in conjunction with the accompanying drawings in which:

FIG. 1 is an enlarged, fragmentary, perspective view of a first embodiment of a distal stapling and cutting end effector and a portion of a shaft connected thereto according to the invention viewed from a distal end thereof with a staple cartridge approximately pulled out half-way from a staple cartridge jaw of the end effector and with an anvil of the stapler separated from a staple-actuating and tissue-cutting slide;

FIG. 2 is an enlarged, fragmentary, side elevational view of the end effector of FIG. 1 with the distal cowl, the proximal castellation axial movement part, and the cartridge removed for clarity, and with the anvil of the stapler connected to the slide;

FIG. 3 is an enlarged, fragmentary, perspective view of the end effector of FIG. 1 with the staple-actuating and tissue-cutting slide in a distal position but with the anvil of the stapler separated from the slide;

FIG. 4 is an enlarged, fragmentary, perspective view of the end effector of FIG. 1 with the staple cartridge removed from the lower jaw/staple cartridge holder and with the clevis rotated in an approximately 45 degree angle with respect to center;

FIG. 5 is an enlarged, fragmentary, wireframe side elevational view of a distal portion of the end effector of FIG. 1;

FIG. 6 is an enlarged, fragmentary, wireframe perspective view of a castellation axial movement assembly of the end effector of FIG. 1 rotated approximately 90 degrees and with an end effector lateral movement locking pin and a proximal screw removed for clarity;

FIG. 7 is an enlarged, fragmentary, wireframe perspective view of the end effector of FIG. 6 viewed from a bottom thereof with an end effector lateral movement locking pin engaging a tooth of the lateral movement sprocket, and with springs and the proximal screw removed for clarity;

FIG. 8 is an enlarged, fragmentary, wireframe bottom plan view of the end effector of FIG. 7 with an end effector lateral movement locking pin engaging a tooth of the lateral movement sprocket;

FIG. 9 is an enlarged, fragmentary, longitudinal cross-sectional view of the end effector of FIG. 8 viewed from a bottom thereof with the end effector lateral movement lock-

ing pin engaging a tooth of the lateral movement sprocket and with the springs removed for clarity;

FIG. 10 is an enlarged, fragmentary, perspective view of the end effector of FIG. 2 rotated about the longitudinal axis with the clevis, the screw, and the distal castellation sleeve axial movement and spring parts removed for clarity;

FIG. 11 is an enlarged, fragmentary, bottom plan view of a distal portion of the end effector of FIG. 1 with the staple-actuating and tissue-cutting slide in a proximal position;

FIG. 12 is an enlarged, fragmentary, bottom plan view of the distal portion of the end effector of FIG. 11 with the staple-actuating and tissue-cutting slide in an intermediate position;

FIG. 13 is an enlarged, fragmentary, radially cross-sectional view through the stapling actuating and tissue-cutting slide of the end effector of FIG. 2;

FIG. 14 is an enlarged, fragmentary, horizontal longitudinal cross-sectional view through a lower half of the end effector of FIG. 1;

FIG. 15 is an enlarged, fragmentary, horizontal longitudinal cross-sectional view through an upper half of a proximal portion of the end effector of FIG. 1;

FIG. 16 is an enlarged, fragmentary, vertical longitudinal cross-sectional view approximately through a longitudinal axis of a proximal portion of the end effector of FIG. 1;

FIG. 17 is an enlarged, fragmentary, vertical longitudinal cross-sectional view through a right half of the proximal portion of the end effector of FIG. 1;

FIG. 18 is an illustration of a left side of the surgical stapler according to the invention with the jaws of the end effector open in an at-rest position of an actuator handle;

FIG. 19 is an illustration of a left side of the surgical stapler of FIG. 18 with the jaws of the end effector closed in an actuated position of a thumb trigger of the actuator handle;

FIG. 20 is an illustration of a left side from above the surgical stapler of FIG. 18 with the lateral movement trigger depressed, with the distal end effector in a laterally free movement state position-dependent upon contact with the environment, such as a surface, and with the jaws of the end effector open in the at-rest position of the actuator handle and laterally positioned at an approximately 45 degree angle;

FIG. 21 is an illustration of a left side from above the surgical stapler of FIG. 18 with the lateral movement trigger in an at-rest state, with the distal end effector in a laterally captured movement state, and with the jaws of the end effector open in the at-rest position of the actuator handle and laterally positioned at an approximately 30 degree angle;

FIG. 22 is a fragmentary illustration of a left side of the end effector of FIG. 18 with the jaws open in the at-rest position and laterally positioned at an approximately 75 degree angle;

FIG. 23 is a fragmentary illustration of a left side of the end effector of the stapler of FIG. 18 with the jaws open in the at-rest position and in a rotated first axial position;

FIG. 24 is a fragmentary illustration of a left side of the end effector of FIG. 23 with the jaws open in the at-rest position and in a normal position rotated counter-clockwise with respect to FIG. 23;

FIG. 25 is a perspective view from a distal end of a second embodiment of a surgical stapling device according to the invention with a removable end effector having a self-contained stapling motor, with the stapling jaws in an at-rest open position and at a right lateral position of approximately 45 degrees, with the ball release lever in an at-rest ball-capture position, and with the motor actuator button in an at-rest motor-off position;

FIG. 26 is an enlarged, perspective view of the removable end effector of FIG. 25 with the jaws in an at-rest open position and with the slide removed for clarity;

FIG. 27 is a perspective view from a distal end of a third embodiment of a surgical stapling device according to the invention with a removable end effector having two ball-connection ends and a self-contained stapling motor, with the stapling jaws in an at-rest open position and at a right lateral position of approximately 45 degrees with staple jaws reversed and facing proximally, with the ball release lever in an actuated ball-released position, and with the motor actuator button in an at-rest motor-off position;

FIG. 28 is an enlarged, perspective view of the removable end effector of FIG. 27 viewed from a right side and a distal end thereof with the jaws in an at-rest open position and with the slide removed for clarity;

FIG. 29 is a fragmentary, enlarged side cross-sectional wireframe view of a distal-most end of an actuating handle of the surgical stapling and cutting device of FIGS. 25 and 26 and of a ball-joint of the removable stapling end effector of FIGS. 25 and 26 in a captured and aligned state;

FIG. 30 is a fragmentary, enlarged side cross-sectional view of a distal-most end of opposite side of the actuating of FIG. 29 with the ball-joint in an un-aligned and released state but still captured in between clamps of the actuating handle;

FIG. 31 is a perspective view from a proximal end of the stapling and cutting device according to the invention with an anvil removed;

FIG. 32 is a fragmentary, perspective view from a proximal end of the device of FIG. 31 with the handle removed to show a proximal portion of an articulation release device with a pushrod therein;

FIG. 33 is an illustration an enlarged, exploded view of parts of the proximal end of an inner tube of the device of FIG. 31;

FIG. 34 is a fragmentary, perspective view from a distal end of interior parts connecting the articulation release device to the articulation joint of the end effector with an outer tube removed;

FIG. 35 is a fragmentary, enlarged, vertically longitudinal cross-sectional view of the parts of FIG. 34;

FIG. 36 is a fragmentary, enlarged, perspective view of a knife guide assembly of the device of FIG. 31 from proximal of a knife guide to distal of a knife blade with outer and inner tubes removed;

FIG. 37 is a fragmentary, enlarged, vertically longitudinal cross-sectional view of a portion of the parts of FIG. 35 at a proximal end of a pullband;

FIG. 38 is a fragmentary, enlarged, vertically longitudinal cross-sectional view of a portion of the parts of FIG. 35 at a distal end of the pullband;

FIG. 39 is a fragmentary, enlarged, side elevational view of a stapler assembly, a drum sleeve, the articulation joint, and a clevis of the device of FIG. 31 with an anvil in an open position;

FIG. 40 is a fragmentary, enlarged, side elevational view of the stapler assembly, the drum sleeve, the articulation joint, and the clevis of the device of FIG. 31 moved distally with respect to FIG. 39 and with the anvil in a closed, firing position;

FIG. 41 is a fragmentary, enlarged, perspective view of a knife guide sub-assembly from proximal of the knife guide to the knife blade with the knife guide, the clevis, the left hammock, the drum sleeve, and the cartridge holder removed;

FIG. 42 is a fragmentary, enlarged, vertically transverse cross-sectional view of the knife-pushrod pin joint of the device of FIG. 31;

FIG. 43 is a fragmentary, enlarged, vertically transverse cross-sectional view of the pullband-aluminum tube pin joint of the device of FIG. 31;

FIG. 44 is a fragmentary, enlarged, vertically transverse cross-sectional view of a proximal face of the clevis of the device of FIG. 31;

FIG. 45 is a fragmentary, enlarged, vertically transverse cross-sectional view of plunger pin spring pockets and an articulation release pin of the device of FIG. 31;

FIG. 46 is a fragmentary, enlarged, vertically transverse cross-sectional view of a plunger pin cam surface and an articulation locking sprocket of the device of FIG. 31;

FIG. 47 is a fragmentary, enlarged, vertically transverse cross-sectional view of the end effector articulation joint of the device of FIG. 31;

FIG. 48 is a fragmentary, enlarged, vertically transverse cross-sectional view of a distal pullband pin joint of the device of FIG. 31;

FIG. 49 is a fragmentary, enlarged, vertically transverse cross-sectional view of an anvil/upper jaw pivot slot of the device of FIG. 31;

FIG. 50 is a fragmentary, enlarged, horizontally longitudinal cross-sectional view of the articulation joint portion of the device of FIG. 31 through spring rods;

FIG. 51 is an illustration of a test bed for knife guiding blades and hammocks of the device of FIG. 31;

FIG. 52 is a fragmentary, enlarged, horizontally longitudinal cross-sectional view of the articulation joint portion of the device of FIG. 31 through an articulation lock release slide;

FIG. 53 is an exploded perspective view of distal components of the device of FIG. 31 viewed from the distal end thereof and without the anvil;

FIG. 54 is a perspective view of an articulating distal portion of a fourth embodiment of the end effector according to the invention with the inner and outer tubes removed;

FIG. 55 is a fragmentary, enlarged, and exploded perspective view of an articulating portion of the end effector of FIG. 54 rotated with the top inward towards the viewer with the outer tube removed;

FIG. 56 is a fragmentary, enlarged, bottom plan view of the articulating portion of the end effector of FIG. 54 with the lower clevis and the closure ring removed;

FIG. 57 is a fragmentary, horizontally longitudinal, cross-sectional view of the articulating portion of the end effector of FIG. 54 through a lower end of the dogbone guide;

FIG. 58 is a fragmentary, vertically longitudinal, cross-sectional view of the articulating portion of the end effector of FIG. 54 through the spring rods with the inner tube and the pushrod-blade support removed;

FIG. 59 is a fragmentary, vertically transverse, cross-sectional view of the articulating portion of the end effector of FIG. 54 through a distal end of the dogbone guide;

FIG. 60 is a fragmentary, vertically transverse, cross-sectional view of the articulating portion of the end effector of FIG. 54 through a proximal end of a dogbone guide chamber of the lower clevis with the dogbone guide removed;

FIG. 61 is a fragmentary, horizontally longitudinal, cross-sectional view of the articulating portion of the end effector of FIG. 54 through a low intermediate portion of the dogbone guide;

FIG. 62 is a fragmentary, horizontally longitudinal, cross-sectional view of the articulating portion of the end effector of FIG. 54 through a high intermediate portion of the dogbone guide;

FIG. 63 is a fragmentary, vertically longitudinal, cross-sectional view of the articulating portion of the end effector of

FIG. 54 through a spring rod with the inner tube, the pushrod-blade support, an anvil, and a near half of the staple sled removed;

FIG. 64 is a fragmentary, vertically longitudinal, cross-sectional view of the articulating portion of the end effector of FIG. 54 through the dogbone guide with a spring plate, the anvil, and the near half of the staple sled removed;

FIG. 65 is a fragmentary, vertically longitudinal, cross-sectional view of a distal end of the articulating portion of the end effector of FIG. 54 with the inner tube, the pushrod-blade support, the anvil, the closure ring, and the near half of the staple sled removed;

FIG. 66 is a perspective view of the lower clevis, the lower dogbone clevis, the dogbone guide, and three adjacent knife blades of the end effector of FIG. 54;

FIG. 67 is a fragmentary, wireframe, vertically transverse cross-sectional view of the end effector of FIG. 54;

FIG. 68 is a fragmentary, wireframe, perspective view of an alternative embodiment of a distal connection of the pullbands of the end effector of FIG. 54;

FIG. 69 is a fragmentary, vertically transverse cross-sectional view of the distal connection of FIG. 68; and

FIG. 70 is a fragmentary perspective view from below of a portion of the distal connection of FIG. 68.

DETAILED DESCRIPTION OF THE INVENTION

As required, detailed embodiments of the present invention are disclosed herein; however, it is to be understood that the disclosed embodiments are merely exemplary of the invention, which can be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present invention in virtually any appropriately detailed structure. Further, the terms and phrases used herein are not intended to be limiting; but rather, to provide an understandable description of the invention. While the specification concludes with claims defining the features of the invention that are regarded as novel, it is believed that the invention will be better understood from a consideration of the following description in conjunction with the drawing figures, in which like reference numerals are carried forward. The figures of the drawings are not drawn to scale.

Alternate embodiments may be devised without departing from the spirit or the scope of the invention. Additionally, well-known elements of exemplary embodiments of the invention will not be described in detail or will be omitted so as not to obscure the relevant details of the invention.

Before the present invention is disclosed and described, it is to be understood that the terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting. The terms "a" or "an," as used herein, are defined as one or more than one. The term "plurality," as used herein, is defined as two or more than two. The term "another," as used herein, is defined as at least a second or more. The terms "including" and/or "having," as used herein, are defined as comprising (i.e., open language). The term "coupled," as used herein, is defined as connected, although not necessarily directly, and not necessarily mechanically.

Referring now to the figures of the drawings in detail and first, particularly to FIG. 1 thereof, there is shown a first exemplary embodiment of a stapling and cutting end effector 1 according to the present invention. The major parts of the end effector 1 include a clevis 10, an anvil 20, a cartridge holder 30 for receiving a staple cartridge 100, an adapter

sleeve 40, and a lateral translation or articulation device 50. FIG. 1 illustrates the removability of the staple cartridge 100 from the cartridge holder 30.

Connecting the anvil 20 to the cartridge holder 30 and the staple cartridge 100 is a staple-actuating and tissue-cutting slide 60. This slide 60 operative engages both the anvil 20 and the cartridge holder 30 to keep the two parts 20, 30 in proper alignment so that the actuated staples inside the cartridge 100 hit their respective stapler anvils within the anvil 20 and secure the staples around tissue disposed between the anvil 20 and the cartridge 100. The distal facing surface of the slide 60 contains a blade 62 for cutting the tissue disposed in the jaws 20, 30 as the tissue is being stapled together. Proximal movement of the slide is shown, diagrammatically, in FIGS. 1 to 3. So that the slide 60 can be seen in FIGS. 1 and 3, the anvil 20 is uncoupled from the top end of the slide 60. In operation, however, the slide 60 must be coupled to the anvil 20 as shown in FIG. 2 and, especially, in FIG. 13.

FIG. 2 illustrates the end effector 1 with the adapter sleeve 40 removed to make visible various features of the translation therein.

A first of two primary parts of the lateral translation device 50 are apparent in FIGS. 1 to 3. A proximal part 52 includes a proximal sprocket 522, an intermediate castellated connector 524, and a distal rod 526. In the exemplary embodiment, the intermediate castellated connector 524 has four distally projecting teeth 5242, clearly shown in FIG. 2.

Also visible in FIG. 2 is a pull cable adapter 70. The pull cable adapter 70 is connected to a pull cable 110 (dashed lines) at a proximal side and to the cartridge holder 30 at a distal side thereof. The pull cable adapter 70, therefore, is used to pull or push the cartridge holder 30 with respect to the anvil 20 and, thereby, pivot the anvil 20 from an open position to a closed position, or vice-versa, dependent upon movement of the cartridge holder 30. The proximal end of the anvil 20 has a cam follower 22 on either side thereof. The proximal end of the cartridge holder 30 defines two cam surfaces 32 on either side thereof and aligned to receive a respective one of the cam followers 22. Accordingly, movement of the cartridge holder in a distal or proximal direction results in a corresponding opening or closing pivoting movement of the anvil 20.

FIG. 4 shows the lateral articulating movement of the stapler 20, 30 with respect to the clevis 10.

In FIGS. 5 to 8, all parts, including the adapter sleeve 40 and the clevis 10 are shown in wire frame, thereby, revealing features therein. The clevis 10 contains four lumens, two of which are shown in FIG. 5 and all four are shown in FIGS. 6 and 7. A first 12 of the lumens is formed to contain a non-illustrated shaft for controlling distal and proximal movement of an end effector lateral movement locking pin 120, which pin 120 is first shown in FIGS. 8 and 9. The two lateral lumens 14 are shaped to receive the pull-wire that moves the pull cable adapter 70 proximally (distal movement of the pull cable adapter 70 is caused by a spring). The other of the two lumens 14 is extra and can receive any number of possible additional instrumentation. The drive cable lumen 16 is the last of the four lumens and is shaped to receive the flexible drive cable that turns the drive screw 34 (see FIG. 1), which controls movement of the slide 60.

At the distal end of the drive cable lumen 16, the clevis 20 defines an oblong cavity 18 for receiving therein the lateral movement locking pin 120. FIGS. 6 to 9, in particular, show an exemplary shape of this cavity 18. Because the lateral movement locking pin 120 is oblong in circumferential shape, the pin 120 does not rotate away from an aligned position with the teeth of the sprocket 522.

Also visible under the top side of the clevis 10 in FIG. 5 are two centering springs 130. These springs 130 are also shown in FIGS. 6 to 9 and, in particular, FIG. 10. To prevent undesired interaction between the springs 130, a dividing plate 140 is sandwiched between the springs 130. FIG. 10 illustrates the two springs 130 with the dividing plate 140 therebetween.

The features underneath the transparent sleeve 40 are better explained with respect to FIGS. 7 to 10. The sleeve 40 defines two exterior structures and two internal bores. The first exterior structure is a proximal cylinder 42. The proximal cylinder 42 defines castellations 422 at a proximal end thereof. These castellations 422 match and interact with the intermediate castellated connector 524 of the proximal part 52. The proximal cylinder 42 also defines a first bore 44 that is shaped to receive the distal rod 526 of the proximal part 52. There is a cylindrical, tubular radial clearance between the rod 526 and the interior surface of the first bore 44 and a longitudinal clearance between the proximal end of the cable adapter 70 and the proximal inside surface of the first bore 44. This tubular-shaped clearance can receive a first tubular biasing device (e.g., a coil spring), which is not illustrated for clarity. The first biasing device is positioned to apply a proximally directed force on the proximal-most end of the adapter sleeve 40. In such a configuration, the force applied by the first biasing device presses the distal castellations 422 towards and against the proximal castellations 5242.

The second exterior structure of the sleeve 40 is a distal cylinder 46. The distal cylinder 46 defines a second bore 48 that is shaped to receive therein the pull cable adapter 70. The pull cable adapter 70 also defines an interior bore 72 that is shaped to receive the distal rod 526 of the proximal part 52. For clarity in the figures, the rod 526 is shown extending entirely into the interior bore 72 only by the dashed lines in FIG. 9. In operation, the rod 526 extends entirely into the interior bore 72. The interior bore 72 is coaxial and, in an exemplary embodiment, has the same interior diameter of the first bore 44. Accordingly, there exists a cylindrical, tubular radial clearance between the rod 526 and the interior surface of the interior bore 72 and a longitudinal clearance between the distal surface of the cable adapter 70 and the inside distal surface of the interior bore 72. This is because it is also shaped to house a second tubular biasing device (e.g., a coiled spring), also not illustrated for clarity. The second biasing device is provided to impart a distally directed biasing force against the pull cable adapter 70. Such a force keeps the jaws 20, 30 in an open position. Accordingly, the jaws 20, 30 have an at-rest open position.

Without providing an intermediate part, the two non-illustrated biasing devices connect and, therefore, form a single spring. However, it is desirable to not have the two biasing devices interact because separation of the castellated parts causes an unwanted force to be applied to the cartridge holder 30 and movement of the cartridge holder 30 may loosen the connection of the castellated parts. Accordingly, a non-illustrated washer is disposed between the two biasing devices in the cylindrical cavity 74 defined by the proximal end surface of the pull cable adapter 70 and the distal end surface of the second bore 48. FIG. 7 particularly illustrates the proximal side for holding this washer, which is shaped to only receive the distal rod 526 therethrough. Accordingly, because the washer is trapped between the pull cable adapter 70 and the sleeve 40, the two springs are decoupled and provide their respective biasing forces independent of one another.

The underside view of FIGS. 11 and 12 illustrate the drive shaft 34 of the slide 60 and the proximal idler bushing 36 that holds the drive shaft 34 in place within the cartridge holder 30. At the position of the idler bushing 36, the drive shaft 34

13

does not have threads. However, distal to the idler bushing 36, the drive shaft 34 has threads (which are not illustrated) extending towards the distal end of the drive shaft 34. FIGS. 11 and 12 do not show the thrust bearing 38 on the opposite end of the drive shaft 34, but FIG. 1 clearly illustrates this bearing 38. Also illustrated in FIGS. 11, 12, and 13 is the bottom of the slide 60 in the form of a drive nut 64. In an exemplary embodiment, this drive nut 64 is a part that is separate from the blade 62 of the slide 60 but is fixedly connected at the bottom of the blade 62. The illustrated shape of the drive nut 64 has a dumbbell-shaped cross-section to relieve some of the forces exerted upon the threads. In FIG. 11, the drive nut 64 is in a proximal position where the anvil 20 is in an opened position. FIGS. 12 and 13, in contrast, show the drive nut 64 in intermediate positions where the anvil 20 is in a partially closed position.

FIG. 13 is especially useful in illustrating the shape and configuration of the slide 60, including the blade 62 and the drive nut 64.

The horizontal cross-section along approximately the longitudinal axis of the end effector in FIGS. 14 and 15 is particularly useful in viewing the bores around the distal rod 526. Again, for clarity, the rod 526 is not shown extending all the way to the distal surface of the bore 72 in the pull cable adapter 70 even though it does extend all the way to this surface. Around the proximal end of the rod 526 is the first bore 44 in the adapter sleeve 46. Just distal of the first bore 44 is the cavity 74 for receiving the washer therein and, just distal of the cavity 74, is the interior bore 72 of the pull cable adapter 70 for receiving the second biasing device.

The vertical cross-section along approximately the longitudinal axis of the end effector in FIG. 16 is particularly useful in viewing the connection between the drive nut 64 and the drive shaft 34. Again, for clarity, the rod 526 is not shown extending all the way to the proximal surface of the bore 72 in the pull cable adapter 70.

The vertical cross-section along approximately the longitudinal axis of the end effector in FIG. 17 is particularly useful in viewing the connection between the slide 60 and both the anvil 20 and the cartridge holder 30. Two upper wings 66 are disposed in a groove inside the anvil 20 and two lower wings 68 form an upper holding surface of the I-shape formed by the lower wings 68 and the drive nut 64.

FIGS. 18 to 24 are illustrations of the entire longitudinal extent of the stapling device according to the invention with the distal end effector 1 and a first exemplary embodiment of the actuating handle 2. As shown in FIG. 60, the jaws 20, 30 are at rest in an open position.

The thumb trigger is connected to the proximal end of the pull cable that ends at the pull cable adapter 70. Thus, when the thumb trigger 3 is actuated (see FIG. 19), the cartridge holder 30 is pulled in a proximal direction. Due to the shape of the cam surfaces 32, the cam followers 22 are caused to move and, thereby, pivot the anvil 20 approximately into its stapling position. As set forth above, it is not the thumb trigger 3 that insures correct parallel orientation of the anvil 20 with respect to the cartridge holder 30 and, thereby, the staple cartridge 100. Rather, it is the slide 60 that insures the proper parallel orientation.

FIGS. 20 to 22 illustrate how the end effector 1 is passively articulated in a lateral direction. When the index finger trigger 4 is depressed, the lateral movement locking pin 120 is moved rearward to disengage from the sprocket 522. If no force is applied to the end effector 1, then, due to the two centering springs 130, the end effector 1 remains in the axial aligned orientation shown in FIGS. 18 and 19. However, when an external force is applied to the end effector 1 (as shown in

14

FIG. 20), the laterally free end effector 1 can be moved about the axis of the sprocket 522 into any position, e.g., an approximately 45 degree left position shown in FIG. 20, or into any other orientation. See, e.g., FIG. 22. When the index finger trigger 4 is released, the lateral movement is prevented by returning the distal end of the locking pin 120 in between two teeth of the sprocket 522. Thus, as shown for example in FIGS. 21 and 22, the end effector can be locked into a significant number of laterally articulated positions. It is noted that the staple cartridge 100 is not illustrated in FIGS. 18 to 24 for clarity.

FIGS. 23 and 24 illustrate the axial rotational control of the end effector. Such axial control is provided by the two respective castellated features 422, 5242 of the adapter sleeve 40 and the lateral translation device 50, respectively. In FIG. 23, the castellations are engaged and the anvil is in the 90 degree position with respect to the handle. To disengage the castellations, a force sufficient to overcome the first biasing device is exerted on the end effector 1 and the castellations features 422, 5242 separate. Then, the end effector 1 can be rotated clockwise or counter-clockwise. FIG. 68 shows, for example, the anvil 20 rotated counter-clockwise into an approximately 9 o'clock position.

FIGS. 1 to 3 can be used to illustrate the operation of the motorized stapling function of the stapling device of the present invention. In FIG. 1, the slide 60 is in a proximal position. A reversible motor is housed inside the handle. A three-way switch is connected to the motor. When in a middle position, for example, the motor is off. When in a proximal position, the motor is turned on and will rotate the drive shaft 34 so that the slide 60 moves in a proximal direction. In contrast, when the switch is in a distal position, the motor is turned on and will rotate the drive shaft 34 so that the slide 60 moves in a distal direction. Of course, the switch can be merely a two-way switch without an off position.

FIGS. 25 and 26 illustrate a second exemplary embodiment of the stapling and cutting system 200 according to the invention. This system 200 is different than the first embodiment in that the motorized stapling assembly is entirely contained in the end effector 210. Therefore, the handle 220 only needs to have two actuating devices. The first actuating device 222 is a ball joint releasing lever and the second actuating device is the stapling/cutting motor on/off button 224.

The end effector 210 is connected to the distal end of the actuation shaft 226 of the handle 220 at a ball-joint connector 228. The end effector 210 has, at its distal-most end, a ball joint 212. The ball joint 212 has two opposing cup-shaped clamps 2122, 2124. The interior surfaces of the clamps 2122, 2124 are shaped to correspond to the outer shape of the ball joint 212. The clamps 2122, 2124 translate towards or away from one another based upon an actuation of the lever 222.

The clamps 2122, 2124 are biased towards one another in a closed position such that, when the ball joint 212 is disposed therein, the two clamps 2122, 2124 tightly grip the ball joint 212. Actuation of the lever 222 causes the clamps 2122, 2124 to separate and, thereby, allow the ball joint 212 to rotate freely in between the two clamps 2122, 2124. Thus, when the lever 222 is actuated, the end effector 210 is "free" to move based upon pressure against structures in the environment, such as tissue near a stapling/cutting site. The lever 222 can be pushed down sufficiently far to allow the ball joint 212 to move entirely out of the clamps 2122, 2124. Therefore, if a first end effector 210 is clamped at a first site and a second end effector 210 is desired to clasp and cut a second site, the first end effector 210 can be left clamped at the first site, the shaft

15

226 can be removed from the body and loaded with a second end effector 210, and the second end effector 210 can be guided to the second site.

The second actuating device 224 is needed when the user desires to effect the stapling and cutting with the end effector 210. When the end effector 210 is at the desired position for stapling/cutting, the actuator 224 (e.g., button) is depressed. This actuation, preferably, completes (or interrupts) a circuit that connects power to the motor inside the end effector 210, thereby causing the slide 60 to move distally and effect the stapling and cutting functions of the jaws.

FIG. 25 illustrates the complete freedom for orienting the end effector 210 in any position with respect to the ball joint 212. In FIG. 25, the end effector 210 is shown in a right lateral orientation of approximately 45 degrees and with an anvil orientation of approximately 90 degrees.

FIGS. 27 and 28 illustrate a variation of the second embodiment of the end effector shown in FIGS. 25 and 26. In particular, the handle 220 is the same as in FIGS. 25 and 26. However, the end effector 310 is different. Specifically, the end effector 310 has a proximal ball joint 312 similar to the ball joint 212 in FIGS. 25 and 26, but also has a second, distal ball joint 314, having a shape virtually identical to the proximal ball joint 312. Therefore, when the lever 222 is pressed down to release the ball joint 312, 314, the end effector 310 can be allowed to rest within the body and the opposite end can be grasped between the clamps 2122, 2124. In such an orientation, shown in FIG. 27, the stapling/cutting can be actuated when the jaw opening is facing the user.

It is also noted that placement of an end effector 210, 310 at a surgical site sometimes requires the access to the surgical site to be rather small in comparison to the opened jaws of the end effector 210, 310. With the ability to reverse the end effector 310, some difficult-to-reach sites may be accessed that are not reachable with the single ball joint end effector 210.

FIGS. 29 and 30 show the clamps 2122, 2124 at the distal-most end of the actuating shaft 226 of the surgical stapling and cutting device 200, 300 of FIGS. 25 to 28 holding a ball-joint 212, 312, 314 of the end effector 210, 310 of FIGS. 25 to 28. These figures illustrate that the lever 222 is connected to a push rod 230 having at its distal end a plunger 232. This plunger 232 has a cup-shaped surface 234 at its distal-most end with a shape corresponding to the outer shape of the ball joint 212, 312, 314. Thus, when the plunger 232 is in its distal-most position in contact with the ball joint 212, 312, 314, the ball is captured and does not move or rotate. In contrast, when the plunger 232 is moved proximally as shown in FIG. 30, the ball of the ball joint 212, 312, 314 is free to rotate between the clamps 2122, 2124.

The endostapler illustrated in FIGS. 31 to 70 add various different alternative and/or additional features to the endostapler illustrated in FIGS. 1 to 30.

In all of FIGS. 31 to 70, the top jaw or anvil 1020 is only shown in FIGS. 39 and 40 for the sake of clarity. Further, the anvil 20 is described above in detail with regard to FIGS. 1 to 30 and, therefore, any repetitive description is avoided hereinafter.

The exemplary handle shown in FIG. 31 is manufactured by Ethicon Endo-Surgery, Inc., and can be found, for example, on Ethicon's linear cutter model ECHELON 60 Endopath Stapler. Description of this handle is, therefore, believed to be redundant as parts and functional descriptions of this handle are published in the art. Such description is hereby incorporated herein by reference in its entirety.

As set forth above, the distal end of the endostapler of the present invention is configured to house a standard staple

16

cartridge 100. This cartridge 100, too, is described in prior publications and does not need to be repeated here. The publications are, therefore, hereby incorporated herein by reference in their entireties.

FIG. 31 illustrates portions of an alternative embodiment of the endostapler 1000 of the present invention. It is noted that two distal actuation levers on the handle 1200 of the endostapler 1000 are hidden from view in FIG. 31 for the sake of clarity.

The distal end of the handle 1200 includes a bell-shaped actuator 1100, which provides two degrees of control for the articulating portions of the endostapler 1000. First, the bell actuator 1100 freely rotates about the central axis of the endostapler 1000 on distal end of the handle 1200. Because the bell actuator 1100 is rotationally fixedly connected to the outer tube 1110, when the bell actuator 1100 is rotated clockwise or counterclockwise, the entire distal end of the endostapler 1000 rotates correspondingly. Second, the bell actuator 1100 can be displaced over a given distance in a proximal direction on the distal end of the handle 1200. As will be described below in further detail, proximal displacement of the bell actuator 1100 causes a corresponding movement of the articulation lock release slide 120, 1120 to allow the distal end effector 1002 to articulate at the translation device 50, 1050. A non-illustrated bias device (i.e., a compression spring) located, for example, in the distal portion of the bell actuator 1100 is used to bias the bell actuator 1100 and the articulation lock release slide 1120 in a distal direction so that the articulation lock release slide 120, 1120 remains in the actuated or locked position while the bell actuator 1100 is in an un-actuated state. See, i.e., FIGS. 8 and 9. This bias device is housed inside the bell actuator 1100 but is not shown in FIG. 32 for clarity. Also not shown is a snap ring that fits into a groove 1139 around the inner tube 1130. The bias device is delimited on the proximal side of the rod pullblock 1105 (see FIG. 34) and the distal side of the snap ring. In such a configuration, when the bell actuator 1100 is pulled proximally, the actuator 1100 forces the rod pullblock 1105 proximally to, thereby, move the articulation lock release slide 120, 1120 into an unlocked position. A keyhole on the interior surface of the bell actuator 1100 form-lockingly surrounds the rod pullblock 1105 so that rotation of bell actuator 1100 about the longitudinal axis of the inner tube 1130 forces the rod pullblock 1105 into a corresponding rotation. A form-locking or form-fitting connection is one that connects two elements together due to the shape of the elements themselves, as opposed to a force-locking connection, which locks the elements together by force external to the elements. As such, the inner tube and the entire distal assemblies of the device 1000 rotates as well. In an alternative configuration, the longitudinal movement of the bell actuator 1100 can function similar to a standard ball point pen by a first actuation placing the slide 120, 1120 in an unlocked state and a second actuation placing the slide 120, 1120 in a locked state.

With the bell actuator 1100 of the present invention, a physician is able to operate every function of the endostapler 1000 with one hand.

FIG. 32 illustrates the proximal end of the endostapler 1000 without the handle 1200. Coaxially disposed inside the bell actuator 1100 is a pushrod 1102 that will be used to move the cutting blade 1060 when the stapler is in the firing orientation.

FIG. 33 is an illustration of the parts at the proximal end of endostapler 1000 that axially fixedly and rotationally freely connect the distal assembly to the bell actuator 1100. More specifically, an inner tube 1130 (to be disposed inside the outer tube 1110) has a proximal extension 1132 defining an

inner tube coupling chamber **1134**. A clam-shell bushing **1131** has a length substantially equal to the extension **1132** of the inner tube **1130** and a bushing coupling chamber **1133** corresponding to the coupling chamber **1134** of the proximal extension **1132**. A rotational couple **1141** has a distal T-shaped rotation link **1143** having an outer shape corresponding to both of the coupling chambers **1133** and **1134** so that, when the link **1143** is disposed between the extension **1132** and the bushing **1131**, the link **1143** is free to rotate therein. This couple **1141** is fixed inside the handle **1200** through a proximal port **1145** on a proximal end of the couple **1141**.

When placed together, the inner tube **1130** is axially held with respect to the couple **1141** but is rotationally independent of the couple **1141**. Because the three coupling parts **1130**, **1131**, **1141** are sized to fit inside the outer tube **1110**, when the parts are placed inside the outer tube **1110**, the outer tube **1110** becomes a form-locking connection that prevents any separation of the inner tube **1130** and the bushing **1131** (so long as the outer tube **1110** sufficiently covers this area). Thus, when the bell actuator **1100** is rotated about the longitudinal axis of the inner tube **1130**, the inner and outer tubes **1110**, **1130** are able to rotate about the coaxial axis of the tubes **1110**, **1130** but remain longitudinally stable with respect to the couple **1141**, which is longitudinally fixed inside the handle **1200**.

FIG. **34** illustrates the proximal end of the endostapler **1000** without the handle **1200**, the bell actuator **1100**, and the outer tube **1110**. As can be seen, the inner tube **1130** is hollow and receives therethrough the pushrod **1102**, which will be described in further detail below. Also shown in these figures are the clevis **1010** and the drum sleeve **1040**, which, together, form the articulating connection or joint **1050** of the endostapler **1000**.

It is noted at this point that the lower jaw/staple cartridge holder **1030** is longitudinally fixed with respect to the handle **1200**. This fixation contrasts with the upper anvil **1020**, which can be pivoted and be moved somewhat longitudinally when sliding through the keyhole shaped cam surfaces **32** to close and/or open the jaws (described in further detail below/above with respect to cam surfaces **1032**).

To form the longitudinally fixed connection of the staple cartridge holder **1030** and the handle **1200**, the inner tube **1130** must be connected to the staple cartridge holder **1030**. But, at the same time, the staple cartridge holder **1030** must be able to articulate with respect to the longitudinal extent of the inner tube **1130**. Thus, an axially fixed but laterally articulating connection must exist between the two parts **1030**, **1130**.

To provide such a connection, the present invention includes at least one pullband **1140**, shown, for example, in FIGS. **35** to **38**. In an exemplary configuration, multiple pullbands **1140** are provided, one next to the other. Three or four bands form two possible configurations. With two pullbands **1140** as opposed to one, the longitudinal strength remains approximately the same but the force needed to laterally bend the pullbands **1140** is reduced. The same is true for three or four pullbands **1140**. FIG. **37** illustrates the proximal end of the pullband **1140**, which is longitudinally pinned to the distal end of the inner tube **1130** with a proximal pullband pin **1142**. To provide a strong connection between the pullband **1140** and the inner tube **1130**, a proximal guide block **1150**, for example, made of brass, is disposed between the distal end of the inner tube **1130** and the pullband **1140**.

The pullband **1140** spans the entire extent of the articulation joint **1050**, as shown in FIG. **35**, and is connected, as shown in FIG. **38**, to a distal guide block **1160**. The distal guide block **1160** (also, e.g., made of brass) has at least one

projection that fits into at least one recess on the proximal end of the staple cartridge holder **1030**. Later figures illustrate the measures by which the distal guide block **1160** is connected to the staple cartridge holder **1030** so that, finally, the staple cartridge holder **1030** is axially fixedly connected to the handle **1200** while being able to articulate with respect to the inner tube **1130**. As shown in FIG. **38**, a distal pullband pin **1144** axially locks the distal end of the pullband **1140** to the distal guide block **1160**.

A first embodiment of jaw **20**, **30** movement is described in the text above. There, the staple cartridge **30** moves axially and the anvil **20** is relatively stationary. In the configuration of the endostapler **1000** shown in FIGS. **31** et seq., movement is operationally opposite.

Noting that the staple cartridge holder **1030** is longitudinally fixed with respect to the handle **1200**, there still must be an assembly that permits closure of the two jaws **20**, **30**; **1020**, **1030**. Closure is, therefore, accomplished by movement of the upper jaw/anvil **1020** as set forth in the following text.

A first of the two levers of the handle **1200** (e.g., a proximal handle) is operatively connected to the outer tube **1110** to move the outer tube **1110** distally when the first lever is compressed/actuated. Because the clevis **1010**, the articulation joint **1050**, and the drum sleeve **1040** are axially fixedly connected to the outer tube **1110** (and because the outer tube **1110** can slide longitudinally along the inner tube **1130**), an actuation of the first lever moves the drum sleeve **1040** distally.

FIG. **39** illustrates the anvil **1020** in an open state. As can be seen therein, a gap **1031** exists between the distal end of the drum sleeve **1040** and a proximal shelf at the bottom of the staple cartridge holder **1030**. In such an orientation, the drum sleeve **1040**, the clevis **1010**, and the outer tube **1110** are proximally disposed at a distance from the shelf.

FIG. **40** illustrates the anvil **1020** in a closed state. As can be seen therein, no gap **1031** exists between the distal end of the drum sleeve **1040** and the proximal shelf of the staple cartridge holder **1030**. In such an orientation, the drum sleeve **1040**, the clevis **1010**, and the outer tube **1110** are in a position where the drum sleeve **1040** contacts the shelf.

In contrast to the axially fixed position of the staple cartridge holder **1030** with respect to the handle **1200**, and similar to the movement of the drum sleeve **1040**, the knife **60**, **1060** must translate with respect to the handle **1200** along the longitudinal axis. FIGS. **35**, **36**, and **38** to **41** illustrate the axially displaceable connection of the knife **1060** to the knife-moving features of the handle **1200**.

With regard to FIG. **35**, a pushrod **1102** extends from the handle **1200** and is connected to a second non-illustrated lever (e.g., a distal lever) of the handle **1200**. The distal end of the pushrod **1102** is connected to at least one flexible knife blade **1062** through a pushrod pin **1122**. The distal end of the knife blade **1062** is connected to the proximal side of the cutting blade **1060** such that the cutting blade **1060** moves distally or proximally to follow corresponding movement of the pushrod **1102**. It is noted that the knife blade **1062** has a proximal, upwardly extending flange **1064** that houses a bore for receiving the pushrod pin **1122**. This off-axis connection between the pushrod **1102** and the knife blade **1062** causes the distal end of the knife blade **1062** to be forced downwardly when pushed in the distal direction and, therefore, to stay in position inside a pushrod-blade support **1070** shown, for example, in FIGS. **36** and **42**.

The knife blade **1062** is flexible enough to bend in any way that the articulation joint **1050** bends. Therefore, the knife blade **1062** is also flexible enough to possibly kink if it was not supported. The present invention, therefore, provides a

pushrod-blade support **1070**, which is shown in FIGS. **36** and **42**. Therein, the proximal end of the pushrod-blade support **1070** clearly reveals the rectangular blade channel **1072** for supporting slidably the rectangular knife blade **1062**. Also shown therein is a curved pushrod channel **1074** for supporting slidably the curved (e.g., cylindrical) exterior of the pushrod **1102**. Thus, the pushrod-blade support **1070** supports the pushrod **1102** at locations where the pushrod **1102** is inside the support **1070** and also supports the knife blade **1062** where the knife blade **1062** is inside the support **1070**.

FIG. **36** shows the connection of the support **1070** and its relation to the proximal guide block **1150**.

Like the pullbands **1140**, more than one knife blade **1062** can be next to one another. In such a configuration, the multiple blades **1062** have the same longitudinal stiffness but provide greater flexibility when there is a bend in the articulation joint **1050**.

Revealed in FIG. **41** is the articulation lock release slide **1120** that locks the articulation of the jaws **1020**, **1030**.

FIGS. **42** to **50** illustrate a vertical cross-section of the tube portion distal of the handle **1200** along planes that are orthogonal to the longitudinal axis of the endostapler **1000**.

FIG. **42** shows the cross-section of the connection junction of the knife blade **1062** and the pushrod pin **1122**. The pushrod pin **1122** passes through the entirety of two adjacent blades **1062** and the pushrod **1102** but does not extend outside the pushrod's outer surface. This figure also illustrates the relationship of the inner and outer tubes **1130**, **1110** and the pushrod-blade support **1070**. Also apparent in this figure is an unlock pullrod **1104** used for unlocking the lock release slide **1120**. The longitudinal extent of the unlock pullrod **1104** is first shown in FIG. **35** and is also shown in FIGS. **36**, **37**, **41**, and **52** and **53**. Most particularly, with exterior parts hidden, FIG. **41** shows how the pullrod **1104** connects the bell actuator **1100** to the articulation lock release slide **1120**. With the distal end of the pullrod **1104** passed through and wrapped around the distal end of the articulation lock release slide **1120** as shown in FIG. **37**, the unlock pullrod **1104** establishes a longitudinally fixed connection between the bell actuator **1100** and the articulation lock release slide **1120**. As such, when the bell actuator **1100** is moved proximally, the articulation lock release slide **1120** moves in a corresponding proximal direction to separate the distal teeth **1121** of the articulation lock release slide **1120** and the spokes **1041** of the sprocket **1522**. See, in particular, FIGS. **46** and **52**. It is noted that the wrapped connection between the pullrod **1104** and the articulation lock release slide **1120** is only an exemplary embodiment. Other form-locking or force-locking connections are possible as well.

FIG. **43** shows the connection through the pullband **1140** and inner tube **1130** pin joint. As set forth above, the proximal pullband pin **1142** passes entirely through the blades **1062**, the proximal guide block **1150**, and the inner tube **1130** but not through the outer tube **1110**.

FIG. **44** shows the area immediately proximal of the proximal end of the articulation lock release slide **1120**. In this exemplary embodiment, two pullbands **1140** are disposed above two blades **1062**. To provide support to at least one of the pullbands **1140** and the blades **1062**, a pair of hammocks **1066** is placed along sides of the articulating portions of the pullbands **1140** and blades **1062**. Each of the hammocks **1066** has a U-shape (along a longitudinal cross-section) so that the proximal arm of each hammock **1066** bends around the proximal surface of the clevis **1010** and the distal arm of each hammock **1066** bends around a catching surface within the drum sleeve **1040**, as shown in FIG. **50**, for example.

Inside the clevis **1010** are disposed two spring rods **1012** about which are respective spring rod collars **1014**, the function of which is to bias laterally the entire assembly distal of the articulation joint **1050** towards and along the longitudinal axis. The spring rods and collars **1012**, **1014** will be described in further detail below.

FIG. **45** illustrates the open area in the center of the articulation lock release slide **1120** that receives the bend portion of the pullrod **1104** (not illustrated in this figure). Also shown are the cavities **1016** in which the non-illustrated bias springs of the spring rods **1012** rest. This cross-sectional area also includes portions of the two pullbands **1140** disposed above the two knife blades **1062**.

FIG. **46** illustrates the open area in which the distal end of spring rods **1012** acts against cam surfaces **1018**. It is noted that the cam surfaces **1018** are arcuate in shape so that contact between the spring rods **1012** and the cam surfaces **1018** always act in an axial direction normal to the surface at the distal-most end of the spring rods **1012**. See, for example, FIG. **56**. In such a configuration, the force that is applied by the spring rods **1012** against the cam surfaces **1018** to bias the distal articulating assembly (e.g., anvil **1020**, staple cartridge holder **1030**, drum sleeve **1040**) towards the longitudinal axis of the inner and outer tubes **1130**, **1110** is always at the same radius about the articulation axis of the articulating staple cartridge holder **1030**. One advantage of such a configuration lies in the fact that the spring rods **1012** are not forced laterally in any way, in which case, the distal-most end of the spring rods **1012** could catch and lock on the cam surface **1018**.

FIG. **47** illustrates, in cross-section, the area within the endostapler articulation joint **1050**. Again, this area includes portions of the two pullbands **1140**, of the two blades **1062**, and of the two hammocks **1066**. Upper and lower axle pucks **1152** are inserted in orifices **1042** above and below on surfaces of the drum sleeve **1040**. Connection of the clevis **1010** to the drum sleeve **1040** at the articulation joint **1050** is symmetrical on the top and bottom. The pucks **1152** are inserted into the orifices **1042** in the top and bottom of the proximal end of the drum sleeve **1040**. In this orientation, the assembly is inserted into the distal end of the clevis **1040** to align screw holes **1011** with center threaded bores **1153** of the pucks **1152**. When aligned, screws **1013** are threaded respectively into the pucks **1152** to axially secure the drum sleeve **1040** into the clevis **1010** while allowing the drum sleeve **1040** to articulate about the axis defined by the longitudinal axis of the two screws **1013**.

FIG. **48** illustrates the area of the distal pullband pin joint. In this area, the distal ends of the pullbands **1140** are secured by the distal pullband pin **1144** disposed inside the bore of the distal guide block **1160**. The distal guide block **1160** is disposed in the staple cartridge holder **1030** and secured thereto as set forth above.

FIG. **49** illustrates the area just proximal of the cutting blade **1060** and the fixed connection of the two knife blades **1062** inside a proximal orifice of the cutting blade **1060**. This view also clearly shows the cam surfaces **1032** that allow the anvil **1020** to pivot and translate with respect to the staple cartridge holder **1030**.

FIG. **50** shows a longitudinal cross-section through the spring rods **1012**. Visible in this view is the entire longitudinal extent of the hammocks **1066**. The distal sections of the hammocks **1066** articulate about a vertical axis near the distal end of the hammocks **1066**. In FIG. **50**, there exists a substantial gap between the spring rods **1012** and the hammocks **1066**. If the hammocks **1066** were not present, there exists the possibility that the thin knife blades **1062** could bend and warp or kink into these gaps. By placing the hammocks **1066**

therebetween, any possibility of impermissible bending of the knife blades **1062** is prevented. FIG. **51** is provided to show the extreme bending extent of the hammocks **1066** and the blades **1062** therebetween in a test bed made for such a purpose. It is noted that the upper hammock **1066** is not utilized in an upward bend with respect to FIG. **51** because it tracks the inside surface of the curve at the critical bending area. In contrast, the lower hammock **1066** is utilized to substantially prevent the knife blades **1062** therebetween (two in this exemplary embodiment) from impermissibly bending into the gap of the test bed. Because each hammock **1066** is held rigidly at either end and is made out of a substantially non-elastic material (e.g., of stainless steel), it forms a sling or "hammock" that supports the bent knife blade(s) **1062** therebetween.

FIG. **52** illustrates a cross-section through the articulation lock release slide **1120** and clearly shows the distal connection bend of the unlock pullrod **1104** inside the slide **1120**. In such a configuration, proximal displacement of the unlock pullrod **1104** causes a corresponding proximal displacement of the slide **1120** to unlock the teeth **1121** of the slide **1120** from between the corresponding teeth **1041** on the proximal side of the drum sleeve **1040**. A distal bias is imparted upon the articulation lock release slide **1120** by a non-illustrated bias device that resides in a hollow **1123** and presses against the distal end of the hollow **1123** and a block **1124** that is fixed with respect to the clevis **1010**.

FIG. **35** shows the connection between the unlock pullrod **1104** and the handle **1200**. A rod pullblock **1105** has a longitudinal bore **1107** for receiving therein the pullrod **1104**. The rod pullblock **1105** also has transverse bores **1109** for receiving non-illustrated set screws therein for securing the pullrod **1104** inside the rod pullblock **1105**. An interior portion of the bell actuator **1100** is shaped to engage the rod pullblock **1105** (for example, in a form-fitting connection such as a keyhole) and displace the rod pullblock **1105** proximally when the bell actuator **1100** is moved proximally.

FIG. **53** is an exploded perspective view of the distal parts of the endostapler as viewed from the distal end thereof.

It is noted that the clevis **1010** in FIGS. **34** to **53** is a one-piece part. Alternatively, the clevis **1010** can be molded in two halves. In such a case, the pucks **1152** can be eliminated and, instead, form parts of each of the two clevis halves, thereby eliminating the need for the screws **1013** because the outer tube **1110** will hold the two halves together when attached to the proximal end of the clevis **1010**. Such a configuration is illustrated in the endostapler embodiment of FIGS. **54** et seq.

FIG. **54** shows some internal parts of this fourth embodiment of the end effector. The anvil **1020** is disposed opposite the staple cartridge holder **1030** and a closure ring **1040** surrounds the proximal end of the staple cartridge holder **1030**. The inner and outer tubes **1130**, **1110** are removed so that the articulation lock release slide **1120**, the pushrod **1102**, and the pushrod-blade support **1070** can be seen clearly. A screen door **1103** is mounted around the pushrod **1102** and inside the inner and outer tubes **1130**, **1110** and the bell actuator **1100**. The handle **1200** and bell actuator **1100** are removed for clarity. The screen door **1103** restricts movement of the pushrod **1102** to only one direction — distal — because the knife/cutting blade **1060** only moves in the distal direction.

The two-part clevis is best illustrated in the views of FIGS. **55** and **56**. These figures show various internal features of the end effector of FIG. **54** with the outer tube **1110** removed. In the exploded view of FIG. **55**, connection of the pullband(s) **1140** to the staple cartridge holder **1030** is apparent. A non-

illustrated pin (see also FIG. **59**) passes through a first proximal flange of the holder **1030**, a first spacer **1170**, a distal flange of the pullband **1140**, a second spacer **1170**, and a second opposing proximal flange of the holder **1030**, respectively. The closure ring **1040**, as shown in FIG. **59**, holds the pin therein to provide the longitudinal connection of these components.

Various features of the knife/cutting blade **1060** are also revealed in FIG. **55**. The blade **1060** has a proximal recess **1061** for connecting a distal end of the knife blade **1062** thereto. In the exemplary embodiment, the recess **1061** and distal end form a keyhole-shaped lock. The upper half of the blade **1060** has two opposing guide wings **1063** having an exterior shape that fits into a corresponding groove inside the bottom surface of the upper anvil **1020**. The lower half of the blade **1060** also has two opposing guide wings **1065**. The holder **1030** has a groove inside the top surface thereof for receiving the lower wings **1065** therein. These two pairs of wings **1063**, **1065** ensure that the anvil **1020** and the holder **1030** are at a fixed parallel position when the blade **1060** is traversing there along in the cutting and stapling process. Also disposed on the lower half of the blade **1060** is a proximally extending flange **1067**. A plate spring **1090** is attached to the staple cartridge holder **1030** by rivets **1036**. The plate spring **1090** and other features of the blade **1060** will be described in greater detail below.

FIGS. **55** and **56** also show various portions of the two-part clevis **2010**, **2020**. As can be seen in FIGS. **56** and **58**, the interior surface of the upper clevis half **2010** defines two cavities **2011** that each house a respective spring rod **1012** and the non-illustrated bias device for that spring rod **1012**. In the exemplary embodiment shown, the upper clevis half **2010** defines the entire cavity **2011** for the spring rods **1012** and the lower clevis half **2020** defines the bottom cavity portion **2021** for accommodating only the bias device. The clevis halves **2010**, **2020** also define articulation ports **2012**, **2022** for receiving therein articulation bosses **2031**, **2041** on each of the two dogbone clevis parts **2030**, **2040**.

FIGS. **56** and **57** illustrate the longitudinal connectivity of the features within the outer tube **1110**. The pushrod-blade support **1070** is disposed inside a lower channel of the inner tube **1130**. This pushrod-blade support **1070** also has a distal extension **1071** with a narrow proximal neck **1074** and a relatively wider distal head **1075**. With a corresponding recess **2023** in the bottom of the lower clevis half **2020**, the distal extension **1071** can be longitudinally fixed to the clevis half **2020** and, therefore, the remainder of the clevis.

The outer tube **1110** and the lower clevis half **2020** are removed in FIG. **56** to illustrate the configuration of the spring rods **1012** inside the spring rod cavities **2011**. Again, the spring rod bias devices (e.g., coil springs) are not shown in the cavities **2011** for clarity. With various parts removed, the articulating extent of the pullbands **1140** is clearly shown in FIG. **56**. The supporting surfaces for the pullbands **1140** inside the upper clevis half **2010** are visible at the cross-section plane of FIG. **58**. The upper dogbone clevis **2030** has two opposing supporting surfaces **2032** each at a similar acute angle with respect to the centerline of the un-articulated pullbands **1140**. Likewise, the upper clevis half **2010** has two opposing supporting surfaces **2013** each at an acute angle with respect to the centerline of the un-articulated pullbands **1140**.

The opposite viewing direction towards the interior of the lower clevis half **2020** is illustrated in FIGS. **55** and **58**. The articulation section for the knife blades **1062** is illustrated along with the supporting surfaces **2042** for the dogbone **1080** inside the lower dogbone clevis **2040** and the supporting

surfaces **2024** for the dogbone **1080** inside the lower clevis half **2010**. Also visible in this orientation are guiding and supporting surfaces for the dogbone guide **1080**. In FIG. **57**, it is seen that the lower dogbone clevis has a kidney-shaped distal dogbone depression **2043** and the lower clevis half **2010** has a kidney-shaped proximal dogbone depression **2025**. These depressions **2025**, **2043** and surfaces **2024**, **2042** are also illustrated in FIG. **66** and will be described in detail below. A further feature visible in FIGS. **59**, **62**, and **66** is the interior passage of the dogbone guide **1080** having left and right surfaces **1082** and will be describe in further detail below.

The distal end of the dogbone guide **1080** is shown in the vertical cross-section of FIG. **59**. The distal dogbone depression **2043** houses the distal end of the dogbone guide **1080** and, when unarticulated, the dogbone guide **1080** does not touch the supporting surfaces **2042** of the lower dogbone clevis **2040**.

The proximal housing for the distal end of the dogbone guide **1080** is illustrated in FIG. **60**. To better reveal the features of the proximal dogbone depression **2025**, the dogbone guide **1080** is removed from these figures.

Both of the depressions **2025**, **2043** with the lower extending portions of the dogbone guide **1080** disposed therein are shown in horizontal, longitudinally transverse cross-section of FIG. **57**. Also shown therein are the lower features of the pushrod-blade support **1070**, the cutting blade **1060**, and the staple sled **102** (which is a part of the removable staple cartridge **100**). These features are enlarged in FIGS. **61** and **62**.

FIGS. **63**, **64**, and **65** illustrate the knife blade **1060** lock-out feature. In other words, the safety that prevents the knife blade **1060** from advancing when there is no staple cartridge **100** or a previously fired staple cartridge **100** in the staple cartridge holder **1030**. For ease of understanding, the only part of the staple cartridge **100** shown in these figures is the staple sled **102**.

The knife blade **1060** should be allowed to move distally only when the staple sled **102** is present at the firing-ready position, i.e., when the sled **102** is in the position illustrated in FIG. **65**. If the sled **102** is not present in this position, this can mean one of two things, either there is no staple cartridge **100** in the holder **1030** or the sled **102** has already been moved distally—in other words, a partial or full firing has already occurred with the loaded staple cartridge **100**. Thus, the blade **1060** should not be allowed to move, or should be restricted in its movement. Accordingly, the sled **102** is provided with a lock-out contact surface **104** and the blade **1060** is provided with a correspondingly shaped contact nose **1069**. It is noted at this point that, the lower guide wings **1065** do not rest against a floor **1034** in the cartridge holder **1030** until the blade **1060** has moved distally past an edge **1035**. With such a configuration, if the sled **102** is not present at the distal end of the blade **1060** to prop up the nose **1069**, then the lower guide wings **1065** will follow the depression **1037** just proximal of the edge **1035** and, instead of advancing on the floor **1034**, will hit the edge **1035** and stop further forward movement of the blade **1060**. To assist with such contact when the sled **102** is not present, the staple cartridge **1030** has a plate spring **1090** (attached thereto by rivets **1036**). With the plate spring **1090** flexed upward and pressing downward against the flange **1067** (at least until the flange **1067** is distal of the distal end of the plate spring **1090**), a downwardly directed force is imparted against the blade **1060** to press the wings **1065** down into the depression **1037**. Thus, as the blade **1060** advances distally without the sled **102** being present, the wings **1065** follow the lower curve of the depression **1037** and are stopped from further distal movement when the distal

edge of the wings **1065** hit the edge **1035**. FIG. **63**, for example, shows the distal edge **1035** and two raised bosses **1038** that extend the height of the edge **1035** to insure that the wings **1065** cannot be forced over the edge **1035** when the sled **102** is not present.

FIG. **66** illustrates an exemplary movement of the dogbone **1080** within the lower clevis half **2020** and the lower dogbone clevis **2040**. In the fully left articulated position of FIG. **66**, the distal bottom projection of the dogbone **1080** is in a rotated position within the distal dogbone depression **2043** and the proximal bottom projection is in a rotated position within the proximal dogbone depression **2025**. Importantly, the left vertical surface of the dogbone **1080** is almost fully supported on the left dogbone supporting surfaces **2024**, **2042**. The shapes of the depressions **2025**, **2043** and the bottom projections of the dogbone **1080** are selected such that there is no elongation or compression of the dogbone **1080** but, merely, a rocking left to right when articulation of the end effector occurs.

Three side-by-side knife blades **1062** are diagrammatically illustrated in FIG. **66** within a left articulated position of the lower clevis halves **2020**, **2040**. When bent to the left, the knife blades **1062** are pressed against the right interior surface **1082** of the dogbone **1080**. Accordingly, the interior surfaces **1082** are shaped dependent upon the extent that the end effector will be articulated. Due to the limitations of drafting the features of the invention, the blades **1062** are only shown in a diagrammatic, approximate curved orientation.

To better understand some features of the knife blades **1062**, enlarged views of the proximal connection to the pushrod **1102** and the pushrod-blade support **1070** are shown in FIG. **67**. While a configuration having co-axially aligned knife blades **1062** and the pushrod **1102** is envisioned and possible, an offset connection shown, for example, in FIGS. **41** and **67**, is used. As set forth above, the length of the knife blades **1062** make it desirable for the knife blades **1062** to be pressed down fully into the blade channel **1072** within the pushrod-blade support **1070**. FIG. **41** shows a first embodiment for an offset connection that biases the blades **1062** into the channel **1072**. FIG. **67** shows a second embodiment for this offset connection. In this second embodiment, the blades **1062** are not fixedly connected to the pushrod **1102** as in the first embodiment (connected by transverse pushrod pin **1122**). Instead, the pushrod **1102** is formed with a chamber **1108** into which is inserted the proximal end of the blades **1062**. By forming the chamber **1108** in a shape that axially longitudinally holds the blades **1062** (e.g., with a transverse offset), there is no need for a fixed connection. In this embodiment, the chamber **1108** is approximately L-shaped in vertical cross-section to provide such a transverse offset, but it can be any number of different shapes.

The distal connection of the pullbands **1140** is shown particularly well in FIG. **59**. It is noted that, in such a configuration, left or right articulation imparts a bend on each of the two, three, four, or more adjacent pullbands **1140**. Because each pullband **1140** has a fixed length, and because the pullbands **1140** are stacked alongside one another, articulation in a given direction bends each of the pullbands **1140** differently, even if the difference is very slight. To compensate for such differences in bending, an alternative embodiment of the distal connection is provided and is shown in FIGS. **68** to **70**. For clarity and simplicity, only a portion of the upper dogbone clevis **2030** is shown diagrammatically in these figures.

This alternative embodiment replaces the spacers **1170** in the first embodiment. Here, five pullbands **1140** are disposed alongside one another. The upper dogbone clevis **2030** defines an interior bore **2033** (e.g., a circular bore) into which

25

is inserted a piston **2050** having an exterior shape corresponding to the interior shape of the bore **2033**. The bore **2033** has a proximal window **2034** through which the pullbands **1140** project into the bore **2033**. The window **2034** has a width approximately equal (but just slightly larger than) the total width of the pullbands **1140**.

The piston **2050** has a transverse bore into which is threaded a proximal pullband pin **2060** that functions as an axle when threaded through the piston **2050** and through the distal pullband bore **1145** of each of the pullbands **1140**. See FIG. **70**. The interior **2051** of the piston **2050** does not have a shape corresponding to the width of the stacked pullbands **1140**. Instead, the interior opening for receiving the distal end of the pullbands **1140** has a winged horizontally cross-sectional shape.

As the end effector articulates, the distal end of the pullbands **1140** are bent into a curve. When adjacent parallel plates such as the pullbands **1140** are bent together, the outside plates move differently than the middle or inner plates. This non-homogeneous movement is compensated for by the winged opening **2051** and the oval-shaped distal pullband bores **1145**. As the end effector is articulated, the bending forces imparted upon the pullbands **1140** cause the piston **2050** to rotate within the bore **2033** of the upper dogbone clevis **2030**. The more that the end effector articulates, the more the piston **2050** rotates, until full articulation presses the outside pullband **1140** against the inner surface of the winged opening **2051**. At this point, the proximal ends of each pullband **1140** are aligned but the distal ends shown in FIGS. **68** to **70** are not. The presence of the oval openings **1145** allow the pullbands **1140** to move slightly with respect to one another.

The foregoing description and accompanying drawings illustrate the principles, preferred embodiments and modes of operation of the invention. However, the invention should not be construed as being limited to the particular embodiments discussed above. Additional variations of the embodiments discussed above will be appreciated by those skilled in the art.

Therefore, the above-described embodiments should be regarded as illustrative rather than restrictive. Accordingly, it should be appreciated that variations to those embodiments can be made by those skilled in the art without departing from the scope of the invention as defined by the following claims.

What is claimed is:

1. A medical device, comprising:
 - a pistol-shaped handle;
 - a laparoscopic shaft extending from the handle having a distal end and defining a shaft axis;
 - a surgical end effector connected to the distal end of the shaft;
 - a surgical procedure actuator operable to carry out a surgical procedure on tissue at the end effector; and
 - a rotating knob at a distal end of the handle:
 - rotatable with respect to the shaft about the shaft axis; and
 - operable to actuate the surgical procedure actuator when slid in a direction towards the handle.
2. The medical device according to claim 1, wherein the end effector is connected to the distal end of the shaft with a passive articulating connection.
3. The medical device according to claim 2, wherein:
 - the end effector is rotationally fixedly connected to the shaft with the passive articulating connection; and
 - the rotating knob is operable to correspondingly rotate the shaft and the end effector when rotated about the shaft axis.

26

4. The medical device according to claim 1, wherein:
 - the end effector is connected to the distal end of the shaft with a passive articulating connection;
 - the surgical procedure actuator is a locking device of the passive articulating connection; and
 - actuation of the surgical procedure actuator by movement of the rotating knob towards the handle unlocks the passive articulating connection.
5. The medical device according to claim 4, wherein:
 - the surgical procedure actuator has an unactuated state and an actuated state;
 - the passive articulating connection has a locked articulation state and an unlocked articulation state; and
 - the surgical procedure actuator:
 - changes the passive articulating connection from the locked articulation state to the unlocked articulation state when the rotating knob is moved towards the handle; and
 - changes the passive articulating connection from the unlocked articulation state to the locked articulation state when the rotating knob is released after movement towards the handle has occurred.
6. The medical device according to claim 4, wherein the end effector articulates after:
 - the surgical procedure actuator is actuated by movement of the rotating knob towards the handle; and
 - thereafter, an external force is applied to the end effector.
7. The medical device according to claim 4, wherein, when the surgical procedure actuator is actuated by movement of the rotating knob towards the handle, the end effector freely articulates dependent upon external forces acting upon the end effector.
8. The medical device according to claim 4, wherein:
 - the shaft has a first longitudinal axis;
 - the end effector has a second longitudinal axis;
 - at least one of the shaft, the end effector, and the passive articulating connection has an alignment device; and
 - the alignment device is operable to bias the end effector to substantially align the first and second longitudinal axes when the surgical procedure actuator is actuated by movement of the rotating knob towards the handle.
9. The medical device according to claim 8, wherein the alignment device is a center-biasing device.
10. The medical device according to claim 1, wherein:
 - the pistol-shaped handle has a stapler-closing device; and
 - the end effector is a surgical stapling end effector having a pair of opposing stapling surfaces, at least one of the stapling surfaces being operable to move with respect to the other of the stapling surfaces upon actuation of the stapler-closing device to apply a compressive force to tissue therebetween.
11. The medical device according to claim 1, wherein the end effector further comprises a knife assembly disposed to cut tissue at the end effector.
12. The medical device according to claim 1, wherein the end effector comprises one of a circular surgical staple head and a linear surgical staple head.
13. The medical device according to claim 1, wherein:
 - the end effector is rotationally fixedly connected to the shaft; and
 - the rotating knob is operable to correspondingly rotate the shaft and the end effector when rotated about the shaft axis.
14. The medical device according to claim 13, wherein the rotating knob is operable to correspondingly rotate the shaft and the end effector when rotated about the shaft axis and simultaneously actuate the surgical procedure actuator.

15. The medical device according to claim 1, wherein:
the end effector is a surgical stapling end effector having a
stapling device with staples and a cutting device with a
blade;

the handle has:

a stapler closing actuator closing the stapling device
when actuated; and

a firing actuator that, when actuated:
staples with the stapling device; and
cuts with the cutting device; and

the stapler closing actuator and the staple firing actuator are
different from the rotating knob.

16. A medical device, comprising:

a pistol-shaped handle;

a laparoscopic shaft extending from the handle having a
distal end and defining a shaft axis;

a surgical end effector connected to the distal end of the
shaft;

a surgical procedure actuator operable to carry out a surgi-
cal procedure on tissue at the end effector; and

a rotating knob at a distal end of the handle:
rotatable with respect to the shaft about the shaft axis;
and

operable to actuate the surgical procedure actuator when
slid in a proximal direction towards the handle.

* * * * *

专利名称(译)	外科缝合和切割装置		
公开(公告)号	US8695865	公开(公告)日	2014-04-15
申请号	US13/547968	申请日	2012-07-12
[标]申请(专利权)人(译)	SMITH KEVIN W. PALMER 马修 川崎汽船寇瑞 - [R DEVILLE DEREK DEE		
申请(专利权)人(译)	SMITH KEVIN W. PALMER MATTHEW A. 川崎汽船寇瑞R. DEVILLE DEREK DEE		
当前申请(专利权)人(译)	爱惜康内镜手术 , INC.		
[标]发明人	SMITH KEVIN W PALMER MATTHEW A KLINE KOREY R DEVILLE DEREK DEE		
发明人	SMITH, KEVIN W. PALMER, MATTHEW A. KLINE, KOREY R. DEVILLE, DEREK DEE		
IPC分类号	A61B17/068 A61B17/68		
CPC分类号	A61B2017/2931 A61B2017/07271 A61B2017/2927 A61B17/07207 A61B17/068 A61B2017/320052 A61B2017/00389 A61B17/00234 A61B17/072 A61B17/115 A61B2017/003 A61B2017/07214 A61B2017/07285		
代理人(译)	MAYBACK , GREGORY L.		
审查员(译)	SMITH , SCOTT A.		
优先权	60/702643 2005-07-26 US 60/760000 2006-01-18 US 60/811950 2006-06-08 US		
其他公开文献	US20120286020A1		
外部链接	Espacenet USPTO		

摘要(译)

一种医疗装置，包括手枪形手柄，从手柄延伸的腹腔镜轴，其具有远端并限定轴轴线，连接到轴的远端的外科端部执行器，可操作以执行在末端执行器处的组织上的外科手术过程，以及在手柄处的旋转旋钮，其可相对于轴绕轴的轴线旋转，并且可操作以致动外科手术致动器并实现外科手术。

