

# (12) United States Patent

### Brustad et al.

### (54) HAND ACCESS LAPAROSCOPIC DEVICE

(71) Applicant: Applied Medical Resources

Corporation, Rancho Santa Margarita,

(72) Inventors: John Brustad, Rancho Santa Margarita,

CA (US); Jeremy Albrecht, Rancho Santa Margarita, CA (US); Nabil Hilal, Rancho Santa Margarita, CA (US); Gary Johnson, Rancho Santa Margarita, CA (US); Charles Hart,

Rancho Santa Margarita, CA (US)

(73) Assignee: Applied Medical Resources

Corporation, Rancho Santa Margarita,

CA (US)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/681,292

(22)Filed: Apr. 8, 2015

(65)**Prior Publication Data** 

> US 2015/0209076 A1 Jul. 30, 2015

### Related U.S. Application Data

(60) Continuation of application No. 14/149,497, filed on Jan. 7, 2014, now Pat. No. 9,017,254, which is a continuation of application No. 13/006,727, filed on Jan. 14, 2011, now Pat. No. 8,647,265, which is a

(Continued)

(51) Int. Cl.

A61B 1/32 (2006.01)A61B 17/02 (2006.01)

(Continued)

(52) U.S. Cl.

CPC ...... A61B 17/0293 (2013.01); A61B 17/02

(2013.01); *A61B* 17/0218 (2013.01);

(Continued)

US 9,474,519 B2 (10) Patent No.:

Oct. 25, 2016 (45) **Date of Patent:** 

Field of Classification Search (58)

CPC .... A61B 1/32; A61B 17/02; A61B 17/3423;

A61M 29/00

USPC ...... 600/201-246; 606/108, 206, 208 See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

558,364 A 4/1896 Doolittle 1,157,202 A 10/1915 Bates et al.

(Continued)

FOREIGN PATENT DOCUMENTS

26 05 148 A1 DE 8/1977 DE 33 36 279 C2 1/1986

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 10/902,756, filed Jul. 29, 2004; Title: Hand Access

Port Device, now abandoned.

(Continued)


Primary Examiner — Ellen C Hammond Assistant Examiner — Christina Negrellirodrigue

(74) Attorney, Agent, or Firm — Patrick Ikehara

ABSTRACT

The application relates to a hand access laparoscopy device having a gelcap, a retainer, a sleeve and a retention ring. The gelcap includes gel that is bonded to a cap. The cap includes an inner cylindrical wall to which the gel in bonded, thereby providing a sealing area between the device and the wound in a body wall. By securing the gel to the inner cylindrical wall, the thickness of the gel and corresponding cap is minimized along with the overall footprint of the device. With the gel thickness reduced and able to be substantially flush, the "doming" phenomenon produced by insufflation of a patient's abdomen is reduced.

### 15 Claims, 16 Drawing Sheets



3,831,583 A 3,841,332 A

3,850,172 A

8/1974 Edmunds et al.

Treacle

Cazalis

10/1974

11/1974

### Related U.S. Application Data

continuation of application No. 12/815,986, filed on Jun. 15, 2010, now Pat. No. 7,878,974, which is a division of application No. 11/548,955, filed on Oct. 12, 2006, now Pat. No. 7,736,306.

- (60) Provisional application No. 60/726,826, filed on Oct. 14, 2005, provisional application No. 60/745,730, filed on Apr. 26, 2006, provisional application No. 60/803,346, filed on May 26, 2006, provisional application No. 60/803,965, filed on Jun. 5, 2006, provisional application No. 60/828,089, filed on Oct. 4, 2006.
- (51) **Int. Cl.**A61B 17/34 (2006.01)

  A61B 17/00 (2006.01)
- (52) U.S. Cl.

CPC ...... *A61B17/3423* (2013.01); *A61B 17/3431* (2013.01); *A61B 17/3462* (2013.01); *A61B 17/3498* (2013.01); *A61B 90/40* (2016.02); *A61B 17/3439* (2013.01); *A61B 17/3496* (2013.01); *A61B 2017/00477* (2013.01); *A61B 2017/00526* (2013.01); *A61B 2017/0287* (2013.01); *A61B 2017/347* (2013.01); *A61B 2017/3419* (2013.01); *A61B 2050/005* (2016.02); *A61B 2050/0051* (2016.02)

### (56) References Cited

### U.S. PATENT DOCUMENTS

1,598,284 A 8/1926 Kinney 1,690,995 A 11/1928 Pratt 1,180,466 A 6/1931 Deutsch 1,810,466 A 6/1931 Deutsch 2,219,564 A 10/1940 Reyniers 2,305,289 A 12/1942 Coburg 2,478,586 A 8/1949 Krapp 2,669,991 A 2/1954 Curutchet 2.695,608 A 11/1954 Gibbon 2,812,758 A 2,835,253 A 11/1957 Blumenschein 5/1958 Borgeson 2,853,075 A 9/1958 Hoffman et al. 3,039,468 A 6/1962 Price 3,057,350 A 10/1962 Cowley 3,111,943 A 11/1963 Orndorff 3,195,934 A 7/1965 Parrish 3,244,169 A 4/1966 Baxter 3,253,594 A 5/1966 Matthews et al. 3,313,299 A 4/1967 Spademan 3,329,390 A 7/1967 Hulsey 3,332,417 A 7/1967 Blanford et al. 3,347,226 A 10/1967 Harrower 3,347,227 A 10/1967 Harrower 3,397,692 A 8/1968 Creager, Jr. et al. 3,402,710 A 9/1968 Paleschuck 3,416,520 A 12/1968 Creager, Jr. 3,447,533 A 6/1969 Spicer 3,522,800 A 8/1970 Lesser 3,523,534 A 8/1970 Nolan 3,570,475 A 3/1971 Weinstein 3,656,485 A 4/1972 Robertson 3,685,786 A 8/1972 Woodson 3,717,151 A 2/1973 Collett 3,717,883 A 2/1973 Mosher 3.729.006 A 4/1973 Wilder et al. 3,729,027 A 4/1973 Bare 3,782,370 A 1/1974 McDonald 3,797,478 A 3/1974 Walsh et al. 3/1974 3,799,166 A Marsan 3,807,393 A 4/1974 McDonald 3,828,764 A 8/1974 Jones

3,853,126 A 12/1974 Schulte 3,853,127 A 12/1974 Spademan 3,856,021 A 12/1974 McIntosh 3,860,274 A 1/1975 Ledstrom et al. 3,861,416 A 1/1975 Wichterle 3,907,389 A 9/1975 Cox et al. 3.915.171 A 10/1975 Shermeta 3.965,890 A 6/1976 Gauthier 7/1976 3,970,089 A Saice 3,996,623 A 12/1976 Kaster 4,000,739 A 1/1977 Stevens 4,016,884 A 4/1977 Kwan-Gett 4,024,872 5/1977 Muldoon 4,030,500 A 6/1977 Ronnquist 4,043,328 A 8/1977 Cawood, Jr. et al. 4.069,913 A 1/1978 Harrigan 4,082,005 A 4/1978 Erdlev 4/1978 4,083,370 A Taylor 4,096,853 A 6/1978 Weigand 4,112,932 A 9/1978 Chiulli 4,117,847 10/1978 Clayton 4,130,113 A 12/1978 Graham 4,177,814 A 12/1979 Knepshield et al. 4,183,357 A 1/1980 Bentley et al. 4,187,849 A 2/1980 Stim 4,188,945 A 2/1980 Wenander 4,217,664 A 8/1980 Faso 4,222,126 A 9/1980 Boretos et al. 4,228,792 A 10/1980 Rhys-Davies 4,239,036 A 12/1980 Krieger 4,240,411 A 12/1980 Hosono 4,253,201 A 3/1981 Ross et al. 4,254,973 A 3/1981 Benjamin 4,306,562 A 12/1981 Osborne 4,321,915 A 3/1982 Leighton 5/1982 4,331,138 A Jessen 7/1982 4.338.934 A Spademan 4,338,937 A 7/1982 Lerman 4,367,728 A 1/1983 Mutke 4,369,284 A 1/1983 Chen 4,399,816 A 8/1983 Spangler 4,402,683 A 9/1983 Kopman 4.411.659 A 10/1983 Jensen et al. 4,421,296 A 12/1983 Stephens 1/1984 4,424,833 A Spector et al. 4.428.364 A 1/1984 Bartolo 4,430,081 A 2/1984 Timmermans 4,434,791 3/1984 Darnell 4,436,519 A 3/1984 O'Neill 6/1984 4,454,873 Laufenberg et al. 4,473,067 A 9/1984 Schiff 4.475,548 A 10/1984 Muto 4.485,490 A 12/1984 Akers et al 4,488,877 12/1984 Klein 4.543.088 A 9/1985 Bootman et al. 4,550,713 A 11/1985 Hyman 4,553,537 11/1985 Rosenberg 4,555,242 A 11/1985 Saudagar 4,556,996 A 12/1985 Wallace 4,601,710 A 7/1986 Moll 4,610,665 A 9/1986 Matsumoto et al. 4.626.245 A 12/1986 Weinstein 4,634,424 A 1/1987 O'Bovle 4,634,432 A 1/1987 Kocak 4,644,951 2/1987 Bays 4,649,904 A 3/1987 Krauter 4,653,476 A 3/1987 Bonnet 4,654,030 A 3/1987 Moll et al 4,655,752 A 4/1987 Honkanen et al. 4,673,393 A 6/1987 Suzuki et al. 4,673,394 A 6/1987 Fenton 4,691,942 A 9/1987 Ford 4,714,749 A 12/1987 Hughes et al. 4,738,666 A 4/1988 Fugua 7/1988 Golden 4,755,170 A 4,760,933 A 8/1988 Christner et al.

# US 9,474,519 B2 Page 3

(56)	Referen	nces Cited	5,242,409	A 9/199	Buelna
U.S	. PATENT	DOCUMENTS	5,242,412 5,242,415	A 9/199	Blake, III Kantrowitz et al.
			5,248,304 5,256,150		
4,776,843 A 4,777,943 A		Martinez et al. Chvapil	5,257,973		
4,784,646 A		Feingold	5,257,975	A 11/199	3 Foshee
4,796,629 A		Grayzel	5,259,366 5,261,883		Reydel et al. Hood et al.
4,798,594 A 4,802,694 A	1/1989 2/1989	Hillstead Varoo	5,262,468		
4,808,168 A		Warring	5,263,922		
4,809,679 A	3/1989		5,269,763 5,269,772		
4,828,554 A 4,842,931 A	6/1989	Griffin Zook	5,273,449	A 12/199	Mattis et al.
4,848,575 A	7/1989	Nakamura et al.	5,273,545 D242,226		
4,856,502 A 4,863,430 A		Ersfeld et al. Klyce et al.	D343,236 5,279,575		
4,863,438 A		Gauderer et al.	5,290,310	A 3/199	Makower et al.
4,889,107 A		Kaufman	D346,022 5,299,582		1 Quigley et al. 1 Potts
4,895,565 A 4,897,081 A		Hillstead Poirier	5,300,034		1 Behnke
4,903,710 A		Jessamine et al.	5,300,035		
4,911,974 A 4,915,132 A		Shimizu et al.	5,300,036 5,308,336		
4,915,132 A 4,926,882 A		Hodge et al. Lawrence	5,309,896	A 5/199	1 Moll et al.
4,929,235 A	5/1990	Merry et al.	5,312,391		
4,944,732 A 4,950,222 A		Russo Scott et al.	5,314,417 5,316,541		1 Stephens et al. 1 Fischer
4,950,222 A 4,950,223 A		Silvanov	5,320,611	A 6/199	1 Bonutti et al.
4,984,564 A	1/1991		5,330,437 5,330,486		1 Durman 1 Wilk
4,991,593 A 4,998,538 A		LeVahn Charowsky et al.	5,330,480		Freitas et al.
5,000,745 A		Guest et al.	5,331,975		1 Bonutti
5,009,224 A	4/1991		5,334,143 5,334,646		1 Carroll 1 Chen
5,015,228 A 5,019,101 A		Columbus et al. Purkait et al.	5,336,192		Palestrant
5,026,366 A	6/1991	Leckrone	5,336,708		
5,037,379 A		Clayman et al. Littrell	5,338,313 5,342,315		Mollenauer et al. Rowe et al.
5,041,095 A 5,045,070 A		Grodecki et al.	5,342,385	A 8/199	1 Norelli et al.
D320,658 S	10/1991	Quigley et al.	5,350,364		1 Stephens et al. 1 Wilk
5,071,411 A 5,073,169 A	12/1991 12/1991	Hillstead	5,353,786 5,354,280		Haber et al.
5,074,878 A		Bark et al.	5,360,417	A 11/199	
5,082,005 A		Kaldany	5,364,345 5,364,372		Lowery et al. Danks et al.
5,086,763 A 5,092,846 A		Hathman Nishijima et al.	5,366,446		
5,104,389 A	4/1992	Deem	5,366,478		
5,125,396 A	6/1992		5,368,545 5,375,588		Yoon
5,125,897 A 5,127,626 A	7/1992	Quinn et al. Hilal et al.	5,380,288	A 1/199	Hart et al.
5,129,885 A	7/1992	Green et al.	5,383,861 5,385,552	A 1/199 A 1/199	Hempel et al. Haber et al.
5,141,498 A 5,149,327 A		Christian Oshiyama	5,385,553	A 1/199	Hart et al.
5,156,617 A	10/1992	Reid	5,385,560		Wulf
5,158,553 A 5,159,921 A		Berry et al.	5,389,080 5,389,081		5 Yoon 5 Castro
5,161,773 A	11/1992	Hoover Tower	5,391,153	A 2/199	5 Haber et al.
5,167,636 A		Clement	5,391,156 5,395,367		5 Hildwein et al. 5 Wilk
5,167,637 A 5,176,648 A		Okada et al. Holmes et al.	5,403,264		Wohlers et al.
5,176,662 A		Bartholomew et al.	5,403,336		Kieturakis et al.
5,176,697 A		Hasson et al.	5,407,433 5,411,483		5 Loomas 5 Loomas
5,178,162 A 5,180,365 A	1/1993 1/1993	Ensminger et al.	5,413,571	A 5/199	Katsaros et al.
5,183,471 A	2/1993	Wilk	5,423,848		
5,188,595 A 5,188,607 A	2/1993 2/1993	Jacobi Wu	5,429,609 5,431,676		
5,188,007 A 5,192,301 A		Kamiya et al.	5,437,683	A 8/199	Neumann et al.
5,197,955 A	3/1993	Stephens et al.	5,439,455		
5,207,656 A 5,209,737 A		Kranys Rirchart et al.	5,441,486 5,443,452		Yoon Hart et al.
5,211,370 A		Powers	5,456,284	A 10/199	5 Ryan et al.
5,211,633 A		Stouder, Jr.	5,460,170		Hammerslag
5,213,114 A 5,226,890 A		Bailey, Jr. Ianniruberto et al.	5,460,616 5,468,248		Weinstein et al. Chin et al.
5,234,455 A		Mulhollan	5,476,475		Gadberry
5,241,968 A	9/1993	Slater	5,480,410	A 1/199	Cuschieri et al.
5,242,400 A	9/1993	Blake, III et al.	5,486,426	A 1/199	McGee et al.

# US 9,474,519 B2

Page 4

(56)		Referen	ces Cited	5,743,884			Hasson et al.
	HC	DATENIT	DOCUMENTS	5,749,882 5,755,660		5/1998 5/1998	Hart et al.
	0.5.	PALENT	DOCUMENTS	5,760,117		6/1998	
5,490,8	43 A	2/1996	Hildwein et al.	5,769,783	A		Fowler
5,492,3			Smith et al.	5,782,812			Hart et al.
5,496,2			Vandenbroek et al.	5,782,817			Franzel et al. Nicholas et al.
5,503,1			Luhman et al.	5,782,859 5,788,676		8/1998	
5,507,7 5,508,3		4/1996	Thomason et al.	5,792,119		8/1998	
5,511,5		4/1996		5,795,290			Bridges
5,514,1		5/1996	Mollenauer et al.	5,803,919			Hart et al.
5,514,1			Golub et al.	5,803,921 5,803,923		9/1998	Bonadio Singh-Derewa et al.
5,514,1 5,518,2			Bonutti Sampson	5,807,350		9/1998	
5,520,6			Leveen	5,810,712		9/1998	
5,522,7		6/1996		5,810,721			Mueller et al.
5,522,8		6/1996		5,813,409			Leahy et al.
5,524,6		6/1996		5,814,026 5,817,062		9/1998	Flom et al.
5,526,5 5,531,7			Cartmill Uschold et al.	5,819,375		10/1998	
5,538,5			Dunlap et al.	5,820,555	A		Watkins, III et al.
5,540,6		7/1996		5,820,600			Carlson et al.
5,540,7			Kieturakis et al.	5,830,191 5,832,925			Hildwein et al. Rothrum
5,545,1			Danks et al.	5,836,871			Wallace et al.
5,545,1 5,549,5			Williamson, IV Kronner	5,841,298		11/1998	
5,549,6			Crainich	5,842,971	A	12/1998	
5,554,1			Alvarado	5,848,992			Hart et al.
5,562,6			Davila et al.	5,853,395 5,853,417			Crook et al. Fogarty et al.
5,562,6			Hildwein et al.	5,857,461			Levitsky et al.
5,562,6 5,571,1		10/1996	Nicholas	5,860,995			Berkelaar
5,571,1			Marlow et al.	5,865,728		2/1999	
5,575,7			Bolanos et al.	5,865,729		2/1999	
5,577,9			Zhu et al.	5,865,807 5,865,817		2/1999 2/1999	
5,578,0 5,580,3		11/1996	Pasqualucci et al.	5,871,474			Hermann et al.
5,584,8			Hart et al.	5,876,413		3/1999	
5,601,5			Semertzides	5,879,368		3/1999	
5,601,5			Fogarty et al.	5,882,344		3/1999	Stouder, Jr.
5,603,7			Smith et al.	5,884,639 5,894,843		3/1999 4/1999	Chen Benetti et al.
5,607,4 5,620,4			Kieturakis et al. Lucey et al.	5,895,377	A	4/1999	Smith et al.
5,620,4			Kriesel	5,899,208		5/1999	Bonadio
5,628,7	32 A		Antoon, Jr. et al.	5,899,913		5/1999	
5,632,2			Graether	5,904,703 5,906,577		5/1999 5/1999	Gilson Beane et al.
5,632,9 5,634,9			Goldberg et al. Hermann et al.	5,913,847		6/1999	Yoon
5,634,9			Linden et al.	5,916,198	A	6/1999	
5,634,9	37 A		Mollenauer et al.	5,916,232		6/1999	
5,636,6		6/1997		5,919,476 5,931,832		7/1999 8/1999	Fischer et al.
5,640,9 5,643,3			Leahy et al. Mollenauer	5,947,922		9/1999	
5,649.5		7/1997		5,951,467			Picha et al.
5,651,7	71 A		Tangherlini et al.	5,951,588		9/1999	Moenning
5,653,7			de la Torre et al.	5,957,888 5,957,913		9/1999	Hinchliffe de la Torre et al.
5,657,9			Hinchliffe et al.	5,962,572		9/1999 10/1999	Chen
5,658,2 5,658,3			Hasson Kieturakis et al.	5,964,781		10/1999	Mollenauer et al.
5,662,6			Blake, III	5,976,174		11/1999	Ruiz
5,672,1	68 A	9/1997	de la Torre et al.	5,989,232		11/1999	
5,681,3			Lunsford et al.	5,989,233 5,989,266		11/1999 11/1999	
5,683,3 5,685,8		11/1997	Christy Green et al.	5,993,471		11/1999	Riza et al.
5,685,8		11/1997	Negus et al.	5,993,485		11/1999	
5,697,9		12/1997	Brimhall	5,994,450		11/1999	Pearce
5,707,7			Rothrum et al.	5,997,515		12/1999	de la Torre et al.
5,709,6			Vandenbroek et al.	6,004,303 6,010,494		12/1999 1/2000	Peterson Schafer et al.
5,713,8 5,713,8			Heruth et al. Morejon	6,017,355		1/2000	
5,720,7			Blake, III	6,018,094		1/2000	
5,725,5			Oberlin et al.	6,024,736		2/2000	de la Torre et al.
5,728,1			Picha et al.	6,025,067		2/2000	
5,730,7			Fogarty et al.	6,033,426		3/2000	
5,735,7			Alexander et al.	6,033,428		3/2000	
5,738,6 5,741,2			Sierocuk et al. Aboul-Hosn	6,035,559 6,042,573		3/2000	Freed et al.
5,741,2			MacLeod	6,045,535			Ben Nun
5,171,2		., 1000		-,,		2000	

# **US 9,474,519 B2**Page 5

(56)	Referen	ces Cited	6,578,577			Bonadio et al.
U.S. I	PATENT	DOCUMENTS	6,579,281 1 6,582,364 1	B2	6/2003 6/2003	Palmer et al. Butler et al.
6,048,309 A	4/2000	Flom et al.	6,589,167 1 6,589,211 1		7/2003 7/2003	Shimomura et al. MacLeod
6,050,871 A	4/2000		6,607,504	B2		Haarala et al.
6,053,934 A		Andrews et al.	6,613,952 1 6,623,426 1		9/2003	Rambo Bonadio et al.
6,059,816 A 6,066,117 A		Moenning Fox et al.	6,627,275	В1	9/2003	Chen
6,068,639 A		Fogarty et al.	6,663,598 1 6,669,674 1		2/2003	Carrillo et al. Macoviak et al.
6,076,560 A 6,077,288 A		Stahle et al. Shimomura	6,676,639	B1	1/2004	Ternström
6,086,603 A		Termin et al.	6,702,787 1 6,705,989 1		3/2004 3/2004	Racenet et al. Cuschieri et al.
6,090,043 A 6,099,506 A		Austin et al. Macoviak et al.	6,706,050	B1	3/2004	Giannadakis
6,110,154 A		Shimomura et al.	6,714,298 1 6,716,201		3/2004 4/2004	Ryer Blanco
6,123,689 A 6,142,935 A		To et al. Flom et al.	6,723,044		4/2004	Pulford et al.
6,142,936 A	11/2000	Beane et al.	6,723,088 1 6,725,080 1		4/2004 4/2004	Gaskill, III et al. Melkent et al.
6,149,642 A 6,150,608 A		Gerhart et al. Wambeke et al.	6,793,621	B2		Butler et al.
6,159,182 A	12/2000	Davis	6,794,440		9/2004	Chen Bonadio et al.
6,162,172 A 6,162,196 A		Cosgrove et al. Hart et al.	6,796,940 1 6,797,765 1		9/2004	
6,162,206 A	12/2000	Bindokas	6,800,084			Davison et al.
6,163,949 A 6,164,279 A		Neuenschwander Tweedle	6,811,546 1 6,814,078 1		1/2004	Callas et al. Crook
6,171,282 B1		Ragsdale	6,814,700	B1 1		Mueller et al.
6,183,486 B1 6,197,002 B1		Snow et al. Peterson	6,817,974 1 6,830,578 1			Cooper et al. O'Heeron et al.
6,217,555 B1		Hart et al.	6,837,893	B2	1/2005	Miller
6,217,590 B1		Levinson	6,840,946 6,840,951	B2 B2	1/2005	Fogarty et al. de la Torre et al.
6,224,612 B1 6,228,063 B1	5/2001	Bates et al. Aboul-Hosn	6,846,287	B2	1/2005	Bonadio et al.
6,238,373 B1		de la Torre et al.	6,860,463 1 6,863,674 1			Hartley Kasahara et al.
6,241,768 B1 6,254,533 B1		Agarwal et al. Fadem et al.	6,866,861		3/2005	Luhman
6,254,534 B1		Butler et al.	6,867,253 1 6,869,393 1		3/2005 3/2005	
6,258,065 B1 6,264,604 B1		Dennis et al. Kieturakis et al.	6,878,110			Yang et al.
6,267,751 B1	7/2001	Mangosong	6,884,253 1 6,890,295			McFarlane Michels et al.
6,276,661 B1 6,287,280 B1	8/2001 9/2001	Laird Lampropoulos et al.	6,895,965	B2	5/2005	Scarberry et al.
6,315,770 B1	11/2001	de la Torre et al.	6,902,541 6,902,569		6/2005	McNally et al. Parmer et al.
6,319,246 B1 6,322,541 B2	11/2001 11/2001	de la Torre et al. West	6,908,430	B2	6/2005	Caldwell et al.
6,325,384 B1	12/2001	Berry, Sr. et al.	6,909,220	B2		Chen
6,346,074 B1 6,371,968 B1	2/2002 4/2002	Roth Kogasaka et al.	6,913,609 1 6,916,310		7/2005 7/2005	Yencho et al. Sommerich
6,382,211 B1	5/2002	Crook	6,916,331			Mollenauer et al.
6,383,162 B1 6,391,043 B1	5/2002	Sugarbaker Moll et al.	6,929,637 1 6,936,037 1			Gonzalez et al. Bubb et al.
6,413,244 B1		Bestetti et al.	6,939,296	B2	9/2005	Ewers et al.
6,413,458 B1 6,420,475 B1	7/2002 7/2002	Pearce	6,945,932 1 6,958,037		9/2005	Caldwell et al. Ewers et al.
6,423,036 B1		Van Huizen	6,972,026	B1 1	2/2005	Caldwell et al.
6,440,061 B1 6,440,063 B1		Wenner et al. Beane et al.	6,979,324 1 6,991,602		1/2006	Bybordi et al. Nakazawa et al.
6,443,957 B1	9/2002		6,997,909	B2	2/2006	Goldberg
6,447,489 B1 6,450,983 B1		Peterson Rambo	7,001,397 7,008,377			Davison et al. Beane et al.
6,454,783 B1	9/2002		7,014,628	B2	3/2006	Bousquet
6,464,686 B1		O'Hara et al.	7,033,319 1 7,052,454		4/2006 5/2006	Pulford et al. Taylor
6,468,292 B1 6,482,181 B1		Mollenauer et al. Racenet et al.	7,056,304	B2	6/2006	Bacher et al.
6,485,435 B1	11/2002		7,056,321 1 7,067,583		6/2006 6/2006	Pagliuca et al. Chen
6,485,467 B1 6,488,620 B1		Crook et al. Segermark et al.	7,077,852	B2	7/2006	Fogarty et al.
6,488,692 B1	12/2002	Spence et al.	7,081,089 7,083,626			Bonadio et al. Hart et al.
6,494,893 B2 6,527,787 B1		Dubrul et al. Fogarty et al.	7,093,599	B2	8/2006	Chen
6,533,734 B1	3/2003	Corley, III et al.	7,100,614	B2		Stevens et al.
6,551,270 B1 6,551,276 B1		Bimbo et al. Mann et al.	7,101,353 1 7,105,009			Lui et al. Johnson
6,551,344 B2	4/2003	Thill	7,105,607	B2	9/2006	Chen
6,552,109 B1 6,554,793 B1	4/2003	Chen Pauker et al.	7,112,185 1 7,118,528 1		9/2006	Hart et al.
6,558,371 B2	5/2003		7,118,328		10/2006	
6,569,120 B1	5/2003		7,153,261			Wenchell

# US 9,474,519 B2

Page 6

(56)	Refere	ices Cited		2003/0078478 A1		Bonadio et al.	
U.S	PATENT	DOCUMENTS		2003/0139756 A1 2003/0167040 A1		Brustad Bacher et al.	
				2003/0187376 A1	10/2003		
7,163,510 B2		Kahle et al. Sing et al.		2003/0192553 A1 2003/0225392 A1	10/2003	McMichael et al.	
7,192,436 B2 7,193,002 B2	3/2007			2003/0236505 A1	12/2003	Bonadio et al.	
7,195,590 B2	3/2007	Butler et al.		2003/0236549 A1		Bonadio et al. Ewers et al.	
7,214,185 B1		Rosney et al. Parihar et al.		2004/0015185 A1 2004/0024363 A1		Goldberg	
7,217,277 B2 7,222,380 B2	5/2007			2004/0049099 A1	3/2004	Ewers et al.	
7,223,257 B2		Shubayev et al.		2004/0049100 A1 2004/0054353 A1	3/2004	Butler Taylor	
7,223,278 B2 7,226,484 B2	5/2007 6/2007	Davison et al.		2004/0054535 AT 2004/0063833 AT	4/2004		
7,235,062 B2	6/2007	Brustad		2004/0068232 A1		Hart et al.	
7,235,084 B2		Skakoon et al.		2004/0070187 A1 2004/0072942 A1	4/2004 4/2004		
7,238,154 B2 7,244,244 B2		Ewers et al. Racenet et al.		2004/0073090 A1	4/2004		
7,276,075 B1		Callas et al.		2004/0092795 A1		Bonadio et al.	
7,290,367 B2	11/2007	Chen Bertolero et al.		2004/0092796 A1 2004/0093018 A1		Butler et al. Johnson	
7,294,103 B2 7,297,106 B2		Yamada et al.		2004/0097793 A1	5/2004	Butler et al.	
7,300,399 B2		Bonadio et al.		2004/0106942 A1 2004/0111061 A1		Taylor et al. Curran	
7,316,699 B2 7,331,940 B2		McFarlane Sommerich		2004/0111001 A1 2004/0127772 A1		Ewers et al.	
7,338,473 B2		Campbell et al.		2004/0138529 A1		Wiltshire et al.	
7,344,546 B2	3/2008	Wulfman et al.		2004/0143158 A1 2004/0154624 A1		Hart et al. Bonadio et al.	
7,344,547 B2 7,344,568 B2	3/2008	Piskun Chen		2004/0154624 A1 2004/0167559 A1		Taylor et al.	
7,377,898 B2		Ewers et al.		2004/0173218 A1		Yamada et al.	
7,390,317 B2		Taylor et al.		2004/0215063 A1 2004/0230161 A1	10/2004	Bonadio et al. Zeiner	
7,393,322 B2 7,412,977 B2		Wenchell Fields et al.		2004/0243144 A1	12/2004	Bonadio et al.	
7,445,597 B2	11/2008	Butler et al.		2004/0249248 A1 2004/0254426 A1*		Bonadio et al.	A 6 1D 17/2422
7,473,221 B2 7,481,765 B2		Ewers et al. Ewers	A61B 17/0203	2004/0234420 AT	12/2004	wenchen	600/207
7,401,703 D2	1/2007	Lweis	600/208	2004/0260244 A1		Piechowicz et al.	
7,537,564 B2		Bonadio et al.		2004/0267096 A1 2005/0020884 A1		Caldwell et al. Hart et al.	
7,540,839 B2 7,559,893 B2		Butler et al. Bonadio et al.		2005/0023844 A1 2005/0033246 A1		Ahlberg et al.	
7,578,832 B2		Johnson		2005/0059865 A1		Kahle et al.	
7,645,232 B2		Shluzas		2005/0065475 A1 2005/0065543 A1		Hart et al. Kahle et al.	
7,650,887 B2 7,661,164 B2	2/2010	Nguyen et al. Chen		2005/0080319 A1	4/2005	Dinkler, II et al.	
7,704,207 B2	4/2010	Albrecht et al.		2005/0090713 A1 2005/0090716 A1		Gonzales et al. Bonadio et al.	
7,717,847 B2 7,727,146 B2		Smith Albrecht et al.		2005/0090710 A1 2005/0090717 A1		Bonadio et al.	
7,727,140 B2 7,727,255 B2		Taylor et al.		2005/0096695 A1	5/2005		
7,736,306 B2		Brustad et al.		2005/0131349 A1 2005/0148823 A1*		Albrecht et al. Vaugh	A61B 17/0293
7,749,415 B2 7,753,901 B2		Brustad et al. Piskun et al.				Ü	600/206
7,758,500 B2	7/2010	Boyd et al.		2005/0155611 A1		Vaugh et al.	
7,766,824 B2 7,811,251 B2		Jensen et al. Wenchell et al.		2005/0159647 A1 2005/0192483 A1		Hart et al. Bonadio et al.	
7,811,231 B2 7,815,567 B2		Albrecht et al.		2005/0192598 A1	9/2005	Johnson et al.	
7,837,612 B2		Gill et al.		2005/0197537 A1 2005/0203346 A1		Bonadio et al. Bonadio et al.	
7,841,765 B2 7,850,667 B2	11/2010 12/2010	Gresham		2005/0209510 A1		Bonadio et al.	
7,867,164 B2	1/2011	Butler et al.		2005/0222582 A1*		Wenchell	606/108
7,878,974 B2 7,883,461 B2		Brustad et al. Albrecht et al.		2005/0240082 A1 2005/0241647 A1		Bonadio et al. Nguyen et al.	
7,892,172 B2		Albrecht et al.		2005/0251124 A1	11/2005	Zvuloni et al.	
7,896,889 B2		Mazzocchi et al.		2005/0261720 A1 2005/0267419 A1	11/2005 12/2005	Caldwell et al.	
7,909,760 B2 7,913,697 B2		Albrecht et al. Nguyen et al.		2005/0207419 A1 2005/0277946 A1		Greenhalgh	
7,930,782 B2	4/2011	Chen		2005/0283050 A1		Gundlapalli et al.	
2001/0037053 A1		Bonadio et al.		2005/0288558 A1 2005/0288634 A1		Ewers et al. O'Heeron et al.	
2001/0047188 A1 2002/0002324 A1		Bonadio et al. McManus		2006/0020164 A1	1/2006	Butler et al.	
2002/0010389 A1	1/2002	Butler et al.		2006/0020241 A1		Piskun et al.	
2002/0013542 A1 2002/0016607 A1		Bonadio et al. Bonadio et al.		2006/0030755 A1 2006/0041270 A1		Ewers et al. Lenker	
2002/0016007 A1 2002/0026230 A1		Moll et al.		2006/0047284 A1		Gresham	
2002/0038077 A1		de la Torre et al.		2006/0047293 A1		Haberland et al.	
2002/0072762 A1 2002/0111536 A1		Bonadio et al. Cuschieri et al.		2006/0052669 A1 2006/0084842 A1	3/2006 4/2006	Hart Hart et al.	
2002/0111330 A1 2003/0004253 A1	1/2003			2006/0106402 A1		McLucas	
2003/0028179 A1	2/2003	Piskun		2006/0129165 A1		Edoga et al.	
2003/0040711 A1	2/2003	Racenet et al.		2006/0149137 A1	7/2006	Pingleton et al.	

# US 9,474,519 B2 Page 7

(56) Refer	ences Cited			Kleyman Kleyman
U.S. PATEI	TT DOCUMENTS	2011/007	71462 A1 3/2011	Ewers et al.
2006/0161049 A1 7/20	Hart et al. Beane et al. Butler et al.	2012/009	95297 A1 4/2012	Ewers et al. Dang et al. Brustad
2006/0247498 A1 11/20	16 Wilk 16 Bonadio et al. 16 Butler et al.		FOREIGN PATE	ENT DOCUMENTS
2006/0247500 A1* 11/20	600/208 Voegele A61B 1/32	DE	37 39 532 37 37 131	12/1988
2006/0247586 A1 11/20	16 Hess et al. 16 Voegele et al. 16 Voegele et al.	DE DE DE EP	37 37 121 296 00 939 19828009 0 113 520	5/1989 6/1996 12/1999 7/1984
2006/0247678 A1 11/20	6 Weisenburgh et al. 6 Gill et al.	EP EP	0 142 262	5/1985
2006/0264706 A1 11/20	96 Piskun 96 Voegele et al.	EP	0 517 248 0 537 768	12/1992 4/1993
2007/0004968 A1 1/20	77 Bonadio et al. 17 Bonadio et al.	EP EP	0 807 416 0 849 517	11/1997 6/1998
2007/0088202 A1 4/20	7 Albrecht et al.	EP EP	0950376 1 118 657	10/1999 7/2001
2007/0093695 A1 4/20	7 Albrecht 7 Bonadio et al.	EP EP	1 125 552 1 312 318	8/2001 5/2003
	7 Butler et al. 7 Albrecht	EP EP	1 407 715 2 044 889	4/2004 4/2009
	7 Kahle et al. 7 Frasier et al.	EP	2 272 450 A2	1/2011
2007/0185387 A1 8/20	7 Albrecht et al.	EP FR	2 340 792 1456623	7/2011 9/1966
2007/0208312 A1 9/20	7 Bonadio et al. 7 Norton et al.	GB GB	1151993 1355611	5/1969 6/1974
	7 Vaugh et al. 7 Labombard	GB GB	1372491 1379772	10/1974 1/1975
	7 Williams et al. 8 Piskun	GB GB	1400808	7/1975
2008/0048011 A1 2/20	8 Weller 8 Bonadio et al.	GB	1407023 1482857	9/1975 8/1977
2008/0097163 A1 4/20	8 Butler et al.	GB GB	1496696 2071502	12/1977 9/1981
2008/0255519 A1 10/20	18 Ewers et al. 18 Piskun et al.	GB GB	2255019 2275420	10/1992 8/1994
	8 Albrecht et al. 8 Albrecht et al.	GB IE	2298906 930649	9/1996 9/1993
	9 Norton et al. 9 Bonadio et al.	IE	930650	9/1993
2009/0069837 A1 3/20	9 Bonadio et al. 9 Richard et al.	IE IE	S940150 S940613	2/1994 8/1994
2009/0093752 A1 4/20	9 Richard et al.	IE IE	S940960 S950055	12/1994 1/1995
	9 Ewers et al. 9 Ewers et al.	IE IE	S950266 S75368	4/1995 8/1997
	9 Bonadio 9 Wenchell et al.	IE IE	S960196 S970810	8/1997
2009/0182282 A1 7/20	9 Okihisa 9 Albrecht et al.	IΕ	991010	11/1997 7/2000
2009/0227843 A1 9/20		IE IE	990218 990219	11/2000 11/2000
2009/0326330 A1 12/20	9 Bonadio et al.	IE IE	990220 990660	11/2000 2/2001
2010/0063364 A1 3/20	<ul><li>0 Bonadio et al.</li><li>0 Bonadio et al.</li></ul>	IE JP	990795 10-108868	3/2001 4/1998
	<ul><li>0 Widenhouse et al.</li><li>0 Murray et al.</li></ul>	JP JP	11-290327 2001-61850	10/1999 3/2001
	<ul><li>0 Widenhouse et al.</li><li>0 Racenet</li></ul>	JP	2002-28163	1/2002
2010/0113882 A1 5/20	0 Widenhouse et al. 0 Bonadio et al.	JP JP	02003 235879 A 2004-195037	8/2003 7/2004
2010/0228091 A1 9/20	0 Widenhouse et al.	SU WO	1342485 WO 86/06272	1/1997 11/1986
2010/0228094 A1 9/20	Ortiz et al. Ortiz et al.	WO WO	WO 86/06316 WO 92/11880	11/1986 7/1992
	0 Richard 0 Spiegal et al.	WO WO	WO 92/21292 WO 93/05740	12/1992 4/1993
	<ul><li>0 Ransden et al.</li><li>0 Shelton, IV et al.</li></ul>	WO	WO 93/14801	8/1993
2010/0249694 A1 9/20	0 Choi et al. 0 Widenhouse et al.	WO WO	WO 94/04067 WO 94/22357	3/1994 10/1994
2010/0261975 A1 10/20	0 Huey et al.	WO WO	WO 95/05207 WO 95/07056	2/1995 3/1995
	<ul><li>0 Stellon et al.</li><li>0 Stellon et al.</li></ul>	WO WO	WO 95/22289 WO 95/24864	8/1995 9/1995
2011/0021877 A1 1/20	1 Fortier et al. 1 Okoniewski	WO WO	WO 95/27445 WO 95/27468	10/1995 10/1995
	1 Kleyman	wo	WO 96/36283	11/1996

(56)	Refere	ences Cited	U.S. Appl. No. 11/564,409, filed Nov. 2
	FOREIGN PAT	ENT DOCUMENTS	Instrument Access Device. U.S. Appl. No. 12/108,400, filed Apr.
WO	WO 97/11642	4/1997	Retraction Apparatus and Method. U.S. Appl. No. 12/119,371, filed May
WO	WO 97/32514	9/1997	Retractor With Gel Pad.
WO	WO 97/32515	9/1997	U.S. Appl. No. 12/119,414, filed May
WO	WO 97/42889	11/1997	
WO	WO 98/19853	5/1998	Retractor.
WO	WO 98/35614	8/1998	U.S. Appl. No. 12/358,080, filed Jan. 2
WO	WO 98/48724	11/1998	Instrument Access Device.
WO	WO 99/03416	1/1999	U.S. Appl. No. 12/360,634, filed Jan. 2
WO	WO 99/15068	4/1999	Access Apparatus and Method.
WO	WO 99/16368	4/1999	U.S. Appl. No. 12/360,710, filed Jan. 2
WO	WO 99/22804	5/1999	Access Apparatus and Method.
WO	WO 99/25268	5/1999	U.S. Appl. No. 12/578,422, filed Oct. 13,
WO	WO 99/29250	6/1999	Access System.
WO	WO 00/32116	6/2000	U.S. Appl. No. 12/905,932, filed Oct. 15
WO	WO 00/32117	6/2000	Wound Retractor.
WO	WO 00/32119	6/2000	U.S. Appl. No. 12/960,449, filed Dec.
WO	WO 00/32120	6/2000	Access Apparatus and Method.
WO	WO 00/35356	6/2000	U.S. Appl. No. 12/960,458, filed Dec.
WO	WO 00/54675	9/2000	Access Apparatus and Method.
WO	WO 00/54676	9/2000	U.S. Appl. No. 13/006,727, filed Jan. 14,
WO	WO 00/54677	9/2000	Laparoscopic Device.
WO WO	WO 01/08563	2/2001 2/2001	U.S. Appl. No. 13/008,728, filed Jan.
WO	WO 01/08581 WO 01/26558	4/2001	Retractor With Gel Cap.
WO	WO 01/26559	4/2001	U.S. Appl. No. 13/023,334, filed Feb.
WO	WO 01/20339 WO 01/45568	6/2001	
WO	WO 01/49363	7/2001	Surgical Retractor.
wo	WO 01/91652	12/2001	U.S. Appl. No. 13/031,892, filed Feb.
WO	WO 02/07611	1/2002	Retractor.
WO	WO 02/17800	3/2002	U.S. Appl. No. 13/050,042, filed Mar. 17
WO	WO 02/34108	5/2002	Wound Retractor With Gel Pad.
WO	WO 03/011153	2/2003	U.S. Appl. No. 10/446,365, filed May 28,
WO	WO 03/011551	2/2003	Seal With Inflatable Membrane.
WO	WO 03/026512	4/2003	U.S. Appl. No. 12/004,439, filed Dec. 20
WO	WO 03/032819	4/2003	U.S. Appl. No. 12/004,441, filed Dec. 20,
WO	WO 03/034908	5/2003	Skin Seal With Inflatable Membrane.
WO	WO 03/061480	7/2003	U.S. Appl. No. 12/607,667, filed Oct. 28,
WO	WO 03/077726	9/2003	Skin Seal With Inflatable Membrane.
WO	WO 03/103548	12/2003	U.S. Appl. No. 10/965,217, filed Oct. 1
WO	WO 2004/026153	4/2004	Sealing Device.
WO	WO 2004/030547	4/2004	U.S. Appl. No. 10/981,730, filed Nov.
WO	WO 2004/075730	9/2004	Sealing Device.
WO	WO 2004/075741	9/2004	U.S. Appl. No. 11/246,909, filed Oct. 11
WO WO	WO 2004/075930	9/2004 2/2005	Access Device.
WO	WO 2005/009257 WO 2005/034766	4/2005	U.S. Appl. No. 11/291,089, filed Dec. 1
WO	WO 2005/089661	9/2005	Sealing Device.
WO	WO 2005/039001 WO 2006/040748	4/2006	U.S. Appl. No. 11/486,383, filed Jul.
WO	WO 2006/059318	6/2006	Retractor.
WO	WO 2006/100658	9/2006	U.S. Appl. No. 11/785,752, filed Apr. 19
WO	WO 2007/044849	4/2007	Access Device.
wo	WO 2008/015566	2/2008	U.S. Appl. No. 12/244,024, filed Oct. 2, 20
WO	WO 2008/093313	8/2008	Use in Surgical Procedures.
WO	WO 2008/121294	10/2008	U.S. Appl. No. 12/578,832, filed Oct. 1
WO	WO 2010/045253	4/2010	Access Device for Use in Surgical Proce
WO	WO 2010/082722	7/2010	U.S. Appl. No. 12/706,043, filed Feb. 16,
WO	WO 2010/104259	9/2010	Seal.
0	., 0 2010/10-1259	2/2010	LLS Appl. No. 12/719 341 filed Mar. 8, 29

### OTHER PUBLICATIONS

- U.S. Appl. No. 10/802,125, filed Mar. 15, 2004; Title: Surgical Guide Valve, now abandoned.
- U.S. Appl. No. 10/927,551, filed Aug. 25, 2004; Title: Surgical Access System, now abandoned.
- U.S. Appl. No. 10/695,295, filed Oct. 28, 2003; Title: Surgical Gel Seal.
- U.S. Appl. No. 11/132,741, filed May 18, 2005; Title: Gas-Tight Seal Accomodating Surgical Instruments With a Wide Range of Diameters
- U.S. Appl. No. 11/245,709, filed Oct. 7, 2005; Title: Surgical Access System.
- U.S. Appl. No. 11/330,661, filed Jan. 12, 2006; Title: Sealed Surgical Access Device.

- 29, 2006; Title: Surgical
- 23, 2008; Title: Wound
- 12, 2008; Title: Surgical
- 12, 2008; Title: Surgical
- 22, 2009; Title: Surgical
- 27, 2009; Title: Surgical
- 27, 2009; Title: Surgical
- 3, 2009; Title: Single Port
- 5, 2010; Title: Split Hoop
- 3, 2010; Title: Surgical
- 3, 2010; Title: Surgical
- 2011; Title: Hand Access
- 18, 2011; Title: Wound
- 8, 2011; Title: Circular
- 22, 2011; Title: Wound
- 17, 2011; Title: Split Hoop
- 8, 2003; Title: Screw-Type
- 20, 2007; Title: Skin Seal. 0, 2007; Title: Screw-Type
- 8, 2009; Title: Screw-Type
- 15, 2004; Title: Surgical
- 5, 2004; Title: Surgical
- 1, 2005; Title: Instrument
- 1, 2005; Title: a Surgical
- 14, 2006; Title: Wound
- 9, 2007; Title: Instrument
- 2008; Title: Seal Anchor for
- 14, 2009; Title: Flexible edure.
- 5, 2010; Title: Flexible Port
- U.S. Appl. No. 12/719,341, filed Mar. 8, 2010; Title: Foam Port and Introducer Assembly.
- U.S. Appl. No. 10/895,546, filed Jul. 21, 2004; Title: Laparoscopic Instrument and Cannula Assembly and Related Surgical Method.
- U.S. Appl. No. 10/913,565, filed Aug. 5, 2004; Title: Surgical Device With Tack-Free Gel and Method of Manufacture.
- Dexterity Protractor Instruction Manual by Dexterity Surgical, Inc., dated 1999
- European Patent Office, European Search Report for European Application No. EP 10 18 4681, entitled "Wound Retraction Apparatus and Method",dated Nov. 22, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 4608, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.
- European Patent Office, European Search Report for European Application No. EP 10 18 4648, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.

#### (56) References Cited

### OTHER PUBLICATIONS

European Patent Office, European Search Report for European Application No. EP 10 18 4731, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.

European Patent Office, European Search Report for European Application No. EP 10 18 4661, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.

European Patent Office, European Search Report for European Application No. EP 10 18 4677, entitled "Wound Retraction Apparatus and Method", dated Nov. 22, 2010.

European Patent Office, European Search Report for European Application No. EP 10 18 9325, entitled "Split Hoop Wound Retractor", dated Dec. 14, 2010.

European Patent Office, European Search Report for European Application No. EP 10 18 9327, entitled "Split Hoop Wound Retractor", dated Dec. 14, 2010.

European Patent Office, European Search Report for European Application No. EP 10 18 9328, entitled "Split Hoop Wound Retractor", dated Dec. 15, 2010.

European Patent Office, European Search Report for European Application No. EP 04 00 2888, entitled "Hand Access Port Device", dated Sep. 10, 2004.

European Patent Office, European Search Report for European Application No. EP 04 00 2889, entitled "Hand Access Port Device", dated Sep. 13, 2004.

European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040154, mailed Jan. 30, 2007.

European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040073, mailed Jan. 26, 2007.

European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039905, mailed Jan. 17, 2007.

European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039883, mailed Jan. 31, 2007.

European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039800, mailed Apr. 16, 2007.

European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039799, mailed Mar. 27, 2007.

European Patent Office, European Search Report for European Application No. EP 08253236 dated Feb. 10, 2009.

Horigame, et al., Silicone Rumen Cannula with a Soft Cylindrical Part and a Hard Flange, Journal of Dairy Science, Nov. 1989, vol. 72, No. 11, pp. 3230-3232.

Horigame, et al., Technical Note: Development of Duodoenal Cannula for Sheep, Journal of Animal Science, Apr. 1992, vol. 70, Issue 4, pp. 1216-1219.

International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US04/05484, mailed on Nov. 12, 2004.

International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US01/29682, mailed on Jun. 14, 2002

McSweeney, Cannulation of the Rumen in Cattle and Buffaloes, Australian Veterniary Journal, Aug. 1989, vol. 66, No. 8, pp. 266-268.

Neil Sheehan, Supplemental Expert Report of Neil Sheehan, Re: U.S. Pat. No. 5,741,298, United States District Court for the Central District of California, Civil Action No. SACV 03-1322 JVS, Aug. 9, 2005.

Office Action in co-pending U.S. Appl. No. 12/360,634, dated Jan. 24, 2011 in 12 pages.

Office Action in co-pending U.S. Appl. No. 12/360,710, dated Jan. 24, 2011 in 12 pages.

Technical Note: Development of Duodenal Cannula for Sheep, Faculty of Agriculture and School of Medicine Tohokju University, Sendai 981, Japan, dated 1992.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2004/028250, dated Aug. 29, 2006.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2006/039799, dated Apr. 16, 2008.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2006/039800 dated Apr. 16, 2008.

Yamazaki, et al., Diurnal Changes in the Composition of Abomasal Digesta in Fasted and Fed Sheep, The Tohoki Journal of Agricultural Research, Mar. 1987, vol. 37, No. 3-4, pp. 49-58.

Kagaya, Laparascopic cholecystecomy via two ports, using the "Twin-Port" system, J. Hepatobiliary Pancreat Surg (2001) 8:76-80, dated Feb. 20, 2001.

Declaration of John R. Brustad dated Dec. 10, 2009, submitted in U.S. Appl. No. 11/548,955, including Appendices A-D regarding product sales brochures and production drawings from 2001 and 2005.

International Search Report and Written Opinion for PCT/IE2005/000113, mailed on Feb. 22, 2006.

International Searching Authority-US, International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US04/25511, mailed Nov. 7, 2007.

International Bureau of WIPO, International Report on Patentability for International Application No. PCT/US04/25511, mailed Dec. 6, 2007.

International Search Report and Written Opinion for PCT/IE2007/000050 mailed on Aug. 13, 2007.

The International Searching Authority, the International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US08/63445, mailed Sep. 29, 2008.

The International Searching Authority, The International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US08/063463 mailed Sep. 10, 2008.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2008/063463, entitled "Surgical Retractor", dated Nov. 17, 2009. The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US08/63445, entitled "Surgical Retractor with Gel Pad", dated Nov. 17, 2009.

International Searching Authority—European Patent Office, the International Search Report and Written Opinion for International Application No. PCT/US2011/054266, mailed Feb. 9, 2012.

European Patent Office, European Search Report for European Patent No. 11172709.5, dated Aug. 16, 2011.

European Patent Office, European Search Report for European Patent No. 11172706.1, dated Aug. 16, 2011.


European Patent Office, European Search Report for European Patent No. 12151288, dated Feb. 10, 2012.


European Patent Office, European Search Report for European Patent No. 08755332, dated Apr. 18, 2012.

European Patent Office, Supplementary European Search Report for European Patent Application No. 08755322, dated Apr. 18, 2012. European Patent Office, Supplementary European Search Report for European Patent Application No. 08755336, dated Jun. 15, 2012. Harold W. Harrower, M.D., Isolation of Incisions into Body Cavities, The American Journal of Surgery, vol. 116, pp. 824-826, Dec. 1968

International Searching Authority—European Patent Office, The International Search Report and Written Opinion for International Application No. PCT/US2013/037213, mailed Jul. 3, 2013.

\* cited by examiner













FIG. 3































FIG. 13



































#### HAND ACCESS LAPAROSCOPIC DEVICE

# CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 14/149,497, filed Jan. 7, 2014, which is a continuation of U.S. application Ser. No. 13/006,727, filed Jan. 14, 2011, now U.S. Pat. No. 8,647,265, which is a continuation of U.S. application Ser. No. 12/815,986, filed Jun. 15, 2010, now 10 U.S. Pat. No. 7,878,974, which is a divisional of U.S. application Ser. No. 11/548,955, filed Oct. 12, 2006, now U.S. Pat. No. 7,736,306, which claims the benefit of U.S. Provisional Application No. 60/726,826, filed Oct. 14, 2005; U.S. Provisional Application No. 60/745,730, filed on Apr. 15 26, 2006; U.S. Provisional Application No. 60/803,346, filed on May 26, 2006; U.S. Provisional Application No. 60/803, 965, filed on Jun. 5, 2006; and U.S. Provisional Application No. 60/828,089, filed Oct. 4, 2006, the entire disclosures of which are incorporated herein by reference.

#### BACKGROUND OF THE INVENTION

This application relates substantially to devices and other apparatuses facilitating sealed access with surgical instru- 25 ments, such as a surgeon's hand, across a body wall and into a body cavity.

In several areas of surgery there exists a need to have mechanisms or devices that can seal a body cavity or space, and yet permit the introduction of surgical instruments such as guidewires, endoscopes, and even the hand of a surgeon. Typical of these areas of surgery is laparoscopic surgery that relies on surgical instruments inserted through the abdominal wall to reach an operative site within the abdominal cavity. In order to increase space around the operative site within the cavity, insufflation gases are typically introduced to inflate the cavity and elevate the abdominal wall. This pressurizing of the abdominal cavity is referred to as pneumoperitoneum. In this context, the need to seal the body cavity or space arises from the need to maintain the pneumoperitoneum even when instruments are present.

Trocars have been commonly used to provide instrument access in laparoscopic surgeries. These trocars have included elaborate seal structures having zero seals that prevent escape of the gases in the absence of instruments, 45 and instrument seals that prevent escape of the gases in the presence of instruments. Unfortunately, the instrument seals have been able to accommodate only a narrow range of instrument diameters. Multiple seal pairs had to be provided where wider ranges were desired.

Some instruments, such as the hand of the surgeon, have been too large for trocar access. Under these circumstances, hand-assisted laparoscopic seals have been provided. Such devices have been large, cumbersome, and largely ineffective in providing the required sealing mechanism. Other 55 access devices, such as Touhy-Borst seals, have been used, but only for very small diameter access such as that required by a guidewire.

Each of the prior devices suffers from drawbacks that make the device difficult or cumbersome to use. For 60 example, a Touhy-Borst seal requires two hands to use and does not form a seal when a guidewire or other device is about to be introduced. Present trocar seals and hand-assisted seals require two valves, one forming an instrument seal in the presence of the instrument, and the other forming 65 a zero seal in the absence of the instrument. For example, in hand-assisted devices, elaborate mechanisms have been

2

required to seal around the surgeon's arm. When the arm is removed, a separate zero seal has been required to prevent the escape of blood or insufflation gases.

### **SUMMARY**

The application is directed to a surgical access device that is adapted for disposition relative to an incision in a body wall. The access device facilitates insertion of an instrument therethrough as well as maintenance of a sealing relationship with the instrument. The surgical access device includes a cap that is substantially annular and has an opening therethrough. The surgical access device also includes a gel pad that is coupled to the cap and adapted for insertion of the instrument therethrough. The gel pad covers and seals the entire opening of the cap. The surgical access device further includes a retainer that is substantially annular and adapted for placement against the body wall. Additionally, the surgical access device includes coupling means that are adapted 20 for coupling the cap and the retainer together. The retainer is configured to be coupled to a proximal portion of an elongate sleeve that is adapted to extend through the incision. The retainer is also adapted, together with the elongate sleeve, to retract the incision.

In one aspect, the cap includes at least one gap along the annular perimeter of the cap. The at least one gap creates at least one first end and at least one second end of the cap. The at least one gap facilitates a transition in the cap from a first, larger periphery to a second, smaller periphery. In another aspect, the surgical access device also includes means for maintaining the periphery of the cap at the second, smaller periphery. In another aspect, when the cap is at the first, larger periphery, the retainer may be inserted into or removed from the opening of the cap, and the retainer may be fixedly coupled to the cap by first, transitioning the perimeter of the cap to the second, smaller periphery with the retainer positioned within the opening of the cap, and second, maintaining the periphery of the cap at the second, smaller periphery with the maintaining means. In one aspect, the maintaining means includes a squeeze release buckle fitting configured to couple the at least one first end of the cap to the at least one second end of the cap. The squeeze release buckle fitting includes a first, barbed portion that extends from the at least one first end of the cap and a second, receiver portion that extends from the at least one second end of the cap. The barbed portion and the receiver portion of the squeeze release buckle fitting are configured to engage each other in a mating relationship. In another aspect, the barbed portion of the squeeze release buckle fitting includes a plurality of arms, two of which are resilient and have projections extending therefrom. The receiver portion of the squeeze release buckle fitting has corresponding sidewalls for engaging the projections of the barbed portion, thereby causing the two arms that have the projections to flex toward each other as the arms slide into a channel defined by the receiver and to flex away from each other as the projections clear the ends of the sidewalls and into a fully engaged state. In another aspect, the cap includes at least a first gap and a second gap. The first and second gaps create first and second arc portions of the annular cap, each of which includes first and second ends. The first end of the first arc portion corresponds with the second end of the second arc portion and the second end of the first arc portion corresponds with the first end of the second arc portion. The first end of each of the first and second arc portions has a barbed portion of the squeeze release buckle fitting extending therefrom and the second end of each of the

first and second arc portions has a corresponding receiver portion of the squeeze release buckle fitting extending therefrom. In another aspect, the maintaining means includes a latch that is pivotally coupled proximate the first end of the cap and a latch receiver that is positioned 5 proximate the second end of the cap. In another aspect, the latch receiver includes a channel that is defined by substantially parallel channel walls. The channel is configured to releasably receive the latch. In another aspect, the latch includes a shaft that has an enlarged head positioned at the 10 non-hinged end of the latch. The perimeter of the enlarged head is larger than the perimeter of the shaft. The head of the latch is configured to engage the channel and to be held in the channel. The width of the channel is smaller than the head of the latch. The channel walls are resilient such that 15 the walls flex away from each other during receipt of the head of the latch. In another aspect, the coupling means include at least one latch that is pivotally coupled to the retainer. The at least one latch is configured to engage the cap. The at least one latch includes a projection that extends 20 substantially orthogonally from the at least one latch and is configured to engage the cap. The cap includes at least one engagement portion for receiving the projection on the at least one latch. In another aspect, the at least one latch is coupled to the retainer with a live hinge. In another aspect, 25 the at least one latch includes a plurality of latches that are spaced along the periphery of the retainer. In another aspect, in a first position the at least one latch extends substantially laterally from the periphery of the retainer in a substantially planar relationship with the retainer. After placing the cap on 30 the retainer, the at least one latch is rotated toward the cap to a second position in which the latch engages the cap to couple the retainer to the cap. In another aspect, the retainer includes at least one resilient snap for releasably coupling the retainer to the cap. The at least one snap extends from the 35 outer periphery of the retainer in a substantially perpendicular direction from a substantially planar, annular surface of the retainer. Each of the at least one snaps has a projection extending substantially perpendicular and radially inwardly from the snap. The at least one snap is configured to deflect 40 radially outwardly to slide over a corresponding lip portion of the cap when the cap and retainer are brought together in a mating relationship. The at least one snap is configured to return toward a neutral position after the projection on the at least one snap passes the lip portion of the cap such that the 45 projection of the at least one snap engages a receiver portion of the cap. In another aspect, the planar, annular surface of the retainer is configured to secure the sleeve to the retainer. In another aspect, the retainer includes a sidewall portion adjacent to each of the at least one snaps and on either side 50 of each of the at least one snaps. The cap includes openings disposed along the edges of the cap for receiving the sidewall portions of the retainer. In another aspect, the cap includes at least one snap for releasably coupling the cap to the retainer. The at least one snap extends perpendicularly 55 from the periphery of the cap. The at least one snap is configured to engage with a corresponding lip portion of the retainer. Each of the at least one snaps has a projection extending substantially perpendicular and radially inward from the snap. The at least one snap is configured to deflect 60 radially outwardly such that the projection on the at least one snap slides over the corresponding lip portion of the retainer when the cap and retainer are brought together in a mating relationship. The at least one snap is configured to return toward a neutral position after the projection on the at least 65 one snap passes the lip portion of the retainer such that the projection of the at least one snap engages a lip portion of

4

the retainer. In another aspect, the cap includes an inner cylindrical wall and the gel pad being coupled to the inner cylindrical wall. In another aspect, the gel pad is bonded to the inner cylindrical wall. In another aspect, the gel pad is molded to the cap. In another aspect, the surgical access device also includes a resilient fabric integrated on a surface of the gel pad and coupled to the periphery of the cap. In another aspect, the surgical access device also includes a first fabric integrated on a first surface of the gel pad and coupled to the periphery of the cap, and a second fabric integrated on a second, opposite surface of the gel pad and coupled to the cap. In another aspect, the surgical access device also includes a first fabric coupled to the periphery of the cap and a second fabric coupled to the cap a distance from the first fabric. The space between the first fabric and the second fabric defines a cavity. The gel pad is positioned within the cavity between the first and second fabric. In another aspect, the gel pad includes multi-cusped lobes. Adjacent lobes are configured to seal upon one another. In another aspect, the gel pad includes at least two concentric regions of differing resiliency. The at least two concentric regions include a first, central region having first resiliency and a second, outer region having less resiliency than the first region. In another aspect, the gel pad has more than two concentric regions having differing resiliency with the resiliency of each region decreasing in relation to the increase in distance from the first, central region. In another aspect, the gel pad includes gas-filled pockets arranged substantially around the center of the gel pad. In another aspect, the gel pad includes gas-filled pockets dispersed randomly throughout a region beyond the center of the gel pad.

These and other features of the invention will become more apparent with a discussion of the various embodiments in reference to the associated drawings.

### DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a top perspective view of a hand access laparoscopic device of the present invention;

FIG. 2 depicts a bottom perspective view of the hand access laparoscopic device of FIG. 1;

FIG. 3 depicts a plan view of a gelcap with a gel pad having regions of varying firmness;

FIG. 4 depicts a side view of a gelcap with gel having gas-filled pockets disbursed therein;

FIG. 5 depicts a plan view of a gelcap with gel having gas-filled pockets disbursed therein;

FIG. 6 depicts a plan view of a gelcap with gel having gas-filled pockets disbursed therein;

FIG. 7 depicts a side view of a hand access laparoscopic device including a gelcap with gel having gas-filled pockets disbursed therein:

FIG. 8 depicts a top perspective view of a multiple-piece cap having squeeze release buckle connectors molded into the ends of the pieces forming the cap;

FIG. 9 depicts a top perspective view of one of the pieces of the cap having a male squeeze release buckle connector fitting at one end and a female squeeze release buckle connector fitting at the other end;

FIG. 10 depicts a top perspective view of a cap having a gap with a latch pivotally coupled on one side of the gap and a groove for accepting the latch on the other side of the gap;

FIG. 11 depicts a top perspective view of a cap having latches for releasable coupling the cap to a retainer;

FIG. 12 depicts a side view of the cap of FIG. 11;

FIG. 13 depicts a top perspective view of a hand access laparoscopic device of the present invention including a cap

and a retainer, the retainer having a plurality of snaps for releasably coupling the retainer to the cap;

FIG. 14 depicts a top perspective view of the cap of FIG. 13:

FIG. 15 depicts a top perspective view of the retainer of 5 FIG. 13;

FIG. 16 depicts a section view depicting the interaction between the cap and the retainer of FIG. 13;

FIG. 17 depicts a top perspective view of a hand access laparoscopic device of the present invention including a cap <sup>10</sup> and a retainer, the cap having a plurality of snaps for releasably coupling the cap to the retainer;

FIG. 18 depicts a top perspective view of the cap of FIG. 17;

FIG. **19** depicts a top perspective view of the retainer of <sup>15</sup> FIG. **17**;

FIG. **20** depicts a section view depicting the interaction between the cap and the retainer of FIG. **17**;

FIG. **21** depicts a side view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention <sup>20</sup> ring, with a plurality of stabilizers in the form of strings or tethers extending from the retention ring to the gelcap;

FIG. **22** depicts a side view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, with a plurality of stabilizers in the form of gussets or <sup>25</sup> webs extending from the retention ring to the gelcap;

FIG. 23 depicts a top perspective view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, with a fabric integrated on the surface of the gel pad;

FIG. 24 depicts a partial side view of the hand access laparoscopic device of FIG. 23;

FIG. **25** depicts a top perspective view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, the gelcap having a cavity defined by fabric 35 with the gel pad housed within the cavity; and

FIG. **26** depicts a bottom perspective view of a hand access laparoscopic device having a gelcap, a retainer, a sleeve and a retention ring, with the gel pad having multicusped lobes that seal upon one another.

## DESCRIPTION

In FIGS. 1 and 2, a surgical hand access device 50 according to one aspect of the present invention is shown. 45 The device includes a retainer 52 and a cap 54. The cap 54 and the retainer 52 are both substantially annular and both include an opening therethrough. The retainer 52 is adapted to be placed against a body wall. The retainer 52, in one aspect, is rigid and is associated with and/or capable of being 50 coupled to an elongate sleeve 56. The surgical hand access device 50 is adapted for disposition relative to an incision in a body wall. The surgical hand access device 50 also facilitates insertion of an instrument through the access device and maintenance of a sealing relationship with the 55 instrument.

In one aspect, the elongate sleeve **56** extends through an incision to a point where an attached retention ring **58** contacts the interior portions of the body cavity and provides tension between the retainer **52** outside the body cavity and 60 the retention ring. The retainer **52** in one aspect also supports or otherwise enables a portion of the elongate sleeve **56** to remain outside of the body cavity. Additionally, the retainer **52**, retention ring **58** and elongate sleeve **56** together allow the incision to be retracted and isolated during a surgical 65 procedure. In one aspect, the elongate sleeve **56** and aspects thereof is a wound retractor type device such as described in

6

U.S. patent application Ser. No. 10/516,198, filed Nov. 30, 2004, the disclosure of which is hereby incorporated by reference as if set forth in full herein.

As shown, the retainer 52 and retention ring 58 are circular, but as one skilled in the art would appreciate, they may be of different shapes and sizes. The retainer 52 in one aspect may be either rigid, flexible or a combination of both. The retention ring 58 may be flexible to facilitate insertion into the body cavity. As will be described in more detail, the access device 50 includes coupling means that are adapted for coupling the cap 54 and the retainer 52 together.

A gel pad 60 may be coupled to, attached to, formed or integrated with the cap 54 so that a gas-tight conduit is formed between the cap and the sleeve 56. The gel pad 60 covers and seals the entire opening in the cap 54. In one aspect, the gel pad includes a plurality of intersecting dead-end slits 62, 64 that form an access portion or passage through the gel pad 60. Unlike foam rubber or other similar types of elastic materials, the gel pad 60 provides a gas tight seal around a variety of shapes and sizes of hands or instruments inserted therethrough.

In one aspect, the gel material from which the gel pad 60 is made is an elastomeric gel. Some such gels have been described in U.S. patent application Ser. No. 10/381,220, filed Mar. 20, 2003, the disclosure of which is hereby incorporated by reference as if set forth in full herein. The gel can be prepared by mixing a triblock copolymer with a solvent for the midblocks. The endblocks are typically thermoplastic materials such as styrene and the midblocks are thermoset elastomers such as isoprene or butadiene, e.g., Styrene-Ethylene-Butylene-Styrene (SEBS). In one aspect, the solvent used is mineral oil. Upon heating this mixture or slurry, the midblocks are dissolved into the mineral oil and a network of the insoluble endblocks forms. The resulting network has enhanced elastomeric properties over the parent copolymer. In one aspect, the triblock copolymer used is KRATON G1651, which has a styrene to rubber ratio of 33/67. Once formed, the gel is substantially permanent and, by the nature of the endblocks, processable as thermoplastic elastomers henceforward. The mixture or slurry has a minimum temperature at which it becomes a gel, i.e., the minimum gelling temperature (MGT). This temperature, in one aspect, corresponds to the glass transition temperature of the thermoplastic endblock plus a few degrees. For example, the MGT for the mixture of KRATON G1651 and mineral oil is about 120° C. When the slurry reaches the MGT and the transformation to a gel state takes place, the gel becomes more transparent, thereby providing means for visually confirming when the transformation of the slurry to the gel state is substantially complete and that the gel may be cooled. In addition to triblocks, there are also diblock versions of the materials that may be used where Styrene is present at only one end of the formula, for example, Styrene-Ethylene/Butylene (SEB).

For a given mass of slurry to form into a complete gel, the entire mass of the slurry is heated to the MGT and remains heated at the MGT for sufficient time for the end blocks to form a matrix of interconnections. The slurry will continue to form into gel at temperatures above the MGT until the slurry/gel reaches temperatures at which the components within the slurry/gel begin to decompose or oxidize. For example, when the slurry/gel is heated at temperatures above 250° C., the mineral oil in the slurry/gel will begin to be volatile and oxidize. Oxidizing may cause the gel to turn brown and become oily.

The speed at which a given volume of slurry forms a gel is dependant on the speed with which the entire mass of

slurry reaches the MGT. Also, with the application of temperatures higher than the MGT, this speed is further enhanced as the end block networks distribute and form more rapidly.

The various base formulas may also be alloyed with one 5 another to achieve a variety of intermediate properties. For example, KRATON G1701X is a 70% SEB 30% SEBS mixture with an overall Styrene to rubber ratio of 28/72. It can be appreciated that an almost infinite number of combinations, alloys, and Styrene to rubber ratios can be formulated, each capable of providing advantages to a particular embodiment of the invention. These advantages will typically include low durometer, high elongation, and good tear strength.

It is contemplated that the gel material may also include 15 silicone, soft urethanes and even harder plastics that might provide the desired sealing qualities with the addition of a foaming agent. The silicone material may be of the types currently used for electronic encapsulation. The harder plastics may include PVC, Isoprene, KRATON neat, and other 20 KRATON/oil mixtures. In the KRATON/oil mixture, oils such as vegetable oils, petroleum oils and silicone oils may be substituted for the mineral oil.

Any of the gel materials contemplated could be modified to achieve different properties such as enhanced lubricity, 25 appearance, and wound protection. Additives may be incorporated directly into the gel or applied as a surface treatment. Other compounds may be added to the gel to modify its physical properties or to assist in subsequent modification of the surface by providing bonding sites or a surface charge. 30 Additionally, oil based colorants may be added to the slurry to create gels of different colors.

In one aspect, the mixture/slurry used with the various embodiments of the caps that are described herein are composed of about 90% by weight of mineral oil and about 35 10% by weight of KRATON G1651. From a thermodynamic standpoint, this mixture behaves similar to mineral oil. Mineral oil has a considerable heat capacity and, therefore, at about 130° C. it can take 3 or 4 hours to heat a pound of the slurry sufficiently to form a homogeneous gel. Once 40 formed, the gel can be cooled as quickly as practical with no apparent deleterious effects on the gel. This cooling, in one aspect, is accomplished with cold-water immersion. In another aspect, the gel may be air-cooled. Those familiar with the art will recognize that other cooling techniques that 45 are well known in the art may be employed and are contemplated as within the scope of the present invention.

Many of the properties of the KRATON/oil mixture will vary with adjustments in the weight ratio of the components. In general, the greater the percentage of mineral oil the less firm the mixture; the greater the percentage of KRATON, the more firm the mixture. If the resultant gel is too soft it can lead to excessive tenting or doming of the gelcap during surgery when a patient's abdominal cavity is insufflated. Excessive tenting or doming may cause the slits 62, 64 to 55 open, providing a leak path. Additionally, if the gel is too soft it might not provide an adequate seal. However, the gel should be sufficiently soft to be comfortable for the surgeon while simultaneously providing good sealing both in the presence of an instrument and in the absence of an instrument.

If the slurry is permitted to sit for a prolonged period of time, the copolymer, such as KRATON, and the solvent, such as mineral oil, may separate. The slurry may be mixed, such as with high shear blades, to make the slurry more 65 homogeneous. However, mixing the slurry may introduce or add air to the slurry. To remove air from the slurry, the slurry

8

may be degassed. In one aspect, the slurry may be degassed in a vacuum, such as within a vacuum chamber. In one aspect, the applied vacuum may be 0.79 meters (29.9 inches) of mercury, or about 1.0 atmosphere. The slurry may be stirred while the slurry is under vacuum to facilitate removal of the air. During degassing within a vacuum, the slurry typically expands, then bubbles, and then reduces in volume. The vacuum may be discontinued when the bubbling substantially ceases. Degassing the slurry in a vacuum chamber reduces the volume of the slurry by about 10%. Degassing the slurry helps reduce the potential of the finished gel to oxidize.

Degassing the slurry tends to make the resultant gel firmer. A degassed slurry composed of about 91.6% by weight of mineral oil and about 8.4% by weight of KRATON G1651, an eleven-to-one ratio, results in a gel having about the same firmness as a gel made from a slurry that is not degassed and that is composed of about 90% by weight of mineral oil and about 10% by weight of KRATON G1651, a nine-to-one ratio.

Mineral oil is of a lighter density than KRATON and the two components will separate after mixing, with the lighter mineral oil rising to the top of the container. This separation may occur when attempting to form static slurry into gel over a period of several hours. The separation can cause the resulting gel to have a higher concentration of mineral oil at the top and a lower concentration at the bottom, e.g., a non-homogeneous gel. The speed of separation is a function of the depth or head height of the slurry being heated. The mass of slurry combined with the head height, the temperature at which the gel sets and the speed with which the energy can be transferred to the gel, factor into the determination or result of homogeneous gel versus a non-homogeneous gel.

One aspect of a cap 70 in accordance with the present invention is illustrated in FIG. 3 with a gel pad 72 that differs in texture in specific regions 74-80. For example, in one aspect, the gel pad 72 has a soft occlusive first, central sealing region 74, a second region 76 less resilient than the first region, a third region 78 less resilient than the second region, a fourth region 80 less resilient than the third region, and so-on. More particularly, the gel pad 72 may include more than two concentric regions having differing resiliency with the resiliency of each region decreasing in relation to the increase in distance from the first, central region 74. The progressively less resilient or pliable regions allow positive attachment of the gel pad 72 to a support structure, such as the cap 70, while preserving the desirable occlusive properties of a softer more resilient material at, or about, the central portion of the gel pad.

In one aspect, the gel pad 72 has gradient concentric portions 74-80 in which the gel pad is centrifugally molded or formed. During gel formation, the slurry is mixed in a centrifuge. By rotating the slurry while forming the gel pad 72, density separation is created in which denser triblocks of the slurry migrate towards the circumference of the container holding the spinning slurry and the mineral oil increases in concentration towards the center. In this manner, a firmer gel is formed on the exterior of the finished part and a softer gel is formed in the central portion of the finished part, which is useful in hand access seals for laparoscopic surgery.

In one aspect, a long flat rectangular part is used instead of a thin circular part. There are three conventional axes of rotation associated with the rectangular part. The first axis is through the center of the part normal to the long and short axes of the part. Rotation about the first axis induces a higher

density gel at the ends of the part as will rotating the gel about the short midpoint of the rectangle. However, rotation about the long axis of the rectangle creates higher density gel along the long edges of the rectangle. The rotation can be altered during processing, as in the case of rotational molding, in which the part is rotated about multiple axes during processing. The axis of rotation does not have to intersect a centroid of the part or even be within the part itself.

A reverse texture layout of the gel pad 70 can be achieved by selecting lighter density triblocks and higher density mineral oils. Other components can be added as well, based on the desired effect, including additives such as colorants, inert filler material, different oils, different triblock or diblock copolymers, polymers, plasticizers, decorative items etc.

In one aspect, heavy plastic components **82** are provided with the gel pad **72** or slurry and gravitate toward outer regions of the gel away from the center, leaving the central region **74** with a particular proportion of plastic material and oil. The outer regions **76-80** of the gel pad **72** are denser and contain more heavy plastic material than the central region **74**. When the particular gradient proportions for the gel pad **72** are achieved, rotation is slowed and the gel pad is allowed to cool.

In one aspect, a non-homogenous gel pad with soft gel on 25 one side and a firmer gel on the other is accomplished with density separation over time commensurate with the timing of the energy input into the gel which can vary with the direction of gravity.

In FIGS. 4-7, a cap 90 includes a gel pad 92 with a 30 plurality of gas-filled pockets 94. The pockets 94 may be formed by the presence of lightweight foam or balloons, or by casting or molding the gel around spheres or solid objects of other shapes that are removed after the gel pad 92 has cured. The foam, balloons, spheres or other shapes may be 35 inserted into the mold cavity either prior to or after filling the mold cavity with the slurry. In one aspect, the arrangement of gas-pockets 94 substantially around the center of the gel pad 92 reduces the weight of the gel pad and resistance to the passage of a surgeon's hand or instruments while retaining occlusive properties. An alternative aspect of the gel pad 92 contemplates a more random dispersion of gas pockets 94 throughout the region beyond the center of the gel pad, which reduces the overall weight of the gel pad.

The gel pad or gelcap in various aspects of the present 45 invention may be gamma sterilized. The relative or comparative simplicity of qualifying the sterilization process, for example of gamma versus ethylene oxide, of the gel pad and the device with the gel pad is desirable. However, under gamma sterilization large bubbles can form in the gel pad 50 causing potential cosmetic or aesthetic issues in the sterilized devices. The bubbles are more than 99% room air, so removal of the dissolved air in the slurry is performed prior to forming the slurry into gel. For example, the slurry may be degassed via vacuum, as described above, and turned into 55 gel by heat. Bubbles may still form in the gel during gamma sterilization but disappear in a period of about 24 to 72 hours. In one aspect, the percentage of dissolved gas in the mineral oil at room temperature is about 10%. The removal of the air in the gel has an additional effect of making the gel 60 firmer. This however is counterbalanced by the softening effect on the gel caused by gamma radiation during gamma sterilization.

If the gel pad is to be gamma sterilized, the gel may include about 90% mineral oil by weight and about 10% 65 KRATON by weight. As stated above, degassing the slurry has the effect of making the gel firmer. However, the gamma

10

radiation softens the gel to substantially the same firmness as a gel having about 90% mineral oil by weight and about 10% KRATON by weight that is not degassed and gamma sterilized

In one aspect, cyanoacrylate, e.g., SUPERGLUE or KRAZY GLUE, may be used to bond or otherwise couple or attach the gel pad 60 to the cap 54. The glue may attach to either the rubber or styrene component of the tri-block and the bond is frequently stronger than the gel material itself. In another aspect, a solvent may be used to dissolve the plastics in the cap and the polystyrene in the gel. The solution of solvent is applied to the gel pad and cap in either a spray or dip form. In effect, the solution melts both the plastic of the cap as well as the polystyrene in the gel pad to allow a chemical bond to form between the two, which remains when the solvent evaporates.

Polyethylene can be dissolved in mineral oil and then applied to the gel pad. The mineral oil will not evaporate but will over time absorb into the gel pad and impart a polyethylene layer on the gel pad that may have some beneficial properties.

In one aspect, the gel pad **60** is cast into a DYNAFLEX or KRATON polymer support structure, e.g., the cap **54**. By using KRATON polymer or a similar material in the cap, ring adhesion between the gel pad **60** and the cap **54** can be achieved. The polystyrene in the gel is identified as achieving adhesion with polyphenylene oxide (PPO), polystyrene and other polymers.

In the casting process the gel pad 60 and the cap 54 are heated to a temperature above about 130° C. and held at that temperature for several hours, e.g., about 3 to 4 hours. The temperature used is not sufficient to deform the cap 54.

The cap **54**, in one aspect, includes a polymer, e.g., polyethylene (PE). In one aspect, the polyethylene is a low density polyethylene (LDPE) or high density polyethylene (HDPE), or ultra high molecular weight polyethylene (UHMWPE). In one aspect, the cap **54** may be made of a polymer, such as polycarbonate and may be fabricated by methods including injection molding.

The gel includes mineral oil. PE has a higher molecular weight than mineral oil. PE is dissolved by mineral oil at high temperatures. As such, as the PE and the mineral oil in the gel pad 60 intermix as both are heated to and held at temperatures above about 130° C., a bond between the PE and gel pad is formed.

In one aspect, the cap **54** includes polycarbonate. The polycarbonate of the cap **54** does not form bonds with the gel pad **60** at 130° C. However, by raising the temperature to about 150° C. for a few minutes during casting, bonding occurs between the gel pad **60** and the cap **54**. As such, heating the gel pad **60** and cap **54** to temperatures at which both the polystyrene of the gel and the polycarbonate are simultaneously beyond their melt points allow bonds to form between the gel pad and the cap. Alternatively, the gel pad **60** and cap **54** may be heated to near or at the glass transition temperature of the polycarbonate cap to form the bond between the gel pad and the cap.

Referring to FIGS. 8-10, the cap 100, 130 includes at least one gap 101, 132 along the annular perimeter of the cap. The at least one gap 101, 132 creates at least one first end 103, 134 and at least one second end 105, 138 of the cap 100, 130. The gap 101, 132 facilitates a transition in the cap from a first, larger periphery to a second, smaller periphery. As will be discussed in more detail below, the cap 100, 130 includes means for maintaining the cap at the second, smaller periphery. When the cap 100, 130 is set at the first, larger periphery, the retainer 52 (FIG. 1) may be inserted into or removed

from the opening of the cap. The retainer 52 (FIG. 1) may be fixedly coupled to the cap 100, 130 by transitioning the perimeter of the cap to the second, smaller periphery while the retainer is positioned within the opening of the cap, and maintaining the periphery of the cap at the second, smaller 5 periphery with the maintaining means.

Referring to FIGS. 8-9, the cap 100 incorporates squeeze release buckles 102 molded into or otherwise coupled to the cap. The cap 100 includes a first arc 108 and a second arc 110, the first and second arcs being separated by first and 10 second gaps 101. The first arc 108 has a first barbed portion 112 extending from a first end and adapted to be inserted in a snap fit mating relationship with a second, receiver portion 114 extending from a second end of the second arc 110, thereby coupling the at least one first end 103 of the cap 100 15 to the at least one second end 105 of the cap. Another barbed portion 112 may extend from the first end of the second arc 110, which is operationally inserted in a snap fit mating relationship with another receiver portion 114 extending from the second end 105 of the first arc 108. In another 20 aspect, the first arc 108 has a barbed portion 112 on each end of the arc with the second arc 110 having corresponding receiver portions 114 on each end of the second arc.

With the first and second arcs 108, 110 placed adjacent to each other, such that the first end 103 of the first arc 25 corresponds with the second end 105 of the second arc and the second end 105 of the first arc corresponds with the first end 103 of the second arc, and prior to being snapped together, the arcs define a first, larger periphery to allow placement of a retainer 52 (FIG. 1) between the two arcs. 30 The barbed portions 112 engage with corresponding receivers 114 coupling the arcs together. Each barbed portion has a plurality of resilient arms 122, two of which have projections 124 extending therefrom. Each receiver 114 has corresponding sidewalls 126 for engaging projections 124 from 35 the barbed portion, which causes the arms 122 to flex towards each other as the arms slide into a channel 128 defined by the receiver. As the projections 124 clear the ends of the sidewalls 126, the arms 122 are allowed to flex away from each other. Engagement or contact between the edges 40 of the projections 124 with edges of the end of the sidewall 126 prevents the arcs 108, 110 from being detached from each other. By coupling the two arcs 108, 110 together, the delimited circumference is reduced to a second, smaller periphery to capture or hold the retainer 52 (FIG. 1). Flexing 45 the arms 122 toward each other allows the barbed portions 112 to disengage from the sidewalls of the corresponding receiver 114 and to slide out from the receiver, thereby allowing the arcs 108, 110 to separate and detach from the retainer 52 (FIG. 1).

Although not shown, additional barbed portions and receiver snap engagements may be included in each arc to assist in the coupling between the cap 100 and the retainer 52 (FIG. 1) or allow for other size and shape configurations of the cap and/or retainer. In one aspect, the cap 100 includes 55 a single gap 101 and a single barbed portion 112 and receiver portion 114 is provided. In one aspect the cap 100 having the single barbed portion 112 and receiver portion 114 may be provided with a hinge or pivot on another portion of the arc.

Referring now to FIG. 10, a cap 130 has a gap or opening 60 132 along a portion of the periphery of the cap. A latch 136 is hinged or pivotally coupled to the cap proximate a first end 134 of the opening 132 of the cap 130. Proximate a second, opposite end 138 of the opening 132, a latch receiver, such as an aperture or channel 140 defined by 65 substantially parallel channel walls 142, 144, is configured to releasably receive the latch 136. The latch 136 has a shaft

12

146 coupled to the cap 130 on one end and an enlarged or bulbous head 148 having a perimeter or diameter larger than the perimeter or diameter of the shaft on the non-hinged end of the latch. The head 148 of the latch 136 is configured to be graspable and the latch swung so that the head may engage and be held in the channel 140 defined by the channel walls 142, 144. The width of the channel 140 is smaller than the diameter of the head 148 of the latch 136 and the channel walls 142, 144 are resilient such that the walls flex away from each other during receipt of the head of the latch. Alternatively, or additionally, portions of the head 148 may compress so that the head may be received and held in the channel 140. In one aspect, one or more projections extend from one or both channel walls 142, 144 and engage notches in the head 148, or vice versa, to secure the latch 136 to the channel 140.

In this manner, with the latch 136 open or not engaged with the channel 140, the initial periphery of the cap 130 allows simple placement of the retainer 52 (FIG. 1) within the periphery of the cap. Actuating the latch 136 closes the cap 130 and reduces the size of the periphery delimited by the cap, thereby securing the cap to the retainer 52 (FIG. 1).

Referring back to FIGS. 8-10, with the cap 100, 130 being separable or otherwise disjointed, placement of the respective retainer 52 (FIG. 1) within the inner periphery of the cap is eased. Subsequent joining or recoupling of the cap together secures the retainer and cap to each other. As such, one skilled in the art would recognize that other types of couplings or engagements may be used to couple or join separate portions of the cap and/or the retainer together to close or delimit a periphery to encase or otherwise secure the cap and the retainer together and vice versa. In one aspect, the retainer, or both the retainer and the cap, are separable, having couplings and/or engagements to recouple the separate portions together to secure the cap and retainer to each other.

In FIGS. 11-12, the retainer 150 has one or more latches 152 to releasably couple the retainer to a cap 54 (FIGS. 1 and 2). In one aspect, a plurality of latches 152 is spaced along the periphery of the retainer 150. The latches 152 are hinged or pivotally coupled to the retainer 150 and are spaced along the periphery of the retainer. In one aspect, each of the latches is coupled to the retainer 150 with a live hinge. In a first position, the latches 152 extend laterally from the periphery of the retainer 150 in a substantially planar relationship with the retainer. Each latch 152 has a projection 156 extending substantially orthogonally from the latch. After placing or fitting the cap 54 on the retainer 150 and/or vice versa, the latches 152 are actuated to couple the cap and retainer together. In particular, the latches 152 are rotated toward the cap to a second position in which the latches engage a portion or edge of the cap 54 to couple the retainer to the cap. In one aspect, the engagement portion of the cap 54 is an opening, aperture, notch, step, projection or other similar type of receiver or engagement to secure the projection of the latch 152 to the cap.

In one aspect, one or more of the latches 152 has notches or openings for receiving corresponding projections or protrusions extending laterally from the cap 54 to couple the retainer 150 to the cap. Additionally or alternatively, although not shown, the cap may have one or more latches hinged along the periphery of the cap for engagement with portions or edges of the retainer to releasably couple the cap and retainer together.

Referring now to FIGS. 13-16, the retainer 160 has one or more resilient snaps 162 for releasably coupling the retainer and a cap 164 together. The snaps 162 extend from the outer

periphery or edge of the retainer 160 in a substantially perpendicular direction from a substantially planar, annular surface 166 of the retainer. The planar, annular surface 166 of the retainer 160 secures the sleeve 56 (FIGS. 1 and 2) to the retainer. In one aspect, the surface 166 has projections or 5 hooks to catch and secure the sleeve 56 to the retainer 160 under tension. The edge of the retainer 160 is also slightly raised to assist in the holding of the sleeve 56 and the handling of the retainer.

Multiple snaps 162 may be spaced along the periphery of the retainer 160. In one aspect, portions of the edge of the retainer 160 adjacent to each snap are elevated, thereby forming sidewall portions 167 on either side of each snap. The sidewall portions 167 protect the snaps 162 and strengthen or bolster the coupling between the retainer 160 15 and the cap 164 once coupled together. Additionally, the sidewall portions 167 facilitate handling and coupling the retainer 160 to the cap 164. Corresponding openings or cutouts 169 are disposed along the edges of the cap 164 to receive the sidewall portions 167 of the retainer 160.

Each snap 162 also has a projection 168 extending substantially perpendicular and radially inwardly from the snap. After placing or fitting a cap 164 on the retainer 160 and/or vice versa, both are squeezed together. The snaps 162 are configured to flex or deflect radially outwardly to slide 25 over a corresponding receiver portion 170, such as a lip portion or an edge, of the cap 164 when the cap and retainer are brought together in a mating relationship. The snaps 162 are also configured to return toward a neutral position after the projection 168 on the snaps pass the receiver portion 170 of the cap 164 such that the projection of the snaps engages the receiver portion 170 of the cap. The receiver portion 170 in one aspect has an opening, aperture, notch, step, projection or other similar type of receiver or engagement means to secure the projection 168 of the snap 162 to the cap 164. 35 Alternatively, one or more of the snaps 162 have notches or openings (not shown) for receiving corresponding projections or protrusions (not shown) extending from the cap to secure the snaps of the retainer 160 to the cap 164. The cap 164 and retainer 160 may each be made via injection 40 molding. Additionally, the cap 164 and retainer 160 may each be made of a polycarbonate material.

In one aspect, as shown in FIGS. 17-20, a cap 180 has one or more snaps 182 for releasably coupling the cap to a retainer 184. The snaps 182 extend perpendicularly from the 45 periphery of the cap 180 for engagement with portions 188, such as corresponding lip portions, and/or edges of the retainer 184. Each snap 182 has a projection 186 extending substantially perpendicular and radially inwardly from the snap. After placing or fitting the cap 180 on the retainer 184, 50 both are squeezed together. The snaps 182 flex or deflect radially outwardly to slide over the lip or edge 188 of the retainer 184 when the cap 180 and retainer are brought together in a mating relationship, thereby securing the cap, retainer and sleeve 56 disposed therebetween. Each snap 182 55 is configured to return toward a neutral position after the projection 186 on the snap passes the lip portion 188 of the retainer 184 such that the projection of the snap engages the lip portion of the retainer.

Referring now to FIGS. 1-20, the retainers and caps 60 previously described in one aspect are rigid, thereby providing manufacturing benefits as well as easing the assembly of the device. In one aspect, the caps 54, 70, 90, 100, 130, 164, 180 also incorporate an inner cylindrical wall 172 (see FIG. 14) to which the gel pad 60 is bonded or otherwise 65 coupled or attached to the cap. In this manner, the gel pad 60 attaches to a "skeleton" inside the sleeve 56 and provides a

14

sealing area between the device and the wound, incision and/or body cavity. The coupling or intersection of the sleeve, cap and retainer together also provides another sealing area between the device and the body.

By securing the gel pad 60 to the inner cylindrical wall 172, the thickness of the gel pad and corresponding cap 54, 70, 90, 100, 130, 164, 180 is minimized along with the overall footprint of the device. A reduced thickness and overall size of the device provides a lighter device and allows for easier hand exchanges. With the gel pad thickness reduced and the gel pad being able to be substantially flush or recessed in the cap, the "doming" phenomena produced by gas pressure exerted on the body and device during insufflation is also reduced.

In various aspects (FIGS. 11-20) in accordance with the present invention, the retainer 150, 160 has a raised edge 158, 174 disposed around the outer periphery of the retainer. A raised edge 159, 190, in one aspect, is also disposed around the inner periphery of the retainer 150, 184. The inner periphery defines an opening 157, 192 through which the sleeve extends. The outer raised edge 158, 174 assists in maintaining or securing the releasable coupling between the cap and the retainer. In one aspect, a groove 129 (FIG. 8) extends along the circumference of the cap for receiving the outer raised edge to further enhance the coupling between the cap and retainer. Similarly, the inner raised edge assists in maintaining or securing the releasable coupling between the retainer and the sleeve. The inner raised edge also facilitates the seal between the inner cylindrical wall and/or gel pad, the sleeve and the retainer. In one aspect, notches or spaced valleys or openings 155 (FIG. 11) are disposed along the inner raised edge 159, which facilitates the engagement of the inner cylindrical wall and/or gel pad with the retainer by reducing binding between the components.

Several of the above-described attachments could be modified to integrate the retainer or a retainer like component directly into a sleeve to which the cap is releasably coupled. Similarly, the cap may be integrated directly into the retainer and/or sleeve creating a non-releasable coupling between the components.

In one aspect, casting the gel pad 60 into the cap 54 to form a gelcap 66 includes placing the cap into a mold cavity of a casting mold. The mold cavity may include support for the annular walls of the cap 54. The mold may be made of aluminum, copper, brass, or other mold material having good heat dissipation properties. However, those familiar with the art will recognize that other mold materials having lower heat dissipation properties will produce acceptable parts and these are contemplated as within the scope of the present invention as well.

The mold cavity having the cap 54 is filled with the slurry such that the slurry is in contact with the cap. To facilitate filling voids in the mold cavity with the slurry, the slurry may be preheated, for example, to about 52° C. (125° F.). Preheating the slurry to a temperature below the MGT reduces the viscosity of the slurry and allows the slurry to flow more easily. As stated above, the slurry may have been degassed in a vacuum. The slurry may be degassed again within the mold after the mold cavity is filled to remove air that may have been introduced during the filling of the mold cavity and to facilitate flow of the slurry into voids in the mold. Heat is applied to the mold having the cap 54 and the slurry, such as in an oven, until the slurry attains a temperature of about 150° C. As stated above, the slurry turns into gel at about 120° C., however, at about 150° C., the gel can bond to a polycarbonate cap 54. Depending on the material used to fabricate the cap 54, bonding may take place at

temperatures other than about 150° C. If the cap **54** is fabricated of a material having a lower melting point than 120° C., then the gel pad **60**, such as a gel slug **60**, may be molded separately and then bonded to the cap. The slits **62**, **64** may be molded into the gel pad **60** through the use of an insert in the form of the slit in the mold.

Once the temperature of the gel pad 60 reaches about 150° C., the gelcap 66 may be cooled, such as by air-cooling, cold-water immersion, or other cooling means that are well known in the art. At 150° C. the gel pad is soft and if it were distorted during cooling it would set with the distortion included. To reduce the likelihood of distorting the gel pad 60, the gelcap 66 may be cooled within the mold. Cooling times may vary based on parameters including size and configuration of the mold, quantity of gel, temperature and quantity of cooling medium, cooling medium properties and the mold material. As an example, the cooling time may be about two (2) hours if cooling in air and about fifteen (15) minutes if cooling in water. Whether cooling with air or 20 water, the final properties of the gel are substantially the same. The gelcap 66 is typically cooled to about ambient room temperature, but may be cooled to lower temperatures. If the gelcap 66 is cooled to the freezing point of the gel, about 0° C., then the gel will freeze and become hard. This 25 may be beneficial for other means of coupling the gel pad 60 to the cap 54, such as with a secondary operation. The gelcap 66 may be removed from the mold at any time after the gel

When removed from the mold, the gel pad 60 typically has a tacky surface. The gelcap 66 may be coated with a powder, such as cornstarch, to substantially reduce or eliminate the tackiness of the cured gel pad 60.

As stated above, in another aspect, the gel pad 60 may be  $_{35}$ molded separately from the cap 54 and coupled to the cap 54 by a secondary operation, such as by bonding. In one aspect, the gel pad 60 may be molded into a gel slug 60 having an outer perimeter smaller than the inner cylindrical wall of the cap **54** and to a height higher that the height of the cap. Since 40 the gel pad 60 is being molded separate from the cap 54, the slurry only needs to be heated until it reaches about 120° C. and completes the transformation from slurry into gel and the gel becomes substantially transparent. The gel slug 60 may then be placed within the inner cylindrical wall of the 45 cap 54. The gel slug 60 may be cooled and/or frozen prior to placing it within the inner cylindrical wall of the cap 54. The gel slug 60 may be coupled to the cap 54 through compression molding with the gel slug being compressed longitudinally so that the outer perimeter of the gel slug 50 expands and compresses against the inner cylindrical wall of the cap. The gel slug 60 and cap 54 are heated to a sufficient temperature for the polystyrene of the gel and the polymer of the cap to form bonds between the gel and the cap. Molding the gel slug 60 separately from the cap 54 and heat 55 bonding the gel slug to the cap at a later time is especially useful when the cap is made of a material that has a lower melting temperature than the MGT. In such situations, the gel slug 60 can be molded first and heat bonded to the cap 54 without melting the cap.

In reference to FIGS. 21-22, a cap 54 has the gel pad 60 attached, formed or integrated with the cap and is capable of being coupled to the retainer 52 which is capable of being coupled to the sleeve 56. In one aspect, the elongate sleeve 56 extends through an incision and is attached to a retention 65 ring 58 that contacts the interior portions of the body cavity and provides tension between the retainer 52 outside the

16

body cavity and the deformable retention ring. A plurality of stabilizers 200-206 extends from the retention ring 58 to the gel pad 60.

In one aspect, the stabilizers 200-206 are sized and configured to prevent excessive bulging of the gel pad 60 in response to the elevated body-cavity pressure. The stabilizers 200, 202, in one aspect, include a plurality of strings or tethers that extend from the retention ring 58 and subsequently through or into the gel pad 60. The stabilizers 204, 206 include a plurality of contiguous gel based gussets or webs that extend between the retention ring 58 and the gel pad 60.

With reference to FIGS. 23-24, a cap 54 has a woven or knitted fabric 210 that is stretchable and/or resilient. The fabric 210 is integrated into or attached onto the surface 211 of the gel pad 60 and coupled to the periphery of the cap 54. The fabric 210 provides support to counteract the "doming" or "bowing" of the gel pad 60 or cap 54 under the influence of the internal inflation gas pressure associated with the inflation of the body cavity. In one aspect, a first fabric 212 can be integrated on a first surface 214 of the gel pad 60 and coupled to the periphery of the cap 54 and a second fabric 216 can be integrated on a second, opposite surface 218 and coupled to the cap. In this manner, counteracting support is provided in both directions to minimize uncontrolled deformation of the gel pad as a hand or instrument is placed through or withdrawn.

In FIG. 25, a first fabric 220 is coupled to the periphery of the cap 54 and a second fabric 222 is coupled to the cap a distance from the first fabric. A cavity 224 is defined by the space between the first fabric 220 and the second fabric 222. The gel pad 60 may be inserted into the cavity 224 or otherwise held within the cavity. The gel pad 60 may be processed alone and formed to a preferred shape and size and firmness prior to coupling to the cap 54. The temperatures commonly required to process SEBS may substantially deform associated plastic structures. Therefore, separate processing and subsequent assembly may be useful for constructing a cap with the gel pad.

Referring to FIG. 26, the gel pad 60 has multi-cusped lobes 230 that seal upon one another. The channel 232 through which a surgeon's hand or instruments may be inserted through is formed between individual lobes of the gel pad 60.

Accordingly, the present invention provides a hand access device and methods thereof. Although this invention has been described in certain specific embodiments, many additional modifications and variations would be apparent to those skilled in the art. It is therefore to be understood that this invention may be practiced otherwise than specifically described, including various changes in the size, shape and materials, without departing from the scope and spirit of the present invention. Thus, embodiments of the present invention should be considered in all respects as illustrative and not restrictive. The scope of the present invention is to be determined by the appended claims and their equivalents rather than the foregoing description.

The invention claimed is:

1. A surgical access device adapted for disposition relative
60 to an incision in a body wall, the access device facilitating
insertion of an instrument therethrough and maintenance of
a sealing relationship with the instrument, comprising:

- a cap, the cap being substantially annular and having an opening therethrough;
- a gel pad coupled to the cap and adapted for insertion of the instrument therethrough, the gel pad covering and sealing the entire opening in the cap;

a retainer, the retainer being substantially annular and adapted for placement against the body wall; and coupling means adapted for coupling the cap and the

retainer together,

- wherein the retainer being configured to be coupled to a 5 proximal portion of an elongate sleeve that is adapted to extend through the incision, and the retainer being adapted together with the elongate sleeve to retract the incision;
- wherein the gel pad comprises of gel material with 10 different regions of resiliency and gas-filled pockets dispersed within the gel material and the different regions of resiliency of the gel material; and
- wherein the disbursement of gas-filled pockets within the gel material is largest at a first region of the gel pad 15 relative to other regions of the gel pad.
- 2. The surgical access device of claim 1 wherein the gel pad has a center and the first region of the gel pad is at the center of the gel pad.
- 3. A surgical access device adapted for disposition relative 20 to a body wall, the access device facilitating insertion of an instrument therethrough and maintenance of a sealing relationship with the instrument, comprising:

a cap defining an opening; and

- a gel pad disposed across the opening of the cap, the gel 25 pad sealing the opening in the cap and forming a seal in the presence of an instrument inserted therethrough and a seal in the absence of an instrument inserted therethrough, the gel pad including a plurality of regions of differing resiliency, the plurality of regions 30 comprising at least a first region and a second region, the first region having at least one of a higher concentration of mineral oil than the second region or a lower density of a triblock copolymer than the second region.
- pad comprises a plurality of intersecting dead-end slits.
- 5. The surgical access device of claim 3 wherein the gel pad including gas-filled pockets dispersed throughout the gel pad.
- 6. The surgical access device of claim 3 wherein the cap 40 has a first state defining a first annular perimeter and a second state defining a second annular perimeter smaller than the first annular perimeter of the cap, the gel pad being relaxed in the first state and compressed by the cap in the second state.
- 7. The surgical access device of claim 3 wherein the cap includes at least one gap along the cap, the at least one gap creating at least one first end and at least one second end of the cap in which the gel pad couples to the at least one first end of the cap to the at least one second end of the cap.
- 8. The surgical access device of claim 3 wherein the cap further comprises a buckle fitting arranged to couple the at least one first end of the cap to the at least one second end of the cap closing the at least one gap.

18

- 9. The surgical access device of claim 3 wherein the cap further comprises a latch pivotably coupled to the cap.
- 10. The surgical access device of claim 3 further comprising a retractor comprising a proximal end; a distal end; and a retention ring at the distal end of the retractor, wherein the retention ring is deformably insertable through an opening into a body cavity; and an elongate sleeve extending proximally from the retention ring, the cap being removably coupled to the proximal end of the retractor.
- 11. The surgical access device of claim 3 further comprising a fabric disposed above and below the gel pad and connected to the cap.
- 12. A surgical access device adapted for disposition relative to a body wall, the access device facilitating insertion of an instrument therethrough and maintenance of a sealing relationship with the instrument, comprising:

a cap defining an opening;

- a gel pad entirely consisting of gel material sealing the opening of the cap and forming a seal in the presence of an instrument inserted therethrough and a seal in the absence of an instrument inserted therethrough, the gel material including a plurality of regions of differing resiliency;
- wherein the plurality of regions comprises at least a first region and a second region, the first region having a higher concentration of mineral oil than the second region.
- 13. The surgical access device of claim 12 wherein the gel pad comprises a plurality of intersecting dead-end slits.
- 14. The surgical access device of claim 12 wherein the cap further comprises a latch pivotably coupled to the cap.
- 15. A surgical access device adapted for disposition 4. The surgical access device of claim 3 wherein the gel 35 relative to a body wall, the access device facilitating insertion of an instrument therethrough and maintenance of a sealing relationship with the instrument, comprising:
  - a cap defining an opening;
  - a gel pad entirely consisting of gel material sealing the opening of the cap and forming a seal in the presence of an instrument inserted therethrough and a seal in the absence of an instrument inserted therethrough, the gel material including a plurality of regions of differing resiliency;
  - wherein the cap includes at least one gap along the cap, the at least one gap creating at least one first end and at least one second end of the cap in which the gel pad couples to the at least one first end of the cap to the at least one second end of the cap;
  - wherein the cap further comprises a buckle fitting arranged to couple the at least one first end of the cap to the at least one second end of the cap closing the at least one gap.



专利名称(译)	手进入腹腔镜装置		
公开(公告)号	<u>US9474519</u>	公开(公告)日	2016-10-25
申请号	US14/681292	申请日	2015-04-08
[标]申请(专利权)人(译)	应用医疗资源		
申请(专利权)人(译)	应用医疗资源CORPORATION		
当前申请(专利权)人(译)	应用医疗资源CORPORATION		
[标]发明人	BRUSTAD JOHN ALBRECHT JEREMY HILAL NABIL JOHNSON GARY HART CHARLES		
发明人	BRUSTAD, JOHN ALBRECHT, JEREMY HILAL, NABIL JOHNSON, GARY HART, CHARLES		
IPC分类号	A61B1/32 A61B17/02 A61B17/34	A61B17/00	
CPC分类号	A61B17/0293 A61B17/02 A61B17 A61B90/40 A61B17/3439 A61B17 /347 A61B2017/3419 A61B2050/0	/3496 A61B2017/00477 A61B2	2017/00526 A61B2017/0287 A61B2017
优先权	60/726826 2005-10-14 US 60/803965 2006-06-05 US 60/745730 2006-04-26 US 60/828089 2006-10-04 US 60/803346 2006-05-26 US		
其他公开文献	US20150209076A1		
外部链接	Espacenet USPTO		

## 摘要(译)

本申请涉及一种手动进入腹腔镜检查装置,其具有胶囊,保持器,套管和保持环。 gelcap包括与帽结合的凝胶。帽包括内圆柱形壁,凝胶结合到该内圆柱形壁上,从而在装置和体壁中的伤口之间提供密封区域。通过将凝胶固定到内圆柱壁上,凝胶和相应帽的厚度随着装置的整体占地面积而最小化。随着凝胶厚度减小并且能够基本上齐平,通过吹入患者腹部产生的"隆起"现象减少。

