



US 20080283577A1

(19) **United States**(12) **Patent Application Publication**
Boyden et al.(10) **Pub. No.: US 2008/0283577 A1**(43) **Pub. Date: Nov. 20, 2008**(54) **STEERABLE SURGICAL STAPLER**

(75) Inventors: **Edward S. Boyden**, Cambridge, MA (US); **Roderick A. Hyde**, Redmond, WA (US); **Muriel Y. Ishikawa**, Livermore, CA (US); **Eric C. Leuthardt**, St. Louis, MO (US); **Nathan P. Myhrvold**, Medina, WA (US); **Dennis J. Rivet, II**, St. Louis, MO (US); **Michael A. Smith**, Phoenix, AZ (US); **Clarence T. Tegreene**, Bellevue, WA (US); **Thomas A. Weaver**, San Mateo, CA (US); **Charles Whitmer**, North Bend, WA (US); **Lowell L. Wood, JR.**, Bellevue, WA (US); **Victoria Y.H. Wood**, Livermore, CA (US)

Correspondence Address:

SEARETE LLC**CLARENCE T. TEGREENE****1756 - 114TH AVE., S.E., SUITE 110****BELLEVUE, WA 98004 (US)**


(73) Assignee: **Searete LLC, a limited liability corporation of the State of Delaware**

(21) Appl. No.: **11/804,219**(22) Filed: **May 16, 2007****Publication Classification**

(51) **Int. Cl.**
A61B 17/04 (2006.01)
A61B 17/00 (2006.01)

(52) **U.S. Cl.** **227/181.1; 606/207**(57) **ABSTRACT**

Embodiments include a surgical device and a method. An embodiment of the surgical instrument includes at least one grasping jaw, the at least one grasping jaw being adapted to deliver surgical staples by a force generated from a force generator mechanism that is contained within the at least one grasping jaw or is in a proximity to the at least one grasping jaw. Another embodiment includes at least one grasping jaw, at least one delivery mechanism adapted to deliver surgical fasteners, the delivery mechanism being located in a proximity to or contained within the at least one grasping jaw, the surgical fasteners containing at least one shape-transforming material, at least one sensor, at least one chemical tissue sealant and at least one cutter. A method includes: grasping a body organ/tissue with at least one grasping jaw, adjusting a configuration of the grasping in response to a signal or a datum or an image, and releasing a surgical staple/fastener in response to the signal, datum or image.






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7






FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15





FIG. 16







FIG. 18







FIG. 19

FIG. 20






FIG. 22




FIG. 23





FIG. 24

FIG. 25





FIG. 26



STEERABLE SURGICAL STAPLER**TECHNICAL FIELD**

[0001] The present application relates, in general, to devices, methods and/or systems for treatment and/or management of disease, disorders, or conditions.

SUMMARY

[0002] An embodiment of a surgical instrument comprises a surgical stapler. In one embodiment, the surgical stapler comprises at least one grasping jaw, the at least one grasping jaw being adapted to deliver surgical staples by a force generated from a force generator mechanism that is contained within the at least one grasping jaw or is in a proximity to the at least one grasping jaw. In a further embodiment, the at least one grasping jaw is configured to movably operate in an opposing manner with respect to at least one other grasping jaw. In another embodiment, at least one grasping jaw is configured to operably mate with at least one other grasping jaw. In yet another embodiment, at least one grasping jaw is configured to serve as an anvil for forming an interaction surface between at least one surgical staple and bodily tissues, the forming being facilitated by reversible mating and unmating of the anvil with an opposite grasping jaw. Furthermore, at least one grasping jaw may form an annular grasp around a body organ/tissue.

[0003] In one embodiment, the surgical stapler has a force generated from a force generator mechanism is communicated to a medium resulting in the release of at least one surgical staple. The force may further result in delivery of one or more linear rows of surgical staples. The force generating mechanism may further include at least one of a pressurized gas canister/cartridge, a spring, a lever, an explosive charge, a piezoelectric actuator, an electric motor, an electroactive polymer and/or a solenoid.

[0004] In another embodiment, the surgical stapler comprises at least one energy module. The energy module may include at least one of a battery, a capacitor, a fuel cell, a mechanical energy storage device, and/or a fluid energy storage device. Furthermore, the energy module may be located in proximity to at least one grasping jaw and/or within at least one grasping jaw. In a further embodiment, the energy module transmits energy through a medium containing at least one of the following: a wire, a tube, an optical fiber and/or a waveguide. Alternatively, the energy module transmits energy through a wireless device.

[0005] In one embodiment, the surgical stapler may include a flexually deformable and steerable shaft connected to at least one grasping jaw. The shaft may contain at least one shape-transforming material, which may include a shape memory alloy. In other embodiments, the shape memory alloy includes at least one of the following components: titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. The shape memory alloy may also include Nitinol™ and/or an electroactive polymer. Furthermore, at least one shape-transforming material includes at least one mechanically reconfigurable material. In an embodiment, the surgical instrument further comprises at least one sensor. At least one sensor may be disposed in at least one grasping jaw of the surgical instrument. Alternatively, the at least one sensor may be disposed in proximity to at least one grasping jaw. In one embodiment, the at least one sensor includes an image-acquisition device.

The image-acquisition device may include at least one of the following: a camera, a charge coupled device, an X-ray receiver, an acoustic energy receiver, a photodetector, an electromagnetic energy receiver and/or an imaging device.

[0006] In an embodiment of the surgical stapler, the sensor includes an illumination device that is operably coupled to at least one image-acquisition device. In a further embodiment, the image-acquisition device is wirelessly coupled to at least one visual display. The at least one sensor may include a data-transmission device. In yet another embodiment, at least one sensor includes a proximity detector. The proximity detector may be adapted to detect proximity of a biological tissue to the surgical instrument. In an embodiment, the proximity detector includes an electromagnetic energy emitter and/or an electromagnetic energy receiver. In yet another embodiment, proximity detector includes an acoustic energy emitter and an acoustic energy receiver. In another embodiment, the proximity detector includes a point source emitter and/or a source illuminator. In an alternative embodiment, point source emitter and/or a source illuminator is operably coupled to at least one image acquisition device. The point source emitter and/or a source illuminator may include at least one of an ultrasonic source, an acoustic source, a visible source, an ultraviolet source, a gamma ray source, an X-ray source and/or an infrared source. Furthermore, the point source and/or source illuminator, may be operably configured within a grasping jaw of the surgical instrument. In one embodiment, the proximity detector includes a communication medium for communication with at least one image display. In another embodiment, the proximity detector may also include at least one image-transmission device and/or one data-transmission device. In yet another embodiment, the proximity detector is wirelessly coupled to at least one image display.

[0007] In an embodiment, at least one sensor provides a feedback signal, a datum or an image to a human or robotic user. Furthermore, at least one sensor provides a force feedback signal to a force generator mechanism. Another embodiment provides at least one sensor that communicates a signal, a datum or an image regarding status of the number of staples in the surgical instrument. Furthermore, at least one sensor may provide a signal, a datum or an image regarding functional status or malfunction status of the surgical instrument.

[0008] In another embodiment, the surgical instrument further comprises at least one cutter. In yet another embodiment the cutter may be an optical cutter and/or a laser-mediated cutting device and/or an electro-thermal cutting device. In a further embodiment, at least one cutter may include a blade, a knife and/or an edge. An embodiment provides that at least one cutter is operably coupled to at least one grasping jaw.

[0009] The surgical instrument may be further configured to deliver a chemical tissue sealant. The chemical tissue sealant may be housed inside at least one grasping jaw. An embodiment provides that the chemical tissue sealant be a biocompatible and/or a biodegradable sealant. Furthermore, the chemical sealant is delivered in a proximity to at least one staple, and is preferably delivered between at least two adjacent layers of body tissue. In some embodiments, surgical staples may include fasteners, pins and/or ties.

[0010] An embodiment of the surgical instrument provides at least one grasping jaw. In another embodiment, the at least one grasping jaw comprises a delivery mechanism adapted to deliver surgical fasteners. In an embodiment, the delivery

mechanism may be located in a proximity to at least one grasping jaw. In an alternative embodiment, the delivery mechanism may be contained within at least one grasping jaw. Furthermore, the surgical fasteners may contain at least one shape-transforming material. The surgical instrument may optionally include at least one sensor. In some embodiments, the at least one grasping jaw is configured to movably operate in an opposing manner with respect to at least one other grasping jaw. In an alternative embodiment, at least one grasping jaw is configured to operably mate with at least one other grasping jaw. In yet another embodiment, at least one grasping jaw is configured to serve as an anvil for forming an interaction surface between at least one surgical fastener and bodily tissues, the forming being facilitated by reversible mating and unmating of the anvil with an opposite grasping jaw. Moreover, at least one grasping jaw may form an annular grasp around a body organ/tissue. In one embodiment, the delivery mechanism utilizes a force generated from a force generator mechanism contained within or in a proximity to at least one grasping jaw. Furthermore, the delivery mechanism results in delivery of one or more linear rows of surgical fasteners. An embodiment provides that the force generated from the force generator mechanism includes at least one of a pressurized gas canister/cartridge, a spring, a lever, an explosive charge, a piezoelectric actuator, an electric motor, an electroactive polymer, a hydraulic force, a pneumatic force, and/or a solenoid.

[0011] An aspect of the invention includes a surgical instrument comprising a flexually deformable and steerable shaft operably connected to at least one grasping jaw having a force generator mechanism that is contained within the at least one grasping jaw or is in a proximity to the at least one grasping jaw. The surgical instrument may further comprise of at least one grasping jaw that is independently maneuverable from an attached shaft and/or sheath. Additionally or alternatively, the flexually deformable and steerable shaft may be enclosed in a bendable and steerable tube or a sheath. Furthermore, in an embodiment, the flexually deformable and steerable shaft may be controllably deformable and steerable to permit a high degree of maneuverability of the surgical instrument. Alternatively or additionally, the flexually deformable and steerable shaft may contain at least one shape-transforming material. In one embodiment, the at least one shape-transforming material contains a shape memory alloy. In another embodiment, the shape memory alloy includes at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. Additionally or alternatively, the at least one shape-transforming material may be preconfigured to a particular application and body part geometry. Furthermore, the at least one shape-transforming material may assume a different shape compared to an original preconfigured shape upon insertion of the surgical instrument into a body to conform to an optimal orientation. The flexually deformable and steerable shaft may include the shape memory alloy Nitinol™. In yet another embodiment, the flexually deformable and steerable shaft may contain at least one shape-transforming material that includes an electro-active polymer. In still another embodiment, the at least one shape-transforming material includes at least one mechanically reconfigurable material. In one embodiment, the flexually deformable and steerable shaft may be controllably deformable and steerable to permit a high degree of maneuverability of the surgical instrument that includes controllable deformation of the shaft that is medi-

ated by at least one of a temperature profile, a pressure profile, an electrical circuitry, a magnetic profile, an acoustic wave profile and/or an electromagnetic radiation profile. The maneuverability of the surgical instrument includes maneuverability around anatomical corners and/or difficult-to-reach anatomical body parts that are normally inaccessible on a straight trajectory. In an embodiment, the flexually deformable and steerable shaft that is being controllably deformable to permit a high degree of maneuverability of the surgical instrument includes bending the shaft in real time to navigate within a body space. In still another embodiment, the flexually deformable and steerable shaft returns to an original shape or configuration for easy removal from a body. In yet another embodiment, the surgical instrument may include at least one grasping jaw having a proximity detector. The proximity detector may be adapted to detect whether a biological tissue is within grasping distance of the grasping jaw. Furthermore, the proximity detector may also be adapted to detect whether a biological tissue is fully grasped by the grasping jaw. In an embodiment, the proximity detector is operably configured to assess whether an entire or a portion of a bodily organ is fully or partly grasped within said grasping jaw. Alternatively or additionally, the grasping jaw may be fully redeployable following at least one grasp-release cycle in a grasping operation of a biological tissue. Additionally or alternately, the surgical instrument may be a surgical stapler that is adapted to deliver biodegradable or non-biodegradable staples, fasteners, pins or ties.

[0012] An aspect of the invention includes a surgical instrument comprising at least one grasping jaw; a force receiver adapted to receive manual force from a user; and an actuation mechanism responsive to the manual force to produce a jaw-laden force without mechanical coupling of the manual force to the grasping jaw. In an embodiment, the surgical instrument further includes the force receiver includes at least one sensor. In yet another embodiment, the at least one sensor is operably coupled to the actuation mechanism. Furthermore, the at least one sensor receives a signal from the actuation mechanism through a wireless medium. In another embodiment, the surgical instrument includes the at least one sensor that transmits a signal to the actuation mechanism through a wireless medium. In still another embodiment, the surgical instrument includes a user-activated sensory-device, tactile-device or audio-sensitive device that transmits a signal to the force receiver. The user-activated sensory, tactile or audio-sensitive device may be a manual trigger, a pushbutton, a latch, a lever, a voice activated device, a touch-sensitive device, a breath-activated device etc. In another embodiment, the surgical instrument includes a jaw-laden force without mechanically coupling the force to the grasping jaw. The force may be carried through a wireless medium, an ether-real medium or other intangible media. In another embodiment, the actuation mechanism converts a manual force from the force receiver into the jaw-laden force. In yet another embodiment, the jaw-laden force results in release of at least one surgical stapler and/or surgical fastener.

[0013] The following embodiments are directed to a surgical instrument that is adapted to deliver surgical fasteners and may contain at least one shape-transforming material and/or at least one sensor.

[0014] In an alternative embodiment of the surgical instrument that is adapted to deliver surgical fasteners, the surgical instrument further comprises at least one energy module that includes at least one of a battery, a capacitor, a fuel cell, a

mechanical energy storage device, and/or a fluid energy storage device. At least one energy module may be located within or in a proximity to the at least one grasping jaw. In an embodiment, least one energy module is located outside the at least one grasping jaw but is within a portion of the surgical instrument. An embodiment provides that at least one energy module is located outside the at least one grasping jaw.

[0015] An embodiment of the surgical instrument that is adapted to deliver surgical fasteners provides that at least one energy module transmits energy through a medium containing at least one of a wire, a tube, an optical fiber and/or a waveguide. Alternately, at least one energy module transmits energy through a wireless device.

[0016] In one embodiment of the surgical instrument that is adapted to deliver surgical fasteners, at least one fastener contains one shape-transforming material. The shape transforming material may contain a shape memory alloy. The shape memory alloy may include at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. Alternatively, the shape memory alloy includes Nitinol™ and/or an electro-active polymer. Alternative embodiments call for at least one shape-transforming material to include at least one mechanically reconfigurable material.

[0017] In an embodiment of the surgical instrument that is adapted to deliver surgical fasteners, the surgical instrument has at least one sensor that is disposed within at least one grasping jaw. Alternatively, at least one sensor may be disposed in a proximity to at least one grasping jaw. In an embodiment, at least one sensor includes an image-acquisition device. The image-acquisition device may include at least one of a camera, a charge coupled device, an X-ray receiver, an acoustic energy receiver, an electromagnetic energy receiver and/or an imaging device. In an embodiment, the image-acquisition device is wirelessly coupled to at least one visual display. The sensor may include an illumination device that is operably coupled to an image-acquisition device. Alternatively, at least one sensor includes a data-transmission device. In an embodiment, the proximity detector is adapted to detect the proximity of a biological tissue to the surgical instrument. In a further embodiment, the proximity detector includes an electromagnetic energy emitter and/or an electromagnetic energy receiver. In yet another embodiment, the proximity detector includes an acoustic energy emitter and an acoustic energy receiver. In an embodiment, the proximity detector includes a point source emitter and/or a source illuminator. The point source emitter and/or a source illuminator, in some embodiment are operably coupled to at least one image acquisition device. Furthermore, the point source emitter and/or a source illuminator include at least one of an ultrasonic source, an acoustic source, a visible source, an ultraviolet source, a gamma ray source, an X-ray source and/or an infrared source. Alternatively or additionally, point source emitter and/or a source illuminator are operably configured within a grasping jaw of the surgical instrument. The proximity detector may include a communication medium for communication with at least one image display. In one embodiment, the proximity detector includes at least one image-transmission device. In a further embodiment, the proximity detector includes at least one data-transmission device. Furthermore, the proximity detector is wirelessly coupled to at least one image display.

[0018] In an embodiment of the surgical instrument that is adapted to deliver surgical fasteners, the surgical instrument

comprises at least one sensor that provides a feedback signal, a datum or an image to a human or robotic user. Additionally, at least one sensor provides a force feedback signal to the delivery mechanism. At least one sensor may provide a signal, a datum or an image regarding status of the number of fasteners in the surgical instrument. Furthermore, at least one sensor provides a signal, a datum or an image regarding functional status or malfunction status of the surgical instrument.

[0019] In another embodiment of the surgical instrument that is adapted to deliver surgical fasteners, the surgical instrument further comprises at least one cutter. Additionally, in some embodiments, at least one cutter is an optical cutter. In a further embodiment, the optical cutter may be a laser-mediated cutting device. The surgical instrument may have at least one cutter that is an electro-thermal cutter. Furthermore at least one cutter may include one of a blade, a knife and/or an edge. In an embodiment, at least one cutter is operably coupled to at least one grasping jaw.

[0020] In an embodiment of the surgical instrument that is adapted to deliver surgical fasteners, the instrument may be further configured to deliver a chemical tissue sealant. In another embodiment, the chemical tissue sealant is housed inside at least one grasping jaw. In an alternative embodiment, the chemical tissue sealant is a biocompatible chemical tissue sealant. Furthermore the sealant may be a biodegradable chemical tissue sealant. Additional embodiments may provide for a chemical tissue sealant that is delivered in a proximity to at least one fastener. Further, the chemical tissue sealant may be delivered between at least two adjacent layers of body tissue.

[0021] In some embodiments of the surgical instrument that is adapted to deliver fasteners, the surgical instrument may deliver surgical fasteners including staples, pins and/or ties. In another embodiment, the surgical instrument may comprise at least one grasping jaw having a curvature that conforms to a body organ/tissue and/or more than two grasping jaws. Further variants of embodiments of the surgical instrument may comprise of a flexually deformable and steerable shaft connected to at least one grasping jaw. In an embodiment, the flexually deformable and steerable shaft contains at least one shape-transforming material. In some embodiments, at least one shape-transforming material contains a shape memory alloy. The shape memory alloy may include at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. In one embodiment, shape memory alloy includes Nitinol™ and/or an electro-active polymer. At least one shape-transforming material may include at least one mechanically reconfigurable material in an embodiment of the surgical instrument.

[0022] An aspect of a surgical instrument may comprise at least one grasping jaw and at least one delivery mechanism that may be adapted to deliver surgical fasteners. Furthermore, the delivery mechanism may be located in a proximity to or may be contained within the at least one grasping jaw. Moreover, the surgical fasteners may contain at least one shape-transforming material and/or at least one chemical tissue sealant. In an embodiment, at least one grasping jaw is configured to movably operate in an opposing manner with respect to at least one other grasping jaw. Furthermore, at least one grasping jaw is configured to operably mate with at least one other grasping jaw. Additionally, at least one grasping jaw may be configured to serve as an anvil for forming an

interaction surface between at least one surgical fastener and bodily tissues, the forming being facilitated by reversible mating and unmating of the anvil with an opposite grasping jaw. In another embodiment, at least one grasping jaw may form an annular grasp around a body organ/tissue. In yet another embodiment, the delivery mechanism utilizes a force generated from a force generator mechanism contained within or in proximity to at least one grasping jaw. Furthermore, the delivery mechanism results in delivery of one or more linear rows of surgical fasteners.

[0023] The following embodiments are directed to a surgical instrument that is adapted to deliver surgical fasteners and may contain at least one shape-transforming material and/or at least one chemical tissue sealant.

[0024] In one embodiment of the surgical instrument that is adapted to deliver surgical fasteners, the surgical instrument further comprises at least one energy module that includes at least one of a battery, a capacitor, a fuel cell, a mechanical energy storage device, and/or a fluid energy storage device. The force is generated from the delivery mechanism may include at least one of a pressurized gas canister/cartridge, a spring, a lever, an explosive charge, a piezoelectric actuator, an electric motor, an electroactive polymer and/or a solenoid. In a further variant of the embodiment, at least one energy module is located within or in a proximity to at least one grasping jaw. Moreover, at least one energy module may be located outside at least one grasping jaw but within a portion of the surgical instrument. Additionally, in some embodiments at least one energy module may be located outside at least one grasping jaw. At least one energy module may transmit energy through a medium containing at least one of a wire, a tube, an optical fiber and/or a waveguide. Alternatively, at least one energy module may transmit energy through a wireless device.

[0025] In an embodiment of the surgical instrument that is adapted to deliver surgical fasteners, the surgical instrument may include at least one shape-transforming material that contains a shape memory alloy. The shape memory alloy may include at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. In one embodiment, the shape memory alloy may include Nitinol™ and/or electro-active polymer. In another embodiment, at least one shape-transforming material includes at least one mechanically reconfigurable material.

[0026] In one embodiment of the surgical instrument that is adapted to deliver surgical fasteners, the surgical instrument further comprises at least one sensor. The at least one sensor may be disposed within at least one grasping jaw. Furthermore, at least one sensor may be disposed in a proximity to at least one grasping jaw. In one embodiment, at least one sensor includes an image-acquisition device. Furthermore, the image-acquisition device may include at least one of a camera, a charge coupled device, an X-ray receiver, an acoustic energy receiver, an electromagnetic energy receiver and/or an imaging device. In one embodiment, the image-acquisition device may be wirelessly coupled to at least one visual display. In an embodiment, at least one sensor includes an illumination device that is operably coupled to at least one image-acquisition device. In yet another embodiment, at least one sensor includes a data-transmission device.

[0027] Furthermore, the surgical instrument adapted to deliver surgical fasteners includes at least one sensor includes a proximity detector, which may be adapted to detect prox-

imity of a biological tissue to the surgical instrument. Furthermore, the proximity detector includes, in one embodiment, an electromagnetic energy emitter and/or an electromagnetic energy receiver. In other embodiments, the proximity detector includes an acoustic energy emitter and an acoustic energy receiver. The proximity detector may further include a point source emitter and/or a source illuminator.

[0028] An embodiment, the surgical instrument that is adapted to deliver surgical fasteners provides for a point source emitter and/or a source illuminator that is operably coupled to at least one image acquisition device. In another embodiment, the point source emitter and/or a source illuminator includes at least one of an ultrasonic source, an acoustic source, a visible source, an ultraviolet source, a gamma ray source, an X-ray source and/or an infrared source. Here the point source emitter and/or a source illuminator may be operably configured within a grasping jaw of the surgical instrument. The proximity detector may additionally include a communication medium for communication with at least one image display. In one embodiment, the proximity detector includes at least one image-transmission device. In another embodiment, the proximity detector includes at least one data-transmission device. In yet another embodiment, the proximity detector is wirelessly coupled to at least one image display. In an embodiment, at least one sensor provides a feedback signal, which may be a datum or an image to a human or robotic user. In another embodiment, at least one sensor provides a force feedback signal to a force generator mechanism. Furthermore, at least one sensor may provide a signal, a datum or an image regarding status of the number of staples in the surgical instrument.

[0029] In one embodiment, the surgical instrument that is adapted to deliver surgical fasteners, the surgical instrument further comprises at least one cutter. Another embodiment provides at least one cutter is an optical cutter. The optical cutter may include a laser-mediated cutting device. The cutter may include at least one cutter is an electro-thermal cutter in one embodiment. Furthermore, at least one cutter may include one of a blade, a knife and/or an edge. In another embodiment, at least one cutter is operably coupled to at least one grasping jaw.

[0030] In an embodiment, the surgical instrument that is adapted to deliver surgical fasteners includes a chemical tissue sealant is housed inside at least one grasping jaw. In another embodiment, the chemical tissue sealant is a biocompatible chemical tissue sealant and/or a biodegradable chemical tissue sealant. In yet another embodiment, the chemical tissue sealant is delivered in a proximity to at least one fastener. One other embodiment provides for a chemical tissue sealant that is delivered between at least two adjacent layers of body tissue.

[0031] In some embodiments, the surgical instrument that is adapted to deliver surgical fasteners includes the surgical instrument delivers surgical fasteners that include staples, pins and/or ties. The surgical instrument may have at least one grasping jaw that has a curvature that conforms to a body organ/tissue. Furthermore, more than two grasping jaws may be included in the surgical instrument.

[0032] Moreover, the surgical instrument that is adapted to deliver surgical fasteners may comprise a flexually deformable and steerable shaft connected to at least one grasping jaw, and may contain at least one shape-transforming material. In some embodiments, the at least one shape-transforming material contains a shape memory alloy. The shape memory

alloy may include at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. In some embodiments, the shape memory alloy includes Nitinol™ and/or electro-active polymer. In an embodiment, the shape-transforming material includes at least one mechanically reconfigurable material.

[0033] In one aspect, an embodiment of the surgical instrument comprises at least one grasping jaw and/or at least one delivery mechanism adapted to deliver surgical fasteners. The delivery mechanism being located in a proximity to or is contained within at least one grasping jaw. In some embodiments, the surgical fasteners contain at least one shape-transforming material and/or at least one cutter. At least one grasping jaw is configured to movably operate in an opposing manner with respect to at least one other grasping jaw. In another embodiment, at least one grasping jaw is configured to operably mate with at least one other grasping jaw. Furthermore, at least one grasping jaw is configured to serve as an anvil for forming an interaction surface between at least one surgical fastener and bodily tissues, the forming being facilitated by reversible mating and unmating of the anvil with an opposite grasping jaw. In an embodiment, at least one grasping jaw forms an annular grasp around a body organ/tissue.

[0034] The following embodiments are directed to a surgical instrument that is adapted to deliver surgical fasteners and may contain at least one shape-transforming material and/or at least one cutter.

[0035] One embodiment of the surgical instrument adapted to deliver surgical fasteners provides that a delivery mechanism utilizes a force generated from the delivery mechanism contained within or in a proximity to at least one grasping jaw. Another provides that the delivery mechanism results in delivery of one or more linear rows of surgical fasteners. Furthermore, the force is generated from the delivery mechanism that includes at least one of a pressurized gas canister/cartridge, a spring, a lever, an explosive charge, a piezoelectric actuator, an electric motor, an electroactive polymer and/or a solenoid.

[0036] The surgical instrument that is adapted to deliver surgical fasteners further comprises at least one energy module that includes at least one of a battery, a capacitor, a fuel cell, a mechanical energy storage device, and/or a fluid energy storage device. In an embodiment, at least one energy module is located within or in a proximity to at least one grasping jaw.

[0037] Yet another embodiment the surgical instrument that is adapted to deliver surgical fasteners includes at least one energy module that is located outside at least one grasping jaw but within a portion of the surgical instrument. Furthermore, at least one energy module may be located outside at least one grasping jaw. In addition, at least one energy module may transmit energy through a medium containing at least one of a wire, a tube, an optical fiber and/or a waveguide. Alternatively, at least one energy module transmits energy through a wireless device.

[0038] In an embodiment of the surgical instrument that is adapted to deliver surgical fasteners, at least one surgical fastener contains one shape-transforming material, which may include a shape memory alloy. The shape memory alloy may further include at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. Alternatively, shape memory alloy includes Nitinol™ and/or electro-active polymer. An

embodiment may have at least one shape-transforming material that includes at least one mechanically reconfigurable material.

[0039] In an embodiment, the surgical instrument that is adapted to deliver surgical fasteners further comprises at least one sensor. In another embodiment, at least one sensor is disposed within at least one grasping jaw. Yet another embodiment may include at least one sensor that is disposed in a proximity to at least one grasping jaw. Furthermore, at least one sensor may include an image-acquisition device. The image-acquisition device may include at least one of a camera, a charge coupled device, an X-ray receiver, an acoustic energy receiver, an electromagnetic energy receiver and/or an imaging device. Furthermore, the image-acquisition device may be wirelessly coupled to at least one visual display. The sensor may include an illumination device that is operably coupled to at least one image-acquisition device. In an embodiment, at least one sensor includes a data-transmission device. Furthermore, at least one sensor includes a proximity detector. The proximity detector may be adapted to detect proximity of a biological tissue to the surgical instrument. Furthermore, proximity detector may include an electromagnetic energy emitter and/or an electromagnetic energy receiver. In another embodiment, the proximity detector includes an acoustic energy emitter and an acoustic energy receiver. The proximity detector may further include a point source emitter and/or a source illuminator. Additional embodiments may include the point source emitter and/or a source illuminator being operably coupled to at least one image acquisition device. In another embodiment, the point source emitter and/or a source illuminator includes at least one of an ultrasonic source, an acoustic source, a visible source, an ultraviolet source, a gamma ray source, an X-ray source and/or an infrared source. In yet another embodiment, the point source emitter and/or a source illuminator is operably configured within a grasping jaw. Still another embodiment includes a proximity detector that may communicate through a medium with at least one image display. An embodiment provides that the proximity detector includes a communication medium for communication with at least one image display. Furthermore, the proximity detector includes at least one data-transmission device. In another embodiment, the proximity detector is wirelessly coupled to at least one image display. Yet another embodiment, at least one sensor provides a feedback signal, a datum or an image to a human or robotic user. Still another embodiment provides that at least one sensor communicates a force feedback signal to a force generator mechanism. At least one sensor provides a signal, a datum or an image regarding status of the number of staples in the surgical instrument.

[0040] An embodiment, the surgical instrument that is adapted to deliver surgical fasteners has at least one cutter that may be an optical cutter. The optical cutter may be a laser-mediated cutting device. At least one cutter may be an electrothermal cutter. In another embodiment, least one cutter includes one of a blade, a knife and/or an edge. In yet another embodiment, at least one cutter is operably coupled to at least one grasping jaw.

[0041] In an embodiment, the surgical instrument that is adapted to deliver surgical fasteners further comprises a chemical tissue sealant. The chemical tissue sealant may be housed inside at least one grasping jaw. Another embodiment provides that the chemical tissue sealant is a biocompatible chemical tissue sealant. Further embodiments specify that the

chemical tissue sealant is a biodegradable chemical tissue sealant. Still another embodiment provides that the chemical tissue sealant be delivered in a proximity to at least one fastener and is delivered between at least two adjacent layers of body tissue.

[0042] In one embodiment, surgical fasteners include staples, pins and/or ties. The surgical instrument further comprises in an embodiment at least one grasping jaw having a curvature that conforms to a body organ/tissue. Furthermore the surgical instrument comprises more than two grasping jaws. The surgical instrument may further comprise a flexually deformable and steerable shaft connected to at least one grasping jaw. Embodiments of the flexually deformable and steerable shaft may contain at least one shape-transforming material. Furthermore, at least one shape-transforming material contains a shape memory alloy, which may contain at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. The shape memory alloy may include Nitinol™ and/or electro-active polymer and/or at least one mechanically reconfigurable material.

[0043] A further aspect of a surgical instrument involves a method of splicing body organs/tissues. In an embodiment, the method comprises the steps of grasping a body organ/tissue with at least one grasping jaw; adjusting a configuration of the grasping in response to a signal or a datum or an image; and releasing a surgical staple/fastener in response to the signal, datum or image. In another embodiment, the method includes grasping a body organ/tissue includes performing end-to-end anastomosis, side-to-side anastomosis, individual ligation, endoscopic or laparoscopic gastro-intestinal operations which include at least one of a bronchus, a pulmonary artery, a pulmonary vein, a large or small intestine, a stomach, a blood vessel and/or skin. The grasping a body organ/tissue may include aligning the body organs between the at least one grasping jaw in a manner compatible with surgical and/or anastomosis operations. In an embodiment, the grasping operation may include displaying an image of the organ/tissue being grasped. Furthermore, adjusting a configuration of the grasping includes annularly adjusting a grasp around the organs/tissues based on the signal or datum or image. In another embodiment, the releasing of a surgical staple/fastener includes driving a plurality of staple/fasteners into at least one layer of body tissue. In still another embodiment, releasing a surgical staple/fastener includes securing at least one layer of a body tissue with the surgical staple/fastener. In yet another embodiment, releasing a surgical staple/fastener includes deformation of one or more staple/fasteners that undergo a conformational change to close a puncture site. Furthermore, releasing a surgical staple/fastener includes closing at least one or more wound sites. The method may additionally include releasing a surgical staple/fastener and a suitable amount of a chemical tissue sealant that permits wound healing.

[0044] An aspect of a surgical instrument includes a method of splicing body organs/tissues comprising: means for grasping a body organ/tissue; means for adjusting a configuration of the grasping in response to a signal or a datum or an image; and means for releasing a surgical staple/fastener in response to the signal, datum or image.

[0045] In addition to the foregoing, other system aspects are described in the claims, drawings, and text forming a part of the present disclosure. Furthermore, various other method and/or system and/or program product aspects are set forth

and described in the teachings such as text (e.g., claims and/or detailed description) and/or drawings of the present disclosure.

[0046] The foregoing summary is illustrative only and is not intended to be in any way limiting. In addition to the illustrative aspects, embodiments, and features described above, further aspects, embodiments, and features will become apparent by reference to the drawings and the following detailed description.

BRIEF DESCRIPTION OF THE FIGURES

[0047] FIG. 1 is a system-level illustration of an exemplary surgical instrument in which embodiments such as grasping jaws and an exemplary force generator mechanism may be implemented;

[0048] FIG. 2 is a schematic of a surgical instrument that includes an exemplary illustrative embodiment of movable grasping jaws that includes an exemplary illustration of a force generator mechanism;

[0049] FIG. 3 is a schematic of a surgical instrument that includes an exemplary illustrative embodiment of closed mating position of movable grasping jaws that includes an exemplary illustration of a force generator mechanism;

[0050] FIG. 4 is a schematic of a surgical instrument that includes an illustrative example of mating grasping jaws configured to grasp tubular organs/tissues;

[0051] FIG. 5 is a schematic of a surgical instrument including an exemplary illustration of two grasping jaws adapted to provide an annular grasp around an exemplary illustration of a bodily organ;

[0052] FIG. 6 is a schematic of a surgical instrument including an exemplary illustration of a force generator mechanism that is configured to deliver an exemplary illustration of a linear row of staples into an exemplary illustration of a bodily organ/tissue;

[0053] FIG. 7 is a schematic of a surgical instrument that includes an exemplary illustration of a split force generator mechanism located in both illustrative grasping jaws;

[0054] FIG. 8 is a schematic of a surgical instrument that includes an exemplary illustration of an example of a flexually deformable and steerable shaft;

[0055] FIG. 9 is a schematic of a surgical instrument including exemplary illustration of shape-conforming grasping jaws with exemplary sensors;

[0056] FIG. 10 is a schematic of a surgical instrument including an exemplary illustration of a grasping jaw housing a delivery mechanism for delivering an exemplary fasteners and an illustrative example of a chemical tissue sealant;

[0057] FIG. 11 is a schematic of a surgical instrument including an exemplary illustration of a portion of a chemical tissue sealant deposited in proximity to an exemplary row of surgical fasteners;

[0058] FIG. 12 is a schematic of a surgical instrument including an exemplary illustration of a portion of a chemical tissue sealant deposited in proximity to an exemplary illustration of layers of bodily tissues;

[0059] FIG. 13 is a schematic of a surgical instrument including an exemplary illustration of a sensor includes an exemplary illustration of an image acquisition device;

[0060] FIG. 14 is a schematic of a surgical instrument including a pair of grasping jaws includes an exemplary illustration of sensors with exemplary illustrations of image acquisition devices in communication with at least one image display;

[0061] FIG. 15 is a schematic of a surgical instrument including exemplary illustrations of sensors including exemplary an illustration of an image acquisition device and an exemplary illustration of a data-transmission device;

[0062] FIG. 16 is a schematic of a surgical instrument including an exemplary illustration of a proximity detector;

[0063] FIG. 17 is a schematic of a surgical instrument including an exemplary illustration of an image acquisition device, an exemplary illustration of a communication medium and an exemplary illustration of a visual display;

[0064] FIG. 18 is a schematic of a surgical instrument including an exemplary illustration of a fastener or staple holder or housing containing an exemplary illustration of an assortment of fasteners/staples;

[0065] FIG. 19 is a schematic of a surgical instrument including an exemplary illustration of detachable grasping jaws;

[0066] FIG. 20 is a schematic of a surgical instrument including an exemplary illustration of a cutting device;

[0067] FIG. 21 is a schematic of a surgical instrument including an exemplary illustration of a force feedback signal;

[0068] FIG. 22 illustrates embodiments of an exemplary operational flow for displaying an image;

[0069] FIG. 23 illustrates embodiments of an exemplary operational flow for grasping a body organ or tissue;

[0070] FIG. 24 illustrates embodiments of an exemplary operational flow for adjusting a configuration of grasping a body organ or tissue;

[0071] FIG. 25 illustrates embodiments of an exemplary operational flow for releasing a surgical fastener;

[0072] FIG. 26 illustrates embodiments for an exemplary surgical instrument.

DETAILED DESCRIPTION

[0073] In the following detailed description, reference is made to the accompanying drawings, which form a part hereof. In the drawings, similar symbols typically identify similar components, unless context dictates otherwise. The illustrative embodiments described in the detailed description, drawings, and claims are not meant to be limiting. Other embodiments may be utilized, and other changes may be made, without departing from the spirit or scope of the subject matter presented here.

[0074] The following disclosure is drawn to a surgical instrument. FIG. 1 shows a system-level schematic illustration of an embodiment of the surgical instrument 100 comprising at least one grasping jaw 110, the at least one grasping jaw being adapted to deliver surgical staples 120 by a force generated from a force generator mechanism 130 that is contained within the at least one grasping jaw 110 or is in a proximity to the at least one grasping jaw. The grasping jaws 110, 112 may be movably 140 attached to a hinge 630. At a system level, the surgical instrument further comprises control circuitry that may control one or more parts of the surgical instrument. Additionally, the surgical instrument may optionally include a shaft 270 connecting the jaws and/or hinge to a handgrip 590. The handgrip includes a trigger 610. The handgrip includes a signal generator 540 that is capable of communicating a signal 550. In some embodiments of the surgical instrument the trigger/handgrip is adapted to receive a feedback signal 600 that may communicate to a user information regarding the functional status of the surgical instrument.

[0075] As used herein, the terms “grasping jaws” or “jaws” include, but are not limited to, any of the various parts or whole of a surgical stapler or parts thereof and/or similar surgical stapling and/or anastomosis devices. Illustrative examples of such staplers, stapling devices and/or anastomosis devices may be those suitable for use in any medical or surgical care including performing end-to-end anastomosis, side-to-side anastomosis, individual ligation, endoscopic or laparoscopic gastro-intestinal operations. Such operations may involve for example, at least one of a bronchus, a pulmonary artery, a pulmonary vein, a large or small intestine, a stomach, a blood vessel and/or skin.

[0076] Turning now to FIG. 2, which is an exemplary illustration of a surgical instrument 100 wherein at least one grasping jaw 110 is configured to movably 140 operate in an opposing manner with respect to at least one other grasping jaw 112.

[0077] FIG. 3 illustrates an exemplary surgical instrument 100 showing an embodiment of at least one grasping jaw 110 that is configured to operably mate 150 with at least one other grasping jaw 112. The term “mate” includes, but is not limited to, juxtapositioning, “coming together” and/or aligning any or all parts of each grasping jaw. Mating includes, but is not limited to, complete or partial coupling of the grasping of the jaws.

[0078] As illustrated in FIG. 4, at least one grasping jaw 112 is configured to serve as an anvil 160 for forming an interaction surface 162 between at least one surgical staple 170 and bodily tissues 180, the forming being facilitated by reversible mating and unmating 190 of the anvil with an opposite grasping jaw 112. Those skilled in the art will recognize that mating and unmating of the grasping jaws may be limited to the movement of at least one grasping jaw while the other grasping jaw may be stationary. Furthermore, the illustration in FIG. 4 does not necessarily limit the surgical instrument to only two jaws. One skilled in the art may envisage similar surgical instruments with more than two grasping jaws that are aligned to achieve the same or similar results illustrated in FIG. 4.

[0079] FIG. 5 shows an exemplary embodiment of a surgical instrument 100 illustrating at least one grasping jaw 110 that forms an annular grasp 200 around a body organ/tissue 210. In another embodiment, the other grasping jaw 112 may form a complementary annular grasp 212. Those skilled in the art will realize that the grasping jaws may be configured to alter the shape and size of the grasping surface based on the size and shape of the bodily organs and/or tissues. In other words, grasping jaws may be constructed in different sizes and shapes to fit the various bodily organs and tissues of patients. Furthermore, one or more grasping jaws may be configured to enter the lumen of tubular organs during anastomosis procedures.

[0080] In an embodiment, the terms “bodily”, “body” or “patient” refer to a human or any animal including domestic, marine, research, zoo, farm animals, fowl and sports animals, or pet animals, such as dogs, cats, cattle, horses, sheep, pigs, goats, rabbits, chickens, birds, fish, amphibian and reptile.

[0081] In an embodiment, the terms “tissue(s)” or “organs” includes any part of a human or animal body. Examples may include but is not limited to, organs associated with the alimentary canal/digestive tract, pulmonary tract, blood vessels, lumen-containing organs, bones, etc.

[0082] Looking at FIG. 6, in an embodiment of a surgical instrument 100, a force 220 generated from a force generator

mechanism 130 is communicated to a medium 230 resulting in the release of one or more linear rows 240 of surgical staples. The force may be generated by a variety of means. In an embodiment, such means may include but are not limited to, an energy module 250. The energy module may include at least one of a battery, a capacitor, a fuel cell, a mechanical energy storage device, and/or a fluid energy storage device. In another embodiment, the force may be generated through the use of a number of devices, which may include but are not limited to at least one of a pressurized gas canister/cartridge, a spring, a lever, an explosive charge, a piezoelectric actuator, an electric motor, an electroactive polymer and/or a solenoid.

[0083] In an embodiment, as illustratively exemplified in FIG. 7, at least one energy module 250 may be located within the opposing grasping jaw 112 (or in a proximity to it). Furthermore, the energy module transmits energy 254 through a wireless device 252 to the remotely located force generator mechanism 130. In alternative embodiments, the energy module may transmit energy via a medium that includes but is not limited to at least one of a wire, a tube, an optical fiber and/or a waveguide.

[0084] FIG. 8 illustrates a further variation of an exemplary surgical instrument 100. Here, an embodiment further illustrates two grasping jaws 110, 112 that are connected to a flexually deformable and steerable shaft 270 that is connected to the grasping jaw. In an embodiment, the shaft may be connected to the jaws via a hinge 630. In another embodiment, the flexually deformable and steerable shaft contains at least one shape-transforming material 280, which may permit complete or partial deformation 260 of the shaft. Deformation of the shaft may increase the capability of the surgical instrument because the human user may move 262 the handgrip 590 of the surgical instrument in numerous directions, thus enabling the use of the surgical instrument in hard-to-reach areas of the patient's body and around anatomical corners. The shape-transforming material may contain a shape memory alloy and/or other materials responsive to an input to change shape and/or physical dimension or characteristic. Examples of shape memory alloy include, but are not limited to, Nitinol™. In addition, embodiments may include at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten. Some materials may contain electro-active polymers and/or mechanically reconfigurable material.

[0085] Turning now to FIG. 9, which illustrates an embodiment of a pair of grasping jaws 110, 112. In this example, the grasping jaws may be shaped differently from those exemplified in the above figures and may be further adapted to conform to a shape 320 of a body organ or tissue 210. Conformity may be achieved, inter alia, through the use of shape transforming material 300 provided within the whole or part of the grasping jaws. The shape-transforming material may be distributed in either or both grasping jaws. In an embodiment, at least one sensor 310 may be disposed in one or more of the grasping jaws.

[0086] In an embodiment of a surgical instrument 100, as illustrated in FIG. 10, at least one grasping jaw 110 and at least one delivery mechanism 132 are adapted to deliver exemplary surgical fasteners 340, 350. Moreover in another embodiment, the delivery mechanism may be contained within at least one grasping jaw 110. Alternatively, the delivery mechanism may be in proximity to a grasping jaw but not within it. Here, the location may include, but is not limited to, another grasping jaw or another portion of the surgical instru-

ment. In yet another embodiment, the surgical fasteners may contain at least one shape-transforming material 350. In still another embodiment, at least one grasping jaw 112 may provide at least one chemical tissue sealant 360. The tissue sealant may be housed in a reservoir 370.

[0087] FIG. 11 illustrates an embodiment of a surgical instrument 100, in which a portion 380 of the chemical tissue sealant 360 is delivered in a proximity to illustrative surgical fasteners 340. The sealant may be applied prior to or after the deployment of the surgical fasteners 340, 350. Here, a portion of the chemical tissue sealant, includes, but is not limited to a drop(s) or droplets or spray or liquid or solid or semi-solid. Further embodiments include the delivery of the chemical tissue sealant in proximity to released fasteners 340, 350.

[0088] FIG. 12 illustrates that, in an embodiment, the chemical tissue sealant portion 380 may be delivered between at least two adjacent layers 390 of body tissue. Those skilled in the art are aware that here "adjacent layers" includes, and is not limited to, tissue or organs brought together in close proximity to each other during anastomosis operations. The organs or tissues may lie on top of each other or within each other or on a side by side position with respect to each other or in any other position with respect to each other. As used here, the term "layers" includes monolayers, bilayers, multilayers, a single layer, and includes one or more layers of body tissue.

[0089] FIG. 13 shows an embodiment of a surgical instrument 100 having two grasping jaws 110, 112 configured to grasp bodily tissues/organs 210. This exemplary illustration further shows at least one grasping jaw 110 that includes at least one sensor 310. In a further embodiment, the other grasping jaw 112 is illustratively shown to carry a sensor 310 as well. In another embodiment, at least one sensor includes an image-acquisition device 406. In yet another embodiment, image-acquisition device includes at least one imaging device 410, which may include but is not limited to one of a lens, a camera, a charge coupled device, an X-ray receiver, an acoustic energy receiver, an electromagnetic energy receiver.

[0090] In still another embodiment, as illustrated in FIG. 14, a surgical instrument 100 may include one or more sensors 310 and image acquisition devices 400. The image acquisition devices may transmit images via a wireless communication medium 420 that is operably coupled with at least one image display 430. The communication medium may include, inter alia, hardwire and at least one image-transmission devices. In an embodiment the image transmission devices may be built into the hardware in the image acquisition devices. Those skilled in the art will recognize that image transmission devices may include those devices which may be used for transmitting encoded data obtained by encoding the data of an image. Examples of image transmission devices are given, for instance, in U.S. Pat. No. 5,305,116 and U.S. Pat. No. 6,157,675, both of which are incorporated herein by reference.

[0091] FIG. 15 illustrates at least one sensor 310 that includes a data-transmission device 440. In another embodiment, the surgical instrument 100 may include two grasping jaws 110, 112 that may have two separate sensors 310 each includes either an image acquisition device 400 or a data transmission device 440. Those skilled in the art will realize that some surgical instruments may include more than two grasping jaws containing more than two image acquisition devices and/or data acquisition devices.

[0092] Turning to FIG. 16, there is illustrated an embodiment of a surgical instrument 100 that includes at least one grasping jaw 112 that includes a sensor 310 which in turn may include a proximity detector 450. In an embodiment, the proximity detector is adapted to detect proximity of a biological tissue 460 to the surgical instrument 100. In another embodiment, the proximity detector includes an electromagnetic energy emitter and/or an electromagnetic energy receiver. In yet another embodiment, the proximity detector includes a point source emitter 480 and/or a source illuminator. In still another embodiment, the point source emitter and/or a source illuminator emits electromagnetic and/or acoustic energy 470. The energy emitter includes at least one of an ultrasonic source, an acoustic source, a visible source, an ultraviolet source, a gamma ray source, an X-ray source and/or an infrared source.

[0093] FIG. 17 schematically illustrates an exemplary proximity detector 450 that includes a communication medium 490 for communication with at least one image display 430. One skilled in the art will realize that communication includes, but is not limited to, image transmission, data transmission, digital data transmission, analogue data transmission and/or an audio transmission. One skilled in the art will also recognize that examples of communication media include, but are not limited to the following devices: a wire, a tube, an optical fiber, a waveguide and/or wireless devices.

[0094] There is illustrated in an embodiment shown in FIG. 18 a surgical instrument 100 comprising multiple types of surgical fasteners made from an assortment of materials. In an embodiment, one surgical instrument 100 may house 500 exemplary surgical staples made from, for instance, shape transforming material 510 and/or mechanically reconfigurable material 512. One skilled in the art will recognize that multiple types of surgical fasteners include, but are not limited to surgical fasteners made from different types of materials/compositions, chemical or electrical properties, different shapes and sizes of fasteners, including biocompatible, biodegradable materials. One skilled in the art will further recognize that the above term "house" includes but is not limited to fastener/stapler cartridge holders and the like that are available in the commercial market, and those that are custom-designed and made to fit into surgical stapler-type medical instruments.

[0095] In FIG. 19, there is shown an embodiment of a surgical instrument 100 wherein the exemplary grasping jaws 110, 112 are configured to become detachable 520. Those skilled in the art will recognize that detachability of grasping jaws includes, but is not limited to, replacement of used grasping jaws with new ones and disposable grasping jaws. In an embodiment, one or more grasping jaws may be replaced sequentially and/or simultaneously. Furthermore, detachability of grasping jaws includes, inter alia, replacement grasping jaws of different sizes and shapes and/or grasping jaws made from different materials/compositions of materials.

[0096] Turning to FIG. 20, which schematically illustrates an embodiment of a surgical instrument 100 containing an exemplary illustration of a cutting device 530. The surgical instrument may further comprise at least one grasping jaw 110, 112 and a deformable and steerable shaft 270 made from shape transformation material 280. The cutting device may include, but is not limited to, at least one cutter. As recognized by those skilled in the art, cutters may include optical cutters, laser-mediated cutting devices, electro-thermal cutters, a blade, a knife and/or an edge.

[0097] FIG. 21 illustrates an embodiment of a surgical instrument 100 that includes a handgrip 590. The handgrip includes a trigger 610. The handgrip further includes a signal generator 540 that is capable of communicating signals 550. In an embodiment, the trigger/handgrip is adapted to receive one or more feedback signals 600 that may communicate to a human or robotic user information regarding the functional status of the surgical instrument. The signals may be, for example, generated by parts within the fastener/staple delivery mechanism 132. Those skilled in the art will appreciate that the term trigger includes, but is not limited to devices such as, pushbutton or lever or latch etc. Furthermore those skilled in the art will recognize that here the term "functional status" includes delivery status of surgical fasteners/staples (including whether a fastener or staple has been released by the instrument and whether the fastener/staple has been delivered into a bodily tissue in a correct or incorrect manner), number of staples/fasteners remaining in the surgical instrument, any defective surgical staples/fasteners in the surgical instrument, jammed surgical staples/fasteners and/or general malfunction of the surgical instrument. One skilled in the art will recognize that the feedback signals may include, inter alia, signals emanating as consequence of an operation of a fastener delivery mechanism 132.

[0098] Those skilled in the art will recognize that any type of feedback signal may be applied. Such signals may be optical, acoustic, provide force feedback, vibrational etc. The force feedback signal as shown in FIG. 21 is provided to the trigger and handle but it can be provided to any other area of the surgical instrument 100. The instrument may include such devices as an LED light, which may be disposed on the handle in easy view that responds to a feedback signal.

[0099] In an embodiment illustrated in FIG. 22, an exemplary operation flow 700 for a method of splicing body organs/tissues comprises: grasping a body organ/tissue with at least one grasping jaw 710; adjusting a configuration of the grasping in response to a signal or a datum or an image 720 provided by the instrument; and releasing a surgical staple/fastener in response to a signal, a datum or an image 730 provided by the instrument.

[0100] As illustrated in FIG. 23, an exemplary operational flow for grasping a body organ/tissue with at least one grasping jaw 710 may further include: performing endoscopic or laparoscopic gastro-intestinal operations 712; end-to-end and/or side to side anastomosis operations, individual ligation, endoscopic or laparoscopic operations and/or gastro-intestinal operations 714; aligning body organs between at least one grasping jaw in a manner compatible with one or more above listed operations 716; and displaying images of organ/tissue 718.

[0101] In an embodiment, there is illustrated in FIG. 24 an exemplary operational flow 720 for implementing a step of adjusting a configuration of grasping in response to a signal or a datum or an image. This step optionally includes annularly adjusting a grasp of grasping jaws around tubular organs/tissues based on signal or datum or image 722.

[0102] FIG. 25 shows another embodiment as provided by the instrument for releasing a surgical staple/fastener in response to signal, datum or image 730. This operation optionally includes the following exemplary steps: driving a plurality of staples/fasteners into at least one layer of body tissue 731; securing at least one layer of a body tissue with surgical staples/fasteners 732; deformation of one or more fasteners that undergo a conformational change to close a

puncture site **733**; closing at least one or more wound sites **734**; and releasing a suitable amount of a chemical tissue sealant that permits wound healing **735**.

[0103] As illustrated in FIG. 26, an embodiment of an exemplary surgical instrument includes: means for grasping a body organ/tissue **810**; means for adjusting a configuration of grasping in response to a signal or a datum or an image **820**; means for releasing a surgical staple/fastener in response to signal, datum or image **830**.

[0104] The foregoing detailed description has set forth various embodiments of the devices and/or processes via the use of flowcharts, diagrams, figures and/or examples. Insofar as such flowcharts, diagrams, figures and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such flowchart, diagram, figure and/or example can be implemented, individually and/or collectively, by a wide range of any combination thereof.

[0105] One skilled in the art will recognize that the herein described components (e.g., steps), devices, and objects and the discussion accompanying them are used as examples for the sake of conceptual clarity and that various configuration modifications are within the skill of those in the art. Consequently, as used herein, the specific exemplars set forth and the accompanying discussion are intended to be representative of their more general classes. In general, use of any specific exemplar herein is also intended to be representative of its class, and the non-inclusion of such specific components (e.g., steps), devices, and objects herein should not be taken as indicating that limitation is desired.

[0106] The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted figures are merely exemplary, and that in fact many other figures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively "associated" or "coupled" such that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as "associated with" each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being "operably connected", or "operably coupled", to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being "operably couplable", to each other to achieve the desired functionality. Specific examples of operably couplable include but are not limited to, physically mateable and/or physically interacting components and/or wirelessly interactable and/or wirelessly interacting components and/or logically interacting and/or logically interactable components.

[0107] In a general sense, those skilled in the art will recognize that the various aspects described herein which can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or any combination thereof can be viewed as being composed of various types of "electrical circuitry." Consequently, as used herein "electrical circuitry" includes, but is not limited to, electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing

device configured by a computer program (e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of random access memory), and/or electrical circuitry forming a communications device (e.g., a modem, communications switch, or optical-electrical equipment). Those having skill in the art will recognize that the subject matter described herein may be implemented in an analog or digital fashion or some combination thereof.

[0108] Those skilled in the art will recognize that it is common within the art to describe devices and/or processes in the fashion set forth herein, and thereafter use engineering practices to integrate such described devices and/or processes into image processing systems. That is, at least a portion of the devices and/or processes described herein can be integrated into an image processing system via a reasonable amount of experimentation. Those having skill in the art will recognize that a typical image processing system generally includes one or more of a system unit housing, a video display device, a memory such as volatile and non-volatile memory, processors such as microprocessors and digital signal processors, computational entities such as operating systems, drivers, and applications programs, one or more interaction devices, such as a touch pad or screen, control systems including feedback loops and control motors (e.g., feedback for sensing lens position and/or velocity; control motors for moving/distorting lenses to give desired focuses). A typical image processing system may be implemented utilizing any suitable commercially available components, such as those typically found in digital still systems and/or digital motion systems.

[0109] One skilled in the art will recognize that the herein described components (e.g., steps), devices, and objects and the discussion accompanying them are used as examples for the sake of conceptual clarity and that various configuration modifications are within the skill of those in the art. Consequently, as used herein, the specific exemplars set forth and the accompanying discussion are intended to be representative of their more general classes. In general, use of any specific exemplar herein is also intended to be representative of its class, and the non-inclusion of such specific components (e.g., steps), devices, and objects herein should not be taken as indicating that a limitation is desired.

[0110] With respect to the use of substantially any plural and/or singular terms herein, those having skill in the art can translate from the plural to the singular and/or from the singular to the plural as is appropriate to the context and/or application. The various singular/plural permutations are not expressly set forth herein for sake of clarity.

[0111] The herein described subject matter sometimes illustrates different components contained within, or connected with, different other components. It is to be understood that such depicted architectures are merely exemplary, and that in fact many other architectures can be implemented which achieve the same functionality. In a conceptual sense, any arrangement of components to achieve the same functionality is effectively "operably coupled" or "coupled" or "in communication with" or "communicates with" or "operatively communicate" such other objects that the desired functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as associated with each other such that the desired functionality

is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “connected”, or “attached”, to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably couplable”, to each other to achieve the desired functionality.

[0112] While particular aspects of the present subject matter described herein have been shown and described, it will be apparent to those skilled in the art that, based upon the embodiments herein, changes and modifications may be made without departing from the subject matter described herein and its broader aspects and, therefore, the appended claims are to encompass within their scope all such changes and modifications as are within the true spirit and scope of the subject matter described herein. Furthermore, it is to be understood that the invention is defined by the appended claims. It will be understood by those within the art that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to inventions containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations. In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that virtually any disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims,

or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms. For example, the phrase “A or B” will be understood to include the possibilities of “A” or “B” or “A and B.”

1. A surgical instrument comprising:

at least one grasping jaw, said at least one grasping jaw being adapted to deliver surgical staples responsive to an actuation force; and

a force generator mechanism that is contained within said at least one grasping jaw or is in a proximity to said at least one grasping jaw, said force generator mechanism being coupled to said grasping jaw and responsive to an input signal to independently produce said actuation force.

2. The surgical instrument of claim 1, wherein said at least one grasping jaw is configured to movably operate in an opposing manner with respect to at least one other grasping jaw.

3. The surgical instrument of claim 1, wherein said at least one grasping jaw is configured to operably mate with at least one other grasping jaw.

4. The surgical instrument of claim 1, wherein said at least one grasping jaw is configured to serve as an anvil for forming an interaction surface between at least one surgical staple and bodily tissues, said forming being facilitated by reversible mating and unmating of said anvil with an opposite grasping jaw.

5. (canceled)

6. The surgical instrument of claim 1, wherein said force generated from said force generator mechanism is communicated to a medium resulting in the release of at least one surgical staple.

7. The surgical instrument of claim 1, wherein said force generated from said force generator mechanism results in delivery of one or more linear rows of surgical staples.

8. The surgical instrument of claim 1, further comprising at least one energy module, said energy module includes at least one of a battery, a capacitor, a fuel cell, a mechanical energy storage device, and/or a fluid energy storage device.

9-12. (canceled)

13. The surgical instrument of claim 8, wherein said energy module transmits energy through a wireless device.

14. The surgical instrument of claim 1, further comprising at least one sensor.

15-16. (canceled)

17. The surgical instrument of claim 14, wherein said at least one sensor includes an image-acquisition device.

18. (canceled)

19. The surgical instrument of claim 14, wherein said sensor includes an illumination device that is operably coupled to at least one image-acquisition device.

20. The surgical instrument of claim 19 wherein said image-acquisition device is wirelessly coupled to at least one visual display.

21. (canceled)

22. The surgical instrument of claim 14, wherein said at least one sensor includes a proximity detector.

23. The surgical instrument of claim 22, wherein said proximity detector is adapted to detect proximity of a biological tissue to said surgical instrument.

24-34. (canceled)

35. The surgical instrument of claim 14, wherein said at least one sensor provides a force feedback signal to a force generator mechanism.

36-50. (canceled)

51. A surgical instrument comprising:

a flexually deformable and steerable shaft operably connected to at least one grasping jaw having a force generator mechanism that is contained within said at least one grasping jaw or is in a proximity to said at least one grasping jaw, said flexually deformable and steerable shaft being controllably deformable to permit a high degree of maneuverability of said surgical instrument.

52. The surgical instrument of claim **51**, wherein said flexually deformable and steerable shaft contains at least one shape-transforming material.

53. The surgical instrument of claim **51**, wherein said flexually deformable and steerable shaft is enclosed in a bendable and steerable tube or a sheath.

54. The surgical instrument of claim **52**, wherein said at least one shape-transforming material contains a shape memory alloy.

55. The surgical instrument of claim **52**, wherein said at least one shape-transforming material includes at least one of titanium, nickel, zinc, copper, aluminum, cadmium, platinum, iron, manganese, cobalt, gallium and/or tungsten.

56. The surgical instrument of claim **52**, wherein said at least one shape-transforming material is preconfigured to a particular application and to a body part geometry.

57. (canceled)

58. The surgical instrument of claim **54**, wherein said shape memory alloy includes Nitinol™.

59. The surgical instrument of claim **52**, wherein said at least one shape-transforming material includes electro-active polymer.

60. The surgical instrument of claim **52**, wherein said at least one shape-transforming material includes at least one mechanically reconfigurable material.

61. The surgical instrument of claim **51**, wherein said flexually deformable and steerable shaft being controllably deformable to permit a high degree of maneuverability of said surgical instrument includes controllable deformation of said shaft that is mediated by at least one of a temperature profile, a pressure profile, an electrical circuitry, a magnetic profile, an acoustic wave profile and/or an electro-magnetic radiation profile.

62-64. (canceled)

65. The surgical instrument of claim **51**, wherein said surgical instrument is a surgical stapler that is adapted to deliver biodegradable staples, fasteners, pins or ties.

66. The surgical instrument of claim **51**, wherein said surgical instrument is a surgical stapler that is adapted to deliver non-biodegradable staples, fasteners, pins or ties.

67. The surgical instrument of claim **51**, further comprising at least one grasping jaw having a proximity detector.

68. The surgical instrument of claim **67**, wherein said proximity detector is adapted to detect whether a biological tissue is partly within grasping distance of said grasping jaw.

69. The surgical instrument of claim **67**, wherein said proximity detector is adapted to detect whether a biological tissue is fully within grasping distance of said grasping jaw.

70. The surgical instrument of claim **67**, wherein said proximity detector is operably configured to assess whether an entire or a portion of a bodily organ is fully or partly grasped within said grasping jaw.

71. The surgical instrument of claim **51**, further comprising at least one grasping jaw that is fully redeployable following

at least one grasp-and-release cycle in a grasping operation of a biological tissue and/or bodily organ.

72. The surgical instrument of claim **51**, further comprising at least one grasping jaw that is independently maneuverable from an attached shaft and/or a sheath.

73. A surgical instrument comprising:

at least one grasping jaw;

a force receiver adapted to receive manual force from a user; and

an actuation mechanism responsive to said manual force to produce a jaw-laden force without mechanically coupling said manual force to said grasping jaw.

74. The surgical instrument of claim **73**, wherein said force receiver includes at least one sensor.

75. The surgical instrument of claim **74**, wherein said at least one sensor is operably coupled to said actuation mechanism.

76. The surgical instrument of claim **74**, wherein said at least one sensor receives a signal from said actuation mechanism through a wireless medium.

77. The surgical instrument of claim **74**, wherein said at least one sensor transmits a signal to said actuation mechanism through a wireless medium.

78. The surgical instrument of claim **73**, wherein said manual force from a user includes a user-activated sensory device, tactile device or audio-sensitive device that transmits a signal to said force receiver.

79. The surgical instrument of claim **73**, wherein said jaw-laden force without mechanically coupling includes force carried through a wireless medium, an etherereal medium or other intangible media.

80. The surgical instrument of claim **73**, wherein said actuation mechanism converts a manual force from said force receiver to said jaw-laden force.

81. The surgical instrument of claim **73**, wherein said jaw-laden force results in release of at least one surgical stapler and/or surgical fastener.

82-271. (canceled)

272. A method of splicing body organs/tissues comprising: grasping a body organ/tissue with at least one grasping jaw; adjusting a configuration of said grasping in response to a signal or a datum or an image; and

releasing a surgical staple/fastener in response to said signal, datum or image.

273. The method of splicing body organs/tissues of claim **272**, wherein grasping a body organ/tissue includes performing end-to-end anastomosis, side-to-side anastomosis, individual ligation, endoscopic or laparoscopic gastro-intestinal operations which include at least one of a bronchus, a pulmonary artery, a pulmonary vein, a large or small intestine, a stomach, a blood vessel and/or skin.

274. The method of splicing body organs/tissues of claim **272**, wherein said grasping a body organ/tissue includes aligning said body organs between said at least one grasping jaw in a manner compatible with surgical and/or anastomosis operations.

275. The method of splicing body organs/tissues of claim **272**, wherein said grasping a body organ/tissue includes displaying an image of said organ/tissue.

276-278. (canceled)

279. The method of splicing body organs/tissues of claim **272**, wherein said releasing a surgical staple/fastener includes deformation of one or more staple/fasteners that undergo a conformational change to close a puncture site.

280. The method of splicing body organs/tissues of claim **272**, wherein said releasing a surgical staple/fastener includes closing at least one or more wound sites.

281. The method of splicing body organs/tissues of claim **272**, wherein said releasing a surgical staple/fastener includes releasing a suitable amount of a chemical tissue sealant that permits wound healing.

282. (canceled)

* * * * *

专利名称(译)	可操纵的外科缝合器		
公开(公告)号	US20080283577A1	公开(公告)日	2008-11-20
申请号	US11/804219	申请日	2007-05-16
[标]申请(专利权)人(译)	特拉华州的SEARETE负债CORP		
申请(专利权)人(译)	SEARETE有限责任公司，特拉华州的有限责任公司		
当前申请(专利权)人(译)	深科技有限责任公司		
[标]发明人	BOYDEN EDWARD S HYDE RODERICK A ISHIKAWA MURIEL Y LEUTHARDT ERIC C MYHRVOLD NATHAN P RIVET II DENNIS J SMITH MICHAEL A TEGREENE CLARENCE T WEAVER THOMAS A WHITMER CHARLES WOOD JR LOWELL L WOOD VICTORIA Y H		
发明人	BOYDEN, EDWARD S. HYDE, RODERICK A. ISHIKAWA, MURIEL Y. LEUTHARDT, ERIC C. MYHRVOLD, NATHAN P. RIVET, II, DENNIS J. SMITH, MICHAEL A. TEGREENE, CLARENCE T. WEAVER, THOMAS A. WHITMER, CHARLES WOOD, JR., LOWELL L. WOOD, VICTORIA Y.H.		
IPC分类号	A61B17/04 A61B17/00		
CPC分类号	A61B17/00491 A61B17/068 A61B17/072 A61B2017/00022 A61B2017/00221 A61B2017/00398 A61B2017/00402 A61B2017/00871 A61B2017/07214 A61B2017/07278 A61B2017/2905		
其他公开文献	US7832611		
外部链接	Espacenet USPTO		

摘要(译)

实施例包括手术装置和方法。外科器械的一个实施例包括至少一个抓握钳口，所述至少一个抓握钳口适于通过力发生器机构产生的力来递送外科钉，所述力发生器机构包含在所述至少一个抓握钳口内或者接近于至少一个抓握钳口。另一个实施例包括至少一个抓握钳口，至少一个适于递送外科紧固件的递送机构，所述递送机构位于所述至少一个抓握钳口附近或包含在所述至少一个抓握钳口内，所述外科紧固件包含至少一种形状转换材料。，至少一个传感器，至少一个化学组织密封剂和至少一个切割器。一种方法包括：用至少一个抓握钳口抓握身体器官/组织，响应于信号或基准或图像调整抓握的配置，以及响应于信号，基准或者释放外科钉/紧固件。图片。

