



US008070676B2

(12) **United States Patent**
Ewers et al.

(10) **Patent No.:** **US 8,070,676 B2**
 (45) **Date of Patent:** ***Dec. 6, 2011**

(54) **SURGICAL ACCESS APPARATUS AND METHOD**

(75) Inventors: **Richard C. Ewers**, Fullerton, CA (US);
John R. Brustad, Dana Point, CA (US);
Edward D. Pingleton, San Juan Capistrano, CA (US); **Nabil Hilal**, Laguna Niguel, CA (US); **Gary R. Dulak**, Valencia, CA (US); **Payam Adlparvar**, Lake Forest, CA (US); **Robert R. Bowes**, Laguna Hills, CA (US)

(73) Assignee: **Applied Medical Resources Corporation**, Rancho Santa Margarita, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/960,449**

(22) Filed: **Dec. 3, 2010**

(65) **Prior Publication Data**

US 2011/0071462 A1 Mar. 24, 2011

Related U.S. Application Data

(63) Continuation of application No. 12/360,710, filed on Jan. 27, 2009, which is a continuation of application No. 11/244,647, filed on Oct. 5, 2005, now Pat. No. 7,481,765, which is a continuation of application No. 10/381,220, filed as application No. PCT/US2001/029682 on Sep. 21, 2001, now Pat. No. 7,473,221.

(60) Provisional application No. 60/241,958, filed on Oct. 19, 2000.

(51) **Int. Cl.**
A61B 1/32

(2006.01)

(52) **U.S. Cl.** **600/208; 524/267**

(58) **Field of Classification Search** 606/108, 606/191, 213, 205-207; 604/164.01-164.11, 604/165, 166, 167, 246, 247, 250, 264; 600/206, 600/208; 524/267, 313, 490, 491
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

558,364 A 4/1896 Doolittle
 (Continued)

FOREIGN PATENT DOCUMENTS

DE 26 05 148 A1 8/1977
 (Continued)

OTHER PUBLICATIONS

5,344,646, Chen, (withdrawn).

(Continued)


Primary Examiner — Tuan Nguyen

(74) *Attorney, Agent, or Firm* — Knobbe Martens Olson & Bear, LLP

(57) **ABSTRACT**

A surgical access device includes an access seal comprising an ultra gel elastomeric material formed of a mixture comprising a triblock copolymer and an oil. The access seal is adapted to be disposed relative to the abdominal wall. At least one access channel is formed through the elastomeric material between a proximal portion and a distal portion of the access seal. The access channel when operatively disposed forms at least a portion of a working channel between a location external to the abdominal wall and a location internal to the abdominal wall. The elastomeric material of the access seal is adapted to conform to a surface of an instrument inserted through the working channel to provide instrument access to the abdominal cavity while maintaining insufflation pressure in the abdominal cavity. The access channel is configured to self seal in the absence of any instrument extending through the access channel.

20 Claims, 18 Drawing Sheets



U.S. PATENT DOCUMENTS			
1,157,202 A	10/1915	Bates et al.	4,331,138 A
1,598,284 A	8/1926	Kinney	4,338,934 A
1,690,995 A	11/1928	Pratt	4,338,937 A
1,180,466 A	6/1931	Deutsch	4,367,728 A
1,810,466 A	6/1931	Deutsch	4,369,284 A
2,219,564 A	10/1940	Reyniers	4,399,816 A
2,305,289 A	12/1942	Coburg	4,402,683 A
2,478,586 A	8/1949	Krapp	4,411,659 A
2,669,991 A	2/1954	Curutchet	4,421,296 A
2,695,608 A	11/1954	Gibbon	4,424,833 A
2,812,758 A	11/1957	Blumenschein	4,428,364 A
2,835,253 A	5/1958	Borgeson	4,430,081 A
2,853,075 A	9/1958	Hoffman et al.	4,434,791 A
3,039,468 A	6/1962	Price	4,436,519 A
3,057,350 A	10/1962	Cowley	4,454,873 A
3,111,943 A	11/1963	Orndorff	4,473,067 A
3,195,934 A	7/1965	Parrish	4,475,548 A
3,244,169 A	4/1966	Baxter	4,485,490 A
3,253,594 A	5/1966	Matthews et al.	4,488,877 A
3,313,299 A	4/1967	Spademan	4,543,088 A
3,329,390 A	7/1967	Hulsey	4,550,713 A
3,332,417 A	7/1967	Blanford et al.	4,553,537 A
3,347,226 A	10/1967	Harrower	4,555,242 A
3,347,227 A	10/1967	Harrower	4,556,996 A
3,397,692 A	8/1968	Creager, Jr. et al.	4,601,710 A
3,402,710 A	9/1968	Paleschuck	4,610,665 A
3,416,520 A	12/1968	Creager, Jr.	4,626,245 A
3,447,533 A	6/1969	Spicer	4,634,424 A
3,522,800 A	8/1970	Lesser	4,634,432 A
3,523,534 A	8/1970	Nolan	4,644,951 A
3,570,475 A	3/1971	Weinstein	4,649,904 A
3,656,485 A	4/1972	Robertson	4,653,476 A
3,685,786 A	8/1972	Woodson	4,654,030 A
3,717,151 A	2/1973	Collett	4,655,752 A
3,717,883 A	2/1973	Mosher	4,673,393 A
3,729,006 A	4/1973	Wilder et al.	4,673,394 A
3,782,370 A	1/1974	McDonald	4,691,942 A
3,797,478 A	3/1974	Walsh et al.	4,714,749 A
3,799,166 A	3/1974	Marsan	4,738,666 A
3,807,393 A	4/1974	McDonald	4,755,170 A
3,828,764 A	8/1974	Jones	4,760,933 A
3,831,583 A	8/1974	Edmunds et al.	4,776,843 A
3,841,332 A	10/1974	Treacle	4,777,943 A
3,850,172 A	11/1974	Cazalis	4,784,646 A
3,853,126 A	12/1974	Schulte	4,796,629 A
3,853,127 A	12/1974	Spademan	4,798,594 A
3,856,021 A	12/1974	McIntosh	4,802,694 A
3,860,274 A	1/1975	Ledstrom et al.	4,808,168 A
3,861,416 A	1/1975	Wichterle	4,809,679 A
3,907,389 A	9/1975	Cox et al.	4,828,554 A
3,915,171 A	10/1975	Shermeta	4,842,931 A
3,965,890 A	6/1976	Gauthier	4,848,575 A
3,970,089 A	7/1976	Saice	4,856,502 A
3,996,623 A	12/1976	Kaster	4,863,430 A
4,000,739 A	1/1977	Stevens	4,863,438 A
4,016,884 A *	4/1977	Kwan-Gett 604/175	4,889,107 A
4,024,872 A	5/1977	Muldoon	4,895,565 A
4,030,500 A	6/1977	Ronnquist	4,897,081 A
4,043,328 A	8/1977	Cawood, Jr. et al.	4,903,710 A
4,069,913 A	1/1978	Harrigan	4,911,974 A
4,082,005 A	4/1978	Erdley	4,915,132 A
4,083,370 A	4/1978	Taylor	4,926,882 A
4,096,853 A	6/1978	Weigand	4,929,235 A
4,112,932 A	9/1978	Chiulli	4,944,732 A
4,130,113 A	12/1978	Graham	4,950,222 A
4,177,814 A	12/1979	Knepshield et al.	4,950,223 A
4,183,357 A	1/1980	Bentley et al.	4,984,564 A
4,187,849 A	2/1980	Stim	4,991,593 A
4,188,945 A	2/1980	Wenander	4,998,538 A
4,217,664 A	8/1980	Faso	5,000,745 A
4,222,126 A	9/1980	Boretos et al.	5,009,224 A
4,228,792 A	10/1980	Rhys-Davies	5,015,228 A
4,239,036 A	12/1980	Krieger	5,019,101 A
4,240,411 A	12/1980	Hosono	5,026,366 A
4,253,201 A	3/1981	Ross et al.	5,037,379 A
4,254,973 A	3/1981	Benjamin	5,041,095 A
4,306,562 A	12/1981	Osborne	5,045,070 A
4,321,915 A	3/1982	Leighton	D320,658 S
			5,071,411 A
			5/1982
			Jessen
			7/1982
			Spademan
			7/1982
			Lerman
			1/1983
			Mutke
			1/1983
			Chen
			8/1983
			Spangler
			9/1983
			Kopman
			10/1983
			Jensen et al.
			12/1983
			Stephens
			1/1984
			Spector et al.
			1/1984
			Bartolo
			2/1984
			Timmermans
			3/1984
			Darnell
			3/1984
			O'Neill
			6/1984
			Laufenberg et al.
			9/1984
			Schiff
			10/1984
			Muto
			12/1984
			Akers et al.
			12/1984
			Klein
			9/1985
			Bootman et al.
			11/1985
			Hyman
			11/1985
			Rosenberg
			11/1985
			Saudagar
			12/1985
			Wallace
			7/1986
			Moll
			9/1986
			Matsumoto et al.
			12/1986
			Weinstein
			1/1987
			O'Boyle
			1/1987
			Kocak
			2/1987
			Bays
			3/1987
			Krauter
			3/1987
			Bonnet
			3/1987
			Moll et al.
			4/1987
			Honkanen et al.
			6/1987
			Suzuki et al.
			6/1987
			Fenton
			9/1987
			Ford
			12/1987
			Hughes et al.
			4/1988
			Fuqua
			7/1988
			Golden
			8/1988
			Christner et al.
			10/1988
			Martinez et al.
			10/1988
			Chvapil
			11/1988
			Feingold
			1/1989
			Grayzel
			1/1989
			Hillstead
			2/1989
			Vargo
			2/1989
			Warring
			3/1989
			Shimonaka et al.
			5/1989
			Griffin
			6/1989
			Zook
			7/1989
			Nakamura et al.
			8/1989
			Ersfeld et al.
			9/1989
			Klyce et al.
			9/1989
			Gauderer et al.
			12/1989
			Kaufman
			1/1990
			Hillstead
			1/1990
			Poirier
			2/1990
			Jessamine et al.
			3/1990
			Shimizu et al.
			4/1990
			Hodge et al.
			5/1990
			Lawrence
			5/1990
			Merry et al.
			7/1990
			Russo
			8/1990
			Scott et al.
			8/1990
			Silvanov
			1/1991
			Yuen
			2/1991
			LeVahn
			3/1991
			Charowsky et al.
			3/1991
			Guest et al.
			4/1991
			Cole
			5/1991
			Columbus et al.
			5/1991
			Purkait et al.
			6/1991
			Leckrone
			8/1991
			Clayman et al.
			8/1991
			Littrell
			9/1991
			Grodecki et al.
			10/1991
			Quigley et al.
			12/1991
			Hillstead




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6





Fig. 9






Fig. 10

Fig. 11






Fig. 12

Fig. 13





Fig. 14




Fig. 15

Fig. 16





Fig. 17




Fig. 18

Fig. 19





Fig. 20

Fig. 21






Fig. 22

75j

Fig. 23






Fig. 24




Fig. 25

Fig. 26





Fig. 27

5,073,169 A	12/1991	Raiken	5,354,280 A	10/1994	Haber et al.
5,074,878 A	12/1991	Bark et al.	5,360,417 A	11/1994	Gravener et al.
5,082,005 A	1/1992	Kaldany	5,364,345 A	11/1994	Lowery et al.
5,086,763 A	2/1992	Hathman	5,364,372 A	11/1994	Danks et al.
5,092,846 A	3/1992	Nishijima et al.	5,366,446 A	11/1994	Tal et al.
5,104,389 A	4/1992	Deem	5,366,478 A	11/1994	Brinkerhoff et al.
5,125,396 A	6/1992	Ray	5,368,545 A	11/1994	Schaller et al.
5,125,897 A	6/1992	Quinn et al.	5,375,588 A	12/1994	Yoon
5,127,626 A	7/1992	Hilal et al.	5,380,288 A	1/1995	Hart et al.
5,129,885 A	7/1992	Green et al.	5,383,861 A	1/1995	Hempel et al.
5,141,498 A	8/1992	Christian	5,385,552 A	1/1995	Haber et al.
5,149,327 A	9/1992	Oshiyama	5,385,553 A	1/1995	Hart et al.
5,156,617 A	10/1992	Reid	5,385,560 A	1/1995	Wulf
5,158,553 A	10/1992	Berry et al.	5,389,080 A	2/1995	Yoon
5,159,921 A	11/1992	Hoover	5,389,081 A	2/1995	Castro
5,161,773 A	11/1992	Tower	5,391,153 A	2/1995	Haber et al.
5,167,636 A	12/1992	Clement	5,391,156 A	2/1995	Hildwein et al.
5,167,637 A	12/1992	Okada et al.	5,395,367 A	3/1995	Wilk
5,176,648 A	1/1993	Holmes et al.	5,403,264 A	4/1995	Wohlers et al.
5,176,662 A	1/1993	Bartholomew et al.	5,403,336 A	4/1995	Kieturakis et al.
5,176,697 A	1/1993	Hasson et al.	5,407,433 A	4/1995	Loomas
5,178,162 A	1/1993	Bose	5,411,483 A	5/1995	Loomas
5,180,365 A	1/1993	Ensminger et al.	5,413,571 A	5/1995	Katsaros et al.
5,183,471 A	2/1993	Wilk	5,423,848 A	6/1995	Washizuka et al.
5,188,595 A	2/1993	Jacobi	5,429,609 A	7/1995	Yoon
5,188,607 A	2/1993	Wu	5,431,676 A	7/1995	Dubrul et al.
5,192,301 A	3/1993	Kamiya et al.	5,437,683 A	8/1995	Neumann et al.
5,197,955 A	3/1993	Stephens et al.	5,439,455 A	8/1995	Kieturakis et al.
5,207,656 A	5/1993	Kranys	5,441,486 A	8/1995	Yoon
5,209,737 A	5/1993	Rirchart et al.	5,443,452 A	8/1995	Hart et al.
5,211,370 A	5/1993	Powers	5,456,284 A	10/1995	Ryan et al.
5,211,633 A	5/1993	Stouder, Jr.	5,460,170 A	10/1995	Hammerslag
5,213,114 A	5/1993	Bailey, Jr.	5,460,616 A	10/1995	Weinstein et al.
5,226,890 A	7/1993	Ianniruberto et al.	5,468,248 A	11/1995	Chin et al.
5,234,455 A	8/1993	Mulhollan	5,476,475 A	12/1995	Gadberry
5,241,968 A	9/1993	Slater	5,480,410 A	1/1996	Cuschieri et al.
5,242,409 A	9/1993	Buelna	5,486,426 A	1/1996	McGee et al.
5,242,412 A	9/1993	Blake, III	5,490,843 A	2/1996	Hildwein et al.
5,242,415 A	9/1993	Kantrowitz et al.	5,492,304 A	2/1996	Smith et al.
5,242,459 A	9/1993	Buelna	5,496,280 A	3/1996	Vandenbroek et al.
5,248,304 A	9/1993	Vigdorchik et al.	5,503,112 A	4/1996	Luhman et al.
5,256,150 A	10/1993	Quiachon et al.	5,507,758 A	4/1996	Thomason et al.
5,257,973 A	11/1993	Villasuso	5,508,334 A	4/1996	Chen
5,257,975 A	11/1993	Foshee	5,511,564 A	4/1996	Wilk
5,259,366 A	11/1993	Reydel et al.	5,514,109 A	5/1996	Mollenauer et al.
5,261,883 A	11/1993	Hood et al.	5,514,133 A	5/1996	Golub et al.
5,262,468 A	11/1993	Chen	5,514,153 A	5/1996	Bonutti
5,263,922 A	11/1993	Sova et al.	5,518,278 A	5/1996	Sampson
5,269,763 A	12/1993	Boehmer et al.	5,520,632 A	5/1996	Leveen
5,269,772 A	12/1993	Wilk	5,522,791 A	6/1996	Leyva
5,273,449 A	12/1993	Mattis et al.	5,522,824 A	6/1996	Ashby
5,273,545 A	12/1993	Hunt et al.	5,524,644 A	6/1996	Crook
D343,236 S	1/1994	Quigley et al.	5,526,536 A	6/1996	Cartmill
5,279,575 A	1/1994	Sugarbaker	5,531,758 A	7/1996	Uschold et al.
5,290,310 A	3/1994	Makower et al.	5,538,509 A	7/1996	Dunlap et al.
D346,022 S	4/1994	Quigley et al.	5,540,648 A	7/1996	Yoon
5,299,582 A	4/1994	Potts	5,540,711 A	7/1996	Kieturakis et al.
5,300,034 A	4/1994	Behnke	5,545,150 A	8/1996	Danks et al.
5,300,035 A	4/1994	Clement	5,545,179 A	8/1996	Williamson, IV
5,300,036 A	4/1994	Mueller et al.	5,549,563 A	8/1996	Kronner
5,308,336 A	5/1994	Hart et al.	5,549,637 A	8/1996	Crainich
5,309,896 A	5/1994	Moll et al.	5,554,124 A	9/1996	Alvarado
5,312,391 A	5/1994	Wilk	5,562,632 A	10/1996	Davila et al.
5,314,417 A	5/1994	Stephens et al.	5,562,677 A	10/1996	Hildwein et al.
5,316,541 A	5/1994	Fischer	5,562,688 A	10/1996	Riza
5,320,611 A	6/1994	Bonutti et al.	5,571,115 A	11/1996	Nicholas
5,330,437 A	7/1994	Durman	5,571,137 A	11/1996	Marlow et al.
5,330,486 A	7/1994	Wilk	5,575,799 A	11/1996	Bolanos et al.
5,330,497 A	7/1994	Freitas et al.	5,577,993 A	11/1996	Zhu et al.
5,331,975 A	7/1994	Bonutti	5,578,048 A	11/1996	Pasqualucci et al.
5,334,143 A	8/1994	Carroll	5,580,344 A	12/1996	Hasson
5,334,646 A	8/1994	Chen	5,584,850 A	12/1996	Hart et al.
5,336,192 A	8/1994	Palestrant	5,601,579 A	2/1997	Semertzides
5,336,708 A	8/1994	Chen	5,601,581 A	2/1997	Fogarty et al.
5,338,313 A	8/1994	Mollenauer et al.	5,603,702 A	2/1997	Smith et al.
5,342,315 A	8/1994	Rowe et al.	5,607,443 A	3/1997	Kieturakis et al.
5,342,385 A	8/1994	Norelli et al.	5,620,415 A	4/1997	Lucey et al.
5,350,364 A	9/1994	Stephens et al.	5,620,420 A	4/1997	Kriesel
5,353,786 A	10/1994	Wilk	5,628,732 A	5/1997	Antoon, Jr. et al.

Fig. 28





Fig. 29

Fig. 30




Fig. 31





Fig. 32







Fig. 35*Fig. 36*





Fig. 39







Fig. 40

Fig. 41



SURGICAL ACCESS APPARATUS AND METHOD**CROSS-REFERENCE TO RELATED APPLICATION**

This application is a continuation of U.S. application Ser. No. 12/360,710, filed Jan. 27, 2009, which is a continuation of U.S. application Ser. No. 11/244,647, filed Oct. 5, 2005, now U.S. Pat. No. 7,481,765, which is a continuation of U.S. application Ser. No. 10/381,220, filed Mar. 20, 2003, now U.S. Pat. No. 7,473,221, which is the National Phase application under 35 U.S.C. §371 of International Application No. PCT/US2001/029682, filed Sep. 21, 2001, which published in English as International Publication No. WO 2002/034108 A1 on May 2, 2002, which claims the benefit of U.S. application Ser. No. 60/241,958, filed Oct. 19, 2000, all of the disclosures of which are incorporated by reference.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

This invention relates generally to devices and other apparatus facilitating sealed access with surgical instruments, such as a surgeon's hand, across a body wall and into a body cavity.

2. Background of the Invention

In several areas of surgery there exists a need to have mechanisms or devices that can seal a body cavity or space, and yet permit the introduction of surgical instruments such as guidewires, endoscopes, and even the hand of a surgeon. Typical of these areas of surgery is laparoscopic surgery which relies on surgical instruments inserted through the abdominal wall to reach an operative site within the abdominal cavity. In order to increase space around the operative site within the cavity, insufflation gases are typically introduced to inflate the cavity and elevate the abdominal wall. This pressurizing of the abdominal cavity is referred to as pneumoperitoneum. In this context, the need to seal the body cavity or space arises from the need to maintain the pneumoperitoneum even when instruments are present.

Trocars have been commonly used to provide instrument access in laparoscopic surgeries. These trocars have included elaborate seal structures having zero seals which prevent escape of the gases in the absence of instruments, and instrument seals which prevent escape of the gases in the presence of instruments. Unfortunately, the instrument seals have been able to accommodate only a narrow range of instrument diameters. Where wider ranges were desired multiple seal pairs had to be provided.

Some instruments, such as the hand of the surgeon, have been too large for trocar access. Under these circumstances, hand-assisted laparoscopic seals have been provided. Such devices have been large, cumbersome, and largely ineffective in providing the required sealing mechanism. Other access devices, such as Touhy-Borst seals, have been used but only for very small diameter access such as that required by a guidewire.

Each of the prior devices suffers from drawbacks which make the device difficult or cumbersome to use. For example, a Touhy-Borst seal requires two hands to use and does not form a seal when a guidewire or other device is about to be introduced. Present trocar seals and hand-assisted seals require two valves, one forming an instrument seal in the presence of the instrument, and the other forming a zero seal in the absence of the instrument. For example, in hand-assisted devices, elaborate mechanisms have been required to

seal around the surgeon's arm. When the arm is removed, a separate zero seal has been required to prevent the escape of blood or insufflation gases.

SUMMARY OF THE INVENTION

These deficiencies of the prior art are overcome with the present invention which includes both a seal apparatus and a method for using this apparatus to perform elaborate surgeries. In one embodiment, the device includes a valve structure formed of a gel including, for example, a thermoplastic base such as KRATON (a trademark of Shell Corporation) and an oil. The resulting elastomer has an excellent tear strength, elongation greater than 1,000 percent, a very low durometer or hardness, and biocompatibility. A process for manufacturing this device is greatly simplified using molding techniques.

Importantly, the access device can function as both a zero seal and an instrument seal. Furthermore, it can accommodate a full range of instrument diameters, such as a range from two French in the case of a guidewire, to three or four inches in the case of a surgeon's hand. In addition, several instruments can be accommodated at the same time with a single access device.

Both tear resistance and sealing capability can be enhanced by encapsulating the gel in a sheath or otherwise providing circumferential reinforcement for the valve structure. Additives can be provided either on or in the gel to enhance properties such as lubricity, appearance, wound treatment and/or protection, anti-cancer protection and anti-microbial protection. Additional chemicals, compounds, pharmaceuticals or even mechanical devices can be mixed with or embedded in the gel material to vary chemical, pharmaceutical or physical properties of the access device.

These and other features and advantageous of the invention will be clarified with a description of preferred embodiments and reference to the associated drawings.

DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing a patient prone on an operating table with his abdomen insufflated, and with instrument access provided by trocars and the access device of the present invention;

FIG. 2 is an enlarged side elevation view of the access device of FIG. 1 operatively disposed exteriorly as the abdominal wall;

FIG. 3 is a side elevation view similar to FIG. 2 showing the access device operatively disposed interiorly of the abdominal wall;

FIG. 4 is a side elevation view similar to FIG. 2 showing the access device operatively disposed within an incision in the abdominal wall;

FIG. 5 is a plan view taken along lines 5-5 of FIG. 2;

FIG. 6 is a side elevation view similar to FIG. 2 and illustrating a further embodiment of the access device having an external flange and an internal flange;

FIG. 7 is a side elevation view similar to FIG. 6 and illustrating the hand of a surgeon being inserted through the access device;

FIG. 8 is an axially cross section view of the access device illustrated in FIG. 6;

FIG. 9 is a cross section view similar to FIG. 8 and illustrating an embodiment with circumferential reinforcement members;

FIG. 10 is an axial cross section view similar to FIG. 9 and illustrating a double-ring retractor with an access device of the present invention;

FIG. 11 is a radial cross section view similar to FIG. 8 and illustrating an embodiment having a lead-in cavity or pocket;

FIG. 12 is a top plan view of the embodiment illustrated in FIG. 11;

FIG. 13 is an axial cross section view taken along lines 13-13 of FIG. 12;

FIG. 14 is an axial cross section view taken along lines 14-14 of FIG. 12;

FIG. 15 is an axial cross section view similar to FIG. 13 and illustrating an embodiment with a duct-bill valve;

FIG. 16 is an axial cross-section view taken along lines 16-16 of FIG. 15;

FIG. 17 is a radial cross section view similar to FIG. 13 comprising a softer hand seal and a firmer base seal;

FIG. 18 is an axial cross section view taken along lines 18-18 of FIG. 17;

FIG. 19 is an axial cross section view of an embodiment having a lead-in cavity or pocket with a conical or funnel configuration;

FIG. 20 is a top plan view of the embodiment illustrated in FIG. 19;

FIG. 21 is an axial cross section view similar to FIG. 13 and showing another embodiment with a trapezoidal slit;

FIG. 22 is an axial cross section view taken along lines 22-22 of FIG. 21;

FIG. 23 is an axial cross section view similar to FIG. 22 taken along lines 23-23 of FIG. 21 and illustrating a slit having other than a perpendicular relationship to the plane of the pad;

FIG. 24 is a perspective view of a further embodiment of the access device having an opening formed by multiple slits angularly disposed and axially spaced relative to each other;

FIG. 25 is a side elevation view of an access device with a slit having a spiral configuration;

FIG. 26 is a top plan view of an access device having a spiral slit and axial channel;

FIG. 27 is a side elevation view of an embodiment having a spiral slit and a septum seal;

FIG. 28 is an axial cross section view of a further embodiment including a superelastic conical seal and a flexible base with annular spoke-like cams;

FIG. 29 is an axial cross section view taken along lines 29-29 of FIG. 22;

FIG. 30 is an axial cross section view taken along lines 30-30 of FIG. 22;

FIG. 31 is an axial cross section view similar to FIG. 28 and illustrating an embodiment including flappers;

FIG. 32 is a perspective exploded view of a further embodiment including a gel cap, a base, and a retraction sheath;

FIG. 33 is a top plan view of the gel cap of FIG. 32;

FIG. 34 is an axial cross section view taken along lines 34-34 of FIG. 33;

FIG. 35 is a top plan view of the base illustrated in FIG. 32;

FIG. 36 is an axial cross section view taken along lines 36-36 of FIG. 35;

FIG. 37 is a side elevation view of the retraction sheath illustrated in FIG. 32;

FIG. 38 is a side elevation view of a further embodiment of the retraction sheath;

FIGS. 39-42 illustrate progressive steps in a preferred method of use associated with the embodiment of FIG. 32;

FIG. 39 is a top plan view showing use of a template;

FIG. 40 is a top plan view of showing placement of the retraction sheath;

FIG. 41 is a top plan view showing placement of the base ring and securement of the traction sheath; and

FIG. 42 is an axial cross section view partially in section showing placement of the gel cap relative to the base.

DESCRIPTION OF PREFERRED EMBODIMENTS AND BEST MODE OF THE INVENTION

A patient is illustrated in FIG. 1 and designated generally by the reference numeral 10. The patient 10 is shown in a prone position on an operating table 12, where abdominal surgery is being performed by a surgeon 14 having an arm 16 and a hand 17. In the illustrated example, the operative procedure is performed within an abdominal cavity 18 with instrument access provided through an abdominal wall 21. In this type of operation, commonly referred to as laparoscopic surgery, trocars 23 and 25 are commonly used to provide minimally invasive access through the abdominal wall 21 for instruments such as a grasper 27 and an endoscope 30.

Although the specific focus of this disclosure will be on a preferred laparoscopic procedure, it will be noted that laparoscopic surgery is merely representative of a type of operation wherein a procedure can be performed in a body cavity with minimal access through a body wall.

Notwithstanding the foregoing generality, it is important to note that with respect to laparoscopic surgery, it is often desirable that the surgeon 14 be able to insert his/her hand 17 through the abdominal wall 21 and into the abdominal cavity 18. This insertion of the hand 17 provides the surgeon 14 with direct access to various elements of the anatomy.

In order to accommodate the hand 17 and arm 16 of the surgeon 14, a small incision 32 is typically created in the abdominal wall 21. An access device 34 of the present invention can be provided to further facilitate this access by the hand of the surgeon 14.

Particularly in the case of laparoscopic surgery, it is advantageous to insufflate the abdominal cavity 18 with a gas, such as carbon dioxide, in order to elevate the abdominal wall 21 and thereby increase the volume of the working space within the cavity 18. Maintenance of this insufflation pressure, commonly referred to as pneumoperitoneum, is particularly difficult where access is desired across the abdominal wall 21, for example, through the trocars 23, 25, as well as the access device 34. For this reason, a substantial effort has been directed to providing such access devices with sealing characteristics both in the presence of instruments and in the absence of instruments, such as the grasper 29, scope 30 and hand 27.

Thus, the trocars 23 and 25 have typically been provided with complex valve structures, including, for each narrow range of instrument sizes, an instrument valve which forms an instrument seal in the presence of an instrument, and a zero valve which forms a zero seal in the absence of an instrument. By providing both an instrument seal and a zero seal the valve structures have been able to inhibit the escape of gases through the trocars both in the presence and the absence of an instrument, respectively.

The instrument seals have been particularly cumbersome, as noted, and have only been effective for a small range of instrument diameters. For example, separate instrument seals have been needed for instruments, such as guidewires, which may have a diameter of only two French to three French. For medium-sized instruments having diameters of three millimeter to five millimeters, a second instrument seal has been required. In some cases, even a third instrument seal has been necessary in order to accommodate instruments having diameters such as nine millimeters to 12 millimeters.

Typically the varying sizes of instruments have also required individual zero seals for each range. Thus, in a complex trocar, such as the trocar 23, there might be as many as six separate seals associated with the access device.

If not for the desire to maintain the pneumoperitoneum, there would be no need for the trocars 23, 25 or the access device 34. One would merely cut an incision in the abdominal wall 21 and insert the instrument directly through the incision. However, without appropriate valves or seals, the insufflation gases would merely escape through the incisions. This would be particularly detrimental in the case of the incision 32 which must be sufficiently large to accept the hand 17 of the surgeon 14. Thus it is a primary purpose of the access device 34 to form with the incision 32 an access or working channel 34, and to provide a valve or other sealing structure across the working channel 34 in order to maintain the pneumoperitoneum.

An enlarged view of one embodiment of the access device 34 is illustrated in FIG. 2 which also shows the abdominal wall 21 and the incision 32. In this simple form, the access device 34 has the general configuration of a pad 35, meaning that it is generally flat and disposed in a plane such as the plane 38. Typically parallel to this plane 38 are a pair of major surfaces of 41 and 43 which provide the pad 35 with a substantial surface area. An opening or slit 45 can be formed through the pad 35, generally along an axis 47 perpendicular to the plane 38.

When operatively disposed, the opening 45 of the pad 35 is in communication with the incision 32 and, in this case, forms with the incision 32, the working channel 36. The alignment of the opening 45 and incision 32 can occur with the pad 35 disposed exteriorly of the abdominal wall as illustrated in FIG. 2, interiorly of the abdominal wall 21 as illustrated in FIG. 3, or within the abdominal wall 21 as illustrated in FIG. 4. In any of these positions, operative disposition of the pad 35 relative to the abdominal wall 21 requires that the pad 35 be maintained in its operative position and that it form a seal around the incision 32. Referring to the plan view of FIG. 5, these two functions are accomplished with an adhesive 50 disposed around the incision 32 between the pad 35 and the abdominal wall 21.

If this adhesive 50 is formed as a continuous ring 52, as illustrated in FIG. 5, the pad 35 can be disposed with the ring 52 positioned circumferentially around the incision 32 to form a seal between the pad 35 and the abdominal wall 21. In the illustrated example, when the pad 35 is operatively positioned, the escape of insufflation gases is inhibited between the pad 35 and the abdominal wall 21 by the adhesive ring 52.

The escape of insufflation gases is inhibited through the opening 45 of the pad 35 by the self-sealing characteristics of the material forming the pad 35. This material and its highly advantageous properties are discussed in significant detail below.

It will be appreciated that the functions of the adhesive ring 52 can be accomplished in many different ways using many different materials and shapes. For example, many materials other than adhesives can be used to maintain the pad 35 in position over the incision 32. The formation of a seal around the incision 32 can also be accomplished with methods other than adhesion. Furthermore, the shape of the continuous seal formed by the adhesive 50 need not be in the shape of a circle. Rather, any continuous pattern sufficiently large to form a perimeter around the incision 32 could facilitate the desired sealing relationship. Finally, it will be noted that the mere placement of the pad 35, for example, interiorly of the abdominal wall 21 as illustrated in FIG. 3, may produce a perimeter seal merely as a result of the insufflation pressure.

A further embodiment of the access device 34 is illustrated in FIG. 6 where elements of structure similar to those previously disclosed or designated with the same reference numeral followed by the lower case "a." In this embodiment, the functions of position-maintenance and sealing are accomplished with an alternative configuration for the access device itself. The pad 35 in this case is disposed within the incision 32 as illustrated in FIG. 4. However, an external flange 54 and an internal flange 56 are formed integral with the pad 35.

When operatively disposed, the external flange 54 is positioned outside of the abdominal wall 21 while the internal flange 56 is disposed interiorly of the abdominal wall 21a. In this matter, the pad 35 can be disposed within the incision 32a and held in position by the flanges 54, 56. When the hand 17 of the surgeon 14 is inserted through the access device 34, the exterior flange 54 prevents the pad 35a from moving distally. Similarly, when the hand 17 of the surgeon 14 is withdrawn, the interior flange 56 prevents the pad 35a from moving proximally.

In this embodiment, the opening 45a extends through the pad 35a as well as the flanges 54 and 56, and completely defines the working channel 34 through the incision 32.

The primary seal which is required between the access device 34a and the abdominal wall 21, can be formed with the adhesive ring 52a as discussed with reference to FIG. 6. Alternatively, this embodiment including the interior flange 56 may rely merely upon the surface contact between the flange 56a and the abdominal wall 21. In this case, the primary seal can be formed between these structural elements and enhanced by the pneumoperitoneum pressure which forces the interior flange 56 against the abdominal wall as illustrated by a plurality of arrows 58. This seal is formed primarily in a radial plan generally perpendicular to the axis 47.

The function of the primary seal may be further enhanced by additional sealing which occurs between the pad 35a and the portions of the abdominal wall 21 forming the incision 32. In this location, the abdominal wall 21 is radially compressed by the mere presence of the pad 35 within the incision 32. The resulting pressure produces an axial seal between the pad 35a and the abdominal wall 21.

If the adhesive ring 52a is desired for this embodiment, it is most advantageously placed around the incision 32, between the exterior flange 54 and the abdominal wall 21.

It will be noted that whenever an instrument, such as the arm 16 or hand 17 of the surgeon 14, is inserted through the pad 35, the material of the pad conforms to the surface of the instrument and forms the instrument seal with the instrument. Accordingly, during the entire period beginning with insertion of the instrument and ending with withdrawal of the instrument, there is substantially no loss of insufflation gas through the pad 35a nor any loss of pneumoperitoneum within the abdominal cavity 18.

With further reference to FIG. 7, it will be appreciated that the arm 16 and hand 17 of the surgeon 14 are merely examples of instruments which can be inserted through the access device 34a. In the absence of the instrument, or hand 17 in the case of FIG. 7, the opening or slit 45a merely closes against itself to form a zero seal, thus preventing the escape of insufflation gases through the access device 34a. When the instrument, such as the hand 17, is inserted through the opening or slit 45a, an instrument seal is formed between the material of the access device 34a and the exterior surface of the instrument. This prevents the escape of insufflation gases through the access device 34a, even when an instrument is present. Thus, insufflation pressures can be maintained within the abdominal cavity 18 whether or not the instrument is in place.

5,632,284 A	5/1997	Graether	5,904,703 A	5/1999	Gilson
5,632,979 A	5/1997	Goldberg et al.	5,906,577 A	5/1999	Beane et al.
5,634,911 A	6/1997	Hermann et al.	5,913,847 A	6/1999	Yoon
5,634,936 A	6/1997	Linden et al.	5,916,198 A	6/1999	Dillow
5,634,937 A	6/1997	Mollenauer et al.	5,916,232 A	6/1999	Hart
5,636,645 A	6/1997	Ou	5,919,476 A	7/1999	Fischer et al.
5,640,977 A	6/1997	Leahy et al.	5,931,832 A	8/1999	Jensen
5,643,301 A	7/1997	Mollenauer	5,947,922 A	9/1999	MacLeod
5,649,550 A	7/1997	Crook	5,951,467 A	9/1999	Picha et al.
5,651,771 A	7/1997	Tangherlini et al.	5,951,588 A	9/1999	Moenning
5,653,705 A	8/1997	de la Torre et al.	5,957,888 A	9/1999	Hinchiffe et al.
5,657,963 A	8/1997	Hinchliffe et al.	5,957,913 A	9/1999	de la Torre et al.
5,658,272 A	8/1997	Hasson	5,962,572 A	10/1999	Chen
5,658,306 A	8/1997	Kieturakis	5,964,781 A	10/1999	Mollenauer et al.
5,662,615 A	9/1997	Blake, III	5,976,174 A	11/1999	Ruiz
5,672,168 A	9/1997	de la Torre et al.	5,989,232 A	11/1999	Yoon
5,681,341 A	10/1997	Lunsford et al.	5,989,233 A	11/1999	Yoon
5,683,378 A	11/1997	Christy	5,989,266 A	11/1999	Foster
5,685,854 A	11/1997	Green et al.	5,993,471 A	11/1999	Riza et al.
5,685,857 A	11/1997	Negus et al.	5,993,485 A	11/1999	Beckers
5,697,914 A	12/1997	Brimhall	5,994,450 A	11/1999	Pearce
5,707,703 A	1/1998	Rothrum et al.	5,997,515 A	12/1999	de la Torre et al.
5,709,664 A	1/1998	Vandenbroek et al.	6,004,303 A	12/1999	Peterson
5,713,858 A	2/1998	Heruth et al.	6,010,494 A	1/2000	Schafer et al.
5,713,869 A	2/1998	Morejon	6,017,355 A	1/2000	Hessel et al.
5,720,730 A	2/1998	Blake, III	6,018,094 A	1/2000	Fox
5,725,536 A	3/1998	Oberlin et al.	6,024,736 A	2/2000	de la Torre et al.
5,728,103 A	3/1998	Picha et al.	6,025,067 A	2/2000	Fay
5,730,748 A	3/1998	Fogarty et al.	6,033,426 A	3/2000	Kaji
5,735,791 A	4/1998	Alexander et al.	6,033,428 A	3/2000	Sardella
5,738,628 A	4/1998	Sierocuk et al.	6,035,559 A	3/2000	Freed et al.
5,741,234 A	4/1998	Aboul-Hosn	6,042,573 A	3/2000	Lucey
5,741,298 A	4/1998	MacLeod	6,045,535 A	4/2000	Ben Nun
5,743,884 A	4/1998	Hasson et al.	6,048,309 A	4/2000	Flom et al.
5,749,882 A	5/1998	Hart et al.	6,050,871 A	4/2000	Chen
5,755,660 A	5/1998	Tyagi	6,053,934 A	4/2000	Andrews et al.
5,760,117 A	6/1998	Chen	6,059,816 A	5/2000	Moenning
5,769,783 A	6/1998	Fowler	6,066,117 A	5/2000	Fox et al.
5,782,812 A	7/1998	Hart et al.	6,068,639 A	5/2000	Fogarty et al.
5,782,817 A	7/1998	Franzel et al.	6,077,288 A	6/2000	Shimomura
5,782,859 A	7/1998	Nicholas et al.	6,086,603 A	7/2000	Termin et al.
5,788,676 A	8/1998	Yoon	6,090,043 A	7/2000	Austin et al.
5,792,119 A	8/1998	Marx	6,099,506 A	8/2000	Macoviak et al.
5,795,290 A	8/1998	Bridges	6,110,154 A	8/2000	Shimomura et al.
5,803,919 A	9/1998	Hart et al.	6,123,689 A	9/2000	To
5,803,921 A	9/1998	Bonadio	6,142,935 A	11/2000	Flom et al.
5,803,923 A	9/1998	Singh-Derewa et al.	6,142,936 A	11/2000	Beane et al.
5,807,350 A	9/1998	Diaz	6,149,642 A	11/2000	Gerhart et al.
5,810,712 A	9/1998	Dunn	6,150,608 A	11/2000	Wambeke et al.
5,810,721 A	9/1998	Mueller et al.	6,159,182 A	12/2000	Davis
5,813,409 A	9/1998	Leahy et al.	6,162,172 A	12/2000	Cosgrove et al.
5,814,026 A	9/1998	Yoon	6,162,196 A	12/2000	Hart et al.
5,817,062 A	10/1998	Flom et al.	6,162,206 A	12/2000	Bindokas
5,819,375 A	10/1998	Kastner	6,163,949 A	12/2000	Neuenschwander
5,820,555 A	10/1998	Watkins, III et al.	6,164,279 A	12/2000	Twedde
5,820,600 A	10/1998	Carlson et al.	6,171,282 B1	1/2001	Ragsdale
5,830,191 A	11/1998	Hildwein et al.	6,183,486 B1	2/2001	Snow et al.
5,832,925 A	11/1998	Rothrum	6,197,002 B1	3/2001	Peterson
5,836,871 A	11/1998	Wallace et al.	6,217,555 B1	4/2001	Hart et al.
5,841,298 A	11/1998	Huang	6,217,590 B1	4/2001	Levinson
5,842,971 A	12/1998	Yoon	6,224,612 B1	5/2001	Bates et al.
5,848,992 A	12/1998	Hart et al.	6,228,063 B1	5/2001	Aboul-Hosn
5,853,395 A	12/1998	Crook et al.	6,238,373 B1	5/2001	de la Torre et al.
5,853,417 A	12/1998	Fogarty et al.	6,241,768 B1	6/2001	Agarwal et al.
5,857,461 A	1/1999	Levitsky et al.	6,254,533 B1	7/2001	Fadem et al.
5,860,995 A	1/1999	Berkelaar	6,254,534 B1	7/2001	Butler et al.
5,865,728 A	2/1999	Moll et al.	6,258,065 B1	7/2001	Dennis et al.
5,865,729 A	2/1999	Meehan et al.	6,264,604 B1	7/2001	Kieturakis et al.
5,865,807 A	2/1999	Blake, III	6,267,751 B1	7/2001	Mangosong
5,865,817 A	2/1999	Moenning et al.	6,276,661 B1	8/2001	Laird
5,871,474 A	2/1999	Hermann et al.	6,287,280 B1	9/2001	Lampropoulos et al.
5,876,413 A	3/1999	Fogarty et al.	6,315,770 B1	11/2001	de la Torre et al.
5,879,368 A	3/1999	Hoskin et al.	6,319,246 B1	11/2001	de la Torre et al.
5,882,344 A	3/1999	Stouder, Jr.	6,322,541 B2	11/2001	West
5,884,639 A	3/1999	Chen	6,325,384 B1	12/2001	Berry, Sr. et al.
5,894,843 A	4/1999	Benetti et al.	6,346,074 B1	2/2002	Roth
5,895,377 A	4/1999	Smith et al.	6,371,968 B1	4/2002	Kogasaka et al.
5,899,208 A	5/1999	Bonadio	6,382,211 B1	5/2002	Crook
5,899,913 A	5/1999	Fogarty et al.	6,383,162 B1	5/2002	Sugarbaker

Note that these seals, the zero seal and the abdominal seal, can be formed as a single valve structure having properties for accommodating a full range of instrument sizes.

Formation of the pad **35a** will typically be accomplished in a simple molding process described in greater detail below. In such a process, the opening or slit **45a** may be formed as part of the molding process.

In most cases, the single access opening **45a** will be sufficient to accommodate the operative procedure. However, a further advantage of the access device **34a** will be particularly appreciated by the surgeon **14** who requires even more access through the pad **35a**. Consider for example, the surgeon **14** having his/her arm **16** inserted through the opening **45a** when he/she decides that a further instrument is required for the operative procedure. Under these circumstances, a further opening through the pad **35a** can be established by merely inserting the desired operative instrument through the pad **35a**. In this manner, the instrument can create its own access hole beside the primary opening **45a**.

Particularly for those operative instruments having pointed distal ends, the instrument can merely be forced through the pad **35a** forming its own access hole, such as the opening **45a**, as it is moved distally. This opening, created by the operative instrument itself, would automatically form an instrument seal as the instrument is inserted, as well as a zero seal as the instrument is withdrawn.

For operative instruments not having pointed distal ends, it is possible to form a new access hole using a secondary instrument, such as a trocar obturator. After the access hole is formed, the obturator can be removed, vacating the access hole to receive the operative instrument. Throughout this process of initially forming an access hole and ultimately inserting an operative instrument through the hole, both zero seals and instrument seals are formed to maintain the pneumoperitoneum.

With the advantages associated with 1) the formation of an instrument seal and a zero seal with a single valve accommodating a wide range of diameters, and 2) the formation of an instrument opening using the instrument itself, it will be appreciated that the concept of this invention will typically be embodied with a structure that is particularly dependent upon the material which forms the access device **34**. In a preferred embodiment, the pad **35** is formed of a KRATON/oil mixture including a KRATON Tri-block with a Styrene-Ethylene/Butylene-Styrene (S-E/B-S) structure in combination with a mineral oil. Other tri-block polymers can be used for this application such as Styrene-Isoprene-Styrene, (S-I-S), Styrene-Butadiene-Styrene (S-B-S), Styrene-Ethylene/Propylene-Styrene (S-E/P-S) manufactured under the trademark SEPTON by the Kuraray Co. These general formulas can be further distinguished by the ratio of the styrene to rubber content: for example, Grade 1650 is a S-E/B-S tri-block with a 29/71 styrene to rubber ratio.

In addition to tri-blocks there are also di-block versions of these materials where styrene is present at only one end of the formula, for example, Styrene-Ethylene/Butylene (S-E/B) di-block.

The various base formulas may also be alloyed with one another to achieve a variety of intermediate properties. For example KRATON G1701X is a 70% S-E/B 30% S-E/B-S mixture with an overall Styrene to rubber ratio of 28/72. It can be appreciated that an almost infinite number of combinations, alloys, and Styrene to rubber ratios can be formulated, each capable of providing advantages to a particular embodiment of the invention. These advantages will typically include low durometer, high elongation, and good tear strength.

It is contemplated that the material of the pad **35** may also include silicone, soft urethanes and even harder plastics which might provide the desired sealing qualities with the addition of a foaming agent. The silicone materials can be of the types currently used for electronic encapsulation. The harder plastics may include PVC, Isoprene, KRATON neat, and other KRATON/oil mixtures. In the KRATON/oil mixture, for example, oils such as vegetable oils, petroleum oils and silicone oils might be substituted for the mineral oil. In the broadest sense, all of these mixtures can be described generally as a gel. The gel will typically have properties including an ability to "flow" which approaches that of a fluid. Particularly in the vicinity of any opening or slit **45** extending through the access device **34**, propagation of the opening may be of concern. Stresses resulting from the presence of an instrument will be concentrated at the ends of such an opening or slit. For this reason, a good tear resistance is desired for the gel material. Such a tear resistance is often inherent in the KRATON/oil mixtures and may be enhanced by encapsulating the gel in other materials. For example, a low tear resistant gel could be encapsulated in a urethane sheath to improve the tear resistant qualities of the resulting products. Such a sheath need not be elastic but could be comprised, for example, of overlapping sheets of a non-elastic material.

Any of the gel materials contemplated could be modified to achieve different properties such as enhanced lubricity, appearance, and wound protection, or to provide anti-cancer or anti-microbial activity. Additives can be incorporated directly into the gel, for example in the case of pharmaceuticals, or applied as a surface treatment to the gel, for example, to improve lubricity or appearance. Other compounds could be added to the gel to modify its physical properties or to assist in subsequent modification of the surface by providing bonding sites or a surface charge. Antioxidants and antirads can be added to the mixture to extend the shelf life of the finished product or increase its ability to withstand radiation sterilization.

Sealing materials used in medical access devices of the past have been chosen primarily for their durometer and elongation. It is these properties which measure the ability of the material to move into small spaces and crevices as may be required to form an instrument seal across the working channel of a trocar. For example, in the past, a silicone mixture was used in medical valves. This mixture had the following properties: an ultimate elongation less than about 1000 percent and a durometer not less than about 5 Shore A.

These properties of the prior art materials are far exceeded by the properties associated with the present invention which in some respects provide a full magnitude of advantage. In fact, the difference between the materials of the prior art and the materials of the present invention are sufficiently substantial, that it is perhaps misleading to refer to the present material as merely a gel. According, the material of the present invention, having properties including an ultimate elongation greater than about 1000 percent and a durometer less than about 5 Shore A, will be referred to herein as an "ultragel."

In a preferred embodiment of the present invention, the ultragel includes KRATON and mineral oil and provides a sealing material with the following properties: an ultimate elongation exceeding about 1500 percent, and a durometer of less than about 200 Bloom. The durometer in this case is considerably lower than that of the prior art materials. In fact, the durometer of the present material is so soft it cannot even be measured on the Shore A scale.

The resulting elongation and durometer of the present material facilitates its use with as an access valve which is capable of forming seals with a full range of instrument sizes,

but is also capable of functioning as a zero seal. Whereas access devices of the prior art may have required as many as six separate seals in order to accommodate a full range of instrument sizes, access devices can now be made with only a single valve formed of the ultragel material.

In a typical manufacturing process, the KRATON G1651 is mixed with the mineral oil in a ratio by weight of 1 to 9. In order to manufacture this material, the combination is heated to a temperature of about 200° centigrade. In a preferred method of manufacturing, the mold is provided with a circumferential ring insert which is molded into the gel, and slit inserts which can be removed from the gel to form the opening or slit 45. The resulting gel can be coated with cornstarch to reduce tack and cooled at room temperature.

Many of the properties of the KRATON/oil mixture will vary with adjustments in the weight ratio of the components. In general, the greater the percentage of mineral oil, the more fluid the mixture; the greater the percentage of KRATON, the more rigid the material. Weight ratios of KRATON to oil as low as 1 to 5 have been contemplated for a more rigid structure. As the KRATON/oil weight ratio approaches 1 to 10, the mixture becomes more liquid. Ratios as high as 1 to 15 have been contemplated for this invention.

The processing temperature can also vary considerably as it is primarily dependent on the type of KRATON used. Temperatures in a range of about 150° centigrade to about 250° centigrade have been contemplated.

With an appreciation that these ratios and temperatures can develop considerably different properties, it is now apparent that these materials can be layered to provide generally different properties within each layer. For example, an outer layer might be formed of a KRATON/oil mixture having more rigid properties, thereby providing the pad 35 with an outer layer that is more rigid. After that layer is at least partially cured, another layer of the material can be poured inside of the outer layer. This second layer might be softer providing the pad 35 with the significant sealing properties. It has been found that successive layers will tend to fuse slightly at their interface, but will generally maintain their separate identities. Additional layers could be added to provide a progression of properties in a particular device.

Having discussed the properties desirable for the gel material, and the process of manufacture, one can now address the other embodiments of the concept which may provide additional advantages for particular surgical procedures. An embodiment of the access device 34, shown in its operative position in FIG. 6, is illustrated by itself in the axial cross section view of FIG. 8.

This same embodiment can be reinforced with o-rings 61 and 63 as illustrated in FIG. 9 where elements of structure are designated by the same reference number followed by the lower case letter "b." Providing these o-rings 61 and 63 may facilitate several functions associated with the access device 34b. For example, the rings 61, 63 will typically aid in maintaining a radial sealing pressure on all sides of the opening 45b. The rings 61 and 63 will also tend to maintain the flanges 54b and 56b respectively, in their generally planar configurations. This further ensures that the flanges 54, 56 will not collapse into the incision 32 with the insertion or withdrawal of an instrument, such as the surgeon's hand 17. Of course, the o-rings 61 and 63 must be sufficiently large to accommodate the instrument during insertion and removal.

A further embodiment of the invention is illustrated in FIG. 10, where elements of structure are similar to those previously disclosed are designated with the same reference numerals followed by the lower case letter "c." This embodiment includes the pad 35c with the opening or slit 45c. The

external perimeter o-ring 61c is inserted molded into the circumference of the pad 35c. The internal o-ring 63c is coupled to the pad 35c, for example, by way of attachment to the o-ring 61c for example, by a membrane 65. In this case, the membrane 65 has a generally cylindrical configuration and elastomeric properties. In preferred embodiments, the membrane 65 is formed of urethane, neoprene or isoprene.

When the embodiment of FIG. 10 is being operatively positioned, the internal o-ring 63b is initially gathered and inserted through the incision 32 (FIG. 2). The pad 35c and external o-ring 61c are left outside the incision 32 so that the only material extending across the incision 32 is the membrane 65. It will be noted that in this case, the working channel 36c is formed by the slit 45c, the cylindrical membrane 65, and the internal o-ring 63c.

In this particular embodiment, the pad 35c functions generally as described with reference to FIG. 2. The primary seal between the pad 35c and the abdominal wall 21 can be formed either with a circumferential ring, such as the adhesive ring 52c, or by relying on the sealing characteristics of the insufflation gas 58c against the internal o-ring 63c and membrane 65.

This embodiment of FIG. 10 is of particular advantage as it incorporates the pad 35c in perhaps its simplest configuration, while providing a primary seal between the device 34c and the abdominal wall 21 which is facilitated by the insufflation pressure. Furthermore, the membrane 65 enhances the sealing characteristics of the device 34c, and provides a lining for the incision 32. With the membrane 65, the incision 32 need not be stretched to a diameter greater than that required by any instrument inserted through the working channel 36c.

A further embodiment of the invention is illustrated in FIG. 11 where elements of structure similar to those previously disclosed are designated with the same reference numeral followed by the lower case letter "d." This embodiment is similar to that of FIG. 8 in that it includes the pad 35b, slit 45d, exterior flange 54d, and internal flange 56d. The embodiment of FIG. 11 differs from that of FIG. 8 in that it includes a lead-in cavity 70 which is in communication with the slit 45d.

In a preferred embodiment, this cavity 70 is sized and configured to receive the arm 16 of the surgeon 14 in a manner illustrated in FIG. 7. In this case, the slit 45d would function primarily to maintain a zero seal, while the portions of the pad 35d or flange 54d which form the cavity 70 would function primarily to form the instrument seal.

A further embodiment of the invention is illustrated in the plan view of FIG. 12 and the cross section views of FIGS. 13 and 14. In this embodiment, elements of structure similar to those previously discussed are designated with the same reference numeral followed by the lower case letter "e." In this case, the lead-in cavity has the general shape of a cylinder 72 with an axis that is collinear with the axis 47e of the pad 35e.

As perhaps best illustrated in FIG. 13, the slit 45e has a trapezoidal configuration. Thus, it begins proximally with a narrow length which may generally be equivalent to the diameter of the cylinder 32. From the cavity 70e, the length of the slit 45e increases with progressive positions distally through the pad 35e. In the illustrated embodiment, the trapezoidal slit 45e is formed as the frustum of an isosceles triangle.

A further embodiment of the invention is illustrated in FIGS. 15 and 16 wherein elements of structure similar to those previously described are designated with the same reference numeral followed by the lower case letter "f." As previously discussed with reference to FIG. 12, this embodiment of the pad 35f is formed with a proximal surface 71 and a distal surface 73. The pad 35f also includes the coaxial lead-in cylinder 72f and the trapezoidal slit 45f. However, in

this case, a duck-bill valve **74** is provided to further enhance the characteristics of the zero seal. As illustrated, the working channel **36f** is formed by the lead-in cavity **70f**, the slit **45f**, and an extension of the slit **45f** which is defined by the duck-bill valve **74f**.

The duck-bill valve **72** can be formed with opposing flanges **76** and **78** which extend distally of the distal surface **73**. When operatively disposed, the pad **35f** can be positioned with its distal surface **73** against the exterior surface of the abdominal wall **21** (FIG. 2) and with the flanges **76** and **78** extending into the incision **32**. With this configuration and operative disposition, the abdominal wall **21** at the incision **32** will produce opposing forces on the flanges **76** and **78** which tend to close the slit **45f**, particularly in the absence of an instrument. In this manner, the duck-bill valve **74** can be relied on to enhance the characteristics of the zero seal.

A further embodiment of the invention is illustrated in FIGS. 17 and 18 wherein elements of structure similar to those previously discussed are designated by the same reference numeral followed by the lower case letter "g." In this embodiment of the access device **34g**, the pad **35g** can be formed generally as discussed with reference to FIG. 13. In this embodiment, however, the pad **35g** can be enclosed along its sides and the distal surface **73g**, by a base **81**. In this case, the pad **35g** might be formed by the highly elastic material previously discussed, while the base **81** might be formed of a more rigid but nevertheless flexible material such as a urethane. With this configuration, the duck-bill valve **74f** would be structured to extend distally of a distal surface **83** associated with the base **81**. This would enable the duck-bill valve **74f** to be formed of the base material rather than the super-elastic material. This might also improve the zero seal characteristics for particular operative applications.

Another simplified form of the invention is illustrated in FIGS. 19 and 20, where elements of structure similar to those previously discussed or designated with the same reference numeral followed by the lower case letter "h." The lead-in cavity **78h**, in this case, is formed as an inverted cone **77** having its base at the proximal surface **71h** and its apex in proximity to the distal surface **73h**. Thus, the lead-in cavity **70h** has an area in radial cross section which decreases with progressive positions distally through the pad **35h**. In this embodiment, the proximal regions near the base of the cone **87** form the instrument seal, while the distal regions at the apex of the cone form the zero seal. The conical configuration of the lead-in cavity **70h** also tends to funnel an instrument into the opening **45h** leading distally to the apex of the cone **87**.

It will be appreciated generally, that the slit **45** and lead-in cavity **70** can be provided with many different individual and cooperative configurations. By way of example, perhaps the simplest form for the pad **35** is illustrated in the embodiment of FIGS. 21 and 22 wherein elements of structure similar to those previously described are designated by the same reference numeral followed by the lower case letter "j." In this embodiment, the pad **35j** with its proximal surface **71j** and distal surface **73j**, is provided with a simple trapezoidal slit **45j**. In this case, the slit **45j** extends between the proximal surface **71j** and the distal surface **73j**.

The slit **45j** in this embodiment of FIG. 21 is typical of many structures which will define the slit **45j** with a planar configuration. In such a case, the portions of the pad **35j** which form the slit will comprise opposing planar surfaces such as those designated by the reference numerals **90** and **92** in FIG. 22.

It will be apparent that the slit **45** need not be formed by opposing surfaces having a planar configuration. Neverthe-

less, these opposing surfaces need to be capable of coming into sealing contact with each other in order to establish the zero seal. Other slit configurations capable of accomplishing this function, may offer further advantages in particular procedures. Other examples of slit configurations are illustrated merely by way of example in FIGS. 23-26.

The embodiment of FIG. 23 is similar to that of FIG. 22 in that the opening **45j** comprises a single slit which extends from the proximal surface **71j** to the distal surface **73j**. In the case of the FIG. 22 embodiment, the axis **47j** is disposed within the plane of the slit **45j**. In the case of the FIG. 23 embodiment, the plane of the slit **45j** does not include the axis **47j**. Rather, the slit **45j** is formed in a plane which has an angular relationship with the axis **47j**, the proximal surface **71j**, as well as the distal surface **73j**. This construction enables the slit **45j** to have a length greater than the thickness of the pad **35j**.

In the embodiment of FIG. 24, elements of structure similar to those previously discussed are designated with the same reference numeral followed by the lower case letter "k." In this case, the opening **45k** is configured as two slits **94** and **96** formed in individual planes that are angularly spaced with respect to each other. Of course, two or more of the planar slits **94** and **96** may be equally angularly spaced around the axis **47k**. In one embodiment, the individual planar slits **94** and **96** intersect at the axis **47k**. Alternatively, the slits **94** and **96** may be axially spaced in order to facilitate formation of the instrument seal.

In the embodiment of FIG. 25, elements of structure similar to those previously discussed are designated with the same reference numeral followed by the lower case letter "m." In this embodiment, the opening **45m** is defined as a slit **98** having a curved rather than planar configuration. In the illustrated embodiment, the curved slit **98** is formed as a spiral around the axis **47m**. Along the axis **47m**, the opposing surfaces forming the spiral slit **98** can "flow" into sealing proximity in order to produce the zero seal.

FIG. 26 illustrates a similar embodiment including a spiral slit. In this figure, elements of structure similar to those previously discussed are designated by the same reference numeral followed by the lower case letter "n." The spiral slit **98n** in this embodiment is also formed around the axis **47n** of the pad **35n**, but in this case the portions forming the slit **98n** do not extend completely to the axis **47n**. As a result, an axial channel **100** is formed at least partially along the axis **47n**. This channel **100** can function in a manner similar to the lead-in cavity **70** discussed with reference to FIGS. 11-12. This channel **100** can even be formed with a conical configuration similar to that discussed with reference to FIG. 19.

In an embodiment where the channel **100** is left open, a zero seal might be provided by positioning a septum valve across the channel **100**. Such an embodiment is illustrated in FIG. 27, wherein the septum valve is designated with a reference numeral **101** and the other elements of structure similar to those previously discussed are designated with the same reference numerals followed by the lower case letter "p." Thus the embodiment of FIG. 27 includes the spiral slit **98p**, the pad **35p**, and the axis **47p**. This embodiment of FIG. 27 is merely representative of many other embodiments that will combine a slit, such as the slit **98p**, with other valve structures, such as the septum valve **101**.

Other curved slit configurations would include embodiments wherein the slit is curved, sinusoidal, or S-shaped in a side elevation view. Such configurations provide a slit part having a length greater than the thickness of the pad. Normally, the more circuitous the slit path, the better the sealing characteristics.

A further and more complex configuration for the opening 45 is illustrated in the embodiment of FIG. 28 wherein elements of structure similar to those previously disclosed are designated with the same reference numeral followed by the lower case letter "q." This embodiment is representative of many other complex embodiments which can be formed with intricate shapes and different materials in order to accomplish the desirable function of forming, with a single valve, a zero seal as well as an instrument capable of accommodating a full range of instrument sizes. In the embodiment of FIG. 28, the pad 35q is formed with a base 110 which is disposed circumferentially of a core 112. In this case, the core 112 is formed of the superelastic material or gel and provided with the shape of the cone 87q as discussed with reference to FIGS. 19 and 20. The base 110 is formed from a material that may not be elastic, but preferably is flexible. In the preferred embodiment, the base 110 is formed of a urethane.

In this construction, the base 110 is provided with a plurality of spokes 114 each of which extends radially inwardly from a base 116 to a tip 118. The core 112 extends from the axis 47q outwardly to the tips 118 of the spokes 114. In the illustrated embodiment, the core 112 has fingers 121 which extend beyond the tips 118 and toward the bases 116 between each adjacent pair of the spokes 114. These fingers 121 extend radially outwardly to an end surface 123 which stops short of the base 116 leaving a void 125 therebetween.

The voids 125 are of particular interest to this embodiment and can be incorporated into any of the embodiments previously discussed. Such voids 125 provide a space or absence of material into which the highly elastic material, such as that of the fingers 121, can expand during insertion of an instrument such as the arm 16 (FIG. 7). Since the gel material is almost fluid in its properties, the voids 125 permit expansion of the gel with very little resistance. Voids, such as the voids 125 in the embodiment of FIG. 28, can be defined solely in the gel material or between the gel material and any other base material.

In the case of FIG. 28, the spokes 114 and fingers 121 are defined generally in planes which are parallel to the axis 47q. Similar fingers, illustrated in the embodiment of FIG. 31 are defined generally in a plane which is perpendicular to the axis. In this embodiment, elements of structure similar to those previously disclosed are designated by the same reference numeral followed by the lower case letter "r." As illustrated, the pad 35r can be formed with a relatively large opening 45r having the configuration of a coaxial cylinder 130. A plurality of fingers or flaps 132 extend into the opening 45r and tend to form a lead-in cavity 70r with properties such as those discussed with reference to FIG. 19. In this case, the annular flaps 132 have a conical configuration extending from a base 134 to an apex 136. It will be noted that the areas between the flaps 132, form voids 125r into which the flaps 132 can be displaced upon insertion of an instrument, such as the arm 16.

A further embodiment of the invention is illustrated in FIG. 32 where elements of structure similar to those previously disclosed are designated with the same reference numeral followed by the lower case letter "s." This exploded view of the access device 34s includes not only the pad 35s but also a complimentary structure for maintaining the position of the pad 35s, for forming a seal between the pad 35s and the abdominal wall 21, and for dilating the incision 32 to a variable extent as required by the surgeon 14. In this case, the access device 34s includes three components, a gel cap 143, base 145, and a retraction sheath 147.

The gel cap 143 includes not only the gel pad 35s, but also a circumferential cap ring 154 which can be inserted and

molded to the pad 35s. The resulting gel cap 143 forms a seal with the base 145, thereby defining the working channel 36s through the pad 35s, the cap ring 154, the base 145, and the retraction sheath 147. In the manner previously discussed, this working channel 36s includes the single valve formed by the gel pad 35s which provides both a zero seal and an instrument seal for a wide range of instrument diameters.

The structure associated with the gel cap 143 is described in greater detail with reference to FIGS. 33 and 34. In the plan view of FIG. 33, it can be seen that this embodiment includes the gel pad 35s centrally disposed within the circumferential cap ring 154. Holding tabs 156 can be provided to extend radially outwardly of the cap ring 154. These holding tabs 156 can facilitate the sealing engagement of the gel cap 143 with the base 145 in the manner described in greater detail below.

The gel pad 35s can be formed of any of the materials previously discussed although the preferred embodiment includes the KRATON/mineral oil gel. The cap ring 154 for such an embodiment can be advantageously formed of KRATON only. This will make the cap ring 154 more rigid than the gel pad 35s while maintaining an excellent material interface between the pad 35s and the ring 154. In a typical manufacturing operation, the cap ring will be pre-disposed in the mold for the gel pad 35s with the unitary structure of the gel cap 143 resulting.

The cross section view of FIG. 34 shows the gel cap 143s and illustrates an annular void 158 formed on the inner circumference of the cap ring 154. This void 158 is of particular advantage in forming a sealing relationship with the base 145 in the manner discussed in greater detail below.

The base 145 of this embodiment is shown in greater detail in the plan and cross section of views of FIGS. 34 and 35, respectively. From these views it will be noted that the base 145 can be provided with a smooth generally cylindrical inner surface 161 which extends proximally to a rounded end surface 163 and outwardly from the end surface 163 along an annular lip 165. A plurality of tabs 167 can be equally spaced to extend outwardly and distally around the circumference of the lip 165.

Distally of the inner surface 163, an annular flange 170 can be provided with an annular projection 172 sized and configured to form the desired sealing relationship between the gel cap 143 and the base 145. The process of molding the base 145 can be facilitated by forming the base as two separate components divided, for example, by a dotted line 174 in FIG. 35. In a preferred embodiment, the base 145 is molded from a polycarbonate material.

A preferred embodiment of the retracting sheath 147 is illustrated in FIG. 37. In this view it can be seen that the retraction sheath 147 includes a tubular wall 175 which has the configuration of the frustum of a cone 176 at its distal end and the configuration of a cylinder 177 at its proximal end. A flexible retaining ring 152 terminates the distal end while a fold 154 is formed at the proximal end. The tubular wall 175 is illustrated to include an outer surface 180 and an inner surface 181. In a preferred embodiment, the sheath 147 is formed of an elastomer, such as neoprene, so its frustule conical and cylindrical configurations exist primarily in the natural unstretched state.

As the sheath 147 is stretched axially, the diameter of the cylindrical proximal end increases thereby placing radial forces on the incision 32. The more the sheath 147 is stretched axially, the greater becomes the diameter of the sheath and consequently the larger becomes the opening through the incision 32. This feature is of particular advantage as it permits the surgeon to define the size of the incision 32 with an appropriate degree of axial tension on the sheath 147. By

maintaining this tension, the preferred size of the incision 132 is maintained throughout the operation. In a preferred apparatus and method, the axial tension is maintained by stretching the sheath 147 over the tabs 167 (FIG. 34) of the base 145. Indicia 182 can be printed on the sheath 147 to provide an indication of the relationship between the axial stretch of the sheath 147 and the size of the incision 32.

The fold 153 is provided to facilitate a grip on the proximal end of the sheath 147. This fold 153 can also function to provide reinforcement where the walls of the sheath 147 engage the tabs 167 of the base 145. In the embodiment illustrated in FIG. 38 additional folds 184, 186 are provided at spaced axial locations, such as those defined by the indicia 182 in FIG. 37. With these folds 184 and 186, additional points of reinforcement are provided to engage the tabs 167 while providing the sheath 147 with predetermined degrees of axial stretch associated with different sizes of the incision 32.

The method of using the embodiment of FIG. 32 is illustrated the progressive use of FIGS. 39-42. In FIG. 39, a top plan view of the abdominal wall 21 of the patient 10 is illustrated with a template 195 positioned to facilitate location of the incision 32. The size of the incision 32 can be determined with the indicia 182 on the template 195 showing, for example, multiple lengths of a line 197, each length being equated with a glove size for the surgeon's hand 17 (FIG. 7). Knowing his/her glove size, the surgeon will merely cut the incision in accordance with an appropriate length of the line 197. The longer lengths of the line 197 are associated with the larger incisions, the larger glove sizes and accordingly the larger hands 17. After the incision 32 has been cut along the line 197, the template 195 can be removed.

As illustrated in FIG. 40, the retraction sheath 147 can then be mounted through the incision 32. Initially the ring 152 is compressed and fed through the incision 32. On the inner surface of the abdominal wall 21, the ring 152 is free to expand to its larger diameter, as shown by a dotted line 158 in FIG. 40. The portions of the wall 176 which define the cylinder 177 are left to extend proximally through the opening 32 as shown in FIG. 40.

Prior to or after inserting the sheath 147, the base 145 can be disposed around the incision 32. Then the exposed portions of the sheath 147 will extend through the incision 32 and within the circumferential base 145. As illustrated in FIG. 41, the wall 176 of the sheath 147 can then be drawn proximally, outwardly of the page in FIG. 41, to axially stretch the sheath 147. As noted, when the sheath 147 is axially stretched, it will create radial forces on the abdominal wall 21 which will tend to enlarge the incision 32. The greater the axial stretch, the larger the incision 32.

When the incision 32 has the desired size, the stretched sheath 147 can be drawn over the tabs 167 to maintain the axial stretch and the desired size for the incision 32. Either the indicia 182, as shown in FIG. 36, or the additional folds 184 and 186 as shown in FIG. 37, can be aligned with the tabs 167 to provide a predetermined size for the incision 32. At this point, the seal between the abdominal wall 21, the sheath 147, and the base 145 is fully established.

A final step remaining in this process is the attachment of the gel cap 143 to the base 145. This is accomplished as illustrated in FIG. 36 by capturing the lip 172 of the base 145 in the annular void 158 of the gel cap 143. Bending the holding tabs 156 upwardly and outwardly facilitates this engagement which ultimately forms a seal between the base 145 and the gel cap 143.

Although this invention has been disclosed with reference to certain structural configurations, it will be appreciated that these products are merely representative of many different

embodiments of the invention. Accordingly, one is cautioned not to limit the concept only to the disclosed embodiments, but rather encouraged to determine the scope of the invention only with reference to the following claims.

What is claimed is:

1. A surgical access device adapted for performing laparoscopic surgical procedures with at least one instrument passing through the surgical access device and through an incision in the abdominal wall of a patient with the abdominal cavity pressurized with an insufflation gas, the surgical access device adapted to provide instrument access to the abdominal cavity for surgical procedures while maintaining insufflation pressure in the abdominal cavity, the surgical access device comprising:

an access seal, the access seal comprising an ultra gel material formed of a mixture comprising a triblock copolymer and an oil, wherein the access seal is adapted to be disposed relative to the abdominal wall in an operative position, and wherein the material of the access seal is adapted to form a seal to maintain insufflation pressure within the abdominal cavity; and

at least one opening formed through the material of the access seal between a proximal portion and a distal portion of the access seal, wherein the at least one opening when operatively disposed is in communication with the incision and forms a working channel between a location external to the abdominal wall and a location internal to the abdominal wall, wherein the material of the access seal is adapted to conform to a surface of an instrument inserted through the working channel, wherein the instrument has a diameter within a range of instrument diameters from the size of a guidewire to the size of a surgeon's hand, and wherein the working channel is configured to self seal in the absence of any instruments extending through the at least one opening.

2. The surgical access device of claim 1, further comprising a trocar configured for placement through the opening.

3. The surgical access device of claim 1, wherein the at least one opening accommodates a range of instrument diameters.

4. The surgical access device of claim 1, wherein the material of the access seal is adapted for direct contact with the abdominal wall during use.

5. The surgical access device of claim 1, wherein the material of the access seal is adapted for direct contact with the instrument during use.

6. The surgical access device of claim 1, wherein the access seal comprises a plurality of openings.

7. The surgical access device of claim 1, wherein several instruments can be accommodated within the access seal at the same time.

8. The surgical access device of claim 1, wherein the material is formed of a mixture consisting essentially of a triblock copolymer and an oil.

9. The surgical access device of claim 1, wherein the material is formed of a mixture consisting essentially of a triblock copolymer, an oil, and a foaming agent.

10. The surgical access device of claim 1, wherein the triblock copolymer comprises a Styrene-Ethylene/Butylene-Styrene structure.

11. A surgical access device adapted for performing laparoscopic surgical procedures with at least one instrument passing through the surgical access device and through an incision in the abdominal wall of a patient with the abdominal cavity pressurized with an insufflation gas, the surgical access device adapted to provide instrument access to the abdominal

17

cavity for surgical procedures while maintaining insufflation pressure in the abdominal cavity, the surgical access device comprising:

an access seal, the access seal comprising an ultra gel elastomeric material formed of a mixture comprising a triblock copolymer and an oil, wherein the access seal is adapted to be disposed relative to the abdominal wall in an operative position; and

at least one access channel formed through the elastomeric material between a proximal portion and a distal portion of the access seal, wherein the at least one access channel when operatively disposed forms at least a portion of a working channel between a location external to the abdominal wall and a location internal to the abdominal wall;

wherein the elastomeric material of the access seal is adapted to conform to a surface of an instrument inserted through the working channel to provide instrument access to the abdominal cavity while maintaining insufflation pressure in the abdominal cavity, wherein the instrument has a diameter within a range of instrument diameters from the size of a guidewire to the size of a surgeon's hand, and wherein the at least one access channel is configured to self seal in the absence of any instrument extending through the at least one access channel.

12. The surgical access device of claim 11, wherein the access seal is adapted to maintain a sealing relationship with a plurality of instruments positioned through the access seal while accommodating relative movement between the plurality of instruments.

13. The surgical access device of claim 11, wherein the elastomeric material of the access seal is adapted to conform to a surface of a trocar inserted through the working channel.

14. The surgical access device of claim 11, wherein the elastomeric material is a thermoplastic elastomer.

15. The surgical access device of claim 11, wherein the access seal in the operative position is adapted to form a seal with the abdominal wall.

16. The surgical access device of claim 11, wherein the triblock copolymer has a Styrene-Ethylene/Butylene-Styrene structure.

18

17. The surgical access device of claim 11, wherein the access seal is adapted to be removably disposed relative to the abdominal wall in an operative position.

18. The surgical access device of claim 11, wherein the elastomeric material of the access seal is adapted to span a thickness of the abdominal wall.

19. A method of using a surgical access device adapted for performing laparoscopic surgical procedures with at least one instrument passing through the surgical access device and through an incision in the abdominal wall of a patient with the abdominal cavity pressurized with an insufflation gas, the surgical access device adapted to provide instrument access to the abdominal cavity for surgical procedures while maintaining insufflation pressure in the abdominal cavity, the method comprising:

providing an access seal, the access seal comprising an ultra gel elastomeric material formed of a mixture comprising a triblock copolymer and an oil, and at least one access channel formed through the elastomeric material between a proximal portion and a distal portion of the access seal;

disposing the access seal relative to the abdominal wall in an operative position, wherein the at least one access channel when operatively disposed forms at least a portion of a working channel between a location external to the abdominal wall and a location internal to the abdominal wall, and wherein the working channel is configured to self seal in the absence of any instruments extending through the working channel; and

inserting at least one instrument through the working channel, wherein the instrument has a diameter within a range of instrument diameters from the size of a guidewire to the size of a surgeon's hand, wherein the elastomeric material of the access seal conforms to a surface of the instrument inserted through the working channel to provide instrument access to the abdominal cavity while maintaining insufflation pressure in the abdominal cavity.

20. The method of claim 19, wherein the access seal is adapted to maintain a sealing relationship with a plurality of instruments positioned through the access seal while accommodating relative movement between the plurality of instruments.

* * * * *

6,391,043	B1	5/2002	Moll et al.	6,936,037	B2	8/2005	Bubb et al.
6,413,244	B1	7/2002	Bestetti et al.	6,939,296	B2	9/2005	Ewers et al.
6,413,458	B1	7/2002	Pearce	6,945,932	B1	9/2005	Caldwell et al.
6,420,475	B1	7/2002	Chen	6,958,037	B2	10/2005	Ewers et al.
6,423,036	B1	7/2002	Van Huizen	6,972,026	B1	12/2005	Caldwell et al.
6,440,061	B1	8/2002	Wenner et al.	6,979,324	B2	12/2005	Bybordi et al.
6,440,063	B1	8/2002	Beane et al.	6,991,602	B2	1/2006	Nakazawa et al.
6,443,957	B1	9/2002	Addis	6,997,909	B2	2/2006	Goldberg
6,447,489	B1	9/2002	Peterson	7,001,397	B2	2/2006	Davison et al.
6,450,983	B1	9/2002	Rambo	7,008,377	B2	3/2006	Beane et al.
6,454,783	B1	9/2002	Piskun	7,014,628	B2	3/2006	Bousquet
6,464,686	B1	10/2002	O'Hara et al.	7,033,319	B2	4/2006	Pulford et al.
6,468,292	B1	10/2002	Mollenauer et al.	7,052,454	B2	5/2006	Taylor
6,482,181	B1	11/2002	Racenet et al.	7,056,304	B2	6/2006	Bacher et al.
6,485,435	B1	11/2002	Bakal	7,056,321	B2	6/2006	Pagliuca et al.
6,485,467	B1	11/2002	Crook et al.	7,067,583	B2	6/2006	Chen
6,488,620	B1	12/2002	Segermark et al.	7,077,852	B2	7/2006	Fogarty et al.
6,488,692	B1	12/2002	Spence et al.	7,081,089	B2	7/2006	Bonadio et al.
6,494,893	B2	12/2002	Dubrul et al.	7,083,626	B2	8/2006	Hart et al.
6,527,787	B1	3/2003	Fogarty et al.	7,093,599	B2	8/2006	Chen
6,533,734	B1	3/2003	Corley, III et al.	7,100,614	B2	9/2006	Stevens et al.
6,551,270	B1	4/2003	Bimbo et al.	7,101,353	B2	9/2006	Lui et al.
6,551,276	B1	4/2003	Mann et al.	7,105,009	B2	9/2006	Johnson
6,551,344	B2	4/2003	Thill	7,105,607	B2	9/2006	Chen
6,552,109	B1	4/2003	Chen	7,112,185	B2	9/2006	Hart et al.
6,554,793	B1	4/2003	Pauker et al.	7,118,528	B1	10/2006	Piskun
6,558,371	B2	5/2003	Dorn	7,134,929	B2	11/2006	Chen
6,569,120	B1	5/2003	Green	7,153,261	B2	12/2006	Wenchell
6,578,577	B2	6/2003	Bonadio et al.	7,163,510	B2	1/2007	Kahle et al.
6,579,281	B2	6/2003	Palmer et al.	7,192,436	B2	3/2007	Sing et al.
6,582,364	B2	6/2003	Butler et al.	7,193,002	B2	3/2007	Chen
6,589,167	B1	7/2003	Shimomura et al.	7,195,590	B2	3/2007	Butler et al.
6,589,211	B1	7/2003	MacLeod	7,214,185	B1	5/2007	Rosney et al.
6,607,504	B2	8/2003	Haarala et al.	7,217,277	B2	5/2007	Parihar et al.
6,613,952	B2	9/2003	Rambo	7,222,380	B2	5/2007	Chen
6,623,426	B2	9/2003	Bonadio et al.	7,223,257	B2	5/2007	Shubayev et al.
6,627,275	B1	9/2003	Chen	7,223,278	B2	5/2007	Davison et al.
6,663,598	B1	12/2003	Carrillo et al.	7,226,484	B2	6/2007	Chen
6,669,674	B1	12/2003	Macoviak et al.	7,235,062	B2	6/2007	Brustad
6,676,639	B1	1/2004	Ternström	7,235,084	B2	6/2007	Skakoon et al.
6,702,787	B2	3/2004	Racenet et al.	7,238,154	B2	7/2007	Ewers et al.
6,705,989	B2	3/2004	Cuschieri et al.	7,244,244	B2	7/2007	Racenet et al.
6,706,050	B1	3/2004	Giannadakis	7,276,075	B1	10/2007	Callas et al.
6,714,298	B2	3/2004	Ryer	7,290,367	B2	11/2007	Chen
6,716,201	B2	4/2004	Blanco	7,294,103	B2	11/2007	Bertolero et al.
6,723,044	B2	4/2004	Pulford et al.	7,297,106	B2	11/2007	Yamada et al.
6,723,088	B2	4/2004	Gaskill, III et al.	7,300,399	B2	11/2007	Bonadio et al.
6,725,080	B2	4/2004	Melkent et al.	7,316,699	B2	1/2008	McFarlane
6,793,621	B2	9/2004	Butler et al.	7,331,940	B2	2/2008	Sommerich
6,794,440	B2	9/2004	Chen	7,338,473	B2	3/2008	Campbell et al.
6,796,940	B2	9/2004	Bonadio et al.	7,344,547	B2	3/2008	Piskun
6,797,765	B2	9/2004	Pearce	7,344,568	B2	3/2008	Chen
6,800,084	B2	10/2004	Davison et al.	7,377,898	B2	5/2008	Ewers et al.
6,811,546	B1	11/2004	Callas et al.	7,390,317	B2	6/2008	Taylor et al.
6,814,078	B2	11/2004	Crook	7,393,322	B2	7/2008	Wenchell
6,814,700	B1	11/2004	Mueller et al.	7,412,977	B2	8/2008	Fields et al.
6,817,974	B2	11/2004	Cooper et al.	7,445,597	B2	11/2008	Butler et al.
6,830,578	B2	12/2004	O'Heeron et al.	7,473,221	B2	1/2009	Ewers et al.
6,837,893	B2	1/2005	Miller	7,481,765	B2	1/2009	Ewers et al.
6,840,946	B2	1/2005	Fogarty et al.	7,537,564	B2	5/2009	Bonadio et al.
6,840,951	B2	1/2005	de la Torre et al.	7,540,839	B2	6/2009	Butler et al.
6,846,287	B2	1/2005	Bonadio et al.	7,559,893	B2	7/2009	Bonadio et al.
6,860,463	B2	3/2005	Hartley	7,578,832	B2	8/2009	Johnson
6,863,674	B2	3/2005	Kasahara et al.	7,645,232	B2	1/2010	Shluzas
6,866,861	B1	3/2005	Luhman	7,650,887	B2	1/2010	Nguyen et al.
6,867,253	B1	3/2005	Chen	7,661,164	B2	2/2010	Chen
6,869,393	B2	3/2005	Butler	7,704,207	B2	4/2010	Albrecht et al.
6,878,110	B2	4/2005	Yang et al.	7,717,847	B2	5/2010	Smith
6,884,253	B1	4/2005	McFarlane	7,727,146	B2	6/2010	Albrecht et al.
6,890,295	B2	5/2005	Michels et al.	7,727,255	B2	6/2010	Taylor et al.
6,895,965	B2	5/2005	Scarberry et al.	7,736,306	B2	6/2010	Brustad et al.
6,902,541	B2	6/2005	McNally et al.	7,749,415	B2	7/2010	Brustad et al.
6,902,569	B2	6/2005	Parmer et al.	7,753,901	B2	7/2010	Piskun et al.
6,908,430	B2	6/2005	Caldwell et al.	7,758,500	B2	7/2010	Boyd et al.
6,909,220	B2	6/2005	Chen	7,766,824	B2	8/2010	Jensen et al.
6,913,609	B2	7/2005	Yencho et al.	7,811,251	B2	10/2010	Wenchell et al.
6,916,310	B2	7/2005	Sommerich	7,815,567	B2	10/2010	Albrecht et al.
6,916,331	B2	7/2005	Mollenauer et al.	7,837,612	B2	11/2010	Gill et al.
6,929,637	B2	8/2005	Gonzalez et al.	7,850,667	B2	12/2010	Gresham

7,867,164	B2	1/2011	Butler et al.	2005/0251124	A1	11/2005	Zvuloni et al.
7,878,974	B2	2/2011	Brustad et al.	2005/0261720	A1	11/2005	Caldwell et al.
7,883,461	B2	2/2011	Albrecht et al.	2005/0267419	A1	12/2005	Smith
7,892,172	B2	2/2011	Albrecht et al.	2005/0277946	A1	12/2005	Greenhalgh
7,896,889	B2	3/2011	Mazzocchi et al.	2005/0283050	A1	12/2005	Gundlapalli et al.
7,909,760	B2	3/2011	Albrecht et al.	2005/0288558	A1	12/2005	Ewers et al.
7,913,697	B2	3/2011	Nguyen et al.	2005/0288634	A1	12/2005	O'Heeron et al.
7,930,782	B2	4/2011	Chen	2006/0020164	A1	1/2006	Butler et al.
2001/0037053	A1	11/2001	Bonadio et al.	2006/0020241	A1	1/2006	Piskun et al.
2001/0047188	A1	11/2001	Bonadio et al.	2006/0030755	A1	2/2006	Ewers et al.
2002/0002324	A1	1/2002	McManus	2006/0041270	A1	2/2006	Lenker
2002/0010389	A1	1/2002	Butler et al.	2006/0047284	A1	3/2006	Gresham
2002/0013542	A1	1/2002	Bonadio et al.	2006/0047293	A1	3/2006	Haberland et al.
2002/0016607	A1	2/2002	Bonadio et al.	2006/0052669	A1	3/2006	Hart
2002/0026230	A1	2/2002	Moll et al.	2006/0084842	A1	4/2006	Hart et al.
2002/0038077	A1	3/2002	de la Torre et al.	2006/0106402	A1	5/2006	McLucas
2002/0072762	A1	6/2002	Bonadio et al.	2006/0129165	A1	6/2006	Edoga et al.
2002/0111536	A1	8/2002	Cuschieri et al.	2006/0149137	A1	7/2006	Pingleton et al.
2003/0004253	A1	1/2003	Chen	2006/0149306	A1	7/2006	Hart et al.
2003/0028179	A1	2/2003	Piskun	2006/0161049	A1	7/2006	Beane et al.
2003/0040711	A1	2/2003	Racenet et al.	2006/0161050	A1	7/2006	Butler et al.
2003/0078478	A1	4/2003	Bonadio et al.	2006/0241651	A1	10/2006	Wilk
2003/0139756	A1	7/2003	Brustad	2006/0247498	A1	11/2006	Bonadio et al.
2003/0167040	A1	9/2003	Bacher et al.	2006/0247499	A1	11/2006	Butler et al.
2003/0187376	A1	10/2003	Rambo	2006/0247500	A1	11/2006	Voegele et al.
2003/0192553	A1	10/2003	Rambo	2006/0247516	A1	11/2006	Hess et al.
2003/0225392	A1	12/2003	McMichael et al.	2006/0247586	A1	11/2006	Voegele et al.
2003/0236505	A1	12/2003	Bonadio et al.	2006/0247673	A1	11/2006	Voegele et al.
2003/0236549	A1	12/2003	Bonadio et al.	2006/0247678	A1	11/2006	Weisenburgh, II et al.
2004/0015185	A1	1/2004	Ewers et al.	2006/0258899	A1	11/2006	Gill et al.
2004/0024363	A1	2/2004	Goldberg	2006/0264706	A1	11/2006	Piskun
2004/0049099	A1	3/2004	Ewers et al.	2006/0270911	A1	11/2006	Voegele et al.
2004/0049100	A1	3/2004	Butler	2007/0004968	A1	1/2007	Bonadio et al.
2004/0054353	A1	3/2004	Taylor	2007/0049966	A1	3/2007	Bonadio et al.
2004/0063833	A1	4/2004	Chen	2007/0093695	A1	4/2007	Bonadio et al.
2004/0068232	A1	4/2004	Hart et al.	2007/0118175	A1	5/2007	Butler et al.
2004/0070187	A1	4/2004	Chen	2007/0151566	A1	7/2007	Kahle et al.
2004/0072942	A1	4/2004	Chen	2007/0156023	A1	7/2007	Frasier et al.
2004/0073090	A1	4/2004	Butler	2007/0203398	A1	8/2007	Bonadio et al.
2004/0092795	A1	5/2004	Bonadio et al.	2007/0208312	A1	9/2007	Norton et al.
2004/0092796	A1	5/2004	Butler et al.	2007/0255219	A1	11/2007	Vaugh et al.
2004/0093018	A1	5/2004	Johnson	2007/0299387	A1	12/2007	Williams et al.
2004/0097793	A1	5/2004	Butler et al.	2008/0027476	A1	1/2008	Piskun
2004/0106942	A1	6/2004	Taylor	2008/0048011	A1	2/2008	Weller
2004/0111061	A1	6/2004	Curran	2008/0097162	A1	4/2008	Bonadio et al.
2004/0127772	A1	7/2004	Ewers et al.	2008/0097163	A1	4/2008	Butler et al.
2004/0138529	A1	7/2004	Wiltshire et al.	2008/0200767	A1	8/2008	Ewers et al.
2004/0143158	A1	7/2004	Hart et al.	2008/0255519	A1	10/2008	Piskun et al.
2004/0154624	A1	8/2004	Bonadio et al.	2008/0281161	A1	11/2008	Albrecht et al.
2004/0167559	A1	8/2004	Taylor et al.	2008/0281162	A1	11/2008	Albrecht et al.
2004/0173218	A1	9/2004	Yamada et al.	2009/0012477	A1	1/2009	Norton et al.
2004/0215063	A1	10/2004	Bonadio et al.	2009/0036745	A1	2/2009	Bonadio et al.
2004/0230161	A1	11/2004	Zeiner	2009/0069837	A1	3/2009	Bonadio et al.
2004/0243144	A1	12/2004	Bonadio et al.	2009/0093683	A1	4/2009	Richard et al.
2004/0249248	A1	12/2004	Bonadio et al.	2009/0093752	A1	4/2009	Richard et al.
2004/0254426	A1	12/2004	Wenchell	2009/0131754	A1	5/2009	Ewers et al.
2004/0260244	A1	12/2004	Piechowicz et al.	2009/0137879	A1	5/2009	Ewers et al.
2004/0267096	A1	12/2004	Caldwell et al.	2009/0149714	A1	6/2009	Bonadio
2005/0020884	A1	1/2005	Hart et al.	2009/0182279	A1	7/2009	Wenchell et al.
2005/0033246	A1	2/2005	Ahlbert et al.	2009/0187079	A1	7/2009	Albrecht et al.
2005/0059865	A1	3/2005	Kahle et al.	2009/0227843	A1	9/2009	Smith et al.
2005/0065475	A1	3/2005	Hart et al.	2009/0292176	A1	11/2009	Bonadio et al.
2005/0065543	A1	3/2005	Kahle et al.	2009/0326330	A1	12/2009	Bonadio et al.
2005/0090713	A1	4/2005	Gonzales et al.	2010/0063362	A1	3/2010	Bonadio et al.
2005/0090716	A1	4/2005	Bonadio et al.	2010/0063364	A1	3/2010	Bonadio et al.
2005/0090717	A1	4/2005	Bonadio et al.	2010/0081880	A1	4/2010	Widenhouse et al.
2005/0096695	A1	5/2005	Olich	2010/0081881	A1	4/2010	Murray et al.
2005/0131349	A1	6/2005	Albrecht et al.	2010/0081995	A1	4/2010	Widenhouse et al.
2005/0148823	A1	7/2005	Vaugh et al.	2010/0100043	A1	4/2010	Racenet
2005/0155611	A1	7/2005	Vaugh et al.	2010/0113882	A1	5/2010	Widenhouse et al.
2005/0159647	A1	7/2005	Hart et al.	2010/0217087	A1	8/2010	Bonadio et al.
2005/0192483	A1	9/2005	Bonadio et al.	2010/0228091	A1	9/2010	Widenhouse et al.
2005/0192598	A1	9/2005	Johnson et al.	2010/0228092	A1	9/2010	Ortiz et al.
2005/0197537	A1	9/2005	Bonadio et al.	2010/0228094	A1	9/2010	Ortiz et al.
2005/0203346	A1	9/2005	Bonadio et al.	2010/0240960	A1	9/2010	Richard
2005/0209510	A1	9/2005	Bonadio et al.	2010/0249523	A1	9/2010	Spiegel et al.
2005/0222582	A1	10/2005	Wenchell	2010/0249524	A1	9/2010	Ransden et al.
2005/0240082	A1	10/2005	Bonadio et al.	2010/0249525	A1	9/2010	Shelton, IV et al.
2005/0241647	A1	11/2005	Nguyen	2010/0249694	A1	9/2010	Choi et al.

2010/0261972	A1	10/2010	Widenhouse et al.
2010/0261975	A1	10/2010	Huey et al.
2010/0286484	A1	11/2010	Stellon et al.
2010/0298646	A1	11/2010	Stellon et al.
2011/0021877	A1	1/2011	Fortier et al.
2011/0028891	A1	2/2011	Okoniewski
2011/0034935	A1	2/2011	Kleyman
2011/0034946	A1	2/2011	Kleyman
2011/0034947	A1	2/2011	Kleyman
2011/0071462	A1	3/2011	Ewers et al.
2011/0071463	A1	3/2011	Ewers et al.

FOREIGN PATENT DOCUMENTS

DE	33 36 279	C2	1/1986
DE	37 39 532		12/1988
DE	37 37 121		5/1989
DE	296 00 939		6/1996
DE	19828009		12/1999
EP	0113520		7/1984
EP	0142262		5/1985
EP	0 517 248		12/1992
EP	0537768		4/1993
EP	0 807 416		11/1997
EP	0 849 517		6/1998
EP	0950376		10/1999
EP	1118657		7/2001
EP	1 125 552		8/2001
EP	1312318		5/2003
EP	1 407 715		4/2004
EP	2044889		4/2009
FR	1456623		9/1966
GB	1151993		5/1969
GB	1355611		6/1974
GB	1372491		10/1974
GB	1379772		1/1975
GB	1400808		7/1975
GB	1407023		9/1975
GB	1482857		8/1977
GB	1496696		12/1977
GB	2071502		9/1981
GB	2255019		10/1992
GB	2275420		8/1994
GB	2298906		9/1996
IE	930649		9/1993
IE	930650		9/1993
IE	S940150		2/1994
IE	S940613		8/1994
IE	S940960		12/1994
IE	S950055		1/1995
IE	S950266		4/1995
IE	S75368		8/1997
IE	S960196		8/1997
IE	S970810		11/1997
IE	991010		7/2000
IE	990218		11/2000
IE	990219		11/2000
IE	990220		11/2000
IE	990660		2/2001
IE	990795		3/2001
JP	10-108868		4/1998
JP	11-290327		10/1999
JP	2001-61850		3/2001
JP	2002-28163		1/2002
JP	02003 235879	A	8/2003
JP	2004-195037		7/2004
RU	1342485		1/1997
WO	WO 86/06272		11/1986
WO	WO 86/06316		11/1986
WO	WO 92/11880		7/1992
WO	WO 92/21292		12/1992
WO	WO 93/05740		4/1993
WO	WO 93/14801		8/1993
WO	WO 94/04067		3/1994
WO	WO 94/22357		10/1994
WO	WO 95/05207		2/1995
WO	WO 95/07056		3/1995
WO	WO 95/22289		8/1995
WO	WO 95/24864		9/1995
WO	WO 95/27445		10/1995

WO	WO 95/27468	10/1995
WO	WO 96/36283	11/1996
WO	WO 97/11642	4/1997
WO	WO 97/32514	9/1997
WO	WO 97/32515	9/1997
WO	WO 97/42889	11/1997
WO	WO 98/19853	5/1998
WO	WO 98/35614	8/1998
WO	WO 98/48724	11/1998
WO	WO 99/03416	1/1999
WO	WO 99/15068	4/1999
WO	WO 99/16368	4/1999
WO	WO 99/22804	5/1999
WO	WO 99/25268	5/1999
WO	WO 99/29250	6/1999
WO	WO 00/32116	6/2000
WO	WO 00/32117	6/2000
WO	WO 00/32119	6/2000
WO	WO 00/32120	6/2000
WO	WO 00/35356	6/2000
WO	WO 00/54675	9/2000
WO	WO 00/54676	9/2000
WO	WO 00/54677	9/2000
WO	WO 01/08563	2/2001
WO	WO 01/08581	2/2001
WO	WO 01/26558	4/2001
WO	WO 01/26559	4/2001
WO	WO 01/45568	6/2001
WO	WO 01/49363	7/2001
WO	WO 01/91652	12/2001
WO	WO 02/07611	1/2002
WO	WO 02/17800	3/2002
WO	WO 02/34108	5/2002
WO	WO 03/011153	2/2003
WO	WO 03/011551	2/2003
WO	WO 03/026512	4/2003
WO	WO 03/032819	4/2003
WO	WO 03/034908	5/2003
WO	WO 03/061480	7/2003
WO	WO 03/077726	9/2003
WO	WO 03/103548	12/2003
WO	WO 2004/026153	4/2004
WO	WO 2004/030547	4/2004
WO	WO 2004/075730	9/2004
WO	WO 2004/075741	9/2004
WO	WO 2004/075930	9/2004
WO	WO 2005/009257	2/2005
WO	WO 2005/034766	4/2005
WO	WO 2005/089661	9/2005
WO	WO 2006/040748	4/2006
WO	WO 2006/059318	6/2006
WO	WO 2006/100658	9/2006
WO	WO 2008/015566	2/2008
WO	WO 2008/093313	8/2008
WO	WO 2008/121294	10/2008
WO	WO 2010/082722	7/2010
WO	WO 2010/104259	9/2010

OTHER PUBLICATIONS

U.S. Appl. No. 10/902,756, filed Jul. 29, 2004; Title: Hand Access Port Device, now abandoned.

U.S. Appl. No. 10/802,125, filed Mar. 15, 2004; Title: Surgical Guide Valve, now abandoned.

U.S. Appl. No. 10/927,551, filed Aug. 25, 2004; Title: Surgical Access System, now abandoned.

U.S. Appl. No. 10/695,295, filed Oct. 28, 2003; Title: Surgical Gel Seal.

U.S. Appl. No. 11/132,741, filed May 18, 2005; Title: Gas-Tight Seal Accomodating Surgical Instruments With a Wide Range of Diameters.

U.S. Appl. No. 11/245,709, filed Oct. 7, 2005; Title: Surgical Access System.

U.S. Appl. No. 11/330,661, filed Jan. 12, 2006; Title: Sealed Surgical Access Device.

U.S. Appl. No. 11/564,409, filed Nov. 29, 2006; Title: Surgical Instrument Access Device.

U.S. Appl. No. 12/108,400, filed Apr. 23, 2008; Title: Wound Retraction Apparatus and Method.

- U.S. Appl. No. 12/119,371, filed May 12, 2008; Title: Surgical Retractor With Gel Pad.
- U.S. Appl. No. 12/119,414, filed May 12, 2008; Title: Surgical Retractor.
- U.S. Appl. No. 12/358,080, filed Jan. 22, 2009; Title: Surgical Instrument Access Device.
- U.S. Appl. No. 12/360,634, filed Jan. 27, 2009; Title: Surgical Access Apparatus and Method.
- U.S. Appl. No. 12/360,710, filed Jan. 27, 2009; Title: Surgical Access Apparatus and Method.
- U.S. Appl. No. 12/578,422, filed Oct. 13, 2009; Title: Single Port Access System.
- U.S. Appl. No. 12/905,932, filed Oct. 15, 2010; Title: Split Hoop Wound Retractor.
- U.S. Appl. No. 12/960,449, filed Dec. 3, 2010; Title: Surgical Access Apparatus and Method.
- U.S. Appl. No. 12/960,458, filed Dec. 3, 2010; Title: Surgical Access Apparatus and Method.
- U.S. Appl. No. 13/006,727, filed Jan. 14, 2011.
- U.S. Appl. No. 13/008,728, filed Jan. 18, 2011.
- U.S. Appl. No. 13/023,334, filed Feb. 8, 2011.
- U.S. Appl. No. 13/031,892, filed Feb. 22, 2011.
- U.S. Appl. No. 13/050,042, filed Mar. 17, 2011.
- U.S. Appl. No. 10/446,365, filed May 28, 2003; Title: Screw-Type Seal With Inflatable Membrane.
- U.S. Appl. No. 12/004,439, filed Dec. 20, 2007; Title: Skin Seal.
- U.S. Appl. No. 12/004,441, filed Dec. 20, 2007; Title: Screw-Type Skin Seal With Inflatable Membrane.
- U.S. Appl. No. 12/607,667, filed Oct. 28, 2009; Title: Screw-Type Skin Seal With Inflatable Membrane.
- U.S. Appl. No. 10/965,217, filed Oct. 15, 2004; Title: Surgical Sealing Device.
- U.S. Appl. No. 10/981,730, filed Nov. 5, 2004; Title: Surgical Sealing Device.
- U.S. Appl. No. 11/246,909, filed Oct. 11, 2005; Title: Instrument Access Device.
- U.S. Appl. No. 11/291,089, filed Dec. 1, 2005; Title: A Surgical Sealing Device.
- U.S. Appl. No. 11/486,383, filed Jul. 14, 2006; Title: Wound Retractor.
- U.S. Appl. No. 11/785,752, filed Apr. 19, 2007; Title: Instrument Access Device.
- U.S. Appl. No. 12/244,024, filed Oct. 2, 2008; Title: Seal Anchor for Use in Surgical Procedures.
- U.S. Appl. No. 12/578,832, filed Oct. 14, 2009; Title: Flexible Access Device for Use in Surgical Procedure.
- U.S. Appl. No. 12/706,043, filed Feb. 16, 2010; Title: Flexible Port Seal.
- U.S. Appl. No. 12/719,341, filed Mar. 8, 2010; Title: Foam Port and Introducer Assembly.
- U.S. Appl. No. 10/895,546, filed Jul. 21, 2004; Title: Laparoscopic Instrument and Cannula Assembly and Related Surgical Method.
- European Patent Office, European Search Report for European Application No. EP 10 18 4681, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".
- European Patent Office, European Search Report for European Application No. EP 10 18 4608, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".
- European Patent Office, European Search Report for European Application No. EP 10 18 4648, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".
- European Patent Office, European Search Report for European Application No. EP 10 18 4731, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".
- European Patent Office, European Search Report for European Application No. EP 10 18 4661, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".
- European Patent Office, European Search Report for European Application No. EP 10 18 4677, dated Nov. 22, 2010, entitled "Wound Retraction Apparatus and Method".
- European Patent Office, European Search Report for European Application No. EP 10 18 9325, dated Dec. 14, 2010, entitled "Split Hoop Wound Retractor".
- European Patent Office, European Search Report for European Application No. EP 10 18 9327, dated Dec. 14, 2010, entitled "Split Hoop Wound Retractor".
- European Patent Office, European Search Report for European Application No. EP 10 18 9328, dated Dec. 15, 2010, entitled "Split Hoop Wound Retractor".
- European Patent Office, European Search Report for European Application No. EP 04 00 2888, dated Sep. 10, 2004, entitled "Hand Access Port Device".
- European Patent Office, European Search Report for European Application No. EP 04 00 2889, dated Sep. 13, 2004, entitled "Hand Access Port Device".
- European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040154, mailed Jan. 30, 2007.
- European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/040073, mailed Jan. 26, 2007.
- European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039905, mailed Jan. 17, 2007.
- European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039883, mailed Jan. 31, 2007.
- European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039800, mailed Apr. 16, 2007.
- European Patent Office, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US2006/039799, mailed Mar. 27, 2007.
- European Search Report for corresponding EP 08253236 date of mailing is Feb. 10, 2009 (6 pages).
- Horigame, et al., Silicone Rumen Cannula with a Soft Cylindrical Part and a Hard Flange, *Journal of Dairy Science*, Nov. 1989, vol. 72, No. 11, pp. 3230-3232.
- Horigame, et al., Technical Note: Development of Duodenal Cannula for Sheep, *Journal of Animal Science*, Apr. 1992, vol. 70, Issue 4, pp. 1216-1219.
- International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US04/05484.
- International Searching Authority/US, International Search Report and the Written Opinion of the International Searching Authority for International Application No. PCT/US01/29682.
- McSweeney, Cannulation of the Rumen in Cattle and Buffaloes, *Australian Veterinary Journal*, Aug. 1989, vol. 66, No. 8, pp. 266-268.
- Neil Sheehan, Supplemental Expert Report of Neil Sheehan, Re: U.S. Patent No. 5,741,298, United States District Court for the Central District of California, Civil Action No. SACV 03-1322 JVS, Aug. 9, 2005.
- Office Action in co-pending U.S. Appl. No. 12/360,634, dated Jan. 24, 2011 in 12 pages.
- Office Action in co-pending U.S. Appl. No. 12/360,710, dated Jan. 24, 2011 in 12 pages.
- Technical Note: Development of Duodenal Cannula for Sheep, Faculty of Agriculture and School of Medicine Tohoku University, Sendai 981, Japan.
- The International Bureau of WIPO, International Preliminary Report on Patentability, dated Aug. 29, 2006, for International Application No. PCT/US2004/028250.
- The International Bureau of WIPO, International Preliminary Report on Patentability, dated Apr. 16, 2008, for International Application No. PCT/US2006/039799.
- The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2006/039800 dated Apr. 16, 2008.
- Yamazaki, et al., Diurnal Changes in the Composition of Abomasal Digesta in Fasted and Fed Sheep, the *Tohoku Journal of Agricultural Research*, Mar. 1987, vol. 37, No. 3-4, pp. 49-58.
- Kagaya, Laparoscopic cholecystectomy via two ports, using the "Twin-Port" system, *J. Hepatobiliary Pancreat Surg* (2001) 8:76-80.
- International Search Report and Written Opinion in PCT/IE2005/000113 mailed on Feb. 22, 2006.

International Search Report and Written Opinion in PCT/IE2007/000050 mailed on Aug. 13, 2007.

Declaration of John R. Brustad dated Dec. 10, 2009, submitted in U.S. Appl. No. 11/548,955, including Appendices A-D regarding product sales brochures and production drawings from 2001 and 2005.

The International Searching Authority, The International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US08/63445, mailed Sep. 29, 2008.

The International Searching Authority, The International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US08/063463 mailed Sep. 10, 2008.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2008/063463, dated Nov. 17, 2009, entitled "Surgical Retractor".


International Searching Authority-US, International Search Report and Written Opinion of the International Searching Authority for International Application No. PCT/US04/25511, mailed Nov. 7, 2007.

International Searching Bureau of WIPO, International Report on Patentability, for International Application No. PCT/US04/25511, mailed Dec. 6, 2007.

The International Bureau of WIPO, International Preliminary Report on Patentability for International Application No. PCT/US2008/063445, issued Nov. 17, 2009, entitled "Surgical Retractor with Gel Pad".

U.S. Appl. No. 10/913,565, filed Aug. 5, 2004; Title: Surgical Device With Tack-Free Gel and Method of Manufacture.

* cited by examiner



专利名称(译)	手术进入装置和方法		
公开(公告)号	US8070676	公开(公告)日	2011-12-06
申请号	US12/960449	申请日	2010-12-03
[标]申请(专利权)人(译)	应用医疗资源		
申请(专利权)人(译)	应用医疗资源CORPORATION		
当前申请(专利权)人(译)	应用医疗资源CORPORATION		
[标]发明人	EWERS RICHARD C BRUSTAD JOHN R PINGLETON EDWARD D HILAL NABIL DULAK GARY R ADLPARVAR PAYAM BOWES ROBERT R		
发明人	EWERS, RICHARD C. BRUSTAD, JOHN R. PINGLETON, EDWARD D. HILAL, NABIL DULAK, GARY R. ADLPARVAR, PAYAM BOWES, ROBERT R.		
IPC分类号	A61B1/32 A61B19/00 A61B17/00 A61B17/02 A61B17/34		
CPC分类号	A61B17/0293 A61B17/3423 A61B17/3498 A61M13/003 A61B17/0218 A61B17/3474 A61B2017/00265 A61B2017/00526 A61B2017/3492 A61B2017/3445 A61B2017/3419		
审查员(译)	阮瞳		
优先权	11/244647 2009-01-27 US 10/381220 2009-01-06 US PCT/US2001/029682 2001-09-21 WO 60/241958 2000-10-19 US		
其他公开文献	US20110071462A1		
外部链接	Espacenet USPTO		

摘要(译)

一种外科进入装置包括进入密封件，该进入密封件包括由包含三嵌段共聚物和油的混合物形成的超凝胶弹性体材料。进入密封件适于相对于腹壁设置。在进入密封件的近端部分和远端部分之间穿过弹性体材料形成至少一个进入通道。当可操作地设置时，进入通道在腹壁外部的位臵和腹壁内部的位臵之间形成工作通道的至少一部分。进入密封件的弹性材料适于与穿过工作通道插入的器械表面一致，以提供进入腹腔的器械通路，同时保持腹腔中的注气压力。访问通道被配置为在没有任何仪器延伸通过访问通道的情况下自密封。

