



US009480466B2

(12) **United States Patent**
Van De Weghe et al.

(10) **Patent No.:** **US 9,480,466 B2**
(45) **Date of Patent:** **Nov. 1, 2016**

(54) **SURGICAL DEVICE AND LINKAGE
SYSTEM FOR SAME**

(56) **References Cited**

U.S. PATENT DOCUMENTS

- (71) Applicant: **CareFusion 2200, Inc.**, San Diego, CA (US)
- (72) Inventors: **Andrew P. Van De Weghe**, Grayslake, IL (US); **Louis P. Mingione**, Mundelein, IL (US); **David A. Schechter**, Boulder, CO (US); **David Scott Hazlitt**, Boulder, CO (US)
- (73) Assignee: **CareFusion 2200, Inc.**, San Diego, CA (US)

5,489,290 A	2/1996	Furnish
5,498,256 A	3/1996	Furnish
5,507,297 A	4/1996	Slater et al.
5,665,105 A	9/1997	Furnish et al.
5,827,323 A	10/1998	Klieman et al.
5,922,007 A	7/1999	Hoogeboom et al.
5,947,996 A	9/1999	Logeman
6,000,138 A	12/1999	Bornancini
6,077,290 A	6/2000	Marini
7,846,177 B2	12/2010	Carpenter et al.
8,512,315 B2	8/2013	Leonard et al.
2007/0299469 A1	12/2007	Carpenter et al.
2008/0021278 A1	1/2008	Leonard et al.

(Continued)

- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 222 days.

FOREIGN PATENT DOCUMENTS

EP	1348381 A2	1/2003
WO	WO 94/25710	12/1994

(Continued)

(21) Appl. No.: **14/292,210**

OTHER PUBLICATIONS

(22) Filed: **May 30, 2014**

Modular Laproscopic-Instruments, Pajunk.

(Continued)

(65) **Prior Publication Data**

US 2015/0342583 A1 Dec. 3, 2015

Primary Examiner — Lynsey Crandall

Assistant Examiner — Qingjun Kong

(74) *Attorney, Agent, or Firm* — Brinks Gilson & Lione

- (51) **Int. Cl.**
A61B 17/00 (2006.01)
A61B 17/29 (2006.01)
A61B 17/28 (2006.01)


(57) **ABSTRACT**

A laparoscopic surgical device is provided, including a removable tool-comprising shaft having an outer shaft and an inner actuation rod that may be removably or permanently connected together. A handle of the device includes a two-button mechanism for engaging and releasing the removable tool-comprising shaft. The two-button mechanism is configured to engage overlapping corresponding apertures of the outer shaft and the inner rod that extends through the outer shaft, and the handle may include a variety of configurations that can readily interchangeably be used with different tool bodies.

- (52) **U.S. Cl.**
CPC **A61B 17/00234** (2013.01); **A61B 17/28** (2013.01); **A61B 17/29** (2013.01); **A61B 2017/0046** (2013.01); **A61B 2017/00424** (2013.01); **A61B 2017/00464** (2013.01); **A61B 2017/292** (2013.01)

- (58) **Field of Classification Search**
None
See application file for complete search history.

20 Claims, 13 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0306342 A1* 12/2008 Leonard A61B 17/2909
600/131
2010/0191225 A1 7/2010 Leonard
2011/0112517 A1* 5/2011 Peine A61B 17/29
606/1
2011/0306952 A1 12/2011 Chen et al.

FOREIGN PATENT DOCUMENTS

WO WO 2008 002574 A2 1/2008
WO WO 2008/154289 12/2009

OTHER PUBLICATIONS

Diamond-Line Laparoscopic Surgical Instruments.
The Economic Scissor System with Disposable Inserts, Panjunk GmbH.
Diamond-Line Laparoscopic Surgical Instruments, Snowden-Pencer® MIS Products.
Think blue for ergonomics, versatility and durability, Snowden-Pencer® in-line and pistol-grip laparoscopic instruments.
Snowden-Pencer® next generation reusable ring-handled laparoscopic instruments, CareFusion.
International Search Report and Written Opinion for International Application No. PCTUS/2015/028146, mailed Jun. 28, 2015.

* cited by examiner




FIG. 1
(PRIOR ART)




FIG. 2




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6








FIG. 6A






FIG. 7




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 7E




FIG. 8

1

SURGICAL DEVICE AND LINKAGE SYSTEM FOR SAME

FIELD OF THE INVENTION

The present invention relates generally to medical devices, and more particularly to a laparoscopic surgical device configured with a removable tool end assembly, and with a linkage system allowing for interchange of different actuator handles.

BACKGROUND

As depicted in FIG. 1, a typical monopolar electrosurgical laparoscopic tool device **100** generally has five main components: a handle **102**, an outer shaft **104** extending longitudinally from the handle, an actuation rod **106** extending through the outer shaft, an electrode **108** in electroconductive contact with the actuation rod, and an actuatable end effector **110**, disposed at the distal end of the device. The handle **102** illustrated is a “ring handle”, which has a stationary finger portion **112** attached to the outer shaft **104** and an actuatable thumb portion **114** attached to the actuation rod **106**. Actuation of the thumb portion **114** by pivoting relative to the finger portion **112** moves the actuation rod **106** axially within the outer shaft **104** to operate the end effector **110**. Although many different variations of each of the above components have been introduced into the art, there exists a need for designs that provide efficiency in manufacturing, and that provide surgeons and other users with ergonomic features to enhance safety and ease of use. In particular, there is a need for a handle design that includes an easy-to-use locking feature that provides for secure attachment and convenient detachment of a tool end assembly.

BRIEF SUMMARY

Embodiments of the present invention are configured to address the needs in the art for ergonomic and economically-efficient designs that present advantages in manufacture and use while helping medical facilities and patients to control expense. Preferred embodiments of the present invention may be configured such that they may be cleaned, sterilized, and reused, or they may be disposable. The most preferred embodiments of the present invention include a tool end retention mechanism that is biased so as to engage a one-piece or two-piece tool end assembly, which can be released using a two-button component of the retention mechanism, certain embodiments of which are shown in U.S. Pat. App. Publ. No. 2011/0306952 to Chen et al., which is incorporated herein by reference in its entirety. This retention mechanism provides a secure engagement of an outer shaft and an inner actuation rod of a tool end, as well as a handle that may be reusable. In certain embodiments, reusable tool end/tool tip assemblies may also be used. While embodiments of the present invention discussed herein are directed to aspects of a handle for a laparoscopic surgical device, those of skill in the art will appreciate that handle embodiments of the present invention may be used with a variety of shaft configurations and end effectors (e.g., needle holders, clamps, scissors, dissectors, graspers), and that such uses may be practiced within the scope of the present invention.

In one aspect, embodiments of a surgical device handle may include a tool body that includes an inner actuation rod reciprocally disposed through a longitudinal lumen of an outer shaft, where the distal ends of the rod and shaft may be permanently attached or may be removably attached with

2

each other and/or with a tool tip. In another aspect, each handle of an in-line configuration and/or an off-set pistol grip configuration includes a linkage member that provides for engagement with an actuation rod of a tool body that may interchangeably be used between those handle configurations and a standard pistol grip handle.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a prior art laparoscopic tool device;

FIG. 2 illustrates a disassembled view of first embodiment of a laparoscopic device including a pistol-grip handle embodiment;

FIG. 2A shows a longitudinal section view, taken along line 2A-2A of FIG. 2, of the tool body retention mechanism of the first handle embodiment;

FIG. 2B is a longitudinal sectional view of a proximal portion of the tool body outer shaft assembly taken along line 2B-2B of FIG. 2;

FIG. 2C shows a detail view of a proximal end portion of the actuation rod of the device of FIG. 2;

FIG. 2D shows an assembled tool body of FIG. 2;

FIGS. 3A-3B show a section view as in FIG. 2A, illustrating a method of assembly; and

FIG. 3C shows a distal end connection embodiment between the actuation rod and tool end shaft body;

FIG. 4 shows a detail perspective view of the distal end connection embodiment from FIG. 3C;

FIG. 5A shows a laparoscopic surgical device embodiment with an in-line handle;

FIG. 5B shows a laparoscopic surgical device embodiment with an off-set pistol-grip handle;

FIGS. 6-6A show a handle configured in the manner of the FIG. 5A embodiment, with a second handle member shown, respectively, in an actuation-range position and in an over-rotated (tool-body engagement/disengagement) position;

FIGS. 6B-6C show perspective views of a linkage member embodiment for the handle of FIGS. 6-6A;

FIGS. 6D-6E show detail perspective views of a ball cage for a linkage member embodiment of FIGS. 6B-6C;

FIGS. 7-7A show a handle configured in the manner of the FIG. 5B embodiment, with a second handle member shown, respectively, in an actuation-range position and in an over-rotated (tool-body engagement/disengagement) position;

FIGS. 7B-7C show perspective views of a linkage member embodiment for the handle of FIGS. 7-7A;

FIGS. 7D-7E show detail perspective views of a ball cage for a linkage member embodiment of FIGS. 7B-7C; and

FIG. 8 shows, in parallel, side views of linkage member embodiments for an in-line handle and an off-set pistol grip handle.

DETAILED DESCRIPTION

The exterior of a first embodiment of a laparoscopic surgical device **200** is illustrated with reference to FIGS. 2-2C. As shown in FIG. 2, which is a disassembled view of a “three-piece embodiment,” the handle **210** includes a thumb ring member **204** (commonly referred to as a “thumb bow”) pivotably attached at a pivot pin **208** to a finger ring member **206** (commonly referred to as a “finger bow”). The handle members **204**, **206** preferably are biased away from each other by, for example, a torsion spring or leaf spring. The thumb and finger ring members **204**, **206** preferably are constructed of a resin material but may alternatively be constructed of plastic or other materials known in the art to be suitable for multiple sterilizations in an autoclave. A

single-use embodiment may be constructed of materials known in the art, but not necessarily configured for multiple sterilizations. The device **200** may be configured as a monopolar or bipolar instrument configured for cutting and coagulation/electrocautery, including a Bovie post **207** or other electrode connection. A knob **212**, configured to rotate about its longitudinal axis in an indexed or smooth-rotating manner (various constructions for both of which are well-known in the art), may be included at the distal end of the handle **210**.

A tool end body including an elongate tubular outer shaft **240** extends distally from the finger ring member **206**. An actuation rod **260** extends distally from the thumb ring member **204** through a longitudinal lumen of the shaft **240** and includes a tool tip **270** at its distal end. At the distal end of the device **200**, an end effector **264** is operably connected both to the shaft **240** and the actuation rod **260**. The actuation rod connection to the outer shaft **240** may be permanent, or it may be removable (e.g., with a bayonet, threaded, snap-fit, or other connection). The shaft **240** may be constructed of metallic or polymeric materials, and preferably has an electroinsulative coating when the device **200** is configured as an electrosurgical instrument with a length that will most often be rigid, semi-rigid, or have very limited flexibility along its longitudinal axis. The shaft **240** preferably is configured for use with laparoscopy trocars for abdominal or other laparoscopic/minimally invasive surgical techniques (e.g., standard embodiments may have an outer diameter of about 5 mm to about 10 mm). All components of preferred embodiments will be configured to maintain fluid seal conditions desirable for use during a procedure on an insufflated patient. The handle **210** may include one or more ratchet mechanisms configured to assist a user in positioning and operating the device **200**. Detailed depictions of handle construction as well as examples of ratchet and other retention/manipulation mechanisms that may be used within the scope of the present invention include those described in U.S. Pat. App. Publ. No. 2007/0299469, to Carpenter et al., which is incorporated herein by reference.

FIG. 2A is a partial longitudinal section view of the handle **210** along line 2A-2A, showing the handle portion of an engagement mechanism for releasably connecting the tool body shaft **240** to the handle **210**. A central channel **211** extends through the knob **212** and the upper portion of the finger bow handle member **206**. This channel **211** is configured to receive the proximal ends of the tool body outer shaft **240** and inner actuation rod **260**. The thumb ring handle member **204** includes an opening **205** configured as a ball-cage that is configured to capture a proximal-end ball **262** of the actuation rod **260**.

The knob **212** substantially houses the shaft-engagement and rod-engagement portions of the engagement mechanism (the ball-cage **205** of the thumb bow **204** not being considered part of the engagement mechanism for purposes of the present description, although it serves an important function in retaining/actuating the inner rod **260**). The knob includes two opposing, depressible buttons **216**, **222**. As shown in FIG. 2A, the first button **216** is attached to and disposed opposite a two-toothed retaining member **218**, which includes teeth **219** that are biased up toward the first button **216** into the channel **211**. The second button **222** is attached to and disposed opposite a one-toothed retaining member **224**, which includes a tooth **225** that is biased down toward the second button **222** into the channel **211**. As shown, the retaining members and their teeth (which collectively may be referred to as "shutters") are permanently attached to the

handle **210** and in direct mechanical communication with their respective/corresponding buttons. Actuation of the retaining members is described below with reference to FIGS. 3A-3B. The bias for each of the retaining members is shown as being provided by coil springs, but other biasing means may be used, as known in the art.

FIG. 2B shows a longitudinal section view (taken along line 2B-2B of FIG. 2) of the proximal portion of the tool end body shaft assembly **240**. In this embodiment, an inner portion **242** of the shaft **240** is metal, and an outer covering portion **244** includes an electroinsulative polymer. In the embodiment shown, which is a "larger outer diameter" embodiment, the outer covering **244** is separated from the inner portion **242** of the shaft **240**, but—in certain "smaller outer diameter" embodiments, the outer covering **244** may be directly in contact with and/or be constructed as an overlay of the inner shaft portion **242**. A nose portion **246**, configured to be received in a complementarily shaped cavity of the knob **212** is mounted near the proximal shaft end. The nose portion **246** includes a flush port **247** that provides fluid communication with a longitudinal lumen **250** extending through the length of the shaft **240**. A proximal endmost portion of the shaft **240**, which is configured to be received into the handle channel **211**, includes at least first and second apertures that are at least partially opposed to each other. In the embodiment shown in FIGS. 2-3C, the first aperture is embodied as a pair of apertures **249** configured to align with and receive the first retaining member teeth **219**. The second aperture is embodied as an aperture **255** that is disposed opposite the first aperture and is configured to align with and receive the second retaining member tooth **225**.

FIG. 2C shows an external top-down view of the proximal portion of the actuation rod **260**. A ball **262** or other flared structure is disposed at its proximal end, configured for capture by the upper end of the thumb-ring handle member **204**. The ball **262** may include a larger outer diameter than a majority length of the rod **260** and most preferably includes a larger outer diameter than a rod portion immediately distally adjacent the ball. The inner rod **260** is configured to be slidably disposed through the shaft lumen **250**. As shown, a proximal rod length may include a larger outer diameter than a majority length of the rod **260** that will facilitate flushing of the shaft lumen **250** with the rod not being removed therefrom while providing a desirable proximal seal therebetween. Pivoting actuation of the thumb bow **204** relative to the finger bow **206** will longitudinally reciprocate the inner rod **260** relative to the shaft **240**. At its distal end the rod **260** includes a tool assembly **270** that is configured to be attached to the outer shaft **240**. This attachment may be removable, as is described below with reference to FIG. 3C, or it may be permanent such that the shaft **240** and rod **260** may be attached/removed from the handle **210** as a single unit. Embodiments where the rod and shaft are permanently connected may be configured to have the distal rod/shaft/tool assembly disposable after a single use or configured to be cleaned and/or sterilized. Many different tool tip assemblies **270** are known in the prior art for use/actuation with a reciprocating inner rod and an outer shaft that is relatively fixed. Tool tips may include clamps, graspers, cutting scissors, or other actuatable tool tips currently known or later-developed, while being practiced within the scope of the present invention. The inner rod **260** may be constructed as a single piece, or in multiple pieces, including that one or more portions (in addition to the proximal ball **262** may have a larger outer diameter than a majority length of the rod).

A proximal region of the rod **260** includes an elongate inner rod groove or aperture **267**. The inner rod aperture **267** is shown as generally obround, but may have varied internal geometry including that it may be embodied as a pair of opposing grooves that do not go all the way through the rod (not shown, but easily able to be understood by those of skill in the art as including a longitudinal wall between the opposed faces of the aperture **267**). It is configured to receive the ends of the first and/or second retaining member teeth **219**, **225**. When the teeth **219**, **225** are engaged with the inner rod aperture **267**, they will allow it to reciprocate longitudinally, but will generally prevent the rod **260** from rotating about its longitudinal axis. As such, when the teeth **219**, **225** are engaged through the outer shaft apertures **249**, **255** into the inner rod aperture **267**, they (the teeth) will: (i) generally maintain the outer shaft **240** in a fixed longitudinal and rotational position relative to the handle **210**; and (ii) generally maintain the inner rod **260** in a fixed rotational position relative to the outer shaft **240** and handle **210** while permitting it to reciprocate longitudinally relative to the handle **210** and outer shaft **240** upon pivoting actuation of the thumb bow **204** relative to the finger bow **206**. This structure and its related functionality are described below with reference to a method of assembling the device **200**.

In most embodiments, the thumb bow **204** will be rotatable relative to the finger bow **206** in only a single plane. However, handle constructions are known in the art, where out-of-plane rotation may be used. Preferred embodiments of the device **200** will include insulative material over all handle and other proximal-region surfaces that are likely to conduct current when the device is configured as an electrosurgical device and attached to an electrosurgical power supply. As shown in FIG. 3B, discussed below, in embodiments where a nose portion is used, it is permanently fixed to the outer shaft and will prevent the outer shaft from rotating relative to the engagement mechanism (whether that engagement mechanism is disposed in an indexing knob, as shown, or disposed in a fixed portion of the handle assembly **210**).

A method of assembling the device **200** of FIGS. 2-2C is described with reference to FIGS. 3A-3C. In FIG. 3A, the thumb bow **204** is over-rotated up and away from the finger bow **206**. This orientation exposes a top end opening of the ball-cage **205** in line with the proximal end of the longitudinal handle channel **211**. The inner rod **260** is disposed through the shaft lumen **250** and longitudinally directed into the handle channel **211**. The first and second buttons **216**, **222** are depressed in toward the central longitudinal axis of the engagement mechanism in the indexing knob **212**. This actuation of the first button **216** pushes the teeth **219** of the two-toothed retaining member **218** down and out of the handle channel **211**. Likewise, this actuation of the second button **222** pushes the tooth **225** of the second retaining member **224** up and out of the handle channel **211**.

With the retaining teeth **219**, **225** held out of the way, the handle channel **211** allows the inner rod **260** and outer shaft **240** to be advanced proximally thereinto until the proximal ball **262** of the rod enters and is captured by the ball-cage **205**. As shown in FIG. 3A, one or more of the teeth **219**, **225** may have an angled, cambered, or rounded distal surface such that the rod **260** and/or shaft **240** can more readily approach, dislodge, and pass the teeth, even if the buttons **216**, **222** are not initially fully depressed. The thumb bow **204** can be released and directed/pivoted down toward the finger bow **206**, fully capturing the ball **262** in the ball-cage **205**, which has a key-hole cross section such that a broader proximal portion engages the ball **262** while a narrower

distal portion prevents the ball from being released distally when the thumb bow **204** is rotated down as shown in FIG. 3B. The ball-cage **205** preferably will not interfere with actuation of the handle members nor of rotation of the inner rod **260** about its longitudinal axis. The elongate inner rod aperture **267** is visible in FIG. 3A, with the rod **260** and outer shaft **240** being shown about 90 degrees out of the rotational position that will allow the retaining teeth **219**, **225** to engage that inner rod aperture **267** through the outer shaft apertures **249**, **255**.

FIG. 3B shows the tool body assembly including the outer shaft **240** and inner rod **260** as being fully advanced proximally. The shaft **240** and rod **260** have been rotated and the buttons **216**, **222** have been released so that: (i) the shaft apertures **249**, **255** are aligned with the inner rod aperture **267**; (ii) the retaining teeth **219**, **225** are extended into their respective biased positions to engage the inner rod aperture **267** through the outer shaft apertures **249**, **255**; and (iii) the nose portion **246** is aligned and engaged with the indexing knob **212**. As shown in this engaged configuration/position, the inner rod **260** will reciprocate longitudinally relative to the outer shaft **240** and finger bow **206**, which are longitudinally fixed relative to each other. In embodiments where the indexing knob **212** is rotatable, the knob **212**, outer shaft **240**, and inner rod **260** can rotate relative to the handle **210** about their mutual longitudinal axis.

FIG. 3C shows one connection construction for embodiments of the device **200** wherein the inner rod **260** is removable from the outer shaft **240** rather than being permanently distally attached thereto. The tool tip **270** is shown as a grasper assembly, but may be constructed as cutting scissors, biopsy forceps, or any number of other laparoscopy-type tool tips. The proximal base **272** of the tool tip body is generally cylindrical and includes a bayonet groove having a longitudinal groove portion **274** and a radial groove portion **275**. The inner rod **260** is axially movable relative to the base **272**. FIG. 3C also shows the distal end of the outer shaft **240**, which includes a distal opening **257** configured to snugly receive the tip base **272**. A groove-engaging pin **258** extends radially into the opening **257**. FIG. 4 shows a perspective detail view of FIG. 3C.

When the actuation rod **260** is directed into the shaft lumen **250**, the groove engaging pin **258** can be guided to the distal end of the longitudinal bayonet groove portion **274**, then the tool tip can be rotated to engage the pin **258** to the end of the radial groove portion **275**. The bayonet mechanism including the pin and groove preferably is constructed such that when the pin **258** is fully engaged at the end of the groove **275**, the rotational position of the inner rod **260** aligns its proximal aperture **267** with the outer shaft apertures **249**, **255**. It should be appreciated that one, two or more bayonet pins and grooves may be used in various embodiments. In other embodiments, a threaded connection including a Luer-like connection requiring only a fractional turn for engagement (e.g., quarter-turn) or traditional multi-twist threading, snap-fit, reverse-bayonet, and/or other connection structures may be used to effect a connection between the distal ends of the shaft **240** and rod **260**, without departing from the scope of the present invention. Whether or not the rod and shaft are engaged with a handle, it is preferable that a distal connection of the outer shaft is configured to engage the distal regions of the inner rod and the outer shaft when the inner shaft aperture is rotationally aligned with at least one of the outer rod apertures.

In view of the ease of use and other advantages for the tool body and engagement/release system described above, it would be further advantageous to provide for using the same

or a similar system with other handle configurations. Specifically, as will be appreciated by those of skill in the art of laparoscopic surgical procedures, different handle configurations may be useful for different specific procedures (e.g., bariatric procedures) while using the same tool body and/or tool tip configurations for grasping, cutting, clamping, or otherwise manipulating tissue and surgical appliances (e.g., sutures, staples, needles, etc.). One example of known handle configurations is shown in FIG. 5A as an in-line handle 302 of a laparoscopic surgical device 300 including a tool body attached to the handle 302 with a two-button or other connection device (e.g., as shown and described above).

Another example of known handle configurations is shown in FIG. 5B as an off-set pistol-grip handle 402 of a laparoscopic surgical device 400 including a tool body attached to the handle 402 with a two-button or other connection device (e.g., as shown and described above), where the main gripping portion of the handle body is offset from the primary device longitudinal axis and is approximately intermediate the handle angles shown in FIGS. 2 and 5A. Other handle configurations, including those disclosed in U.S. Pat. No. 5,498,256 to Furnish et al. and U.S. Pat. No. 8,512,315 to Leonard et al. (each of which is incorporated herein by reference), often did not include a removable tool body, nor provide for an ability to readily and interchangeably use tool bodies with other handle configurations.

Currently, tool bodies are generally configured for use with just one of the handle configurations noted, and many devices are unitary, without even having the ability to exchange tool bodies between identical handles. It will be particularly useful to provide a linkage system for a handle that will provide for using the same tool bodies interchangeably between the different handle configurations. This will present advantages in the operating room for efficiency and effectiveness of surgical personnel, as well as potentially reducing procedure time and equipment costs, both of which are valuable areas for innovation.

The present disclosure includes a linkage system that provides for easily-releasable engagement (e.g., using the two-button system described above for quick, single-touch release) of a single tool body to any of the handles shown in FIGS. 2, 5A, and 5B. An assembled tool body including an outer shaft 240 and an inner rod 260 is shown in FIG. 2D, without a tool tip installed at the distal end (in contrast with the disassembled view of FIG. 2, which includes an installed tool tip 270 on the rod 260).

A first embodiment of a linkage member 380 is shown in FIGS. 6B-6E, for use in and with an in-line handle 300 shown in longitudinal section view (with a truncated tool body view) in FIGS. 6-6A. This handle configuration corresponds to that shown in FIG. 5A. The linkage member 380 includes an elongate body with a distal-end ball-engagement cage 381, an intermediate dual-camming region 382, and a proximal-end pivotable attachment structure 383. A first side 384 of the intermediate dual-camming region 382 includes a first contact portion 384a that is offset from, and oriented along a different (non-collinear) plane than, a generally longitudinal second contact portion 384c (where the planes of the first and second contact portions may be generally curved or flat).

As shown in greater detail in FIGS. 6D-6E, the ball cage 381 includes a ball-receiving socket 381a configured to snugly and securely receive a ball 262 of a tool body inner rod 260. The partially-closed distal end of the ball-receiving socket 381a also includes a notch 381b configured to engage circumferentially around at least a portion of the inner rod

260 immediately adjacent the ball 262 where the rod diameter is less than the ball diameter. As will be understood with reference to FIGS. 6-6A and to FIGS. 6D-6E, the orientation of the ball cage 381 and its socket 381a and notch 381b are dimensioned, oriented, and located to receive a ball 262 when a tool body including an inner rod 260 is being installed with a handle 300 including the linkage member 380.

FIG. 6 shows the handle 300 with the ball cage 381 engaged around the ball 262. When the handle 304 is actuated within normal actuation parameters, the second contact surface 384c of the linkage member 380 rides along the camming surface of the lower pin 359b. Reciprocating (up/down) actuation of the second handle member 304 corresponds to movement of the linkage along a line that is generally congruent with or parallel to a central longitudinal axis of the first handle and, perhaps more relevant, along the central longitudinal axis of the inner actuation rod 260 such that it moves reciprocatingly to actuate a tool tip.

As shown in FIG. 6A, the second handle member 304 (attached to the proximal end 383 of the linkage member 380) may be over-rotated away from the first handle member 306 to push the linkage member distally. This lifts the ball cage 381 out of a longitudinal axis defined by the inner rod 260 so that the ball 262 can be moved into or out of an engagement position relative to the ball cage 381. This out-of-axis movement is effected in part by interaction of first and second camming surfaces provided, respectively, by upper and lower pins 359a, 359b. In this embodiment, these pins are collinear with mounting screws for a ratchet pawl member 248. When the second handle member 304 is over-rotated, the first contact portion 384a contacts the lower pin 359a. Specifically, distal movement of the linkage member relative to the pins 359a, 359b levers the distal ball cage 381 upward, and proximal movement of the linkage member relative to the pins 359a, 359b levers the distal ball cage 381 downward (e.g., to where it will engage around an appropriately disposed ball 262).

As shown in FIG. 6, when the rod 262 is fully installed to this handle embodiment 300, the ball cage 381 fully and securely engages around a significant portion of the ball such that handle actuation (of the second handle member 304) predictably transmits force to and through the inner rod 260 so as to move it reciprocatingly relative to the outer shaft, along its longitudinal axis. During this generally longitudinal linear reciprocation, the second contact portion 384c of the linkage member 380 rides along or adjacent the lower pin 359b and generally linearly between the upper and lower pins 359a, 359b. A second side 385 of the intermediate dual-camming region 382 is opposite the first side 384 and is configured to interact complementarily with the upper pin 359a to facilitate the structure and function described above.

A second embodiment of a linkage member 480 is shown in FIGS. 7B-7E, for use in and with an offset-pistol-grip handle 400 shown in longitudinal section view (with a truncated tool body view) in FIGS. 7-7A. This handle configuration corresponds to that shown in FIG. 5B. The linkage member 480 includes an elongate body with a distal-end ball-engagement cage 481, an intermediate dual-camming region 482, and a proximal-end pivotable attachment structure 483. A first side 484 of the intermediate dual-camming region 482 includes a first contact portion 484a that is offset from, and oriented along a different (non-collinear) plane than, a generally longitudinal second contact portion 484c (where the planes of the first and second contact portions, whether curved or flat, may be generally parallel).

As shown in greater detail in FIGS. 7D-7E, the ball cage 481 includes a ball-receiving socket 481a configured to snugly and securely receive a ball 262 of a tool body inner rod 260, and also includes a notch 481b configured to engage circumferentially around at least a portion of the inner rod 260 immediately adjacent the ball 262. As will be understood with reference to FIGS. 7-7A and to FIGS. 7D-7E, the orientation of the ball cage 481 and its socket 481a and notch 481b are dimensioned, oriented, and located to receive a ball 262 when a tool body including an inner rod 260 is being installed with a handle 300 including the linkage member 480.

As shown in FIG. 7A, the second handle member 404 (attached to the proximal end 483 of the linkage member 480) may be over-rotated away from the first handle member 406 to push the linkage member distally. This lifts the ball cage 481 out of a longitudinal axis defined by the inner rod 260 so that the ball 262 can be moved into or out of an engagement position relative to the ball cage 481. This out-of-axis movement is effected in part by interaction of first and second camming surfaces provided, respectively, by upper and lower pins 459a, 459b. In this embodiment, these pins are collinear with mounting screws for a ratchet pawl member 248. When the second handle member 404 is over-rotated, the first contact portion 484a contacts the lower pin 459a. Specifically, distal movement of the linkage member relative to the pins 459a, 459b and contact with the first contact portion 484a levers the distal ball cage 481 upward, and proximal movement of the linkage member relative to the pins 459a, 459b levers the distal ball cage 481 downward (e.g., to where it will engage around an appropriately disposed ball 262).

As shown in FIG. 7, when the rod is fully installed, the ball cage 481 fully and securely engages around a significant portion of the ball such that handle actuation (of the second handle member 404) predictably transmits force to and through the inner rod 260 so as to move it reciprocatingly relative to the outer shaft, along its longitudinal axis. During this generally longitudinal linear reciprocation, the second contact portion 484c of the linkage member 480 rides along or adjacent the lower pin 459b and generally linearly between the upper and lower pins 459a, 459b. A second side 485 of the intermediate dual-camming region 482 is opposite the first side 484 and is configured to interact complementarily with the upper pin 459a to facilitate the structure and function described above.

FIGS. 6-6A and 7-7A, and the functionality of the linkage members 380, 480 may be further understood with reference to FIG. 8, which shows them aligned relative to each other in the position/alignment where each is shown in, respectively, FIG. 6 and FIG. 7. References to other handle components not shown in FIG. 8 (e.g. lower pin 359b, ball 262 of rod 260, etc.) should be understood with reference to FIG. 6 for the in-line embodiment and to FIG. 7 for the off-set pistol-grip embodiment.

A horizontal linkage embodiment 880 is (like linkage member 380 from FIGS. 6-6A) configured for use in an in-line handle. The horizontal linkage embodiment is shown in the upper portion of FIG. 8, with the first contact surface 884a that will, when advanced distally (left to right in the image), contact the lower pin 359b and will angle up the distal ball cage 881 out of its current long axis to disengage from a ball 262. The line followed for that motion intersects with the line that will be followed when the second contact surface 884c rides back and forth (right/left) across the lower pin 359b in a manner providing for generally longitudinal reciprocation of an actuation rod relative to a handle

body and outer shaft. Those of skill in the art of mechanical design will appreciate, in view of the present disclosure, that the lines of motion (and the contact surfaces that define them) may be straight or may have some curvature.

Similarly, but with modification for use in and oriented to show congruence with the offset angle of the off-set pistol-grip handle 400 shown in FIG. 7 (an angle shown here as about 30°), an angled linkage member embodiment 880 is shown in the lower portion of FIG. 8. Its first contact surface 984a will, when advanced distally (generally left to right in the image), contact the lower pin 459b and will angle up the distal ball cage 981 out of its current long axis to disengage from a ball 262. The line followed for that motion intersects with the line that will be followed when the second contact surface 984c rides back and forth (right/left) across the lower pin 459b in a manner providing for generally longitudinal reciprocation of an actuation rod relative to a handle body and outer shaft. The shape and relative orientation of the ball cage 981 and contact surfaces 984a, 984c differ from the horizontal embodiment in a manner providing the functionality described above.

As such, each of the linkage embodiments includes an engagement/disengagement region x84a along a first line, and an actuation region x84c along a second line. For each of these and the above-described embodiments, actuation of the handle that effects movement/contact along the actuation line/region will most preferably correspond to standard operating tolerances for opening/closing or otherwise actuating a tool tip of the surgical device. Over-rotation of the handle that moves the engagement/disengagement region into contact with internal handle components (e.g., pins 359/459) will slide and/or lever the distal ball cage into or out of a position for engaging a ball 262 of an actuation rod 260 of a tool body. It should be appreciated that the outer contours of ball cage surfaces and other surfaces of linkage member embodiments may be squared, rounded, or otherwise configured in a manner to fit and operate within a handle cavity without affecting the first and second lines defined by the first and second contact surfaces. Also, the socket of each ball cage may be tooled, molded, or otherwise worked/configured to form a generally spherical cavity that will conform around a proximal-end ball of an actuation rod.

In one aspect, certain embodiments may include a system or kit that includes more than one handle configuration (e.g., two or more of the handle configurations shown in FIGS. 2A, 5A, and 5B and/or other handle configurations). Such a system or kit may also include a plurality of tool bodies including an outer rod an inner shaft as described above. For embodiments where a tool tip is affixed onto an inner rod (constructed in a manner such as other tool/rod assemblies known in the art including the V. Mueller Switchblade® type of products), a plurality of such "rod+tip" configurations with different procedure-appropriate tool tips (e.g., biopsy forceps, straight or curved cutting scissors, graspers, clamps, retractors, and/or other tool tips known in the art) may be provided, where the handle configurations are interchangeable between engagement with the different tool bodies without special adapters or other modification. For embodiments with a removable tool tip, a plurality of such tool tips may be provided as part of the system or kit. As such, a system of the present disclosure can provide two or more different handle configurations with two or more readily-interchangeable tool bodies (each of which may have a plurality of tool tips for different surgical tasks). This ability for ready interchange of parts provides unique advantages for the present system as compared to previous systems.

Those of skill in the art will appreciate that there are known means for controlling the relative position/bias of the ratchet members disclosed above that are appropriate for use within the scope of the present invention, and that different materials may be useful in embodiments of the present invention, and particular ratchet systems (including, for example, those described in U.S. Pat. No. 7,846,177 to Carpenter et al. and U.S. Pat. No. 8,512,315 to Leonard et al., and U.S. Pat. App. Publ. No. 2010/0191225 to Leonard et al., each of which is incorporated by reference). Those of skill in the art will appreciate that embodiments not expressly illustrated herein may be practiced within the scope of the present invention, including that features described herein for different embodiments may be combined with each other and/or with currently-known or future-developed technologies while remaining within the scope of the claims presented here. It is therefore intended that the foregoing detailed description be regarded as illustrative rather than limiting. And, it should be understood that the following claims, including all equivalents, are intended to define the spirit and scope of this invention. Furthermore, the advantages described above are not necessarily the only advantages of the invention, and it is not necessarily expected that all of the described advantages will be achieved with every embodiment of the invention.

We claim:

1. A surgical instrument, comprising:
 - a handle comprising:
 - a first handle member;
 - a second handle member including a second handle member proximal end portion pivotably attached to a proximal end portion of the first handle member; and
 - an actuation mechanism configured to provide a releasable connection between the handle and a tool body, the actuation mechanism comprising an elongate linkage member disposed longitudinally within the first handle member,
 - where the linkage member includes an elongate body with a distal-end ball-engagement cage, an intermediate dual-camming region, and a proximal-end pivotable attachment structure that is attached to the second handle member,
 - where a first side of the intermediate dual-camming region slidably contacts a first camming surface within the first handle member, said first side including a generally longitudinal first contact portion and a second generally longitudinal contact portion offset from the first contact portion,
 - where the first side of the intermediate dual-camming region is dimensioned such that generally longitudinal movement of the linkage member along and relative to the first camming surface occurs along a first line when the first contact portion contacts the first camming surface and occurs along a second line, non-collinear with the first line, when the second contact portion contacts the first camming surface.
2. The surgical instrument of claim 1, further comprising a tool body, the tool body comprising:
 - a tubular outer shaft removably attached to the first handle member;
 - an inner rod extending through a longitudinal lumen of the outer shaft and including a proximal engagement ball, said proximal engagement ball having a larger outer diameter than the diameter of a longitudinal inner rod portion extending through the outer shaft, where

- the ball is removably receivingly engaged by the ball cage and thereby mechanically communicates with the second handle member in a manner providing reciprocal longitudinal movement relative to the outer shaft.
3. The surgical instrument of claim 2, wherein one of the handle and the tool body further comprises an indexing knob configured to rotate the tool body, relative to the handle, about a central longitudinal axis of the tool body.
4. The surgical instrument of claim 2, where the second line is generally congruent with or parallel to a central longitudinal axis of the first handle, and the second line is at an intersecting angle relative to the first line,
 - where the lines are oriented such, and the first camming surface, an intermediate transition surface of the linkage member, and a second camming surface are oriented such, that proximal-ward movement of the intermediate transition surface across the second camming surface moves the ball cage into engagement around the proximal engagement ball of the tool body.
5. The surgical instrument of claim 2, further comprising a tool tip attached to a distal portion of the outer shaft and the inner rod.
6. The surgical instrument of claim 1, where the handle is configured as one of an in-line grip handle or an offset pistol-grip handle.
7. The surgical instrument of claim 2, wherein the linkage member provides for interchangeable mounting of the tool body, which tool body is configured particularly for distal mounting into a selected pistol-grip handle, into any of:
 - said handle configured as an in-line grip handle, and
 - said handle configured as an offset pistol grip handle.
8. The surgical instrument of claim 2, where movement along the first line directs the ball cage, engaged around the ball, along an axis that is collinear with or parallel to a longitudinal axis defined by the inner rod.
9. The surgical instrument of claim 2, where distal movement of the linkage member along the second line directs the ball cage out of engagement around the ball, or proximal movement of the linkage member along the first line directs the ball cage into engagement with the ball.
10. The surgical instrument of claim 1, further comprising a ratchet mechanism for engaging the first handle member and second handle member.
11. The surgical instrument of claim 1, where at least one of the first camming surface and a second camming surface remains in contact with a surface of the linkage member throughout an operation of the handle.
12. A surgical instrument system comprising:
 - a surgical instrument according to claim 1, where the handle is a first handle;
 - a first tool body comprising:
 - a tubular outer shaft removably attached to the first handle member;
 - an inner rod extending through a longitudinal lumen of the outer shaft and including a proximal engagement ball, said proximal engagement ball having a larger outer diameter than the diameter of a longitudinal inner rod portion extending through the outer shaft, where the ball is removably receivingly engaged by the ball cage and thereby mechanically communicates with the second handle member in a manner providing reciprocal longitudinal movement relative to the outer shaft; and
 - at least one tool tip removably engageable with a distal end of the first tool body.

13

13. The surgical instrument system of claim 12, where the at least one tool tip comprises a plurality of interchangeable tool tips.

14. The surgical instrument system of claim 12, further comprising a second tool body.

15. The surgical instrument system of claim 12, further comprising at least one second handle configured differently from the first handle, where the at least one second handle is selected from a pistol-grip handle, an in-line grip handle, and an offset pistol-grip handle.

16. A surgical instrument system comprising:

a surgical instrument according to claim 1, where the handle is a first handle;

a first tool body comprising:

a tubular outer shaft removably attached to the first handle member;

at least one inner rod extending through a longitudinal lumen of the outer shaft and including a proximal engagement ball, said proximal engagement ball having a larger outer diameter than the diameter of a longitudinal inner rod portion extending through the outer shaft, where the ball is removably receivingly engaged by the ball cage and thereby mechanically communicates with the second handle member in a manner providing reciprocal longitudinal movement relative to the outer shaft; and

at least one tool tip affixed to a distal end of the at least one inner rod and removably engageable with a distal end of the tubular outer shaft.

17. The surgical instrument system of claim 16, where the at least one tool tip comprises a plurality of tool tips, each affixed to an inner rod and forming thereby an interchangeable unit removably engageable from the handle and outer rod.

18. The surgical instrument system of claim 16, further comprising at least one second handle configured differently from the first handle, where the at least one second handle is selected from a pistol-grip handle, an in-line grip handle, and an offset pistol-grip handle.

14

19. A surgical instrument handle comprising:

a first handle member;

a second handle member including a second handle member proximal end portion pivotably attached to a proximal end portion of the first handle member; and an actuation mechanism configured to provide a releasable connection between the handle and a tool body, the actuation mechanism comprising an elongate linkage member disposed longitudinally within the first handle member,

where the linkage member includes an elongate body with

a distal-end ball-engagement cage,

an intermediate dual-camming region, and

a proximal-end pivotable attachment structure that is attached to the second handle member and that provides for generally longitudinal reciprocating movement of the linkage member when the second handle member is pivoted relative to the first handle member,

where a first side of the intermediate dual-camming region slidably contacts a first camming surface within the first handle member, said first side including a generally longitudinal first contact portion and a second generally longitudinal contact portion offset from the first contact portion,

where the first side of the intermediate dual-camming region is dimensioned such that generally longitudinal movement of the linkage member along and relative to the first camming surface occurs along a first line when the first contact portion contacts the first camming surface and occurs along a second line, non-collinear with the first line, when the second contact portion contacts the first camming surface.

20. The surgical instrument handle of claim 19, further comprising a tool body including a proximal-end ball received by the ball cage.

* * * * *

专利名称(译)	手术装置及其连接系统		
公开(公告)号	US9480466	公开(公告)日	2016-11-01
申请号	US14/292210	申请日	2014-05-30
[标]申请(专利权)人(译)	CAREFUSION 2200		
申请(专利权)人(译)	CAREFUSION 2200 , INC.		
当前申请(专利权)人(译)	CAREFUSION 2200 , INC.		
[标]发明人	VAN DE WEGHE ANDREW P MINGIONE LOUIS P SCHECHTER DAVID A HAZLITT DAVID SCOTT		
发明人	VAN DE WEGHE, ANDREW P. MINGIONE, LOUIS P. SCHECHTER, DAVID A. HAZLITT, DAVID SCOTT		
IPC分类号	A61B17/00 A61B17/29 A61B17/28		
CPC分类号	A61B17/00234 A61B17/28 A61B17/29 A61B2017/0046 A61B2017/00424 A61B2017/00464 A61B2017/292		
助理审查员(译)	KONG , 清军		
其他公开文献	US20150342583A1		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种腹腔镜手术装置，包括可移除的包含工具的轴，其具有外轴和可移除地或永久地连接在一起的内致动杆。该装置的手柄包括用于接合和释放可移除的包含工具的轴的双按钮机构。双按钮机构构造成为接合延伸穿过外轴的外轴和内杆的重叠的对应孔，并且手柄可包括可容易地与不同工具主体互换地使用的各种构造。

