



US009549719B2

(12) **United States Patent**
Shohat et al.

(10) **Patent No.:** **US 9,549,719 B2**
(45) **Date of Patent:** ***Jan. 24, 2017**

(54) **RAPID LAPAROSCOPY EXCHANGE SYSTEM AND METHOD OF USE THEREOF**

(58) **Field of Classification Search**
CPC . A61B 17/02; A61B 17/1714; A61B 17/0218; A61B 17/3403; A61B 2017/00362
(Continued)

(71) Applicant: **EON Surgical Ltd., Tel-Aviv (IL)**

(72) Inventors: **Shaul Shohat, Kfar HaOranim (IL); Danny Farin, Hod-Hasharon (IL); Yehoda Bachar, Givat-Shmuel (IL); Ronny Winshtein, Tel-Aviv (IL)**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,300,035 A 4/1994 Clement
5,375,588 A 12/1994 Yoon
(Continued)

(73) Assignee: **EON SURGICAL LTD., Tel-Aviv (IL)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 53 days.

This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

JP 2007-534380 A 11/2007
WO 94/22382 A1 10/1994
(Continued)

Primary Examiner — Mary Hoffman
Assistant Examiner — Tara R Carter

(74) *Attorney, Agent, or Firm* — Baker and Hostetler LLP

(21) Appl. No.: **14/274,281**

(22) Filed: **May 9, 2014**

(57) **ABSTRACT**

(65) **Prior Publication Data**

US 2014/0343360 A1 Nov. 20, 2014

A system for positioning an interchangeable tool in a body cavity includes a channel having a lumen in direct communication with the body cavity, a tool introducer having a longitudinal axis and a distal end, and a tool holder covering at least a portion of the interchangeable tool that is pivotally connected to the tool introducer allowing angular positioning of the interchangeable tool after the tool holder emerges from the channel into the body cavity. A method for engaging an interchangeable tool with a distal portion of a tool manipulator in a body cavity includes inserting a tool introducer into a channel, orienting the distal portion of the tool manipulator in the body cavity, emerging the interchangeable tool from the channel into the body cavity, and positioning the interchangeable tool eccentrically to the lumen of the channel.


Related U.S. Application Data

(63) Continuation of application No. 13/010,661, filed on Jan. 20, 2011, now Pat. No. 8,721,539.
(Continued)

(51) **Int. Cl.**
A61B 1/32 (2006.01)
A61B 17/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 17/0218** (2013.01); **A61B 1/00154** (2013.01); **A61B 17/3403** (2013.01);
(Continued)

19 Claims, 14 Drawing Sheets



Related U.S. Application Data

- (60) Provisional application No. 61/296,485, filed on Jan. 20, 2010.
- (51) **Int. Cl.**
A61B 17/34 (2006.01)
A61B 1/00 (2006.01)
A61B 17/00 (2006.01)
A61B 17/29 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 2017/00362* (2013.01); *A61B 2017/2931* (2013.01); *A61B 2017/3407* (2013.01); *A61B 2017/3466* (2013.01)
- (58) **Field of Classification Search**
 USPC 606/96-98, 205-208; 600/201-230
 See application file for complete search history.

5,658,306	A	8/1997	Kieturakis et al.
6,146,402	A	11/2000	Munoz
6,197,002	B1	3/2001	Peterson
6,312,443	B1	11/2001	Stone
8,137,267	B2	3/2012	Shelton, IV et al.
8,852,253	B2	10/2014	Mafi
2003/0130693	A1	7/2003	Levin et al.
2005/0234294	A1	10/2005	Saadat et al.
2006/0200184	A1	9/2006	Deal
2007/0073323	A1	3/2007	Carter et al.
2007/0179507	A1	8/2007	Shah
2008/0228213	A1	9/2008	Blakeney et al.
2008/0287926	A1	11/2008	Abou El Kheir
2009/0259175	A1	10/2009	Nordgren
2009/0259184	A1	10/2009	Okoniewski
2009/0270676	A1	10/2009	Sicvol

FOREIGN PATENT DOCUMENTS

- (56) **References Cited**
 U.S. PATENT DOCUMENTS
 5,441,059 A 8/1995 Dannan
 5,645,549 A * 7/1997 Boyd A61B 18/1402
 606/45

WO	03-015848	A9	2/2003
WO	2005-122921	A2	12/2005
WO	2007008332	A3	1/2007
WO	2007073931	A1	7/2007

* cited by examiner




FIG. 1A











FIG. 1B








FIG.4A
(Prior Art)




FIG.4B




FIG. 5A





FIG. 5B






FIG. 5C






FIG. 5D




FIG. 5E








FIG. 5F






FIG. 7A




FIG. 7B





FIG. 7C





FIG. 10A




FIG. 10B






FIG. 10C




J2



I2

FIG. 10D






FIG. 10E








FIG. 10F





RAPID LAPAROSCOPY EXCHANGE SYSTEM AND METHOD OF USE THEREOF

RELATED APPLICATIONS

This application is a continuation of U.S. Non-Provisional application Ser. No. 13/010,661, filed on Jan. 20, 2011, which claims priority to U.S. Provisional Application Ser. No. 61/296,485, filed Jan. 20, 2010, both entitled Rapid Laparoscopy Exchange System And Method Of Use Thereof, and both of which are hereby incorporated by reference herein in their entireties.

FIELD OF THE INVENTION

The present invention generally relates to surgical methods and devices, and more specifically to laparoscopic and/or any endoscopic related surgical interventions.

BACKGROUND OF THE INVENTION

Laparoscopic or minimally invasive surgery includes the use of several relatively small ports into the abdomen by which different types of instrumentation and accessories are introduced and used for different surgical interventions (usually performed under endoscopic vision). Although usually considered superior in several aspects to open surgery, the use of plurality of 5 to 15 mm ports still leads to local pain, scars, and possibly port related complications such as hernia in scars and the need for one or two assistants in addition to the surgeon. Laparoscopic methods and surgical device are described, for example, in U.S. Pat. Nos. 5,980,493, 7,593,777 and 7,316,699, the disclosures of which are fully incorporated herein by reference.

In past years, new versions of laparoscopic systems and approaches were introduced to overcome several of the "classic" laparoscopy disadvantages, mainly the Single-Port Access (SPA) and the Needlescopy approaches. In SPA the surgeon operates almost exclusively through a single entry point, typically through the patient's navel, using access ports and hand instrument. Highly experienced and skilled physicians may still use standard laparoscopic hand instruments, although the use of a single port access decreases its triangulation and complicates maneuverability. The use of special-purpose articulating instrumentation was introduced to overcome this difficulty, although it is considered very expensive, necessitates special training and still involves complex surgical maneuverability.

Minilaparoscopy/needlescopic laparoscopy is intended to overcome the problems encountered in single port access surgery. While the advantages of SPA includes improved cosmetic, less abdominal wall pain and less incision related complications, this surgical approach has its disadvantages. The vision is partially obscured by the paralleled inserted instruments; there is minimal triangulation and limited maneuverability of the surgical instruments. Minilaparoscopy maintains the same mode of surgery as standard laparoscopy however there is only one trocar and all the rest of the instruments are connected to needle like shafts which are inserted with no trocar and therefore provide comparable cosmetic and painless results as SPA.

In needlescopy, the laparoscopic ports are replaced with small incisions, usually between 2 to 3 mm in diameter. The surgery is performed by inserting narrow guide tubes into the small incisions and then passing tiny instruments through the tubes, while using a small television camera for guidance. The small instruments have very slender tips

which make dissection and tissue maneuveration very difficult. Furthermore the instrument tips may have a greater tendency to break and their removal may be cumbersome and difficult.

In order to avoid such difficulties while maintaining small incision porting, it has been advised to combine the single-port and the needlescopic approaches. This is achieved by first inserting regular-sized interchangeable end-effectors through a regular size single port access and then detachably attaching them to corresponding distal portions of needle-sized manipulators. The manipulators are protruding into abdomen cavity via miniature needlescopic type incisions. The concept and several device derivatives were described in the following patents, the disclosures of which are fully incorporated herein by reference.

U.S. Pat. No. 5,352,219 to Reddy describes a two-part modular tool and method for use thereof in conjunction with laparoscopic techniques enhances such techniques by enabling tools to be manipulated within a body cavity through small needle holes. The tool has an instrument head initially inserted through a laparoscopic port and an acuminate shaft which intracorporeally attaches to the instrument head. The instrument head is then manipulable through the needle hole at the site of desired use. The instrument head may be any tool configuration useful in surgical procedures which can be miniaturized to pass through a laparoscopic port.

U.S. Pat. No. 5,441,059 to Dannan describes a method of conducting minimally invasive surgery that includes the steps of making a primary incision; importing at least one surgical instrument head through the primary incision; making at least one secondary incision, smaller than the primary incision and the cross-section of the surgical instrument head, for a handle; extending the distal end of the handle through each secondary incision; attaching one of the surgical instrument heads to the distal end of the handle; manipulating the surgical instrument head with the handle to which it is attached; detaching the surgical instrument head from the handle; removing the surgical instrument head through the primary incision; and withdrawing the distal end of the handle from the secondary incision.

U.S. Pat. No. 6,723,043 to Kleeman et al. describes a surgical instrument assembly that includes an operative element and an insertion instrument removably engageable to the operative element. The insertion instrument is positionable in a patient with the operative element engaged thereto to position the operative element at an operative site in the patient. A transfer instrument is removably engageable to the operative element when the operative instrument is located at the operative site. The insertion instrument can then be removed. Methods for using the surgical instrument assembly are also disclosed.

SUMMARY OF THE INVENTION

In a broad aspect of some embodiments there is provided a laparoscopic system applicable for delivering, guiding and/or coupling an interchangeable laparoscopic end-effector (e.g., surgical tool) to a distal portion of a tool manipulator in a body cavity. Appropriately utilizing the system may constitute a shorter duration, reduced uncertainty and improved safety of procedure preparation and initiation.

In some embodiments, the interchangeable surgical tools are of regular laparoscopic size and are sequentially deliverable through a single regular laparoscopic port (usually between 5 and 10 mm in diameter). Once delivered into body cavity, each surgical tool may then be connected to a

slender shaft manipulator having a diameter of 5 mm or less, optionally about 2 mm or less. The surgical tool may be connected to the manipulator distal end by a variety of interlocking means, including snap-lock mechanisms.

Optionally, a tool introducer may be used to position the interchangeable surgical tool in a chosen operation site within body before coupling to a tool manipulator. The introducer or manipulator distal end may have a pivoting connection to the surgical tool. An introducer pivoting distal end may be selectively angled for remote manipulation.

In some embodiments, at least one endoscope and/or camera may be introduced via the laparoscopic port to monitor surgical procedure and/or tool guidance and transfer between introducer and manipulator. An endoscope may have an angled or beveled tip for viewing the process of connecting between tool and manipulator. An endoscope/camera may be inserted through the port/trocar any time before or after the tool introducer is positioned there. In some embodiments, the laparoscopic system includes a special purpose monitoring endoscope: besides using a camera to monitor procedure as custom in laparoscopic procedures, a special purpose endoscope (which may be a standard/commercially available or specially designed endoscope) may be advanced via an introducer inner lumen for monitoring adaptor/interlocking operation. In some embodiments, a detachable mini-camera optionally in the form of a capsule or an end-effector is percutaneously introduced into the body cavity in a minimally invasive technique (e.g., using a tool introducer), and connected to a previously introduced tool holders (e.g., a distal end of a tool manipulator).

In some embodiments, the laparoscopic system includes an external guiding template indicating specific insertion ports for trocar and/or manipulators. Optionally, each port is specifically designed to guide a manipulator to a specific orientation within body for a rapid and accurate in-vivo coupling to an interchangeable end-effector. The operator may selectively choose between a fixed manipulator guiding, that is relevant for manipulator introduction into body and engaging with the effector, and a free manipulator movement, relevant for proper surgical intervention. A template frame may be procedure-specific and/or patient-specific (and allow all possible relevant ports) or adjustable according to need. It may be operated manually and/or remotely. Beneath or included in the template frame, there may be an adhesive sealant cloth and/or pad that provides adequate sealing around port/incision to avoid contamination and CO₂ leakage.

In some embodiments, the laparoscopic system includes a needlescopic manipulator supporting mechanism capable of setting a specific chosen position of a miniature element (e.g., effector or camera) within body. The supporting mechanism may be operated manually or robotically, and allow fixedly 3O orientation change of the miniature element manipulator/holder (slender shaft/handle). The supporting mechanism may be a truss-based mechanism or a ball-socket mechanism; may include a ratchet mechanism and may be implemented in the external guiding template, for example in or in association to at least one of its ports.

In some embodiments, the laparoscopic system includes a surgical tool vectoring mechanism selectively and/or automatically altering introducer distal end when/after the effector is protruding into body through the trocar, in order to facilitate accurate and rapid engagement with manipulator distal end. The vectoring mechanism may allow an accurate, timely direction shift of the surgical tool/effector with respect to tool-holder longitudinal axis. Optionally, the tool

is detachable from the introducing tool holder, and is further connectable to a second tool holder (e.g., a manipulator) that is substantially parallel and/or collinear and/or concentric with respect to a receiving portion of the tool/adaptor after the said direction shift. The vectoring mechanism may be passive (e.g., using a spring/nitinol set to shift the tool to a predetermined direction), or active/adjustable (e.g., either mechanically—for example by maneuvering the introducing tool holder along the trocar path, or electronically/robotically—after the tool is completely protruding through the trocar).

Optionally, an end-effector may be coupled to manipulator using rapid interlocking means (e.g., snap locking means). In some embodiments, the laparoscopic system includes a “handoff” coupling mechanism, i.e., a double-action locking mechanism allowing secure passing between two end-portions of laparoscopic slender shafts (e.g., trocars, manipulators, introducers, etc.) whereby the effector is released from introducer only after interlocking with manipulator and vice versa. Optionally, a special tool removal device may be used for detaching an effector to/from a manipulator, or this may be performed by the tool introducer itself.

According to an aspect of some embodiments there is provided a system for positioning an interchangeable tool in a body cavity, the system comprising:

a channel comprising a lumen in direct communication with the body cavity;

a tool introducer comprising a longitudinal axis and a distal end, the tool introducer is capable of traveling through the channel lumen; and

a tool holder covering at least a portion of the interchangeable tool, the tool holder is pivotally connected to the tool introducer distal end, thereby allowing angular positioning of the interchangeable tool after the tool holder emerges from the channel into the body cavity.

In some embodiments, the angular positioning is predetermined. Alternatively and/or additionally, the angular positioning is constant. Alternatively and/or additionally, the angular positioning is selectively chosen after the tool holder emergence into the body cavity.

In some embodiments, the interchangeable tool includes a passage for accommodating a distal portion of a tool manipulator. Alternatively and/or additionally, the angular positioning positions the passage with respect to the distal portion of the tool manipulator. Alternatively and/or additionally, the passage is concentric to the distal portion of the tool manipulator after the angular positioning.

In some embodiments, the interchangeable tool comprises one of the group consisting of a grasper, a dissector, a needle holder, scissors, a camera, an endoscope, a heat source, a sensing probe, a cryogenic probe, a dissector, a biopsy probe, a cutting tool, a laser source, an IR source, a light source, an illumination source, an ultrasound probe, an electrocautery device, a drug delivery device and combinations thereof.

In some embodiments, the system further comprising an external guiding device configured to guide a tool manipulator to engage the interchangeable tool in the body cavity, wherein the guiding device comprises:

a center guide comprising a first lumen adapted to accommodate the channel;

an adjustable peripheral guide having a proximal end connected to the center guide and a distal end incorporating a second lumen; wherein:

the tool introducer is distally connected to the interchangeable tool and readily deployed in the body cavity through the channel accommodated in the first lumen of the center guide; and

the adjustable peripheral guide is adjusted to guide the tool manipulator through the second lumen to engage the interchangeable tool.

In some embodiments, the external guiding device is further adapted to guide a distal portion of the tool manipulator in a defined orientation and/or depth in the body cavity. Alternatively and/or additionally, the external guiding device is adapted to selectively lock the distal portion of the tool manipulator in the orientation and/or depth. Alternatively and/or additionally, the distal portion of the tool manipulator is concentric to an inner passage of said interchangeable tool.

In some embodiments, the second lumen includes a longitudinal axis that is angled towards the center guide in at least one dimension.

In some embodiments, the adjustable peripheral guide is adjustable by at least one of: lengthening, bending, tilting, rotating, deforming and/or any combination thereof.

In some embodiments, the interchangeable tool is tilted with respect to the tool introducer.

In some embodiments, the system further comprises an external frame comprising at least one external guiding device.

In some embodiments, the tool holder is a tool cartridge.

In some embodiments, the tool introducer comprises a tubular section. Alternatively and/or additionally, the tubular section further comprises an endoscope deployable in the tubular section. Alternatively and/or additionally, the tubular section includes a window, thereby enabling endoscopic visualization by the endoscope.

According to an aspect of some embodiments there is provided a method for engaging an interchangeable tool, the tool having an inner passage, with a distal portion of a tool manipulator in a body cavity, the method comprising the steps of:

inserting a tool introducer into a channel, the channel comprising a lumen providing direct communication into the body cavity and wherein a proximal end of said interchangeable tool is reversibly connected to a distal end of the tool introducer;

orienting the distal portion of the tool manipulator in the body cavity;

emerging the interchangeable tool from the channel into the body cavity; and positioning the interchangeable tool eccentrically to the lumen of the channel

wherein the inner passage of the interchangeable tool is angled towards the distal portion of the tool manipulator.

In some embodiments, the positioning is automatically executed once the interchangeable tool entirely emerges from the channel. Alternatively and/or additionally, the positioning is selectively executed by an operator.

In some embodiments, the method further comprising predetermining an angle of the positioning of the interchangeable tool. Alternatively and/or additionally, the method comprising using a constant angle for the positioning of the interchangeable tool. Alternatively and/or additionally, the method further comprising selectively choosing an angle of the positioning of the interchangeable tool after emerging the interchangeable tool. Alternatively and/or additionally, the inner passage of the interchangeable tool is concentric to the distal portion of the tool manipulator after the positioning.

In some embodiments, the orientating step is accomplished by means of an external guiding device.

In some embodiments, the method further comprises the steps:

advancing the distal portion of said tool manipulator to engage with the inner passage of the interchangeable tool; and

engaging the distal portion of the tool manipulator with the inner passage of the interchangeable tool. Alternatively and/or additionally, the method further comprising the steps of locating the distal end of the tool manipulator before introducing the interchangeable tool by:

introducing an elongated tool introducer through the lumen into the body cavity and moving the distal end of the tool introducer into a position adjacent to a position to which the distal portion of the tool manipulator is oriented and guiding the distal end of the tool manipulator to engage with the inner passage when the interchangeable tool is emerged into the body cavity

and/or

introducing an elongated channel, the channel comprising a lumen, into the body cavity and moving the distal end of the elongated channel into a position in the body cavity adjacent to a position to which the distal portion of the tool manipulator is oriented and guiding the distal end of the tool manipulator to engage with the inner passage when the interchangeable tool is emerged into the body cavity; and

advancing the distal portion of tool manipulator to engage with the inner passage.

In some embodiments, the method and further comprising the step of capturing the distal end of the tool manipulator at an entry point of the tool manipulator as the distal end of the tool manipulator emerges into the body cavity and before the distal end of the tool manipulator moves substantially into the body cavity by utilizing the elongated tool introducer and/or the elongated channel having an lumen.

In some embodiments comprising monitoring the engaging procedure via an endoscope situated in a tubular section of the tool introducer.

In some embodiments, the interchangeable tool is housed in a tool holder.

In some embodiments, the first lumen is a laparoscopic port having a diameter that is equal or more than 5 mm. In some embodiments, the second lumen is a needlescopic port having a diameter that is equal or less than 3 mm. Optionally, the second lumen includes a longitudinal axis that is angled towards the center guide in at least one dimension. Optionally, the adjustable peripheral guide is adjustable by at least one of: lengthening, bending, tilting, rotating, deforming and/or any combination thereof. Optionally, the interchangeable tool is tilted with respect to the tool introducer.

BRIEF DESCRIPTION OF THE DRAWINGS

Some embodiments of the invention are herein described, by way of example only, with reference to the accompanying drawings. With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of embodiments of the invention. In this regard, the description taken with the drawings makes apparent to those skilled in the art how embodiments of the invention may be practiced.

In the drawings:

FIGS. 1A-B illustrate rapid laparoscopy system in operation, and a corresponding zoom-in portion, in accordance with an exemplary embodiment of the present invention;

FIG. 2 illustrates a rapid-laparoscopy external template, in accordance with an exemplary embodiment of the present invention;

FIGS. 3A-H illustrate several deployment possibilities of a rapid-laparoscopy external template, in accordance with an exemplary embodiment of the present invention;

FIGS. 4A-B illustrate exemplary prior-art and an optional laparoscopic ports schemes, in accordance with an exemplary embodiment of the present invention;

FIGS. 5A-F illustrate an exemplary interchangeable tools insertion system and steps of introduction thereof, in accordance with an exemplary embodiment of the present invention;

FIGS. 6A-B illustrate a side view and a corresponding top cut-view of a tool nested in an introduced cartridge, in accordance with an exemplary embodiment of the present invention;

FIGS. 7A-C illustrate several interlocking possibilities to a tool, in accordance with an exemplary embodiment of the present invention;

FIG. 8 illustrates a side view of a tool connected to manipulator, in accordance with an exemplary embodiment of the present invention;

FIG. 9 illustrates a side view of a tool connected to a manipulator pressed against a tool cartridge, in accordance with an exemplary embodiment of the present invention;

FIGS. 10A-F illustrate several regular and cut views of tool interlocking with a cartridge and release from a manipulator, in accordance with an exemplary embodiment of the present invention; and

FIGS. 11A-C illustrate two alternative ways of positioning a trocar and a tool-introducer inside the body cavity for safely connecting an interchangeable tool to a manipulator, in accordance with an exemplary embodiment of the present invention.

DETAILED DESCRIPTIONS OF EXEMPLARY EMBODIMENTS

(a) Exemplary Rapid Laparoscopy System

FIG. 1 illustrate an exemplary rapid laparoscopy system 100 deployed in patient body 200 (shown in a “sliced” proportion for demonstrative purposes), the system includes an introducing sleeve 110 and at least one tool manipulator 140. In some embodiments, sleeve 110 is a trocar having a tubular body 112 and a substantially sharp or blunt distal end that is capable of channeling a surgical tool 130 into a cavity within body 200 using a tool introducer 120. Sleeve 110 may be of any preferred size, and usually between 3 to 20 mm in diameter, optionally 5 to 10 mm (e.g., similar in size to regular laparoscopic port). Sleeve 110 may be sized (e.g., smallest cross section) to accommodate a largest of tools 130 in a specific tool kit. In some embodiments, system 100 includes a single regular-sized laparoscopic port that may be utilized for tool(s) 130 insertion into body and/or connection to manipulator(s) 140.

Tool 130 may be any operational element (e.g., a probe or an instrument) deployable within a body, including but not limited to: surgical tools, grasping elements, dissectors, needle holders, clippers, scissors, connecting (e.g., stapling) elements, biopsy related instruments, sensor elements, imaging elements, clamping or grasping devices, heat generating probes (including RF, laser, IR, light, etc.), cryogenic probes, cutting and dissecting devices or energy sources, ultrasound probes, etc. In some embodiments, tool 130 is interchangeable and may be releasably attached to a distal

tip 146 of manipulator 140, as shown in FIG. 1B. In some embodiments, tool 130 includes a tool head or effector 132 (e.g., grasping means as presently illustrated), a body 134 and an inner passage 136 for accommodating a manipulator distal tip 146. In some embodiments, tool 130 further includes locking mechanism (not shown) that allows safe coupling to manipulator 140.

In some embodiments, introducer 120 includes a tubular body 122, with an optional distal projection (optionally, tail-like), that is associated with (e.g., connected to, for example by using a Babcock grasper) tool 130. In some embodiments, tool introducer 120 is releasably connected to tool 130 and/or to any sort of adapter or cartridge 124 (shown in FIG. 5) that may be associated with (e.g., connect to or contain) tool 130 until deployment and/or operation. In some embodiments, introducer 120 allows a defined 30 orientation of tool 130 within body, thus providing a simpler and a potentially rapid approach for engaging manipulator 140 with inner passage 136 of tool 130. Optionally, tool 130 orientation is selectively chosen, optionally adequately accurate. Optionally, tool 130 is oriented to a specific predefined position, for example by using a pivoting mechanism that combines spring energy and motion limiting (not shown). Alternatively or additionally, tool orientation is achieved by manual or computerized operation, either remotely or at site. In some embodiments, introducer 120 and/or any associated tool holder, adapter or cartridge, further includes a safe tool passing mechanism (not shown), optionally a “handoff” type mechanism, which allows release of tool 130 only after the latter is safely interlocked with manipulator 140, and optionally vice versa.

In some embodiments, manipulator 140 includes a shaft 142, distal tip 146 and a tool operating handle 144. Shaft 142 and tip 146 largest cross section may be 0.5 to 5 mm in diameter, optionally 1 to 2.5 mm, optionally about 1 mm, about 1.5 mm or about 2 mm or higher or lower or intermediate. Tip 146 is optionally sharp and/or pointed in order to allow at least one of tissue penetration and easier engagement into tool inner passage 136. Optionally, tip 146 is a Veres needle which optionally permits penetration through skin and abdominal wall tissue while preventing injury of internal organs (e.g., bowels), when not “armed”. Optionally, tip 146 includes interlocking means, e.g., threading or a groove for snap-locking (not shown), for firmly connecting with tool 130. Handle 144 may be any manually operated type laparoscopic instrumentation handle or may be replaced with any robotic or other non-manually operated arm. In some embodiments, handle 144 includes mechanisms which operates tool 130 and/or their association (e.g., locking or releasing modes or operations).

At least part of the instruments are made from rigid biocompatible materials as known to a person skilled in the art, and may include stainless steel, optionally hardened or reinforced by carbon coating or fibers, ceramic materials, plastic/polymeric materials (e.g., PEEK), composite materials (e.g., carbon-epoxy), or any combination thereof.

In some embodiments, rapid laparoscopy system 100 further includes at least one, and preferably at least two, intraoperative imaging devices (e.g., microcameras and/or endoscopes), at least one of which can be used to monitor tool 130 transfer, locking and/or handoff from introducer 120 to manipulator 140, and optionally vice versa. Optionally, tool handoff monitor is an endoscope 128 (as shown in FIG. 5) located within or adjacent to trocar 110 and/or introducer 120. Additionally or alternatively, a grasped microcamera is transferred into body via trocar 110 using introducer 120 and then handed over to one of manipulators

140 which locates it in a preferred position to monitor the surgical operation. Other microcameras and/or endoscopes may be deployed in other locations using different manipulators.

In some embodiments, manipulator **140** is supported with an external holding device **150** which allows selective locking of manipulator in a certain positioning. This may be especially advantageous for example when a physician chooses to fixate a tool (e.g., a grasper) in a certain position while avoiding any unnecessary movements for a chosen period of time, and/or when he needs to occupy his hands with other manipulator(s). Holding device **150** may use a manipulator shaft grasper associated with a locking and/or guiding elements (not shown), thereby allowing selective alternating between a free movement mode and a position locking/guiding mode.

Reference is now made to FIG. **2** showing patient body **200** setting prior to a rapid laparoscopy procedure using an exemplary external holding device **150** in a form of template. In some embodiments, device **150** includes a template frame **154**, a single tool introducer opening **156** and a plurality of manipulators openings **158**. Frame **154** includes several extensions upon which laparoscopic instrumentation may be supported, the extensions may be provided in a predefined design according to a specific instrumentation allocation pattern (as derived from a specific surgical method) or may be assembled or manipulated (e.g., manually, electronically or other) to a different chosen arrangement.

Frame **154** may have a curved base for improved fitting over patient body **200** and/or may include fastening elements (not shown), such as fastening belts, for a firmer connection to patient body **200**. Frame **154** may be made from any rigid or semi-rigid material, including metals, plastics and polymers.

External holding device **150** may include introducer-manipulators coordinating means which allow accurate manipulator engagement with a tool-head within body by guiding the manipulator in a specific correlated angle, plane and/or depth with respect to the tool head.

Exemplary holding device **150**, as specifically illustrated in FIG. **2**, is adapted for a single-port micro-laparoscopic procedure in which a single regular-sized laparoscopic port is used for delivering regular-sized laparoscopic instrumentation into body to be assembled to and operated with micro-sized, "needlescopic", manipulators. Accordingly, in some embodiments, tool introducer opening **156** is approximately 5 to 15 mm in diameter (although it may be changed to or replaced with to different sizes according to need) in order to allow regular sized tools and endoscope(s) as accustomed in "classic" laparoscopy approaches. Furthermore, in some embodiments, manipulators openings **158** are approximately 1 to 2.5 mm in diameter in order to allow needlescopic manipulation of tools within body with substantially lessened scarring effect of body **200**.

Exemplary holding device **150** may include or be provided with a sealing pad or sheath **152** that may be especially useful in order to seal any entrapped gaseous substances (e.g., CO₂) within cavity of body **200**, and/or for protecting against any potential contamination as may be resulted in case of directly communicating with open air. Sealing pad **152** may be made from any relatively pliant or elastic material such as soft polymer or silicone, while maintaining re-sealing capabilities when pierced with a micro-sized element, such as a needle (similarly to a septum seal).

Device **150** may serve as a needle introducer template using specific pre-set orientation means. This may be advan-

tageous especially for rapid location and handoff of tool **130** from introducer **120** to manipulator **140**, as device **150** may be used to guide manipulator distal tip **146** adequately accurately towards tool inner passage **136**. An exemplary pre-set orientation means are illustrated in FIGS. **3A-B**, in which tool manipulator **140** is operated through manipulator opening **158** and a portion of sealing pad **152**. As shown in FIG. **3A**, a needle guiding element **148** is placed over a portion of shaft **142** and maintains a specific orientation according to a preformed design of opening **158**. Optionally, guiding element **148** is a sleeve, optionally a splitting sleeve, and is made of a relatively rigid material, such as metal, plastic or polymer. After tool **130** is connected to manipulator distal end **136** and released from introducer **120**, guiding element **148** may be removed and manipulator can be freely maneuverable as illustrated in FIG. **38**. FIG. **3C** illustrates a different type of an exemplary external supporting and/or guiding mechanism for manipulator **140** that includes a socket and a ball **151** design. Manipulator shaft **142** is passed through a lumen in ball joint **151** and allowed to freely move. Manipulator shaft **142** may be selectively paused in a specific orientation by deploying ball-joint lock **153**.

Reference is now made to FIG. **30-H** schematically illustrating possible applications of external holding device **150** having a template arm **155**. In some embodiments, template arm **155** is applied for coordinating a rapid and accurate engagement of manipulator shaft **142** distal end and a tool coupled to cartridge or any other coupling element **124** that is angularly connected to introducer body **122**. In some embodiments, the engagement coordination includes guiding at least two members in body to a specific point and a specific angle in a **30** coordinate system within body **200** in order to allow the rapid and accurate engagement. In some embodiments, template arm **155** includes at least one introducer path **156** and at least one manipulator path **158** that are located in the same plane, optionally a perpendicular plane (e.g., a sagittal plane or a transverse plane) of patient body **200**, optionally an anterior or a posterior plane. In some embodiments, at least one of introducer path(s) and manipulator(s) path(s) are at least partially circular thereby allowing a relative rotation of circular shaft therein. Additionally or alternatively, at least one of the paths includes a specific mating pattern (not shown), for example a recess, a protrusion or any non-axisymmetrical shape, thereby allowing sliding of a shaft therein, the shaft having a mating cross section in a specific predetermined sliding plane into body.

FIG. **30** illustrates a template arm **155** having a single introducer path **156** and a single manipulator path **158**, that are angled one with respect to the other in a same plane. In some embodiments, trocar body **112** is inserted through introducer path **156** thereby channeling introducer body **122** into patient body **200**. In some embodiments, introducer body **122** is coupled to an interchangeable tool (not shown) via a tool coupling element **124** that takes an angular orientation with respect to introducer body **122** when it is completely emerged in body **200** through trocar body **122**. In some embodiments, manipulator shaft **142** is inserted through manipulator path **158** and travels into body **200** in an angled orientation towards coupling element **124**. In some embodiments, coupling element **124** (and/or a tool coupled to and/or an inner passage of the tool) are in same angle and same plane as manipulator shaft **142** when are inserted through paths **156** and **158**, respectively, of template frame **155**. In some embodiments, at least one of paths **156** and **158** includes a guiding slot, recess, projection, etc. (not shown) that necessitates tool-manipulator engagement in

same point and/or angle and/or plane within body **200**. Additionally or alternatively, markings are used to allow instruments manipulation within body to the desired tool-manipulator orientation.

In some embodiments, template arm **155** is rotational around path **156** in order to allow penetration points of same or different manipulator(s) shaft(s) **142** around said rotational axis. FIGS. **3E-3G** suggest different template arms **155a**, **155b** and **155c**, which further allow penetration ports at different lengths along its longitudinal axis. In this way, an operator may use a single template arm to insert a plurality of manipulators at different penetration ports (e.g., as illustrated in FIG. **4B**) which are located in different angles and lengths with respect to tool introducing port **210b**.

FIG. **3E** illustrates a template arm **155a** having a single introducer path **156** and a plurality of manipulator paths, in this case three manipulator paths **158a**, **158b** and **158c**. In some embodiments, at least some of the manipulator paths are angled in such a way that manipulator passing there-through will engage a tool in the same depth but in a different angle (so at least two paths will have different angles) or in a different depth but in the same angle (so at least two paths will have same angles), or any combination thereof. FIG. **3F** illustrates a template arm **155b** having a single introducer path **156** and at least one, optionally a single, manipulator path **158**. In some embodiments, template arm **155b** has at least two parts, a first part that includes path **156** and a second part that includes path **158**, that are telescopically connected, thereby allowing a selective distance alternation between the two paths.

FIG. **3G** illustrates a template arm **155c** having a similar approach to arm **155b**, but uses at least two members jointly coupled to allow a selective distance alternation between introducer path **156** and manipulator path **158**.

In some embodiments, for example when a template arm having a single manipulator path **158** is used, an operator may still choose a path angle. In some embodiments, path **158** is angled, either automatically or manually, using a mechanism (not shown) which correlates the distance between paths **156** and **158** and/or the depth of tool coupling element **124** and/or the angle of coupling element **124**. Alternatively or additionally, manipulator insertion angle may be altered while using a constant manipulator path **158** angle, using angle adaptors **143** that are assembled (permanently or detachably) to a portion of manipulator shaft **142** (as illustrated in FIG. **3H**).

(b) Exemplary Micro-Laparoscopy Approach

The present invention will provide descriptions for laparoscopic cholecystectomy procedures, although it should be clear that the proposed treatment and medical tools can be applied in many different minimally invasive and/or anterior and/or endoscopic surgical procedures.

FIG. **4A** illustrates a prior-art laparoscopic cholecystectomy procedure which utilizes a minimal sum of four laparoscopic ports:

(1) An endoscope port **210a** of approximately 10 mm in diameter, usually located at patient's umbilicus. Port **210a** allows insertion of a trocar by which an endoscope may be inserted into body;

(2) A main operating port **220a**, approximately 10 mm in diameter, usually located below the sternum. Port **220a** allows insertion of different types of surgical and other instruments, for example tools for suction, clipping, dissecting, cutting and hooking;

(3) Two graspers ports **230b**, approximately 5 mm in diameter each, usually located adjacently below the right-lateral ribs. Commonly, two graspers are delivered through ports **230b** to grasp and hold the gall bladder in a certain position prior to executing surgical intervention steps.

In a normal laparoscopic cholecystectomy, the abdomen is first inflated with CO₂ via a 2.5 mm special-purpose Veres-needle, followed by opening of ports **210a**, **220a** and **230a**. An endoscope is then inserted through port **210a**. After the abdomen is thoroughly scanned, graspers are introduced through ports **230a**. A first grasper grasps the gall bladder at the Fundus region and then stretches and pushes it over the liver. A second grasper grasps the gall bladder at the Infundibulum region to maneuver it laterally towards abdomen walls, thereby uncovering the cystic duct and the cystic artery. Several surgical instruments are then serially introduced via port **220a**. At first, a dissector is used to separate between the cystic duct and artery, a clipper is then introduced to block inflow of duct and artery, later to be both cut by scissors. Finally, the gall bladder is separated using hooks or scissors and removed from patient body through port **210a** (either as a whole or in pieces).

The use of a combined single-port laparoscopy and needlescopy approaches, allows the surgeon more flexibility in choosing a laparoscopic ports scheme that may be procedure-specific and/or patient-specific. For example, the use of slender manipulators allows more flexibility in choosing a number of manipulators and associated tools to be applied simultaneously or in sequence while optionally covering larger or smaller operated regions. Furthermore, more imaging and/or illumination sources may be introduced and operated at different regions within abdomen, thus allowing improved visual monitoring of procedure and tool handling within body. Once a camera is situated within body (e.g., via a needlescopic port) and abdomen cavity is adequately monitored, an endoscope may be considered unnecessary or be pulled in and out the single laparoscopic port for sequential tools introductions into the abdomen through this port.

FIG. **4B** illustrates an optional exemplary porting scheme for laparoscopic cholecystectomy, which may be advantageously utilized using a rapid micro-laparoscopy approach of the present invention:

(1) A tools introducing port **210b** of approximately 10 mm in diameter, usually located at patient's umbilicus. Port **210b** allows insertion of a trocar by which tools (e.g., tools **130**) may be sequentially inserted into body optionally followed by an endoscope. The 10 mm port may serve to introduce regular size instruments such as clippers, Ligasure/harmonic scalpel, suction, electrosurgical hook, etc.;

(2) At least one camera port **220b** of approximately 1 mm in diameter, usually located adjacently below the left-lateral ribs. A micro-camera (sized 1 to 10 mm in diameter) may be inserted through port **210b** using a tool introducer (e.g., introducer **120**) and transferred to a manipulator that is operated and/or protruding through port **220b**. Alternatively or additionally, an even smaller camera (sized 1 mm or less) may be delivered into body directly through the 1 mm incision of port **220b**;

(3) At least two graspers' ports **230b** of approximately 2 mm in diameter each, usually located adjacently below the right-lateral ribs. Similarly to the micro-camera, the graspers may be delivered through port **210b** and connected to manipulators protruding through ports **230b**.

(4) Optionally one or more illuminator ports **240b** for holding illumination source, such as LED illumination, IR light, regular light, fiber optics etc. Port **240b** is approximately 1 mm in diameter and located adjacently to port

220b, also below the left-lateral ribs. This may be especially useful in case that the mini-camera does not include indigenous illumination capabilities, for example in view of the importance to minimize its size.

In some embodiments, similarly to normal laparoscopic cholecystectomy, the abdomen is first inflated with CO₂ using a 2.5 mm special-purpose Veres-needle. Camera and illumination manipulators are then introduced through 1 mm incisions made as ports **220b** and **240b**, respectively. Port **210b** is then opened and a trocar is introduced. An interchangeable mini-camera and illumination are then introduced via the trocar at port **210b** and connected to corresponding manipulators distal ends protruding at ports **220b** and **240b**. Two 5 mm sized interchangeable graspers may then be introduced via port **210b** and connected to corresponding manipulators distal ends protruding at ports **230b**. The rest of the surgical procedure steps may be carried out as in the prior art approach previously described, while “regular” laparoscopy instruments are inserted to abdomen and manipulated via port **210b**. Alternatively, at least one interchangeable surgical tool replaces a “regular” laparoscopy instrument and delivered to abdomen cavity later to be connected to a corresponding needlescopic manipulator that is located at a special purpose port (not shown) according to need and/or surgeon choice.

In some embodiments, an external holding device or template **150** is used for any of the purposes previously described, whereas a specific template frame **154** design and/or template frame **155** are chosen and/or assembled at-site according to the requested laparoscopic porting scheme.

(c) Exemplary Deployment of a Rapid Micro-Laparoscopy System

Reference is now made to FIGS. 5A-F illustrating an exemplary rapid micro-laparoscopy system **100** and steps of introduction of tools therethrough. For demonstrative purposes, in FIGS. 5A-C a tool itself is not illustrated.

In some embodiments, after deployment of system **100** as previously described, a trocar **110**, having a tubular body **112** of about 10 mm in diameter, is introduced through port **210b** thereby allowing a safe passage of laparoscopic tools and instrumentation into body. Optionally, an introducer **120** having a body **122** of about 5 to 9 mm in diameter is inserted through trocar **110**. Optionally, body **122** is tubular with an inner diameter of equal or less than 8 mm, optionally about 5 mm, and allowing insertion therethrough of endoscope **128** which is about 8 mm or less in diameter. In some embodiments, endoscope **128** is a side-vision endoscope having a lens **129** projected through a special lateral opening **127**, and can provide monitoring for the tool exchange within body via lateral window(s) **125** of body **122**. Body **122** includes a distal end **126** that is pivotally connected to tool cartridge **124** currently illustrated without a tool for demonstrative purposes.

Phase A of a tool delivery is illustrated in FIG. 5A where an assembly of introducer body **122**, endoscope **128** and cartridge **124** are traveled within trocar body **112** lumen towards abdomen cavity.

Phase B of tool delivery is illustrated in FIG. 5B where cartridge **124** almost entirely protrudes out of trocar **110** lumen. Tool introducer distal end **126** including lateral window **125** also protrudes, so endoscope monitoring may be initiated.

In Phase C (FIG. 5C), cartridge **124** is oriented with respect to the longitudinal axis of trocar-introducer assembly

after entirely protruded into body cavity. In some embodiments, a released potential energy based device (e.g., a released spring motion; not shown) is used for a passive cartridge **124** altering to a specific, optionally predefined orientation, optionally further using any orientation control mechanism (such as a motion limiter, a designated cam, an electronic control element, etc.). Alternatively or additionally, cartridge **124** alternation is actively performed either manually or remotely via a robotic arm. In some embodiments, cartridge **124** and/or the encapsulated tool longitudinal axis are substantially parallel or concentric to manipulator shaft **146**, thereby allowing a rapid engagement and connecting therebetween, as suggested in phase D (FIG. 5D).

The last delivery phase E (FIG. 5E) takes place once or after tool **130** is appropriately connected to manipulator shaft **146**. In a first embodiment, two distinct locking mechanisms (not shown) are situated in cartridge **124** and/or tool **130** and are used for locking the tool to cartridge **124** and to manipulator shaft **146**, respectively. In a second embodiment, the two locking mechanisms are interrelated in a way that when a first lock is in locked mode the second lock is in released mode, and vice versa, thus allowing a “handoff” passing of the tool in a secure way.

Once phase E is complete, and tool **130** is connected to manipulator **140** and disconnected from introducer **120**, the tool may be utilized to its designated task. In case that an external template **150** is used for guiding manipulator shaft **146** towards tool **130**, the guiding element (e.g., guiding sleeve **148**) may be released or removed, thereby allowing relatively free movement of manipulator shaft **146**.

(d) Exemplary Tool Handoff Delivery

Reference is now made to FIG. 6 that illustrate a side view and a corresponding top cut-view of an exemplary tool **1300** nested in an exemplary cartridge **1240** that is connected and/or part of an exemplary tool introducer **1200** having a body **1220**. An exemplary needlescopic manipulator shaft **1400** is proximately distant and optionally concentric to tool **1300** suggesting an initial pre-connecting phase (e.g., phase C as previously described).

In some embodiments, cartridge **1240** is pivotally connected to introducer body **1220** with a pivot **1210** thereby allowing at least partial rotation around pivot **1210** axis. Optionally, cartridge **1240** rotation is accomplished using a spring mechanism (not shown) or by any other means known to art. Optionally, a desired 30 cartridge/tool orientation is accomplished by maneuvering cartridge **1240** from outside patient body, either manually or remotely.

In some embodiments, tool **1300** is an interchangeable grasper having a head **1320**, body **1340** and an inner passage **1360** capable of telescopically accommodating a distal tip of manipulator **1400**. Optionally, grasper **1300** is approximately 5 mm in diameter. In some embodiments, for example as illustrated in FIG. 6, only grasper head **1320** is encapsulated by cartridge **1240**, within cartridge tool head housing **1242**, whereas at least part of grasper body **1340**, optionally most or all its length, extends outwardly within body cavity. Cartridge **1240** may further include a tool grasper **1270** for locking grasper head **1320** within housing **1242** or selectively releasing it when deployed.

Reference is now made to FIG. 7A illustrating a top cut-view of grasper **1300**, having a tubular frame **1342**, nested in cartridge **1240** while interlocked with a manipulator distal tip **1460**. Optionally, tool **1300** includes a beveled tool opening **1362** for an easier accommodation of manipulator distal tip **1460**. In some embodiments, tool

1300 includes a manipulator tip lock 1370 situated along a portion of inner passage 1360, for snap-locking to a distal tip of manipulator 1400, using a lock beveled opening 1372 and a lock narrow section 1374 which is designed to mate with a corresponding recess 1462 located proximally to manipulator tip 1460. In some embodiments, tip lock 1370 is connected at its proximal side to a tool inner shaft 1380 and is blocked from moving distally by a releasing mechanism lock widener 1394 shown in FIG. 7 in a locking position. In some embodiments, lock widener 1394 has a rounded portion 1396 for an optional selective smoother proximal travel within lock beveled opening 1374. In some embodiments, lock widener is coupled to a releasing mechanism outer sleeve 1392 that is rotatable around tool body tubular frame 1342.

When locked to manipulator 1400, grasper 1300 may now be released from tool cartridge 1240 as illustrated in FIG. 8. In some embodiments, when grasper 1300 is distally pulled (e.g., by manipulator 1400) it easily disconnects from cartridge 1240 by laterally widening cartridge tool grasper 1270 during pullout. Optionally, a threshold force is required for achieving disconnection in order to avoid unintentional tool escapes from cartridge grasping.

Additionally or alternatively, grasper release is achieved by unlocking a second locking mechanism that releasably holds it within cartridge housing 1242. FIGS. 7B and 7C illustrate another exemplary design for manipulator 1400 in unlocked and locked modes, respectively. In some embodiments, manipulator 1400 includes an inner shaft 1422 having a distally pointed end 1460, an intermediate sleeve 1466 having a distal compressible portion 1464 and optionally maintains substantially same outer diameter with shaft 1422 maximal diameter, and an outer sleeve 1424. In some embodiments, compressible portion 1464 expands and/or send arms when compressed, thereby produced interlocking when engaged into a recess in a smaller diameter lumen. Optionally, compressible portion 1464 includes a tubular portion that is elastic and/or braided and/or slitted and/or bellowed (i.e., includes bellows). Optionally, compressible 1464 includes a stent-like design, optionally a cage-like design, optionally includes at least one strip that is bendable to an arch. Optionally, outer sleeve 1424 is connectable to tool 1300 and allows rotatability to an inner rotatable part and/or a sliding movement of an inner slidable part of tool 1300. Optionally, outer sleeve rotates and/or slides with respect to shaft 1422 and/or intermediate sleeve 1466 thereby allowing operation of tool 1300 and/or locking/unlocking modes shift. Optionally, locking and unlocking are achieved by relative movement of shaft 1422 and intermediate sleeve 1466 (e.g., by pulling or pushing sleeve 1466 proximal end).

(e) Exemplary Tool Removal

In some embodiments, after final utilization of a tool and/or at procedure termination the tool should be disconnected from its corresponding manipulator 1400 and be safely removed from body via tool introducing port 210b. Optionally, special removing device and/or tool grasping cartridge are used (not shown). Alternatively, same instrumentation is used in a substantially reverse order for tool(s) removal. Reference is now made to FIG. 9 illustrating a side view of grasper 1300 connected to manipulator 1400 while pressed against cartridge 1240. In some embodiments, cartridge tool grasper 1270 includes a tool opening teeth 1272 including beveled end portions 1274 allowing tool grasper

widening when grasper head 1320 is pressed against it with a force that exceeds a defined threshold force.

Now that grasper 1300 is re-nested in cartridge 1240 a second mechanism is operated for releasing the grasping of manipulator tip 1460 and disconnecting from manipulator 1400, as illustrated FIG. 10. In some embodiments, releasing mechanism outer sleeve 1392 includes a diagonal slot 1397 that is engaged with a pin 1398 laterally projecting from tool body inner shaft 1380. Optionally, outer sleeve 1392 and inner shaft 1380 can slide and/or rotate one with respect to the other, so that pin 1398 travel from a first corner (position 11 in FIG. 10C) to a second corner (position 12 in FIG. 10D) of diagonal slot 1397 is accomplished by a proximal partial sliding of inner shaft 1380 and its rotation counter-clockwise partial rotation with respect to outer sleeve 1392.

In some embodiments, tool body tubular frame 1342 includes an L-slot 1344 that is engaged with a pin 1382 laterally projecting from tool body inner shaft 1380. Optionally, tubular frame 1342 and inner shaft 1380 can slide and/or rotate one with respect to the other, so that pin 1382 travel from a first corner (position J1 in FIG. 10C) to a second corner (position J2 in FIG. 10D) of L-slot 1344 is accomplished by a proximal partial sliding of inner shaft 1380 and its rotation counter-clockwise partial rotation with respect to tubular frame 1342.

Since that pin 1398 and pin 1382 are both projections of inner shaft 1380, a counter-clockwise rotation of the inner shaft promotes a relative inward motion between tool frame 1342 and outer sleeve 1392. Referring back to FIG. 7A, releasing mechanism lock widener 1394 is situated with respect to lock beveled opening 1372 in a manner that corresponds to positions I1/J1 (FIG. 10C). In some embodiments, lock widener 1394 is firmly connected to outer sleeve 1392 in a manner that denies lengthwise movement between them, so that when frame 1342 and outer sleeve 1392 are moving inwardly, lock beveled opening 1372 and lock widener 1394 are moving inwardly as well, resulting in widening of opening 1372 by widener 1394. This allows manipulator tip 1460 removal from tool inner passage 1360, so that tool 1300 may be removed from body via port 210b. FIG. 10E illustrates the widening of opening 1372 by widener 1394 in a manner that corresponds to positions I2/J2 (FIG. 10D).

In some embodiments, the lengthwise and/or rotational movement of inner shaft 1380 (hence of pins 1398 and 1382) is executed by a corresponding motion of a manipulator body 1420. As shown in FIG. 10F, body 1420 comprises a shaft 1422 and an outer sleeve 1424, optionally capable of relative rotation. In some embodiments, tool inner passage 1360 includes at least one tenon 1364 which engages corresponding recesses or slots (not shown) on manipulator outer sleeve 1424, thereby denying rotational movement between them. Hence, in some embodiments, when manipulator 1400 is traveled inward and/or counter-clockwise rotated, tool inner shaft 1380 follows the same movement and consequently manipulator 1400 is disconnected from tool 1300 and may be easily pulled out.

(f) Other Exemplary Embodiments

In some embodiments, the system is connectible and/or is part of a surgical robotic system and/or a telesurgery system. In an exemplary embodiment, at least one of: introducer, tool, tool-cartridge, manipulator, template, template arm, are controlled and/or operated robotically and/or remotely.

In some embodiments, the system includes at least partial fail-proof locking mechanisms, for example between the

tool and the tool-cartridge and/or between the tool-cartridge and the introducer and/or between the tool and the manipulator distal end. In an exemplary embodiment, a locking mechanism is normally opened, hence in a fail-mode will resume unlocked mode, or vice versa.

In some embodiments, a system locking mechanism includes pneumatic and/or hydraulic and/or electronic components. Optionally the locking mechanism includes sensors which detect connection and/or disconnections of two elements (e.g., tool and cartridge, tool and manipulator, cartridge and introducer, etc.). Optionally, in a fail-mode situation, a passive locking mechanism may be bypassed with a different active locking mechanism (e.g., remotely manually operated), and vice versa.

In some embodiments, the system is designed to allow only a specific sequence of steps. One of many sequences may include the step of connecting and/or deploying a template arm in a specific manner; followed by the step of introducing an introducer into body and pivoting cartridge to a predetermined orientation in body; followed by the step of introducing a manipulator shaft using the template arm to directly engage and connect to the tool nested or connected to the cartridge; followed by the step of releasing the tool from the cartridge. In some embodiments, this "one-way" sequence may be applied by using a control mechanism that allows a proper utilization of a second locking element only after a first locking element was properly utilized, and vice versa.

(g) Exemplary Positioning of the Tool-Introducer

System **1000** is deployed prior to utilization in a body cavity, for example, an abdominal cavity **2000**. System **1000** includes a laparoscopic working channel or port, referred to here as, but not limited to, a trocar **1100**, and at least one handheld micro-laparoscopic manipulator referred to as tool manipulator **1400**. Tool manipulator **1400** includes a shaft **1420** and an operation handle **1440**. Shaft **1420**, such as a slender shaft, is configured to be attached at its distal end to a detachable and/or an interchangeable surgical end-effector or tool (not shown). In some embodiments, the tool manipulator could be configured as described herein in respect to FIG. 6-10.

In FIG. 11A, trocar **1100** and tool manipulator **1400** are positioned after insertion into abdominal cavity **2000** and prior to attachment of a tool. Optionally, trocar **1100** may be housing an endoscope (not shown). In order to attach the tool to the distal end of shaft **1420**, the surgeon needs to position it adjacent to the lumen of trocar **1100** by aiming towards the endoscope lens (or "towards his eye" as seen in the monitor). Optionally, the endoscope is then withdrawn from trocar **1100**. A tool introducer then introduces a tool through the path of the trocar **1100**. In some embodiments the endoscope is deployed in the tool introducer. In some further embodiments the introduction of a tool and the transfer of the tool between a tool introducer and the shaft **1420** could be performed according to any of the methods described herein.

A tool may be any operational element (e.g., a probe or an instrument) deployable within a body, including but not limited to: surgical tools, grasping elements, dissectors, needle holders, clippers, scissors, connecting (e.g., stapling) elements, biopsy related instruments, sensor elements, imaging elements, clamping, clipping elements or grasping devices, heat generating probes (including RF, laser, IR, light, etc.), cryogenic probes, illuminating elements cutting and dissecting devices or energy sources, ultrasound probes,

camera or other imaging probes, lenses, lenses tubes, or any other optical instruments, etc.

Trocar **1100** may be of any preferred size, and usually between 3 mm to 20 mm in diameter, optionally about 10 mm or 12 mm (e.g., similar in size to regular laparoscopic port). Trocar **1100** may be sized (e.g., smallest cross section) to accommodate a largest of a surgical tool in a specific tool kit. In some embodiments, system **1000** includes a single regular-sized laparoscopic port that may be utilized for tool(s) insertion into the body and/or connection to the tool manipulator **1400**.

In some embodiments, shaft **1420** includes a distal tip. The largest cross section of the shaft and tip may be 0.5 mm to 5 mm in diameter, optionally 1 to 2.5 mm, optionally about 1 mm, about 1.5 mm or about 2 mm or higher or lower or intermediate. The shaft tip is optionally sharp and/or pointed in order to allow at least one of tissue penetration and easier engagement with a tool. Optionally, the shaft tip is a Veres needle which optionally permits penetration through skin and abdominal wall tissue while preventing injury of internal organs (e.g., bowels) when not "armed". Optionally, shaft **1420** includes interlocking means, e.g., threading or a groove for snap-locking (not shown), for firmly connecting with the tool, or alternatively by any means of friction, pressure or other means known to the art. Handle **1440** may be any manually operated type laparoscopic instrumentation handle or may be replaced with any robotic or other non-manually operated arm. In some embodiments, handle **1440** includes mechanisms which operate the introduced tool(s) and/or their association (e.g., locking or releasing modes or operations).

At least part of the instruments are made from rigid biocompatible materials as known to a person skilled in the art, and may include stainless steel, optionally hardened or reinforced by carbon coating or fibers, ceramic materials, plastic/polymeric materials (e.g., PEEK), composite materials (e.g., carbon-epoxy), or any combination thereof.

In some situations, the process of maneuvering the tool manipulator **1400** until locating the trocar **1100** may be difficult, time consuming and/or unsafe, due to the possibility that the shaft **1420** may harm adjacent tissues. Reference is now made to FIGS. 11B-C, illustrating different (partial) deployment stages of a second schematically illustrated exemplary micro-laparoscopic system, in accordance with an exemplary embodiment of the invention. This embodiment comprises an elongated tool introducer **1200** (as shown in Figs.) and/or an elongated trocar **1100** (not shown). An elongated tool introducer **1200** assists in locating and guiding distal end of shaft **1420** before transferring the tool to the shaft **1420**. The elongated tool introducer **1200** is introduced via trocar **1100**, and travels into the abdominal cavity **2000** until it is adjacent the distal end of shaft **1420** (as shown in FIG. 11B). In this embodiment, an endoscope (not shown) may be placed inside the elongated tool introducer **1200**. Additionally and/or alternatively an elongated trocar **1100** could be used to locate and guide the distal end of shaft **1420** before introducing the tool introducer **1200** into the lumen of the trocar **1100**. If an elongated trocar **1100** is utilized an endoscope could in some embodiments be placed inside the trocar **1100**.

Additionally or alternatively to using an elongated trocar **1100** and/or an elongated tool introducer **1200**, other locating and/or guiding and/or grasping/connecting devices (not shown) may be used to locate and/or guide and/or grasp shaft **1420** in the abdominal cavity **2000** and assist in transferring and engaging the interchangeable tool.

FIG. 11C suggests a slightly different approach using a substantially longer or more distally advanceable elongated tool introducer 1200' (shown) and/or elongated trocar 1100 (not shown), which is sized and/or configured to advance towards and to reach at and/or capture the inlet/incision or a position adjacent to the inlet/incision of manipulator 1400 through and into abdominal cavity 2000, so the tip of the shaft 1420 may be captured at the entry of the abdominal cavity 2000, located at the periphery of the abdominal cavity 2000. In some instances it will be preferable to use this approach, as may be important not only to prevent injury to organs but also to prevent working against the direction of viewing which may be considered cumbersome.

In some embodiments the release, transfer and engagement of the interchangeable tool could then be performed according to any of the methods described herein. Alternatively, such release, transfer and engagement maybe performed in other methods known to the art.

Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the spirit and broad scope of the appended claims.

All publications, patents and patent applications mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual publication, patent or patent application was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present invention. To the extent that section headings are used, they should not be construed as necessarily limiting.

What is claimed is:

1. A system for positioning an interchangeable tool in a body cavity, the system comprising:
 - a channel comprising a lumen for direct communication with said body cavity;
 - a tool introducer comprising a longitudinal axis and a distal end, said tool introducer is capable of traveling through said channel lumen; and
 - a tool holder covering at least a portion of said interchangeable tool, said tool holder is pivotally connected to said tool introducer distal end for angular positioning said interchangeable tool in said body cavity after said tool holder emerges from said channel,
 wherein said tool introducer comprises a tubular section.
2. The system according to claim 1, wherein said angular positioning is predetermined.
3. The system according to claim 1, wherein said angular positioning is constant.
4. The system according to claim 1, wherein said angular positioning is selectively chosen after said tool holder emerges from said channel and into said body cavity.
5. The system according to claim 1, wherein said interchangeable tool comprises one of the group consisting of a grasper, a dissector, a needle holder, scissors, a camera, an endoscope, a heat source, a sensing probe, a cryogenic probe, a dissector, a biopsy probe, a cutting tool, a laser source, an IR source, a light source, an illumination source, an ultrasound probe, an electrocautery device, a drug delivery device and combinations thereof.
6. The system according to claim 1, and further comprising an endoscope deployable in said tubular section.

7. The system according to claim 6, wherein said tubular section includes a window, thereby enabling endoscopic visualization by said endoscope.

8. A system for positioning an interchangeable tool in a body cavity, the system comprising:

- a channel comprising a lumen for direct communication with said body cavity;
 - a tool introducer comprising a longitudinal axis and a distal end, said tool introducer is capable of traveling through said channel lumen;
 - a tool holder covering at least a portion of said interchangeable tool, said tool holder is pivotally connected to said tool introducer distal end for angular positioning said interchangeable tool in said body cavity after said tool holder emerges from said channel; and
 - an external guiding device configured to guide a tool manipulator to engage said interchangeable tool in said body cavity, said guiding device comprising a center guide comprising a first lumen adapted to accommodate said channel and an adjustable peripheral guide having a proximal end connected to said center guide and a distal end incorporating a second lumen;
- wherein said tool introducer is distally connected to said interchangeable tool and readily deployable in said body cavity through said channel accommodated in said first lumen of said center guide, and wherein said adjustable peripheral guide is adjusted to guide said tool manipulator through said second lumen to engage said interchangeable tool.

9. The system according to claim 8, wherein said external guiding device is further adapted to guide a distal portion of said tool manipulator in a defined orientation and/or depth in said body cavity.

10. The system according to claim 9, wherein said external guiding device is adapted to selectively lock said distal portion of said tool manipulator in said orientation and/or depth.

11. The system according to claim 9, wherein said distal portion of said tool manipulator is concentric to an inner passage of said interchangeable tool.

12. The system according to claim 8, wherein said second lumen includes a longitudinal axis that is angled towards said center guide in at least one dimension.

13. The system according to claim 8, wherein said adjustable peripheral guide is adjustable by at least one of: lengthening, bending, tilting, rotating, deforming and/or any combination thereof.

14. A method for engaging an interchangeable tool, said interchangeable tool having an inner passage, with a distal portion of a tool manipulator in a body cavity, said method comprising the steps of:

- inserting a tool introducer into a channel, said channel comprising a lumen providing direct communication into said body cavity and wherein a proximal end of said interchangeable tool is reversibly connected to a distal end of said tool introducer;
 - orienting said distal portion of said tool manipulator in said body cavity;
 - emerging said interchangeable tool from said channel into said body cavity; and positioning said interchangeable tool eccentrically to said lumen of said channel
- wherein said inner passage of the interchangeable tool is angled towards said distal portion of said tool manipulator.

15. The method according to claim 14, wherein said positioning is automatically executed once said interchangeable tool entirely emerges from said channel.

16. The method according to claim 14, wherein said positioning is selectively executed by an operator.

5

17. The method according to claim 14, and further comprising predetermining an angle of said positioning of said interchangeable tool.

18. The method according to claim 14, comprising using a constant angle for said positioning of said interchangeable tool.

10

19. The method according to claim 14, and further comprising selectively choosing an angle of said positioning of said interchangeable tool after emerging said interchangeable tool.

15

* * * * *

专利名称(译)	快速腹腔镜检查交换系统及其使用方法		
公开(公告)号	US9549719	公开(公告)日	2017-01-24
申请号	US14/274281	申请日	2014-05-09
[标]申请(专利权)人(译)	意昂外科有限公司		
申请(专利权)人(译)	EON手术LTD.		
当前申请(专利权)人(译)	EON手术LTD.		
[标]发明人	SHOHAT SHAUL FARIN DANNY BACHAR YEHODA WINSHTEIN RONNY		
发明人	SHOHAT, SHAUL FARIN, DANNY BACHAR, YEHODA WINSHTEIN, RONNY		
IPC分类号	A61B1/32 A61B17/02 A61B17/34 A61B1/00 A61B17/00 A61B17/29		
CPC分类号	A61B17/0218 A61B1/00154 A61B17/3403 A61B2017/00362 A61B2017/2931 A61B2017/3407 A61B2017/3466 A61B1/3132 A61B1/00066 A61B1/00087 A61B1/00098 A61B1/053 A61B17/2909 A61B17/3201 A61B34/35		
优先权	61/296485 2010-01-20 US		
其他公开文献	US20140343360A1		
外部链接	Espacenet USPTO		

摘要(译)

一种用于在体腔中定位可互换工具的系统包括：通道，其具有与体腔直接连通的内腔；工具导引器，其具有纵向轴线和远端；以及工具保持器，其覆盖可互换工具的至少一部分，其枢转地连接到所述工具导入器，从而在所述工具保持器从所述通道进入所述体腔之后允许所述可互换工具的角度定位。一种用于使可互换工具与在体腔中的工具操纵器的远端部分接合的方法包括将工具导引器插入通道中，将所述工具操纵器的远端部分定向在体腔中，使可互换工具从通道出来进入体腔，并且将所述可互换工具偏心地定位到所述通道的内腔。

