



US008562623B2

(12) **United States Patent**  
**McDonald et al.**

(10) **Patent No.:** **US 8,562,623 B2**  
(45) **Date of Patent:** **Oct. 22, 2013**

(54) **VAGINAL OCCLUSION DEVICE**

(76) Inventors: **Ross Alan McDonald**, Mesa, AZ (US);  
**Laura McDonald**, Mesa, AZ (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 227 days.

(21) Appl. No.: **13/024,106**

(22) Filed: **Feb. 9, 2011**

(65) **Prior Publication Data**

US 2012/0203244 A1 Aug. 9, 2012

(51) **Int. Cl.**  
**A61B 17/42** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **606/119**

(58) **Field of Classification Search**  
USPC ..... 600/38; 604/279; 606/119, 191, 193,  
606/197  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,996,930 A \* 12/1976 Sekulich ..... 601/137  
4,509,504 A 4/1985 Brundin  
4,994,069 A 2/1991 Ritchart  
5,540,658 A 7/1996 Evans  
5,643,311 A \* 7/1997 Smith et al. .... 606/193

5,674,239 A \* 10/1997 Zadini et al. .... 606/193  
5,840,077 A 11/1998 Rowden  
5,853,362 A \* 12/1998 Jacobs ..... 600/38  
6,174,317 B1 1/2001 Engman  
6,602,251 B2 8/2003 Burbank  
6,958,069 B2 10/2005 Shipp  
7,052,454 B2 5/2006 Taylor  
7,220,259 B2 5/2007 Harrington  
7,223,279 B2 5/2007 Burbank  
7,398,780 B2 7/2008 Callister  
7,404,821 B2 7/2008 Burbank  
7,572,274 B2 8/2009 Yassinzadeh  
2004/0230093 A1 \* 11/2004 Marshall ..... 600/38  
2005/0107818 A1 5/2005 Valtchev  
2007/0244538 A1 10/2007 Eder  
2008/0009775 A1 \* 1/2008 Murison ..... 601/46  
2010/0180422 A1 \* 7/2010 Valtchev ..... 29/428  
2010/0312199 A1 \* 12/2010 Lu ..... 604/279  
2011/0021870 A1 \* 1/2011 Lee ..... 600/38  
2012/0065601 A1 \* 3/2012 Gubachy et al. .... 604/294

\* cited by examiner

*Primary Examiner* — Ryan Severson


*Assistant Examiner* — Ashley Fishback



(74) *Attorney, Agent, or Firm* — Thomas W. Galvani, P.C.;  
Thomas W. Galvani




(57) **ABSTRACT**

A vaginal occlusion device that prevents the leak of gas out of the vaginal cavity during a laparoscopic surgery. The vaginal occlusion device includes a shaft with a handle attached to one end and a round or oval shaped head attached to the other end. The head is adapted to be inserted into a vagina.

**18 Claims, 2 Drawing Sheets**







## VAGINAL OCCLUSION DEVICE

## BACKGROUND OF THE INVENTION

The present invention generally relates to a minimally invasive surgical device. More particularly, the present invention relates to a vaginal occlusion device. In recent years, laparoscopic surgery has become a very popular surgical procedure. Laparoscopic surgery may be less invasive than the previous abdominal surgical procedures. Laparoscopic procedures require the abdominal cavity to be filled with gas, forming pneumoperitoneum to allow the surgeon to see and move instruments. Unfortunately, using the vagina as a route for natural orifice extraction following colpotomy, the gas tends to escape through the vaginal opening, making it difficult to maintain surgical exposure during the laparoscopic surgical procedure. In addition, the size of women's vaginal areas varies considerably, necessitating the use of various sized surgical devices.

As can be seen, there is a need for a vaginal device that has universal use and at the same time prevents the leak of gas during laparoscopic surgery.

## SUMMARY OF THE INVENTION

In one aspect of the present invention, a vaginal occlusion device having a shaft, including a handle attached to one end, a head attached to the other end, the head has an oval or round shape, and wherein the head is adapted to be inserted into a vagina.

In another aspect of the present invention, a vaginal occlusion device having a one-piece body, including a shaft with a handle attached to one end, a head attached to the other end, the head has an oval or round shape, and the head is adapted to be inserted into a vagina.

These and other features, aspects and advantages of the present invention will become better understood with reference to the following drawings, description and claims.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a side view of the vaginal occlusion device according to an exemplary embodiment of the present invention;

FIG. 2 illustrates a cross-sectional view of a female pelvis showing the vaginal occlusion device of FIG. 1 inserted into the vagina;

FIG. 3 illustrates a side view of the vaginal occlusion device according to a second exemplary embodiment of the present invention;

FIG. 4 illustrates a side view of the vaginal occlusion device according to a third exemplary embodiment of the present invention; and

FIG. 5 illustrates a side view of the vaginal occlusion device according to a fourth exemplary embodiment of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

The following detailed description is of the best currently contemplated modes of carrying out exemplary embodiments of the invention. The description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating the general principles of the invention, since the scope of the invention is best defined by the appended claims.

Various inventive features are described below that can each be used independently of one another or in combination with other features.

Broadly, embodiments of the present invention generally provide a vaginal occlusion device used to maintain pneumoperitoneum following a minimally invasive surgery using the vagina for specimen extraction.

FIG. 1 illustrates the vaginal occlusion device **10a** according to an exemplary embodiment of the present invention. In this embodiment, the vaginal occlusion device **10a** may include a shaft **14** having a head **12** at one of its ends and a handle **16** on the other end. The vaginal occlusion device **10** may be manufactured under current biomedical standards.

The shaft **14** may have a length that allows the surgeon to properly place the head **12** inside the vagina **18**. In one embodiment, the shaft **14** together with the head **12** may have a length A of approximately 160 mm. The shaft **14** may have a geometrical shape. In one embodiment, the shape of the shaft **14** may be cylindrical, rectangular, or triangular. In one embodiment, the shape of the shaft **14** may be cylindrical with a diameter C of approximately 16 mm. The shaft **14** may be made of a rigid material. In one embodiment, the shaft **14** may be made of a non latex-based material or plastic. The shaft **14** and the handle **16** may be made as a one-piece device.

The handle **16** may allow the surgeon to grip the vaginal occlusion device **10a** when being inserted in the vagina **18** that is heavily contaminated with body fluids. The handle **16** may be ergonomically designed to facilitate maintaining the grip of the vaginal occlusion device **10a**. The handle **16** may include an anti-slip surface **16a** to facilitate the grip of the handle **16**.

The handle **16** may have a length B that allows the surgeon to properly control the insertion of the vaginal occlusion device **10a** in the vagina **18**. In one embodiment, the length B of the handle **16** may be from approximately 120 mm to approximately 140 mm. The handle **16** may have a width C that allows the surgeon to properly control the insertion of the vaginal occlusion device **10a** in the vagina **18**. In one embodiment, the width C of the handle **16** may be 20 mm. In one embodiment, the handle **14** and the shaft **16** may have the same cross areas. In one embodiment, the handle **14** and the shaft **16** may have different cross areas.

The handle **16** may be configured at any angle with respect to the shaft **14** from 0 degrees to 180 degrees. FIG. 4 illustrates a third alternate embodiment of the present invention on which the vaginal occlusion device **10c** may include a handle **16b** that may be configured at a 45 degree angle with respect to the shaft **14**. In addition, FIG. 4 illustrates that the vaginal occlusion device **10c** may include a handle **16c** that may be configured on the same plane with respect to the shaft **14**.

The head **12** may be used to obstruct the vagina **18**, preventing the gas from leaking from the abdomen cavity during the laparoscopic procedure. The head **12** may be attached to or form an integral part of the shaft **14** and may not be removable from the shaft **14**. The head **12** may be made of a medical-grade rigid material. In one embodiment, the head **12** may be made of medical-grade plastic, non-latex rubber, or silicon. The material of the head **12** may be strong enough to prevent the head **12** from being punctured by a needle **22** on the thread **24** when suturing the vaginal cuff **20** at the end of the vaginal laparoscopic surgery.

The shape of the head **12** may be round or oval to allow the surgeon to block the passage of gas through the vaginal cavity. The round or oval shape of the head **12** may be configured to anatomically match the vaginal cuff area, providing a seal that may prevent the passage of gas from the peritoneal cavity through the vaginal defect. The head **12** may include a smooth

3

surface to protect the interior of the vagina **18**. The size of the cross-sectional area D of the head **12** may depend on the female anatomical variances. In one embodiment, the head **12** may have a diameter from 35 mm to 45 mm. In one embodiment, the head **12** may have a diameter of 40 mm. The head **12** may have any color. In one embodiment, the size of the head **12** may be color coded.

FIG. **2** illustrates the vaginal occlusion device **10a** that may be inserted into the vagina **18** by the surgeon using the handle **16** to grip and control the angle of insertion. The surgeon may slide the vaginal occlusion device **10a** into the vaginal opening **19** of the vagina **18** until the vaginal occlusion device **10a** reaches the vaginal cuff **20**, blocking the passage of gas from the peritoneal cavity through the vaginal defect.

FIG. **3** shows a second alternate embodiment of the present invention on which a vaginal surgical device **10b** may include a handle **17** having fingered grips **17a**. In addition, the FIG. **3** illustrates that the head **12** may be round. The size of the head **12** may vary from a small size rounded shaped head **12b** to a large size round shaped head **12a**.

FIG. **5** illustrates a fourth embodiment of the present invention showing a vaginal occlusion device **10d** showing a head **26** having an oval shape. The size of the head **26** may vary from a small size oval shaped head **26b** to a large size oval-shaped head **26a**. The oval-shaped head **26a** may allow for use in other laparoscopic surgical applications.

The vaginal occlusion device **10a-d** may be sterile, radio-opaque, and disposable.

The vaginal occlusion device **10a-d** may prevent the retention of foreign bodies caught by sutures, such as glove materials or surgical sponges in the vagina **18**.

It should be understood, of course, that the foregoing relates to exemplary embodiments of the invention and that modifications may be made without departing from the spirit and scope of the invention as set forth in the following claims.

What is claimed is:

1. A plurality of vaginal occlusion devices, each device for maintaining pneumoperitoneum of a peritoneal cavity in laparoscopic surgery, each device comprising:

a shaft having a first end and a second end;  
a handle attached to the first end of the shaft;  
a head attached to the second end of the shaft, wherein the head has an oval or round shape;  
the head is adapted to be inserted into a vagina in an inserted condition of the device;  
the head of each device has a respective size different from the sizes of the heads of the other devices;  
the head of each device carries a respective color different from the colors of the heads of the other devices;  
the color of the head of each device corresponds to the respective size of the head; and  
in the inserted condition of one of the devices, the head of the device occludes a vaginal cuff to block passage of gas from the peritoneal cavity through a vaginal cavity so as to maintain pneumoperitoneum.

2. The vaginal occlusion device according to claim 1, wherein the head is made of a rigid material.

3. The vaginal occlusion device according to claim 1, wherein the handle and shaft are made of a non latex-based material.

4

4. The vaginal occlusion device according to claim 1, wherein the handle includes at least one of a non-slip surface and finger grips.

5. The vaginal occlusion device according to claim 1, wherein the handle is placed at a 0 to 180 degree angle with the shaft.

6. The vaginal occlusion device according to claim 1, wherein the head has a smooth surface.

7. The vaginal occlusion device according to claim 1, wherein the shaft, handle, and head comprise a one-piece body.

8. The vaginal occlusion device according to claim 7, wherein the one-piece body is rigid.

9. The vaginal occlusion device according to claim 1, wherein the device is constructed of a radio-opaque material.

10. The vaginal occlusion device according to claim 1, wherein the head of the device is constructed of a puncture-resistant material.

11. The vaginal occlusion device according to claim 1, wherein the head of the device is constructed of a needle-impermeable material providing a hard surface adapted to prevent the head of the device from being sutured.

12. The vaginal occlusion device according to claim 1, wherein in the inserted condition of the device, the head of the device is stationary with respect to the vaginal cuff.

13. The vaginal occlusion device according to claim 1, wherein:

the shaft has a width; and

the head has a width about twice as great as the width of the shaft.

14. A plurality of vaginal occlusion devices, each device for maintaining pneumoperitoneum in laparoscopic surgery of a peritoneal cavity, each device comprising:

a rigid shaft including an enlarged head and an opposed handle;

each head having a size different from the sizes of the heads of the other devices;

the head of each device carries a respective color different from the colors of the heads of the other devices;

the color of the head of each device corresponds to the respective size of the head; and

an inserted condition of the shaft of one of the devices in a vagina;

wherein in the inserted condition of the shaft, the shaft is inserted into the vagina against a vaginal cuff of the vagina, providing a seal against the vaginal cuff preventing passage of gas from the peritoneal cavity through the vagina.

15. The vaginal occlusion device according to claim 14, wherein the device is constructed of a radio-opaque material.

16. The vaginal occlusion device according to claim 14, wherein the head of the device is constructed of a needle-impermeable material providing a hard surface adapted to prevent the head of the from being sutured.

17. The vaginal occlusion device according to claim 14, wherein in the inserted condition of the device, the head of the device is stationary with respect to the vaginal cuff.

18. The vaginal occlusion device of claim 14, wherein:

the shaft has a width; and

the head has a width about twice as great as the width of the shaft.

\* \* \* \* \*

|                |                                                 |         |            |
|----------------|-------------------------------------------------|---------|------------|
| 专利名称(译)        | 阴道闭塞装置                                          |         |            |
| 公开(公告)号        | <a href="#">US8562623</a>                       | 公开(公告)日 | 2013-10-22 |
| 申请号            | US13/024106                                     | 申请日     | 2011-02-09 |
| [标]申请(专利权)人(译) | MCDONALD ALAN ROSS<br>MCDONALD LAURA            |         |            |
| 申请(专利权)人(译)    | MCDONALD ALAN ROSS<br>MCDONALD LAURA            |         |            |
| 当前申请(专利权)人(译)  | MCDONALD , ALAN ROSS                            |         |            |
| [标]发明人         | MCDONALD ROSS ALAN<br>MCDONALD LAURA            |         |            |
| 发明人            | MCDONALD, ROSS ALAN<br>MCDONALD, LAURA          |         |            |
| IPC分类号         | A61B17/42                                       |         |            |
| CPC分类号         | A61B17/12099 A61B17/42                          |         |            |
| 其他公开文献         | US20120203244A1                                 |         |            |
| 外部链接           | <a href="#">Espacenet</a> <a href="#">USPTO</a> |         |            |

#### 摘要(译)

一种阴道闭塞装置，用于在腹腔镜手术期间防止气体泄漏出阴道腔。阴道闭塞装置包括轴，该轴具有连接到一端的手柄和连接到另一端的圆形或椭圆形头部。头部适于插入阴道。

