



US009974567B2

(12) **United States Patent**
Singh et al.

(10) **Patent No.:** **US 9,974,567 B2**
(45) **Date of Patent:** ***May 22, 2018**

(54) **GENERAL UTERINE MANIPULATOR AND SYSTEM**

(71) Applicants: **Jiwan Steven Singh**, Woodvale (AU);
Jai Singh, Woodvale (AU)

(72) Inventors: **Jiwan Steven Singh**, Woodvale (AU);
Jai Singh, Woodvale (AU)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 11 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/246,140**

(22) Filed: **Aug. 24, 2016**

(65) **Prior Publication Data**
US 2017/0135727 A1 May 18, 2017

Related U.S. Application Data
(63) Continuation of application No. 14/007,820, filed as application No. PCT/AU2012/000332 on Mar. 30, 2012, now Pat. No. 9,451,985.
(Continued)

(51) **Int. Cl.**
A61B 17/42 (2006.01)
A61B 17/00 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 17/4241** (2013.01); **A61B 17/00234** (2013.01); **A61B 2017/4216** (2013.01)

(58) **Field of Classification Search**
CPC A61B 17/4241; A61B 17/42; A61B 2017/4216; A61B 2017/4225; A61B 10/0291

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,191,721 A 2/1940 Milarch
2,201,372 A 5/1940 Miller
(Continued)

FOREIGN PATENT DOCUMENTS

AU 773391 5/2004
AU 2011101651 A4 2/2012
(Continued)

OTHER PUBLICATIONS

SecuFix Uterus Manipulator, 4 pages, www.richard-wolf.com. The "publication date" of this reference is not readily available. Applicant requests that the Examiner review the reference as prior art. Applicant reserves the right to disqualify the reference as prior art if needed.


(Continued)

Primary Examiner — Jonathan Miles
(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

A general uterine manipulator 10 incorporates an elongated hollow tube 12 defining an internal passage 14. Tube 12 has opposite first and second ends 16 and 18, formed with internal threads T1 and T2; and a smooth continuous outer surface 20 of constant outer diameter. A first fitting comprising a tail screw 22 is screwed into thread T1 and a second fitting cervical screw 24 is screwed in thread T2. An inner manipulator rod 26 extends through the first fitting 22, tube 12, and second fitting 24. A range of alternate first and second fitting is provided. A forceps holder 70 is attachable to the tube 12 between ends 16 and 18. The manipulator 10 may also support a cervical funnel 90 and a plug 92.

20 Claims, 11 Drawing Sheets



Related U.S. Application Data						
(60)	Provisional application No. 61/472,705, filed on Apr. 7, 2011.					
(56)	References Cited					
	U.S. PATENT DOCUMENTS					
	2,400,251 A	5/1946	Nagel	8,567,754 B1	10/2013	Gilstad et al.
	2,470,308 A	5/1949	Haddican	8,568,423 B2	10/2013	Boebel et al.
	2,636,598 A	4/1953	Hopgood	8,574,221 B2	11/2013	Deeds
	2,707,471 A	5/1955	Koff	8,603,105 B2	12/2013	Sauer
	3,465,529 A	9/1969	Helle	8,623,070 B2	1/2014	Bales et al.
	3,926,192 A	12/1975	Van Maren	8,647,325 B2	2/2014	Charlez
	4,045,027 A	8/1977	Manska	8,647,326 B2	2/2014	Solomon et al.
	4,117,847 A	10/1978	Clayton	8,647,349 B2	2/2014	Gruber et al.
	4,207,872 A	6/1980	Meiri et al.	8,663,239 B2	3/2014	Hess
	4,382,445 A	5/1983	Sommers	8,709,362 B2	4/2014	Leventhal et al.
	4,430,076 A	2/1984	Harris	8,740,916 B2	6/2014	Blair et al.
	4,573,452 A	3/1986	Greenberg	8,770,200 B2	7/2014	Ahluwalia
	4,840,613 A	6/1989	Balbierz	8,876,800 B2	11/2014	Kaufmann et al.
	4,859,067 A	8/1989	Hoppe et al.	8,876,886 B2	11/2014	Kaufmann et al.
	4,863,133 A	9/1989	Bonnell	9,101,390 B2	8/2015	Singh et al.
	4,863,174 A	9/1989	Cummings	9,451,985 B2	9/2016	Singh et al.
	4,998,924 A	3/1991	Ranford	9,532,837 B2	1/2017	Singh et al.
	5,003,146 A	3/1991	Alexander	2002/0095160 A1	7/2002	Bonutti
	5,052,998 A	10/1991	Zimmon	2002/0120252 A1	8/2002	Brock et al.
	5,112,346 A	5/1992	Hiltebrandt et al.	2004/0097961 A1	5/2004	Burbank et al.
	5,138,228 A	8/1992	Thomas et al.	2004/0204720 A1	10/2004	Harrington et al.
	5,156,599 A	10/1992	Ranford et al.	2004/0236285 A1	11/2004	Fisher et al.
	5,167,614 A	12/1992	Tessmann et al.	2005/0085827 A1	4/2005	G. et al.
	5,191,888 A	3/1993	Palmer et al.	2005/0277948 A1	12/2005	Cedars et al.
	5,205,831 A	4/1993	Ryan et al.	2007/0135819 A1	6/2007	Spiritos et al.
	5,320,613 A	6/1994	Houge et al.	2008/0039865 A1	2/2008	Shaher et al.
	5,338,313 A	8/1994	Mollenaer et al.	2009/0048609 A1	2/2009	Atiomo et al.
	5,395,331 A	3/1995	O'Neill et al.	2009/0062839 A1	3/2009	Kurrus
	5,425,739 A	6/1995	Jessen	2010/0160928 A1	6/2010	Navas
	5,472,419 A	12/1995	Bacich	2010/0274260 A1	10/2010	D'Arpiany et al.
	5,487,377 A	1/1996	Smith et al.	2011/0282368 A1	11/2011	Swayze et al.
	5,542,321 A	8/1996	Fuca	2011/0306829 A1	12/2011	Sharp et al.
	5,643,285 A	7/1997	Rowden et al.	2012/0109124 A1	5/2012	Morozov
	5,741,333 A	4/1998	Frid	2012/0143209 A1	6/2012	Brecheen et al.
	RE35,849 E	7/1998	Soehendra	2012/0143210 A1	6/2012	Brecheen et al.
	5,792,165 A	8/1998	Klieman	2013/0066328 A1	3/2013	Singh et al.
	5,800,514 A	9/1998	Nunez et al.	2013/0197536 A1	8/2013	Singh et al.
	5,840,077 A	12/1998	Rowden	2014/0100595 A1	4/2014	Morgenstern Lopez et al.
	5,876,383 A	3/1999	Grooters et al.	2014/0135587 A1	5/2014	Hess
	5,931,820 A	8/1999	Morse	2014/0276916 A1	9/2014	Ahluwalia et al.
	5,947,954 A	9/1999	Bonaldo	2014/0303641 A1	10/2014	Boebel et al.
	5,957,423 A	9/1999	Kronner	2016/0081717 A1	3/2016	Singh et al.
	6,004,302 A	12/1999	Brierley			
	6,010,520 A	1/2000	Pattison	FOREIGN PATENT DOCUMENTS		
	6,096,022 A	8/2000	Laymon et al.	AU	2007335226	9/2012
	6,124,523 A	9/2000	Banas et al.	CA	2778976	8/2012
	6,203,532 B1	3/2001	Wright	CN	201005764	1/2008
	6,254,578 B1	7/2001	Grooters et al.	DE	10208508	1/2003
	6,371,981 B1	4/2002	Yang et al.	EP	0400458	12/1990
	6,423,075 B1	7/2002	Singh et al.	JP	2006-122674	10/2005
	6,516,216 B1	2/2003	Fontenot et al.	JP	2009-273891	11/2009
	6,517,570 B1	2/2003	Lau et al.	JP	2011-104399	6/2011
	6,572,593 B1	6/2003	Daum	KR	10-2001-0052102 A	6/2001
	6,589,213 B2	7/2003	Reydel	WO	WO 2008/074054	6/2008
	6,692,504 B2	2/2004	Kurz et al.	WO	WO 2008/136024	9/2008
	6,758,834 B2	7/2004	Grooters	WO	WO 2010/151429	12/2010
	6,767,339 B2	7/2004	Reydel	WO	WO 2011/140604	9/2011
	6,811,547 B2	11/2004	Wilkinson	WO	WO 2012/135893	10/2012
	6,893,428 B2	5/2005	Willemstyn	WO	WO 2013/102235	7/2013
	7,044,962 B2	5/2006	Elliot	WO	WO 2013/159019	10/2013
	7,195,641 B2	3/2007	Palmaz et al.	WO	WO 2014/047554	3/2014
	7,338,530 B2	3/2008	Carter et al.			
	7,811,148 B2	10/2010	Fridrich	OTHER PUBLICATIONS		
	7,811,278 B2	10/2010	Knipple, Jr. et al.	Cooper Surgical, "Uterine Positioning System™ Facilitates accurate and secure uterine placement," Brochure, revision Dec. 2008, in 5 pages, Trumbull, CT.		
	7,993,328 B2	8/2011	Whitley	Surgitools, Instructions for Use: Singh MultiGuide ARC, Apr. 30, 2013.		
	8,042,775 B1	10/2011	Gallegos	International Preliminary Report on Patentability for PCT Application No. PCT/AU2012/000332, dated Feb. 27, 2013.		
	8,052,650 B2	11/2011	Young et al.	International Search Report and Written Opinion, International Application No. PCT/AU2012/000332, International Filing Date, Mar. 30, 2012, dated May 17, 2012.		
	8,287,517 B2	10/2012	Hanlon et al.	International Search Report and Written Opinion for PCT Application No. PCT/US2013/061180, dated Dec. 17, 2013.		
	8,298,213 B2	10/2012	Singh			
	8,495,809 B2	7/2013	Valtchev			

(56)

References Cited



OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US2013/037417, dated Jul. 29, 2013.

Ob.Gyn.News, "Kronner non-Pneumatic Scope/Instrument Holder for laparoscopic and other endoscopic surgery," updated Mar. 16, 2013, in 2 pages, product.zone.obgynnews.com.

R. Kronner, MD FACS, "The Kronner Side-Kick: A Perineal Instrument Holder," manual in 13 pages, Kronner Medical, Roseburg, Oregon.

Stryker, "Give Yourself a Hand," Stryker Endoscopy Brochure, in 2 pages, 2006, Stryker, San Jose, CA.






Fig. 2




Fig. 5




Fig. 3




Fig. 8

Fig. 7




Fig. 6




Fig. 9a




Fig. 9b







Fig. 9c






Fig. 11




Fig. 12




Fig. 13b




Fig. 13a




Fig. 13c




Fig. 14b




Fig. 14a




Fig. 15

GENERAL UTERINE MANIPULATOR AND SYSTEM

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

This application is a Continuation of U.S. Patent Application Ser. No. 14/007,820, titled GENERAL UTERINE MANIPULATOR AND SYSTEM, filed Oct. 31, 2013, which is a National Stage of PCT Application No. PCT/AU2012/000332, titled GENERAL UTERINE MANIPULATOR AND SYSTEM, filed Mar. 30, 2012, which claims the benefit of U.S. Provisional Patent Application Ser. No. 61/472,705, titled GENERAL UTERINE MANIPULATOR AND SYSTEM, filed Apr. 7, 2011. Each of the foregoing applications is hereby incorporated by reference herein in its entirety.

FIELD OF THE INVENTION

The present invention relates to a general uterine manipulator and system which may be used in general surgery, gynaecological or non-surgical procedures.

BACKGROUND OF THE INVENTION

The present inventor has invented numerous medical instruments which are currently in use in surgical and non-surgical procedures. One such instrument is described in International publication no. WO 2008/074054 which is used in various procedures including total laparoscopic hysterectomy. The instrument described in this publication comprises a tube provided with an integral funnel at one end and through which a uterine cannula can be inserted. Both the tube and the cannula are provided with longitudinal slots or cut outs that aid in visualising the rotational position of a distal end of the instrument when inserted into the vagina and also aid in gripping of the instrument.

The success and efficacy of the above described and other instruments developed by the present inventor together with the need for improved and more versatile instruments have lead to the present invention.

SUMMARY OF THE INVENTION

According to one aspect of the present invention there is provided a general uterine manipulator comprising:

an elongated hollow tube defining an internal passage and having opposite first and second ends;

a smooth continuous outer surface of constant outer diameter extending between the first and second ends; and,

internal first and second screw threads formed in the elongated hollow tube, the first screw thread being formed at the first end and the second screw thread being formed at the second end.

The general uterine manipulator may comprise a first fitting having a screw thread arranged to engage the first screw thread, the first fitting also having an axial through hole and configured to receive an inner manipulator shaft.

In some embodiments the first fitting is configured to apply increasing clamping force on a received inner manipulator when the first fitting a screw further into the first end.

The general uterine manipulator may comprise a hydrotubation port in fluid communication with the internal passage wherein a fluid injected into or through the hydrotubation port is able to flow into the internal passage.

In some embodiments the hydrotubation port is formed in the elongated hollow tube at a location near the first end and beyond the first screw thread.

In some embodiments the hydrotubation port is formed in the first fitting and is in fluid communication with the axial through hole.

The axial through hole may comprise a first length which opens onto an end of the first fitting distant the screw thread of the first fitting, and a second contiguous length wherein the first length has a first internal diameter and the second length has a second internal diameter which is greater than the first internal diameter; and wherein the hydrotubation port opens onto the second length of the axial through hole.

The general uterine manipulator may comprise a second fitting having a threaded portion provided with a screw thread configured to engage the second internal thread on the elongated hollow tube and a body portion extending co-linearly from the threaded portion.

In some embodiments the body portion comprises a tubular member which is open at one end distal the threaded portion and is closed at an end near to the threaded portion to form a cavity.

In some embodiments the tubular member comprises a circumferential wall and at least one internal passage formed in the circumferential wall, the or each internal passage opening onto axially opposite ends of the circumferential wall.

In some embodiments the body portion comprises a conically shaped portion with decreasing outer diameter in a taper direction being away from the threaded portion and wherein the conically shaped portion is provided with an external coarse screw thread.

In some embodiments the second fitting is provided with an axial through hole.

The general uterine manipulator may comprise an inner manipulator shaft, the shaft capable of being received in the axial through hole of the first fitting and the axial through hole of the second fitting and extending through the internal passage.

In some embodiments a crest of the coarse screw thread is provided with a flattened surface wherein a line on the flattened surface is inclined relative to a central axis of the coarse screw thread in the taper direction.

In some embodiments the coarse screw thread is a ball screw thread.

In some embodiments the general uterine manipulator comprising a forceps holder supported on the elongated hollow tube and configured to be releasably lockable in a plurality of positions along the elongated hollow tube.

In some embodiments the forceps holder comprises a first component seated on the elongated hollow tube and provided with a detent for gripping a finger hole of the forceps.

In some embodiments the forceps holder comprises a locking nut engagable with the first component and arranged to releasably lock the first component in a fixed position along the elongated hollow tube when rotated in a first direction, and to release the second component to allow sliding motion along the elongated hollow tube when rotated in an opposite direction.

In a second aspect there is provided general uterine manipulator comprising:

an elongated hollow tube defining an internal passage and having opposite first and second ends;

a smooth continuous outer surface of constant outer diameter extending between the first and second ends;

internal first and second screw threads formed in the elongated hollow tube, the first screw thread being formed at the first end and the second screw thread being formed at the second end

a first fitting having a screw thread arranged to engage the first screw thread, the first fitting also having an axial through hole;

a second fitting having a threaded portion provided with a screw thread configured to engage the second internal thread on the elongated hollow tube and a body portion extending co-linearly from the threaded portion; and,

an inner manipulator shaft arranged to extend through the axial through hole, the internal passage and the second fitting, the inner manipulator shaft having one end which is bent and protrudes from the second fitting.

In one embodiment the general uterine manipulator comprises a resistance mechanism enabling the axial and rotational position of the inner manipulator shaft to substantially held in the absence of adjustment by a user of the manipulator.

In one embodiment the resistance mechanism comprises clamp shells incorporated in the first fitting.

In one embodiment the resistance mechanism comprises a bend in a portion of the inner manipulator shaft within the internal passage the bend being to an extent that the inner manipulator shaft bears against an inside surface of the tube.

In one embodiment the general uterine manipulator comprises a hydrotubation port formed in the first fitting and in fluid communication with the axial through hole wherein a fluid injected into or through the hydrotubation port is able to flow into the internal passage. In this embodiment the axial through hole comprises a first length which opens onto an end of the first fitting distant the screw thread of the first fitting, and a second contiguous length wherein the first length has a first internal diameter and the second length has a second internal diameter which is greater than the first internal diameter; and the hydrotubation port opens onto the second length of the axial through hole.

In one embodiment the second fitting comprises a threaded portion provided with a screw thread configured to engage the second internal thread on the elongated hollow tube and a body portion extending co-linearly from the threaded portion, the body portion having a frusto-conical shape with decreasing outer diameter in a direction away from the threaded portion and on which is provided an external coarse screw thread.

In one embodiment the general uterine manipulator comprises a forceps holder supported on the elongated hollow tube and configured to be releasably lockable in a plurality of positions along the elongated hollow tube.

In one embodiment the forceps holder comprises a first component seated on the elongated hollow tube and provided with a detent for gripping a handle of the forceps.

In one embodiment the forceps holder comprises a locking nut engagable with the first component and arranged to releasably lock the first component in a fixed position along the elongated hollow tube when rotated in a first direction, and to release the second component to allow sliding motion along the elongated hollow tube when rotated in an opposite direction.

In one embodiment the general uterine manipulator comprises a cervical funnel mounted on the tube.

In a third aspect there is provided a general uterine manipulator system comprising:

an elongated hollow tube defining an internal passage and having opposite first and second ends;

a smooth continuous outer surface of constant outer diameter extending between the first and second ends;

internal first and second screw threads formed in the elongated hollow tube, the first screw thread being formed at the first end and the second screw thread being formed at the second end

at least one first fitting the or each first fitting having a screw thread arranged to engage the first screw thread, the first fitting also having an axial through hole;

at least one second fitting the or each second fitting having a threaded portion provided with a screw thread configured to engage the second internal thread on the elongated hollow tube and a body portion extending co-linearly from the threaded portion;

wherein the at least one first fitting comprises one or both of: (a) a clamping first fitting configured to apply increasing clamping force on a received inner manipulator when the first fitting a screw further into the first end; and (b) a hydrotubation first fitting which has a hydrotubation port in fluid communication with the internal passage wherein a fluid injected into or through the hydrotubation port is able to flow into the internal passage; and wherein

the at least one second fitting comprises one or both of: (c) a cervical second fitting in which its body portion is of a frusto-conical shape with decreasing outer diameter in a direction away from the threaded portion and is provided with an external coarse screw thread; and (d) a tubular second fitting in which its body portion comprises a tubular member which is open at one end distal the threaded portion of the second fitting and is closed at an end near to the threaded portion of the second fitting to form a cavity.

In one embodiment the tubular member of the tubular second fitting comprises a circumferential wall and at least one internal passage formed in the circumferential wall, the or each internal passage opening onto axially opposite ends of the circumferential wall.

In one embodiment the general uterine manipulator system comprises an inner manipulator shaft arranged to extend through the axial through hole, the internal passage and the second fitting when the second fitting is the cervical second fitting, the inner manipulator shaft having one end which is bent and protrudes from the cervical.

In one embodiment the general uterine manipulator system a resistance mechanism enabling the axial and rotational position of the inner manipulator shaft to substantially held in the absence of adjustment by a user.

In one embodiment the general uterine manipulator system a forceps holder supported on the elongated hollow tube and configured to be releasably lockable in a plurality of positions along the elongated hollow tube.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1a is a representation of one embodiment of a general uterine manipulator in accordance with the present invention;

FIG. 1b is a disassembled view of the general uterine manipulator depicted in FIG. 1a;

FIG. 2 is a longitudinal section view of the tube incorporated in the general uterine manipulator shown in FIGS. 1a and 1b;

FIG. 3 is an isometric view of a tail screw incorporated in the general uterine manipulator shown in FIGS. 1a and 1b;

FIG. 4 is a side view of the tail screw shown in FIG. 3;

FIG. 5 is an end view of the tail screw shown in FIG. 3;

FIG. 6 is an isometric view of a second form of tail screw that may be incorporated in the general uterine manipulator shown in FIGS. 1a and 1b;

FIG. 7 is a side view of the tail screw shown in FIG. 6;

FIG. 8 is an end view of the tail screw shown in FIG. 6;

FIG. 9a is a side view of a second fitting incorporated in the general uterine manipulator shown in FIGS. 1a and 1b;

FIG. 9b is a longitudinal section view of the second fitting shown in FIG. 9a;

FIG. 9c is an isometric representation of the second fitting;

FIG. 10a is a side view of a second form of setting fitting that may be incorporated in the general uterine manipulator depicted in FIGS. 1a and 1b;

FIG. 10b is an end view of the second fitting shown in FIG. 9a;

FIG. 10c is an isometric view from one end of the second fitting;

FIG. 10d is a isometric view from an opposite angle of the second fitting;

FIG. 11 is an isometric view of a forceps holder incorporated in the uterine manipulator;

FIG. 12 is an isometric view of an embodiment of the general uterine manipulator and associated system with additional fittings to enable performance of a total laparoscopic hysterectomy; and,

FIG. 13a is a side view of a cervical funnel incorporated in an embodiment of the general uterine manipulator shown in FIGS. 1a and 1b;

FIG. 13b is a longitudinal section view of the cervical funnel;

FIG. 13c is an end view of the cervical funnel shown in FIGS. 13a and 13b;

FIG. 14a is an isometric representation of a vaginal plug incorporated in an embodiment of the general uterine manipulator shown in FIGS. 1a and 1b;

FIG. 14b is a section view of the vaginal plug shown in FIG. 14a; and,

FIG. 15 is a side view of a manipulator handle which may be incorporated in an embodiment of the general uterine manipulator.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Embodiments of the general uterine manipulator and associated system provide a multipurpose manipulator that may be used for a variety of procedures by interchanging particular fittings of the manipulator. With particular reference to FIGS. 1a to 2, each embodiment of the general uterine manipulator 10 (hereinafter referred to in general as "manipulator 10") is based on or incorporates an elongated hollow tube 12 defining an internal passage 14. Tube 12 has opposite first and second ends 16 and 18 and a smooth continuous outer surface 20 of constant outer diameter. A first internal screw thread T1 is formed at the first end 16 and a second internal screw thread T2 is formed at the second end 18.

The versatility of the manipulator 10 and associated system arises from the ability to connect with a number of different fittings depending on the specific application at hand. FIGS. 1a and 1b illustrate a first fitting in the form of tail screw 22 and a second fitting in the form of a cervical screw 24. An inner manipulator rod 26 is also illustrated in FIGS. 1a and 1b which extends through the first fitting 22, tube 12, and second fitting 24.

One form of the first fitting 22 is shown in greater detail in FIGS. 3 to 5. In this embodiment the first fitting 22 comprises a threaded portion 28; an integral body portion 30; and, an internal axial hole 32. Threaded portion 28 is configured to engage screw thread T1 and is provided with a transverse slot 34 terminating prior to the body portion 30. Slot 34 in effect divides the threaded portion 28 into opposed clamp shells 36a and 36b (hereinafter referred to in general as "clamp shells 36"). Body portion 30 is in the general form of a cylinder with two flats 38a and 38b on opposed sides that assist in gripping of the fitting 22. Axial hole 32 is of constant diameter for the length of the fitting 22 except for a counter sink 40 at a distal end of fitting 22.

Threaded portion 28 is slightly flared outwardly so as it is screwed into screw thread T1 at end 16, the clamp shells 36 move toward each other. When an inner manipulator rod 26 is used in the manipulator 10 this results in a clamping action on the rod providing resistance to movement of the rod 26 so as to hold it at a desired rotational and translational position. Unscrewing of the portion 28 releases or reduces this resistance to enable adjustment of the position and orientation of the rod 26. Thus the first fitting can be considered in this embodiment as incorporating or comprising a resistance mechanism which substantially maintains the position of the rod 26 until moved or adjusted by a surgeon or other user.

FIGS. 6 to 8 depict an alternate form of the first fitting denoted as 22'. Features of the fitting 22' which are of the same or similar configuration or function as those of fitting 22 are denoted with the same reference numbers but with the addition of the prime (') symbol. Fitting 22' comprises a threaded portion 28', body 30', an inner axial hole 32' with counter sink 40' at a distal end, and opposed flats 38'a and 38'b formed on body portion 30'. Fitting 22' differs from fitting 22 by the omission of slot 34, the inclusion of a hydrotubation port 42, and a re-configuring of the axial hole 32'. With particular reference to FIG. 7 it can be seen that the axial hole 32' has a first length 44 and a contiguous second length 46. The first length 44 extends from the threaded portion 28' for a majority of the axial length of fitting 22'. The second length 46 extends between and joins the counter sink 40' to the first length 44. The inner diameter of the first length 44 is greater than the inner diameter of second length 46'. Further, the inner diameter of second length 46 is dimensioned to be slightly greater than an outer diameter of the inner manipulator rod 26 forming a close fit but enabling the rod 26 to pass through the axial hole 32'.

Hydrotubation port 42 is formed in the body 30' at a location where it communicates with the first length 44. The thread on threaded portion 28' is arranged to engage with the thread T1 at end 16. In the event that for example the manipulator 10 is being used in a gynaecological application and it is desired to inject a liquid such as a dye to assist in the visualisation of tissue the dye may be injected through the hydrotubation port 42. The dye then flows through the internal passage 14 and from an opposite end of second fitting 24 attached to end 18. In this regard in the event that manipulator rod 26 is in use, a clearance exists between second fitting 24 and an outer surface of rod 26 to allow the flow of dye or other fluid. Further, the close fitting between the rod 26 and second length 46 of axial hole 32' substantially prevents any back leakage of the dye. Alternately and/or in addition if desired, a rubber grommet seal (not shown) may be provided in the second length 46 to further minimize back leakage of dye or other liquid injected through the hydrotubation port 42.

As the fitting 22' does not have the clamping shells 36 of fitting 22 it is unable to clamp inner manipulation rod 26. However in embodiments of the manipulator 10, the inner manipulator rod 26 can be bent to varying degrees intermediate of its length so that the rod 26 bears against an inside surface of tube 12 to provide resistance to both axial and rotational motion when fitting 22' is used. This still allows the rod 26 to substantially maintain its position until moved or adjusted manipulated by a surgeon or other user. Thus the intermediate bend in the rod 26 can be equated with or considered to be another or alternate form of resistance mechanism which substantially maintains the position of the rod 26 until moved or adjusted by a surgeon or other user.

The second fitting 24 of FIGS. 1a and 1b is shown in greater detail in FIGS. 9a, 9b and 9c. The fitting 24 comprises a threaded portion 48 configured to engage thread T2, and an integral body portion 50. Body portion 50 is of a frusto-conical shape with a decreasing outer diameter in a taper direction D being away from threaded portion 48. A coarse screw thread 52 is formed about the conically shaped body portion 50. The crest of thread 52 has a flattened surface orientated so that a line 53 on the surface of the crest is inclined parallel with a central axis 55 of second portion 24. An axial through hole 57 is also formed through second portion 24. This allows for the passage of the inner manipulator rod 26 and/or other instruments as well as fluids including saline, dye, and air. In this embodiment of the manipulator 10, second fitting 24 is a cervical screw which is configured to screw into the cervix forming an attachment point as well as a seal.

However, alternate forms of second fittings may be incorporated in the manipulator 10. FIGS. 10a-10d illustrate an alternate second fitting 24a. Fitting 24a is in the form of a hollow probe having a threaded portion 48a and a body portion 50a. Threaded portion 48a has a thread configured to engage with thread T2. Body portion 50a is in the form of a tubular member which is open at its distal end 56 and is closed at an end 58 near threaded portion 48a to define or otherwise form a cavity 60. Distal end 56 is formed with a chamfer or bevel 62 to assist in insertion of the fitting 24a into a body cavity such as a vagina or rectum. Fitting 24a may be used for example during a hysterectomy to maintain pneumoperitoneum after removal of the uterus. The cavity 60 also allows for collection of pelvic tissue and specimens from the abdominal and pelvic cavities. A lumen (i.e. through hole) 64 may be formed axially through a circumferential wall 66 of the body 50a. In one embodiment the lumen 64 may have an internal diameter of approximately 6 mm to enable the receipt of a 4 mm telescope to enable illumination and visualization of tissue in cavities. For example this may be used in pelvic floor operations where the vagina and rectum septum need to be dissected out. This reduces the possibility of a recto-vaginal fistula occurring.

It is envisaged that the fitting 24a may be made in a variety of different sizes and in particular different diameters. For example 40 mm outer diameter, 30 mm outer diameter, and 20 mm outer diameter.

FIG. 11 illustrates one form of a forceps holder 70 that may be incorporated in an embodiment of manipulator 10. The forceps holder 70 is configured to seat on the elongated hollow tube 12 and releasably lock at a desired location along the tube 12. Forceps holder 70 comprises a first component 72 that is able to slide over and along tube 12 and is provided with detents 74 for gripping a handle of the forceps. Two detents 74 are shown on opposite sides of a central boss 76. However in other configurations alternate numbers of detent 74 may be provided. The boss 76 is

provided with a screw thread 78 extending from a cross piece 80 which contains the detent 74. Extending axially from the thread portion 78 is a split collar 82. The forceps holder 70 also includes a locking nut 84 that is able to screw onto the threaded portion 78 over the split collar 82 and act to clamp the collar 82 onto an outer surface of the tube 12 thereby releasably locking the holder 70 at an outside location along the tube 12. In one example, the forceps holder 70 may be used to hold vascellum forceps which in turn holds the manipulator 10 to the cervix making the manipulator self retaining.

With reference to FIGS. 12-14b, the manipulator 10 may also support a cervical funnel 90 and a plug 92. The cervical funnel 90 is formed as a unitary device comprising a tube 94 of constant inner and outer diameter and an integral conical portion 96 which increases in outer diameter in a direction away from first end 16 of tube 12. The conical portion is provided with a lip 98 that extends about a part of the circumference of conical portion 96 and is flared in a radial outward direction.

Plug 92 sits on the outside of funnel 90 and when used in gynaecological procedures forms a plug in the vagina. With reference to FIG. 12, it can be seen that the forceps holder 70 may also act as a positioning device for the funnel 90.

FIGS. 13a and 13b depict in greater detail the cervical funnel 90 incorporated in the manipulator 10 shown in FIG. 12. The lip 98 is flared outwardly by an angle of approximately 130°. In this embodiment the outermost edge of the lip 98 extends for an arc α of approximately 115° about the conical portion 96. An inside diameter of the tube 94 is arranged to be slightly greater than the outer diameter of the tube 12 to enable the cervical funnel 90 to be rotatably and linearly moveable with respect to the tube 12.

FIGS. 14a and 14b depict in greater detail the vaginal plug 92 shown previously in FIG. 12. The plug 92 has a main body 100 formed of a constant outer diameter and a contiguous distal end portion 102 of progressively reducing outer diameter tapering to the distal end 104 of the plug 92. When the plug 92 is used with the manipulator 10, it is orientated so that the distal end portion 102 is directed toward the second fitting 24. An interior surface 106 of the plug 92 has a first portion 108 of constant inner diameter, and a contiguous second portion 110 of progressively increasing outer diameter. More particularly, the surface of the portion 110 is arranged to seat an exterior surface of the conical portion 96 of cervical funnel 90. Thus the increase in inner diameter of the surface of portion 110 is substantially the same as the angle of increasing diameter of the outer surface of conical portion 96.

FIG. 15 depicts an optional handle 120 incorporated in embodiments of the manipulator 10. The handle 120 comprises a grip 122 and a contiguous extension 124. The extension 124 is provided with a through hole 126 and a screw thread 128. The screw thread 128 extends from approximately the location of the hole 126 to an end 130 of the handle 120. The through hole 126 is dimensioned to enable the tube 12 to pass there through either with a slight interference fit or a small clearance. Thus the handle 120 extends perpendicular to the tube 12. The screw thread 130 is configured to enable coupling with a nut such as a second locking nut 84. The locking nut when tightened on screw thread 128 can then act to clamp the handle 120 to the tube 12. The handle 120 can be applied to any portion of the tube 12 between the end fittings 22 and 24 which is not otherwise covered by other components such as the cervical funnel 90.

From the above description it will be recognised that dependant on the application at hand the manipulator may

take many different forms owing the interchangeability of first and second fittings and the ability to use additional components such as the rod 26, the forceps holder 70, cervical funnel 90 and the plug 92. It is envisaged that a general uterine manipulator system or kit may be provided to surgeons and doctors composed of all or at least a selection of the first and second fitting; together with other components such as the rod 26, forceps holder 70, cervical funnel 90 and the plug 92. In this way the surgeon or doctor will always have at hand various components to enable the performance of many different procedures.

Now that an embodiment of the invention has been described in detail it will be apparent to those skilled in the relevant arts that numerous modifications and variations may be made without departing from the basic inventive concepts. For example, in one embodiment, the hydrotubation port 42 is illustrated and described as being formed on the first fitting 22. However in an alternate embodiment, a hydrotubation port may be formed on the tube 12 at a location near first end 16 but beyond the screw thread T1. In one embodiment, the first and second fittings 22, 24 may be formed from a plastics material so as to be disposable after a single use while the elongated hollow tube 12 may be made from surgical grade stainless steel so as to be reusable. All such modifications and variations together with others that would be obvious to persons of ordinary skill in the art are deemed to be within the scope of the present invention the nature of which is to be determined from the above description and the appended claims.

What is claimed is:

1. A uterine manipulator system comprising:
 - a cervical funnel that is formed as a unitary device, the cervical funnel having a conical portion and a straight portion, the straight portion extending from a distal end of the conical portion, and the cervical funnel configured for insertion into and for contact with a vaginal cavity;
 - the straight portion having an integral lip extending circumferentially about the straight portion; and
 - the integral lip extending radially outward, the integral lip comprising a distal tip portion and first and second side portions, the distal tip portion having a straight surface extending in an arc between the first side portion and the second side portion, the first and second side portions tangentially aligned with the straight portion of the cervical funnel,
 - wherein a distal end of the integral lip defines a plane, and the straight surface is substantially perpendicular to the plane, at least at a midpoint of the integral lip.
2. The uterine manipulator system of claim 1, further comprising a manipulator configured to support the cervical funnel.
3. The uterine manipulator system of claim 2, wherein the cervical funnel is configured to be rotatably and linearly moveable with respect to the manipulator.
4. The uterine manipulator system of claim 2, the manipulator comprising:
 - an elongated hollow tube defining an internal passage and having opposite first and second ends;
 - a smooth continuous outer surface of constant outer diameter extending between the first and second ends; and,
 - internal first and second screw threads formed in the elongated hollow tube, the first screw thread being formed at the first end and the second screw thread being formed at the second end.

5. The uterine manipulator system of claim 4, the manipulator further comprising a first fitting having a screw thread arranged to engage the first screw thread, the first fitting also having an axial through hole and configured to receive an inner manipulator shaft.

6. The uterine manipulator system of claim 5, wherein the first fitting is configured to apply increasing clamping force on a received inner manipulator when the first fitting is screwed further into the first end.

7. The uterine manipulator system of claim 5, the manipulator further comprising a hydrotubation port formed in the first fitting and in fluid communication with the axial through hole wherein a fluid injected into or through the hydrotubation port is able to flow into the internal passage.

8. The uterine manipulator system of claim 7, wherein the axial through hole comprises a first length which opens onto an end of the first fitting distant the screw thread of the first fitting, and a second contiguous length wherein the first length has a first internal diameter and the second length has a second internal diameter which is greater than the first internal diameter; and wherein the hydrotubation port opens onto the second length of the axial through hole.

9. The uterine manipulator system of claim 5, the manipulator further comprising a second fitting having a threaded portion provided with a screw thread configured to engage the second internal thread on the elongated hollow tube and a body portion extending co-linearly from the threaded portion.

10. The uterine manipulator system of claim 9, wherein the body portion comprises a tubular member which is open at one end distal the threaded portion and is closed at an end near to the threaded portion to form a cavity.

11. The uterine manipulator system of claim 4, the manipulator further comprising a hydrotubation port in fluid communication with the internal passage wherein a fluid injected into or through the hydrotubation port is able to flow into the internal passage.

12. The uterine manipulator system of claim 11, wherein the hydrotubation port is formed in the elongated hollow tube at a location near the first end and beyond the first screw thread.

13. The uterine manipulator system of claim 1, wherein the lip comprises an outermost edge that forms an arc of about 115 degrees.

14. The uterine manipulator system of claim 1, further comprising a plug configured for insertion into a vagina, the plug configured to plug the vagina, the plug configured to be coupled to the cervical funnel, wherein the plug comprises a main cylindrical body having a constant outer diameter.

15. The uterine manipulator system of claim 14, wherein the plug comprises a distal end portion having a progressively reduced outer diameter tapering to the distal direction.

16. The uterine manipulator system of claim 14, wherein the plug comprises an interior surface having a first portion comprising a constant inner diameter.

17. The uterine manipulator system of claim 16, wherein the interior of the surface further comprises a second portion having a progressively increasing diameter.

18. The uterine manipulator system of claim 17, wherein the progressively increasing diameter of the second portion is substantially the same as an angle of the conical portion to enable the second portion to seat the conical portion.

19. A uterine manipulator system for insertion into a vaginal cavity, the uterine manipulator system comprising: a cervical funnel comprising a first portion and a second portion, the first portion including an angled surface

and the second portion including a straight surface that extends from a distal end of the first portion;
 wherein the straight surface has a lip that extends distally from the straight surface and extends about the straight surface; 5
 wherein the lip comprises a first side, a second side, and an edge extending between the first and second sides, wherein the edge has a substantially straight end extending between the first side and the second side, and wherein the first and second sides are tangentially aligned with the straight surface of the second portion; 10
 and
 wherein a distal end of the lip defines a plane, and the straight surface is substantially perpendicular to the plane, at least at a midpoint of the lip. 15

20. A method of using the uterine manipulator system of claim 1 to perform a laparoscopic surgery, the method comprising:

inserting the cervical funnel of the uterine manipulator system into the vaginal cavity; 20
 rotating the cervical funnel to cause the integral lip to present a location for incision of vaginal tissue;
 cutting the vaginal tissue at the presented location;
 removing the cervical funnel from the vaginal cavity; and
 removing a uterus through the vaginal cavity. 25

* * * * *

专利名称(译)	一般子宫操纵器和系统		
公开(公告)号	US9974567	公开(公告)日	2018-05-22
申请号	US15/246140	申请日	2016-08-24
[标]申请(专利权)人(译)	SINGH几碗史蒂芬 JAI SINGH		
申请(专利权)人(译)	辛格几碗史蒂芬 SINGH, JAI		
当前申请(专利权)人(译)	辛格几碗史蒂芬 SINGH, JAI		
[标]发明人	SINGH JIWAN STEVEN SINGH JAI		
发明人	SINGH, JIWAN STEVEN SINGH, JAI		
IPC分类号	A61B17/42 A61B17/00		
CPC分类号	A61B17/4241 A61B17/00234 A61B2017/4216 A61B10/0291 A61B17/42 A61B2017/00464 A61B2017/00473		
优先权	61/472705 2011-04-07 US PCT/AU2012/000332 2012-03-30 WO		
其他公开文献	US20170135727A1		
外部链接	Espacenet USPTO		

摘要(译)

一般的子宫操纵器10包括细长的中空管12，其限定内部通道14。管12具有相反的第一和第二端16和18，形成有内螺纹T1且T2的；并且具有恒定外径的光滑连续外表面20。将包括尾螺钉22的第一配件拧入螺纹T1中，并将第二配件颈椎螺钉拧入螺纹T2中。内部操纵杆26延伸穿过第一配件22，管12和第二配件24。提供一系列备选的第一和第二配件。镊子夹持器70可附接到端部16和18之间的管12。操纵器10也可以支撑子宫颈漏斗90和塞子92。

