



US006494893B2

(12) **United States Patent**
Dubrul et al.

(10) **Patent No.:** **US 6,494,893 B2**
(45) **Date of Patent:** ***Dec. 17, 2002**

(54) **TROCAR SYSTEM HAVING EXPANDABLE PORT**

(75) Inventors: **William R. Dubrul**, Redwood City, CA (US); **Craig K. Tsuji**, Sunnyvale, CA (US); **John E. Carlson**, Mountain View, CA (US)

(73) Assignee: **Innderdyne, Inc.**, Norwalk, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/879,778**

(22) Filed: **Jun. 12, 2001**

(65) **Prior Publication Data**

US 2001/0039430 A1 Nov. 8, 2001

Related U.S. Application Data

(60) Continuation of application No. 09/477,227, filed on Jan. 4, 2000, now Pat. No. 6,325,812, which is a continuation of application No. 08/424,696, filed on Apr. 19, 1995, now Pat. No. 6,080,174, which is a division of application No. 08/026,922, filed on Mar. 5, 1993, now Pat. No. 5,431,676.

(51) **Int. Cl.**⁷ **A61B 17/34**

(52) **U.S. Cl.** **606/185**

(58) **Field of Search** 606/1, 194, 195, 606/198, 184, 185, 190; 604/164.01-164.03

(56) **References Cited**

U.S. PATENT DOCUMENTS

668,879 A 2/1901 Miller
1,213,001 A 1/1917 Phillips
1,248,492 A 12/1917 Hill
2,548,602 A 4/1948 Greenburg

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

EP	0177177	4/1986
EP	0385920	9/1990
WO	WO92/19312	11/1992
WO	WO95/30374	11/1995

OTHER PUBLICATIONS

Product brochure BLUNTPORT, Auto Suture Company, a Division of United States Surgical Corporation (1992) 2 pages.

Product brochure DEXIDE® Inc., Dexide, Inc. (1992) 1 page.

Product brochure ENDOMED™. Cooper Surgical Inc. (1992) 2 pages.


Primary Examiner—Michael J. Milano

Assistant Examiner—Vy Q. Bui

(57) **ABSTRACT**

An apparatus and method for forming and enlarging percutaneous penetrations comprises an elongate dilation member which receives an elongate expansion member in an axial lumen thereof. The dilation tube includes a tubular braid which usually comprises a mesh of non-elastic filaments which are radially expandable from a small diameter configuration to a large diameter configuration and which is optionally covered by a removable sheath. The dilation tube is percutaneously introduced to a target site within a patient's body, usually within the abdomen in a laparoscopic procedure. The sheath (if present) is then removed, and the tubular braid thereafter radially expanded by axial insertion of the expansion member through its lumen. The tubular braid is anchored by axial shortening of the mesh and remains in place to permit subsequent exchange of dilation members to provide for different diameter access lumens. Trocar valves may be removably attached to the proximal end of the expansion member to permit the apparatus to be used as a trocar system in laparoscopic. procedures where the patient's abdomen has been insufflated. An anchoring means may optionally be provided at the distal end of the expansion member.

7 Claims, 8 Drawing Sheets



U.S. PATENT DOCUMENTS

3,509,883 A	11/1967	Dibelius		4,986,830 A	1/1991	Behl	
3,742,958 A	7/1973	Rundles		5,078,736 A	1/1992	Behl	
3,789,852 A	* 2/1974	Kim et al.	604/164.01	5,100,388 A	3/1992	Behl et al.	
3,902,492 A	9/1975	Greenhalgh		5,112,304 A	5/1992	Barlow et al.	
4,018,230 A	4/1977	Ochiai et al.		5,116,318 A	5/1992	Hillstead	
4,141,364 A	2/1979	Schultze		5,122,122 A	6/1992	Allgood	
4,411,655 A	10/1983	Schreck		5,139,511 A	8/1992	Gill et al.	
4,447,237 A	* 5/1984	Frisch et al.	604/175	5,158,545 A	10/1992	Trudell et al.	
4,479,497 A	10/1984	Fogarty et al.		5,183,464 A	2/1993	Dubrul et al.	
4,581,025 A	4/1986	Timmermans		5,188,602 A	2/1993	Nichols	
4,589,868 A	5/1986	Dretler		5,201,756 A	4/1993	Horzewski et al.	
4,601,713 A	7/1986	Fuqua		5,222,938 A	6/1993	Behl	
4,610,688 A	* 9/1986	Silvestrini et al.	623/1.13	5,222,971 A	6/1993	Willard et al.	
4,650,466 A	3/1987	Luther		5,234,425 A	8/1993	Fogarty et al.	
4,716,901 A	1/1988	Jackson et al.		5,250,025 A	10/1993	Sosnowski et al.	
4,738,666 A	4/1988	Fuqua		5,250,033 A	10/1993	Evans et al.	
4,739,762 A	4/1988	Palmar		5,275,611 A	1/1994	Behl	
4,772,266 A	9/1988	Groshong		5,312,360 A	5/1994	Behl	
4,789,193 A	1/1989	Giesy et al.		5,316,360 A	5/1994	Feikema	
4,846,791 A	7/1989	Hattler et al.		5,320,611 A	6/1994	Bonutti et al.	
4,865,593 A	9/1989	Ogawa et al.		5,392,766 A	2/1995	Masterson et al.	
4,869,717 A	9/1989	Adair		5,407,430 A	4/1995	Peters	
4,888,000 A	12/1989	McQuilkin et al.		5,431,676 A	* 7/1995	Dubrul et al.	606/185
4,896,669 A	1/1990	Bhate et al.		5,433,708 A	7/1995	Nichols et al.	
4,899,729 A	2/1990	Gill et al.		5,454,790 A	10/1995	Dubrul	
4,921,479 A	5/1990	Grayzel		5,460,170 A	10/1995	Hammerslag	
4,954,126 A	* 9/1990	Wallsten	606/191	5,540,658 A	7/1996	Evans et al.	
4,955,895 A	9/1990	Sugiyama et al.		5,542,928 A	8/1996	Evans et al.	
4,972,827 A	11/1990	Kishi et al.		6,080,174 A	* 6/2000	Dubrul et al.	606/185

* cited by examiner




FIG. 1.




FIG. 4.




FIG. 2.




FIG. 3.







FIG. 5.






FIG. 9.




FIG. 10.



FIG. 11.





FIG. 12.

*FIG. 12A.*




FIG. 13.




FIG. 14.




FIG. 15.








FIG. 16.



TROCAR SYSTEM HAVING EXPANDABLE PORT

This is a Continuation of U.S. application Ser. No. 09/477,227 filed on Jan. 4, 2000, now U.S. Pat. No. 6,325,812 which is now a Continuation of U.S. application Ser. No. 08/424,696 filed on Apr. 19, 1995, now U.S. Pat. No. 6,080,174 which is a Divisional of U.S. application Ser. No. 08/026,922 filed on Mar. 5, 1993, now U.S. Pat. No. 5,431,676.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to apparatus and methods for providing percutaneous access to an internal operative site during a surgical procedure. More particularly, the present invention relates to a trocar system which can be percutaneously introduced while in a narrow diameter configuration and which after introduction can be radially expanded to accommodate passage of larger diameter surgical instruments.

Minimally invasive surgical procedures rely on obtaining percutaneous access to an internal surgical site using small-diameter access tubes (typically 5 to 12 mm), usually referred to as trocars, which penetrate through the skin and which open to the desired surgical site. A viewing scope is introduced through one such trocar, and the surgeon operates using instruments introduced through other appropriately placed trocars while viewing the operative site on a video monitor connected to the viewing scope. The surgeon is thus able to perform a wide variety of surgical procedures requiring only several 5 to 12 mm punctures at the surgical site. Patient trauma and recovery time are thus greatly reduced.

Particular minimally invasive surgical procedures are often referred to based on the type of scope used to view the region of the body which is the operative site. Thus, procedures in the abdominal area, which rely on a laparoscope for viewing, are referred to as laparoscopic procedures. In such laparoscopic procedures, the patient's abdominal region is typically insufflated (filled with pressured carbon dioxide or nitrogen gas) to raise the abdominal wall and create sufficient operating space to perform a desired procedure. The trocars used in laparoscopic procedures must therefore include a valve at their proximal end to allow passage of the scope or surgical instruments while inhibiting leakage of the insufflating gas. It has also been proposed to perform laparoscopic procedures by mechanically expanding the abdomen rather than using insufflation.

Other minimally invasive surgical procedures include thoracoscopic procedures performed in the region of the chest, arthroscopic procedures performed in body joints, particularly the knee, gynecological laparoscopic procedures, and endoscopic surgical procedures performed in various regions of the body, typically with a flexible scope. These latter procedures do not normally employ pressurization and the trocars used generally do not include pressure valves at their proximal ends.

The design of suitable trocars must fulfill many requirements, particularly for those used in laparoscopic procedures in a pressurized environment. All trocars should be introducible to the patient with minimum trauma and with minimum risk of injury to internal organs. The trocars used in laparoscopic procedures should be readily sealable to inhibit the leakage of gas from the abdomen, and in particular should be designed to inhibit leakage in the region surrounding the external periphery of the trocar which

passes through the abdominal wall. It is further desirable that trocars have means for anchoring within the percutaneous passage, and it would be particularly desirable if a single trocar could accommodate instruments having a wide variety of cross-sectional shapes and sizes.

Heretofore, trocar designs have met the above listed requirements with mixed results. The accommodation of various sized instruments has been met by providing trocars having different fixed diameters. Often, a surgeon will introduce the largest sized trocar, usually 10 to 12 mm, which can then accommodate most or all instruments (which are sized within this maximum) using a rubber adapter. While such an approach is feasible, the introduction of larger sized trocars exposes the patient to greater trauma and risk of injury than would be the case if smaller trocars were used.

External sealing about the periphery of the trocar has also not been adequately addressed. Certain trocar designs employ a tapered helical thread about their periphery. The thread is useful for anchoring, but greatly enlarges the trocar puncture in order to seal against the loss of pressurized insufflation gas. Other anchors, such as malecot structures have been employed on the distal end of the trocars, and are effective for anchoring but provide little sealing against the loss of pressure.

For these reasons, it would be desirable to provide trocars suitable for use in laparoscopic and other minimally invasive surgical procedures which can be easily introduced to the patient via a relatively small puncture (preferably less than 5 mm), which can then be radially expanded (and optionally subsequently reduced) to accommodate a wide variety of instrument sizes, and which provide for improved sealing about the trocar periphery and anchoring within the target site of the operative procedure.

2. Description of the Background Art

U.S. Pat. No. 5,183,464, assigned to the assignee of the present invention, describes a radially expandable dilator including an elongate dilation tube which receives an elongate expansion tube. European Patent Application 385 920 describes a variable diameter braid structure intended for capturing and removing stenotic material from blood vessels. U.S. Pat. No. 5,122,122, describes a trocar sleeve having a malecot structure at its distal end. Trocars for use in laparoscopic procedures are commercially available from suppliers such as United States Surgical Corp., Norwalk, Connecticut; Endomed division of Cooper Surgical, Inc., Shelton, Connecticut; and Dexide Inc., Fort Worth, Tex.

U.S. Pat. No. 4,738,666, describes an expandable catheter having an external sheath which is perforated to facilitate removal as the catheter is being expanded. U.S. Pat. No. 4,601,713, describes a variable diameter catheter having an inflatable retention balloon at its distal end. The catheter is introduced with an internal stylet which holds the catheter in a collapsed (reduced diameter) configuration. Removal of the stylet allows the catheter to expand. U.S. Pat. No. 4,141,364, describes an expandable endotracheal tube which is inserted in a collapsed configuration and springs back to an expanded configuration when air is introduced. Inflatable dilator apparatus are described in U.S. Pat. Nos. 4,589,868 and 2,548,602. Catheters having expandable structures are described in U.S. Pat. Nos. 4,986,830; 4,955,895; 4,896,669; 4,479,497; and 3,902,492.

U.S. Pat. No. 4,772,266, describes a dilator/sheath assembly that may be passed over an in-dwelling guide wire in order to enlarge an access hole, with entry of the sheath further enlarging the hole. U.S. Pat. No. 1,213,001, describes a trocar and cannula assembly which includes an

intermediate tube to form a three-piece structure. U.S. Pat. No. 3,742,958, discloses a cannula having an axial slot to allow the cannula to be stripped from a working catheter which has been introduced through the cannula. U.S. Pat. Nos. 4,888,000; 4,865,593; 4,581,025; 3,545,443; and 1,248,492, each describe devices suitable for percutaneous penetration of a body cavity, blood vessel, or solid tissue. The disclosures of each of the U.S. Patents cited in this paragraph are hereby incorporated herein by reference.

U.S. Pat. No. 4,899,729, describes an expandable cannula which includes a coiled conical sheath which can be percutaneously introduced and thereafter expanded by advancing an internal cylinder. U.S. Pat. No. 4,716,901 discloses an expandable trocar (not including a trocar valve) comprising a pair of opposed components having sharpened distal tips and covered by an elastic sleeve over a proximal portion thereof. U.S. Pat. No. 4,846,791, describes a multi-lumen catheter which includes an elastic outer sleeve and an internal divider which, when inserted, expands the sleeve. See also U.S. Pat. Nos. 668,879; 3,789,852; 4,411,655; 4,739,762; 4,798,193; 4,921,479; 4,972,827; 5,116,318; and 5,139,511, which were made of record in U.S. Pat. No. 5,183,464, assigned to the assignee of the present invention.

A dilator assembly including a guide member having an anchor at its distal end is described in copending application Ser. Nos. 07/616,122 and 07/913,129, assigned to the assignee of the present invention, the disclosures of which are incorporated herein by reference. A peel away sheath is described in copending application Ser. No. 07/967,602, assigned to the assignee of the present invention, the disclosure of which is incorporated herein by reference.

SUMMARY OF THE INVENTION

According to the present invention, improved apparatus and methods for forming and enlarging percutaneous penetrations into target locations within a patient's body are provided. The apparatus comprises an elongate dilation member including a radially expandable tubular braid and an elongate expansion member which is received in an axial lumen of the elongate dilation member to radially expand the braid and provide an enlarged access lumen there-through. The elongate dilation member further includes a puncturing means near its distal end, typically being an elongate penetrating element having a sharpened distal tip which is removably received in and extends distally from the axial lumen of the braid. The elongate dilation member may thus be percutaneously introduced by puncturing the skin. The penetrating member is then removed to permit introduction of the elongate expansion member. The elongate expansion member includes a fixed-radius tubular element having an axial lumen which defines the desired access path.

The expanded braid of the elongate dilation member provides both an anchoring function and a sealing function. The tubular braid, which is preferably in the form of a mesh formed from non-elastic polymeric, stainless steel, or other filaments, shortens as it is radially expanded, causing the braid to tighten or clamp on the tissue with which it is in contact. Such tightening of the braid, when combined with the radial expansion, prevents separation of the tissue layers, provides excellent anchoring of the elongate dilation member within the percutaneous penetration, and enhances the peripheral sealing to inhibit loss of insufflation pressure utilized in laparoscopic procedures. A further advantage of the tubular braid in the elongate dilation member is that it will remain in place as the elongate expansion member is withdrawn therefrom. Thus, elongate expansion members

having different cross-sectional areas and geometries can be introduced and withdrawn into the lumen of the tubular braid, thus allowing the cross-sectional area of the access lumen to be changed as desired. Tissue over the exterior of the braid will be able to stretch or relax, as appropriate, to accommodate such changes in diameter of the braid.

In a preferred aspect of the present invention, the elongate dilation member further comprises a removable protective sheath formed over the braid to facilitate the initial percutaneous introduction. After the elongate dilation member is in place, the protective sheath can be removed, either before, during, or after expansion of the tubular braid. In an exemplary embodiment, the removable sheath is axially split as the tubular braid is radially expanded, and the split portions of the sheath removed after expansion.

In a second preferred aspect of the present invention, the elongate expansion member further includes a rod having a tapered distal end removably received in the axial lumen of the fixed-radius tubular element. The tapered end extends distally from the tubular element, thus facilitating introduction of the expansion member through the axial lumen of the tubular braid. The rod can be withdrawn from the tubular element after it has been introduced through the braid, leaving the lumen of the tubular element available as the desired percutaneous access path.

In a further preferred aspect of the present invention, the elongate expansion member will include means for attaching a trocar valve at its proximal end. Typically, the trocar valve will be removably attached to the expansion member, permitting the same trocar valve to be used on different elongate expansion members having different cross-sectional areas, as they are exchanged during a procedure.

In a further preferred aspect of the present invention, the elongate penetrating element is a needle having a retractable obturator at its distal end. The obturator retracts as the needle is penetrated through skin, and extends forwardly as soon as the needle enters the patient's body, thus helping to protect the patient against accidental injury from the needle. The exemplary needle is a Veress needle of a type commonly used in insufflation devices.

The present invention further provides an improved radially expandable dilator of the type including a radially expandable dilation member and an elongate expansion member which is insertable through an axial lumen of the dilation member. The improvement comprises an expandable dilation member including a radially expandable tubular braid covered by a removable sheath. The tubular braid preferably comprises an open mesh composed of a non-elastic polymeric or metallic filaments, whereby the braid will shorten as its radius is increased.

The present invention still further provides an improved trocar of the type having a fixed-radius tubular element and a trocar valve disposed at a proximal end of the tubular element. The improvement comprises providing a plurality of tubular elements having different fixed diameters and interchangeable means at their proximal ends for securing a trocar valve thereto. The trocar further comprises means defining a radially expandable axial lumen for selectively receiving and conforming to particular ones of said plurality of tubular elements, whereby the defining means may be percutaneously introduced to provide an access lumen for introducing and interchanging tubular members, with the trocar valve being selectively attached to the tubular element after it has been introduced. Preferably, the defining means comprises an elongate radially expandable tubular braid having means at its distal end for puncturing tissue as the braid is percutaneously advanced.

The method according to the present invention comprises penetrating an elongate dilation member through a body surface to a target location within a patient's body. Optionally, a cover may be removed from the dilation member to expose a radially expandable tubular braid having an axial lumen which extends from the body surface to the target location. A first fixed-radius tubular element is then inserted through the lumen of the tubular braid, whereby the tubular braid is expanded to anchor itself within the percutaneous penetration. The tubular element thus provides an access lumen having an enlarged cross-sectional area. Optionally, the method further comprises removing the first fixed-radius tubular element and inserting a second fixed-radius tubular element having a lumen with a different cross-sectional area than that of the first tubular element. In this way, access lumens having a desired cross-sectional area can be introduced at the same location while causing the patient minimum trauma. Tissue abrasion is reduced or eliminated by sliding the second tubular element through the tubular braid, and there is no need to form new percutaneous penetrations.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a first component of a trocar system constructed in accordance with the principles of the present invention. The first component includes an elongate dilation member having an elongate penetrating element received in an axial lumen thereof.

FIG. 2 is a detailed, cross-sectional view taken at region 2—2 of FIG. 1.

FIG. 3 is a detailed view of the proximal end of the component of FIG. 1, shown with portions broken away.

FIG. 4 illustrates a first elongate expansion member constructed in accordance with the principles of the present invention, which forms a second component of the trocar system of the present invention.

FIG. 5 is a detailed, cross-sectional view of the distal tip taken at line 5—5 in FIG. 4.

FIG. 6 is similar to FIG. 5, except that a rod having a tapered distal end has been removed from a lumen of the structure, with an expanded anchoring means shown in broken line.

FIG. 7 illustrates a second elongate expansion member, similar to the first elongate expansion member of FIG. 4, except that it has a larger diameter. The expansion member of FIG. 7 is shown with an expanded anchoring member in broken line and with the inner tapered rod removed.

FIG. 8 is an enlarged view of the proximal end of the expansion member of FIG. 9, shown with portions broken away and with a trocar valve secured thereto.

FIG. 9 illustrates the use of the elongate expansion member of FIGS. 4 or 7 for expanding the elongate dilation tube of FIG. 1 and splitting the sheath about the braid.

FIG. 10 illustrates the elongate dilation member of FIG. 9, shown after expansion and deployment of a distal anchoring means.

FIGS. 11 and 12 illustrate the tubular braid of the elongate dilation member in the radially non-expanded and radially expanded configurations, respectively.

FIG. 12A is a graph illustrating the degree of shortening of the tubular braid of FIGS. 11 and 12 as a function of radial expansion.

FIGS. 13—20 illustrate use of the trocar system of the present invention in forming and enlarging a percutaneous penetration.

DESCRIPTION OF SPECIFIC EMBODIMENTS

The present invention is useful for forming and enlarging percutaneous penetrations into a variety of target locations within a patient's body for a multiplicity of purposes. Such purposes include drainage, intra-organ drug administration, feeding, perfusion, aspiration, and the like, most usually being the introduction of viewing scopes and surgical instruments for use in minimally invasive surgical procedures, such as laparoscopic procedures, thoracoscopic procedures, arthroscopic procedures, endoscopic procedures, and the like.

The devices of the present invention are particularly valuable since they will create a very small initial penetration, usually being below about 5 mm, more usually being below about 4 mm, frequently being below about 3.5 mm, and preferably being 3 mm or below. The penetration will be subsequently enlarged to a desired final size, usually having a final diameter in the range from about 5 mm to 15 mm, more usually being from about 5 mm to 12 mm, and typically being from about 5 mm to 10 mm. The enlarged penetration will define an access lumen from the outside of the patient's body to the desired internal location, and it is a particular advantage of the present invention that the diameter of the access lumen can be changed as will be described in more detail hereinafter.

The dilation apparatus according to the present invention includes an elongate dilation tube having a distal end, a proximal end, and an axial lumen extending from the distal end to the proximal end. The dilation tube includes an expandable tubular braid which is initially in an elongated, narrow-diameter configuration. The braid may be open, but will often be laminated or covered with a coating or layer of elastic or plastically deformable material, such as silicone rubber, latex, polyethylene C-flex, or the like. The tubular braid is percutaneously introduced in its narrow-diameter configuration, and thereafter radially expanded using an elongate expansion member, as described in more detail hereinafter. The tubular braid is preferably formed as a mesh of individual non-elastic filaments (e.g., composed of polyamide fiber (Kevlar7, DuPont), stainless steel, or the like) so that radial expansion causes axial shortening of the braid. Such axial shortening as the braid filaments are radially penetrated into the surrounding tissue helps anchor the dilation member in place within the patient's tissue and helps seal the exterior of the dilation member against the tissue. Such a firmly anchored and gas-tight seal is a particular advantage in laparoscopic procedures.

The braid may be of conventional construction, comprising round filaments, flat or ribbon filaments, square filaments, or the like. Non-round filaments may advantageously reduce the axial force required to provide radial expansion. The filament width or diameter will typically be from about 0.002 inch to 0.25 inch, usually being from about 0.005 to 0.010 inch. Suitable braids may be obtained from a variety of commercial suppliers, such as Bently Harris, Lionville, Penn.; Manville Sealing Components, Denver, Co.; and 3M Ceramic Materials, St. Paul, Minn. A particularly suitable braid is available under the tradename Exando7 PT from Bently-Harris.

The elongate dilation member may optionally further include a removable sheath covering the tubular braid. The sheath is usually composed of a lubricous material, such as a thin-walled flexible plastic, such as polyethylene, tetrafluoroethylene, fluorinated ethylene-propylene, and the like. The sheath protects the tubular braid during initial insertion of the dilation member, but is removed from the

braid after the dilation member is in place. Preferably, the sheath will be weakened along an axial line to facilitate splitting of the sheath at some point during the procedure. Such removable sheaths will usually be employed only if the tubular braid does not itself include an elastic or deformable layer secured to the braid filament material. The construction of suitable sheaths is described in detail in copending application Ser. No. 07/702,642, assigned to the assignee of the present invention, the full disclosure of which is incorporated herein by reference.

The elongate dilation member will further comprise means at its distal end for puncturing tissue as the dilation member is percutaneously advanced. The puncturing means could be secured, either removably or permanently, to either the tubular braid, optional protective sheath, or both. In the exemplary embodiment, however, the puncturing means comprises a separate elongate penetrating element which is received in an axial lumen of the tubular braid, while the braid is in its axially elongate configuration. The penetrating means includes a sharpened distal tip which extends distally beyond the distal end of the tubular braid and optional cover sheath, thus facilitating penetration of the dilation member through the tissue.

In a particularly preferred embodiment, the penetrating element is a needle which includes an obturator which is retractably mounted therein and which extends distally beyond the sharpened distal tip. The obturator is usually spring-loaded, and will thus automatically retract as the needle is advanced through tissue and encounters significant tissue resistance to puncture. The obturator will, however, extend distally beyond the sharpened distal tip to protect the patient from injury after the dilation member has entered the desired target location, such as within the insufflated region of the abdomen during a laparoscopic procedure. Such needles are known as Veress needles and are commonly employed for insufflation in laparoscopic and other procedures.

The elongate dilation member may further comprise an anchor at its distal end to be deployed after penetration but prior to expansion. The anchor would serve to hold the dilation member in place and to prevent separation of the skin and fascial layers as the expansion member is introduced through the dilation member. Usually, however, the inherent anchoring capacity of the tubular braid is sufficient by itself to hold the dilation member in place and prevent tissue separation, so that the anchor will not be necessary.

The elongate expansion member includes a fixed-radius tubular element having a distal end, a proximal end, and an axial lumen extending therebetween. The axial lumen will have a cross-sectional area which is greater than that of the tubular braid in its non-radially expanded configuration. Thus, by introducing the expansion member through the lumen of the tubular braid and causing the braid to radially expand, an enlarged access channel will be provided by the lumen of the fixed-radius tubular element. To facilitate introduction of the elongate expansion member through the axial lumen of the tubular braid, a rod having a tapered distal end is preferably provided in the lumen of the tubular element. The tapered end extends distally from the tube and acts to spread apart the tubular braid as the expansion member is advanced. The rod can then be removed from the tube to leave the access lumen unobstructed after the expansion member has been fully advanced through the tubular braid. Trocar systems of the present invention will preferably include at least two elongate expansion members having different cross-sectional areas so that the same dilation member can be selectively used as a channel to introduce access ports of many different sizes.

The elongate expansion member may optionally include an anchoring means at or near its distal end. The anchoring means can take a variety of forms, including malecot structures, hooks, inflatable balloons, and the like, and will serve to hold the expansion member in place at the target location after deployment. To further enhance anchoring, an external clamp or anchor may further be provided at or near the proximal end of the expansion member so that tissue disposed between the anchors, e.g., the abdominal wall, may be captured therebetween. Anchoring provided by such clamping will, of course, be in addition to the inherent anchoring achieved by expansion of the tubular braid, as described above.

Usually, the elongate expansion member will include means at its proximal end for removably securing a trocar valve. The trocar valve is similar to conventional trocar valves which are fixedly mounted on trocars. The valve will include internal structure which permits the introduction of viewing scopes and/or surgical instruments having different cross-sectional areas, while sealing about the periphery of such devices to prevent loss of insufflation pressure in laparoscopic procedures. The valves will also typically include stopcocks which permit introduction or venting of insufflation gas, irrigation, aspiration, and the like. Conventional trocar valves are manufactured by various suppliers, such as Ethicon, Inc., Somerville, N.J.; United States Surgical Corporation, Norwalk, Conn.; Dexide, Inc., Fort Worth, Tex.; and others.

The length of the elongate dilation tube will vary depending on the intended usage, but will generally be in the range from about 10 cm to 25 cm. The length of dilation tubes intended for laparoscopic procedures will generally be in the range from about 10 cm to 20 cm, typically being in the range from about 10 cm to 15 cm.

The length of dilation tubes used in trocar systems intended for thoracoscopic use will generally be shorter, typically having a length in the range from about 5 cm to 10 cm. The length of the elongate expansion member, of course, will generally be somewhat greater than that of the elongate dilation member, thus permitting radial expansion of the entire length of the dilation member.

Referring now to the figures, an exemplary trocar system constructed in accordance with the principles of the present invention will be described. The three principle components of the trocar system are an elongate dilation member **10**, best illustrated in FIGS. 1-3, one or more elongate expansion members **12** and **14**, best illustrated in FIGS. 4-8, and a trocar valve **16**, best illustrated in FIG. 8. Each of these components, and the use of these components in the method of the present invention, will now be described in greater detail.

The elongate dilation member **10** comprises a tubular braid **20** having an axial lumen which extends from a handle **22** located at its proximal end to a ferrule **24** on the needle **40** located at its distal end. The braid **20** is attached to the proximal handle **22** in a manner that permits radial expansion of the braid as the expansion member **12** or **14** is subsequently introduced therethrough, as will be described in greater detail hereinafter. The tubular braid will include discrete braid filaments, as described above, and may further comprise a laminated elastomeric or plastically deformable layer, as described above. A passage **26** is formed in the proximal handle **22** in order to permit passage of the expansion members into the axial lumen of the tubular braid **20**.

The tubular braid **20** is covered with a removable sheath **30** (in the illustrated embodiment) having a handle **32** at its

proximal end. The sheath **30** extends the entire length of the tubular braid **20** and terminates at its proximal end, generally at the location of ferrule **24**, as best illustrated in FIG. 2. The removable sheath **30** may be constructed as described in copending application Ser. No. 07/967,602, the full disclosure of which has been previously incorporated herein by reference.

A needle **40** having a sharpened distal tip **42** and a proximal handle **44** is initially received within the axial lumen of tubular braid **20**. The ferrule **24** is secured near the sharpened distal tip **42** of the needle **20** and includes a forward tapered surface **46** (FIG. 2) which facilitates penetration of the elongate dilation member **10** through the patient's skin, fascial tissues, and organ walls. In particular, the ferrule **24** acts as a transition from the narrow diameter needle **40** to the slightly larger diameter removable sheath **30**. The tubular braid **20** is received within an annular lumen which is defined between the outer surface of the needle **40** and the inner surface of the sheath **30**. Alternatively, the distal end of the sheath **30** may itself be tapered in order to provide the desired smooth transition. It will thus be possible to eliminate the ferrule **24** in certain embodiments of the invention.

The needle **40** is preferably in the form of an insufflation needle having a protective element at its distal tip **42**. As illustrated, the protective element is an obturator **48** having a blunt end **50** which is reciprocatably received in the axial lumen of the needle **40**. The obturator **48** is spring-loaded so that the blunt end **50** extends distally from the sharpened distal tip **42** of the needle **40** in its shelf or "at rest" configuration. As the needle **42** is pressed firmly against the patient's skin or other tissue, however, the blunt end **50** will be retracted back into the needle **40** so that the sharpened tip **42** can penetrate. Usually, the obturator **48** will be hollow and include a port **52** at its distal end. By providing a valve assembly **54** at its proximal end, the combination of needle **40** and obturator **48** can be used to introduce or withdraw fluids, particularly being useful for performing the initial stages of insufflation. Insufflation needles which can be modified for use in the present invention are available from commercial suppliers, such as Ethicon, Inc., Somerville, N.J., (under the tradename Endopath7 Ultra Veress Needle) and United States Surgical Corporation, Norwalk, Conn. (available under the tradename Auto Suture7 Surgineedle7).

Referring now to FIGS. 4-6, the first elongate expansion member **12** will be described in detail. The expansion member **12** comprises a fixed-radius tubular element **60** having a distal end **62** and a proximal end **64**. An inner coaxial tube **66** is slidably received within the axial lumen of the fixed-radius tubular element **60**, being secured to the tubular element only at the distal end **68**. A proximal handle **70** includes a distal half **70A** which is secured to the proximal end of inner coaxial tube **66** and a proximal half **70B** which is connected to the proximal end of the tubular element **60**. Thus, the inner coaxial tube to be drawn proximally relative to the fixed-radius tubular element **60** by drawing the halves **70A** and **70B** axially apart (as shown in FIG. 7 with respect to a second embodiment of the expansion member). In this way, a malecot structure **72** formed near the distal end of the fixed-radius tubular element **60** may be expanded, as illustrated in broken line in FIG. 6.

The first elongate expansion member **12** further includes an internal obturator or rod **74** having a handle **76** at its proximal end and a tapered conical surface **78** at its distal end. The tapered conical surface **78** extends distally from the distal end **62** of the fixed-radius tubular element **60**, as best illustrated in FIG. 5. The outer peripheral surfaces of both

the fixed-radius tubular element **60** and inner coaxial tube **66** are chamfered to form a conical surface **80** which is aligned with the tapered conical surface **78** when the rod **74** is fully inserted within the expansion member **12**. As will be seen hereinafter in connection with FIG. 9, the combination of the tapered conical surface **78** and tapered region **80** facilitates introduction of the expansion member **12** through the tubular braid **20** of the elongate dilation member **10**.

Referring now to FIG. 7, a second elongate expansion member **14** is illustrated. The second expansion member **14** is similar in all respects to the first expansion member **12**, except that the diameter of fixed-radius tubular element **60'** is larger than that of the tubular element **60** of the first expandable member **12**. The particular diameters of the expansion members are not critical, with exemplary ranges being set forth above. In the exemplary embodiment, the diameter of the first elongate expansion member **12** will typically be about 6 mm to 8 mm, to provide an access lumen of approximately 5 mm. The diameter of the second expansion member **14** will be about 12 mm to 14 mm, to provide an access lumen of about 10 mm. The use of 5 mm and 10 mm access lumens are conventional in laparoscopic surgery. It is a particular advantage of the present invention, however, that a wide variety of access lumen diameters can be provided. Thus, it will be expected that trocar systems may include two, three, four, or more expansion members with incrementally different diameters to accommodate virtually any scope or instrument which might be introduced.

FIG. 7 illustrates the expansion member **14** having the inner rod removed therefrom. After the inner rod is removed, the two halves **70A'** and **70B'** of the handle **70'** may be drawn axially apart, as illustrated in broken line, in order to expand the malecot structure **72'**, as also illustrated in broken line.

Referring now to FIG. 8, the handle **70** of first expansion member **12** (as well as handle **70'** of the second expansion member **14**) will be constructed to removably receive the trocar valve **16**. The trocar valve **16** will be of conventional construction, except that it will include a mounting means at its distal end. As illustrated in FIG. 8, the mounting means comprises a male bayonet mount **90** which is detachably received within a female bayonet receptacle **92** in the proximal half **70B** of the handle **70**. In this way, the trocar valve **16** can be mounted on different expansion members as they are exchanged within the tubular braid **20** of dilation member **10**. This is a particular advantage since it reduces the cost and complexity associated with maintaining an inventory of trocars having dedicated valves on each diameter sheath.

Referring now to FIGS. 9 and 10, insertion of elongate expansion member **12** through the elongate dilation member **10** will be described in more detail. Prior to introducing the expansion member **12**, of course, the needle **40** will have been removed from the axial lumen of tubular braid **20** of the dilation member **10**. The tapered distal end defined by surfaces **78** and **80** is introduced through the passage **26** in handle **22**, and thus enters the axial lumen in tubular braid **20**. The sheath **30** will optionally have been split by withdrawal of the needle **40** and passage of the ferrule **24** through the sheath. Alternatively, introduction of the expansion member **12** will axially split the sheath **30**, as illustrated in FIG. 9. As can be seen, distal advancement of the dilation member **12** causes radial expansion of the tubular braid **20**, eventually resulting in the fully expanded braid as illustrated in FIG. 10 (where the inner rod **74** has been removed).

After the expansion member **12** is fully inserted, the (undeployed) malecot structure **22** will extend distally from

11

the distal end of the tubular braid, as illustrated in FIG. 10. The sheath 30 (which will have been split by passage of the expansion member therethrough) will then be withdrawn using handle 32, and the inner rod 74 will be withdrawn using handle 76. The halves 70A and 70B of handle 70 will then be drawn axially apart to deploy the malecot structure 72. The trocar valve 16 will then be mounted on the proximal half 70B of the handle 70, and the structure will be generally as illustrated in FIG. 10. Note that it is the fixed-radius tubular element 60 which provides the structural support within the expanded tubular braid 20. It is also the axial lumen within the fixed-radius tubular element 60 which provides the desired access channel from the trocar valve 16 to the distal end of the structure.

Referring now to FIGS. 11 and 12, the expansion of tubular braid 20 from its initial narrow-diameter configuration illustrated in FIG. 11 to its radially expanded configuration illustrated in FIG. 12 will be described. FIG. 12A illustrates the percentage shortening effect as the exemplary Expando7 PT braid is radially expanded from about 0.1 inch to 0.45 inch.

Referring now to FIGS. 13–20, use of the exemplary trocar system of the present invention for performing a percutaneous penetration will be described. The elongate dilation member 10 is initially positioned at a location on the patient's skin S where it is desired to form the penetration. The dilation member 10 is then penetrated through the skin S by advancing the sharpened distal tip 42 of the needle 40 (FIG. 1) through the skin, as illustrated in FIG. 14. In the case of laparoscopic procedures, as soon as the sharpened tip 42 of the needle 40 penetrates through the skin into the abdomen, the blunt end 48 of obturator 48 will automatically extend to protect the patient's internal organs from accidental injury. At this point, the lumen of needle 40 may be used for insufflation if desired.

After the dilation member 10 has been advanced to its desired location, the needle 40 will be withdrawn using handle 44, leaving the sheath 30 (which may have been split by withdrawal of the needle 40 and attached ferrule 24) and the tubular braid therein with handle 22 at its proximal end, as illustrated in FIG. 15.

Elongate expansion member 12 is next introduced through the passage 26 in handle 22, thus expanding the tubular braid 20 and splitting the sheath 30 (if not already accomplished), as illustrated in FIG. 16. The presence of the sheath 30 and braid 20 facilitates radial expansion of the penetration which has been formed through the skin S, as illustrated in FIG. 16.

After the expansion member 12 has been fully inserted through the dilation member 10, the inner coaxial rod 66 will be withdrawn from the fixed-radius tube 60, and the sheath 30 will be withdrawn from over the expanded tubular braid, as illustrated in FIG. 17. The malecot structure 72 will be expanded by drawing halves 70A and 70B axially apart, as illustrated in FIG. 17. Trocar valve 16 may then be secured to the proximal half 70B of handle 70, as illustrated in FIG. 18.

If it is desired to change the diameter of the access channel of the expansion member, the first expansion member 12 may be withdrawn from the tubular braid, as illustrated in FIG. 19. The tubular braid 20 will at least partially collapse, but will still provide an internal lumen to permit introduction of a second expansion member, such as the larger diameter second expansion member 14. The second expansion member 14 may be introduced through the handle 22 in a manner analogous to introduction of the first expan-

12

sion member 12, except that the sheath 30 will no longer be in place. The tubular braid 20, however, is sufficient by itself to permit the passage of the expansion member 14 through the percutaneous penetration through skin S with minimum trauma to the patient. It will be appreciated that expansion members having smaller or larger diameters may be exchanged for the initially present expansion member in the tubular braid 20. Final placement of second expansion member 14 is illustrated in FIG. 20, where the malecot structure 72' has been deployed by pulling the handle 70' proximally relative to fixed radius tube 60'.

Although the foregoing invention has been described in some detail by way of illustration and example, for purposes of clarity of understanding, it will be obvious that certain changes and modifications may be practiced within the scope of the appended claims.

What is claimed is:

1. A radially expandable sleeve system for forming a percutaneous surgical access port in a patient's body, comprising:

a radially expandable sleeve member;

an elongate expansion assembly comprising a rigid tubular member of a first diameter and a rigid elongate member receivable within said tubular member, said elongate expansion assembly being insertable through an axial lumen of the sleeve member;

said expandable sleeve member including a radially expandable tubular braid having an open distal end and an open proximal end thereby defining an open ended axial lumen extending completely through said tubular braid, wherein said tubular braid is made from a mesh of non-elastic filaments which axially shortens as the braid is radially expanded upon insertion of said expansion assembly into said tubular braid, wherein said tubular braid remains expanded upon removal of said rigid elongate member from said tubular member.

2. A radially expandable sleeve system as in claim 1, wherein the sleeve member further comprises a removable sheath which covers the tubular braid.

3. A radially expandable sleeve system as in claim 1, wherein the tubular braid of the sleeve member is a laminated structure comprising the braid filaments in an elastic deformable matrix layer.

4. A radially expandable sleeve system for forming a percutaneous surgical access port in a patient's body, comprising:

a radially expandable sleeve member having a first diameter;

an elongate expansion assembly comprising a rigid tubular member of a first diameter and a rigid elongate member receivable within said tubular member, said elongate expansion assembly being insertable through an axial lumen of the sleeve member; said expandable sleeve member including a radially expandable tubular braid having an open distal end and an open proximal end thereby defining an open ended axial lumen extending completely therethrough, wherein said tubular braid is made of a non-elastic fabric which radially expands to a second diameter, which second diameter is greater than said first diameter, in response to an insertion of said expansion assembly into said tubular braid, wherein said tubular braid remains expanded upon removal of said rigid elongate member from said tubular member.

5. A radially expandable sleeve system according to claim 4, wherein said non-elastic fabric comprises a tubular braid comprising a mesh of non-elastic filaments.

6. A radially expandable sleeve system according to claim 5, wherein said tubular braid of the sleeve member is a

13

laminated structure wherein the braid filaments are in an elastic deformable matrix layer.

7. A radially expandable sleeve system according to claim 5, wherein said tubular braid of the sleeve member is a

14

laminated structure wherein the braid filaments are in a plastically deformable matrix layer.

* * * * *

专利名称(译)	具有可扩展端口的套管系统		
公开(公告)号	US6494893	公开(公告)日	2002-12-17
申请号	US09/879778	申请日	2001-06-12
[标]申请(专利权)人(译)	DUBRUL WILLIAM - [R] 辻CRAIG 卡尔森John发		
申请(专利权)人(译)	DUBRUL威廉R. 辻CRAIG K. 卡尔森约翰·		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	DUBRUL WILLIAM R TSUJI CRAIG K CARLSON JOHN E		
发明人	DUBRUL, WILLIAM R. TSUJI, CRAIG K. CARLSON, JOHN E.		
IPC分类号	A61B17/34 A61F2/00 A61B19/00 A61M25/06 A61B17/00 A61B1/00		
CPC分类号	A61B17/3439 A61B17/00234 A61B17/3431 A61B17/3474 A61B2017/00986 A61B2017/3484 A61B2019/4878 A61F2/0063 A61M25/0662 A61M2025/0025 A61B2090/0815		
其他公开文献	US20010039430A1		
外部链接	Espacenet USPTO		

摘要(译)

用于形成和扩大经皮穿透的装置和方法包括细长的扩张构件，该细长的扩张构件在其轴向内腔中接收细长的扩张构件。扩张管包括管状编织物，该管状编织物通常包括非弹性细丝网，其可从小直径构型径向扩张到大直径构型，并且可选地由可移除的护套覆盖。将扩张管经皮引入患者体内的目标部位，通常在腹腔镜手术中通常在腹部内。然后移除护套（如果存在的话），然后将膨胀构件轴向插入其内腔使管状编织物径向膨胀。管状编织物通过网状物的轴向缩短而锚定并保持在适当位置以允许随后更换扩张构件以提供不同直径的进入腔。套管阀可以可拆卸地连接到扩张构件的近端，以允许该装置在腹腔镜中用作套管针系统。患者腹部充气的程序。可选地，可在膨胀构件的远端处设置锚固装置。

