



US007883515B2

(12) **United States Patent**
Kear

(10) **Patent No.:** **US 7,883,515 B2**
(45) **Date of Patent:** **Feb. 8, 2011**

(54) **MEDICAL DEVICE**

(75) Inventor: **Jason W. Kear**, Bloomington, IN (US)

(73) Assignee: **Boston Scientific Scimed, Inc.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,430,073 A	2/1984	Bemis et al.
4,468,216 A	8/1984	Muto
4,469,090 A	9/1984	Konomura
4,469,100 A	9/1984	Hardwick
4,561,428 A	12/1985	Konomura

(Continued)

(21) Appl. No.: **12/394,407**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Feb. 27, 2009**

EP 0958787 11/1999

(65) **Prior Publication Data**

US 2009/0198250 A1 Aug. 6, 2009

(Continued)

Related U.S. Application Data

(62) Division of application No. 10/202,978, filed on Jul. 25, 2002, now abandoned.

OTHER PUBLICATIONS

White, Frank M., Fluid Mechanics, Copyright 1986, McGraw-Hill, Inc. 2nd Edition, pp. 332-339.*

(51) **Int. Cl.**
A61B 17/22 (2006.01)

(Continued)

(52) **U.S. Cl.** **606/127**

Primary Examiner—Anhtuan T Nguyen
Assistant Examiner—Elizabeth Houston

(58) **Field of Classification Search** 606/108,
606/110, 115, 123, 127, 128, 159, 111–114;
604/19, 27, 35–38, 41, 48, 118, 119, 313–316,
604/540–544, 902, 22; 433/91, 93
See application file for complete search history.

(57) **ABSTRACT**


(56) **References Cited**

U.S. PATENT DOCUMENTS

2,711,586 A *	6/1955	Groves	433/95
3,908,637 A	9/1975	Doroshov	
3,958,566 A	5/1976	Furihata	
4,031,896 A	6/1977	Ronnmark	
4,146,019 A	3/1979	Bass et al.	
4,198,958 A	4/1980	Utsugi	
4,243,040 A	1/1981	Beecher	
4,253,448 A	3/1981	Terada	
4,270,525 A	6/1981	Furihata	
4,408,598 A	10/1983	Ueda	
4,412,531 A	11/1983	Chikashige	

A stone retrieval suction device facilitates the retention and then relocation and/or removal of objects disposed in a patient's urinary system. The device includes an elongated member for placement in a channel of a flexible ureteroscope. The elongated member defines a suction passageway which extends longitudinally therethrough. The elongated member is flexible enough to bend with the flexible ureteroscope, and it is strong enough to prevent collapse of the suction passageway when suction is provided through the suction passageway by a vacuum source. The elongated member includes a distal portion for contacting and retaining an object when the suction is provided.

12 Claims, 24 Drawing Sheets



U.S. PATENT DOCUMENTS

4,562,830 A 1/1986 Yabe
 4,572,163 A 2/1986 Collins et al.
 4,616,631 A 10/1986 Takahashi
 4,643,197 A 2/1987 Greene et al.
 4,672,953 A 6/1987 DiVito
 4,686,965 A 8/1987 Bonnet et al.
 4,759,348 A 7/1988 Cawood
 4,794,913 A 1/1989 Shimonaka et al.
 4,807,626 A 2/1989 McGirr
 4,813,926 A 3/1989 Kerwin
 4,832,048 A 5/1989 Cohen
 4,878,900 A 11/1989 Sundt
 4,898,574 A 2/1990 Uchiyama et al.
 4,899,733 A 2/1990 DeCastro et al.
 4,973,311 A 11/1990 Iwakoshi et al.
 4,982,726 A 1/1991 Taira
 5,057,080 A 10/1991 Takahashi
 5,059,178 A * 10/1991 Ya 604/101.03
 5,127,393 A 7/1992 McFarlin et al.
 5,129,910 A 7/1992 Phan et al.
 5,190,050 A 3/1993 Nitzsche
 5,199,417 A 4/1993 Muller et al.
 5,222,949 A 6/1993 Kaldany
 5,226,885 A 7/1993 Takahashi
 5,244,459 A 9/1993 Hill
 5,257,773 A 11/1993 Yoshimoto et al.
 5,269,785 A 12/1993 Bonutti
 5,295,830 A 3/1994 Shen et al.
 5,299,561 A 4/1994 Yoshimoto
 5,320,627 A 6/1994 Sorensen et al.
 5,322,263 A 6/1994 Yoshimoto et al.
 5,334,171 A 8/1994 Kaldany

5,392,764 A 2/1995 Swanson et al.
 5,403,317 A 4/1995 Bonutti
 5,453,088 A 9/1995 Boudewijn et al.
 5,476,450 A 12/1995 Ruggio
 5,569,219 A 10/1996 Hakki et al.
 5,718,709 A 2/1998 Considine et al.
 5,722,980 A 3/1998 Schulz et al.
 5,725,478 A 3/1998 Saad
 5,730,742 A * 3/1998 Wojciechowicz 606/49
 5,788,681 A 8/1998 Weaver et al.
 5,813,856 A 9/1998 Lee
 5,843,028 A 12/1998 Weaver et al.
 5,879,342 A 3/1999 Kelley
 5,891,114 A 4/1999 Chien et al.
 5,935,131 A 8/1999 Bonutti
 5,938,645 A 8/1999 Gordon
 5,947,988 A 9/1999 Smith
 5,975,897 A 11/1999 Propp et al.
 6,095,971 A 8/2000 Takahashi
 6,174,313 B1 1/2001 Bonutti
 6,197,014 B1 3/2001 Samson et al.
 6,280,415 B1 * 8/2001 Johnson 604/118
 7,278,972 B2 10/2007 Lamoureux et al.
 7,309,334 B2 12/2007 von Hoffmann

FOREIGN PATENT DOCUMENTS

WO WO 00/12011 3/2000

OTHER PUBLICATIONS

International Search Report for International Patent Application No.
 PCT/US03/23078, 9 pages.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B





FIG. 10C

**FIG. 10D**




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 12




FIG. 13A




FIG. 13B




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B




FIG. 24A




FIG. 24B




FIG. 24C

MEDICAL DEVICE**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a divisional application of U.S. patent application Ser. No. 10/202,978, filed Jul. 25, 2002, now abandoned entitled "Medical Device," which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

The invention relates generally to medical devices.

BACKGROUND INFORMATION

Typical stone retrieval devices are used for retrieving objects, such as kidney stones, that are disposed in easily-accessed areas of a patient's urinary tract. Some known stone retrieval devices are configured such that a physician must advance the device past the object, deploy a basket, and then pull the device back toward the object to capture the object in the basket. In situations where the object is embedded in tissue or located in a lower calyx of a patient's kidney, the device cannot be advanced beyond the object and therefore cannot capture the object. Stone retrieval devices configured with graspers can be used to try to retrieve stones embedded in tissue or located in the lower calyx. These devices typically are not very flexible, however, and therefore frequently are not useful in reaching and capturing such objects. Further, grasping stone retrieval devices may not be able to retrieve a certain object due to the size and/or shape of that object.

SUMMARY OF THE INVENTION

Objects, such as kidney stones and other natural or foreign materials, can become trapped in a patient's urinary system. These objects can be disposed in areas of the urinary system which are not easily accessed by currently available stone retrieval devices. The present invention relates to medical retrieval devices and related methods for accessing and then retaining, relocating, and/or removing an object disposed in an internal location of a patient's body (such as the urinary system) which is not easily accessed by currently available retrieval devices.

In one aspect, the invention involves a medical device. The medical device includes an elongated member that is configured for placement in a channel of a flexible ureteroscope. The elongated member defines a suction passageway which extends longitudinally therethrough. The elongated member bends with the flexible ureteroscope when placed within the channel of the flexible ureteroscope. The suction passageway resists collapsing when suction is provided through the suction passageway by a vacuum source. The elongated member includes a proximal portion for communicating with the vacuum source to provide the suction through the suction passageway and a distal portion for contacting an object and retaining the object in contact with the distal portion when the suction is provided through the suction passageway.

Embodiments according to this aspect of the invention can include various features. For example, the distal portion can include a tapered tip. The distal portion can include a tip which includes a concave portion for contacting the object and retaining the object in contact with the concave portion when the suction is provided through the suction passageway. The distal portion can include a tip which includes a plurality of members extending radially outward from the tip. The

plurality of members prevent tissue proximate to the object from being drawn into the suction passageway when suction is provided through the suction passageway. The distal portion can include a tip which includes a concave portion. The concave portion prevents tissue proximate the object from being drawn into the suction passageway when the suction is provided through the suction passageway. The elongated member can include a mesh to reinforce the member and thus resist collapse of the suction passageway when suction is provided. The mesh can extend longitudinally and circumferentially along the elongated member. The mesh can include stainless steel. The elongated member can include a coil which extends longitudinally, and circumferentially along the elongated member. The proximal portion can include a luer connector and/or a handle for connecting to the vacuum source. The handle can include a switch for selectively enabling and disabling the suction through the suction passageway. The proximal portion can be in communication with a regulator for regulating the suction through the suction passageway. The elongated member can be made of a material such as a biocompatible plastic, a biocompatible polyurethane, or a biocompatible rubber, for example. The elongated member can have an outside diameter of between two and three french. At least some of the distal portion can be radiopaque.

In another aspect, the invention involves a method of contacting and moving an object disposed in a patient. The method includes providing a vacuum source, providing a flexible ureteroscope and introducing the ureteroscope into a patient, and providing a medical device. The medical device includes an elongated member that is configured for placement in a channel of the flexible ureteroscope. The elongated member defines a suction passageway extending longitudinally therethrough. The elongated member bends with the ureteroscope when the elongated member is placed within the channel of the flexible ureteroscope. The suction passageway resists collapsing when suction is provided through the suction passageway by the vacuum source. The elongated member includes a proximal portion for communicating with the vacuum source to provide the suction through the suction passageway, and a distal portion for contacting an object and retaining the object in contact with the distal portion when the suction is provided through the suction passageway. The method further includes introducing the medical device into the channel of the flexible ureteroscope, providing suction through the suction passageway and retaining the object in contact with the distal portion, and moving the retained object from a first location in the patient to a second location.

Embodiments according to this aspect of the invention can include various features. For example, the method can further include moving the retained object to a second location. Moving the retained object to a second location can include moving the retained object outside the patient or to another location inside the patient.

The foregoing and other objects, aspects, features, and advantages of the invention will become more apparent from the following description and from the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, like reference characters generally refer to the same parts throughout the different views. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention.

FIG. 1A is an illustrative diagram of a stone retrieval suction device, according to one embodiment of the invention.

FIG. 1B is an illustrative cross sectional view of the stone retrieval suction device of FIG. 1A, taken along line B-B in FIG. 1A.

FIG. 2 is an illustrative diagram of a flexible ureteroscope disposed in a patient and a stone retrieval suction device in communication with a vacuum source disposed outside of the patient, according to one embodiment of the invention.

FIG. 3 is an illustrative diagram of the stone retrieval suction device of FIG. 2 partially disposed in a channel of the flexible ureteroscope.

FIG. 4A is an illustrative diagram of the stone retrieval suction device of FIG. 2 disposed in the channel of the flexible ureteroscope and extending out of a distal end of the ureteroscope and into the patient's kidney.

FIG. 4B is an illustrative diagram of a stone retrieval suction device disposed in the channel of the flexible ureteroscope and also in communication with a remote vacuum source through an extension tube, according to another embodiment of the invention.

FIG. 5 is an illustrative cross sectional view of a distal portion of a stone retrieval suction device disposed inside the patient and proximate an object disposed in the patient's kidney, according to one embodiment of the invention.

FIG. 6 is an illustrative cross sectional view of the distal portion of the stone retrieval suction device of FIG. 5 contacting and retaining the object disposed in the patient's kidney.

FIG. 7 is an illustrative cross sectional view of the distal portion of the stone retrieval suction device of FIG. 6 after the object disposed in a patient's kidney has been relocated.

FIG. 8 is an illustrative cross sectional view of the distal portion of the stone retrieval suction device of FIG. 7 after the object disposed in a patient's kidney has been released.

FIG. 9 is an illustrative cross sectional view of the distal portion of the stone retrieval suction device of FIG. 7 removing the object from the patient's kidney.

FIG. 10 is an illustrative diagram of a stone retrieval suction device including a mesh, according to another embodiment of the invention.

FIG. 10B is an illustrative cross sectional view of the stone retrieval suction device of FIG. 10A, taken along line B-B in FIG. 10A, according to one embodiment of the invention.

FIG. 10C is an illustrative cross sectional view of the stone retrieval suction device of FIG. 10A, taken along line B-B in FIG. 10A, according to another embodiment of the invention.

FIG. 10D is an illustrative cross sectional view of the stone retrieval suction device of FIG. 10A, taken along line B-B in FIG. 10A, according to still another embodiment of the invention.

FIG. 11A is an illustrative diagram of a stone retrieval suction device including a coil, according to one embodiment of the invention.

FIG. 11B is an illustrative cross sectional view of the stone retrieval suction device of FIG. 11A, taken along line B-B in FIG. 11A, according to one embodiment of the invention.

FIG. 11C is an illustrative cross sectional view of the stone retrieval suction device of FIG. 11A, taken along line B-B in FIG. 11A, according to another embodiment of the invention.

FIG. 11D is an illustrative cross sectional view of the stone retrieval suction device of FIG. 11A, taken along line B-B in FIG. 11A, according to still another embodiment of the invention.

FIG. 12 is an illustrative cross sectional view of a tapered tip coupled to a distal portion of the stone retrieval suction device, according to one embodiment to the invention.

FIG. 13A is an illustrative cross sectional view of a tip including a concave portion coupled to a distal portion of the stone retrieval suction device, according to another embodiment to the invention.

FIG. 13B is an illustrative cross sectional view of a tip including a concave portion coupled to a distal portion of the stone retrieval suction device, according to yet another embodiment to the invention.

FIG. 14 is an illustrative cross sectional view of a tip including a plurality of arms extending radially outward coupled to a distal portion of the stone retrieval suction device, according to still another embodiment to the invention.

FIG. 15 is an illustrative cross sectional view of a tapered tip coupled to a distal portion of the stone retrieval suction device including a mesh disposed on the inner surface of a wall of the elongated member, according to one embodiment to the invention.

FIG. 16 is an illustrative cross sectional view of a tip including a concave portion coupled to a distal portion of the stone retrieval suction device including a mesh disposed in a wall of the elongated member, according to another embodiment to the invention.

FIG. 17 is an illustrative cross sectional view of a tip including a plurality of arms extending radially outward coupled to a distal portion of the stone retrieval suction device including a mesh disposed on the outer surface of a wall of the elongated member, according to still another embodiment to the invention.

FIG. 18 is an illustrative cross sectional view of a tapered tip coupled to a distal portion of the stone retrieval suction device including a coil disposed on the inner surface of a wall of the elongated member, according to one embodiment to the invention.

FIG. 19 is an illustrative cross sectional view of a tip including a concave portion coupled to a distal portion of the stone retrieval suction device including a coil disposed in a wall of the elongated member, according to another embodiment to the invention.

FIG. 20 is an illustrative cross sectional view of a tip including a plurality of arms extending radially outward coupled to a distal portion of the stone retrieval suction device including a coil disposed on the outer surface of a wall of the elongated member, according to still another embodiment to the invention.

FIG. 21 is an illustrative diagram of the stone retrieval suction device including a handle disposed in the channel of the flexible ureteroscope and extending out of a distal end of the ureteroscope and into the patient's kidney.

FIGS. 22A and 22B are illustrative cross sectional diagrams of a handle of the stone retrieval suction device, according to one embodiment of the invention.

FIGS. 23A and 23B are illustrative cross sectional diagrams of a handle of the stone retrieval suction device, according to another embodiment of the invention.

FIG. 24A is an illustrative diagram of a handle of the stone retrieval suction device, according to still another embodiment of the invention.

FIGS. 24B and 24C are illustrative cross sectional diagrams of the handle shown in FIG. 24A.

DESCRIPTION

Objects, such as kidney stones (calculi) and other natural or foreign materials, can become trapped in a patient's urinary system. These objects can be disposed in areas of the urinary system that are easily accessed by currently available stone

retrieval devices. These objects can also be disposed in areas of the urinary system, such as embedded in tissue or located in a lower calyx of a patient's kidney, for example, which are not easily accessed by currently available stone retrieval devices. The present invention relates to medical devices and related methods for accessing and then retaining, relocating, and/or removing an object disposed in an internal area of a patient's body (such as the urinary system) which is difficult or impossible to access with currently available retrieval devices or methods.

Referring to FIGS. 1A and 1B, in one embodiment, the stone retrieval suction device **100** includes an elongated member **102** which defines a suction passageway **110** extending longitudinally therethrough. The elongated member **102** is designed to be placed in a channel of a flexible ureteroscope and has an outside diameter of between two and three french. The elongated member **102** bends with the flexible ureteroscope when placed within the channel of the flexible ureteroscope. The suction passageway **110** resists collapsing when suction is provided through the suction passageway **110** by a vacuum source. For example, the elongated member **102** can be reinforced to resist collapse of the suction passageway **110** when suction is provided through the suction passageway **110**. Materials that can be used for the elongated member **102** include, but are not limited to, biocompatible plastic, biocompatible rubber, and biocompatible polyurethane. In one embodiment, the bendable elongated member **102** is formed of Pebax, PTFE, or Polyurethane. The elongated member further includes a proximal portion **108**. The proximal portion **108** is in communication with the vacuum source to provide suction through the suction passageway **110**. In one embodiment, the proximal portion **108** can also include a luer connector **104**. The luer connector **104** is used to connect the elongated member **102** to the vacuum source. The elongated member further includes a distal portion **106** for making contact with an object disposed in a patient, such as a kidney stone. The distal portion **106** retains the object in contact with the distal portion **106** when suction is provided through the suction passageway **110**. In one embodiment, the distal portion **106** can also include a tapered tip **112** which is used to contact the object. In other embodiments, the distal portion **106** can include other types of tips which are discussed in further detail below. In some embodiments, the distal portion **106** can also include a radiopaque material which facilitates easily locating the elongated member **102** with a fluoroscope when the elongated member **102** is disposed within the patient. The radiopaque material can be painted on, and/or embedded in, the elongated member **102**. The radiopaque material can also be a band painted on, embedded in, and/or wrapped around the distal portion **106** of the elongated member **102**. In some embodiments, the radiopaque material can be tungsten filled ink, bismuth subcarbonate, or barium sulfate. In other embodiments, the radiopaque material can be a platinum or tantalum metal band.

The elongated member **102** can be extruded from any of the materials previously described using known extrusion techniques. The luer connector **104** can be made of molded plastic or metal, such as stainless steel. The tapered tip **112** can also be made of molded plastic or metal.

Referring to FIGS. 2-4A, in operation, a user (e.g. a doctor or other medical personnel) inserts a distal end **216** of a flexible ureteroscope **214** into the patient's urethra **202**. The user advances the flexible ureteroscope **214** so that the distal end **216** passes into and through the urinary bladder **204**, into and through the ureter **206**, and into the kidney **208**. The user positions the distal end **216** of the flexible ureteroscope **214** within the patient's kidney **208** by manipulating positioning

knobs **230**, **232**. The knob **230** moves the distal end **216** vertically and the knob **232** moves the distal end **216** horizontally. By manipulating the positioning knobs **230**, **232**, and viewing the kidney's **208** interior with an eyepiece **224**, the user can position a distal channel opening **228** of the flexible ureteroscope **214** proximate an object, such as a kidney stone, that is disposed in the patient's kidney **208**.

The user then connects the luer connector **104** to a regulator **210** which, in turn, is connected to a vacuum source **212**. The vacuum source **212** provides suction through the suction passageway **110** and the regulator **210** allows the user to vary the suction provided by the vacuum source **212** by adjusting a suction adjustment dial **222**. In this embodiment, the vacuum source **212** is located near the patient. In another embodiment, the vacuum source **212** can be located remotely and is discussed in further detail below.

As previously described, the elongated member **102** includes a material that enables the elongated member **102** to bend with the flexible ureteroscope **214**. After the user has inserted the flexible ureteroscope **214** into the patient, the user then inserts the distal portion **106** of the elongated member **102** into a proximal channel opening **226** at a proximal end **218** of the flexible ureteroscope **214**. The user then advances the distal portion **106** through the channel **502** (shown in FIG. 5) of the flexible ureteroscope **214** until the tapered tip **112** extends out of the distal channel opening **228** at the distal end **216** of the flexible ureteroscope **214**.

Referring to FIG. 4B, in another embodiment, the elongated member **102** can be connected to a remotely located vacuum source **212** (such as a vacuum source located on a wall). In this embodiment, the elongated member **102** communicates with the regulator **210** through an extension tube **402**. The luer connector **104** of the elongated member **102** is mated to a first luer connector **406** disposed on a proximal end **408** of the extension tube **402**. A second luer connector **404** disposed on a distal end **410** of the extension tube is connected to the regulator **210**.

Referring to FIGS. 4A, 5, and 6, after the elongated member **102** is advanced through the channel **502** so that the tapered tip **112** extends out of the channel **502** through the distal channel opening **218** and is proximate to a kidney stone **504**, the user switches on the suction (using switch **220**). The suction pulls the kidney stone **504** in a direction (indicated by arrow **506**) toward the tapered tip **112**. Eventually, the kidney stone **504** makes contact with the tapered tip **112** and is held in contact with the tapered tip **112** by the continuous suction through the suction passageway **110** (shown in FIG. 1B). If the kidney stone **504** is embedded in tissue, the user moves the tapered tip **112** toward the embedded kidney stone **504**. After the tapered tip **112** makes contact with the embedded kidney stone **504**, the suction through the suction passageway **110** retains the kidney stone **504** in contact with the tapered tip **112**. The user can then pull the kidney stone **504** free by retracting the distal portion **106** of the elongated member **102** into the channel **502**.

This device and method enables the user to capture and retain the kidney stone **504** even when the kidney stone **504** is embedded in tissue or located in a portion of the patient's body that is difficult or impossible to access with typical basket and/or grabber stone retrieval devices.

Referring to FIGS. 7-8, after contacting and retaining the kidney stone **504**, the user can reposition the distal end **216** of the flexible ureteroscope **214** with the distal portion **106** of the elongated member **102** still extending beyond the distal channel opening **218** and retaining the kidney stone **504** in contact with the tapered tip **112**. The purpose of repositioning the distal end **216** of the flexible ureteroscope **214** is to move the

kidney stone **504** to an area in the kidney that is easily accessed by typical stone retrieval baskets or grabbers. After the user relocates the kidney stone **504**, the user can release the kidney stone **504** by discontinuing the suction and retracting the distal portion **106** of the elongated member **102** through the distal channel opening **218**. After the kidney stone **504** is released, the user can use any of a variety of existing stone retrieval devices to capture and remove the kidney stone **504** from the patient's urinary system. If the kidney stone **504** is too large to remove, the user can employ any of a variety of stone destruction devices (such as laser or vibration devices, for example) to break the kidney stone **504** into smaller pieces. If the kidney stone **504** has a diameter smaller than the diameter of the channel **502** of the flexible ureteroscope **214**, the user can remove the kidney stone **504** from the patient by pulling the kidney stone **504** through the channel **502** of the flexible ureteroscope **214**.

Referring to FIGS. 10A-D and 15-17, in another embodiment, the stone retrieval suction device **100** includes a mesh **1002** which extends longitudinally and circumferentially along the elongated member **102**. The mesh **1002** can be made of stainless steel and/or other material(s). The mesh **1002** can be, for example, formed by two or more cords that are woven together to form the mesh **1002** with each cord having one or more, for example three or more, component strands. Each of the strands could be thin wire or metal or a metal alloy, for example. The mesh **1002** reinforces the elongated member **102** so that the elongated member **102** does not collapse when suction is provided through the suction passageway **110** by the vacuum source **212** (FIG. 4A). The cords of the mesh **1002** can be either spaced closely together to form a dense mesh or spaced far apart to form a sparse or open mesh. The mesh **1002** can be affixed to an inner surface **1006** (FIGS. 10C and 15) or an outer surface **1004** (FIGS. 10B and 17) of the elongated member **102**. The mesh **1002** can also be embedded between the inner surface **1006** and the outer surface **1004** of the elongated member **102** (FIGS. 10D and 16).

Referring to FIGS. 11A-D and 18-20, in still another embodiment, the stone retrieval suction device **100** includes a coil **1102** which extends circumferentially and longitudinally along the elongated member **102**. The coil **1102** can be made of stainless steel and/or other material(s). The coil **1102** can be, for example, formed by a cord with the cord having one or more, for example three or more, component strands. Each of the strands could be thin wire or metal or a metal alloy, for example. The coil **1102** reinforces the elongated member **102** so that the elongated member **102** does not collapse when suction is provided through the suction passageway **110** by a vacuum source. The coil **1102** can be tightly wound so that the individual coils are spaced closely together to form a dense coil or the coil **1102** can be loosely wound so that the individual coils are spaced far apart to form an open coil. As with the mesh **1002**, the coil **1102** can be affixed to the inner surface **1006** (FIGS. 11C and 18) or the outer surface **1004** (FIGS. 11B and 20) of the elongated member **102**. The coil **1102** can also be embedded between the inner surface **1006** and the outer surface **1004** of the elongated member **102** (FIGS. 11D and 19).

Referring to FIG. 12, the distal portion **106** of the elongated member **102** can include a tapered tip **112**. The tapered tip **112** includes a side wall **120** having an inner surface **124**, an outer surface **126**, and a distal end surface **122**. The inner surface **124** of the tapered tip **112** defines a lumen **128** that is a portion of the suction passageway **110**. The distal end surface **122** defines a distal end opening **123** in fluid communication with the suction passageway **110**. As shown in FIG. 12, the diameter of the distal end opening **123** is greater than the thick-

ness of the side wall **120**. The tapered tip **112** can be made of molded plastic or metal, for example, although other materials or combinations of materials are possible. In another embodiment shown in FIG. 13A, the distal portion **106** can include a tip **1302** with a concave portion **1304**. The concave portion **1304** is used to contact an object disposed in a patient's urinary system and retain the object in contact with the concave portion **1304** when suction is provided through the suction passageway **110**. In still another embodiment shown in FIG. 13B, the distal portion **106** can include a concave portion **1306** with a tapered tip **1308** within the concave portion **1306**. The concave portion **1306** is used to keep surrounding tissue away from the suction in the tapered tip **1308** when the tapered tip **1308** contacts an object. In yet another embodiment shown in FIG. 14, the distal portion **106** can include a tip **1402** which includes a plurality of members **1404**. The plurality of members **1404** extend radially outward from the tip **1402** and prevent tissue (proximate to an object being contacted) from being pulled into the suction passageway **110**. The tips **1302**, **1402** can also be made of molded plastic or metal.

Referring to FIGS. 21, 22A, and 22B, in another embodiment, the suction retrieval device **100** can include a handle **2102**. The handle **2102** includes a suction button **2104** which is used to enable and disable the suction in the suction passageway **110** by uncrimping and crimping a portion of the elongated member **102** disposed in the handle **2102**. When the suction button **2104** is not pressed (default position), the suction button **2104** is positioned such that a rigid member **2108** presses against the suction tube **302** thereby crimping the elongated member **102** and disabling the suction in the suction passageway **110**.

When the suction button **2104** is pressed (in the direction indicated by arrow **2106**), the suction button **2104** is positioned such that the rigid member **2108** no longer crimps the elongated member **102**, thereby enabling suction in the suction passageway **110**. As long as the suction button **2104** is pressed, the suction in the suction passageway **110** is enabled. As soon as the suction button **2104** is released, the suction in the suction passageway **110** is disabled.

In operation, after inserting the flexible ureteroscope **214** into the patient's urinary system, the user connects the luer connector **104** to the regulator **210** and then guides the elongated member **102** into and through the channel of the flexible ureteroscope **214**. The user then turns on the vacuum source **212** with the switch **220** and adjusts the suction with suction adjustment knob **222** on the regulator **210**. The user positions the elongated member **102** proximate to an object disposed in the patient's urinary system by the method previously described, and then presses the suction button **2104** on the handle **2102** to engage the suction (by uncrimping the portion of elongated member **102** disposed in the handle **2102**). After the object is captured and relocated to a new position or removed from the patient, the user releases the button **2104** to disengage the suction (by crimping the portion of elongated member **102** disposed in the handle **2102**) thereby releasing the object.

Referring to FIGS. 23A and 23B, in still another embodiment, the suction retrieval device **100** can include a handle **2302**. The handle **2302** includes a suction port **2306** which is used to enable and disable the suction in the distal portion **106** of the suction passageway **110**. The suction port **2306** is an opening to the suction passageway **110** and allows outside air to be sucked into the suction passageway **110** by the vacuum source (as indicated by arrows **2304**) when left open or uncovered. As a result, the suction in the distal portion **106** of the suction passageway **110** is significantly reduced or dis-

abled entirely. When the suction port **2306** is covered, by a user's finger **2308** for example, the suction port **2306** is sealed and the suction in the distal portion **106** of the suction passageway **110** is restored.

Referring to FIGS. **24A-C**, in yet another embodiment, the suction retrieval device **100** can include a handle **2402**. The handle **2402** includes a rotatable valve **2404** which is used to enable and disable the suction in the distal portion **106** of the suction passageway **110** by redirecting the suction from the vacuum source. The valve **2404** includes a handle **2412** (for rotating the valve) and two perpendicular suction tubes **2416**, **2414**. When the valve **2404** is rotated to an open position (FIG. **24B**), a suction port **2406** is put in communication with the vacuum source via the suction tubes **2414**, **2416**. Outside air is pulled through the suction port **2406**, through the suction tubes **2414**, **2416**, and into the suction passageway **100** by a vacuum source as indicated by arrow **2408**. The suction in the distal portion **106** of the suction passageway **110** is thereby disabled. When the valve **2404** is rotated to a closed position (FIG. **24C**), the suction port **2406** is sealed and the distal portion **106** of the suction passageway **110** is put in communication with the vacuum source via suction tube **2414**. The suction in the suction passageway **110** is thereby enabled as indicated by arrows **2410**.

Variations, modifications, and other implementations of what is described herein may occur to those of ordinary skill in the art without departing from the spirit and scope of the invention. Accordingly, the invention is not to be defined only by the preceding illustrative description.

What is claimed is:

1. A medical device, comprising:

an elongated member configured to be disposed within a urinary tract of a patient, the elongated member defining a suction passageway along a longitudinal axis of the elongated member, the elongated member having a proximal portion and a distal portion, the proximal portion configured to be coupled to a vacuum source configured to provide suction through the suction passageway,

the distal portion of the elongated member having a tip, the tip including a side wall having an outer surface, a distal end surface, and an inner surface defining a portion of the suction passageway, the side wall between the inner surface and the outer surface being devoid of another lumen, the inner surface being gradually tapered such that an inner diameter of the tip is less than an inner diameter of a portion of the elongated member disposed proximally from the tip, the distal end surface of the side wall configured to contact a kidney stone and retain the kidney stone when the suction is provided through the suction passageway; and

a blocking member coupled to the tip such that a portion of the blocking member extends from the outer surface of the tip, the blocking member configured to contact a portion of the urinary tract of the patient, the blocking member being substantially rigid and having a distal end surface that is substantially co-planar with the distal end surface of the side wall.

2. The medical device of claim **1**, wherein a maximum outer diameter of the blocking member is greater than a maximum outer diameter of the tip.

3. The medical device of claim **1**, wherein the blocking member configured to prevent tissue proximate the kidney stone from entering the suction passageway when the suction is provided through the suction passageway.

4. The medical device of claim **1**, wherein at least a portion of the tip is disposed within a cavity defined by the blocking member.

5. The medical device of claim **1**, wherein the elongated member includes a reinforcement configured to help resist collapse of the suction passageway.

6. The medical device of claim **1**, wherein the elongated member includes a mesh reinforcement configured to help resist collapse of the suction passageway.

7. The medical device of claim **1**, wherein the elongated member includes a coil member.

8. A medical device, comprising:

an elongated member configured to be disposed within a urinary tract of a patient, the elongated member defining a suction passageway along a longitudinal axis of the elongated member, the elongated member having a proximal portion and a distal portion, the proximal portion configured to be coupled to a vacuum source to provide suction through the suction passageway,

the distal portion of the elongated member having a tip, the tip including a side wall having an outer surface and an inner surface defining a portion of the suction passageway, the side wall between the inner surface and the outer surface being devoid of another passageway, the inner surface being gradually tapered such that an inner diameter of the tip is less than an inner diameter of a portion of the elongated member disposed proximally from the tip, the distal end surface of the side wall configured to contact a kidney stone and retain the kidney stone when the suction is provided through the suction passageway; and

a concave member coupled to the tip, the concave member being substantially rigid, the concave member configured to prevent tissue proximate the kidney stone from entering the suction passageway when the suction is provided through the suction passageway, a maximum outer diameter of the concave member is greater than a maximum outer diameter of the tip, the concave member having a distal end surface substantially co-planar with the distal end surface of the side wall.

9. The medical device of claim **8**, wherein a portion of the concave member extends radially from the outer surface of the tip.

10. The medical device of claim **8**, wherein the elongated member includes a reinforcement configured to help resist collapse of the suction passageway.

11. The medical device of claim **8**, wherein the elongated member includes a mesh reinforcement configured to help resist collapse of the suction passageway.

12. The medical device of claim **8**, wherein the elongated member includes a coil member.

* * * * *

专利名称(译)	医疗装置		
公开(公告)号	US7883515	公开(公告)日	2011-02-08
申请号	US12/394407	申请日	2009-02-27
[标]申请(专利权)人(译)	KEAR JASONW		
申请(专利权)人(译)	KEAR JASONW		
当前申请(专利权)人(译)	BOSTON SCIENTIFIC SCIMED , INC.		
[标]发明人	KEAR JASON W		
发明人	KEAR, JASON W.		
IPC分类号	A61B17/22 A61B17/00 A61B17/30 A61B19/00		
CPC分类号	A61B17/22031 A61B19/54 A61B2017/00292 A61B2017/0046 A61B2017/306 A61B2017/308 A61B90/39		
其他公开文献	US20090198250A1		
外部链接	Espacenet USPTO		

摘要(译)

石头取回抽吸装置便于保持然后重新定位和/或移除设置在患者泌尿系统中的物体。该装置包括细长构件，用于放置在柔性输尿管镜的通道中。细长构件限定了抽吸通道，该抽吸通道纵向延伸穿过其中。细长构件足够柔韧以与柔性输尿管镜一起弯曲，并且当用真空源通过抽吸通道提供抽吸时，细长构件足够强以防止抽吸通道的塌陷。细长构件包括远端部分，用于在提供抽吸时接触和保持物体。

