



US008715299B2

(12) **United States Patent**
Menn et al.

(10) **Patent No.:** **US 8,715,299 B2**
(45) **Date of Patent:** **May 6, 2014**

(54) **HERMETIC ROTATING HANDLE ASSEMBLY FOR A SURGICAL CLIP APPLIER FOR LAPAROSCOPIC PROCEDURES**

(75) Inventors: **Pavel Menn**, Marblehead, MA (US);
Nathaniel Risler Rosso, Gloucester, MA (US)

5,772,673	A	6/1998	Cuny et al.
6,059,799	A	5/2000	Aranyi et al.
6,099,537	A	8/2000	Sugai et al.
2003/0040745	A1	2/2003	Frazier et al.
2006/0025811	A1	2/2006	Shelton, IV
2006/0079912	A1	4/2006	Whitfield
2007/0074762	A1	4/2007	Menn

(73) Assignee: **EndoDynamix, Inc.**, Salem, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 388 days.

FOREIGN PATENT DOCUMENTS

WO WO/2011/127223 10/2011

(21) Appl. No.: **13/081,480**

(22) Filed: **Apr. 6, 2011**

(65) **Prior Publication Data**

US 2011/0245847 A1 Oct. 6, 2011

Related U.S. Application Data

(60) Provisional application No. 61/321,237, filed on Apr. 6, 2010.

(51) **Int. Cl.**
A61B 17/10 (2006.01)

(52) **U.S. Cl.**
USPC **606/142**

(58) **Field of Classification Search**
USPC 606/139-149; 600/101-105; 623/1.11, 623/1.23

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,484,095	A	*	1/1996	Green et al.	227/181.1
5,499,992	A		3/1996	Meade et al.		

OTHER PUBLICATIONS

International Search Report for International Application No. PCT/US2011/031484, issued May 27, 2011 by the International Bureau of WIPO.

Written Opinion of the International Search Authority International Search Report for International Application No. PCT/US2011/031484, issued May 27, 2011 by WIPO.

International Preliminary Report on Patentability Chapter I for International Application No. PCT/US2011/031484, issued May 23, 2011 by WIPO.

* cited by examiner


Primary Examiner — Gregory Anderson

Assistant Examiner — Christina Lauer

(57) **ABSTRACT**

This invention provides hermetically-sealed handle assembly with a rotating trigger for use with disposable components, such as surgical clip appliers. The rotating trigger reduces the gripping force necessary to fully control the internal actuator mechanism to operate a disposable surgical clip applier to fully ligate a vessel or other tissue. The hermetic seal on the handle assembly prevents any patient fluids and other bio burden from entering the internal structures. This reduces the possibility of cross-contamination and the costs of sterilization.

7 Claims, 5 Drawing Sheets






FIG. 2




FIG. 3




FIG. 4




FIG. 5

**HERMETIC ROTATING HANDLE ASSEMBLY
FOR A SURGICAL CLIP APPLIER FOR
LAPAROSCOPIC PROCEDURES**

CROSS REFERENCE TO RELATED
APPLICATION

This application claims the benefit of U.S. Provisional Patent Application No. 61/321,237 filed on Apr. 6, 2010, the contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

This invention relates to a novel hermetic rotating handle assembly for a surgical clip applier for laparoscopic or endoscopic procedures.

BACKGROUND OF INVENTION

Laparoscopic and endoscopic surgical procedures are conducted through a small incision in the skin or natural body orifices. In order to operate, surgeons must use instruments that have a small enough cross section to fit within these small openings and long enough to reach the surgical area within the body.

Surgical instruments designed for these procedures are often separated into two components to reduce costs and minimize cross contamination.

The first component is a long and narrow disposable portion that is inserted into the small opening during surgery. These disposable components contain surgical tools, such as surgical jaws or surgical clip appliers, dissectors or other instruments, on the end which enters the patient. These disposable components also contain small actuators which control the operation of the surgical tools within the patient.

These small actuators on the first component are operatively attached to the second component of these surgical instruments. The second component is a non-disposable control unit for moving the long disposable component within the patient and operating the actuators to control the surgical tools on the disposable component. The second component is often a handle with a trigger. A surgeon may control the movement and placement of the disposable component by holding the handle and operate the small actuators by squeezing the trigger. For instance, a surgeon may squeeze the trigger to place a surgical clip over a vessel.

By separating these two components, the risk of cross contamination between separate patients or separate tissues on the same patient is reduced. The non-disposable control unit does not enter the patient and the contaminated long and narrow component is simply disposed after each surgical procedure is completed. In addition, costs are saved since medical providers only need to replace the disposable component between surgical procedures.

However, one the problems with currently existing surgical instruments used in these procedures is the possible contamination of the non-disposable control unit. This non-disposable component may still contact patient fluids during surgeries and become contaminated. This may be especially problematic for handle and trigger assemblies. In order for a trigger to be squeezed and moveable, these assemblies have openings to their internal structures.

One solution to this problem is for medical providers to autoclave and sterilize each non-disposable component after each surgical procedure. However, the time needed to autoclave and sterilize these non-disposable handle and trigger assemblies is significantly high due to the need to sterilize the

internal structures. This sterilization increases maintenance costs for medical providers. Current surgical clip appliers include many disposable handles since they cannot be sterilized effectively, even with hours in an autoclave.

According, the subject invention is a non-disposable hermetically-sealed handle assembly with a rotating trigger for use with disposable components, such as surgical clip appliers. The hermetic seal on the handle assembly prevents any patient fluids and other bioburden from entering the internal structures. This reduces the possibility of cross-contamination and the costs of sterilization.

SUMMARY OF THE INVENTION

There are additional features of the invention that will be described hereinafter and which will form the subject matter of the claims appended hereto. In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein are for the purpose of the description and should not be regarded as limiting.

The subject invention discloses an endoscopic surgical tool comprising, a housing comprising an upper portion and a handle; an actuating mechanism contained within the housing along a first axis, wherein the actuating mechanism is adapted to operatively couple to a disposable external shaft that extends away from the housing along a first shaft axis from a proximal end to a distal end, wherein the first axis and the first shaft axis are substantially parallel; a lever coupled at a proximal end to the actuating mechanism and extending in a downward direction, wherein the lever is pivotably coupled at a distal end to an internal shaft that extends along a second shaft axis that is substantially perpendicular to the first shaft axis; a first end of the internal shaft extending through a first opening in the housing proximate to the top of the handle, and further extending through a central opening of a first disc spring; a second end of the internal shaft extending through a second opening in the housing proximate to the top of the handle, and further extending through a central opening of a second disc spring, wherein the first opening and the second opening are substantially parallel with each other; a first trigger shaft comprising a first substantially semi-spherical top portion coupled to the first end of the internal shaft after extending through the first disc spring, wherein the first trigger shaft further comprises a first substantially half-cylindrical lower portion with a first substantially flat surface, wherein the first disc spring provides a first seal about the first end of the internal shaft by providing a first compressive force on the first substantially semi-spherical top portion of the first trigger shaft and an opposing second compressive force on the exterior surface about the first opening in the housing; a second trigger shaft comprising a second substantially semi-spherical top portion coupled to the second end of the internal shaft after extending through the second disc spring, wherein the second trigger shaft further comprises a second substantially half-cylindrical lower portion with a second substantially flat surface, wherein the second disc spring provides a second seal about the second end of the internal shaft by providing a third compressive force on the second substantially semi-spherical top portion of the second trigger shaft and an opposing fourth compressive force on the exterior surface about the second opening in the housing, wherein the

first and second substantially flat surface of the first and second trigger shafts couple to form a substantially cylindrical lower trigger shaft defining a longitudinal axis; a hollow substantially cylindrical trigger grip coupled over the cylindrical lower trigger shaft; wherein application of compressive force to the trigger grip towards the handle rotates the cylindrical lower trigger shaft about the longitudinal axis in a first direction to rotate the first and second ends of the internal shaft in a direction away from the second shaft axis, wherein rotation of the internal shaft pivots the coupled lever to operate the actuating mechanism.

In another embodiment of the subject invention, the first and second trigger shafts comprise complementary configurations.

In another embodiment of the subject invention, the external shaft comprises a cartridge containing surgical clips.

In another embodiment of the subject invention, the distal end of the external shaft is adapted to receive an end effector.

In another embodiment of the subject invention, the end effector comprises a distally attached surgical jaws assembly.

In another embodiment of the subject invention, the first and second disc springs comprise conical spring washers.

In another embodiment of the subject invention, the housing is non-disposable.

In another embodiment of the subject invention, the cylindrical lower trigger shaft rotates about the longitudinal axis in a second direction, opposite the first direction, when the trigger is released.

In another embodiment of the subject invention, the housing comprises a single piece.

In another embodiment of the subject invention, the housing comprises two coupled pieces with complementary configurations.

The subject invention also discloses a hermetically sealed handle assembly for a surgical clip applier comprising: a housing comprising an upper portion and a lower handle; an actuating mechanism contained within the upper portion of the housing that controls a disposable cartridge containing surgical clips; a shaft extending from the housing containing rotating means so as to permit rotation of the shaft about an axis that extends substantially longitudinally through the shaft, wherein the shaft rotates in a first direction about an axis that extends substantially longitudinally through the shaft when a gripping force is applied to the shaft, and further wherein the actuating mechanism within the housing is coupled to the shaft such that rotation of the shaft operates the actuating mechanism.

There has thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the invention that will be described hereinafter and which will form the subject matter of the claims appended hereto. These together with other objects of the invention, along with the various features of novelty, which characterize the invention, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of the present invention will be apparent from the following detailed description of embodiments thereof, which description should be considered in conjunction with the accompanying drawings, in which:

FIG. 1 illustrates an exploded view of a hermetically-sealed rotating trigger and handle assembly for a clip applier.

FIG. 2 illustrates a front view of the hermetically-sealed rotating trigger and handle assembly.

FIG. 3 illustrates a side cross-sectional view of the hermetically-sealed rotating trigger and handle assembly along line "A" of FIG. 2.

FIG. 4 illustrates a cross-sectional front internal view of the hermetically-sealed rotating trigger and handle assembly.

FIG. 5 illustrates a side view of the hermetically-sealed rotating trigger and handle assembly.

DETAILED DESCRIPTION OF THE EMBODIMENTS

While several variations of the present invention have been illustrated by way of example in particular embodiments, it is apparent that further embodiments could be developed within the spirit and scope of the present invention, or the inventive concept thereof. However, it is to be expressly understood that such modifications and adaptations are within the spirit and scope of the present invention, and are inclusive, but not limited to the following appended claims as set forth.

FIGS. 1-5 illustrate a hermetically-sealed handle and trigger assembly 101 with a handle 102 and a rotating trigger 103 for a surgical clip applier (not shown). FIG. 3 illustrates a side cross-sectional view of the handle and trigger assembly 101 as shown by lines "A" of FIG. 2. The hermetic seal on the handle and trigger assembly 101 prevents any patient fluids from entering the internal structures. This reduces the possibility of cross-contamination and the costs of sterilization, which allows the handle and trigger assembly 101 to be non-disposable.

The rotating trigger 103 rotates in a first direction that is substantially perpendicular to the length of the trigger 103 when squeezed in a direction towards handle 102. The rotating trigger 103 rotates in a second direction, opposite the first direction, when released and moving away from handle 102.

The elements of the handle and trigger assembly 101 include an external housing 107 that is formed by a hollow left half section 305 and a hollow right half section 306. Hollow left half section 305 and hollow right half section 306 are complementarily shaped to each other. The housing 107 may be made of a polycarbonate, ABS, stainless steel or other suitable material known to those skilled in the art. The separate half sections 305 and 306 may be attached together by adhesives, fasteners, welding, or other attachment means known to those skilled in the art.

Left half section 305 has an upper left housing 305a, a lower left half-handle housing 305b and a hollow left hinge housing 305c. Hollow left hinge housing 305c has a traversing left opening 305d.

Right half section 306 has an upper right housing 306a, a lower right half-handle housing 306b, and a hollow right hinge housing 306c. Hollow right hinge housing 306c has a traversing right opening 306d.

An actuator mechanism 104 is contained within upper left housing 305a and upper right housing 306a. Once the left half section 305 and the right half section are connected to form the external housing 107, the upper left housing 305a and the upper right housing 306a form housing opening 106. This opening 106 contains the actuator mechanism 104 and allows it to control the disposable cartridge containing surgical clips and a plurality of distal end effectors. The internal actuator mechanism 104 of the subject invention may be any mechanism, known to those skilled in the art, which operates a cartridge containing surgical clips and a distal end effector that is controllable with pivotable lever 105.

A pivotable lever **105** has a top end **105a** and a bottom end **105b**. The top end **105a** of lever **105** is operatively connected to actuator mechanism **104**. Trigger shaft **310** is substantially perpendicular to lever **105**. The top end **105a** of lever **105** may pivot about the pivot point of bottom end **105b** by rotating around the axis of trigger shaft **310**.

Trigger shaft **310** has a left end **310a** and a right end **310b**. Trigger shaft bearings **309** are placed over left end **310a** and right end **310b**.

Left end **310a** passes through left opening **305d** of left hinge housing **305** and then passes through a spring seal washer **311**. A left hinge element of the trigger **304** has an upper semi-spherical portion **304a** with an indentation **304b** that houses the spring seal washer **311**. After passing through spring seal washer **311**, left end **310a** of trigger shaft **310** attaches within indentation **304b** of the left hinge element of the trigger **304**.

Right end **310b** passes through left opening **306d** of right hinge housing **306** and then passes through a spring seal washer **311**. A right hinge element of the trigger **303** has an upper semi-spherical portion **303a** with an indentation **303b**. After passing through spring seal washer **311**, right end **310b** of trigger shaft **310** attaches within indentation **303b** of the right hinge element of the trigger **303**.

Right hinge element of the trigger **303** has a lower trigger spine **303c** attached to upper semi-spherical portion **303a**. Lower trigger spine **303c** has a half-cylindrical shape with a substantially flat face **303d**.

Left hinge element of the trigger **304** has a middle trigger spine **304c** attached to upper semi-spherical portion **304a**. The upper section of middle trigger spine **304c**, proximate to semi-spherical portion **304a**, has a half-cylindrical shape with a substantially flat face **304d**. The lower section of middle trigger spine **304c**, distal to semi-spherical portion **304a**, has a substantially cylindrical shape. Left hinge element of the trigger **304** also has a lower substantially cylindrical trigger spine **304e** attached to middle trigger spine **304c**.

As left end **310a** attaches within indentation **304b** and right end **310b** attaches within indentation **303b**, substantially flat face **303d** is attached to the opposing substantially flat face **304d** above the lower section of middle trigger spine **304c**. Once joined, flat faces **303d** and **304d** form a substantially cylindrical shape that is substantially equivalent in diameter to the lower section of middle trigger spine **304c**. The right hinge element of the trigger **303** is torsionally fixed to the right end **310b** of trigger shaft **310**. The left hinge element of the trigger **304** is torsionally fixed to the left end **310a** of trigger shaft **310**.

A hollow substantially cylindrical trigger grip **301** has a top opening **301a** and a bottom opening **301b**. The trigger grip **301** is placed over the connected right hinge element **303** and left hinge element **304** through top opening **301a**. The lower trigger spine **304e** of left hinge element of the trigger **304** passes through bottom opening **301b**, a bushing **307**, a retaining ring **308** and is attached to an end cap **302**.

FIG. 5 illustrates the rotating trigger in the resting position **103a** and the squeezed position **103b**. When a user applies gripping force to the trigger grip **301** by squeezing rotating trigger **103**, the trigger grip **301**, the lower trigger spine **303c**, and the middle trigger spine **304c** all begin to rotate about the axis of trigger shaft **310** in either a clockwise or counterclockwise direction. As trigger spine **304c** begins to rotate, the left end **310a** of trigger shaft **310** also begins to rotate in the same direction. Concurrently, as trigger spine **303c** begins to rotate, the right end **310b** of trigger shaft **310** also begins to rotate in the same direction. The rotation of trigger shaft **310** causes the top end **105a** of lever **105** to begin to pivot about the about the

pivot point of bottom end **105b** by rotating around trigger shaft **310**. The pivoting of top end **105a** operates actuator mechanism **104** which controls the surgical clip applier distal end effector (not shown). Thus, application of gripping force to the trigger **103** operates the surgical clip applier.

Once a user releases the trigger grip **301**, the trigger grip **301**, the lower trigger spine **303c**, and the middle trigger spine **304c** all begin to rotate about the axis of trigger shaft **310** in the opposite clockwise or counterclockwise direction. The trigger shaft **310** rotating in an opposite direction causes the top end **105a** of lever **105** to begin to pivot in an opposite direction about the about the pivot point of bottom end **105b** by rotating around trigger shaft **310**. The opposite pivoting of top end **105a** releases the actuator mechanism **104** which controls the surgical clip applier distal end effector (not shown). Thus, release of gripping force to the trigger **103** stops the operation of the surgical clip applier.

The rotating trigger **103** reduces the gripping force necessary to fully pivot lever **105** to operate actuator mechanism **104** to operate a disposable surgical clip applier (not shown) to fully ligate a vessel or other tissue. In one embodiment of the subject application the gripping force required to fully actuate for full ligation is reduced from 25 lbs to 5 lbs.

The trigger assembly **101** and the rotating trigger **103** remain hermetically sealed in the resting **103a** and squeezed **103b** positions. A spring seal washer **311** around the left end **310a** of trigger shaft **310** provides a compressive force against semi-spherical portion **304a** and an opposing compressive force against housings **305a** and **305c**. Another spring seal washer **311** around the right end **310b** of trigger shaft **310** provides a compressive force against semi-spherical portion **303a** and an opposing compressive force against housings **306a** and **306c**. These opposing compressive forces on both sides and surrounding trigger shaft **310** provide an air seal between trigger **103** and housing **107**. This air seal is maintained during rotation of trigger **103** from the resting **103a** to squeezed position **103b**.

Handle and trigger assembly **101** does not require a change of the trigger body volume inside the handle when the trigger **103** is gripped or released. This allows the handle and trigger assembly **101** to contain a completely air tight seal, making the assembly **101** infinitely reusable while reducing sterilization time. This also minimizes autoclave ineffectiveness and the possibility of cross contamination from patient to patient.

In embodiments of the subject invention, the washer seals **311**, the bushing **307**, the retaining ring **308** and the trigger shaft bearings **309** may be composed of titanium, plastic, steel or any combination thereof. In another embodiment of the subject invention, the washer seals **311**, the bushing **307**, the retaining ring **308** and the trigger shaft bearings **309** may all be composed of a unitary construction.

What is claimed is:

1. An endoscopic surgical tool comprising,
 - a housing comprising an upper portion and a handle, the handle having a top and a bottom, the top of the handle coupled to the upper portion of the housing;
 - an actuating mechanism disposed in the housing along a first axis, the actuating mechanism having a first shaft axis extending from a proximal end to a distal end, wherein the first axis and the first shaft axis are substantially parallel;
 - a lever coupled at a proximal end to the actuating mechanism and extending in a downward direction, wherein the lever is pivotably coupled at a distal end to a trigger shaft that extends along a second shaft axis that is substantially perpendicular to the first shaft axis;

7

a first end of the trigger shaft extending through a first opening in the housing proximate to the top of the handle, and further extending through a central opening of a first disc spring;

a second end of the trigger shaft extending through a second opening in the housing proximate to the top of the handle, and further extending through a central opening of a second disc spring, wherein the first opening and the second opening are substantially parallel with each other;

a first hinge element comprising a first substantially semi-spherical top portion coupled to the first end of the trigger shaft after extending through the first disc spring, wherein the first hinge element further comprises a first substantially half cylindrical lower portion with a first substantially flat surface, wherein the first disc spring provides a first seal about the first end of the trigger shaft by providing a first compressive force on the first substantially semi-spherical top portion of the first hinge element and an opposing second compressive force on the exterior surface about the first opening in the housing;

a second hinge element comprising a second substantially semi-spherical top portion coupled to the second end of the trigger shaft after extending through the second disc spring, wherein the second hinge element further comprises a second substantially half-cylindrical lower portion with a second substantially flat surface, wherein the second disc spring provides a second seal about the second end of the trigger shaft by providing a third compressive force on the second substantially semi-spherical top portion of the second hinge element and an

8

opposing fourth compressive force on the exterior surface about the second opening in the housing, wherein the first and second substantially flat surface of the first and second hinge elements couple to form a substantially cylindrical trigger defining a longitudinal axis;

a hollow substantially cylindrical trigger grip coupled over the cylindrical trigger;

wherein application of compressive force to the trigger grip towards the handle rotates the cylindrical trigger about the longitudinal axis in a first direction to rotate the first and second ends of the trigger shaft in a direction away from the second shaft axis, wherein rotation of the trigger shaft pivots the coupled lever to operate the actuating mechanism.

2. The endoscopic surgical tool of claim 1, wherein the first and second hinge elements comprise complementary configurations.

3. The endoscopic surgical tool of claim 1, wherein the first and second disc springs comprise conical spring washers.

4. The endoscopic surgical tool of claim 1, wherein the housing is nondisposable.

5. The endoscopic surgical tool of claim 1, wherein the cylindrical trigger rotates about the longitudinal axis in a second direction, opposite the first direction, when the cylindrical trigger is released.

6. The endoscopic surgical tool of claim 1, wherein the housing comprises a single piece.

7. The endoscopic surgical tool of claim 1, wherein the housing comprises two coupled pieces with complementary configurations.

* * * * *

专利名称(译)	用于腹腔镜手术的手术施夹器的密封旋转手柄组件		
公开(公告)号	US8715299	公开(公告)日	2014-05-06
申请号	US13/081480	申请日	2011-04-06
[标]申请(专利权)人(译)	梅恩PAVEL ROSSO NATHANIEL RISLER		
申请(专利权)人(译)	梅恩PAVEL ROSSO NATHANIEL RISLER		
当前申请(专利权)人(译)	ENDODYNAMIX INC.		
[标]发明人	MENN PAVEL ROSSO NATHANIEL RISLER		
发明人	MENN, PAVEL ROSSO, NATHANIEL RISLER		
IPC分类号	A61B17/10		
CPC分类号	A61B2017/0046 A61B17/2909 A61B17/1285 A61B2019/4868 A61B17/105 A61B17/00234 A61B90/08 A61B2017/00477 A61B2017/2925 A61B2090/0813		
审查员(译)	ANDERSON , GREGORY		
优先权	61/321237 2010-04-06 US		
其他公开文献	US20110245847A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供了一种带有旋转触发器的气密密封手柄组件，用于一次性部件，例如手术施夹器。旋转触发器减小了完全控制内部致动器机构以操作一次性手术施夹器以完全结扎血管或其他组织所需的夹持力。手柄组件上的气密密封防止任何患者流体和其他生物负载进入内部结构。这降低了交叉污染的可能性和灭菌成本。

