



US 20150265294A1

(19) **United States**

(12) **Patent Application Publication**
HONDA et al.

(10) **Pub. No.: US 2015/0265294 A1**

(43) **Pub. Date: Sep. 24, 2015**

(54) **CALCULUS RETRIEVING/REMOVING
DEVICE AND METHOD**

(52) **U.S. Cl.**

CPC *A61B 17/22* (2013.01); *A61B 17/2202*
(2013.01); *A61B 2017/22067* (2013.01); *A61B*
2017/22082 (2013.01)

(71) Applicant: **TERUMO KABUSHIKI KAISHA,**
Shibuya-ku (JP)

(57) **ABSTRACT**

(72) Inventors: **Kei HONDA,** Kanagawa (JP); **Wataru
KARINO,** Kanagawa (JP)

A method of removing/retrieving calculus in a ureteral lumen involves moving a ureteral plug part along the ureter lumen to position the ureteral plug part between the calculus and the kidney. The method additionally includes occluding the ureteral lumen at a location at which the ureteral plug part is located, and introducing fluid into the ureter lumen at a point between the location of the occlusion and the calculus so that the fluid washes the calculus toward the bladder. Another aspect involves a method in which an drainage tube is positioned in the ureteral lumen so that a ureteral plug part and an irrigation port are positioned distally of the calculus while an operation part of the drainage tube is positioned proximally of the calculus. The method includes occluding the ureteral lumen, washing the ureteral lumen, and releasing the occlusion and uncoupling the operation part from the ureteral plug.


(73) Assignee: **TERUMO KABUSHIKI KAISHA,**
Shibuya-ku (JP)

(21) Appl. No.: **14/221,954**

(22) Filed: **Mar. 21, 2014**

Publication Classification

(51) **Int. Cl.**
A61B 17/22 (2006.01)






FIG. 1








FIG. 2






FIG. 9






FIG. 7






FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15A




FIG. 15B




FIG. 16




FIG. 18





FIG. 19






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25A




FIG. 25B




FIG. 25C




FIG. 26




FIG. 27

CALCULUS RETRIEVING/REMOVING DEVICE AND METHOD

TECHNICAL FIELD

[0001] The present invention generally pertains to methods and systems for retrieving/removing a mass from a human body. More specifically, the invention involves methods and systems for retrieving/removing calculus (e.g., stones) from a portion of a human body such as the renal pelvis or the ureter.

BACKGROUND DISCUSSION

[0002] The term urinary calculus (e.g., kidney stones and ureteral stones) refers to masses or stones, typically solid particles, that form in the human body and are located in the kidneys and/or the ureter. They can exhibit a variety of chemical compositions including calcium oxalate, calcium phosphate, uric acid, cystine, and struvite.

[0003] Stone disease (e.g., kidney stones and ureteral stones) is a relatively common urological disorder. The presence of calculus in the body can manifest itself in a variety of ways and can produce a number of medical ailments. For example, the presence of calculus in the renal pelvis (kidney) can cause blood in the urine, urinary obstruction, infection, and various degrees of pain ranging from vague flank pain to much more severe pain not capable of being relieved through general pain medication. The presence of stones or calculus in the ureter can result in relatively severe side and back pain, pain below the ribs, and pain that sometimes spreads to the lower abdomen and groin, as well as pain during urination and hematuria.

[0004] Fortunately, many calculus or stones pass out of the body without requiring any specific medical intervention. In those situations where the calculus does not naturally pass out of the body, a medical procedure may be required. Known medical procedures typically fall into three categories.

[0005] In the past, three main treatments have been used to address calculus or kidney stones. These include shock wave lithotripsy (ESWL), transurethral lithotripsy or ureteroscopy (URS), and percutaneous nephrouretero lithotripsy (PCNL) which is sometimes also referred to as percutaneous nephrolithotomy (PCN).

[0006] Shock wave lithotripsy is performed as an extracorporeal treatment. This treatment utilizes a machine called a lithotripter that operates by directing ultrasonic or shock waves from outside the body, through the skin and tissue, and at the calculus or stones. Repeated shock waves apply stress to the stones, eventually breaking the individual stones into smaller pieces which can more easily pass through the urinary tract in urine. One benefit associated with shock wave lithotripsy is that it is a rather simple procedure. But it has been found that there is a relatively high rate of kidney stone recurrence following shock wave lithotripsy.

[0007] Transurethral lithotripsy or ureteroscopy represents one such alternative form of treatment. This treatment involves the use of small fiber optic instrument called a ureteroscope which allows access to the calculus in the ureter or kidney. The ureteroscope can be a rigid ureteroscope or more commonly, a flexible ureteroscope. The ureteroscope allows the medical professional to visualize the stone as the ureteroscope moves along the ureter or enters the kidney by way of the bladder and the urethra. Once the calculus is visualized, a basket-like device is used to grasp smaller stones and remove

them. If the calculus is excessively large to remove as a single piece, it can be broken into a smaller pieces by using laser energy.

[0008] The third form of treatment is percutaneous nephrolithotomy. This procedure is often used with relatively larger calculus that cannot be effectively treated with either ESWL or URS. Percutaneous nephrolithotomy involves nephrostomy; making an incision at the appropriate location, needling by paracentesis needle, positioning a guide wire through the paracentesis needle's lumen into the kidney under radiographic guidance, and then expanding perforated site. A nephroscope is then moved into the kidney via nephrostomy to visualize the calculus. Fragmentation of the calculus can be performed using an ultrasonic probe or laser.

[0009] Though these procedures have been commonly used, they are susceptible of certain short comings. For example, the ESWL procedure results in a relative large number of small calculus or small stones, while other procedures require a relatively narrow and long access route or are difficult to implement due to the inability to accurately capture the stones. In addition to, many crush pieces should be removed one by one in URS and PCNL procedure. The procedure time can also be excessively long, and can result in a relatively low "stone free rate." The recurrence rate can also be unacceptably high. And the potential patient complications (e.g., ischemia of the ureter, obstruction of ureter, back-flow and/or high-stress to the renal pelvis, infection of the urinary tract, and other possible injury) can be undesirably high.

SUMMARY

[0010] According to one aspect, a method for removing a calculus located in a lumen of a ureter involves moving a ureteral plug part of an elongated member in the lumen of the ureter toward the calculus located in the lumen of the ureter and past the calculus so that the ureteral plug part is positioned beyond the calculus. The ureteral plug part is positioned at the distal end portion of the elongated member, and the elongated member also includes at least one irrigation port positioned between the ureteral plug part and a proximal end portion of the elongated member, with the ureteral plug part being sized so that the outer surface of the ureteral plug part is spaced from the inner surface of the lumen in the ureter. The method additionally involves occluding the lumen in the ureter while the ureteral plug part is positioned beyond the calculus, washing away the calculus in the ureter in a direction away from the ureteral plug part by discharging fluid from the irrigation port into the lumen and toward the calculus, releasing the occlusion of the lumen in the ureter, and withdrawing the elongated member, inclusive of the ureteral plug part lumen in the ureter, from the lumen of the ureter.

[0011] According to another aspect, a method for removing a calculus located in a lumen of a ureter comprises positioning an elongated drainage tube in the lumen of the ureter, with the elongated drainage tube including an irrigation port and an operation part, and the elongated drainage tube being positioned in the ureter so that the ureteral plug part and the irrigation port are positioned distally of the calculus while the operation part of the elongated drainage tube is positioned proximally of the calculus. The method also involves occluding the lumen in the ureter, washing the ureteral lumen by discharging fluid from the irrigation port toward the calculus, and releasing the occlusion of the lumen of the ureter and uncoupling the operation part from the ureteral plug.

[0012] In accordance with a further aspect, a method for removing a calculus located in a lumen of a ureter includes moving a ureteral plug part along the lumen in the ureter, wherein the ureter is connected at one end to a kidney and at an opposite end to a bladder, and wherein the ureteral plug part is moved in the lumen of the ureter from the bladder toward the kidney so that the ureteral plug part is moved to a position between the calculus and the kidney. The method additionally involves occluding the lumen of the ureter at a location in the lumen at which the ureteral plug part is located, introducing fluid into the lumen of the ureter between the location of the occlusion and the calculus so that the fluid washes the calculus toward the bladder, and releasing the occlusion of the lumen in the ureter.

[0013] Other features and aspects of the calculus retrieving/removing device and method disclosed here will become more apparent from the following detailed description considered with reference to the accompanying drawing figures in which like elements are designated by like reference numerals.

BRIEF DESCRIPTION OF DRAWINGS

[0014] FIG. 1 is a schematic illustration of a portion of the human anatomy, including the urinary tract.

[0015] FIG. 2 is a schematic cross-sectional view of a kidney.

[0016] FIG. 3 is a longitudinal cross-sectional view of a calculus removing/retrieving device representing one example of the device disclosed here used to carry out an aspect of the disclosed method.

[0017] FIG. 4 is a cross-sectional view of a check valve used in the calculus removing/retrieving device shown in FIG. 3.

[0018] FIG. 5 is a cross-sectional view of the check valve shown in FIG. 4, with the distal portion of a syringe moving the check valve to the open position.

[0019] FIG. 6 is a perspective view of the end portion of the rubber plug used in the check valve shown in FIGS. 4 and 5.

[0020] FIG. 7 is a schematic illustration of the calculus removing/retrieving device shown in FIG. 3 positioned in the lumen of a ureter (ureteral lumen).

[0021] FIG. 8 is a schematic illustration of the calculus removing/retrieving device shown in FIG. 7 positioned in the ureteral lumen while being guided by a guide wire under observation with an ureteroscope.

[0022] FIG. 9 is a schematic illustration of the calculus removing/retrieving device used with an ureteroscope.

[0023] FIG. 10 is a schematic illustration of another embodiment of the calculus removing/retrieving device disclosed here by way of example and positioned in a ureteral lumen.

[0024] FIG. 11 illustrates the calculus removing/retrieving device shown in FIG. 10 after separation of a proximal end portion to result in a ureteral stent.

[0025] FIG. 12 is a schematic illustration of the elongated member shown in FIG. 11 serving as a ureteral stent extending between the kidney and the bladder.

[0026] FIG. 13 is a schematic illustration of another embodiment of the calculus removing/retrieving device disclosed here by way of example and positioned in a ureteral lumen.

[0027] FIG. 14 illustrates the calculus removing/retrieving device shown in FIG. 13 depicting a different operational aspect of the device.

[0028] FIG. 15A is a schematic illustration of another embodiment of the elongated member disclosed here by way of example that includes an aspiration part.

[0029] FIG. 15B is a schematic illustration of the elongated member shown in FIG. 15A aspirating a ureteral lumen.

[0030] FIG. 16 is a schematic illustration of another embodiment of the elongated member disclosed here by way of example, wherein the calculus removing/retrieving device is specifically configured for use in the renal pelvis.

[0031] FIG. 17 is a schematic illustration of the elongated member shown in FIG. 16 positioned in a renal pelvis.

[0032] FIG. 18 is a schematic illustration of a renal pelvis illustrating an aspect of the method in which calculus in one portion of the renal pelvis are moved to another portion of the renal pelvis.

[0033] FIG. 19 is a schematic illustration of the calculus removing/retrieving device shown in FIG. 16 positioned in the renal pelvis after the calculus has been moved from the one portion of the renal pelvis to the other portion of the renal pelvis.

[0034] FIG. 20 is a schematic illustration of the procedure that the volume of “pulling back the ureteroscope” and “additional pouring irrigation water” is continuously adjusted to be equal (i.e., the same) to avoid a rise or increase in the intrarenal pressure.

[0035] FIG. 21 is a schematic cross-sectional view of a calculus removing/retrieving device according to a further embodiment disclosed here by way of example, wherein the calculus removing/retrieving device has particular application for use in a renal pelvis.

[0036] FIG. 22 is a schematic illustration of the calculus removing/retrieving device shown in FIG. 21 depicting a different operational aspect of the device.

[0037] FIG. 23 is a schematic illustration of the calculus removing/retrieving device shown in FIGS. 21 and 22, depicting the convection produced during operation of the device.

[0038] FIG. 24 illustrates the calculus removing/retrieving device shown in FIGS. 21 and 22 positioned in a renal pelvis and producing convection.

[0039] FIGS. 25A-25C are illustrations of a rubber seal check valve that can be used as an example of the check valve for the calculus removing/retrieving device shown in FIGS. 21 and 22.

[0040] FIG. 26 illustrates duck bill-type check valves that can be used as an example of the check valve for the calculus removing/retrieving device shown in FIGS. 21 and 22.

[0041] FIG. 27 is an illustration of an impeller.

DETAILED DESCRIPTION

[0042] Before discussing details and aspects of the methods and calculus removing/retrieving device described here as examples of the invention disclosed here, reference is made to FIGS. 1 and 2 to describe anatomical aspects of relevant aspects of a human body, including the urinary tract. Referring first to FIG. 1, the urinary tract includes the kidney 200, the bladder 202 and the ureter 204. The ureter 204 extends between and is connected to both the kidney 200 and the bladder 202. The ureter 204 possesses a lumen (ureteral lumen) that communicates with the interior of the kidney 200 and the interior of the bladder 202. The terminal end portion of the ureter penetrates through the muscle wall of bladder, and opens into the inside of the bladder at the ureteral orifice. Additional features illustrated in FIG. 1 include the physiological stricture of the ureter 204, the ureteropelvic junction

(UPJ) 208, the iliac artery crossing 210 and the ureterovesical junction (ureter bladder junction (UBJ)) 212.

[0043] FIG. 2 illustrates additional details associated with the kidney 200. The identified parts of the kidney in FIG. 2 include the renal pelvis 220, the renal vein 222, the renal artery 224, several of the minor calyces 226, one of the major calyx 228, the cortex 230, the capsule 232, the papilla of medulla 234 and the medulla (pyramids) 236.

[0044] The methods and devices disclosed here for removing/retrieving calculus have particularly useful application to address calculus located in the ureter 204 (ureter stones) and calculus located in the renal pelvis 220 (kidney stones).

[0045] A first embodiment of the calculus removing/retrieving device disclosed here is illustrated in FIG. 3. The calculus removing/retrieving device 30 includes an elongated member 31 having a ureter plug part 32 and an irrigation port or irrigation nozzle 34. The ureter plug part 32 is configured to be expanded to a relatively larger size as shown in FIG. 3 and contracted to a relatively smaller size. The ureter plug part 32 is thus configured to be enlarged and reduced in size. In the illustrated embodiment disclosed by way of example, the ureter plug part 32 is an inflatable balloon. The ureter plug part 32 is expanded by introducing a fluid into the interior of the ureter plug part 32, and the ureter plug part 32 is contracted by allowing the fluid to empty from the ureter plug part 32. The fluid can be water, air, contrast medium, etc.

[0046] Fluid is introduced into the ureter plug part 32 and is expelled from the ureter plug part 32 by way of a ureter plug part lumen 38. One end of the ureter plug part lumen 38 opens to the interior of the ureter plug part 32 and the opposite end of the ureter plug part lumen 38 is provided with a check valve 40. The check valve 40 can be of any known construction. One example is illustrated in FIG. 4.

[0047] The check valve in FIG. 4 includes a movable rubber plug 42 and a spring 44, both of which are positioned in, and enclosed within, a housing 46. The housing 46 includes an open end 49 at one end (the right end in FIGS. 4 and 5) and a closed end (equipped with a through hole) at the opposite end (the left end in FIGS. 4 and 5). The spring 44 normally biases the rubber plug 42 in the direction of the open end 49 and into sealing engagement with the valve seat 48 of the housing 46. FIG. 4 illustrates the normally closed position of the check valve 40 in which the rubber plug 42 is in sealing engagement with the valve seat 48 of the housing 46. The check valve 40 is configured to be opened by moving the rubber plug 42 against the biasing force of the spring 44 (i.e., to the left in FIGS. 4 and 5). In the illustrated embodiment, this is accomplished by inserting the tip end portion of a syringe 50 into the open end 49 of the housing 46. Inserting the tip end portion of the syringe 50 into the open end 49 of the housing 46 causes the tip end of the syringe 50 to contact the rubber plug 42. Pushing the syringe 50 further inward overcomes the biasing force of the spring 44 and urges the rubber plug 42 out of engagement with valve seat 48. This thus opens the check valve 40. Next, by forwardly moving the plunger 52 within the barrel of the syringe, air in the barrel of the syringe is introduced into the ureter plug part lumen 38 to thus inflate or expand the ureter plug part 32.

[0048] FIG. 6 illustrates the end portion of the rubber plug 42 that faces and is contacted by the tip end of the syringe 50. As illustrated, the end portion of the rubber plug 42 possesses a forked configuration in which the center region is cut-out (i.e., a U-shaped cut-out). This allows the fluid inside the barrel of the syringe 50 to be discharged from the tip end of

the syringe when the tip end of the syringe is in contact with the rubber plug 42. After an appropriate amount of fluid is introduced into the ureter plug part 32 to expand or inflate the ureter plug part 32, the syringe 50 can be disengaged from the check valve 40. At such time, the spring 44 biases the rubber plug 42 back into engagement with the valve seat 48 to close the check valve 40. The ureter plug part 32 thus remains in the expanded or inflated state. Naturally, the ureter plug part 32 can be contracted by the reverse method to that described above.

[0049] The irrigation lumen 36 is connected to a fluid source 60. The fluid source 60 is preferably a liquid, more preferably saline. In a more preferable example, the cross-sectional area of the irrigation lumen 36 is larger than the cross-sectional area of the ureter plug part lumen 38, because efficient irrigation needs a relatively high flow rate, but efficient inflation does not require such a high flow rate.

[0050] FIG. 7 is an illustration of the calculus removing/retrieving device 30 positioned in the lumen 205 of the ureter 204. In use, the calculus removing/retrieving device 30 is introduced into the ureteral lumen 205 by way of the bladder and the urethra. That is, with the ureteral plug part 32 in the contracted or deflated condition, the tip end of the calculus removing/retrieving device 30 is introduced into the urethra, is advanced through the bladder 202 and is moved along the ureter 204. The calculus removing/retrieving device 30 is moved in the forward direction in the ureter 204 to position the ureteral plug part 32 at a position beyond the calculus or stone(s) 300 to be removed. That is, the calculus removing/retrieving device is moved within the ureter 204 so that the ureteral plug part 32 moves past the calculus or stone(s) 300 to position the ureteral plug part 32 at a position between the renal pelvis (kidney) and the calculus 300.

[0051] After the ureteral plug part 32 is positioned at the appropriate place in the ureter, the ureteral lumen 205 is occluded. This occlusion is accomplished by inserting the tip end portion of the syringe 50 into the open end 49 of the valve 40 to open the valve 40, forwardly pushing the plunger 52 in the barrel of the syringe 50 to deliver fluid from the syringe barrel to the ureteral plug part 32 by way of the valve 40 and the ureteral plug part lumen 38, thus causing the ureter plug part 32 to outwardly expand as described above so that the outer surface of the expanded ureteral plug part 32 contacts the inner surface of the ureteral lumen 205. More specifically, the expanded ureteral plug part 32 preferably contacts the inner wall of the ureteral lumen 205 along a continuous circumference of the ureteral plug part 32. The expanded or inflated ureteral plug part 32 is an example of an occlusion means for occluding the ureteral lumen 205.

[0052] Once the ureteral lumen 205 is occluded as shown in FIG. 7, fluid (liquid) is discharged from the irrigation port 34 to wash the ureteral lumen 205. The fluid discharged from the irrigation port 34 flows towards the calculus 300 and then continues flowing towards the bladder. The fluid discharged into the ureteral lumen 205 by way of the irrigation port 34 carries away (flushes or washes away) the calculus 300 towards the bladder. The fluid thus washes away or flushes the calculus 300 to remove the calculus 300 from the ureteral lumen. The calculus 300 can flow out of the bladder with the urine stream naturally because the urethral lumen size is larger than the size of the calculus 300 and the ureteral lumen 205. After the discharge of the fluid is completed (i.e., after the calculus 300 has been washed away), the ureteral plug part 32 is contracted or deflated by simply pressing against the

rubber plug **42** in the check valve **40** so that the rubber plug **42** lifts off the valve seat **48**, thus allowing fluid to leave the ureteral plug part **32**. Once the ureteral plug part **32** is deflated or contracted, the ureteral lumen **205** is no longer occluded. It is now possible to withdraw the elongated member **32** out of the ureteral lumen (i.e., away from the kidney and towards the bladder).

[0053] If the calculus or stones **300** in the ureter **204** are many, it is possible to carry-out the above-described operation in a step-wise manner. For example, when moving the ureteral plug part **32** within the ureter **204** toward the kidney, the ureteral plug part **32** can be moved past some of the calculus or stones **300**, whereupon the above-described operation is carried out to flush or wash away the calculus or stones **300** downstream of the ureteral lumen **205**. After such flushing, the ureteral plug part **32** is moved once again in the forward direction toward the kidney past more of the calculus or stones **300**. This is repeated until all of the calculus or stones **300** have been washed out of or removed from the ureter **204**. As another example or possibility, the fluid can be discharged from the irrigation port **34** while rotating the calculus removing/retrieving device **30**. In this way, it is possible to more evenly discharge fluid with respect to the calculus or stones **300**.

[0054] It is also possible to use the expanded or inflated ureteral plug part **32** as a “rake” to rake-out the calculus or stones **300** from the ureter and thus assist the washing or flushing by the fluid. After washing, or during washing, the partly expanded or inflated ureteral plug part **32** is moved rearwardly within the ureter **204** in the direction toward the bladder **202**. The ureteral plug part **32** is moved in this way while the ureteral plug part **32** is in the expanded or inflated state so that the expanded or inflated ureteral plug part **32** pulls along or rakes the calculus or stones **300**.

[0055] As a part of the operational procedures described above, it is also possible to perform lithotripsy to break-up the calculus or stones **300** using an acoustic pulse. The use and effect of lithotripsy is known in the art and so a detailed discussion is not set forth here. The lithotripsy procedure can be performed after the ureteral plug part **32** is moved/positioned beyond the calculus or stones **300**, but before expanding the ureteral plug part **32**. Alternatively, the lithotripsy procedure can be performed after the ureteral plug part **32** is moved/positioned beyond the calculus or stones **300** and after expanding the ureteral plug part **32**, but before discharging fluid from the irrigation port or nozzle to flush or wash the ureteral lumen **205** with the discharged fluid. It is further possible to perform lithotripsy to break-up or fragment the calculus or stones before moving the ureteral plug part **32** into the ureter **204**.

[0056] FIG. 8 illustrates another aspect of the disclosure here involving the calculus removing/retrieving device, and associated method, shown in FIGS. 3-7. The calculus removing/retrieving device **30** may be used together with a guide wire **62**. The calculus removing/retrieving device **30** may be appropriately configured in the normal way to accommodate the guide wire **62**, for example by inserting the calculus removing/retrieving device in the direction toward the ureter **204** across the UBJ **212** with a guide wire **62**. The guide wire **62** is then used to guide the calculus removing/retrieving device **30** to the desired location in the ureter. FIG. 9 illustrates that the calculus removing/retrieving device **30** can be used with an ureteroscope **64**. This ureteroscope **64** possesses a known construction and so a detailed discussion of associ-

ated features will not be described in detail. In this version of the calculus removing/retrieving device **30** and method, the ureteroscope **64** can be a rigid ureteroscope.

[0057] In use, the guide wire **62** is appropriately introduced into the body (e.g., through the urethra) and advanced through the bladder, ureteral orifice and into the ureter **204**, and the tip of the guide wire **62** enters the kidney **200** through the ureter **204**. The ureteroscope **64** is then inserted into the ureter **204** along the guide wire **62**. The calculus removing/retrieving device **30** is inserted into the instrument lumen in the ureteroscope **64**, and then debouched into the ureter **204** from the tip or open end of the instrument lumen of the ureteroscope **64**. Alternatively, the calculus removing/retrieving device **30** may be inserted into the instrument lumen in the ureteroscope **64** first. Then the calculus removing/retrieving device **30** and the ureteroscope **64** are inserted into the ureter **204** along the guide wire **62** together. The ureteroscope **64** provides a mechanism for visually observing the calculus in the ureter to appropriately position the calculus removing/retrieving device relative to the calculus, including advancing the ureteral plug part **32** to a position beyond the calculus (i.e., between the kidney and the calculus). The procedure discussed above for discharging fluid (liquid) into the ureter to wash or flush the ureter lumen and the calculus or stones is then followed.

[0058] In the operation discussed above, after the calculus removing/retrieving device **30** is properly positioned in the ureter **204**, the ureteroscope **64** can be pulled-back in the rearward direction to a position outside the ureter **204** (e.g., to a position in the bladder) or the ureteroscope **64** can be pulled-back so that it is removed from the living body. That is, the ureteroscope **64** can be pulled-back to a position outside the ureter **204** or outside the body before discharging fluid from the irrigation port or nozzle to flush or wash the ureteral lumen **205** with the discharged fluid. As an alternative, after the calculus removing/retrieving device **30** is positioned at the desired place in the ureter **204**, the ureteroscope **64** can be kept at its position, and pulled-back to outside the living body concurrently with the discharging of the fluid from the irrigation port or nozzle to flush or wash the ureteral lumen **205** with the discharged fluid. In this latter situation, the ureteroscope **64** is pulled-back together with the calculus and the liquid.

[0059] As discussed above, the guide wire **62** may be used to help guide the calculus removing/retrieving device **30** and/or the ureteroscope **64**. The guide wire **62** can also be used to change and keep the ureter **204** shape as a straight shape. The guide wire **62** can also be used to open the ureteral orifice before the washing to facilitate draining of the fluid after the washing begins. Such shape's changes help create or maintain a drainage passage easily through the ureteral lumen **205**.

[0060] FIGS. 10-12 illustrate another variation on the calculus removing/retrieving device described above. The calculus removing/retrieving device **30'** is similar to the calculus removing/retrieving device **30** described above, except that a distal end **35** of the elongated member **31** is extended and possesses an open distal end **37**. In addition, the proximal end portion of the elongated member **31** is configured so that the proximal-most end portion (operation portion) **33** is separable from the remainder of the elongated member **31** by way of a separable connector **39**. The operation portion or proximal-most end portion **33** of the elongated member **31** is the part that is grasped and operated by the operator or medical professional.

[0061] A proximal end portion of the elongated member **31** and the proximal-most end portion (operation portion) **33** are connected by the separable connector **39** temporarily. That is, the separable connector **39** is a temporary connector. By way of example, the separable connector **39** can consist of weak fusion splicing or fitting parts (e.g., convex and concave). If the cross-sectional surface of the remainder of the elongated member **31** at the separable connector **39** side is forced in the forward direction toward the kidney by a pusher force existing in the proximal-most end portion (operation portion) **33** additional lumen, the elongated member **31** and the proximal-most end portion (operation portion) **33** can be separated rather easily.

[0062] In use, the calculus removing/retrieving device **30'** is introduced into the ureter **204** in a manner similar to that described above (e.g., by way of the urethra and the bladder, and with or without the aid of a guide wire **62** and/or the ureteroscope **64**). By virtue of the open distal end **37**, the calculus removing/retrieving device **30'** can serve as a ureteral stent or drainage tube prior to carrying out the medical procedure. That is, after the calculus removing/retrieving device **30'** is positioned in the ureter **204** at the intended or desired location, the open ends of the calculus removing/retrieving device **30** creates or allows urinary flow through the calculus removing/retrieving device **30'**. Urinary flow can thus continue while waiting to begin the medical procedure or operation (i.e., while waiting to begin flushing or washing with the liquid).

[0063] In addition, using the calculus removing/retrieving device **30'** shown in FIG. 10, after the calculus removal/retrieval method is carried out as described above, the proximal-most end portion or operation portion **33** of the elongated member **31** can be separated from the remainder of the elongated member **31** at the separable connector **39**. Following this separation, the proximal end portion of the elongated member **31** is open and positioned in the bladder **202**, while the open distal end portion **35** remains positioned in the renal pelvis (kidney). Thus, following the medical procedure or operation to remove/retrieve the calculus, the elongated member **31** remains in place and operates as a drainage tube or ureteral stent that maintains urinary flow. Thus, this embodiment of the calculus removing/retrieving device **30** illustrated in FIGS. 10-12 provides a mechanism for maintaining urinary flow both before and after the calculus removing/retrieving procedure.

[0064] FIGS. 13 and 14 illustrate calculus removing/retrieving devices representing other examples of the device (and associated method) disclosed here. These embodiments of the calculus removing/retrieving device are the same as described above and illustrated in FIG. 3, except that the device is outfitted with a ureter wall pushing element to maintain a space or flow path for the fluid (liquid) discharged from the calculus removing/retrieving device as well as the calculus being washed away by the fluid. In the embodiment illustrated in FIG. 13, the calculus removing/retrieving device **30''** includes a ureter wall pushing element **66** in the form of two spaced apart projections **68** affixed to the elongated member **31** and projecting away from the elongated member **31** into direct contact with the inner surface of the ureteral wall surrounding the ureteral lumen **205**. The pushing element **66** is configured to be enlarged and reduced in size (expanded and contracted). In the illustrated embodiment disclosed by way of example, the pushing element **66** is an inflatable balloon in the same way of the ureter plug part **32**. Through an

additional lumen terminated at the pushing element **66** in the elongated member **31**, the pushing element **66** is expanded (inflated) by introducing the fluid into an interior space of the pushing element **66**, and the pushing element **66** is contracted (deflated) by allowing the fluid to empty from the ureter plug part **32**. The fluid can be water, air, contrast medium, etc. The pushing element **66** has different characteristics from the ureter plug part **32**; in the expanded state, the projections **68** are more shaped (elongated) and more rigid than the ureter plug part **32**. FIG. 14 illustrates the contracted or deflated state of the pushing element **66**.

[0065] The ureter wall pushing element **66** is beneficial in that it helps ensure that adequate space exists for flow of the flushing fluid which is generally illustrated by the arrow in FIG. 13. That is, the ureter wall pushing element **66** provides a flow path for the fluid (liquid) discharged from the calculus removing/retrieving device as well as the calculus being washed away by the flushing/washing fluid. The ureter wall pushing element **66** is especially helpful in this regard with respect to the narrowed ureter lumen such as UBJ **212**.

[0066] FIGS. 15A and 15B illustrate a calculus removing/retrieving device representing another example of the device and associated method disclosed here. In the earlier embodiments of the calculus removing/retrieving device, the ureteral plug part **32** is configured to expand into contact with the lumen **205** of the ureter **204**. This version of the calculus removing/retrieving device **30'''** differs in that the ureteral plug part **32'''** is configured to draw or pull, through suction or vacuum, the inner surface or wall of the ureteral lumen **205** of the ureter **204** towards and into contact with the ureteral plug part **32'''**. FIG. 15A illustrates an example of the configuration of the ureteral plug part **32'''**. The distal end portion of the elongated member **31'''** is provided with a series of through holes or openings **72** which communicate with the interior of the elongated member **31'''**. The interior of the ureteral plug part **32'''** is connected to a suction source or vacuum source. In the illustrated embodiment, the vacuum or suction source is the syringe illustrated in FIG. 5. In the embodiment discussed above and illustrated in FIG. 5, the plunger **52** is pushed in the forward direction to inflate the ureteral plug part **32**. In this embodiment, the plunger **52** is pulled in the rearward direction after the syringe is connected to the end of the elongated member **31'''** to create a vacuum or suction that draws the inner surface of the ureteral lumen **205** towards and into direct contact with the outer surface of the ureteral plug part **32'''** as illustrated in FIG. 15B. This embodiment thus provides an alternative way for occluding or closing-off the ureteral lumen **205** in the ureter **204**. The ureteral plug part **32'''** operates as an aspiration port.

[0067] The embodiment described above uses a syringe as a vacuum or suction source. But other vacuum or suction sources can be used.

[0068] FIGS. 16 and 17 illustrate a calculus removing/retrieving device representing a further example of the device and associated method disclosed here. This embodiment has particularly useful applications for removing/retrieving calculus located in the renal pelvis (kidney). Generally speaking, the calculus removing/retrieving device **130** is configured to occlude or cover one part of the renal pelvis, and at the same time deliver or discharge washing or flushing fluid (liquid) to the remaining part of the renal pelvis to wash or flush away the calculus located in the other uncovered part of the renal pelvis.

[0069] Referring to FIG. 16, the calculus removing/retrieving device 130 includes an elongated member (main body) 131 and a tubular member or catheter 172 provided with the irrigation port or irrigation nozzle 134. The elongated member or main body 131 possesses a lumen open at both ends, and the tubular member 172 is axially movable within the lumen of the elongated member 131. The tubular member 172 also includes a lumen extending throughout the tubular member and open at both ends. In the illustrated embodiment disclosed by way of example, the irrigation port or irrigation nozzle 134 is the open distal end of the tubular member 172. The lumen in the tubular member 172 is connected to a fluid source, an example of which is the fluid source 60 illustrated in FIG. 3.

[0070] The lumen in the elongated member 131 (i.e., the space between the outer surface of the tubular member 172 and the inner surface of the elongated member 131) communicates with the interior of an expandable and contractible renal cover part 132 which is fixed to the elongated member 131. The renal cover part 132 serves as an occluding means for occluding a portion of the renal pelvis as described in more detail below.

[0071] The lumen in the elongated member 131 is connected to a fluid source like the syringe 50 illustrated in FIG. 5. A check valve similar to that illustrated in FIGS. 3-6 can be employed to control the introduction of the fluid (e.g., air/gas) into the expandable/contractible renal cover part 132. The syringe 50 and the check valve also allow the fluid to be discharged from the renal cover part 132 as explained above. In the illustrated example, the expandable/contractible renal cover part 132 is an expandable balloon which expands (inflates) when fluid is introduced into the balloon and contracts (deflates) when fluid is expelled from the balloon.

[0072] An example of a method for retrieving/removing calculus from a renal pelvis using the calculus removing/retrieving device 130 illustrated in FIG. 17 is as follows. The calculus removing/retrieving device 130 is inserted into the body (e.g., by way of the urethra), passed through the bladder 202, and moved along the ureter 204 until entering the renal pelvis. Throughout this movement of the calculus removing/retrieving device 130 and introduction to the renal pelvis, the renal cover part 132 is in a deflated/contracted condition, and fluid is not discharged from the irrigation port or irrigation nozzle 134. After positioning the renal cover part 132 in the renal cavity, the renal cover part 132 is expanded or inflated to occlude or cover a part of the renal pelvis as generally illustrated in FIG. 17. After the one part of the renal pelvis is covered or occluded by the expanded renal cover part 132, fluid is discharged from the irrigation port or nozzle 134 and is directed at the other part of the renal pelvis that is not covered or occluded by the renal cover part 132. This fluid that is discharged from the irrigation port 134 washes out or flushes the uncovered part of the renal pelvis, taking with it the calculus. The calculus 300 and the fluid are then washed away or flushed-out by way of the ureter 204.

[0073] As a part of carrying out this operation, the irrigation port 134 can be pointed at the uncovered portion of the renal pelvis. This directed approach can help facilitate the flushing or washing-out of the calculus.

[0074] It is also possible as a part of this medical procedure to use lithotripsy on the calculus located in the renal pelvis before covering a part of the renal pelvis by inflating the renal

cover part 132. In this case, lithotripsy is preferably carried out before introducing the renal cover part 132 into the renal pelvis.

[0075] The calculus removing/retrieving device 130 illustrated in FIG. 16 can be delivered to the renal pelvis using a ureteral access sheath and a ureteroscope, preferably a flexible ureteroscope. Here, the ureteral access sheath is first inserted into the living body and then the device 130 is inserted into the ureteroscope, and then the ureteroscope is inserted into the ureteral access sheath. The ureteral access sheath is introduced into the living body (for example by way of the urethra) and is advanced to a position where the tip end of the ureteral access sheath is located beyond (i.e., at the upper part or proximal part) the ureteropelvic junction. This is favorable positioning to help maintain or keep the flexibility of the tip end of the ureteroscope. The ureteroscope is used to visually observe the progress or movement of the calculus removing/retrieving device 130 towards the renal pelvis. Once the calculus removing/retrieving device 130 is properly positioned in the renal pelvis, the ureteroscope can be pulled back outside the body. The renal cover part 132 is then inflated to cover the one portion of the renal pelvis. In addition, the ureteroscope can be pulled back after the one part of the renal pelvis is covered or occluded by the expanded renal cover part 132. The fluid is discharged from the irrigation port or nozzle 134 to wash out the other part of the renal pelvis. The fluid and the calculus flow through the ureteral access sheath to outside the body.

[0076] FIGS. 18 and 19 illustrate an additional aspect of the calculus retrieving and removing method disclosed here and described above. This additional aspect involves subjecting the calculus to relatively small power to move or shift calculus (calculus-moving power or calculus-position changing power). This power may involve applying small impact waves generated when water flows from the irrigation port of the ureteroscope, or by vibrating or shaking the bed/table on which the patient is lying. The objective here is to move calculus from the one part of the renal pelvis to another part of the renal pelvis. This movement of the calculus from the one part of the renal pelvis to the other part of the renal pelvis is schematically illustrated in FIG. 18. The calculus is then collected in one part or region of the renal pelvis. The parts or region at which the calculus is collected is preferably the minor calyx. After the calculus is collected in the one part or region of the renal pelvis, the calculus removing/retrieving device is introduced into the renal pelvis, and the one part of the renal pelvis from which the calculus was removed or evacuated is covered by the inflated renal cover part 132 as illustrated in FIG. 19. The uncovered part of the renal pelvis is then washed or flushed by introducing fluid (liquid) into the renal pelvis through the irrigation port 134 as described above. Employing this additional aspect illustrated in FIGS. 18 and 19 improves the efficiency of the calculus removal/retrieval operation in that most or all of the calculus is moved to the area or region of the renal pelvis that is flushed-out by the fluid delivered from the irrigation port or nozzle 134.

[0077] FIG. 19 illustrates an additional aspect associated with this embodiment of the calculus retrieval/removal device and method. As shown in FIG. 19, a pressure sensor 145 is attached to the calculus removing/retrieving device 130, specifically the elongated member 131. This pressure sensor 145 senses the pressure in the renal pelvis. The pressure sensor 145 is connected to a control unit 146 which controls operation of the calculus removing/retrieving device 130, includ-

ing the discharge of the fluid out of the irrigation nozzle 134. When information provided by the pressure sensor 145 indicates that the intra-renal pressure (i.e., the pressure inside the renal pelvis) is greater than a certain pressure (e.g., from 0.2 mH₂O to 0.7 mH₂O, more favorable, from 0.3 mH₂O to 0.5 mH₂O), the control unit 147 can alert the high intra-renal pressure to the physician and/or stop discharging additional fluid (water) into the renal pelvis.

[0078] FIG. 20 illustrates another aspect of the disclosure here. First, the renal cover part 132 is inflated to cover the one portion of the renal pelvis. Then the ureteroscope is pulled back, and simultaneously fluid is discharged from the irrigation port or nozzle 134 to wash out the other part of the renal pelvis. As shown in FIG. 20, to avoid a rise of the intra-renal pressure, the volume of “pulling back the ureteroscope” represented by the shaded portion near the arrow in FIG. 20 and the “additional pouring irrigation water” represented by the other shaded portion in FIG. 20, should be continuously adjusted as equal. Through this procedure, physician can see the calculus state by ureteroscope during washing out.

[0079] The calculus removing/retrieving device 130 shown in FIG. 16 can also be used to “rake” out the calculus or stones in a manner similar to that described above. For example, after the one part of the renal pelvis is covered or occluded by the expanded renal cover part 132, the fluid that is discharged from the irrigation port 134 washes out or flushes the uncovered part of the renal pelvis, taking with it the calculus. The calculus 300 and the fluid partially can be washed away or flushed-out by way of the ureter 204, but residues (residual calculi) exist in the ureter 204. To remove these residual calculi, the renal cover part 132 may be deflated or contacted, and moved rearwardly within the ureter 204 in the direction toward the bladder 202. Then the renal cover part 132 is re-expanded or re-inflated until the surface of the renal cover part 132 partially touches the ureter 204. The renal cover part 132 is moved in this way while the renal cover part 132 is in the expanded or inflated state so that the expanded or inflated renal cover part 132 pulls along or rakes the calculus or stones 300.

[0080] It is also possible to use the calculus removing/retrieving device 130 shown in FIG. 16 to “rake” out the calculus or stones in the ureteral access sheath when the ureteral access sheath is used. In this situation, the residual calculus 300 and the fluid exist in the ureteral access sheath the same as above. The calculus removing/retrieving device 130 is delivered to the lumen of the ureteral access sheath while the renal cover part 132 is deflated or contacted. After reaching the desired position in the ureteral access sheath lumen, the renal cover part 132 is expanded (inflated) and then pulled rearwardly within the ureteral access sheath lumen to rake-out calculus or stones in the ureteral access sheath lumen. In this variation, the extent to which the renal cover part 132 can be expanded or inflated will be dictated by the inner diameter of the ureteral access sheath lumen.

[0081] According to another aspect of the disclosure here, when the calculus removing/retrieving device 130 shown in FIG. 16 is used with a ureteroscope, the amount of pull-back or rearward movement of the calculus removing/retrieving device 130 is controlled according to the amount of water being discharged into the renal pelvis. As explained above, it is possible to use a ureteroscope to visually observe the movement of the calculus removing/retrieving device 130 into the renal pelvis. When the calculus removing/retrieving device 130 reaches the desired position in the renal pelvis, the uret-

eroscope can be pulled-back before the convection-producing discharge of the fluid into the renal pelvis or the ureteroscope can be held at its current position. In the latter case, as the fluid (wash-out fluid) is discharged into the renal pelvis, the ureteroscope is pulled-backward, accompanied by the calculus/stones and the wash-out fluid. This pull-back of the ureteroscope is controlled so that the volume of the pulling-back of the ureteroscope equals the volume of fluid (water) being discharged from the irrigation port 134.

[0082] FIGS. 21-24 illustrate a calculus removing/retrieving device representing a further example of the device and associated method disclosed here. This embodiment of the calculus removing/retrieving device 330 includes an elongated member 331 provided with an irrigation port or nozzle 334, representing an example of an outlet. An irrigation lumen 336 extends along the elongated member 331. The irrigation lumen 336 communicates with the irrigation port or nozzle 334 and also possesses an open proximal end. A plunger 376 is movably positioned in the irrigation lumen 336 to slide along the length of the irrigation lumen. The plunger includes a rubber gasket or plug 378 fixed to the plunger 376 so that the rubber gasket 378 moves together with the plunger 376 as a unit. The gasket 378 fluid-tightly engages the inner surface of the irrigation lumen 336.

[0083] The calculus removing/retrieving device 330 also includes a suction port 380, representing an example of an inlet. In the illustrated embodiment shown in FIGS. 21 and 22, the suction port 380 is positioned proximally of the irrigation port 334. A check valve 382 (one-way valve) closes the irrigation port 334, while another check valve 384 (one-way valve) closes the suction port 380. The check valve 382 allows fluid to be discharged from the irrigation lumen 336 to outside the device as illustrated by the arrow 375 in FIG. 21. On the other hand, the check valve 382 prevents the fluid from flowing into the irrigation lumen 336 in the direction opposite the arrow 375.

[0084] Referring to FIG. 21, when the plunger 376 is pushed in the forward direction indicated by the direction of the arrow 373 in FIG. 21, fluid (liquid) in the irrigation lumen 336 and positioned ahead of the gasket 378 (i.e., on the right side of the gasket 378 in FIG. 21) is discharged out through the irrigation port 334 by way of the check valve 382. The check valve 382 is configured to permit flow in the direction of the arrow 375 while preventing flow in the direction opposite the arrow 375.

[0085] Referring to FIG. 22, when the plunger is pulled rearwardly in the direction indicated by the direction of the arrow 377 in FIG. 22, a suction or vacuum is created on the distal side of the gasket 378 (i.e., the right side of the gasket with reference to FIGS. 21 and 22) to draw fluid and calculus into the lumen 336 by way of the check valve 384. The check valve 384 is configured to permit flow in the direction of the arrow 379 while preventing flow in the direction opposite the arrow 379.

[0086] The calculus removing/retrieving device 330 shown in FIGS. 21 and 22 also includes a retrieval part 386 generally in the form of a housing or enclosure 386. A check valve 390 is provided in the enclosure 388 to separate the interior of the enclosure 386 and the exterior of the enclosure. When open, the check valve 390 permits communication between the interior of the enclosure 386 and the exterior of the enclosure. The check valve 390 is similar to the check valve 384, but the check valve 390 can be opened more easily than the check valve 384. In other words, the closing power of the check

valve 390 is less than the closing power of the check valve 384. Thus, when the plunger is pulled rearwardly in the direction of the arrow 377 in FIG. 22, the check valve 390 is opened more widely and/or is opened for a longer period of time than the check valve 384. The check valve 390 permits fluid and calculus (kidney stones or stone fragments) to pass through into the enclosure 388, but the check valve 384 permits only the fluid to pass through into the lumen 336.

[0087] FIG. 23 generally illustrates operational aspects associated with use of the calculus removing/retrieving device 330. The irrigation lumen 336 that communicates with the irrigation port or nozzle 334 is filled with a fluid (e.g., a liquid such as water, saline, etc.) and then the plunger/gasket 378 is positioned inside the irrigation lumen 336 and moved in the forward direction toward the irrigation port 334. As the plunger 376 moves in the forward direction indicated by the arrow 373, the fluid inside the irrigation lumen is discharged through the irrigation port 334 by way of the check valve 382 and creates convection in the renal pelvis as schematically indicated by the arrow 381 in FIG. 23. This convection is beneficial because when the calculus removing/retrieving device is positioned in the renal pelvis, the convection created by the fluid discharged through the irrigation port 334 stirs-up the calculus or stone fragments that are present in the renal pelvis. That is, the calculus is lifted-off of the surface of the renal pelvis and is suspended in the convection, thus helping to facilitate the retrieval of the calculus. During this forward movement of the plunger 376, the check valve 382 is open while the check valve 384 at the suction port and the check valve 390 at the retrieval part 386 remain closed.

[0088] After the plunger 376 has reached the end of its forward stroke, movement of the plunger 376 stops and the check valve 382 automatically closes. Next, the plunger 376 is pulled in the rearward direction to retrieve the calculus that has been stirred-up or lifted by the fluid convection. This rearward movement of plunger 376 in the direction of the arrow 377 causes the check valve 382 to close. As the plunger 376 is pulled in the rearward direction, a vacuum or suction is created in front of the gasket 378. This causes the check valve 384 to open, and causes the check valve 390 to be wide-opened (more widely-open than the check valve 384) so that fluid and calculus or stones in the renal pelvis flow through the check valve 390 and enter the enclosure 388. The calculus or stones 300 which have passed through the check valve 390 tend to remain in the enclosure 388 and fall toward the bottom of the enclosure due to their weight, whereas the fluid passing through the check valve 390 and entering the enclosure 388 is drawn through the open check valve 384, enters the inside of the irrigation lumen 336. If the plunger 376 is pushed and pulled continuously, a relatively stable convection can be generated in the renal pelvis.

[0089] FIG. 24 schematically illustrates the calculus removing/retrieving device 330 positioned in the renal pelvis of the kidney 200. As described previously, the calculus removing/retrieving device can be inserted through the urethra, advanced through the bladder and along ureter 204 where it enters the renal pelvis. Once the calculus removing/retrieving device 330 is properly positioned in the renal pelvis, the plunger 376 is moved in the forward direction to discharge fluid out of the irrigation lumen 336, through the irrigation port or nozzle 334 and into the renal pelvis to create fluid convection as described above. FIG. 24 illustrates the way that the fluid convection lifts and suspends the calculus 300. During the discharge of the fluid through the irrigation

port 334, the check valve 382 is open while the check valve 384 and the check valve 390 remain closed. After the plunger reaches the end of its forward stroke, the plunger is pulled in the rearward direction to cause fluid and calculus/stone fragments to be drawn through the check valve 390 and into the enclosure 388. The calculus or stone fragments collect in the enclosure 388 where they gather and are held by virtue of their weight. On the other hand, the fluid that is drawn through the check valve 390 passes through the check valve 384 and continues to be drawn along the irrigation lumen 336. During the rearward movement of the plunger, the check valve 384 and the check valve 390 are open while the check valve 382 remains closed.

[0090] As in the embodiments described above, it is possible to insert the calculus removing/retrieving device 330 into the living body using a ureteroscope, preferably a flexible ureteroscope. The calculus removing/retrieving device 330 is introduced into the instrument channel of the ureteroscope and is advanced to the renal pelvis while being observed through operation of the ureteroscope.

[0091] As an alternative to the configuration of the calculus removing/retrieving device 330 shown in FIGS. 21 and 22, it is possible to do away with the retrieval part 386 of the calculus removing/retrieving device 330. In this alternative, the ureteroscope is used in the manner described above to visually observe the forward movement of the calculus removing/retrieving device toward the renal pelvis. Once the calculus removing/retrieving device is appropriately positioned in the removing/retrieving device, the ureteroscope is pulled back to the ureteropelvis junction 208 (shown in FIG. 1) or into the ureter 204 (shown in FIG. 1). This creates a space between the distal end of the ureteroscope and the ureteral inner wall. The calculus/stone fragments are then collected in this space formed by the tip end of the ureteroscope and the ureteral inner wall when the ureteroscope is pulled back, instead of the retrieval part 386. The calculus/stone fragments together with the fluid enter this space and flow along the ureter to the bladder or outside the body. As explained above, a continuous pushing and pulling procedure is necessary to generate the stable convection in the renal pelvis and maintain the renal pelvis capacity.

[0092] FIGS. 25A and 25C illustrate a rubber seal check valve which can be used as a specific form of the check valve 382, 384 in the calculus removing/retrieving device 330. The rubber seal check valve includes a rubber element 392 secured to the elongated member 331. The rubber element 392 covers a plurality of holes or through openings 394 in the elongated member 331. The rubber element 392 is secured to the elongated member 331 in any appropriate way so that the rubber element 392 normally covers the holes or through openings 394. When pressure is applied from the side opposite the rubber element 392, the rubber element 392 is lifted as shown in FIG. 25C to allow fluid to discharge or pass through the holes 394.

[0093] Thus, if the rubber seal check valve is used for the valve 382 shown in FIGS. 21 and 22, the valve would take the position shown in FIG. 25C when the plunger 376 is pushed in the forward direction and would take the position shown in FIG. 25B when the plunger 376 is pulled in the rearward direction. If the rubber seal check valve is used for the valve 384 shown in FIGS. 21 and 22, the valve would be in the position shown in FIG. 25B when the plunger 376 is moved in

the forward direction and would move to the position shown in FIG. 25C when the plunger 376 is pulled in the rearward direction.

[0094] FIG. 26 illustrates known duck bill-type valves which can be used as another specific form of the check valve 382, 384 in the calculus removing/retrieving device 330. If the duck bill-type valve is used for the valve 382 shown in FIGS. 21 and 22, the narrowed mouth of the duck bill-type valve would open when the plunger 376 is pushed in the forward direction and would return to the closed position when the plunger 376 is pulled in the rearward direction. If the duck bill-type valve is used for the valve 384 shown in FIGS. 21 and 22, the narrowed mouth of the duck bill-type valve would open when the plunger 376 is pulled in the rearward direction and would return to the closed position when the plunger 376 is pushed in the forward direction.

[0095] FIG. 27 illustrates an example of an impeller which can also be employed in the calculus removing/retrieving device 330. Instead of the plunger 376 pushing and pulling action (movement) in the lumen 336 equipped with the oppositely-oriented check valve arrangement, mechanically rotating the impeller can create the objective convection in the renal cavity.

[0096] The detailed description above describes a device and method for retrieving/removing calculus from parts of a living body such as the ureter and the renal pelvis. The invention is not limited, however, to the precise embodiments and variations described. Various changes, modifications and equivalents can be effected by one skilled in the art without departing from the spirit and scope of the invention as defined in the accompanying claims. It is expressly intended that all such changes, modifications and equivalents which fall within the scope of the claims are embraced by the claims.

What is claimed is:

1. A method for removing a calculus located in a lumen of a ureter, the method comprising:

moving a ureteral plug part of an elongated member in the lumen of the ureter toward the calculus located in the lumen of the ureter and past the calculus so that the ureteral plug part is positioned beyond the calculus, the ureteral plug part being positioned at a distal portion of the elongated member, the elongated member also including at least one irrigation port positioned between the ureteral plug part and a proximal end portion of the elongated member, the ureteral plug part being spaced so that an outer surface of the ureteral plug part is spaced from an inner surface of the lumen in the ureter;

occluding the lumen in the ureter while the ureteral plug part is positioned beyond the calculus;

washing away the calculus in the ureter in a direction away from the ureteral plug part by discharging fluid from the irrigation port into the lumen and toward the calculus;

releasing the occlusion of the lumen in the ureter; and
withdrawing the elongated member, inclusive of the ureteral plug part lumen in the ureter, from the lumen of the ureter.

2. The method of claim 1, wherein the ureteral plug part is moved in a first direction during the movement of the ureteral plug part in the lumen of the ureter toward the calculus, and wherein the ureteral plug part is moved in a second direction opposite the first direction during the withdrawing of the elongated member from the lumen of the ureter, and further comprising raking out the calculus using the ureteral plug part to help remove the calculus from the lumen, the raking out of

the calculus using the ureteral plug part comprising contacting the calculus with the ureteral plug part while moving the ureteral plug part in the second direction.

3. The method of claim 1, wherein the ureteral plug part is moved in a first direction during the movement of the ureteral plug part in the lumen of the ureter toward the calculus, and wherein the ureteral plug part is moved in a second direction opposite the first direction during the withdrawing of the elongated member from the lumen of the ureter, and further comprising raking out the calculus using the ureteral plug part to help remove the calculus from the lumen during the washing, the raking out of the calculus using the ureteral plug part comprising contacting the calculus with the ureteral plug part while moving the ureteral plug part in the second direction

4. The method of claim 1, further comprising fracturing the calculus into smaller pieces while washing the ureteral lumen.

5. The method of claim 1, wherein the ureteral plug part is introduced into the lumen of the ureter by inserting the elongated device with the ureteral plug part into a channel in a ureteroscope which is positioned in the lumen of the ureter; and wherein the moving of the ureteral plug part past the calculus to position the ureteral plug part beyond the calculus is performed while observing the calculus through use of the ureteroscope.

6. The method of claim 1, wherein the ureter is connected to a bladder, and the ureter includes a ureteral orifice that opens into the bladder; further comprising opening the ureteral orifice through use of a guide wire before the washing to facilitate draining of the fluid after the washing begins.

7. The method of claim 1, wherein the ureteral plug part includes an inflatable balloon used to occlude the lumen in the ureter.

8. The method of claim 1, wherein the occluding of the lumen in the ureter includes inflating an inflatable balloon so that the balloon directly contacts an inner surface surrounding the lumen in the ureter.

9. The method of claim 1, wherein the elongated member possesses an irrigation lumen in communication with the irrigation port and an inflation lumen in communication with the inflatable balloon, the method further comprising inflating the balloon by introducing fluid into the balloon through the inflating lumen.

10. The method of claim 1, wherein the ureteral plug part includes an aspiration part connected to a source of suction, the aspiration part being used to occlude the space between the outer surface of the ureteral plug part and the inner surface of the lumen.

11. A method for removing a calculus located in a lumen of a ureter, the method comprising:

positioning an elongated drainage body in the lumen of the ureter, the elongated drainage body including an irrigation port and an operation part, the elongated drainage body being positioned in the ureter so a the ureteral plug part and the irrigation port are positioned distally of the calculus while the operation part of the elongated drainage body is positioned proximally of the calculus;

occluding the lumen in the ureter;

washing the ureteral lumen by discharging fluid from the irrigation port toward the calculus; and

releasing the occlusion of the lumen of the ureter and uncoupling the operation part from the ureteral plug part.

12. The method of claim **11**, wherein the ureter extends between a bladder and a kidney, and after the uncoupling of the operation part from the ureteral plug part, a part of the elongated drainage body remains in the lumen of the ureter and provides fluid communication between the kidney and the bladder.

13. A method for removing a calculus located in a lumen of a ureter, the method comprising:

moving a ureteral plug part along the lumen in the ureter, the ureter being connected at one end to a kidney and at an opposite end to a bladder, the ureteral plug part being moved in the lumen of the ureter from the bladder toward the kidney, the ureteral plug part being moved to a position between the calculus and the kidney;

occluding the lumen of the ureter at a location in the lumen at which the ureteral plug part is located;

introducing fluid into the lumen of the ureter between the location of the occlusion and the calculus so that the fluid washes the calculus toward the bladder; and

releasing the occlusion of the lumen in the ureter.

14. The method of claim **13**, further comprising subjecting the calculus to shock wave lithotripsy while the fluid is being introduced into the lumen of the ureter to break-up the calculus into smaller pieces.

15. The method of claim **13**, further comprising moving the ureteral plug part toward the bladder after releasing the occlusion of the lumen in the ureter, and further comprising raking out the calculus using the ureteral plug part to help remove the calculus from the lumen, the raking out of the calculus using

the ureteral plug part comprising contacting the calculus with the ureteral plug part while moving the ureteral plug part toward the bladder.

16. The method of claim **13**, further comprising moving the ureteral plug part toward the bladder after releasing the occlusion of the lumen in the ureter, and further comprising raking out the calculus using the ureteral plug part to help remove the calculus from the lumen while the fluid is washing the calculus toward the bladder, the raking out of the calculus using the ureteral plug part comprising contacting the calculus with the ureteral plug part while moving the ureteral plug part toward the bladder.

17. The method of claim **13**, wherein the ureteral plug part is introduced into the lumen of the ureter by inserting the elongated device with the ureteral plug part into a channel in a ureteroscope which is positioned in the lumen of the ureter; and wherein the moving of the ureteral plug part in the lumen of the ureter to the position between the calculus and the kidney is performed while observing the calculus through use of the ureteroscope.

18. The method of claim **13**, wherein the ureteral plug part includes an inflatable balloon, and the occluding of the lumen in the ureter includes inflating the balloon so that the balloon contacts an inner surface of the lumen of the ureter.

19. The method of claim **13**, wherein the ureteral plug part includes an aspiration part connected to a source of suction, and the occluding of the lumen in the ureter includes applying suction to the aspiration part to draw an inner surface of the lumen of the ureter into contact with the aspiration part.

* * * * *

专利名称(译)	微积分检索/移除装置和方法		
公开(公告)号	US20150265294A1	公开(公告)日	2015-09-24
申请号	US14/221954	申请日	2014-03-21
[标]申请(专利权)人(译)	泰尔茂株式会社		
申请(专利权)人(译)	泰尔茂株式会社		
当前申请(专利权)人(译)	泰尔茂株式会社		
[标]发明人	HONDA KEI KARINO WATARU		
发明人	HONDA, KEI KARINO, WATARU		
IPC分类号	A61B17/22		
CPC分类号	A61B17/22 A61B2017/22082 A61B2017/22067 A61B17/2202 A61B2017/306 A61B2217/005 A61B2217/007		
其他公开文献	US9610087		
外部链接	Espacenet USPTO		

摘要(译)

移除/取回输尿管腔中的牙结石的方法包括沿着输尿管腔移动输尿管塞部分以将输尿管塞部分定位在牙结石和肾之间。该方法另外包括在输尿管塞部分所在的位置处闭塞输尿管腔，并且在闭塞位置和牙结石之间的点处将流体引入输尿管腔中，使得流体将牙结石冲向膀胱。另一方面涉及一种方法，其中引流管定位在输尿管腔中，使得输尿管塞部分和冲洗端口定位在牙结石的远侧，同时引流管的操作部分位于牙结石的近侧。该方法包括闭塞输尿管腔，清洗输尿管腔，以及释放闭塞并使手术部分与输尿管塞脱开。

