



US007445597B2

(12) **United States Patent**
Butler et al.

(10) **Patent No.:** **US 7,445,597 B2**
(45) **Date of Patent:** ***Nov. 4, 2008**

(54) **RETRACTOR**

(75) Inventors: **John Butler**, Blackrock (IE); **Derek William Young**, Blackrock (IE); **Aoibheann Gill**, Longford (IE); **Alan Reid**, Dublin (IE); **Frank Bonadio**, Bray (IE)

(73) Assignee: **Atropos Limited**, Dublin (IE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 636 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/374,523**

(22) Filed: **Feb. 27, 2003**

(65) **Prior Publication Data**

US 2004/0049100 A1 Mar. 11, 2004

Related U.S. Application Data

(63) Continuation of application No. 09/849,341, filed on May 7, 2001, now Pat. No. 6,582,364, which is a continuation of application No. 09/688,138, filed on Oct. 16, 2000, now Pat. No. 6,254,534.

(30) **Foreign Application Priority Data**

Oct. 14, 1999	(IE)	990861
Dec. 16, 1999	(IE)	991053
Feb. 18, 2000	(EP)	00650010

(51) **Int. Cl.**
A61B 1/32 (2006.01)

(52) **U.S. Cl.** 600/208

(58) **Field of Classification Search** 600/204-210;
128/849, 856

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,157,202 A 10/1915 McLeland

(Continued)

FOREIGN PATENT DOCUMENTS

DE 37 39 532 12/1988

(Continued)

OTHER PUBLICATIONS

Portions of U.S. Appl. No. 10/133,979, including complete original application filed Apr. 29, 2002; Amendment filed Oct. 15, 2003; Office Action dated Dec. 30, 2003; and Notice of Allowability and Examiner's Amendment dated Mar. 15, 2004.

(Continued)


Primary Examiner—Anu Ramana

(74) *Attorney, Agent, or Firm*—Finnegan, Henderson, Farabow, Garrett & Dunner LLP

(57) **ABSTRACT**

A retractor (101) for retracting the margins of a wound opening (103) comprises an inner anchoring O-ring (105) attached to a cylindrical sleeve (106) at a distal end and a reinforcing O-ring (109) attached to a proximal end of the sleeve (106). The sleeve (106) is led between an inner ring part (110) and a corresponding recess (116) in an outer ring part (111). The outer ring part (111) has anchor formations (120) over which the proximal end of the sleeve (106) is attached to anchor the sleeve (106). To retract the wound opening (103) the sleeve (106) is pulled while the guide rings (110, 111) are moved against the tissue surrounding the wound opening (103). This pulls the inner O-ring (105) against the inside of the tissue adjacent the wound opening (103), and retracts the wound opening (103). The sleeve (106) is manipulated locally for maximum retraction efficiency.

12 Claims, 24 Drawing Sheets



U.S. PATENT DOCUMENTS				
1,598,284 A	8/1926	Kinney	5,391,156 A	2/1995 Hildwein et al.
1,810,466 A	6/1931	Deutsch	5,423,848 A	6/1995 Washizuka et al.
2,219,564 A	10/1940	Reyniers	5,429,609 A	7/1995 Yoon
2,305,289 A	12/1942	Coburg	5,480,410 A	1/1996 Cuschieri et al.
2,695,608 A	11/1954	Gibbon	5,514,133 A	5/1996 Golub et al.
2,835,253 A	5/1958	Borgeson	5,522,791 A	6/1996 Leyva
3,111,943 A	11/1963	Orndorff	5,524,644 A	6/1996 Crook
3,244,169 A	4/1966	Baxter	5,526,536 A	6/1996 Cartmill
3,253,594 A	5/1966	Matthews et al.	5,545,179 A	8/1996 Williamson, IV
3,332,417 A	7/1967	Blanford et al.	5,634,911 A	6/1997 Hermann et al.
3,347,226 A	10/1967	Harrower	5,634,937 A	6/1997 Mollenauer et al.
3,347,227 A	10/1967	Harrower	5,636,645 A	6/1997 Ou
3,397,692 A	8/1968	Creager, Jr. et al.	5,640,977 A	6/1997 Leahy et al.
3,522,800 A	8/1970	Lesser	5,649,550 A	7/1997 Crook
3,523,534 A	8/1970	Nolan	5,653,705 A	8/1997 de la Torre et al.
3,570,475 A	3/1971	Weinstein	5,672,168 A	9/1997 de la Torre et al.
3,729,006 A	4/1973	Wilder et al.	5,707,703 A	1/1998 Rothrum et al.
3,782,370 A	1/1974	McDonald	5,738,628 A	4/1998 Sierocuk et al.
3,797,478 A	3/1974	Walsh et al.	5,741,234 A	4/1998 Aboul-Hosn
3,807,393 A	4/1974	McDonald	5,741,298 A	4/1998 MacLeod
3,841,332 A	10/1974	Treacle	5,755,660 A	5/1998 Tyagi
3,907,389 A	9/1975	Cox et al.	5,769,783 A	6/1998 Fowler
3,915,171 A	10/1975	Shermeta	5,803,921 A	9/1998 Bonadio
3,965,890 A	6/1976	Gauthier	5,810,721 A	9/1998 Mueller et al.
4,024,872 A	5/1977	Muldoon	5,813,409 A	9/1998 Leahy et al.
4,030,500 A	6/1977	Ronnquist	5,832,925 A	11/1998 Rothrum
4,096,853 A	6/1978	Weigand	5,853,395 A	12/1998 Crook et al.
4,130,113 A	12/1978	Graham	5,899,208 A	5/1999 Bonadio
4,188,945 A	2/1980	Wenander	5,906,577 A	5/1999 Beane et al.
4,228,792 A	10/1980	Rhys-Davies	5,916,232 A	6/1999 Hart
4,239,036 A	12/1980	Krieger	5,947,922 A	9/1999 MacLeod
4,367,728 A	1/1983	Mutke	5,951,467 A	9/1999 Picha et al.
4,399,816 A	8/1983	Spangler	5,957,913 A	9/1999 de la Torre et al.
4,434,791 A	3/1984	Darnell	5,964,781 A	10/1999 Mollenauer et al.
4,485,490 A	12/1984	Akers et al.	5,994,450 A	11/1999 Pearce
4,550,713 A	11/1985	Hyman	5,997,515 A	12/1999 de la Torre et al.
4,553,537 A	11/1985	Rosenberg	6,033,426 A	3/2000 Kaji
4,601,710 A	7/1986	Moll	6,033,428 A	3/2000 Sardella
4,654,030 A	3/1987	Moll et al.	6,042,573 A	3/2000 Lucey
4,777,943 A	10/1988	Chvapil	6,048,309 A	4/2000 Flom et al.
4,889,107 A	12/1989	Kaufman	6,077,288 A	6/2000 Shimomura et al.
4,895,565 A	1/1990	Hillstead	6,110,154 A	8/2000 Shimomura et al.
4,903,710 A	2/1990	Jessamine et al.	6,142,935 A	11/2000 Flom et al.
4,950,222 A	8/1990	Scott et al.	6,142,936 A	11/2000 Beane et al.
4,984,564 A	1/1991	Yuen	6,163,949 A	12/2000 Neuenschwander
4,991,593 A	2/1991	LeVahn	6,164,279 A	12/2000 Tweedle
4,998,538 A	3/1991	Charowsky et al.	6,171,282 B1	1/2001 Ragsdale
5,041,095 A	8/1991	Littrell	6,183,486 B1	2/2001 Snow et al.
5,045,070 A	9/1991	Grodecki et al.	6,254,533 B1	7/2001 Fadem et al.
D320,658 S	10/1991	Quigley et al.	6,254,534 B1	7/2001 Butler et al.
5,125,897 A	6/1992	Quinn et al.	6,319,246 B1	11/2001 de la Torre et al.
5,158,553 A	10/1992	Berry et al.	6,346,074 B1	2/2002 Roth
5,159,921 A	11/1992	Hoover	6,382,211 B1	5/2002 Crook
5,161,773 A	11/1992	Tower	6,450,983 B1	9/2002 Rambo
5,178,162 A	1/1993	Bose	6,578,577 B2	6/2003 Bonadio et al.
5,188,595 A	2/1993	Jacobi	6,582,364 B2	6/2003 Butler et al.
5,211,370 A	5/1993	Powers	6,623,426 B2	9/2003 Bonadio et al.
5,213,114 A	5/1993	Bailey, Jr.	6,796,940 B2	9/2004 Bonadio et al.
5,234,455 A	8/1993	Mulhollan	6,814,700 B1	11/2004 Mueller et al.
5,248,304 A	9/1993	Vigdorchik et al.	6,840,951 B2	1/2005 de la Torre et al.
5,263,922 A	11/1993	Sova et al.	6,846,287 B2	1/2005 Bonadio et al.
D343,236 S	1/1994	Quigley et al.	6,884,253 B1	4/2005 McFarlane
D346,022 S	4/1994	Quigley et al.	7,081,089 B2	7/2006 Bonadio et al.
5,299,582 A	4/1994	Potts	7,195,590 B2	3/2007 Butler et al.
5,309,896 A	5/1994	Moll et al.	2001/0037053 A1	11/2001 Bonadio et al.
5,316,541 A	5/1994	Fischer	2001/0039430 A1	11/2001 Dubrul et al.
5,342,385 A	8/1994	Norelli et al.	2004/0049099 A1	3/2004 Ewers et al.
5,350,364 A	9/1994	Stephens et al.	2004/0049100 A1	3/2004 Butler et al.
5,364,345 A	11/1994	Lowery et al.	2004/0073090 A1	4/2004 Butler et al.
5,366,478 A	11/1994	Brinkerhoff et al.	2004/0092796 A1	5/2004 Butler et al.
5,368,545 A	11/1994	Schaller et al.	2004/0143158 A1	7/2004 Hart et al.
			2004/0215063 A1	10/2004 Bonadio et al.
			2005/0020884 A1	1/2005 Hart et al.

2005/0090716	A1	4/2005	Bonadio et al.
2005/0090717	A1	4/2005	Bonadio et al.
2005/0148823	A1	7/2005	Vaugh et al.
2005/0240082	A1	10/2005	Bonadio et al.
2006/0247498	A1	11/2006	Bonadio et al.

FOREIGN PATENT DOCUMENTS

DE	37 37 121	5/1989
DE	296 00 939	6/1998
EP	0142262	5/1985
EP	0537768	4/1993
EP	0950376	10/1999
EP	1118657	7/2001
FR	1456623	9/1966
GB	1151993	5/1969
GB	1355611	6/1974
GB	1372491	10/1974
GB	1379772	1/1975
GB	1400808	7/1975
GB	1407023	9/1975
GB	1496696	12/1977
GB	2071502	9/1981
GB	2255019	10/1992
GB	2275420	8/1994
JP	10-108868	4/1998
JP	2001-61850	3/2001
JP	2004-195037	7/2004
SU	1342485	10/1997
WO	WO 86/06272	11/1986
WO	WO 92/11880	7/1992
WO	WO 92/21292	12/1992
WO	WO 93/05740	4/1993
WO	WO 95/05207	2/1995
WO	WO 95/07056	3/1995

WO	WO 95/22289	8/1995
WO	WO 95/27445	10/1995
WO	WO 95/27468	10/1995
WO	WO 96/36283	11/1996
WO	WO 97/32514	9/1997
WO	WO 97/32515	9/1997
WO	WO 98/35614	8/1998
WO	WO 98/48724	11/1998
WO	WO 99/03416	1/1999
WO	WO 99/25268	5/1999
WO	WO 99/29250	6/1999
WO	WO 00/32116	6/2000
WO	WO 00/32117	6/2000
WO	WO 00/32119	6/2000
WO	WO 00/32120	6/2000
WO	WO 00/35356	6/2000
WO	WO 00/54675	9/2000
WO	WO 00/54676	9/2000
WO	WO 00/54677	9/2000
WO	WO 01/08563	2/2001
WO	WO 01/08581	2/2001
WO	WO 01/26558	4/2001
WO	WO 01/91652	12/2001
WO	WO 02/34108 A2	5/2002
WO	WO 03/026512 A1	4/2003
WO	WO 03/034908 A3	5/2003
WO	WO 03/061480 A1	7/2003
WO	WO 03/103548 A1	12/2003
WO	WO 2004/026153 A1	4/2004
WO	WO 2004/030547 A1	4/2004
WO	WO 2005/009257 A2	2/2005

OTHER PUBLICATIONS

Original specification of U.S. Appl. No. 11/486,383, filed Jul. 14, 2006.






Fig.1

*Fig. 2*






Fig. 4








Fig. 5










Fig. 9











Fig. 10







*Fig. 16*






Fig. 18








Fig. 19





*Fig. 25*





Fig. 26






Fig. 28(a)





Fig. 28(b)






Fig. 30





Fig. 31



RETRACTOR

This is a continuation of application Ser. No. 09/849,341, filed May 7, 2001 now U.S. Pat. No. 6,582,364, which is a continuation of application No. 09/688,138, filed Oct. 16, 2000, now U.S. Pat. No. 6,254,534 B1, the contents of both of which are incorporated herein by reference.

INTRODUCTION

The invention relates to a retractor. In particular the invention relates to a retractor for retracting the margins of an incision or a natural bodily orifice to provide maximum exposure of an organ or body structures for examination and/or access for surgical procedures, while also providing protection for the exposed sides of the incised tissue.

Various retractors are known. However in general known retractors are difficult and cumbersome to use, and/or are relatively expensive. In addition known retractors are limited to use with a particular size of incision and a particular patient anatomy.

This invention is directed towards providing an improved wound retractor which will overcome at least some of these problems, and in addition provide a means of wound protection during a surgical procedure.

STATEMENTS OF INVENTION

According to the invention there is provided a surgical wound retractor comprising:

a distal anchoring member for insertion into a wound opening;

a connecting means having an inner wound engaging portion and an outer portion, the wound engaging portion being mounted to the distal anchoring member, the connecting means having an insertion configuration in which the inner wound engaging portion has a reduced radial dimension and a retracting configuration;

an external guide means for the outer portion of the connecting means;

the external guide means being movable relative to the connecting means to shorten the axial extent of the connecting means and thereby bias the wound engaging portion of the connecting member into the retracting configuration to retract the wound opening laterally; and

external anchoring means for anchoring the connecting means to maintain retraction of the opening.

In one preferred embodiment of the invention at least the inner wound engaging portion of the connecting means comprises a sleeve for extending around the wound opening to protect the opening.

In one embodiment the outer portion of the connecting means comprises a sleeve extension of the inner wound engaging portion of the connecting means.

Preferably the connecting means comprises a generally cylindrical sleeve.

In a preferred embodiment the guide means comprises an annular ring means. The annular ring means preferably comprises inner and outer ring parts between which the connecting means is led. In a preferred embodiment the outer ring part includes the anchor means for anchoring the connecting means. In one arrangement the anchor means comprises anchor formations on the outer ring to which the connecting means is attached on retraction of the opening.

Preferably the inner ring means defines a projection for location in a complementary recess of the outer ring with the connecting means located therebetween.

In one embodiment the inner ring is a relatively loose fit in the recess of the outer ring part.

Preferably at least portion of one of the ring parts is movable from a rest position in which the connecting member is substantially clamped between the ring parts to a release position in which at least portion of the connecting member is movable relative to the ring parts. Ideally only portion of the connecting member is movable relative to the ring parts in the release position.

In another embodiment the inner ring is a relatively tight fit in the outer ring part to grip the connecting member therebetween.

In one aspect of the invention the outer ring part comprises a plurality of interconnected segments which are independently movable to facilitate localised release of the connecting member for adjusting of the retraction force applied at the opening. The ring part or segment thereof is preferably manually manipulable between the clamped rest position and the release position.

In one embodiment of the invention the connecting means includes a proximal reinforcing means for engagement with the external anchoring means. Ideally the proximal reinforcing means is a proximal ring.

Preferably the distal anchoring means is of resilient material. Typically the distal anchoring means is an O-ring.

Preferably at least an outer surface of the guide means which engages with the connecting means is of a material with a low coefficient of friction such as polytetrafluoroethylene.

In a particularly preferred embodiment the retractor includes a platform for attachment of another device to the retractor.

In an especially preferred arrangement one of the ring parts defines a platform for attachment of another device to the retractor.

In another aspect the invention provides a method for retracting a wound opening using a surgical wound retractor comprising a distal anchoring member, a connecting means having a wound engaging portion mounted to the distal anchoring member and an outer portion, an external guide means for the outer portion of the connecting means and an external anchoring means; the method comprising the steps:

positioning the distal anchoring member to be retained inside a wound opening with the connecting means extending outwardly therefrom through the opening; moving the external guide means relative to the outer portion of the connecting means to shorten the axial extent of the connecting means and thereby bias the wound engaging portion into a retracting configuration to retract the wound opening; and anchoring the connecting means to maintain retraction of the wound opening.

Preferably the method includes the steps of moving the external guide means relative to the outer portion of the connecting means to partially retract the wound opening, gripping the outer portion of the connecting means and pulling it relative to the guide means to fully retract the wound opening.

In one embodiment the method includes the steps of:

- (a) gripping a local section of the outer portion of the connecting means while the remaining section of the outer portion of the connecting means is anchored,
- (b) pulling the local section to increase the retraction at a local area of the wound opening, and
- (c) anchoring the local section of the connecting means.

Ideally the method includes repeating steps (a) to (c) for other local sections of the outer portion of the connecting means.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more clearly understood from the following description thereof given by way of example only with reference to the accompanying drawings, in which:

FIG. 1 is an exploded view of a wound retractor according to the invention;

FIG. 2 is a perspective view of the retractor of FIG. 1 assembled;

FIG. 3 is a side cross sectional view of the assembled retractor of FIG. 2;

FIG. 4 is a perspective view of an unretracted wound opening;

FIG. 5 is a perspective view illustrating insertion of part of the retractor of FIG. 2 into the wound opening;

FIG. 6 is a side cross sectional view of the retractor of FIG. 2 after insertion;

FIG. 7 is a plan view of the retractor of FIG. 2 after insertion;

FIGS. 8(a) and 8(b) are side cross sectional views illustrating lateral retraction of the wound opening using the retractor of FIG. 2;

FIG. 9 is a side cross sectional view of the retractor of FIG. 2 after lateral retraction of the wound opening;

FIG. 10 is a plan view of the retractor of FIG. 2 after lateral retraction of the wound opening;

FIG. 11 is a plan view of a part of a guide means of the retractor of FIG. 2;

FIG. 12 is a side view of the part of FIG. 11;

FIG. 13 is a cross sectional view along the line A-A in FIG. 11;

FIG. 14 is a cross sectional view of part of another wound retractor according to the invention;

FIG. 15 is a cross sectional view of the retractor of FIG. 14, in use;

FIG. 16 is an exploded view of parts of another wound retractor according to the invention;

FIG. 17 is a perspective view of the wound retractor of FIG. 16 assembled;

FIGS. 18 and 19 are perspective cut-away views of the retractor of FIG. 17 in different positions;

FIG. 20 is a schematic plan view illustrating manipulation of a part of the retractor of FIGS. 17 to 19;

FIG. 21 is a side cross sectional view of the retractor part in the configuration of FIG. 20;

FIG. 22 is a schematic plan view of the retractor part in a release position;

FIG. 23 is a side cross sectional view of the retractor part in the configuration of FIG. 22;

FIG. 24 is a perspective view of a hand access device for use with a wound retractor according to the invention;

FIG. 25 is a side cross sectional view of the retractor of FIG. 2 with the hand access device of FIG. 24 in position;

FIG. 26 is a perspective view of a drape for use with a wound retractor according to the invention;

FIG. 27 is a side cross sectional view of the retractor of FIG. 2 with the drape of FIG. 26 in position;

FIG. 28(a) is a perspective view of a form retaining device in a pliable state for use with a wound retractor according to the invention;

FIG. 28(b) is a perspective view of the form retaining device of FIG. 28(a) in a stiff state;

FIG. 29 is a side cross sectional view of the retractor of FIG. 2 with the stiffened form retaining device of FIG. 28(b) in position;

FIG. 30 is an exploded view of the form retaining device of FIG. 28 and a clamp;

FIG. 31 is a side view of the form retaining device of FIG. 28 and the clamp of FIG. 31; and

FIG. 32 is a side cross sectional view of the retractor of FIG. 2 with the form retaining device of FIG. 28 and the clamp of FIG. 30 in position.

DETAILED DESCRIPTION

Referring to FIGS. 1 to 13 there is illustrated a wound retractor 101 according to the invention, which in the case illustrated is used to retract the margins of a wound such as an abdominal wound opening 103, as illustrated in FIG. 4.

The reactor 101 comprises a distal anchoring member, in this case in the form of a resilient inner O-ring 105, for insertion into the wound opening 103, and a connecting means, in this case in the form of an elastomeric sleeve 106 which is substantially cylindrical. The sleeve 106 has an inner wound engaging portion and an outer portion, and the wound engaging portion is attached to the inner O-ring 105. The sleeve has an insertion configuration in which the inner wound engaging portion has a reduced radial dimension and a retracting configuration to retract the wound opening 103 laterally.

An external guide means is provided for the outer portion of the sleeve 106, and in this case the guide means comprises an inner ring part 110 and an outer ring part 111 between which the sleeve 106 is led. The retractor 101 includes external anchoring means for anchoring the sleeve 106 to maintain retraction of the wound opening 103, and in this case the anchoring means is provided by a plurality of anchor formations 120 on the outer surface of the outer ring part 111 (FIG. 2), the formations 120 extending radially outwardly to define hooks.

The outer ring part 111 is of the same annular shape as the inner ring part 110 but has a larger diameter and a recess 116. The inner ring part 110 is of a relatively stiff material and mates with the outer ring part 111 in the recess 116 to slidably retain the sleeve 106 therebetween, as illustrated in FIG. 3. In this case the ring parts 110, 111 are a relatively loose fit to facilitate movement of the ring parts 110, 111 relative to the sleeve 106 to shorten the axial extent of the sleeve 106 and thereby bias the wound engaging portion into the retracting configuration to retract the wound opening 103 laterally.

The ring parts 110, 111 are of a material with a low coefficient of friction such as Polytetrafluoroethylene (PTFE). PTFE is a tough, non-resilient material of moderate tensile strength and with excellent lubricity.

The retractor 101 also includes a proximal reinforcing means for engagement with the anchor formations 120, and in this case the reinforcing means is provided by a resilient outer O-ring 109 of a material which is flexible relative to the inner O-ring 105. The outer O-ring 109 is attached to the proximal end of the sleeve 106, the rings 105, 109 helping to maintain the open shape of the sleeve 106 at its extremities (FIG. 2).

In use the inner O-ring 105 and the sleeve 106 are squeezed into the insertion configuration for insertion of the inner O-ring 105 into the wound opening 103 (FIG. 5). The inner O-ring 105 is of a polymeric material which facilitates scrunching up of the inner O-ring 105 into a low-profile, elongate shape, as illustrated in FIG. 5, to facilitate ease of use. On release of the inner O-ring 105, the resilient O-ring 105 returns to its normal O-shape overlapping an inner edge of the wound opening 103 to safely anchor the retractor 101 in the wound, as illustrated in FIG. 6. As may be seen from FIGS. 6 and 7, after insertion of the inner O-ring 105, the wound opening 103 is substantially closed and the sleeve 106 is in a wrinkled compressed configuration.

The sleeve 106 is then pulled while pushing the ring parts 110, 111 against the tissue surrounding the wound opening 103, as illustrated in FIG. 8(a), to shorten the axial extent of the sleeve 106 and thereby bias the wound engaging portion into the retracting configuration to retract laterally the right-hand side (as viewed in FIG. 8(a)) of the wound opening 103. The right-hand side of the outer O-ring 109 is hooked around the formations 120 to maintain the right-hand side of the wound opening 103 retracted (FIG. 8(b)). The left-hand side of the sleeve 106 is then pulled while pushing the ring parts 110, 111 to retract laterally the left-hand side of the wound opening 103, as illustrated in FIG. 8(b). The left-hand side of the outer O-ring 109 is then hooked around the formations 120 to maintain the entire wound opening 103 fully retracted, as illustrated in FIGS. 9 and 10.

The separate formations 120 and the configuration of the wound retractor 101 generally allow the sleeve 106 to be readily manipulated locally as illustrated in FIGS. 8(a) and 8(b) to provide an optimised retraction force. Thus, the manipulation is not simply limited to a single vertical axis but can be carried out in several different directions by pulling of the sleeve 106, and localised hooking of the outer O-ring 109 to the appropriate formation 120. In this way the retractor can be tailored to a particular application.

The recess 116 against which the sleeve 106 is slidably retained by the inner ring part 110 is C-shaped with an extended upper lip 117, as may be seen in FIG. 13. The upper lip 117 maintains the inner ring part 110 safely within the recess 116 regardless of the pulling direction or tensile pulling force exerted on the sleeve 106. It is preferable to pull the sleeve 106 in a non-vertical direction and to perform localised hooking of the outer O-ring 109, and the extended upper lip 117 encourages non-vertical pulling of the sleeve 106.

The elastomeric sleeve 106 lines the side of the retracted wound opening 103, as illustrated in FIG. 9, and thus acts both as a means of wound retraction and wound protection.

The surgical wound retractor is of simple construction, is easy to use and can be manufactured inexpensively to provide a disposable unit.

A single wound retractor according to the invention may be used for a wide range of incision sizes and to achieve a range of different localised retraction forces which are required to accommodate the incision, the patient anatomy and the surgical procedure to be performed.

In the retractor of FIGS. 1 to 10 the sleeve 106 is a relatively tight fit between the outer and inner guide ring parts 110, 111. It is also possible to configure the outer and inner ring parts 110, 111 so that the inner ring part 110 is a relatively looser fit in the outer part 111. In this case the guide means comprises an outer ring part or other annular shape within which slides a second component. The second component is of the same annular shape as the outer ring part but with a lesser diameter and has an exterior compartmental recess designed so that the outer ring part fits loosely around the second component and both can easily slide relative to each other. The components fit loosely together so that an elastomeric sleeve can fit in the gap between them and slide therein. Such an arrangement is illustrated in FIGS. 14 and 15. On pulling of a local area of the sleeve 106 as indicated in FIG. 15 the inner ring part 110 moves to an appropriate side clamping the sleeve 106 at that opposite side while allowing local manipulation of the gripped section of sleeve allowing the local retraction force at the gripped side to be optimised prior to anchoring of the sleeve at that side. This procedure may be repeated at other local regions of the sleeve 106.

Referring to FIGS. 16 to 23 there is illustrated another wound retractor 150 according to the invention which is simi-

lar to the wound retractor 101 described with reference to FIGS. 1 to 13 and like parts are assigned the same reference numerals in FIGS. 16 to 23.

In this case the guide means comprises the inner ring part 110 and an outer PTFE ring part 151 configured so that the outer ring part 151 engages the inner ring part 110 at a plurality of discrete points circumferentially spaced around the outer ring part 151 to clamp the sleeve 106 between the inner and outer ring parts 110, 151 at each discrete point. The outer ring part 151 comprises a plurality of interconnected segments 155 circumferentially spaced around the outer ring part 151 which press on the inner ring part 110 to clamp the sleeve 106 and are independently movable to facilitate localised release of the sleeve 106 for adjustment of the retraction force. Cut-out T-slots 156 are provided between the segments 155 and a main body 158 of the outer ring part 151, and handles 160 project radially outwardly of the main body 158 of the outer ring part 151 intermediate the segments 155.

In use, adjacent handles 160 are manually gripped as illustrated in FIG. 20 to apply a release force in the direction of arrows A which in turn pulls the local segment 155 in the direction of arrow B from a rest position clamping the sleeve 106 (FIGS. 20 and 21) to a release position (FIGS. 22 and 23) in which the sleeve 106 is readily pulled and manipulated locally. By releasing the clamp between the inner ring part 110 and the segment 155 the elastomeric sleeve 106 is readily slid from one position to another. This arrangement is particularly advantageous to facilitate local manipulation of the retraction force.

In general, the wound retractor 150 according to the invention is employed by inserting the inner O-ring 105 into a wound opening 103 and pulling the sleeve 106 so that the inner O-ring 105 lies flat against the interior anatomical surface. The inner O-ring 105 anchors the retractor 150 in the wound and prevents the elastomeric sleeve 106 from slipping out of the wound opening 103. The guide means clamp is then released by squeezing handles 160 and the ring parts 110, 151 are slid down the elastomeric sleeve 106 until they come into contact with the exterior anatomical surface. Retraction is achieved by pulling the sleeve 106 to shorten the distance between the inner O-ring 105 and the ring parts 110, 151 and thereby displace the elastomeric sleeve 106 laterally and with it the margins of the wound opening 103. The elastomeric sleeve 106 is anchored to maintain retraction of the wound opening 103 by releasing the handles 160 of the outer ring part 151 to clamp the sleeve 106.

The wound refractors according to the invention also provides a platform on which a wide range of devices may be mounted. In one case the platform is provided by an inner projection part of the inner ring part 110 on which a ring part 171 with a complementary recess 172 may be easily fitted somewhat in the manner of a snap-type engagement. Various devices may be provided with such a ring part 171. For example, as illustrated in FIGS. 24 and 25 the device may be a hand access device 175 for use in laparoscopic surgery. Alternatively the device may be a drape 180 (FIGS. 26 and 27) or a form retaining device 185 which is manipulated to the form of, for example, an organ 187 to be held back and from which air is then evacuated along an evacuation line 186 to retain the desired organ holding configuration (FIGS. 28 and 29).

The platform may alternatively be provided by a clamp 200 as illustrated in FIGS. 30 to 32. The clamp 200 comprises an upper jaw 201, a lower jaw 202, a clip 203 and an arm 204.

The clamp 200 is assembled by screwing the clip 203 to the base of the lower jaw 202, sliding the upper jaw 201 over the lower jaw 202 to engage the male projecting parts 208 within

the corresponding female recesses **209** and extending the arm **204** through the open mouth **207** between the upper and lower jaws **201**, **202**. A plurality of teeth **205** are provided on the arm **204**, the teeth **205** being sized to project upwardly through a recess **206** in the upper jaw **201** when the arm **204** is within the open mouth **207**. The teeth **205**, as shown more clearly in FIG. **31**, are shaped such that the arm **204** may be pulled back through the open mouth **207** in a ratchet-type arrangement but cannot be pushed forward again. A suitable material for the clamp components **201**, **202**, **203**, **204** is spring steel.

Various devices may be attached to the free end of the arm **204**, such as the form retaining device **185**, as illustrated in FIG. **30**. In use, the clip **203** is securely fixed to the wound retractor **101** by a snap-fit arrangement with the form retaining device **185** extending into the wound opening **103**, as illustrated in FIG. **31**. The form retaining device **185** is then ratcheted laterally across the wound opening **103** to retract, for example, an internal organ **220**. The ratchet configuration of the clamp **200** and the rigidity of the form retaining device **185** ensure that the internal organ **220** is securely maintained in a desired position.

It will be appreciated that any of the embodiments of the wound retractor according to the invention may be used as a platform on which to mount other devices for use in various surgical procedures. Such devices may include: a capping device to cover the incision site or orifice; a hand-access device to allow the surgical procedure to be converted from an open procedure into a hand-assisted laparoscopic procedure; an instrument port for the insertion of instruments; a trocar for use in laparoscopic surgery; an internal organ retractor to assist in the displacement of internal structures from the operative field; or an illuminating means to deliver illumination to an area shaded from the theatre lights. It will be clear to those skilled in the art that the enhancements are not limited to the brief list mentioned here.

The wound retractor may be constructed in other annular shapes. For example the distal and proximal rings attached to the elastomeric sleeve may be oval or elliptical instead of circular.

The retractor may be used to retract and protect the margins of a natural bodily orifice such as the anus or vagina, or can be used to retract and protect the edges of a man-made stoma such as is created for tracheostomy or following gastrointestinal surgery.

The invention is not limited to the embodiments hereinbefore described which may be varied in both construction and detail.

The invention claimed is:

1. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures, comprising:

making an incision in a patient;

providing a wound retractor system including a distal ring, a proximal ring, a sleeve extending between the distal ring and the proximal ring and fixedly coupled to both the proximal ring and distal ring, and a proximal receiver including a recess;

inserting the distal ring through the incision such that the sleeve extends through the incision and the proximal ring is located outside of the incision;

retracting the incision with the sleeve;

coupling a portion of the proximal ring to the recess of the proximal receiver so that the receiver restricts movement of the proximal ring and an actual length of the sleeve between the distal ring and the proximal receiver is shortened; and

coupling a hand access device to the proximal receiver.

2. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **1**, wherein the coupling of a hand access device to the proximal receiver includes a snap-type engagement.

3. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **1**, wherein the coupling of a portion of the proximal ring to the recess includes coupling the proximal ring to a plurality of recesses of the proximal receiver.

4. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **1**, wherein the retracting of the incision includes inverting at least a portion of the sleeve prior to said coupling of a portion of the proximal ring to the recess of the proximal receiver.

5. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **4**, wherein the coupling of a portion of the proximal ring to the recess helps to maintain the inverted portion of the sleeve in an inverted state.

6. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures, comprising:

making an incision in a patient;

providing a wound retractor system including a distal ring, a proximal ring, a sleeve extending between the distal ring and the proximal ring and fixedly coupled to both the proximal ring and distal ring, and a proximal receiver including a recess;

inserting the distal ring through the incision such that the sleeve extends through the incision and the proximal ring is located outside of the incision;

retracting the incision with the sleeve; and

inverting at least a portion of the sleeve prior to coupling a portion of the proximal ring to the recess of the proximal receiver so that the receiver restricts movement of the proximal ring and an actual length of the sleeve between the distal ring and the proximal receiver is shortened.

7. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **6**, further including coupling a hand access device to the proximal receiver.

8. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **7**, wherein the coupling of a hand access device to the proximal receiver includes a snap-type engagement.

9. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **6**, wherein the coupling of a portion of the proximal ring to the recess includes bringing the sleeve into engagement with the proximal receiver.

10. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **6**, wherein the coupling of a portion of the proximal ring to the recess includes drawing the portion of the sleeve beyond a proximal end of the proximal receiver.

11. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **6**, wherein the coupling of a portion of the proximal ring to the recess helps to maintain the inverted portion of the sleeve in an inverted state.

12. A method of retracting and sealing an incision for hand-assisted laparoscopic procedures according to claim **6**, wherein the coupling of a portion of the proximal ring to the recess includes bringing the proximal ring into direct contact with the recess.

专利名称(译)	牵开器		
公开(公告)号	US7445597	公开(公告)日	2008-11-04
申请号	US10/374523	申请日	2003-02-27
[标]申请(专利权)人(译)	阿特波斯有限公司		
申请(专利权)人(译)	阿特洛波斯有限公司		
当前申请(专利权)人(译)	阿特洛波斯有限公司		
[标]发明人	BUTLER JOHN YOUNG DEREK WILLIAM GILL AOIBHEANN REID ALAN BONADIO FRANK		
发明人	BUTLER, JOHN YOUNG, DEREK WILLIAM GILL, AOIBHEANN REID, ALAN BONADIO, FRANK		
IPC分类号	A61B1/32 A61B17/00 A61B17/02 A61B17/34		
CPC分类号	A61B1/32 A61B17/0293 A61B17/3423 A61B2017/00557 A61B17/3431 A61B17/3421 A61B90/50 A61B17/0206 A61B17/0218 A61B2017/00265 A61B2017/0225 A61B2017/3419 A61B2017/3429 A61B2017/3488 A61B2017/3492		
优先权	19990861 1999-10-14 IE 19991053 1999-12-16 IE 2000650010 2000-02-18 EP		
其他公开文献	US20040049100A1		
外部链接	Espacenet USPTO		

摘要(译)

用于缩回伤口开口 (103) 的边缘的牵开器 (101) 包括在远端处连接到圆柱形套管 (106) 的内部锚固O形环 (105) 和连接到其上的加强O形环 (109) 。套管 (106) 的近端。套筒 (106) 在内环部分 (110) 和外环部分 (111) 中的相应凹部 (116) 之间引导。外环部分 (111) 具有锚定结构 (120) ，套管 (106) 的近端附接在锚定结构 (120) 上以锚定套管 (106) 。为了缩回伤口开口 (103) ，拉动套管 (106) ，同时引导环 (110,111) 抵靠伤口开口 (103) 周围的组织移动。这将内O形环 (105) 拉向与伤口开口 (103) 相邻的组织内侧，并使伤口开口 (103) 缩回。套筒 (106) 被局部操纵以获得最大的收缩效率。

