



US008043248B2

(12) **United States Patent**
Pasricha

(10) **Patent No.:** **US 8,043,248 B2**
(45) **Date of Patent:** **Oct. 25, 2011**

(54) **METHOD FOR SECURING A BARRIER
DEVICE WITHIN THE GASTROINTESTINAL
TRACT AND INTEGRAL COMPONENT FOR
SAME**

(75) Inventor: **Pankaj Jay Pasricha**, Cupertino, CA
(US)

(73) Assignee: **The Board of Trustees of the Leland
Stanford Junior University**, Palo Alto,
CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 387 days.

(21) Appl. No.: **12/416,932**

(22) Filed: **Apr. 2, 2009**

(65) **Prior Publication Data**

US 2010/0256654 A1 Oct. 7, 2010

(51) **Int. Cl.**
A61M 5/00 (2006.01)
A61B 17/00 (2006.01)

(52) **U.S. Cl.** **604/8; 604/9; 606/139**

(58) **Field of Classification Search** **604/8-10,**
604/96.01; 600/37; 606/151, 191; 623/23.64-23.68
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,025,791 B2 * 4/2006 Levine et al. 623/23.64
7,074,229 B2 7/2006 Adams et al.
7,288,101 B2 10/2007 Deem et al.

2004/0243152 A1 12/2004 Taylor et al.
2004/0249362 A1 12/2004 Levine et al.
2005/0055038 A1 3/2005 Kelleher et al.
2005/0075653 A1 4/2005 Saadat et al.
2005/0075654 A1 4/2005 Kelleher
2005/0192615 A1 9/2005 Torre et al.
2007/0135825 A1 * 6/2007 Binmoeller 606/153
2008/0125797 A1 5/2008 Kelleher
2008/0200930 A1 8/2008 Saadat et al.

FOREIGN PATENT DOCUMENTS

WO WO 2007/038715 4/2007

OTHER PUBLICATIONS

Seaman et al., "Tissue anchors for transmural gut-wall apposition,"
Gastrointestinal Endoscopy. vol. 64, Issue 4, pp. 577-581 (Oct. 2006)
(Abstract of article provided, sheets 1-3).

Kuroiwa et al., "Usefulness of Introducer Technique Combined with
a Commercially Available Anchoring Device for Percutaneous
Endoscopic Gastrostomy;" Pediatric Endosurgery and Innovative
Techniques. vol. 6, Issue 1, pp. 35-40 (2002). (Brief paper of article
provided, sheets 1-3).

* cited by examiner

Primary Examiner — Leslie Deak

Assistant Examiner — Philip Wiest

(74) *Attorney, Agent, or Firm* — Neal Marcus

(57) **ABSTRACT**

A method is disclosed for creating an anchor within the gas-
trointestinal tract for supporting a barrier device therein. The
gastrointestinal tract has a first wall, a second wall and a body
lumen. The method comprises advancing an anchoring device
through the first wall and the second wall, threading the
barrier device over the anchoring device and advancing the
barrier device into the body lumen, and forming a closed loop
with the anchoring device for supporting the barrier device.

9 Claims, 17 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17





FIG. 18

1

METHOD FOR SECURING A BARRIER DEVICE WITHIN THE GASTROINTESTINAL TRACT AND INTEGRAL COMPONENT FOR SAME

FIELD OF THE INVENTION

The present invention relates to method of securing a barrier device within the gastrointestinal tract and an integral component for the same.

BACKGROUND OF THE INVENTION

It estimated that almost twenty four million people in the United States have diabetes. The most common form of diabetes is type 2 diabetes. In adults, 90 to 95% of the people with diabetes have type 2 diabetes. Type 2 diabetes is a chronic condition that affects the way the body metabolizes sugar (glucose), the body's main source of fuel. With type 2 diabetes, the body is resistant to the effects of insulin or the body produces some insulin, but in insufficient amounts to maintain a normal glucose level. This is known as insulin resistance. (Insulin is a hormone that regulates the absorption of sugar into the body.) If type 2 diabetes is left untreated, the consequences can be deadly. Unfortunately, type 2 diabetes is on the rise. This is fueled largely by the current obesity epidemic.

In recent years, the medical community has made inroads in the fight against type 2 diabetes. Specifically, gastric bypass studies in rats and humans have shown that an endoscopically implanted barrier device such as a sleeve within the lumen of the duodenum causes a marked reduction in insulin dependence and hence a greater improvement in the control of type 2 diabetes. In short, the sleeve acts as a barrier to prevent nutrients from being absorbed by the lining of the duodenum. Current methods for securing the barrier sleeve within the lumen involve anchoring the device to the wall of the gastrointestinal tract. In this approach, the sleeve is actually implanted into tissue of the wall using clips, sutures, struts, barbs or other implantable anchoring devices. However, this method of securing the sleeve has not been effective over the long term. In some circumstances, the sleeve has dislodged after implantation and has migrated down into the gastrointestinal tract. In other circumstances, the specific areas in which the sleeve is implanted have become inflamed, and removal has become difficult. Dislodgement and/or inflammation cause serious complications for the patient.

It would be therefore desirable to offer a solution that would overcome the disadvantages of the method described above.

SUMMARY OF THE INVENTION

In accordance with an embodiment of the present invention, a method is disclosed for creating an anchor within the gastrointestinal tract for supporting a barrier device therein. The gastrointestinal tract has a first wall, a second wall and a body lumen. The method comprises advancing an anchoring device through the first wall and the second wall, threading the barrier device over the anchoring device and advancing the barrier device into the body lumen, and forming a closed loop with the anchoring device for supporting the barrier device.

In accordance with another embodiment of the present invention, a method is disclosed for creating an anchor within the gastrointestinal tract for supporting a barrier device therein. The gastrointestinal tract has a stomach and duode-

2

num, each having a wall defining a lumen. The method comprises advancing an anchoring device through the duodenum wall and the stomach wall, threading the barrier device over the anchoring device and advancing the barrier device into the duodenum lumen, and forming a closed loop with the anchoring device for supporting the barrier device within the duodenum lumen.

In accordance with another embodiment of the present invention, a method is disclosed for creating an anchor within the gastrointestinal tract for supporting a sleeve, the gastrointestinal tract having a stomach and duodenum, each having a lumen and a wall. The method comprises introducing a guide wire through the duodenum wall and stomach wall, advancing an anchoring device over the guide wire through the stomach wall and the duodenum wall, threading the sleeve over the anchoring device and advancing the sleeve into the duodenum lumen, and forming a closed loop with the anchoring device for supporting the sleeve within the duodenum lumen.

In accordance with another embodiment of the present invention, a method is disclosed for creating an anchor within the gastrointestinal tract for supporting a barrier device therein. The gastrointestinal tract has a first wall, a second wall and a body lumen. The method comprises advancing an integral component through the first wall and the second wall, the integral component being configured to include the barrier device and an anchoring device, advancing the integral component to position the barrier device within the body lumen, and forming a closed loop with the anchoring device for supporting the barrier device within the body lumen.

In accordance with yet another embodiment of the present invention, an integral component is disclosed that is adapted to be delivered within a body. The component comprises a barrier device for preventing the absorption of food products within a body lumen of the body and an anchoring device for supporting the barrier device within the body lumen.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a block diagram of the steps of the method of securing a barrier device within the gastrointestinal tract in accordance with present invention.

FIGS. 2-12 depict cross-sectional views of the gastrointestinal tract corresponding to the steps of the method depicted in FIG. 1.

FIGS. 13-16 depict cross-sectional view of the gastrointestinal tract illustrating steps of the method in accordance with an alternative embodiment of the present invention.

FIG. 17 depicts a cross-sectional view of the gastrointestinal tract similar to FIG. 16 but illustrating an alternative embodiment of the anchoring and barrier device.

FIG. 18 depicts a cross-sectional view of the deployed barrier device illustrated in FIG. 17.

DETAILED DESCRIPTION

FIG. 1 depicts a block diagram of the steps of the method for securing a barrier sleeve within the gastrointestinal tract. FIGS. 2-12 depict cross-sectional views of the gastrointestinal tract corresponding to the steps of the method shown in FIG. 1, and such FIGS. 2-12 will be discussed as they correspond to the steps of the method depicted in FIG. 1.

In accordance with one illustrative embodiment, steps 200-1100 are performed sequentially, but it will be clear to those skilled in the art, after reading this disclosure, how to make

and use alternative embodiments of the present invention in which some of the steps 200-1100 are performed in a different order.

At step 200, a medical doctor (typically a surgeon), will introduce a delivery apparatus into the gastrointestinal tract. Reference is made to FIGS. 2 and 3 in which esophagus 22, stomach 24 and duodenum 26 of the gastrointestinal tract are shown. Note, however, that only a portion of esophagus 22 is shown. As part of step 200, the doctor will advance endoscope 28 into a patient's mouth (not shown), down esophagus lumen 30 through stomach lumen 32, and into duodenum lumen 34. (Esophagus lumen 30, stomach lumen 32, and duodenum lumen 34 are all body lumens of the gastrointestinal tract.) Next, as part of step 200, the doctor will advance guide wire 36 through stomach lumen 32 and into duodenum lumen 34 via endoscope 28. As known to those skilled in the art, endoscope 28 has a lumen that extends from the proximal end (proximate the mouth) to a distal end thereof (proximate the delivery site) for receiving and advancing guide wire 30. Guide wire 36 is actually inserted into endoscope 22 into the lumen thereof for such advancement into the gastrointestinal tract. End 36a of guide wire 36 is shown adjacent the delivery site of duodenum lumen 34 in FIG. 3.

Note that the steps of the method shown in FIG. 1 are described herein as being performed by one doctor, but one skilled in the art will know, after reading this disclosure, that one or more steps of this method may be performed by more than one doctor or medical professional (under the care and supervision of a doctor).

As discussed herein, the introduction of the delivery apparatus includes the step of advancing the endoscope 28 and the guide wire 36. However, those skilled in the art, after reading this disclosure, know that the step of introducing a delivery apparatus disclosed herein may refer to the step of advancing an endoscope or a guide wire individually or in combination, and/or some other device(s) to achieve desired results (i.e., to advance anchoring device 42 and barrier device 44 as discussed below). Such a device(s) may be one or more laparoscopic devices (also known to those skilled in the art) or another device. This is discussed in more detail below.

At step 300, the doctor will pierce duodenum wall 36 and then stomach wall 28 with end 36a of guide wire 36. In an alternative embodiment, the doctor may advance a needle along with guide wire 36 to the delivery site for piercing the tissue as is known to those skilled in the art. In FIG. 4, end 36a has pierced duodenum wall 38 and stomach wall 40 and has advanced into stomach lumen 32.

The doctor may not require visualization to pierce the tissue at the appropriate location on the duodenum wall 38. In this respect, the doctor will pierce a hole in the tissue by poking guide wire 36 or needle blindly against the tissue without any visualization, as shown in FIG. 4. However, visualization may be desirable. Visualization may be achieved in several ways to assist the doctor in piercing tissue at the appropriate location along duodenum wall 36 (and stomach wall 38). If the doctor desires direct visualization, he/she will introduce and advance a second endoscope (with appropriate lens/camera technology for visualization) within the gastrointestinal tract. In this respect, the second endoscope will enable the doctor to directly visualize the delivery site and duodenum wall 38.

If direct (sight) visualization is not desired, the doctor has several tools to obtain visualization indirectly. For example, the doctor may use an endoscopic ultrasound device (EUS) to obtain visualization indirectly. The EUS combines endoscopy and ultrasound to obtain images of the gastrointestinal tract to provide visualization of the delivery site as known by

those skilled in the art. In yet another alternative embodiment, the doctor may use an X-ray or a CAT scan to enable visualization. Alternatively, the doctor may use trans-reflectance illumination to provide visualization as known to those skilled in the art.

The embodiments described above are merely examples of obtaining visualization (directly or indirectly) to enable a doctor to pierce the appropriate tissue for this procedure. It will be, however, clear to those skilled in the art, after reading this disclosure, how to make and use alternative embodiments of the present invention to achieve visualization.

At step 400, the doctor will thread and advance anchoring device 42 over guide wire 36 via endoscope 28 through esophagus lumen 30 and stomach lumen 32 and then into duodenum lumen 34. Anchoring device 42 will be used to anchor a barrier device within duodenum lumen 34 as described in detail below. FIG. 5 illustrates anchoring device 42 in the advanced position but it has not yet passed through duodenum wall 38. In an alternative embodiment, anchoring device 42 may be threaded and advanced over a needle-guide wire combination as described above. Anchoring device 42 is preferably a soft catheter made of atraumatic elastic (stretchable) material such as polyurethane or a combination of latex and silicon materials.

At step 500, the doctor will advance anchoring device 42 through (the openings in) duodenum wall 38, stomach wall 40, and into stomach lumen 32. FIG. 6 illustrates anchoring device 42 in an advanced position through duodenum wall 38 and stomach wall 40. Distal end 42a of anchoring device 42 is shown unattached. In this embodiment of the method described with respect to FIG. 1, note that endoscope 28 is generally held in place to maintain guide wire 36 in place to enable the advancement and delivery of anchoring device 42 and the barrier device 44 (described below) into position.

At step 600, the doctor will thread barrier device 44 over anchoring device 42 and guide wire 36 through endoscope 28. Hence, barrier device 44 is advanced through esophagus lumen 30 and stomach 32, and then passed out endoscope 28 to the delivery site within duodenum lumen 34. Barrier device 44 is shown in FIG. 7 partially exiting endoscope 28, and fully deployed in FIG. 8. Barrier device 44 may be advanced through endoscope 28 using (i.e., with the assistance of) a separate collapsible/expandable tube or similar device (not shown). The doctor will advance the tube within endoscope 28 over anchoring device 42 behind barrier device 44 to force it through and out endoscope 28. At the same time, the doctor will begin to withdraw endoscope 28 to allow barrier device 44 to completely exit endoscope 28. In this respect, barrier device 44 is deployed (positioned) to the proper location using endoscope 28 (itself). Alternatively, a doctor may use a second endoscope (not shown) to assist in the deployment from endoscope 28 and proper placement of the barrier device 44.

In this embodiment, barrier device 44 is a flexible sleeve that is self-expanding as it departs from endoscope 28. As known by those skilled in the art, the self-expanding characteristic may be achieved using a stent or other expandable structure that is embedded within the sleeve material. The sleeve can be collapsed into a small enough diameter (typically less than 1/4 inch) to enable endoscopic delivery.

In the embodiment of the method described with respect to FIG. 1, the sleeve is maintained in place without any extra assistance while the remaining steps of the method are performed (including forming a closed loop as described below). However, in some other circumstances, a balloon apparatus may be employed within the sleeve to prevent migration while the other remaining steps of the method are performed.

In practice, a second endoscope (not shown) equipped with appropriate balloon apparatus (e.g., a balloon and inflating channel/tube as known by those skilled in the art) will be used to deploy and expand the balloon inside the sleeve to hold the sleeve in place.

The sleeve is constructed of a synthetic material that is typically thin and comfortable as well as a low coefficient of friction (less than 0.20) so that chyme slides easily through it while allowing bile to slide around it. (Chyme is a liquid mass of partially digested food that passes from the stomach through the pyloric sphincter into the duodenum). The sleeve is of low permeability to fluids so that the chyme does not touch duodenum wall **38** and the digestive enzymes do not significantly break down the chyme. The synthetic material is biologically inert and non-irritating to the body tissues. Examples of the materials include polytetrafluoroethylene (ePTFE), a fluoropolymer with a wall thickness of about 0.0006 inches. Another material may be polyethylene with a wall thickness of less than 0.001 inches. Other materials (and thicknesses) may be used as well to achieve desired results. The material may be coated in the inside and/or outside of the sleeve as required.

As described above, the length of the sleeve is selected to bypass duodenum **26**. The length, however, is increased to further decrease absorption within duodenum **26** by bypassing a longer section (e.g., including the jejunum of the gastrointestinal tract). The length of the sleeve is variable and dependent on the patient's Body Mass Index (BMI). In practice, the sleeve length ranges from about 10 to 25 centimeters (cm) and width ranges from 8 to 15 millimeters (mm) for delivery within duodenum lumen **34** (typically between the pyloric region of stomach **24** and the jejunum). The typical length of the sleeve is about 20 cm and the width is about 10 millimeters. However, any length and width may be used to achieve desired results as known by those skilled in the art. The sleeve can be marked on the exterior surface thereof to help detect the position and orientation of the sleeve on a fluoroscopic image.

In accordance with one illustrative embodiment, barrier device **44** is a sleeve that is sized, shaped and constructed as described herein, but it will be clear to those skilled in the art, after reading this disclosure, how to make and use alternative embodiments of the present invention in which the type, size, shape and construction (including materials) of barrier device **44** may differ to achieve desired results.

As described above, the sleeve (barrier device **44**) is deployed using a separate tube via endoscope **28**. However, for sleeves of sufficient size, a doctor may be unable to use an endoscope for actual delivery of the sleeve. In this case, the doctor will remove endoscope **28** and deliver the sleeve over anchoring device **42** as known by those skilled in the art. In this respect, the doctor may use another endoscope with a clamp to push the sleeve down. Alternatively, the doctor may thread and advance a tube over anchoring device **42** to engage and push the sleeve to the delivery site. As indicated above, the procedure provides a treatment approach for type 2 diabetes.

Returning to FIG. 1 wherein step **800** of the method is performed, the doctor removes guide wire **36** from endoscope **28**, but the anchoring device **42** remains within the gastrointestinal tract. This is shown in FIG. 9.

At step **900**, a closed loop is formed with anchoring device **42** by securing distal end **42a** of anchoring device **42** to a portion thereof within stomach lumen **32**. Reference is made to FIG. 10. The doctor performs this step using a second endoscope, i.e., endoscope **46**. The doctor introduces endo-

scope **28**. Note that endoscope **28** is shown retracted or partially withdrawn to expose the necessary portion of anchoring device **42** to enable the doctor to make the closure loop. (In an alternative embodiment, the doctor may remove endoscope **28** entirely at this point, as long as distal end **42a** is firmly grasped as described below.)

At this point, the doctor uses a clamping mechanism **46a** of endoscope **46**, as known to those skilled in the art, to grasp distal end **42a** of anchoring device **42**. Distal end **46a** can be secured to a portion of anchoring device **42** (to form a closed loop or ring) by several methods. In one method, distal end **42a** may be secured by a snap on device such as a mechanical clip or clamp such as an "alligator" clamp wherein the jaws may be activated or expanded to receive the anchoring device **42** or a "paper clip" type device. Alternatively, distal end **42a** may be secured to anchoring device **42** using cinching device as known by those skilled in the art or an adhesive (e.g., glue or Velcro like material). The glue material may be acrylate for example. On the other hand, distal end **42a** may be thermally secured to anchoring device **42** to form a loop. In this respect, distal end **42a** will be heated to melt it to anchoring device **42**. The closure is all accomplished endoscopically as known by those skilled in the art. (FIGS. 13-16 illustrate alternate steps for obtaining a closed loop by securing the distal end **42a** to the body of anchoring device **42**. This is discussed below.)

At step **1000**, the doctor will remove the residual portion of anchoring device **42** outside of the closed loop, by manipulating the clamping mechanism and clipping the anchoring device **42** above the point at which distal end **42a** is secured. This is shown in FIG. 11 (except the remaining part of anchoring device **42** is shown about to be removed). (Note that the clamping mechanism includes the clipping mechanism but a separate clipping mechanism may be employed.)

At step **1100**, the doctor removes endoscope **28** and endoscope **46** from the gastrointestinal tract of the patient to complete the procedure. The closed loop (of anchoring device **42**) is shown in FIG. 12. The tissue surrounding anchoring device **42** within duodenum wall **38** and stomach wall **40** eventually grows around and to anchoring device **42**.

Reference is made to FIGS. 13-16 wherein a closed loop is formed (step **900**) by securing the distal end **42a** of anchoring device **42** to the body thereof in accordance with an alternative embodiment of the present invention. (For this embodiment, however, steps **200-800** are the same as identified in FIG. 1. Therefore, these steps will not be discussed herein.) In this alternative embodiment, step **900** is performed, but with some variation to achieve loop closure as follows. As indicated above with respect to step **900**, the doctor performs this step using a second endoscope, i.e., endoscope **46**. The doctor introduces endoscope **46** within the gastrointestinal tract in a similar manner as endoscope **28**. The doctor uses a clamping mechanism **46a** of endoscope **46**, as known to those skilled in the art, to grasp distal end **42a** of anchoring device **42**. This is shown in FIG. 13. In this alternative embodiment, however, endoscope **46** is used to pull distal end **42a** upwardly through stomach **24**, esophagus **22** and out the patient's mouth. Now, both ends of anchoring device **42** extend out of the patients mouth as shown in FIG. 14 (mouth not shown).

At this point, endoscope **28** is removed. Note, however, that endoscope **28** could have been removed immediately after endoscope **46** clamped distal end **42a**. Alternatively, the doctor may remove endoscope **28** immediately after the doctor removed guide wire **36**, but before he/she clamps distal end **42a** with clamping mechanism **46a**. In this respect, the distal end **42a** is sufficiently advanced into stomach lumen **32** to ensure that anchoring device does not retract though the pierced holes in stomach wall **40** and duodenum wall **38** while

endoscope **28** is being removed. These are illustrative embodiments for deploying and retrieving both ends of anchoring device **42** out a patient's mouth. Those skilled in the art will know that there are other ways in which a doctor may properly deploy and obtain both ends of anchoring device **42** out of the patient's mouth.

Now, at the next step, the doctor will actually create a loop with anchoring device. In particular, the doctor makes a loose knot with distal end **42a** around the upper portion of anchoring device **42** and uses clamp **46a** of endoscope **46** to push the loose knot down esophagus **22** into stomach **24**. The doctor will attempt to remove any excess slack by pushing the knot down the length of anchoring device **42**. At the next step, the doctor uses clamp **46a** to tighten the knot, and then cuts the anchoring device **46** above the knot to remove the residual portion of anchoring device **42**. This is similar to the description of step **1000** set forth above. The doctor will then remove endoscope **46**. While a knot is described herein, those skilled in the art, after reading this disclosure, know that a similar effect may be achieved use a ring for securing distal end **42a** of anchoring device **42** to the body thereof within stomach lumen **32**.

It will also be clear to one skilled in the art, after reading this disclosure, that the step of forming a closed loop with anchoring device **42** may be accomplished in other ways. For example, anchoring device **42** may be advanced as described in FIG. 1, but both ends of anchoring device **42** may be located within stomach lumen **32** and held in place using two independent endoscopes (clamps). These ends may be attached together using similar means described above, e.g., adhesive, Velcro like material, knot, etc. Thus, one end will be attached to a portion of anchoring device **42** as described above, but in this case, the portion will be the other end of anchoring device **42**. In this respect, there will be no residual portion of anchoring device to cut and remove. The specific steps and the order in which they are performed may vary to form the closed loop in accordance with the method of present invention.

Alternatively, a closed loop may be formed with anchoring device **42** by securing it through the wall of duodenum **26** only. For example, duodenum **28** will be pierced in two separate points along duodenum wall **38** for the advancement of anchoring device **42**. In this respect, anchoring device **42** will anchor (i.e., support) barrier device **42** by means of duodenum **26** (only). Those skilled in the art, after reading this disclosure, know that other variations exist to achieve the same result.

It will be clear to those skilled in the art that while one or two endoscopes are used for the embodiments described above, a single scope may be used with dual (or multiple) channels to achieve some or all of the steps described above (when an endoscope is required). It will be also clear to those skilled in the art, after reading this disclosure, that while the embodiments described above employ a method wherein anchoring device **42** is advanced through duodenum wall **38** and subsequently stomach wall **40**, anchoring device **42** may alternatively be advanced through stomach wall **40** first and then through duodenum wall **38** (or other body portions to achieve desired results).

In the embodiments of the method described herein in accordance with the present invention, the position of barrier device **44** is actually maintained (secured) in place within duodenum lumen **34**. That is, the distal end of anchoring device **42** (adjacent the pierced duodenum wall **38**) prevents barrier device **44** from migrating downstream. Conversely, the proximal end of anchoring device **42** and the general anatomy of the gastrointestinal tract prevents barrier **44** from

moving upstream within the gastrointestinal tract. In addition, it is noted that anchoring device **42** is used as the sole device or anchor for supporting barrier device **44** within the gastrointestinal tract. No other devices are needed to maintain the device within the gastrointestinal tract. The application of the anchoring device **42** as the sole support simplifies the procedure, and also reduces the incidence of tissue damage and inflammation.

FIG. 17 depicts a cross-sectional view of the gastrointestinal tract similar to FIG. 16 but illustrates an alternative embodiment of the anchoring device and barrier device. In particular, anchoring device **52** and barrier device **54** are shown deployed within the duodenum lumen **34**. In this embodiment, however, anchoring device **52** and barrier device **54** are constructed as one integral component **50** that is delivered and secured in place in a similar manner as discussed above with respect to the method steps in FIG. 1.

In brief, a doctor will perform steps **200** and **300**, and the doctor will then advance the integral component **50** over a guide wire via an endoscope through the stomach lumen and into the duodenum. In this case, barrier device **54**, as an integral part of component **50**, is compressed within the endoscope. The guide wire is removed (step **800**) and, as integral component **50** is advanced, barrier device **54** will decompress/expand as it is released from the endoscope. Note that the integral component is sufficiently advanced to position barrier device **54** within the duodenum lumen **34**. A loop is formed with anchoring device as described above with respect to step **900** as known by those skilled in the art. The doctor will remove the residual portion of anchoring device **52** of integral component **50** and then remove the endoscope from the gastrointestinal tract similar to steps **1000** and **1100**, respectively. However, those skilled in the art know that variations in this method (that include different or additional steps or less steps) will produce the same results, i.e., deliver and secure barrier device **54** within the gastrointestinal tract. Note that anchoring device **52** and barrier device **54** (of integral component **50**) may be constructed of the same or difference materials to achieve desired results. Examples of the materials are described above.

FIG. 18 depicts a cross-sectional view of the deployed barrier device **54** (as part of integral component **50**) illustrated in FIG. 17.

As discussed above, the method for securing a barrier device within the gastrointestinal tract may alternatively employ a laparoscopic device for one or more of the steps of the method. That is, the laparoscopic device may be used to effect desired results without using an endoscope or may be used in combination with an endoscope. In one exemplary circumstance, a laparoscopic device may be used to assist in the threading of an anchoring device over a guide wire between the duodenum and stomach. That is, a doctor (endoscopic operator) would push the guide wire and/or needle out of the duodenum and the same or different doctor (i.e., laparoscopic operator) would grasp the guide wire with the laparoscopic device and pierce the stomach wall and place it in the stomach lumen. The laparoscopic device will also assist with the deployment of the anchoring device. That is, the doctor will pull the end of the anchoring device over the guide wire into the stomach lumen.

In another exemplary circumstance, a laparoscopic device may be used for loop closure within the stomach after the barrier device is properly positioned. That is, as known by those skilled in the art, the loop closure may be accomplished using the laparoscopic device to assist in tying the knot as described above. Once the anchoring device is secured, the tissue openings may be closed by the doctor. While two

9

exemplary circumstances have been described hereinabove with respect to the laparoscopic device, those skilled in the art, after reading this disclosure, know that a laparoscopic device may be used to perform other the steps of the method for securing a barrier device within the gastrointestinal tract as disclosed in this application.

As discussed above, those skilled in the art, after reading this disclosure, know that the step of introducing the delivery apparatus may refer or include the step of advancing or introducing an endoscope, a guide wire, a laparoscopic device or other device individually or any combination of these devices. Also, the delivery apparatus disclosed herein may refer or include an endoscope, a guide wire, a laparoscopic device or other device individually or any combination of these devices.

It is to be understood that the disclosure teaches examples of the illustrative embodiments of the present invention and that many variations of the invention can easily be devised by those skilled in the art after reading this disclosure and that the scope of the present invention is to be determined by the following claims.

What is claimed is:

1. A method for creating an anchor within a gastrointestinal tract for supporting a barrier device therein, the gastrointestinal tract having a stomach and a duodenum, each having a wall defining a lumen, the method comprising:

advancing an anchoring device through the duodenum wall and the stomach wall;

threading the barrier device over the anchoring device and advancing the barrier device into the duodenum lumen; and

forming a closed loop with the anchoring device for supporting the barrier device within the duodenum lumen.

2. The method of claim 1 wherein the anchoring device is a soft catheter.

10

3. The method of claim 1 wherein the barrier device is a flexible sleeve sized so as to substantially prevent the absorption of food products within the body lumen.

4. The method of claim 1 further comprising introducing a delivery apparatus into the gastrointestinal tract, wherein introducing a delivery apparatus includes advancing an endoscope within the stomach lumen.

5. The method of claim 4 wherein introducing a delivery apparatus further includes advancing a laparoscopic device into the duodenum lumen.

6. The method of claim 1 wherein the forming a closed loop including attaching an end of the anchoring device to a portion thereof.

7. The method of claim 1 further comprising introducing a delivery apparatus into the gastrointestinal tract, wherein introducing a delivery apparatus includes introducing a guide wire through the duodenum wall and stomach wall.

8. The method of claim 1 further comprising introducing a delivery apparatus into the gastrointestinal tract, wherein introducing a delivery apparatus includes advancing a laparoscopic device into the duodenum lumen.

9. A method for creating an anchor within a gastrointestinal tract for supporting a sleeve, the gastrointestinal tract having a stomach and a duodenum, each having a lumen and a wall, the method comprising:

introducing a guide wire through the duodenum wall and stomach wall;

advancing an anchoring device over the guide wire through the stomach wall and the duodenum wall;

threading the sleeve over the anchoring device and advancing the sleeve into the duodenum lumen; and

forming a closed loop with the anchoring device for supporting the sleeve within the duodenum lumen.

* * * * *

专利名称(译)	用于将屏障装置固定在胃肠道内的方法和用于该屏障装置的整体部件		
公开(公告)号	US8043248	公开(公告)日	2011-10-25
申请号	US12/416932	申请日	2009-04-02
[标]申请(专利权)人(译)	斯坦福大学		
申请(专利权)人(译)	THE利兰·斯坦福，齐齐哈尔大学董事会		
当前申请(专利权)人(译)	斯坦福大学大学，伦敦理工学院		
[标]发明人	PASRICHA PANKAJ JAY		
发明人	PASRICHA, PANKAJ JAY		
IPC分类号	A61M5/00 A61B17/00 A61F2/958		
CPC分类号	A61F5/0076 A61B2017/00818		
其他公开文献	US20100256654A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种用于在胃肠道内形成锚以在其中支撑屏障装置的方法。胃肠道具有第一壁，第二壁和体腔。该方法包括使锚固装置前进穿过第一壁和第二壁，将屏障装置穿过锚固装置并将屏障装置推进体腔内，并与锚固装置形成闭合环以支撑屏障装置。

