



US008517995B2

(12) **United States Patent**
Voegelé et al.

(10) **Patent No.:** **US 8,517,995 B2**
(45) **Date of Patent:** **Aug. 27, 2013**

(54) **ACCESS DEVICE**

(75) Inventors: **James W. Voegelé**, Cincinnati, OH (US);
Robert P. Gill, Mason, OH (US); **Aaron C. Voegelé**, Loveland, OH (US);
William B. Weisenburgh, II,
Maineville, OH (US); **Christopher J. Hess**, Cincinnati, OH (US); **William P. Geis**, Baltimore, MD (US)

(73) Assignee: **Ethicon Endo-Surgery, Inc.**, Cincinnati, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 731 days.

(21) Appl. No.: **12/579,625**

(22) Filed: **Oct. 15, 2009**

(65) **Prior Publication Data**

US 2010/0030032 A1 Feb. 4, 2010

Related U.S. Application Data

(62) Division of application No. 11/398,985, filed on Apr. 5, 2006.

(60) Provisional application No. 60/700,176, filed on Jul. 18, 2005, provisional application No. 60/669,514, filed on Apr. 8, 2005.

(51) **Int. Cl.**
A61M 5/32 (2006.01)

(52) **U.S. Cl.**
USPC **604/175**

(58) **Field of Classification Search**
USPC 604/27, 43, 93, 174, 175, 506, 96.01,
604/104, 164.1, 913, 19; 600/367, 362, 573,
600/579, 363, 576; 606/201, 202
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,129,391 A 9/1938 Wappler
3,299,883 A 1/1967 Rubens

3,402,710 A 9/1968 Paleshuck
3,503,396 A 3/1970 Pierie et al.
3,654,965 A 4/1972 Gramain
4,041,931 A 8/1977 Elliott et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2095064 9/2009
EP 0646358 4/1995

(Continued)

OTHER PUBLICATIONS

EP 0646358, Applicant: Pacesetter AB, Inventor: Staffan Bowald, date of filing Sep. 14, 1994.*

Co-pending application filed Apr. 5, 2006, U.S. Appl. No. 11/398,985.

Co-pending application filed Apr. 5, 2006, U.S. Appl. No. 11/399,172.

Co-pending application filed Apr. 5, 2006, U.S. Appl. No. 11/399,045.

Co-pending application filed Apr. 5, 2006, U.S. Appl. No. 11/399,044.

Co-pending application filed Apr. 5, 2006, U.S. Appl. No. 11/399,181.

Co-pending application filed Oct. 15, 2009, U.S. Appl. No. 12/579,625.

Co-pending application filed May 18, 2010, U.S. Appl. No. 12/781,996.

International Search Report dated Apr. 30, 2010, International Application No. PCT/US06/13456.



(Continued)

Primary Examiner — Manuel Mendez

(57) **ABSTRACT**

A surgical access device includes a base having two or more ports or apertures that provide for the insertion of surgical instruments. The multi-port insert may be used with a laparoscopic access device. The multi-port insert may also include one or more instrument supports that are attached to the base to fix the position of one or more surgical instruments inserted through the multi-port insert.

1 Claim, 78 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,048,987 A	9/1977	Hurson	5,891,013 A	4/1999	Thompson
4,112,932 A	9/1978	Chiulli	5,893,878 A	4/1999	Pierce
4,120,302 A	10/1978	Ziegler	5,906,577 A	5/1999	Beane et al.
4,306,545 A	12/1981	Ivan et al.	5,941,890 A	8/1999	Voegelé et al.
4,373,532 A	2/1983	Hill et al.	5,947,922 A	9/1999	MacLeod
4,402,683 A	9/1983	Kopman	5,957,913 A	9/1999	de la Torre et al.
4,417,888 A	11/1983	Cosentino et al.	5,971,995 A	10/1999	Rousseau
4,559,947 A	12/1985	Renger et al.	5,977,431 A	11/1999	Knapp et al.
4,669,473 A	6/1987	Richards et al.	5,990,382 A	11/1999	Fox
4,821,719 A	4/1989	Fogarty	6,007,561 A	12/1999	Bourque et al.
4,831,070 A	5/1989	McInally et al.	6,024,736 A	2/2000	de la Torre et al.
5,027,800 A	7/1991	Rowland	6,033,428 A	3/2000	Sardella
5,082,111 A	1/1992	Corbitt, Jr. et al.	RE36,702 E	5/2000	Green et al.
5,183,471 A	2/1993	Wilk	6,074,419 A	6/2000	Healy et al.
5,197,955 A	3/1993	Stephens et al.	6,077,288 A	6/2000	Shimomura et al.
5,207,213 A	5/1993	Auhll et al.	6,086,603 A *	7/2000	Termin et al. 606/191
5,209,741 A	5/1993	Spaeth	6,093,141 A	7/2000	Mosseri et al.
5,269,772 A	12/1993	Wilk	6,110,154 A	8/2000	Shimomura et al.
5,308,336 A	5/1994	Hart et al.	6,120,513 A	9/2000	Bailey et al.
5,342,315 A	8/1994	Rowe et al.	6,123,689 A	9/2000	To et al.
5,345,927 A	9/1994	Bonutti	6,126,671 A	10/2000	Richards et al.
5,362,294 A	11/1994	Seitzinger	6,132,385 A	10/2000	Vain
5,366,478 A	11/1994	Brikerhoff	6,149,642 A	11/2000	Gerhart et al.
5,368,597 A	11/1994	Pagedas	6,159,200 A	12/2000	Verdura et al.
5,385,553 A	1/1995	Hart et al.	6,165,184 A	12/2000	Verdura et al.
5,385,560 A	1/1995	Wulf	6,197,034 B1	3/2001	Gvozdic et al.
5,391,154 A	2/1995	Young	6,217,555 B1	4/2001	Hart et al.
5,398,671 A	3/1995	Ortiz et al.	6,220,248 B1	4/2001	Voegelé et al.
5,443,452 A	8/1995	Hart et al.	6,228,055 B1	5/2001	Foerster et al.
5,443,484 A	8/1995	Kirsch et al.	6,245,052 B1	6/2001	Orth et al.
5,460,170 A *	10/1995	Hammerslag 600/201	6,258,069 B1	7/2001	Carpentier et al.
5,480,410 A	1/1996	Cuschieri et al.	6,258,102 B1	7/2001	Pagedas
5,501,653 A	3/1996	Chin	6,261,302 B1	7/2001	Voegelé et al.
5,545,123 A	8/1996	Ortiz et al.	6,262,196 B1	7/2001	Mecking
5,545,179 A	8/1996	Williamson, IV	6,264,599 B1	7/2001	Slater et al.
5,547,458 A	8/1996	Ortiz et al.	6,290,705 B1	9/2001	Chan et al.
5,569,205 A	10/1996	Hart et al.	6,293,966 B1	9/2001	Frantzen
5,569,254 A	10/1996	Carlson et al.	6,315,770 B1	11/2001	de la Torre et al.
5,582,577 A	12/1996	Lund et al.	6,319,246 B1	11/2001	de la Torre et al.
5,586,977 A	12/1996	Dorsey, III	6,347,940 B1	2/2002	Gordils Wallis
5,591,182 A	1/1997	Johnson	6,348,034 B1	2/2002	Thompson
5,595,193 A	1/1997	Walus et al.	6,352,503 B1	3/2002	Matsui et al.
5,624,381 A	4/1997	Kieturakis	6,425,903 B1	7/2002	Voegelé
5,630,831 A	5/1997	Lahr	6,447,443 B1	9/2002	Keogh et al.
5,634,882 A	6/1997	Gagner	6,447,489 B1	9/2002	Peterson
5,634,911 A	6/1997	Hermann et al.	6,454,783 B1	9/2002	Piskun
5,634,937 A	6/1997	Mollenauer et al.	6,458,077 B1	10/2002	Boebel
5,636,645 A	6/1997	Ou	6,471,714 B1	10/2002	Kim
5,640,977 A	6/1997	Leahy et al.	6,485,467 B1	11/2002	Crook et al.
5,643,283 A	7/1997	Younker	6,551,270 B1 *	4/2003	Bimbo et al. 604/93.01
5,643,301 A	7/1997	Mollenauer	6,551,282 B1	4/2003	Exline et al.
5,647,372 A	7/1997	Tovey et al.	6,578,577 B2	6/2003	Bonadio et al.
5,653,705 A *	8/1997	de la Torre et al. 606/1	6,579,304 B1	6/2003	Hart et al.
5,665,093 A	9/1997	Atkins et al.	6,589,167 B1	7/2003	Shimomura et al.
5,672,168 A	9/1997	de la Torre et al.	6,605,063 B2	8/2003	Bousquet
5,676,146 A	10/1997	Scarborough	6,623,426 B2	9/2003	Bonadio et al.
5,676,657 A	10/1997	Yoon	6,634,883 B2	10/2003	Ranalli
5,681,324 A	10/1997	Kammerer et al.	6,669,674 B1	12/2003	Macoviak et al.
5,695,448 A	12/1997	Kimura et al.	6,702,787 B2	3/2004	Racenet et al.
5,716,327 A	2/1998	Warner et al.	6,706,033 B1	3/2004	Martinez et al.
5,716,407 A	2/1998	Knapp et al.	6,706,050 B1	3/2004	Giannadakis
5,728,121 A	3/1998	Bimbo et al.	6,725,083 B1	4/2004	Burbank et al.
5,735,289 A	4/1998	Pfeffer et al.	6,764,473 B2	7/2004	Morton
5,743,851 A	4/1998	Moll et al.	6,766,186 B1	7/2004	Hoyns et al.
5,772,654 A	6/1998	Leyva	6,810,880 B1	11/2004	Jennings, Jr. et al.
5,793,113 A	8/1998	Oda	6,821,247 B2	11/2004	Vierra et al.
5,813,409 A *	9/1998	Leahy et al. 128/897	6,846,287 B2	1/2005	Bonadio et al.
5,814,058 A	9/1998	Carlson et al.	6,908,430 B2	6/2005	Caldwell et al.
5,816,257 A	10/1998	Chin	6,939,296 B2	9/2005	Ewers et al.
5,827,319 A	10/1998	Carlson et al.	6,945,932 B1	9/2005	Caldwell et al.
5,840,078 A	11/1998	Yerys	6,972,026 B1	12/2005	Caldwell et al.
5,842,971 A	12/1998	Yoon	6,994,712 B1	2/2006	Fisher et al.
5,853,395 A	12/1998	Crook et al.	7,014,628 B2	3/2006	Bousquet
5,865,807 A	2/1999	Blake, III	7,052,454 B2	5/2006	Taylor
5,876,447 A	3/1999	Arnett	7,083,576 B2	8/2006	Zarins et al.
			7,118,528 B1	10/2006	Piskun
			7,163,510 B2	1/2007	Kahle et al.
			7,214,185 B1	5/2007	Rosney et al.
			7,311,661 B2	12/2007	Heinrich

7,338,473	B2	3/2008	Campbell et al.
7,344,547	B2	3/2008	Piskun
7,393,322	B2	7/2008	Wenchell
7,416,533	B2	8/2008	Gellman et al.
7,438,702	B2	10/2008	Hart et al.
7,585,288	B2	9/2009	Haberland et al.
2001/0034528	A1	10/2001	Foerster et al.
2001/0053510	A1	12/2001	Ranalli
2002/0007112	A1	1/2002	Rupp et al.
2002/0026201	A1	2/2002	Foerster et al.
2002/0038179	A1	3/2002	Tschernoster
2002/0103434	A1	8/2002	Swanbom
2002/0193815	A1	12/2002	Foerster et al.
2003/0113540	A1	6/2003	Anderson et al.
2003/0139756	A1	7/2003	Brustad
2003/0206860	A1	11/2003	Bleyer et al.
2003/0225420	A1	12/2003	Wardle
2004/0015185	A1	1/2004	Ewers et al.
2004/0024304	A1	2/2004	Foerster et al.
2004/0049100	A1	3/2004	Butler et al.
2004/0106942	A1	6/2004	Taylor et al.
2004/0106986	A1	6/2004	Andersson et al.
2004/0138528	A1	7/2004	Richter et al.
2004/0147933	A1	7/2004	McGovern
2004/0154624	A1	8/2004	Bonadio et al.
2004/0215063	A1	10/2004	Bonadio et al.
2004/0230160	A1	11/2004	Blanco
2004/0230161	A1	11/2004	Zeiner
2004/0254426	A1	12/2004	Wenchell
2004/0267213	A1	12/2004	Knapp
2005/0020884	A1	1/2005	Hart et al.
2005/0033342	A1	2/2005	Hart et al.
2005/0085842	A1	4/2005	Eversull et al.
2005/0137609	A1	6/2005	Guiraudon
2005/0148823	A1	7/2005	Vaugh et al.
2005/0155611	A1	7/2005	Vaugh et al.
2005/0192483	A1	9/2005	Bonadio et al.
2005/0209608	A1	9/2005	OHeeron
2005/0222582	A1	10/2005	Wenchell
2005/0267419	A1	12/2005	Smith
2005/0273132	A1	12/2005	Shluzas et al.
2005/0277946	A1	12/2005	Greenhalgh et al.
2006/0020214	A1	1/2006	Mori et al.
2006/0020281	A1	1/2006	Smith
2006/0071432	A1	4/2006	Staudner
2006/0212062	A1	9/2006	Farascioni
2006/0224129	A1	10/2006	Beasley et al.
2006/0224164	A1	10/2006	Hart et al.
2006/0229501	A1	10/2006	Jensen et al.
2006/0241651	A1	10/2006	Wilk
2006/0241671	A1	10/2006	Greenhalgh
2006/0247500	A1	11/2006	Voegelé et al.
2006/0247516	A1	11/2006	Hess et al.
2006/0247586	A1	11/2006	Voegelé et al.
2006/0247673	A1	11/2006	Voegelé et al.
2006/0247678	A1	11/2006	Weisenburgh, II et al.
2006/0254706	A1	11/2006	Swisher et al.
2006/0258899	A1	11/2006	Gill et al.
2006/0270911	A1	11/2006	Voegelé et al.
2007/0049966	A1	3/2007	Bonadio et al.
2007/0060939	A1	3/2007	Lancial et al.
2007/0085232	A1	4/2007	Brustad et al.
2007/0088202	A1	4/2007	Albrecht et al.
2007/0088277	A1	4/2007	McGinley et al.
2007/0118021	A1	5/2007	Pokorney
2007/0151566	A1	7/2007	Kahle et al.
2007/0208312	A1	9/2007	Norton et al.
2007/0255219	A1	11/2007	Vaugh et al.
2008/0027476	A1	1/2008	Piskun
2008/0051739	A1	2/2008	McFarlnae
2008/0065021	A1	3/2008	Jenkins et al.
2008/0119821	A1	5/2008	Agnihotri et al.
2008/0255519	A1	10/2008	Piskun et al.
2009/0012477	A1	1/2009	Norton et al.
2009/0036738	A1	2/2009	Cuschieri et al.
2009/0062618	A1	3/2009	Drew et al.
2010/0030032	A1	2/2010	Voegelé et al.

FOREIGN PATENT DOCUMENTS

EP	0966925	B1	4/2003
EP	0966924	B1	8/2003
EP	1350476		10/2003
JP	06320750		6/1984
JP	2000/033089	A	2/2000
JP	2000/511788	A	9/2000
JP	2003/126105	A	5/2003
WO	WO 96/08208	A1	3/1996
WO	WO 97/29709	A1	8/1997
WO	WO 97/35521	A1	10/1997
WO	WO 98/10712	A1	3/1998
WO	WO 99/03536	A1	1/1999
WO	WO 00/30592	A1	6/2000
WO	WO 00/32253	A1	6/2000
WO	WO 00/35529	A1	6/2000
WO	WO 02/39890	A2	5/2002
WO	WO 02/39918	A1	5/2002
WO	WO 02/058543	A2	8/2002
WO	WO 02/094133	A1	11/2002
WO	WO 03/005890	A2	1/2003
WO	WO 03/028525	A2	4/2003
WO	WO 03/061738	A1	7/2003
WO	WO 03/077730	A2	9/2003
WO	WO 2004/049902	A2	6/2004
WO	WO 2005/094432		10/2005
WO	WO 2007/119232		10/2007
WO	WO 2008/024502		2/2008

OTHER PUBLICATIONS

International Search Report dated Mar. 27, 2012; International Application No. EP0674974.

“Adult Cardiac Surgical Instruments”, from the website of Genesee BioMedical, Inc. (date of first publication unknown) Applicants admit the status of this publication as prior art for the limited purpose of examination of this application, but otherwise reserve the right to challenge the status of this publication as prior art.

“Hand Instruments”, from the website of Olympus Surgical America (date of first publication unknown) Applicants admit the status of this publication as prior art for the limited purpose of examination of this application, but otherwise reserve the right to challenge the status of this publication as prior art.

“Pen Competitors”.

“1 Lap Disc Hand Access Device—Ref. LD111”, by Ethicon Endo-Surgery, Inc. (date unknown).

Webpage of Novare Surgical, Inc. featuring clamps (date of first publication unknown) Applicants admit the status of this publication as prior art for the limited purpose of examination of this application, but otherwise reserve the right to challenge the status of this publication as prior art.

“Bard® Bi-Directional and Kelly-Wick Tunnelers—Instructions for Use,” Bard Peripheral Vascular (Apr. 2006).

Ashida, R. et al., “Indocyanine Green is an Ideal Dye for Endoscopic Ultrasound-Guided Fine-Needle Tattooing of Pancreatic Tumors” *Endoscopy*, 38, pp. 190-192 (2006).

Twentieth Edition—Illustrations of Surgical Instruments, by the Kny-Scheerer Company, New York, USA, pp. 1003, 1026, 1028-1029, 1133, 2034, 2068-2069, 2097-2099, 2132, 2137, 2144, 2155-2156, 2162, 2167-2171, 2173, 2175, 2244, 2255, 2281-2282, 2327, 2333, 2338-2348, 2352, 2355, 2359, 2371, 3017, 3039-3073, 3132, 3165, 3168-3169, 3208, 3209, 3219 (Jul. 1915).

Lee, D.I. et al., “Novel Approach to Minimizing Trocar Sites during Challenging Hand-Assisted Laparoscopic Surgery Utilizing the Gelpert: Trans-Gel Instrument Insertion and Utilization,” *Journal of Endourology*, vol. 17, No. 2, pp. 69-71 (Mar. 2003).

“Applied GelPort System” by Applied Medical Resources Corporation (2004).

“Applied GelPort Advanced Access Device,” by Applied Medical Resources Corporation (Nov. 2002).

“intrack XT—Low Profile Atraumatic Clamps,” by Novacare Surgical Systems, Inc. (2002).

* cited by examiner




FIG. 1-1




FIG. 1-2




FIG. 1-3




FIG. 1-4




FIG. 1-5




FIG. 1-6




FIG. 1-7




FIG. 1-8




FIG. 1-9




FIG. 1-10




FIG. 1-11




FIG. 1-12




FIG. 2-1
(PRIOR ART)




FIG. 2-2




FIG. 2-3




FIG. 2-4




FIG. 2-5




FIG. 2-6




FIG. 2-7




FIG. 2-8




FIG. 2-9




FIG. 2-10




FIG. 3-1




FIG. 3-2




FIG. 3-3




FIG. 3-4




FIG. 3-5A




FIG. 3-5B




FIG. 3-5C




FIG. 3-6




FIG. 3-7




FIG. 3-8




FIG. 3-9




FIG. 3-10




FIG. 3-11




FIG. 3-12




FIG. 3-13




FIG. 3-14




FIG. 3-15




FIG. 3-16




FIG. 3-17




FIG. 3-18




FIG. 3-21

FIG. 3-20

FIG. 3-19




FIG. 3-24

FIG. 3-23

FIG. 3-22




FIG. 3-25




FIG. 3-26




FIG. 3-27




FIG. 3-28




FIG. 3-29




FIG. 3-30




FIG. 3-31




FIG. 3-32




FIG. 3-33




FIG. 3-34




FIG. 3-35




FIG. 3-36




FIG. 3-37




FIG. 3-38




FIG. 3-39




FIG. 3-40




FIG. 3-41




FIG. 3-42




FIG. 4-1




FIG. 4-2




FIG. 4-3




FIG. 4-4




FIG. 4-5




FIG. 4-6




FIG. 4-7




FIG. 4-8




FIG. 4-9




FIG. 4-10




FIG. 4-11




FIG. 4-12




FIG. 4-13






FIG. 5-1






FIG. 5-4




FIG. 5-5




FIG. 5-6




FIG. 5-7




FIG. 5-8




FIG. 5-9




FIG. 5-10









FIG. 5-11








FIG. 5-16




FIG. 5-17




FIG. 5-18




FIG. 5-19




FIG. 5-20




FIG. 5-21




FIG. 5-22




FIG. 5-23




FIG. 5-24




FIG. 5-25




FIG. 5-26B




FIG. 5-26A




FIG. 5-27




FIG. 5-28




FIG. 5-29




FIG. 5-30




FIG. 5-31




FIG. 5-32




FIG. 5-33




FIG. 5-34




FIG. 5-35







FIG. 5-36






FIG. 5-39




FIG. 5-40




FIG. 5-41




FIG. 5-42




FIG. 5-43




FIG. 5-44




FIG. 5-45




FIG. 5-46




FIG. 5-47




FIG. 5-48




FIG. 5-49




FIG. 5-50




FIG. 5-51




FIG. 5-52




FIG. 5-53




FIG. 5-54




FIG. 5-55




FIG. 5-56

FIG. 5-57




FIG. 6-1

FIG. 6-2




FIG. 6-3




FIG. 6-4




FIG. 6-5




FIG. 6-6




FIG. 6-7




FIG. 6-8




FIG. 6-9




FIG. 6-10




FIG. 6-11




FIG. 6-12




FIG. 6-13




FIG. 7-1




FIG. 7-2




FIG. 7-4




FIG. 7-6A

FIG. 7-5




FIG. 7-6B




FIG. 7-7




FIG. 7-8




FIG. 7-9




FIG. 7-10




FIG. 7-11




FIG. 7-12




FIG. 7-13

ACCESS DEVICE

REFERENCE TO RELATED APPLICATIONS

The present application is a divisional of and claims priority to U.S. patent application Ser. No. 11/398,985 filed Apr. 5, 2006 (published as US 2006/0247673 on Nov. 2, 2006), which application claims priority to U.S. provisional patent application Ser. Nos. 60/669,514, filed on Apr. 8, 2005, and 60/700,176, filed on Jul. 18, 2005; all of which are incorporated herein by reference.

This application cross references and incorporates by reference the following copending commonly assigned patent applications:

Multi-Port Laparoscopic Access Device, U.S. Ser. No. 11/398,985, filed Apr. 5, 2006;

SURGICAL ACCESS DEVICE, U.S. Ser. No. 11/399,172, filed Apr. 5, 2006;

TISSUE MARKER AND METHOD FOR USE, U.S. Ser. No. 11/399,045, filed Apr. 5, 2006;

INTRA-ABDOMINAL STORAGE DEVICE, U.S. Ser. No. 11/399,044, filed Apr. 5, 2006;

TISSUE RETRACTION DEVICE, U.S. Ser. No. 11/399,149, filed Apr. 5, 2006;

SURGICAL INSTRUMENT SYSTEM, U.S. Ser. No. 11/399,145, filed Apr. 5, 2006; and

TISSUE SUSPENSION DEVICE, U.S. Ser. No. 11/399,181, filed Apr. 5, 2006.

FIELD OF THE INVENTION

The present application relates to methods and devices for surgical procedures and, more particularly, to laparoscopic procedures.

BACKGROUND

In a minimally invasive, laparoscopic surgical procedure, a surgeon may place a number of small ports into the abdomen to gain access into the abdominal cavity of the patient. A surgeon may use, for example, a port for insufflating the abdominal cavity to create space, a port for introducing a laparoscope for viewing, and a number of other ports for introducing surgical instruments for operating on tissue. The benefits of minimally invasive procedures compared to open surgery procedures for treating certain types of wounds and diseases are now well-known to include faster recovery time and less pain for the patient, better outcomes, and lower overall costs.

In traditional, open surgery, surgeons may use their hands, together with surgical instrumentation, to manipulate tissues, to perform particular steps of the procedure and to obtain tactile feedback through their fingertips to verify the nature of particular tissues. Also in open surgery, the size and shape of instruments that a surgeon may place into the abdominal cavity, as well as the size and shape of tissues that a surgeon may remove, obviously is not nearly as limited as in laparoscopic surgery.

Hand-assisted, laparoscopic surgery ("HALS") combines some of the benefits of both the open and the laparoscopic methods. In a HALS procedure, a surgeon still places small ports into the abdomen to insufflate, to view and to introduce instruments into the abdominal cavity. In a HALS procedure, however, a surgeon also creates an incision into the abdominal wall large enough to accommodate the surgeon's hand. The incision may be retracted and draped to provide a suitably sized and protected opening. A surgeon may also place a

laparoscopic access device, also referred to as a lap disc, into the incision to maintain insufflation in the abdominal cavity while the surgeon's hand is either inserted into the cavity through the device or removed from the cavity. The advent of HALS and the lap disc creates numerous opportunities for creating and/or improving surgical devices and methods.

SUMMARY

A surgical access device is provided for surgical access through an incision in the body wall to the inside of a body cavity of a patient. A multi-port insert is provided for use with a laparoscopic access device. The multi-port insert includes a base having two or more ports or apertures that provide for the insertion of surgical instruments. The multi-port insert may be used with a laparoscopic access device, such as a Lap Disc Hand Access Device model #LD111, commercially available from Ethicon Endo-Surgery, Inc. of Cincinnati, Ohio. The multi-port insert provides for the insertion of one or more surgical instruments through the laparoscopic access device. Each port or aperture in the base includes its own seal assembly to provide a seal and prevent the escape of insufflation gases.

In one embodiment the multi-port insert may also include one or more instrument supports that are attached to the base to fix the position of one or more surgical instruments inserted through the multi-port insert.

A method is also provided for accessing a body cavity of a patient during a surgical procedure. The method includes providing an access device that includes a subassembly having a multi-port insert. The access device is positionable in the incision and defines a passageway through the body wall between the opening in the subassembly and the body cavity. The surgical access device further includes at least two access channels for insertion of one or more surgical instruments through the access device. The method further includes providing at least one instrument support on the access device for supporting one or more surgical instruments inserted through the multi-port insert.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the invention are set forth with particularity in the appended claims. The invention itself, however, both as to organization and methods of operation, may best be understood by reference to the following description, taken in conjunction with the accompanying drawings in which:

FIG. 1-1 is a perspective view of a first aspect of a base;

FIG. 1-2 is a top view of the base of FIG. 1-1;

FIG. 1-3 is a sectional side view of a first aspect of a seal assembly for use with the base of FIG. 1-1;

FIG. 1-4 is a top view of the seal assembly of FIG. 1-3;

FIG. 1-5 is a sectional side view of a first embodiment of the base of FIG. 1-1;

FIG. 1-6 is a sectional side view of an alternate embodiment of the base of FIG. 1-5;

FIG. 1-7 is a sectional side view of a laparoscopic access device including the base of FIG. 1-5;

FIG. 1-8 is an expanded cross-sectional view of an instrument support;

FIG. 1-9 is a view of the instrument support of FIG. 1-8 in an assembled state;

FIG. 1-10 is a sectional view of an alternate embodiment of an instrument support;

FIG. 1-11 is a sectional view of a third embodiment of an instrument support;

FIG. 1-12 is a sectional view of a fourth embodiment of an instrument support;

FIG. 2-1 is a partially sectioned front view of an access device of the prior art;

FIG. 2-2 is a partially sectioned front view of a first aspect of an access device;

FIG. 2-3 is a top view of the access device shown in FIG. 2-2;

FIG. 2-4 is a sectional view of a port of the access device shown in FIG. 2-3;

FIG. 2-5 is a partially sectioned front view of a second aspect of an access device;

FIG. 2-6 is a top view of the access device shown in FIG. 2-5;

FIG. 2-7 is schematic representation of a third aspect of an access device;

FIG. 2-8 is a partial side view of a fourth aspect of an access device;

FIG. 2-9 is a partial top view, taken at line 9-9 of FIG. 2-10, of the access device shown in FIG. 2-8;

FIG. 2-10 is a partial front, sectional view taken at line 10-10 of FIG. 2-9, of the access device shown in FIG. 2-8;

FIG. 3-1 is a top view of a first aspect of a tissue marker;

FIG. 3-2 is a side view of the tissue marker shown in FIG. 3-1, while in a flat configuration;

FIG. 3-3 is a side view of the tissue marker shown in FIG. 3-1, while in a deployed configuration;

FIG. 3-4 is a sectional view of the tissue marker shown in FIG. 3-1 being attached to tissue;

FIG. 3-5A is a perspective view of two tissue markers of FIG. 3-1, each including a flag and attached to tissue;

FIG. 3-5B is a perspective view of the tissue marker shown in FIG. 3-1, but with an alternate embodiment of a flag, shown in a non-extended position;

FIG. 3-5C is a perspective view of the tissue marker shown in FIG. 3-5B, with the flag shown in an extended position;

FIG. 3-6 is a top view of a second aspect of a tissue marker;

FIG. 3-7 is a side view of the tissue marker shown in FIG. 3-6, shown before deployment;

FIG. 3-8 is a side sectional view of the tissue marker shown in FIG. 3-6, shown after deployment;

FIG. 3-9 is a top view of a third aspect of a tissue marker;

FIG. 3-10 is a side sectional view of the tissue marker shown in FIG. 3-9; shown before deployment;

FIG. 3-11 is a side view of the tissue marker shown in FIG. 3-9, shown after deployment;

FIG. 3-12 is a top view of a fourth aspect of a tissue marker;

FIG. 3-13 is a side sectional view of the tissue marker shown in FIG. 3-12, shown before deployment;

FIG. 3-14 is a side view of the tissue marker shown in FIG. 3-12, shown after deployment;

FIG. 3-15 is a side view of a fifth aspect of a tissue marker;

FIG. 3-16 is an end view of the tissue marker shown in FIG. 3-15;

FIG. 3-17 is a front view of the tissue marker shown in FIG. 3-15, shown before deployment;

FIG. 3-18 is a front view of the tissue marker shown in FIG. 3-15, shown after deployment;

FIG. 3-19 is an end view of a sixth aspect of a tissue marker;

FIG. 3-20 is a front view of the tissue marker shown in FIG. 3-19, shown before deployment;

FIG. 3-21 is a front view of the tissue marker shown in FIG. 3-19, shown after deployment;

FIG. 3-22 is a top view of a seventh aspect of a tissue marker;

FIG. 3-23 is a front view of the tissue marker shown in FIG. 3-22, shown before deployment;

FIG. 3-24 is a front view of the tissue marker shown in FIG. 3-22, shown after deployment;

FIG. 3-25 is a top view of an eighth aspect of a tissue marker;

FIG. 3-26 is a side view of the tissue marker shown in FIG. 3-25;

FIG. 3-27 is a top view of a ninth aspect of a tissue marker;

FIG. 3-28 is a side view of the tissue marker shown in FIG. 3-27, shown before deployment;

FIG. 3-29 is a side view of the tissue marker shown in FIG. 3-27, shown after deployment;

FIG. 3-30 is a top view of a tenth aspect of a tissue marker;

FIG. 3-31 is a side view of the tissue marker shown in FIG. 3-30, shown before deployment;

FIG. 3-32 is a side view of the tissue marker shown in FIG. 3-30, shown after deployment;

FIG. 3-33 is a side view of a first embodiment of a marking fluid applier;

FIG. 3-34 is a partial side view of a second embodiment of a marking fluid applier;

FIG. 3-35 is a partial top view of the marking fluid applier shown in FIG. 3-34;

FIG. 3-36 is an enlarged view of a tissue interfacing surface of the marking fluid applier shown in FIG. 3-34;

FIG. 3-37 is an illustration of a plurality of tissue markings on the colon of a surgical patient;

FIG. 3-38 is an illustration of a tissue marker being deployed onto tissue with a surgical instrument;

FIG. 3-39 is an illustration of a marking fluid being applied to tissue;

FIG. 3-40 is an illustration of a colon of a surgical patient prior to resection;

FIG. 3-41 is an illustration of a colon of a surgical patient during resection;

FIG. 3-42 is an illustration of a colon of a surgical patient after resection;

FIG. 4-1 is a perspective view of a first aspect of a storage device;

FIG. 4-2 is a perspective view of a second aspect of a storage device;

FIG. 4-3 is a perspective view of a third aspect of a storage device;

FIG. 4-4 is a perspective view of a fourth aspect of a storage device;

FIG. 4-5 is a perspective view of a storage device, including a first embodiment of an attaching element;

FIG. 4-6 is a perspective view of a storage device, including a second embodiment of an attaching element;

FIG. 4-7 is a perspective view of a storage device, including a third embodiment of an attaching element;

FIG. 4-8 is a perspective view of a storage device, including a fourth embodiment of an attaching element;

FIG. 4-9 illustrates a storage device positioned against the inside of the body wall of the patient;

FIG. 4-10 illustrates a storage device removably attached to a trocar cannula, which is positioned through the body wall of the patient;

FIG. 4-11 illustrates a storage device in a closed configuration and removably attached to the trocar cannula, which is positioned through the body wall of the patient;

FIG. 4-12 illustrates a storage device in an open configuration and positioned inside the body cavity, and prior to the removable attachment of a cap onto an attaching rod;

FIG. 4-13 illustrates a storage device in a closed configuration and positioned inside the body cavity, and after the removable attachment of the cap onto the attaching rod;

FIG. 5-1 illustrates a first aspect of a surgical retraction device retracting the colon of a surgical patient;

FIG. 5-2 is a perspective view of a second aspect of a retraction device;

FIG. 5-3 is a perspective view of a third aspect of a retraction device;

FIG. 5-4 is a perspective view of a fourth aspect of a retraction device, while in a closed configuration;

FIG. 5-5 is a perspective view of the retraction device shown in FIG. 5-4, while in an opened configuration;

FIG. 5-6 is a perspective view of a fifth aspect of a retraction device; while in a closed configuration;

FIG. 5-7 is a perspective view of the retraction device shown in FIG. 5-6, while in an opened configuration;

FIG. 5-8 is a perspective view of a sixth aspect of a retraction device;

FIG. 5-9 is a perspective view of an seventh aspect of a retraction device;

FIG. 5-10 illustrates an eighth aspect of a retraction device retracting the colon of a surgical patient;

FIG. 5-11 illustrates a ninth aspect of a retraction device retracting the colon of a surgical patient;

FIG. 5-12 is a perspective view a tenth aspect of a retraction device in a closed configuration;

FIG. 5-13A is a perspective view the retraction device shown in FIG. 5-12, while in a partially open configuration;

FIG. 5-13B is a perspective view the retraction device shown in FIG. 5-12, while in an open configuration;

FIG. 5-14 is a perspective view of an eleventh aspect of a retraction device;

FIG. 5-15 is a perspective view of a twelfth aspect of a retraction device;

FIG. 5-16 is a side view of a thirteenth aspect of a retraction device while in an opened configuration;

FIG. 5-17 is a side view of the retraction device shown in FIG. 5-16, while in a partially opened configuration;

FIG. 5-18 is a side view of the retraction device shown in FIG. 5-16 while in a closed configuration;

FIG. 5-19 illustrates a fourteenth aspect of a retraction device retracting the colon of a surgical patient;

FIG. 5-20 is a perspective view of an arm of the retraction device shown in FIG. 5-19;

FIG. 5-21 is a sectional view of a fifteenth aspect of a retraction device, while in a closed configuration and being passed through a laparoscopic port;

FIG. 5-22 is an end view of the retraction device shown in FIG. 5-21, while in the closed configuration;

FIG. 5-23 is a front view of the retraction device shown in FIG. 5-21, while in the closed configuration;

FIG. 5-24 is a front view of a sixteenth aspect of a retraction device;

FIG. 5-25 illustrates an seventeenth aspect of a retraction device retracting the colon of a surgical patient;

FIG. 5-26A is a front view of the retraction device shown in FIG. 5-25, while in an open configuration;

FIG. 5-26B is a front view of the retraction device shown in FIG. 5-25, while in a partially closed configuration;

FIG. 5-27 illustrates an eighteenth aspect of a retraction device retracting the colon of a surgical patient;

FIG. 5-28 illustrates a nineteenth aspect of a retraction device retracting the colon of a surgical patient;

FIG. 5-29 is a perspective view of a twentieth aspect of a retraction device;

FIG. 5-30 is a front view of a twenty-first aspect of a retraction device, while in a first, partially closed configuration;

FIG. 5-31 is a front view of the retraction device shown in FIG. 5-30, while in a second, partially closed configuration;

FIG. 5-32 is a front view of the retraction device shown in FIG. 5-30, while in an opened configuration;

FIG. 5-33 is a top view of a twenty-second aspect of a retraction device;

FIG. 5-34 is a front view of the retraction device shown in FIG. 5-33;

FIG. 5-35 is a top view of a twenty-third aspect of a retraction device;

FIG. 5-36 is a front view of the retraction device shown in FIG. 5-35;

FIG. 5-37A is a top view of a twenty-fourth aspect of a retraction device;

FIG. 5-37B is a detailed, top view of the retraction device shown in FIG. 5-37A, while being rolled up into a closed configuration;

FIG. 5-38 is a front view of the retraction device shown in FIG. 5-37;

FIG. 5-39 is a top view of a twenty-fifth aspect of a retraction device;

FIG. 5-40 is a front view of the retraction device shown in FIG. 5-39;

FIG. 5-41 is an end view of the retraction device shown in FIG. 5-39;

FIG. 5-42 is a front view of a twenty-sixth aspect of a retraction device;

FIG. 5-43 is a front view of the retraction device shown in FIG. 5-42, while in a twisted configuration;

FIG. 5-44 is a top view of a twenty-seventh aspect of a retraction device;

FIG. 5-45 is a front view of the retraction device shown in FIG. 5-44;

FIG. 5-46 is a top view of a twenty-eighth aspect of a retraction device;

FIG. 5-47 is a front view of the retraction device shown in FIG. 5-46;

FIG. 5-48 is a top view of a twenty-ninth aspect of a retraction device;

FIG. 5-49 is a front view of the retraction device shown in FIG. 5-48;

FIG. 5-50 is a top view of a thirtieth aspect of a retraction device;

FIG. 5-51 is a front view of the retraction device shown in FIG. 5-50, while in a closed configuration;

FIG. 5-52 is a front view of the retraction device shown in FIG. 5-50, while in an opened configuration;

FIG. 5-53 is a front view of a thirty-first aspect of a retraction device;

FIG. 5-54 is a top view of the retraction device shown in FIG. 5-53, when opened;

FIG. 5-55 is a top view of the retraction device shown in FIG. 5-53, when folded;

FIG. 5-56 is a front view of a thirty-second aspect of a retraction device;

FIG. 5-57 is an end view of the retraction device shown in FIG. 5-56;

FIG. 6-1 is a front view of the distal portion of a surgical instrument, shown with a first aspect of an end effector;

FIG. 6-2 is a sectional view, taken at line 2-2 of FIG. 1, of a first embodiment of an arm of the surgical instrument;

FIG. 6-3 is a front sectional view of the first embodiment of the arm of the surgical instrument shown in FIG. 6-1;

FIG. 6-4 is a front sectional view of a second embodiment of an arm of a surgical instrument;

FIG. 6-5 is an end view of a second aspect of an end effector;

FIG. 6-6 is a front view of the end effector shown in FIG. 6-5;

FIG. 6-7 is an end view of a third aspect of an end effector;

FIG. 6-8 is a front view of the end effector shown in FIG. 6-7;

FIG. 6-9 is a front view of the distal portion of a surgical instrument, shown with a fourth aspect of an end effector;

FIG. 6-10 is a top view of the end effector shown in FIG. 6-9;

FIG. 6-11 is an end view of the end effector shown in FIG. 6-9;

FIG. 6-12 illustrates part of a first method for performing a hand-assisted, laparoscopic procedure;

FIG. 6-13 illustrates part of a second method for performing a hand-assisted, laparoscopic procedure;

FIG. 7-1 is a side view of a patient;

FIG. 7-2 is a cross-sectional view of a patient's abdomen, taken at line 2-2 of FIG. 7-1;

FIG. 7-3 is an end view of a first aspect of a tissue suspension device;

FIG. 7-4 is a side view of the tissue suspension device shown in FIG. 7-3;

FIG. 7-5 is an enlarged side view of a second end of the tissue suspension device shown in FIG. 7-3;

FIG. 7-6A is an enlarged side view of a first end of the tissue suspension device shown in FIG. 7-3;

FIG. 7-6B is an isometric view of the first end of the tissue suspension device shown in FIG. 7-3, assembled to a supporting element;

FIG. 7-7 is an end view of a second aspect of a tissue suspension device;

FIG. 7-8 is a side view of the tissue suspension device shown in FIG. 7-7;

FIG. 7-9 is an enlarged view of a support element on the end of the tissue suspension device shown in FIG. 7-7;

FIG. 7-10 is top view of a retaining element of the support element shown in FIG. 7-9;

FIG. 7-11 is a partial side view of a third aspect of a tissue suspension device;

FIG. 7-12 is a partial side view of a fourth aspect of a tissue suspension device; and

FIG. 7-13 is a partial side view of a fifth aspect of a tissue suspension device.

DETAILED DESCRIPTION

Before explaining the present invention in detail, it should be noted that the invention is not limited in its application or use to the details of construction and arrangement of parts illustrated in the accompanying drawings and description. The illustrative embodiments of the invention may be implemented or incorporated in other embodiments, variations and modifications, and may be practiced or carried out in various ways. Further, unless otherwise indicated, the terms and expressions employed herein have been chosen for the purpose of describing the illustrative embodiments of the present invention for the convenience of the reader and are not for the purpose of limiting the invention.

Further, it is understood that any one or more of the following-described embodiments, expressions of embodiments, examples, etc. can be combined with any one or more of the other following-described embodiments, expressions of embodiments, examples, etc.

Multi-Port Insert

A first aspect of a multi-port insert, generally designated 100, relates to an insert for use with a laparoscopic access device 122. Referring now to the figures, FIG. 1-1 and FIG.

1-2 depict one embodiment of the multi-port insert 100. The multi-port insert 100 includes a base 102 having two or more ports or apertures 104 that provide for the insertion of surgical instruments. The multi-port insert 100 may be used with a laparoscopic access device 122 (FIG. 1-7) such as a Lap Disc Hand Access Device model #LD111, commercially available from Ethicon Endo-Surgery, Inc. of Cincinnati, Ohio. The multi-port insert provides for the insertion of one or more surgical instruments through the laparoscopic access device 122, while preventing insufflation gases from escaping from the body cavity.

As illustrated in FIG. 1-1 and FIG. 1-2, the base 102 may include four separate apertures 104 spaced evenly around the center of the base 102 with each aperture 104 having a raised lip or rim 106. This configuration allows surgical tools, such as gripping devices to be inserted through two apertures 104. The gripping devices may be used to manipulate or lift a portion of the bowel to provide the surgeon with access to the either the bowel tissue being manipulated or the underlying tissue. An endoscope including a camera and light may be inserted through a third aperture 104 to provide the surgeon with the ability to view the interior of the body cavity. An additional surgical instrument, such as a needle, scissors, an ultrasonic transducer or any other surgical instrument, may be inserted through the fourth aperture 104. Although FIG. 1-1 and FIG. 1-2 illustrate a base 102 including four apertures 104, alternate numbers and configurations of apertures may be used. In addition, a base 102 may include apertures 104 of varying sizes able to provide for the insertion of differently sized surgical instruments. In one embodiment the apertures may be sized to provide for instruments between five and twelve millimeters in diameter. The base 102 may also include an reference indicator 180 that may be used by the surgeon as a reference point during laparoscopic procedures.

Referring now to FIG. 1-3 and FIG. 1-4, each port or aperture 104 in the base 102 includes its own seal assembly 108 to provide a seal and prevent the escape of insufflation gases. There are many possible types of seals which may be utilized in the seal assembly 108. In one embodiment, each seal assembly 108 includes an iris seal 110 and a duck bill valve 112 such as the seal assembly described in U.S. Patent Application Publication No. 2004/0230161 (Ser. No. 10/815,356; filed Mar. 31, 2004) to Zeiner, the entire contents of which are hereby incorporated herein by reference. Each iris seal 110 may include a plurality of layered elastic members 114 having a semi-circular profile disposed between two rigid seal rings 116. The elastic members 114 may form a conical-shaped seal such that when a surgical instrument is inserted from the top side thereof, the elastic members 114 are displaced downwardly and radially outwardly and form a seal around the surgical instrument. Each seal assembly 108 may also include a zero-closure valve such as a duckbill valve 112 to prevent the seal assembly 108 from leaking when there is no surgical instrument inserted through the seal assembly 108. The duckbill valve 112 may include two overlapping flaps 113. Pressure from below the duckbill valve 112 pushes the flaps 113 together, maintaining the seal. Pressure from above the duckbill valve 112 pushes the flaps 113 apart, allowing a surgical instrument to pass through.

In one embodiment, each seal assembly 108 is flexibly attached to the base 102 using a floatation system such as bellows 118 located around the periphery of each seal assembly 108. The bellows 118 may be made from a flexible, elastic material and allow the seal assembly 108 to move laterally and pivot within the aperture 104. The movement of the seal assembly 108 allows surgical instruments to be inserted through the apertures 104 at an angle rather than along the

axis of the aperture **104**. The bellows **118** may be attached to the lip of the aperture **104** by a retaining ring **120** that frictionally fits over each rim **106**. The force required to deflect the bellows **118** is much less than the pressure exerted by surgical instrument on the elastic members **114** while the surgical instrument is inserted in the seal assembly **108**. This allows the floatation system to deflect within each aperture **104** while the elastic members **114** maintain a sealing condition with the instrument.

The multi-port insert **100** may be attached to a laparoscopic access device **122** as shown in FIG. 1-7. The laparoscopic access device **122** may include a generally coaxially aligned upper ring **146** and lower ring **148** and a membrane **128** coupled to and extending generally axially between the upper ring **146** and lower ring **148**. The membrane **128** has a central opening of variable size. For example, in one embodiment the upper ring **146** and lower ring **148** are rotatable in opposite directions relative to one another to change the size of the opening. The base **102** of the multi-port insert **100** may be attached to the laparoscopic access device **122** by a simple latch mechanism **124** to allow the multi-port insert **100** to be attached to currently available laparoscopic access devices **122**. Alternatively, one or more C-clamps or other clamping devices or structures may be used to attach the multi-port insert **100** to a laparoscopic access device **122**. In addition, the multi-port insert **100** may be attached to a laparoscopic access device **122** using a threadable surface on the multi-port insert **100** and a corresponding mating threadable surface on the laparoscopic access device **122**.

Once attached to the laparoscopic device, the base **102** of the multi-port insert **100** may form a seal with the laparoscopic access device **122** to prevent the escape of insufflation gas. As shown in FIG. 1-5, the base **102** may include a collar **126** that may be inserted into the laparoscopic access device **122**. As illustrated in FIG. 1-7, the collar **126** extends into the laparoscopic access device **122** and forms a seal with the membrane. In addition, the collar **126** may also protect the membrane **128** of the laparoscopic access device from any surgical instruments inserted through the apertures **104**. As depicted in FIG. 1-5, the collar **126** may include a generally tapered portion **127**. The tapered portion **127** allows the apertures **104** to be seated within the laparoscopic access device **122**. Lowering the apertures **104** lowers the pivot points of the surgical instruments and increases the range of motion of the surgical instruments inserted through the apertures **104**. In an alternate embodiment, the collar **126** does not include a tapered portion and may be generally cylindrically shaped.

In an alternate embodiment illustrated in FIG. 1-6, a resilient layer **150** may be located on a lower surface of the base **102** such that when the multi-port insert **100** is attached to the laparoscopic access device **122**, the resilient layer **150** forms a seal between the multi-port insert **100** and the laparoscopic device. The resilient layer **150** may be formed from a closed-cell elastomer or any other suitable material.

In another embodiment, the base **102** of the multi-port insert may be inserted through the opening in the membrane **128** of the laparoscopic access device **122** and attached to the lower ring **148** of the laparoscopic access device **122**. This configuration would provide a greater range of motion within the body cavity for the surgical instruments by lowering the pivot points for the instruments below the surface of the skin.

The multi-port insert **100** may also include one or more instrument supports **130** that are attached to the base **102** to fix the position of one or more surgical instruments inserted through the multi-port insert **100**. FIG. 1-8 illustrates a first embodiment of a surgical instrument support **130** extending generally axially from the base **102**. The surgical instrument

support **130** may include a gripping portion **138**, a stem **154** and an instrument support base **134**. The gripping portion **138** may be used to hold one or more surgical instruments and may include a C-clamp or any other device suitable for holding a surgical instrument. The stem **154** connects the gripping portion **138** and the instrument support base **134**. In one embodiment, the stem **154** may be composed of a malleable substance, such as copper wire, to allow the surgical instrument support **130** to be positioned to hold a surgical instrument.

The instrument support base **134** attaches the instrument support **130** to the multi-port insert **100**. The base **134** may be inserted into a track **132** that extends around the periphery of the multi-port insert **100**. The track **132** may include an opening **178** to allow an instrument support base **134** to be inserted into the track **132**. The instrument support **130** may be positioned along the track **132** around the circumference of the multi-port insert **100**.

The instrument support **130** includes a positional lock **136** for fixing the position of the instrument support base **134** with respect to the multi-port insert **100**. The stem **154** may be inserted through an aperture in the positional lock **136**. The positional lock **136** may be threadably connected to the instrument support base **134**, such that when the positional lock **136** is rotated in a first direction the instrument support base **134** is drawn upward away from the base **102**. Frictional forces between the track **132**, the instrument support base **134** and the positional lock **136** secure the instrument support base **134** relative to the base **102** of the multi-port insert **100**. In an alternative embodiment, a clamp may be used to secure the instrument support **130** to the base **102**.

The instrument support **130** may also include an extension control **152** and an extension lock **140**. The extension control **152** includes a generally conical portion **166** and an aperture shaped to receive the stem **154**. The conical portion **166** of the extension control **152** includes one or more slits (not shown). The extension lock **140** includes an aperture shaped to receive the stem **154** and a generally conical shaped opening **156**. The extension lock **140** may be threadably connected to the extension control **152** such that the extension lock **140** may be drawn downward over the extension control **152**. The pressure exerted by the extension lock **140** on the extension control **152** pushes the conical portion **166** of the extension control **152** down and inward, exerting pressure against the stem **154**, preventing the stem **154** from sliding through the apertures in the extension control **152** and thereby locking the stem **154** in place. The surface of the stem **154** may be rough, textured or covered with a coating to increase friction between the stem and the extension control **152** and facilitate locking the stem **154** in place.

FIG. 1-10 illustrates an alternate embodiment of an instrument support **130'** in which the instrument support **130'** covers and is radially aligned with an aperture **104** of the multi-port insert **100**. The instrument support **130'** may be attached to one or more of the apertures **104**. One or more of the rims **106** may be shaped to form a socket-shaped housing **142'**. The instrument support **130'** includes an instrument support base **134'** having a semispherical portion seated within the housing **142'**. The instrument support base **134'** is capable of pivoting within the housing **142'** to provide a range of motion to the surgical instruments received therethrough. The instrument support **130'** may include a rotation lock **164'** threadably connected to the instrument support base **134'**. Rotating the rotation lock **164'** in a first direction causes the rotation lock **164'** to exert pressure downward on the housing **142'** while at the same time drawing the instrument support base **134'** upward against the housing **142'**. The frictional forces

11

between the instrument support base **134'**, the housing **142'** and the rotational lock **164'** may prevent the instrument support base **134'** from pivoting or rotating within the housing **142'**.

The instrument support **130'** may include an instrument contact ring **160'** and an instrument locknut **162'** designed to control the depth of insertion into the body cavity of the surgical instruments. The instrument locknut **162'** may be threadably connected to the instrument support base **134'** such that, when the locknut **162'** is rotated and engages the threads of the instrument support base **134'**, the locknut **162'** exerts pressure against the instrument contact ring **160'** causing the contact ring **160'** to close around the surgical instrument and thereby controlling the depth of insertion of the instrument.

FIG. 1-11 illustrates a third embodiment of an instrument support **130"**. This embodiment also covers and is radially aligned with an aperture **104** of the multi-port insert **100**. The instrument support **130"** may include a socket-shaped, metalized or metal impregnated housing **142"** that attaches to the upper surface of the base. The instrument support **130"** includes an instrument support base **134"** having a semi-spherical portion which rests upon the housing **142"**. The instrument support base **134"** is capable of pivoting on the housing **142"** to provide a range of motion to the surgical instruments received therethrough. The instrument support **130"** may include includes one or more magnets **170"** attached to the instrument support base **134"**. The attraction between the housing **142"** and the magnets **170"** holds the instrument support base **134"** in place relative to the housing **142"**. The instrument support **130"** includes an elastic boot **168"** attached to the housing **142"** and the instrument support base **134"**. The elastic boot **168"** maintains a seal and prevents the escape of insufflation gases. As in the previous embodiment, the instrument support **130"** may include seal assembly **108**, an instrument contact ring **160** and an instrument locknut **162** to control the depth of insertion of a surgical instrument. The seal assembly **108** may include a duckbill valve **112** and an iris seal **110**.

FIG. 1-12 illustrates a further embodiment of the instrument support **130'''** in which the housing **142'''** may include a set of concentric ridges **172'''**. The instrument support base **134'''** may include one or more legs **174'''** include a set of teeth **176'''** that mate with the ridges **172'''** of the housing **142'''** to hold the instrument support base **134'''** in place relative to the housing **142'''**. In this embodiment, the elastic boot **168'''** attaches holds the instrument support base **134'''** in contact with the housing **142'''**.

The multi-port insert may be utilized during laparoscopic procedures to provide the surgeon with the ability to insert multiple surgical instruments into the body cavity of the patient without substantial loss of insufflation gases and without requiring multiple additional incisions. In one embodiment the lower ring of the laparoscopic access device **122** may be inserted into the body of a patient through an incision in the abdomen of the patient. During laparoscopic surgery, the surgeon may elect to attach a multi-port insert **100** to the upper ring **148** of the laparoscopic access device **122** using the latch mechanisms **124**, clamps or the like. Once attached, the multi-port insert **100** forms a seal with the laparoscopic access device **122**. The seal between the multi-port insert **100** and the laparoscopic access device **122** and the seal assemblies **108** prevent excessive amounts of the insufflation gases from escaping the body cavity. The surgeon may insert a surgical instrument through any or all of the apertures **104**. This allows the surgeon to insert multiple surgical instruments into the body cavity patient at the same time. The seal

12

assemblies **108** automatically reseal upon removal of the surgical instruments allowing the surgeon to insert and remove multiple surgical instruments during surgery.

The multi-port insert **100** may also include one or more instrument supports **130** designed to hold surgical instruments inserted through the multi-port insert. In one embodiment the instrument supports **130** attach to the track **132** in the base **102**. The instrument supports **130** may be positioned at an appropriate location on the base **102** and locked into place using the positional lock **136**. The surgeon may control the distance the instrument support **130** extends from the base **102** using the extension control **152** and extension lock **140**. The instrument support **130** may be attached to a surgical instrument using the gripping portion **138**. The surgeon may reposition and readjust the instrument support **130** at any time. At any time during the procedure the surgeon may elect to disconnect the multi-port insert **100** from the laparoscopic access device **122**.

Surgical Access Device

FIG. 2-1 is a partially sectioned front view of an access device **202** of the prior art, positioned in a body wall **299** of a patient. Access device **202** is disclosed in U.S. Pat. No. 6,110,154, which issued to Shimomura et al. on Aug. 29, 2000, and is titled "Valve and Valved Trocar Jacket Tube." Access device **202** includes an upper ring **204**, a lower ring **206**, a first cylindrical elastic member **208** (or first elastic member **208**), a second cylindrical elastic member **210** (also referred to as second elastic member **210** and sleeve **210**), and a resilient member **212**. First elastic member **208** and second elastic member **210** are each made of a thin-walled, silicone rubber tubing material, or any one of a number of other elastic, biocompatible materials in sheet or tube form. The ends of first elastic member **208** are assembled with upper ring **204** and lower ring **206**, respectively, to form a hyperboloid ("hour glass") shape defining an opening **250** centered on a vertical axis **249** of access device **202**. Similarly, the ends of second elastic member **210** are assembled with lower ring **206** and resilient ring **212** to form a hyperboloid shape and defining a passageway **223** therethrough. The surgeon may position second elastic member **210** in the body wall **299** of the patient by pushing resilient ring **212** (while folded) through the surgical incision. Once in the body cavity, resilient ring **212** resumes an approximately circular shape to sealingly retain access device **202** in body wall **299**. An annular interface **211** between upper ring **204** and lower ring **206** frictionally holds the relative angular orientation of upper ring **204** and lower ring **206** in order to maintain the size of opening **250**. The frictional holding force is easily overcome by the surgeon turning either one of upper ring **204** and lower ring **206** while holding the other. Additionally, upper ring **204** and lower ring **206** may each be molded from a plastic to have interlocking features around the perimeter of their mating surfaces. The surgeon may accordingly adjust the relative angular position about vertical axis **249** of upper ring **204** with respect to lower ring **206**, and thus set the size of opening **250** to numerous diameters ranging from a fully closed configuration to a fully open configuration. The surgeon may adjust opening **250**, therefore, to seal against the surgeon's hand or one or more surgical instruments extending through opening **250**, providing the ability to insufflate the body cavity with carbon dioxide during the surgical procedure.

Upper ring **204**, lower ring **206** and first elastic member **208** are also referred to together as a valve subassembly **201**. As will become apparent to those skilled in the art, the aspects and features described herein are also applicable to surgical access devices having other types of valve assemblies such as,

for example, those including a hydrophilic gel material with a sealable slit opening for surgical access into the body cavity.

FIG. 2-2 is a front view and FIG. 2-3 is a top view, of a first aspect of an access device 222 while in a closed configuration. Access device 222 includes a tubular access channel 238 extending from a lower ring 226 to a resilient ring 232. The surgeon may position a second elastic member 230 in the surgical incision and adjust an upper ring 224 with respect to lower ring 226 to set the size of opening 250 in a first elastic member 228 as described for access device 202 of FIG. 2-1. Access channel 238 increases the overall functionality of access device 202. The surgeon may use access channel 238 to introduce ancillary, remotely operable, surgical implements and/or accessories into the body cavity of the patient, separate from and without obstructing opening 250 and passageway 223. Access channel 238 may be made of, but is not limited to, any one of numerous flexible, biocompatible materials including polyvinyl chloride, polyethylene, silicone rubber, and polyurethane extruded tubing. A proximal end 246 of access channel 238 attaches to a port 236 having a cap 242. Port 246 attaches to a tab 234 extending radially from lower ring 226. Port 246, tab 234, and lower ring 226 may be injection molded unitarily. The surgeon may introduce a surgical implement into port 246 along a longitudinal axis 247, which forms an angle 248 with longitudinal axis 249. Angle 248 may be approximately in the range of, but is not limited to, 0-90 degrees. Access channel 238 has a distal end 244 attached to resilient member 232 with a clip 240. Clip 240 may be, for example, made of a resilient material, such as silicone rubber, and adhered to second elastic member 230 around resilient member 232. Access channel 238 may also be adhered to the outside or inside of second elastic member 230, or molded integrally into the wall of second elastic member 230. Distal end 244 may extend a short distance, such as 0-5 centimeters, distal to resilient member 232, and is oriented in a generally downward direction as shown. Access channel 238 has sufficient length to conform to the outside shape of second elastic member 230 so that the body wall of the patient may easily seal around both access channel 238 and second elastic member 230.

Port 236 may alternately be attached to upper ring 224, rather than to lower ring 226. If port 236 is attached to upper ring 224, than access channel 238 would need to be long enough to wrap around second elastic element 230, spiraling around second elastic element 230 at least one wrap, so that the surgeon may rotate upper ring 224 in either direction to adjust the size of opening 250.

FIG. 2-4 is an enlarged, sectional view of port 236 of access device 222 shown in FIG. 2-2 and FIG. 2-3. Proximal end 246 of access channel 238 assembles into port 236, for example, with a biocompatible adhesive. Port 236 retains a seal 237, which is made of a silicone rubber, for example. Seal 237 has a disc shape and contains a small, central hole that may easily stretch and seal around a surgical implement and/or accessory introduced into port 236. To maintain insufflation in the body cavity when the surgeon is not using access channel 238, the surgeon may press cap 242 onto port 236. Port 236 of FIG. 2-4 is shown as merely one example; many other versions of a sealable port assembly will become apparent to those skilled in the art, such as those versions incorporating a duckbill valve, a gel, or a closed-cell foam material. The size, shape, orientation, and sealing method of port 236 may be adapted to one or more particular surgical implements and/or accessories to be used in the surgical procedure.

FIG. 2-5 is a front view and FIG. 2-6 is a top view, of a second aspect of an access device 252 while in an open configuration. Access device 252 includes a first access chan-

nel 268 having a first port 266, a second access channel 272 having a second port 270, a third access channel 276 having a third port 274, and a fourth access channel (not visible) having a fourth port 278. Each of the ports is attached to or unitarily formed with a lower ring 256 by one of four tabs 264. Each of the access channels pass through one of four entrance holes 253 near the proximal end of a second elastic member 230, extend between an inner wall 259 and an outer wall 257 of second elastic member 260, and pass through one of four exit holes 255 near the distal end of second elastic member 230. The surgeon may position second elastic member 230 in the surgical incision and adjust upper ring 254 with respect to lower ring 256 to set the size of opening 250 in a first elastic member 258 as described for access device 202 of FIG. 2-1.

FIG. 2-7 is an isometric view of a third aspect of an access device 282, shown schematically in combination with eight ancillary devices and/or systems typically used in a surgical procedure. Access device 282 has eight access channels that are separate from and do not obstruct opening 250 and passageway 223. Access device 282 includes an upper flange 283 that extends from a lower ring 286. Eight inlet ports ((291, 292, 293, 294, 295, 296, 297, and 298) are shown spaced apart evenly on upper flange 283 (although they may be spaced apart unevenly). Each inlet port has a corresponding outlet port (291', 292', 293', 294', 295', 296, 297, and 298') attached to a flexible, lower flange attached to a second elastic element 290. As for the second aspect of access device 252 described in FIG. 2-5, each access channel is retained between inner and outer walls of second elastic element 290.

In FIG. 2-7, access device 282 is shown, by way of example, with a variety of ancillary, surgical devices and systems. Other surgical implements, accessories, systems, and devices will become apparent to those skilled in the art. Some of these devices may be small enough to pass through the access channel. Other devices may first need to be introduced into the body cavity via opening 250, and then operably connected to the corresponding outlet port. In some instances, the inlet port or outlet port may include a short pigtail connection.

In FIG. 2-7, a light source 229 operably connects to an outlet port 298' via a fiber optic bundle introduced into inlet port 298, to illuminate the body cavity. An ultrasonic generator 227 operably connects to outlet port 291' via a cable introduced into inlet port 291. An ultrasonic device (not shown) may be introduced into the body cavity via opening 250, and then operably connected to outlet port 291'. An electrical power source 225 electrically connects to outlet port 292' (hidden) via an electrical conductor introduced into inlet port 292. Electrical power may be used, for example, for lighting inside the body cavity, or for powering a tissue-morcelating device (not shown). A flexible, mechanical instrument 231, such as a surgical grasper, is introduced into inlet port 297. A drug/dye administering device 233 is shown, for direct injection into the body cavity via inlet port 293 to treat or mark tissues and organs. A vacuum source 235 fluidly connects with outlet port 294' (hidden) via a tube introduced into inlet port 294, for the suction of fluids out of the body cavity. A fluid source 241 fluidly connects with outlet port 296' via a tube introduced into inlet port 296, for irrigation of tissue in the body cavity. An electrosurgical generator 239 electrically connects to outlet port 295' via an electrical conductor introduced into inlet port 295. An RF instrument (not shown) may be electrically connected to outlet port 295' to be used by the surgeon to cauterize tissue in the body cavity.

Each access channel described in FIG. 2-7 may include either a single or a multilumen, extruded tube. For example, a

double lumen access channel may provide both suction and irrigation functions, or electrically isolate a pair of electrical conductors.

FIG. 2-8, FIG. 2-9, and FIG. 2-10 illustrate partial views of a fourth aspect of an access device 203, which provides the surgeon with the ability to conveniently and quickly change access device 203 from a closed or partially closed configuration to an open configuration. Access device 203 includes an intermediate ring 209 disposed between an upper ring 205 and a lower ring 207. A locking element 215 attaches to an outer circumferential surface 218 (FIG. 2-8) of upper ring 205, and releasably locks upper ring 205 to intermediate ring 209. Intermediate ring 209 has a plurality of undercut, upper teeth 213 spaced apart on the perimeter of intermediate ring 209. Upper teeth 213 may interlock with a like plurality of undercut, lower teeth 214 spaced apart on the perimeter of lower ring 207. When a surgeon rotates either of upper ring 205 and lower ring 207 relative to the other in a first rotational direction, upper teeth 213 and lower teeth 214 engage to prevent relative movement of upper ring 205 and lower ring 207 in an opposite, second rotational direction, which is promoted by the spring-back force from twisting first elastic member 208 as opening 250 closes. To release upper ring 205 from lower ring 207, the surgeon may, for example, slightly turn upper ring 205 in the first rotational direction while holding lower ring 207, and pull upper ring 205 apart from lower ring 207 to disengage the upper teeth 213 from the lower teeth 214.

Locking element 215 allows the surgeon to quickly release upper ring 205 from lower ring 207, so that access device 203 may instantly spring back from a closed configuration to an open configuration. Locking element 215 is attached at a fulcrum 219 (FIG. 2-9) on surface 218 of upper ring 205. A pawl 217 of locking element 215 engages a recess 216 in intermediate ring 209 (FIG. 2-9) to lock upper ring 205 to intermediate ring 209, which, in turn, locks to lower ring 207 via the engagement of upper teeth 213 to lower teeth 214. The surgeon may press a pad 220 of locking element 215 to unlock upper ring 205 from intermediate ring 209. The spring back force caused by the twisting of first elastic member 208 while closing opening 250 allows access device 203 to immediately change to the open configuration. When the surgeon changes access device 203 from the open to the closed configuration, the relative rotation of upper ring 205 and lower ring 207 allows pawl 217 to automatically engage with recess 217. Further rotation then allows upper teeth 213 and lower teeth 214 to engage in order to maintain the size of opening 250. This type of locking mechanism is incorporated into the "Lap Disc Hand Access Device," which is available from Ethicon Endo-Surgery, Inc., Cincinnati, Ohio.

Those skilled in the art will appreciate that numerous other aspects of an access device are possible for providing a way to quickly change access device from a closed or partially closed configuration to an open configuration, and that access device 203 is provided as only one example. Access device 203 may also incorporate at least one access channel as described for, but not limited to, the other aspects of the access device described herein.

Tissue Markers and Method for Planning a Surgical Procedure

During a surgical procedure such as hand-assisted laparoscopy, the surgeon must identify tissue structures that are highly mobile within the body cavity, that have a similar coloration as surrounding tissues, and that are generally difficult to find under laparoscopic visualization. The surgeon uses laparoscopic tools and his/her hand to move organs and identify key, anatomical structures in order to plan the surgi-

cal procedure. For a tissue resection, for example, in which the surgeon cuts and removes internal tissue from the patient, the surgeon generally needs three types of information to plan the procedure: (1) Where are the proximal and distal end points of the resection? (2) Where is the proximal artery supplying blood to the tissue to be resected? and (3) Where should the line of resection be? Obtaining this information may be very time consuming, and so once the surgeon identifies a key, anatomical structure (or "landmark"), the surgeon would like to mark that area of tissue very conspicuously before searching for other key landmarks. Then the surgeon would be able to quickly find the structure again later during the procedure. Using the "zoom" feature on a laparoscope, and switching back and forth between a close-up view of tissue and a view of a wider area of tissue, may also disorient even experienced surgeons. Accordingly, a method for planning a surgical procedure using a tissue marker, and numerous aspects of a tissue marker, are provided.

FIG. 3-1 through FIG. 3-32 show ten different aspects of a tissue marker, which a surgeon may attach to tissue to indicate a key, anatomical structure. Each of the ten aspects of the tissue marker may be applied to tissue using an applier (single or multiple deploying) that is adapted for that particular tissue marker. Other tissue marker and applier aspects or modifications are possible, and may become apparent to those skilled in the art.

Generally, the tissue marker aspects described herein allow fast, easy, and accurate attachment to internal, soft tissue, and are highly visible throughout the surgical procedure. Each tissue marker aspect also provides the surgeon with the ability to label or otherwise signify meaningful information (using color coding, written information, etc.) to the tissue, to help the surgeon to plan the surgical procedure.

Depending on the type of surgical procedure, the tissue marker may also be made of a material to facilitate medical imaging. For example, the tissue marker may be formed from a radio opaque material for X-ray imaging. The tissue marker may be formed from or coated with a fluorescent material to enhance visibility during the procedure. Or the tissue marker may be made of a material that contains a multiplicity of microbubbles for ultrasonic imaging. The tissue marker may also include a doping agent to facilitate magnetic resonance imaging.

The tissue marker may also be made of an absorbable polymer such as "Vicryl" (Ethicon, Inc., Somerville, N.J.), which may be absorbed by the patient's body within a few weeks. Using an absorbable polymer provides the surgeon with the option to leave the tissue marker in the body after the surgical procedure is completed. Of course, the tissue marker may also be applied to a portion of tissue that is removed from the patient.

The tissue marker may also include an antimicrobial or a drug-eluting coating to inhibit the growth of bacteria in tissue surrounding the tissue marker.

FIG. 3-1 is a top view, FIG. 3-2 is a side view (before deployment), and FIG. 3-3 is a side view (after deployment) of a first aspect of a tissue marker 301. FIG. 3-4 is an illustration of tissue marker 301 during attachment to tissue, and FIG. 3-5A is an illustration of tissue marker 301 after attachment to tissue. Tissue marker 301 is a thin disc of metal or rigid plastic, having a central, fluted aperture 302 for entrapping tissue pulled within. An applier 303 (FIG. 3-4) retains tissue marker 301 and supplies a negative pressure to pull soft tissue 399 into aperture 302. Applier 303 may be attached to a length of flexible tubing that is fluidly connected to a controllable vacuum source (not shown). Applier 303 may also include the vacuum source, which may be a hand-operable

pump, for example. Tissue marker **301** may further comprise a flag **304** attached to disc **301**. Flag **303** may be color coded, preprinted with written matter (for example, “distal”), or contain a writing area on which the surgeon may create a custom label. Flag **304** may be made of any one of a number of biocompatible materials, including a fabric, plastic, elastomer, metal foil, coiled wire, and paper. Flag **304** may also be incorporated into the design of any of the other aspects of the tissue marker shown in FIG. 3-6 through FIG. 3-32.

FIG. 3-5B and FIG. 3-5C show a tissue marker **356** having an exemplary embodiment of a flag **359** that is formed from a flat coil of spirally wound, malleable material having an attached end **357** and a colored, free end **358**. The surgeon may attach tissue marker **356** to tissue while it is in a compact configuration, using an applicator as described for FIG. 3-5A. The surgeon then may grasp free end **358** with a conventional grasping instrument to extend flag **359**, thus making tissue marker **356** more conspicuous.

FIG. 3-6 is a top view, FIG. 3-7 is a side view (before deployment), and FIG. 3-8 is a side sectional view (after deployment) of a second aspect of a tissue marker **305**. Tissue marker **305** includes a disc **306** and a receiver **308**. A pair of legs **307** extend from the bottom of disc **306**, and insert into a pair of ramps **309** in the bottom of receiver **308**, so that during deployment, pair of legs **307** come together tip-to-tip to entrap tissue. Receiver **308** retains disc **306** in a one-time assembly. Tissue marker **305** attaches to tissue securely during the surgical procedure, but may be pulled off of the tissue when no longer needed. Tissue marker **305** may be injection molded, for example, from any one of a number of biocompatible polymers.

FIG. 3-9 is a top view, FIG. 3-10 is a sectional side view (after deployment), and FIG. 3-11 is a side view (before deployment) of a third aspect of a tissue marker **310**. Tissue marker **310** includes a plunger **311** inserted into a housing **312**. A hook **314** is attached to plunger **311** and extends from the bottom of housing **311** when the surgeon squeezes plunger **311** and housing **312** together, much like the way a “fishing bobber” can be attached to a fishing line. A spring **313** biases retraction of hook **314** into housing **312**. The surgeon may attach hook **314** into tissue and release plunger **311** to attach tissue marker **305** to the tissue. Plunger **311** and receiver **312** may be made of a biocompatible polymer, and hook **314** may be made of a stainless steel, for example.

FIG. 3-12 is a top view, FIG. 3-13 is a sectional side view (before deployment), and FIG. 3-14 is a side view (after deployment) of a fourth aspect of a tissue marker **315**. Tissue marker **315** includes a plunger **316** inserted into a housing **317**. A spring hook **318** is attached to plunger **316** and extends through the bottom of housing **317** and engages tissue (like a “cork screw”) when a surgeon grips plunger **316**, and pushes and rotates tissue marker **315** against the tissue of interest.

FIG. 3-15 is a side view, FIG. 3-16 is an end view, FIG. 3-17 is a front view (before deployment), and FIG. 3-18 is a front view (after deployment) of a fifth aspect of a tissue marker **319**. Tissue marker **319** includes a crown **324** from which extend a pair of legs **321**, spaced apart by a latch beam **323**. A latch **322** extends from the bottom side of crown **324**, so that when the surgeon deploys tissue marker **319** into the tissue of interest, latch **322** engages with a hole in beam **323** to hold legs **321** together, thus entrapping tissue and attaching tissue marker **319** to the tissue. A tab **320** extends from crown **320** to provide additional visibility and space for information. Tissue marker **319** may be injection molded from a biocompatible polymer. FIG. 3-19 is an end view, FIG. 3-20 is a front view (before deployment), and FIG. 3-21 is a front view (after deployment) of a sixth aspect of a tissue marker **325**. Tissue

marker **325** includes a hinged crown **326**, from which extends a pair of legs **327** separated by a spring beam **328**. Tissue marker **325** employs an “over-center” method of holding legs **327** together after deployment. When deployed, the bending of spring beam **328** provides a locking force to hold hinge crown **326** in the deployed configuration as shown in FIG. 3-21. Tissue marker **325** may be made of a biocompatible polymer.

FIG. 3-22 is a top view, FIG. 3-23 is a side view (before deployment), and FIG. 3-24 is a side view (after deployment) of a seventh aspect of a tissue marker **329**. Tissue marker **329** includes a clip **332** having a pair of legs **331** and molded from a biocompatible plastic. Clip **332** retains a thin washer **330** in a first position (before deployment) and a second position (after deployment). Washer **330** may be formed from a metal, a rigid polymer, or an absorbable material. Washer **330** holds legs **331** together after deployment, thus entrapping tissue therebetween.

FIG. 3-25 is a top view, and FIG. 3-26 is a side view, of an eighth aspect of a tissue marker **333**. Tissue marker **333** includes a button **334** attached to one end of a flexible (but stiff) cord **335**. An T-fastener **336** is attached to the other end of cord **335**. During deployment, T-fastener **336** is momentarily bent approximately parallel to cord **335** and penetrated into tissue. When released, T-fastener **336** resumes the original T-shaped configuration with cord **335**, thus attaching tissue marker **333** to the tissue. Tissue marker **333** may be made of a biocompatible polymer.

FIG. 3-27 is a top view, FIG. 3-28 is a sectional side view (before deployment), and FIG. 3-29 is a side view (after deployment) of a ninth aspect of a tissue marker **337**. Tissue marker **337** includes a metal disc **339** from which extends a pair of hooks **338** integrally formed from disc **339** in a stamping process. Before deployment, hooks **338** extend from the top side of disc **339**. After deployment, hooks **338** extend from the bottom side of disc **339**, thus entrapping tissue and attaching tissue marker **337** to the tissue.

FIG. 3-30 is a top view, FIG. 3-31 is a side view before deployment, and FIG. 3-32 is a side view after deployment, of a tenth aspect of a tissue marker **340**. Tissue marker **340** includes a metallic clip **341**, to which is attached a loop **342**. A surgeon may attach tissue marker **340** to tissue using any one of a number of conventional, surgical grasping and clamping instruments. FIG. 3-38 is an illustration of tissue marker **340** being attached to tissue **399** using an endoscopic grasping instrument **372**. Loop **342** may be color coded to designate key anatomical landmarks, and also provides a convenient handle for manipulating tissue during the procedure, or for attaching additional labels.

Surgeons have used marking pens routinely for marking incision lines on the skin of patients, but before now, specialized instruments and methods for marking lines on the surfaces of soft tissue inside the body have not been available. In addition to using tissue markers to identify key anatomical structures, the surgeon may also use marking fluids, for example, to indicate internal cutting lines during the planning of a surgical procedure.

FIG. 3-33 is a side view of a first embodiment of a marking tissue applicator **343**, which includes a syringe **348**, a connector **347**, a tube **346**, a stylus **345**, and a dispensing tip **344**. The surgeon may insert stylus **345** into the body cavity via a laparoscopic port. For hand-assisted surgery, stylus **345** may be approximately 5-10 centimeters long and handheld (like a pencil) by the surgeon inside the body cavity. For laparoscopic surgery, stylus **345** may be much longer (over 20 centimeters) for access into the abdomen via a trocar cannula. Syringe **348** may be filled with any one of a number of

marking fluids, including a biocompatible dye, stain, or colored adhesive. The surgeon may hold the dispensing tip **344** near the tissue to be marked (see FIG. 3-39) and inject drops of marking fluid onto the tissue along the desired cutting line.

FIG. 3-34 is a top view, and FIG. 3-35 is a side view of the distal portion of a second embodiment of a marking fluid applicator **349**. Marking fluid applicator **349** includes a pair of opposable arms **351** extending from the distal end of a closing tube **350** and normally biased in an open configuration. An end effector **352** is attached to each of arms **351** and configured for grasping tissue (a closed configuration is shown with phantom lines) when closing tube **350** is moved distally by an actuator on a handle (not shown). FIG. 3-36 is an enlarged, side view of a tissue interfacing surface **354** on one of end effectors **352**. Surface **354** contains a multiplicity of holes **353** for dispensing the marking fluid from a reservoir inside of end effector **352** (hidden) to the interfacing tissue. A tube **355** supplies marking fluid to end effector **352** from a syringe or other type of dispensing device on the proximal portion of the instrument (not shown). The diameter of holes **353** is dictated primarily by the viscosity of the marking fluid. Alternately, an absorbent material such as a foam rubber may be used in combination or instead of holes **353**, so that marking fluid may be properly transferred from the reservoir to the tissue without excessive dripping, etc.

The surgeon may use the tissue markers and marking fluids described for FIG. 3-1 through FIG. 3-39 to help plan and execute a surgical procedure by identifying key, anatomical structures in the body cavity. A method for performing a sigmoidectomy (removal of the sigmoid colon) is briefly described in conjunction with FIG. 3-37, and a method for performing a left colectomy (removal of the left colon) is briefly described in conjunction with FIG. 3-40 through FIG. 3-42. The broad method that includes the step of marking key anatomical structures, however, is equally applicable to numerous other surgical procedures, including any type of colectomy, nephrectomy, adrenalectomy, hepatic resection, distal gastrectomy, and exploratory surgery such as for trauma (knife and gunshot wounds, etc.) and peritonitis.

FIG. 3-37 is an illustration of the colon **360** of a surgical patient. A distal end point **366** is marked by tissue marker **301**, and a proximal end point **368** is marked by another tissue marker **301** to identify the portion (with adequate margin of healthy tissue) of the diseased sigmoid colon **362** to be resected. The mesenteric artery **370**, which supplies arterial blood to the sigmoid colon **362**, is marked by another tissue marker **301**. A cutting line **364** is marked by a marking fluid **372**. A method for resecting tissue from the body of a patient may include the following steps, although not necessarily in the order described. The surgeon accesses the body cavity, such as through a laparoscopic port or disc. The surgeon identifies and attaches a first tissue marker to the distal end point of the tissue to be resected. The surgeon identifies and attaches a second tissue marker to the proximal end point of the tissue to be resected. The surgeon identifies a cutting line and marks the cutting line with a marking fluid. The surgeon identifies and attaches a third tissue marker to the vessel that supplies arterial blood to the tissue to be resected. The surgeon ligates the arterial blood supply where the third tissue marker is attached. The surgeon resects the tissue between the first and second tissue markers, and along the cutting line. The surgeon removes the tissue from the body cavity of the patient.

FIG. 3-40 illustrates a portion of the colon **360** of a surgical patient, showing tissue marker **340** attached at a proximal end point **368**, and a cut line identified by marking fluid **372**. (The distal end point **366** is not visible.) A retraction device **374**,

attached to the body wall at first attachment **375** and second attachment **376**, assist the surgeon in visualizing and accessing the surgical site. FIG. 3-41 illustrates the next stage of the procedure, in which the mesenteric artery **370**, has been ligated with a surgical clip to block the blood supply to the tissue to be resected. Also, a portion of cutting line **364** has been cut (with a electrosurgical cutting instrument, for example) to create a window in the mesentery for insertion of a stapling instrument. FIG. 3-42 illustrates the next stage of the procedure, in which the surgeon has stapled and cut across the colon **360** to isolate the proximal portion of the tissue to be resected from the surrounding healthy tissue. The surgeon may do a similar stapling and cutting of the distal portion of the colon **360**.

Intra-Abdominal Storage Device

FIG. 4-1, FIG. 4-2, FIG. 4-3, and FIG. 4-4 are perspective views of a first, a second, a third, and a fourth aspect, respectively, of an intra-abdominal storage device, also referred to as a storage device. A surgeon may use the storage device for temporarily storing surgical instruments intra-abdominally (inside the abdominal cavity) during hand-assisted laparoscopic (HAL) surgery. The surgeon may also use the storage device to store and/or retrieve other objects associated with the surgery, such as tissue specimens, sutures, and sponges, and in other types of surgery, including open or thoracic procedures. During the HAL procedure and other minimally invasive procedures, the surgeon uses endoscopic visualization and has available a wide assortment of endoscopic instruments to aid in the placement, use, and removal of the storage device.

FIG. 4-1 is a perspective view of the first aspect of a storage device **402A**, which includes a pouch **404** having an opening **408** and a compartment **403**, a closing element **406**, and an attaching element **410A**. Pouch **404** may be made of a thin, flexible, biocompatible material that is resistant to tearing and puncture. For example, pouch **404** may be made of any one of numerous polymers including polyvinylchloride, polyethylene, polyester, polyurethane, and silicone films, and may alternately be made of a paper material, a mesh, or a fabric woven from a natural or synthetic fiber. Storage device **402A** and its packaging, as provided to the surgeon, may be sterilized using conventional methods such as gamma radiation, and in general, is made of cost-effective, disposable materials.

The surgeon may removably attach storage device **402A** to the inside of the body wall of the patient using attaching element **410A**, so that the surgeon may easily access storage device **402A** during the surgical procedure to insert or remove surgical instruments. In this first aspect, attaching element **410A** may be made of a braided or monofilament suture material, or any one of a number of materials having appropriate tensile strength, including stainless steel wire, natural fibers, and polymers.

In the first, second, third and fourth aspects of the storage device (**402A**, **402B**, **402C**, and **402D**, respectively) closing element **406** is a purse string disposed around the perimeter of opening **408**. Numerous other possible variations of closing element **406** include, but are not limited to, a clip, wire twist, snap, button, spring wire device such as used for some coin purses, and an interlocking seal, such as "ZIPLOC" (trademark, S.C. Johnson and Co.) that is well known for the application of food storage bags.

Attaching element **410A** is joined to a retaining element **412**, which provides a flat and robust attachment to pouch **404** to secure storage device **402A** to a structure in the body cavity. Retaining element **412** may be secured to the inside of pouch **404** by any one of a number of methods, including

adhering, sewing, or capturing in a fold of pouch **404**. Retaining element **412** is a thin, flat, and relatively rigid, compared to the material of pouch **404**, and may be made, for example, of a biocompatible plastic or paper. Retaining element **412** may alternately be secured to the outside of pouch **404**.

During the surgical procedure, the surgeon may introduce storage device **402A** into the body cavity of the patient via the main surgical opening that provides access to the surgical site. The surgeon may fold or roll up storage device **402A** to facilitate insertion into the body cavity, either via the primary surgical incision (that may contain a hand port or laparoscopic disc) or via a trocar cannula. As illustrated in FIG. 4-9, attaching element **410A** may be provided with a surgical needle **411** attached to the free end so that the surgeon may pass the needle through the body wall from inside of body cavity **494** to outside of the body, thus minimizing the size of the wound and eliminating the step of first making an body incision in body wall **494** for passing attaching element **410A**. Under laparoscopic visualization on the operating room monitor, the surgeon may insert and remove surgical instruments into opening **408**. Alternately, the surgeon may pass the free end of attaching element **410A** (without needle **411**) through a small incision in the body wall, pulling attaching element **410A** outwardly to position storage device **402A** against the inside of the body wall. The surgeon may secure the free end of attaching element **410A** to the patient's skin using, for example, tape, suture, or staples. The surgeon may change storage device **402A** from an open configuration to a closed configuration by holding slip knot **407**, while pulling on the free end of closing element **406**. Conversely, the surgeon may change storage device **402A** from the closed to the open configuration by loosening closing element **406**, in order to retrieve a surgical instrument. At the end of the surgical procedure, the surgeon may easily detach the free end of attaching element **410A** from the patient, and remove storage device **402A** from within the body cavity. Although not shown in the drawings, a suture needle may also be provided on the free end of closing element **406**, so that the free end of closing element **406** may be externalized, thus allowing the surgeon to close storage device **402** from outside the body.

Storage device **402A** and the other aspects of the storage device, may be manufactured in a number of different sizes to accommodate various surgical procedures. For HAL procedures in which the surgeon may desire to temporarily store very small, fingertip instruments inside of the patient's body, for example, the diameter of opening **408** may be approximately in the range of 3-5 cm, and the length of pouch **404** may be approximately in the range of 5-10 cm.

FIG. 4-2 is a perspective view of the second aspect of a storage device **402B** including pouch **404** having an opening **408**. A partition **422** separates a first compartment **418** from a second compartment **420**. The surgeon may temporarily store a surgical instrument inside of each of first compartment **418** and second compartment **420**, keeping them separated by partition **422**, and thus allowing easy retrieval of one or the other instruments. The surgeon may use closing element **406**, as described for the first aspect, for closing and opening storage device **402B**.

FIG. 4-3 is a perspective view of the third aspect of a storage device **402C**, including pouch **404** having opening **408**. A partition **435** separates a first compartment **424**, a second compartment **426**, and a third compartment **428**. The surgeon may separately store three surgical instruments in the third aspect of storage device **402C**.

FIG. 4-4 is a perspective view of the fourth aspect of a storage device **402D**, including pouch **404** having an opening

408. A partition **446** separates a first compartment **438**, a second compartment **440**, a third compartment **442**, and a fourth compartment **444**. The surgeon may separately store four surgical instruments in the fourth aspect of storage device **402D**.

Those skilled in the art will also recognize that storage devices **402B**, **402C**, and **402D** may be constructed using any one of numerous techniques. For example, separate plastic or cloth bags may be joined together to form a pouch with multiple compartments. Alternately, a single sheet of polymeric material may be folded and joined at seams by welding, gluing, or sewing, for example, to form a multi-compartment pouch. The plurality of compartments may also be arranged in a row or in other arrangements.

FIG. 4-5, FIG. 4-6, FIG. 4-7, and FIG. 4-8 show embodiments of the attaching element, as adapted for the third aspect of storage device **402C**, although all embodiments are equally adaptable to the other aspects of the storage device. Each embodiment allows the surgeon to removably secure storage device **402C** within a body cavity of a patient during a surgical procedure.

FIG. 4-5 is a perspective view of storage device **402C**, including a second embodiment of attaching element **410B** that includes an attaching rod **456** and a button **460**. Attaching rod **456** may be made of a biocompatible plastic or metal and attached to retaining element **412**, or attaching rod **456** and retaining element **412** may be injection molded from plastic as one piece. Attaching rod **456** may also be made of a flexible material, such as high density polyethylene, and passed through an incision already made in the body wall by the surgeon. Button **460** may be made of a plastic such as polyethylene. The surgeon introduces storage device **402C** into the body cavity of the patient, and pushes a piercing tip **459** of attaching rod **456** through the body wall, externalizing piercing tip **459** and a portion of attaching rod **456**. The surgeon holds storage device **402C** firmly against the inside of the body wall and (perhaps with assistance) positions button **460** onto attaching rod **456** so that a slot **462** of button **460** engages one of a plurality of teeth **458** on attaching rod **456**, thus holding storage device **402C** securely against the inside of the body wall. The surgeon may cover, bend over, or cut-off tip **459** to avoid accidental injury during the rest of the surgical procedure. The surgeon may remove button **460** from attaching rod **456** in order to relocate storage device **402C** or to remove storage device **402C** from the body cavity. The surgeon may also bend over the externalized portion of attaching rod **456** and tape it to the skin of the patient, rather than use button **460**.

FIG. 4-6 is a perspective view of a third embodiment of an attaching element **410C**, including an attaching rod **464** having a plurality of holes **466**, and a pin **468**. Attaching rod **464** may be made of a rigid, biocompatible plastic or metal. Attaching rod **464** is attached to or molded as one piece with retaining element **412**. Attaching rod **464** includes a piercing tip **469** so that attaching element **410** may be positioned in the body wall as described for the first embodiment shown in FIG. 4-5. Once a portion of attaching rod **464** is externalized from within the body cavity, the surgeon may insert a pin **468** into one of the plurality of holes **466** in attaching rod **464**, to secure storage device **402** inside of the body cavity. The piercing tip may be covered, bent over, or cut-off to prevent accidental injury during the procedure. Upon completion of the surgical procedure, the surgeon may easily remove pin **468** and withdraw storage device **402C** from the body cavity.

FIG. 4-7 is a perspective view of a fourth embodiment of an attaching element **410D**, including an elastic loop **470** attached to retaining element **412**. The surgeon may external-

ize a portion of elastic loop **470** through a small incision in the body wall, and hold storage device **402** against the inside of the body wall, for example, by pulling up on elastic loop **470** and clamping surgical clamps onto elastic loop **470** against the skin of the patient. Alternately, elastic loop **470** may be stretched around the portion of the trocar cannula extending into the body cavity, or around a portion of any one of a number of surgical instruments used during the surgical procedure and having at least a portion extending inside of the body cavity. Elastic loop **470** may be made of a biocompatible elastomer, for example, such as silicone rubber or polyurethane rubber.

FIG. **4-8** is a perspective view of a fifth embodiment of an attaching element **410E**, including a clip **472** attached to retaining element **412** with a fastener **474**. The surgeon may removably attach clip **472** to the internal portion of the cannula of a surgical trocar port as shown in FIG. **4-10**. Fastener **474** may be a post that is molded integrally with retaining element **412**, and loosely heat-staked to clip **472**, so that clip **472** may pivot. Clip **472** is made of a biocompatible, spring-like plastic or metal so that clip **472** may grip onto the trocar cannula. FIG. **4-11** illustrates storage device **402C** in the closed configuration and with the fifth embodiment of attaching element **410D** (not shown in FIG. **4-11**; see FIG. **4-10**) removably attached to the cannula **498** of a surgical trocar **496** penetrating body wall **490**. Closing element **406** has been drawn through slip knot **407** to securely contain a surgical instrument **499** within storage device **402C**.

FIG. **4-12** is a sectional view of a sixth embodiment of an attaching element **410F**, shown on storage device **402A** in the open configuration and within the body of a patient. Sixth embodiment of attaching element **410F** includes a tubular attaching rod **484** and a cap **486**. Attaching rod **486** has a flange **480**, which is analogous to retaining element **412**, and is made of a biocompatible metal or plastic. The surgeon may initially penetrate attaching rod **484** into body wall **490** as described for the embodiments of the attaching element shown in FIG. **4-5** and FIG. **4-6**. The sixth embodiment shown in FIG. **4-12** includes the free ends of closing element **406** (which is again a purse string disposed about opening **408**)) extending through a channel **477** of attaching rod **484** so that the surgeon may close or open storage device **402C** from outside of the patient. The surgeon may removably press cap **486** over attaching rod **484**, as shown in FIG. **4-13**, to hold storage device **402C** in the closed configuration and to protect a piercing tip **479**. A cap flange **482** presses against the outside of body wall **490** to retain storage device **402C** against the inside of body wall **494**. Cap **486** is made of a biocompatible plastic or elastomer and has a tight sliding fit over attaching rod **484**.

Other embodiments for the attaching element are possible. For example, attaching element may incorporate a ferrous material attached to the pouch and held against the inside of the body wall using an external magnet.

Surgical Retraction Device for Creating a Visceral Barrier

The viscera inside the abdominal cavity is highly mobile and slippery. During a hand-assisted laparoscopic procedure, for example, the surgeon may need to “compartmentalize” the abdominal cavity in order to view and operate on particular organs. During some laparoscopic procedures, the surgeon tips the operating table to cause the patient’s abdominal viscera to shift away from an area of interest in the body cavity. The surgeon may refrain from tipping certain patients (gun-shot wounded patients, elderly patients, etc.) to minimize stress on the heart. In those and other cases, the surgeon may use any one of the numerous aspects of a retraction device illustrated in FIG. **5-1** through FIG. **5-52** to “corral” viscera

(such as the colon) out of the way, or to “put away” tissues already examined. The retraction device helps the surgeon to create a wall-like structure, or visceral barrier, at a transverse abdominal line somewhere between the rib cage and the pelvis. The retraction device has a tissue interface with a large, projected area for holding the viscera away from the surgical site. The surgeon may use the retraction device to lift or to suspend tissue, such as when examining the vasculature the intestinal mesentery. The retraction device generally is easy to manipulate and position in the body cavity, easy to hold in position for the duration of the procedure, and easy to remove from the body cavity.

Turning now to the drawings, FIG. **5-1** illustrates a first aspect of a surgical retraction device **501** retracting a colon **500** of a surgical patient. Retraction device **501** includes an elongated column **502** removeably attached to an attachment handle **504** centrally located on a rectangular, barrier element **503**. Column **502** includes a conventional, laparoscopic, surgical clamping instrument that the surgeon may pass through a laparoscopic port (not shown) before attaching to attachment handle **504**. The surgeon may introduce barrier element **503** into the body cavity, for example, via the laparoscopic disc. Barrier element **503** is formed from a malleable material, such as a metallic wire reinforced, biocompatible elastomer. Barrier element **503** has a length of approximately 20 centimeters and a width of approximately 5 centimeters. The surgeon may use retraction device **501** in combination with a number of ancillary, surgical instruments **599**, to manipulate and support visceral tissues in the body cavity. Once the surgeon is satisfied with the placement of the visceral barrier, the external portion of column **502** may be held by a surgical assistant, weighted, or temporarily attached to an immobile structure outside the body cavity.

The surgeon may use each of the remaining aspects of the retracting device in a similar fashion as the first aspect of FIG. **5-1**, with some variations as will be described. FIG. **5-2** is a perspective view of a second aspect of a retraction device **505**, which includes a bifurcated column **506** having a pair of arms **509**. The end of each of arms **509** pivotally attach to the opposing sides of a book-like, foldable barrier element **507**. A remotely operable, actuating rod **508** of column **506** attaches to barrier element **507** so that the surgeon may change retracting device **505** between a closed configuration and an opened configuration. The surgeon may introduce the distal portion of retracting device **505** into the body cavity via a laparoscopic disc.

FIG. **5-3** is a perspective view of a third aspect of a retraction device **510** including a column **511** removeably attached to a barrier element **512**. Barrier element **512** has a plurality of vacuum apertures **513**, which fluidly communicate via a channel through column **511** with a vacuum source (not shown). Barrier element **512** is covered with a cover material **514**, which may comprise a cotton gauze or fabric, to improve the surgeon’s ability to manipulate tissue atraumatically. The surgeon may introduce barrier element **512** through a laparoscopic disc or port before attaching it to the distal end of column **511**.

FIG. **5-4** is a perspective view of a fourth aspect of a retraction device **515**, while in a closed configuration, and FIG. **5-4** shows retraction device **515** in an opened configuration. Retraction device **515** includes three arms **517** extendable from the open, distal end of a column **516**. A barrier element **518**, including a flexible material such as a fabric or plastic film, is attached to arms **517**, so that when arms **517** are remotely actuated by the surgeon to extend from the end of column **516**, arms **517** spread apart and tension barrier element **518**.

FIG. 5-6 is a perspective view of a fifth aspect of a retraction device 519, while in a closed configuration, and FIG. 5-7 shows retraction device 519 in an opened configuration. Retraction device 519 includes a pair of parallel bars 521 that are extendable from the distal end of a column 520 so that bars 521 are perpendicular to column 520 in the opened configuration. Bars 521 are pivotally attached to column 520 so that bars 521 are parallel to column 520 in the closed configuration, and so that the surgeon may pass the distal portion of retraction device 519 through a laparoscopic port. A barrier element 523 is formed by a webbing material.

FIG. 5-8 is a perspective view of a sixth aspect of a retraction device including a pair of L-shaped, bar elements 526 that are covered with a cover material 527, and each of which are attached at a common pivot 593 to the distal end of a column 525. The surgeon may actuate bar elements 526 to be approximately flush with the outside diameter of column 525 while in a closed configuration, and to swing out to be perpendicular to column 525 while in an opened configuration.

FIG. 5-9 is a perspective view of a seventh aspect of a retraction device 528 including a barrier element 530 that is extendable from the open end of a column 529. Barrier element 530 may be formed from a flat stock of spring steel that forms a ninety degree bend when unconstrained. Barrier element 530 is covered with a cover material 531.

FIG. 5-10 illustrates an eighth aspect of a retraction device 532, while in an opened configuration and retracting the colon 500 of a surgical patient. Retraction device 532 includes a pair of arms 534 attached to an attachment handle 535, which a surgeon may hold with a conventional laparoscopic clamp 533. Arms 534 may be opened as shown to form a V-shape, tensioning a pair of cords 537 attached to arms 534. A webbing type, barrier element 536 is attached to cords 537 and arms 534, forming a large, see-through, tissue interface surface while in an opened configuration.

FIG. 5-11 illustrates a ninth aspect of a retraction device 538, while in an opened configuration and retracting the colon 500 of a surgical patient. Retraction device 538 includes a webbing type, barrier element 542 attached to a collapsible, elliptical ring 594, which may be made of a spring steel wire or a shape-memory metal (Nitinol). The ends of a beam element 541 are attached to ring 594. A handle 542 centrally located on beam element 541 provides a convenient grasping point for a laparoscopic clamping instrument 539.

FIG. 5-12 is a perspective view a tenth aspect of a retraction device 543 in a closed configuration. FIG. 5-13A shows retraction device 543 while in a partially open configuration. FIG. 5-13B shows retraction device 543 while in an opened configuration. Retraction device 543 includes a barrier element 545 that passes through a hollow column 544. Barrier element 545 is formed by a band composed of a flexible but stiff material such as high density polyethylene. The distal end of barrier element 545 extends out of the open, distal end of column 544, and is attached to an attachment canopy 547 on the outside of column 544. As shown in the drawings, the surgeon may remotely push barrier element 545 out of the open end of column 544 to form a T-shape, supported in the center of the extended barrier element 545 by a remotely operable rod 546.

FIG. 5-14 is a perspective view of an eleventh aspect of a retraction device 548 including a pair of arms 550 that may be retracted into the open end of a column 549 by a retraction rod 595.

FIG. 5-15 is a perspective view of a twelfth aspect of a retraction device 551, shown retracting the colon 500. Retraction device 551 includes a pair of arms 553 formed from a flat, spring material and extendable from a column 552.

FIG. 5-16 is a side view of a thirteenth aspect of a retraction device 554 while in an opened configuration. FIG. 5-17 shows a partially opened configuration, and FIG. 5-18 shows a closed configuration. Retraction device 554 includes a barrier element 558 formed by a collapsible frame 556 and a webbing 557. Barrier element 558 is retractable into the open end of a column 555, to facilitate introduction into and removal from the body cavity via a laparoscopic port.

FIG. 5-19 illustrates a fourteenth aspect of a retraction device 559 retracting the colon 500 of a surgical patient. Retraction device 559 includes a pair of arms 561 that spring apart when not constrained inside the open end of a column 560. On the end of each arm is a pad 562 having an atraumatic cover 563 (see FIG. 5-20).

Each of the following aspects of the retraction device (shown in FIG. 5-21 through FIG. 5-52) comprise a wall-like, barrier element that optionally may be positioned and held in the body cavity by a laparoscopic clamping instrument. For clarity, the clamping instrument is not shown in some of FIG. 5-21 through FIG. 5-52. Each of the following aspects of the retraction device may be "self-supporting" inside of the body cavity. That is, the perimeter of the barrier element is positionable against the body wall and organs within the body cavity to remain in place without being held by a clamping instrument. In most aspects to be described, however, handles are provided on the barrier elements to facilitate manipulation and holding by a clamping instrument. Each of the aspects of the retracting device shown in FIG. 5-21 through FIG. 5-52 may be sized, while in the opened configuration, to substantially span either or both the transverse width and the vertical height of the patient's body cavity.

FIG. 5-21 is a sectional view of a fifteenth aspect of a retraction device 564, while in a closed configuration and being passed through a laparoscopic port. FIG. 5-22 is an end view of retraction device 564, while in the extended configuration. FIG. 5-23 is a front view of retraction device 564, while in the closed configuration. Retraction device 564 includes a plurality of panel barrier elements 565 attached together, edge-to-edge, in a row by a plurality of hinges 567. Retraction device 564 includes a plurality of handle cutouts 566 to facilitate grasping by a clamping instrument. In one version of this aspect, each of hinges 567 may flex in either direction so that panels 565 may be rolled up from either side. In another version of this aspect, hinges 567 may flex in only one direction so that panels 565 may be rolled up from only one side. When unrolled to the opened configuration, retraction device 564 resists bending from one direction.

FIG. 5-24 is a front view of a sixteenth aspect of a retraction device 568 including a first barrier element 569 and a second barrier element 570 that interlock at a central, interlocking joint 571 once introduced into the body cavity. A cover material 572, such as a gauze of fabric, covers each of first and second barrier elements, 569 and 570. The surgeon may hold retraction device 568 with a clamping instrument clamped onto one of handles 573.

FIG. 5-25 illustrates an seventeenth aspect of a retraction device 574 retracting the colon 500 of a surgical patient. FIG. 5-26A is a front view of retraction device 574, while in an opened configuration. FIG. 5-26B is a front view of retraction device 574, while in a partially closed configuration. Retraction device 574 includes four panel barrier elements joined together at folds 577, and includes a plurality of handle cutouts 576. Retraction device 574 may be die-cut from a polyethylene sheet, for example, with folds 577 including thermally-formed creases. As shown in FIG. 5-26B, retraction

device **574** is foldable in a concertina manner, and may be easily deployed into the opened configuration while inside the body cavity.

FIG. **5-27** illustrates an eighteenth aspect of a retraction device **578** retracting the colon **500** of a surgical patient. Retraction device **578** includes a barrier element **579** formed by a plurality of frames **581** flexibly joined in a row, side-to-side. Each of frames **581** is covered with a mesh or webbing material.

FIG. **5-28** illustrates a nineteenth aspect of a retraction device **582** retracting the colon **500** of a surgical patient. Retraction device **582** includes a barrier element **583** formed from a sheet of flexible, biocompatible material, such as polyethylene, and including a plurality of handle cut-outs **584**.

FIG. **5-29** is a perspective view of a twentieth aspect of a retraction device **585** including a barrier element **586** injection molded from a biocompatible polymer such as polypropylene. Retraction device **585** includes a plurality of handle projections **587** extending from one side of barrier element **586**, and a plurality of handle cutouts **588**.

FIG. **5-30** is a front view of a twenty-first aspect of a retraction device **589**, while in a first, partially closed configuration. FIG. **5-31** shows retraction device **589**, while in a second, partially closed configuration. FIG. **5-32** shows retraction device **589**, while in an opened configuration. Retraction device **589** includes four panel barrier elements joined by a plurality of hinges **591**, and including a plurality of handle cutouts **592**. Retraction device **589** may be formed, for example, by either a die-cutting or an injection molding process from a biocompatible polymer.

FIG. **5-33** is a top view and FIG. **5-34** is a front view of a twenty-second aspect of a retraction device **5000**, which includes four panel barrier elements **5001** joined edge-to-edge in a row by three pinned hinges **5002** that swing in either direction. Panels **5001** may be formed from a metal or injection molded from a biocompatible polymer. Each of hinges **5002** may contain a detent or locking feature that holds panels **5001** in the instant configuration until a sufficient external force is applied. Retraction device **5000** includes a plurality of handle cutouts **5003**.

FIG. **5-35** is a top view and FIG. **5-36** is a front view of a twenty-third aspect of a retraction device **5005**. Retraction device **5005** includes four panel barrier elements **5006** joined together in a row by a plurality of flexible bands **5007** woven alternately on the front and the back sides of each of barrier elements **5006**, forming three hinges **5008** that may swing in either direction. A surgeon may extend and position retraction device **5005** in the body cavity and allow the abdominal wall to rest on the top edge of retraction device **5005**, perhaps by reducing insufflation pressure in the body cavity, so that retraction device **5005** may remain extended while resisting the force of tissue bearing against it.

FIG. **5-37A** is a top view and FIG. **5-38** is a front view of a twenty-fourth aspect of a retraction device **5010**, while in an extended configuration. FIG. **5-37B** is a detailed, top view of retraction device **5010**, while being folded into a rolled-up or closed configuration. Retraction device **5010** includes a plurality of panel barrier elements **5011** joined together edge-to-edge in a row by a plurality of hinges **5013**. A plurality of wires **5012** embedded in barrier elements **5011** form hinges **5013**. A plurality of stop elements **5009** attached to or integrally formed on the tissue-bearing side of each of panel barrier elements **5011** are arranged so that retraction device **5010** may fold in only one direction. This allows the surgeon to introduce retraction device **5010** while in the rolled-up or closed configuration into the body cavity. When in the

extended configuration, retraction device **5010** resists the force of tissue bearing against it, so that it remains extended.

FIG. **5-39** is a top view, FIG. **5-40** is a front view, and FIG. **5-41** is an end view of a twenty-fifth aspect of a retraction device **5015**. Retraction device **5015** includes a malleable barrier element **5016** formed from a metallic mesh **5018** embedded in a biocompatible, elastomeric material **5019**. Metallic mesh **5018** may be formed from a screen-like material, a plurality of wires or rods, and the like. Barrier element **5016** includes a plurality of fingers **5017** that may be bent over to a desired shape to fit inside the body cavity and properly retract tissue. The surgeon may easily form barrier element **5016** into the desired shape after placement into the body cavity, but barrier element **5019** is stiff enough to provide a visceral barrier.

FIG. **5-42** is a front view of a twenty-sixth aspect of a retraction device **5021**. FIG. **5-43** shows retraction device **5021**, while in a twisted configuration. Retraction device **5021** includes a barrier element **5024** formed from a metallic mesh **5022** covered with an polymeric, biocompatible coating. The surgeon may easily form barrier element **5024** into the desired shape after placement into the body cavity, but barrier element **5024** is stiff enough to provide a visceral barrier.

FIG. **5-44** is a top view and FIG. **5-45** is a front view of a twenty-seventh aspect of a retraction device **5027**, including a plurality of panel barrier elements **5028** joined together edge-to-edge in a row by a pair of flexible bands **5030**. Because barrier elements **5028** are assembled with substantially no gap between adjoining barrier elements, and because bands **5030** are affixed to only one side of barrier elements **5028**, retraction device **5027** may flex in only one direction. The surgeon may position retraction device **5027** against the viscera so that retraction device **5027** is flexible in the distal direction (towards the viscera) to create the visceral barrier. A flexible, plastic cover **5029** is provided to cover potential pinch-points between adjoining barrier elements **5028**.

FIG. **5-46** is a top view and FIG. **5-47** is a front view of a twenty-eighth aspect of a retraction device **5031**, including a barrier element **5032** formed by a plurality of nested segments **5033** that may telescope in one direction between an opened and a closed configuration. A second retraction device **5031** may be joined by numerous methods (barb and hook latches, for example) to a first so that the two nested segments **5033** of the two retraction devices **5031** telescope in opposing, lateral directions. Sliding-fit frictional force, detents, or interlocking features may be incorporated into nested segments **5033** to hold retraction device **5031** in the desired configuration to provide an effective visceral barrier, yet be adjustable by the surgeon within the body cavity.

FIG. **5-48** is a top view and FIG. **5-49** is a front view of a twenty-ninth aspect of a retraction device **5035**, including a plurality of panel barrier elements **5036** joined together, edge to edge in a row, by a plurality of hinges **5037**. Barrier elements **5036** may be unitarily formed, such as by die-cutting from a sheet of polyethylene. Hinges **5037** may be thermally formed creases in the sheet material. A plurality of extendable fingers **5039**, which may be made from the same material as barrier elements **5036**, are pivotally attached to barrier elements **5036**. The surgeon may swing each of fingers **5039** independently between a down and an up position as required, to increase the effective height of the visceral barrier. Retraction device **5035** also includes a plurality of windows **5038** for viewing through the device or for grasping with a clamping instrument.

FIG. **5-50** is a top view of a thirtieth aspect of a retraction device **5042**. FIG. **5-51** is a front view of retraction device

5042, while in a closed configuration. FIG. **5-52** is a front view of retraction device **5042**, while in an opened configuration. Retraction device **5042** includes a hollow, barrier element **5043** that houses a curtain **5047** in the closed configuration. The ends of a flexible dowel **5045** are inserted into the opposing ends of barrier element **5043**. An external loop portion **5040** of dowel **5045** wraps around approximately one half of the perimeter of barrier element **5043**. The ends of dowel **5045** are operably connected to an extension mechanism **5046** inside of barrier element **5043**. The top of curtain **5047** is attached to loop portion **5040**, and the bottom of curtain **5047** is retained inside of barrier element **5043**. The surgeon may grasp a handle **5044** with a clamping instrument and rotate handle **5044** in the counter clockwise direction to deploy curtain **5047** to extend the height of barrier element **5043**. Curtain **5047** may be formed from any one of a number of fabrics, mesh materials, films, and the like.

FIG. **5-53**, FIG. **5-54**, and FIG. **5-55** show a thirty-first aspect of a retraction device **5050** including at least one central panel **5052** of uniform thickness, and a pair of end panels, **5054** and **5056**, each attached to central panel **5052** by at least one flexible hinge element **5058**, and each having a non-uniform thickness that tapers in a direction away from hinge element **5058**. As shown in FIG. **5-55**, end panels **5054** and **5056** may fold onto central panel **5052** so that the overall thickness of retraction device **5050** is relatively small as compared to a similar device in which all panels have a uniform thickness.

FIG. **5-56** is a front view and FIG. **5-57** is an end view of a thirty-second aspect of a retraction device **5060** while in an extended configuration. Retraction device **5060** includes a plurality of panels **5062** joined by a plurality of hinges **5064**. Each of panels **5062** may be formed from a spring-like material, such as for example, shape memory metal (Nitinol) so that each panel **5062** may be flattened for rolling up into a closed configuration for introduction into the body cavity. When retraction device **5060** is in the extended configuration, each of panels **5062** may curl as shown in FIG. **5-57** so that retraction device **5060** may resist the force of tissue bearing against one side and form an effective partition. Surgical Instrument System Having Removably Attachable End Effectors

During some surgical procedures, the surgeon must grasp, clamp, retract, suspend, and/or manipulate soft, fluidic tissues within the insufflated body cavity, being careful not to injure the tissues. In open surgical procedures, the surgeon has a large array of surgical instruments with large end effectors specifically designed for various steps of the procedure. Also in open surgical procedures, the surgeon often places a folded-over, gauze sponge within the end effectors of an open surgery instrument to broaden and soften the tissue interface surface. During traditional, laparoscopic procedures, it is not always possible to pass such large instruments or a folded sponge through a laparoscopic port. During hand-assisted, laparoscopic procedures, however, the lap disc provides a relatively large port for introducing devices into the body cavity, with only momentary loss of insufflation pressure. Consequently, it is possible to provide a surgical system that allows a surgeon to introduce a surgical instrument with extra large end effectors into a body cavity.

FIG. **6-1** through FIG. **6-11** show numerous aspects of surgical instruments, each having removably attachable end effectors that are too large to pass through a conventionally sized trocar cannula. FIG. **6-1** is a front view of the distal portion of a first embodiment of a surgical instrument **601**, shown with a first end effector **614** and a second end effector **616**. A first arm **604** and an opposable second arm **606** extend

from the distal end of an elongated shaft **602**, which may pass through a conventional trocar cannula when end effectors **614** and **616** are not attached. Surgical instrument **601** includes a handle with an actuator (not shown) for opening and closing arms **604** and **606**. As shown for arm **604** in FIG. **6-2** and FIG. **6-3**, each of arms **604** and **606** has an attachment slot **608** and a detent recess **610**. Each of first and second end effectors **614** and **616** also has an attachment element **620** for insertion into attachment slot **608**, and a detent **612** for engagement with detent recess **610**. Each of first and second end effectors **614** and **616** has an atraumatic grasping element **618** made of a soft, elastic, biocompatible material such as a foam rubber. When end effectors **614** and **616** are attached to arms **604** and **606**, the distal portion of surgical instrument **601** may be too large to pass through some conventional, laparoscopic ports.

Atraumatic grasping elements **618** may also be formed or coated from any one of a number of medical grade hydrophilic polymers. These polymers have high water permeability, are waterproof, have low water absorption, have high flexibility and impact strength at low temperatures, have good mechanical and elastic properties, have good heat stability, have good resistance to chemicals, and are easy to process. Very common commercial hydrophilic materials are copolymers made of polyethylene oxide, crystallizable polyamide, polyurethane, and polyester.

FIG. **6-4** is a front sectional view of a second embodiment of an arm **626** having an attachment aperture **626** and a female thread **628**. An alternate version of an end effector **621** has an attachment element **622** with a male thread **624** for removable attachment to arm **630**. Attachment elements **620** and **622** are only examples of the many types of features for removably attaching an end effector to an arm of a surgical instrument, as is apparent to those skilled in the art.

FIG. **6-5** is an end view and FIG. **6-6** is a front view of a second aspect of an end effector **632**, including a pair of parallel side walls **634** and **636** connected by three, transverse columns **638** arranged to hold a replenishable, tissue interface element **640**. Interface element **640** may be formed, for example, from a conventional, surgical sponge or gauze material. End effector **632** also includes attachment element **620** and detent **612**, as shown for end effector **614** in FIG. **6-1**, for removable attachment to surgical instrument **601**.

FIG. **6-7** is an end view and FIG. **608** is a front view of a third aspect of an end effector, which is the same as end effector **632** shown in FIG. **6-6**, but having a replenishable, tissue interface element **644** formed from a roll of biocompatible material such as cotton gauze or a silicone foam tape, for example. Interface element **644** includes a free end **646** that may be pulled by the surgeon to present a fresh surface of interface element **644** to the tissue. Free end **646** may be externalized through the body wall via the laparoscopic port so that the surgeon may remotely replenish interface element **644**.

FIG. **6-9** is a front view and FIG. **6-10** is a top view of the distal portion of a surgical instrument **646**, shown with a first end effector **650** and a second end effector **652**, each of which represent a fourth aspect of an end effector. Surgical instrument **646** includes a pair of opposing, wire-formed arms **654** and **656**. The surgeon remotely operates closing tube **648** to translate longitudinally in the distal direction to close arms **654** and **656**, and in the proximal direction to open arms **654** and **656**. Each of first and second end effectors **650** and **652** has a slot **658** (see FIG. **6-11**) for removable attachment onto arms **654** and **656**. End effectors **650** and **652** may be formed by any one or a composite of a number of biocompatible materials, including a foam rubber or a low durometer sili-

cone rubber. Slot **658** may be sized to stretch slightly during attachment to one of arms **654** and **656** to insure retention during use.

FIG. **6-12** illustrates part of a first method for performing a hand-assisted, laparoscopic procedure. The method includes providing a surgical instrument system **670** that includes a lap disc **662** and a surgical instrument **601** with a first and a second, detachable end effector, **614** and **616**. The method further includes placing lap disc **662** in the body wall **666** of the patient, placing the distal portion of surgical instrument **601** into body cavity **668** when end effectors **614**, **616** are not attached to surgical instrument **601**, introducing end effectors **614**, **616** into body cavity **668** via lap disc **662**, and assembling end effectors **614**, **616** to surgical instrument **601**. For removal of surgical instrument **601**, the method further includes removing end effectors **614**, **616** from the surgical instrument **601**, removing surgical instrument **601** from body wall **666**, and removing end effectors **614**, **616** from body cavity **668** via lap disc **662**. The first method may also include the step of storing the end effectors in an intra-abdominal storage device (see FIG. **4-1** through **4-15**) inside of the body cavity.

FIG. **6-13** illustrates part of a second method of performing a hand-assisted, laparoscopic procedure. The second method includes providing a surgical instrument system **672** that includes a lap disc **662**, a lap disc insert **680** having at least one port **682**, and a surgical instrument **601** with a first and a second, detachable end effector, **614** and **616**. The method further includes placing lap disc **662** in the body wall **666** of the patient, placing the distal portion of surgical instrument **601** through lap disc port **682** of lap disc insert **680**, attaching end effectors **614**, **616** to surgical instrument **601**, and attaching lap disc insert **680** to lap disc **662** so that end effectors **614**, **616** are inside body cavity **668**. For removal of surgical instrument **601** from body cavity **668**, the method further includes removing lap disc insert **680** from lap disc **662** so that end effectors **614**, **616** are removed from body cavity **668** via lap disc **662**.

The first and second methods for performing a hand-assisted, laparoscopic procedure may also be used with other surgical instruments having removably attachable end effectors. The first and second methods may also include insufflating the body cavity while the end effectors are inside the body cavity.

Tissue Suspension Device

FIG. **7-1** through FIG. **7-13** disclose a tissue suspension device for suspending tissues within the body cavity of a patient. A surgeon may use the tissue suspension device in combination with insufflation, orientation of the patient, and other well-known laparoscopic surgery techniques, to improve visualization of and access to tissues of interest within the abdominal cavity during a hand-assisted, laparoscopic procedure. The surgeon may also use the tissue suspension device for open, abdominal, surgical procedures, to eliminate the need for other retraction devices currently used that partially obstruct the surgical opening, to provide the surgeon with improved access and visualization into the abdominal cavity.

FIG. **7-1** is a side view of surgical patient **799** while abdomen **798** is insufflated with carbon dioxide. For clarity, the associated instruments, systems, and personnel required for laparoscopic surgery are not shown. FIG. **7-2** is a cross-sectional view of patient **799**, taken at line **2-2** of FIG. **7-1**. A first aspect of a tissue suspension device **702** suspends an organ **796** (in this example, the transverse colon). Tissue suspension device **702** includes an elongated spanning element **704** having a first end **712** removably attached to body

wall **794** by a first supporting element **708**, and a second end **714** removably attached to body wall **794** with a second supporting element **709**. The patient's body wall, therefore, supports the weight of the suspended tissue, as opposed to "wall lift" or "gasless surgery" devices that attach to a structure mounted on the surgical table and are sometimes used in place of insufflation to enlarge the body cavity. Suspension system **702** further includes at least one, hook-like suspending element **706** removably attached to spanning element **704**. FIG. **7-1** shows a pair of suspending elements **706** suspending organ **796** within body cavity **792**, thereby providing improved access to and visualization of the mesenteric vasculature **790**, which supplies blood to organ **796**.

FIG. **7-3** through FIG. **7-6** show additional views of suspension system **702**. FIG. **7-4** shows spanning element **704** with a plurality of holes **716** arranged to provide multiple positions for inserting a pair of ends **707** of suspending element **706**. Each of first end **712** and second end **714** of spanning element **704** includes an offset **728**. Offset **728** allows the surgeon to attach spanning element **704** to the body wall while maintaining an assured vertical clearance between the top of the body cavity and spanning element **704**. FIG. **7-6A** shows first end **712** having a retention portion **726** for the removable attachment of a first elastomeric tube **710** of supporting element **708**. FIG. **7-5** shows second end **714** having a retention portion **726** for the removable attachment of a second, elastomeric tube **710** of supporting element **709**. In a manner to be described, the surgeon places spanning element **704** across the body cavity so that first end **712** extends through the body wall on one side of the patient and second end **714** extends through the body wall on the opposite side of the patient. Then the surgeon may attach one of tubes **710** on each of first and second ends, **712** and **714**. The surgeon next may place one of a pair of cuffs **711** onto each of first and second ends, **712** and **714**, to atraumatically support spanning element **704** against the external surface of body wall **794**. Each cuff **711** has a pair of parallel slits **713** for "weaving" onto first and second ends, **712** and **714**. FIG. **7-6B** shows first end **712** assembled to supporting element **708**. Cuffs **711** also provide torsional resistance to spanning element **704**, which may tend to twist within the body wall when supporting tissue.

The surgeon may position spanning element **704** into the body cavity using a number of methods. For example, the surgeon may first incise body wall **794** with a scalpel, or penetrate the body wall with a sharp tip **722** of second end **714**, and then guide second end **714** across the body cavity to avoid accidental injury to internal organs, using his/her hand inserted into the body cavity via the laparoscopic disc. The surgeon may then penetrate the body wall on the opposite side of the patient, or create an incision with a scalpel, to externalize second end **714**. In another example, the surgeon may attach a cap **718** (FIG. **7-5**) onto retention portion **724** of second end **714**. The surgeon may then insert the free end of a filament **720**, which may be a metal wire or a suture attached to cap **718**, into an entry incision on one side of the patient, and out of an exit incision on the other side of the patient. Then the surgeon may use filament **720** to pull spanning element **704** into the body cavity. Alternately, a needle (not shown) may be attached to the free end of filament **720** for penetration through the body wall.

Once the surgeon has placed spanning element **704** into the body cavity and attached first and second ends, **712** and **714**, to the body wall, the surgeon may next hook at least one suspending element into a pair of adjacent holes **716** of spanning element **704**, again using his/her hand inserted into the body cavity via the laparoscopic disc. The surgeon may then

lift the tissue/organ into suspending element 706. When the surgeon no longer needs suspension system 702, the surgeon may remove suspending element 706, detach either first end 712 or second end 714 from one side of the patient, and pull spanning element 704 out of the opposite side of the patient. Alternately, the surgeon may merely hook suspending element 706 over spanning element 704, rather than using holes 716. Although not shown in the figures, it is possible also to provide spaced-apart, annular grooves along the length of spanning element 704. The surgeon may hook suspending element 706 into the grooves so that suspending element 706 may not slide along the length of spanning element 704, but is permitted to rotate about the axis of spanning element 704.

Each of supporting element 706, spanning element 704, tube 710, and cap 718 may be formed from any one of a number of rigid, biocompatible materials, including a metal such as stainless steel. Supporting element 706 may also be formed from a semi-rigid material, such as a malleable metal coated with an elastomer or hydrophilic material, so that the surgeon can reshape supporting element 706 during the surgical procedure. Supporting element 706 may also be formed from a memory metal (Nitinol) so that it may be folded to facilitate placement into (perhaps through a trocar cannula) or removal out of the body cavity.

FIG. 7-7 through FIG. 7-10 show views of a second aspect of a tissue suspension device 732, including a spanning element 740, a pair of supporting elements 736, and at least one, hook-like suspending element 738. Spanning element 740 is a straight bar having a plurality of holes 740 spaced apart along its length. Each hole is sized and oriented to receive an end 737 of supporting element 736. Suspending element 738 includes a tray 739 onto which the surgeon may hang a tissue/organ. FIG. 7-9 is an enlarged view of supporting element 736, which includes a cord 741 attached to spanning element 734, and a plurality of spaced-apart, bead-like markers 742 attached to cord 741. Supporting element 736 further includes a retaining element 744 having a slot 746 for receiving cord 741 (see FIG. 7-10). Once the surgeon has placed spanning element 734 into the body cavity via the laparoscopic disc or a small incision in the body wall, the surgeon may externalized each cord 741 through an appropriately placed incision in the body wall, and lift up on cord 741 to raise spanning element 734. Alternately, a needle (not shown) may be attached to the free end of each of cords 741, so that the surgeon may penetrate the needle through the body wall from inside the body cavity. The surgeon may use markers 742 to estimate the position of spanning element 734 in the body cavity, and then position retaining element 744 onto cord 741 to hold spanning element 734 at the desired vertical height inside of the body cavity. Spanning element 734 is thereby suspended from the body wall like a trapeze so that the suspended tissue/organ has additional mobility. To remove suspension system 732, the surgeon uses the reverse of the preceding procedure.

Spanning element 734 and suspending element 738 may be formed from any one of a number of rigid, biocompatible materials, including stainless steel. Supporting element 736 and retaining element 744 may be formed, for example, from a polymer. Spanning element 734 may be coated with an anti-bacterial agent and/or a lubricious coating to facilitate insertion through the body wall. At least a portion of supporting element 738 may be coated or covered with a soft material, such as a medical grade hydrophilic material, a foam rubber, or a cotton gauze, to provide an atraumatic support for the tissue/organ. Tray 738 may be formed from a malleable material, such as an annealed stainless steel, so that the surgeon may reshape it while it is inside of the body cavity. Tray

738 may be curved to help retain the slippery tissue within it, and the depth of the curvature may be approximately in the range of, but not limited to, 2-6 centimeters.

FIG. 7-11 shows a partial view of a third aspect of a tissue suspension device 748, including a hollow, spanning element 750 formed from a rigid material such as stainless steel tubing. Spanning element 750 includes a plurality of spaced-apart holes 752 for the removable attachment of suspending element 738 shown in FIG. 7-8. The surgeon places spanning element 750 into the patient using a guide wire 754. The surgeon creates a first incision in the body wall on one side of the patient and inserts an end of guide wire 754. The surgeon then pulls guide wire 754 across the body cavity, using his/her hand inserted into the body cavity via the laparoscopic disc. The surgeon then passes the end of guide wire 754 out a second incision in the body wall on the opposite side of the patient. The surgeon next threads the external portion of guide wire 754 through spanning element 750, and pushes spanning element 750 into the first incision along guide wire 754, across the body cavity, and out the second incision. The surgeon may then remove guide wire 754 from spanning element 750, and secure the externalized ends of spanning element 750 to the skin of the patient using a medical adhesive tape, for example.

FIG. 7-12 shows a fourth aspect of a tissue suspension device 758, including an articulating spanning element 759 made from a titanium alloy or a stainless steel bar or tube, for example, and having a plurality of holes 760 for the removable attachment of suspending element 738 shown in FIG. 7-8. The surgeon may use supporting element 708 shown in FIG. 7-6A to removably attach spanning element 759 to the body wall. At least one end of spanning element 759 has an articulating element 762 that may swing about a pivot 764. The surgeon may adjust articulating element 762 to a shortened configuration while introducing spanning element 759 into the body cavity via the laparoscopic disc. The surgeon may then use a scalpel to create two incisions in the body wall to externalize the ends of articulating element 762 at the locations best suited for supporting spanning element 759.

FIG. 7-13 shows a fifth aspect of a tissue suspension device 768, including a flexible spanning element 770 and a pair of adjustable tension, supporting elements 771. Each of supporting elements 771 include a threaded rod 772 attached with a connector to flexible spanning element 770, and a tensioning knob 774. While knobs 774 are detached from threaded rods 772, the surgeon may position spanning element 770 into the patient using any of the methods described for the previous aspects, so that each of threaded rods 772 extends through the body wall. The surgeon may then screw one tensioning knob 774 on each of threaded rods 772, and tension spanning element 770 by rotating one or both of the tensioning knobs in the appropriate direction. The surgeon may then hook at least one suspending element such as shown in FIG. 7-4 onto spanning element 770. Spanning element 770 may be formed from, but is not limited to, any one or a combination of the following materials: a plastic cord or bar, a braided metal wire, a natural or a synthetic fiber rope, an extruded rubber or plastic tube, a malleable metal bar, a wire-reinforced elastomer, a hydrophilic material, and a "gooseneck" conduit such as used for certain desk lamps.

While the present invention has been illustrated by description of several embodiments, it is not the intention of the applicant to restrict or limit the spirit and scope of the appended claims to such detail. Numerous variations, changes, and substitutions will occur to those skilled in the art without departing from the scope of the invention. Moreover, the structure of each element associated with the present

invention can be alternatively described as a means for providing the function performed by the element. Accordingly, it is intended that the invention be limited only by the spirit and scope of the appended claims.

What is claimed is:

5

1. A surgical port assembly comprising: a rigid mounting ring disposable on and releasably attachable a patient's skin surface; a body member attachable to said ring to depend downwardly therefrom through an incision in the patient's skin surface to facilitate deployment of instruments in the patient via the incision, said body member having an outer side facing away from the patient and an inner side facing inwardly of or towards the patient's skin surface during a surgical procedure, said body member being rotatably attachable to said ring for turning about an axis oriented perpendicularly to a plane defined by said ring; and a cannula unit attachable to said body member and carrying a plurality of cannulas.

10

15

* * * * *

专利名称(译)	访问设备		
公开(公告)号	US8517995	公开(公告)日	2013-08-27
申请号	US12/579625	申请日	2009-10-15
[标]申请(专利权)人(译)	VOEGELE JAMESW GILL ROBERT P VOEGELE AARONÇ WEISENBURGH II WILLIAM - [R HESS CHRISTOPHERJ GEIS威廉·佩特斯·		
申请(专利权)人(译)	VOEGELE JAMESW GILL ROBERT P VOEGELE AARONÇ WEISENBURGH II WILLIAM - [R HESS CHRISTOPHERJ GEIS威廉·佩特斯·		
当前申请(专利权)人(译)	爱惜康内镜手术 , INC.		
[标]发明人	VOEGELE JAMES W GILL ROBERT P VOEGELE AARON C WEISENBURGH II WILLIAM B HESS CHRISTOPHER J GEIS WILLIAM P		
发明人	VOEGELE, JAMES W. GILL, ROBERT P. VOEGELE, AARON C. WEISENBURGH, II, WILLIAM B. HESS, CHRISTOPHER J. GEIS, WILLIAM P.		
IPC分类号	A61M5/32 A61B46/23		
CPC分类号	A61B1/32 A61B17/0281 A61B17/115 A61B17/122 A61B17/1285 A61B17/29 A61B17/3417 A61B17/3423 A61B17/3462 A61B17/4241 A61B19/54 A61F2/0063 A61B17/0218 A61F2002/0072 A61B17/064 A61B17/0644 A61B17/1227 A61B17/3474 A61B17/3476 A61B19/26 A61B19/5202 A61B2017/00265 A61B2017/00287 A61B2017/00362 A61B2017/00473 A61B2017/00893 A61B2017/0419 A61B2017/0461 A61B2017/0462 A61B2017/0464 A61B2017/0647 A61B2017/2825 A61B2017/2829 A61B2017/2931 A61B2017/306 A61B2017/3405 A61B2017/3437 A61B2017/3445 A61B2017/3447 A61B2017/3449 A61B2017/3466 A61B2019/5408 A61B2019/5425 A61B2019/5437 A61B2019/5454 A61B2019/5487 A61B90/30 A61B90/39 A61B90/50 A61B2090/3908 A61B2090/3925 A61B2090/3937 A61B2090/3954 A61B2090/3987		
审查员(译)	门德斯MANUEL		
优先权	60/700176 2005-07-18 US 60/669514 2005-04-08 US		
其他公开文献	US20100030032A1		
外部链接	Espacenet USPTO		

摘要(译)

一种外科进入装置，包括具有两个或更多个端口或孔的基部，所述端口或孔用于插入手术器械。多端口插入件可以与腹腔镜进入装置一起使用。多端口插入件还可包括一个或多个器械支撑件，所述器械支撑件附接到基部以固定通过多端口插入件插入的一个或多个手术器械的位置。

