



US008603161B2

(12) **United States Patent**  
**Drews et al.**

(10) **Patent No.:** **US 8,603,161 B2**  
(45) **Date of Patent:** **\*Dec. 10, 2013**

(54) **ATTACHMENT DEVICE AND METHODS OF USING THE SAME**

(75) Inventors: **Michael J. Drews**, Palo Alto, CA (US);  
**Donnell W. Gurskis**, Belmont, CA (US);  
**Steven R. Bacich**, Half Moon Bay, CA (US)

(73) Assignee: **Medtronic, Inc.**, Fridley, MN (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1189 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/498,195**

(22) Filed: **Jul. 6, 2009**

(65) **Prior Publication Data**

US 2010/0010616 A1 Jan. 14, 2010

**Related U.S. Application Data**

(63) Continuation of application No. 10/681,700, filed on Oct. 8, 2003, now Pat. No. 7,556,647.

(51) **Int. Cl.**  
**A61B 17/10** (2006.01)

(52) **U.S. Cl.**  
USPC ..... **623/2.11**; 606/142; 606/215; 606/216

(58) **Field of Classification Search**  
USPC ..... 606/139, 142, 148, 151, 215, 216, 219;  
623/904, 2.11

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

3,143,742 A 8/1964 Cromie  
3,320,974 A 5/1967 High et al.  
3,370,305 A 2/1968 Goott et al.  
3,371,352 A 3/1968 Siposs

3,409,013 A 11/1968 Berry  
3,464,065 A 9/1969 Cromie  
3,546,710 A 12/1970 Ivanovich et al.

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 2356656 1/2000  
DE 19532973 11/1996

(Continued)

**OTHER PUBLICATIONS**

Lutter, et al., Percutaneous Valve Replacement: Current State and Future Prospects; Ann. Thorac. Surg. 2004;78:2199-2206.

(Continued)



*Primary Examiner* — Melanie Tyson

*Assistant Examiner* — Todd J Scherbel

(57) **ABSTRACT**

Devices for attaching a first mass and a second mass and methods of making and using the same are disclosed. The devices can be made from an resilient, elastic or deformable materials. The devices can be used to attach a heart valve ring to a biological annulus. The devices can also be used for wound closure or a variety of other procedures such as anchoring a prosthesis to surrounding tissue or another prosthesis, tissue repair, such as in the closure of congenital defects such as septal heart defects, tissue or vessel anastomosis, fixation of tissue with or without a reinforcing mesh for hernia repair, orthopedic anchoring such as in bone fusing or tendon or muscle repair, ophthalmic indications, laparoscopic or endoscopic tissue repair or placement of prostheses, or use by robotic devices for procedures such as those above performed remotely.

**13 Claims, 13 Drawing Sheets**



(56)

## References Cited

## U.S. PATENT DOCUMENTS

3,571,815 A	3/1971	Somyk	5,071,431 A	12/1991	Sauter et al.
3,574,865 A	4/1971	Hamaker	5,104,406 A	4/1992	Curcio et al.
3,628,535 A	12/1971	Ostrowsky et al.	5,147,391 A	9/1992	Lane
3,686,740 A	8/1972	Shiley	5,163,953 A	11/1992	Vince
3,691,567 A	9/1972	Cromie	5,163,954 A	11/1992	Curcio et al.
3,710,744 A	1/1973	Goodenough et al.	5,163,955 A	11/1992	Love et al.
3,744,060 A	7/1973	Bellhouse et al.	5,178,633 A	1/1993	Peters
3,755,823 A	9/1973	Hancock	5,192,303 A	3/1993	Gattorna
3,800,403 A	4/1974	Anderson	5,258,023 A	11/1993	Reger
3,839,741 A	10/1974	Haller	5,316,016 A	5/1994	Adams et al.
3,959,827 A	6/1976	Kaster	5,326,370 A	7/1994	Love et al.
3,974,854 A	8/1976	Kurpanek	5,326,371 A	7/1994	Love et al.
3,996,623 A	12/1976	Kaster	5,332,402 A	7/1994	Teitelbaum
3,997,923 A	12/1976	Possis	5,370,685 A	12/1994	Stevens
4,035,849 A	7/1977	Angell et al.	5,376,112 A	12/1994	Duran
4,078,268 A	3/1978	Possis	5,396,887 A	3/1995	Imran
4,078,468 A	3/1978	Civitello	5,397,346 A	3/1995	Walker et al.
4,084,268 A	4/1978	Ionexcu et al.	5,397,348 A	3/1995	Campbell et al.
4,106,129 A	8/1978	Carpentier et al.	5,397,351 A	3/1995	Pavcnik et al.
4,164,046 A	8/1979	Cooley	5,406,857 A	4/1995	Eberhardt et al.
4,172,295 A	10/1979	Batten	5,423,887 A	6/1995	Love et al.
4,211,325 A	7/1980	Wright	5,425,741 A	6/1995	Lemp et al.
4,217,665 A	8/1980	Bex et al.	5,431,676 A	7/1995	Dubrui et al.
4,218,782 A	8/1980	Rygg	5,449,384 A	9/1995	Johnson
4,245,358 A	1/1981	Moasser	5,449,385 A	9/1995	Religa et al.
4,259,753 A	4/1981	Liotta et al.	5,469,868 A	11/1995	Reger
4,291,420 A	9/1981	Reul	5,476,510 A	12/1995	Eberhardt et al.
4,297,749 A	11/1981	Davis et al.	5,488,789 A	2/1996	Religa et al.
RE30,912 E	4/1982	Hancock	5,489,297 A	2/1996	Duran
4,343,048 A	8/1982	Ross et al.	5,489,298 A	2/1996	Love et al.
4,364,126 A	12/1982	Rosen et al.	5,500,016 A	3/1996	Fisher
4,388,735 A	6/1983	Ionescu et al.	5,531,784 A	7/1996	Love et al.
4,441,216 A	4/1984	Ionescu et al.	5,533,515 A	7/1996	Coller et al.
4,451,936 A	6/1984	Carpentier et al.	5,549,665 A	8/1996	Vesely et al.
4,470,157 A	9/1984	Love	5,549,666 A	8/1996	Hata et al.
4,477,930 A	10/1984	Totten et al.	5,562,729 A	10/1996	Purdy et al.
4,485,816 A	12/1984	Krumme	5,571,175 A	11/1996	Vanney
4,501,030 A	2/1985	Lane	5,571,215 A	11/1996	Sterman et al.
4,506,394 A	3/1985	Bedard	5,573,007 A	11/1996	Bobo, Sr.
4,535,483 A	8/1985	Klawitter et al.	5,573,543 A	11/1996	Akopov et al.
4,548,202 A	10/1985	Duncan	5,578,076 A	11/1996	Krueger et al.
4,605,407 A	8/1986	Black et al.	5,584,803 A	12/1996	Stevens et al.
4,626,255 A	12/1986	Reichart et al.	5,607,470 A	3/1997	Milo
4,629,459 A	12/1986	Ionescu et al.	5,613,982 A	3/1997	Goldstein
4,665,906 A	5/1987	Jervis	5,618,307 A	4/1997	Donlon et al.
4,666,442 A	5/1987	Arru et al.	5,626,607 A	5/1997	Malecki et al.
4,680,031 A	7/1987	Alonso	5,628,789 A	5/1997	Vanney et al.
4,683,883 A	8/1987	Martin	5,662,704 A	9/1997	Gross
4,687,483 A	8/1987	Fisher et al.	5,669,917 A	9/1997	Sauer
4,692,164 A	9/1987	Dzemeshekevich et al.	5,693,090 A	12/1997	Unsworth et al.
4,702,250 A	10/1987	Ovil et al.	5,695,503 A	12/1997	Krueger et al.
4,705,516 A	11/1987	Barone et al.	5,713,952 A	2/1998	Vanney et al.
4,725,274 A	2/1988	Lane et al.	5,713,953 A	2/1998	Vallana et al.
4,731,074 A	3/1988	Rousseau et al.	5,716,370 A	2/1998	Williamson, IV et al.
4,743,253 A	5/1988	Magladry	5,716,399 A	2/1998	Love
4,758,151 A	7/1988	Arru et al.	5,720,755 A	2/1998	Dakov
4,775,378 A	10/1988	Knoch et al.	5,725,554 A	3/1998	Simon
4,778,461 A	10/1988	Pietsch et al.	5,728,064 A	3/1998	Burns et al.
4,790,843 A	12/1988	Carpentier et al.	5,728,151 A	3/1998	Garrison et al.
4,816,029 A	3/1989	Penny, III et al.	5,735,894 A	4/1998	Krueger et al.
4,851,000 A	7/1989	Gupta	5,752,522 A	5/1998	Murphy
4,865,600 A	9/1989	Carpentier et al.	5,755,782 A	5/1998	Love et al.
4,888,009 A	12/1989	Lederman et al.	5,766,240 A	6/1998	Johnson
4,892,541 A	1/1990	Alonso	5,776,187 A	7/1998	Krueger et al.
4,917,097 A	4/1990	Proudian et al.	5,776,188 A	7/1998	Shepherd et al.
4,917,698 A	4/1990	Carpentier et al.	5,800,527 A	9/1998	Jansen et al.
4,935,030 A	6/1990	Alonso	5,807,405 A	9/1998	Vanney et al.
4,960,424 A	10/1990	Grooters	5,814,097 A	9/1998	Sterman et al.
4,993,428 A	2/1991	Arms	5,814,098 A	9/1998	Hinnenkamp et al.
4,994,077 A	2/1991	Dobben	5,814,100 A	9/1998	Carpentier et al.
5,002,567 A	3/1991	Bona et al.	5,824,060 A	10/1998	Christie et al.
5,010,892 A	4/1991	Colvin et al.	5,824,061 A	10/1998	Quijano et al.
5,032,128 A	7/1991	Alonso	5,824,064 A	10/1998	Taheri
5,035,709 A	7/1991	Wieting et al.	5,830,239 A	11/1998	Toomes
5,037,434 A	8/1991	Lane	5,840,081 A	11/1998	Andersen et al.
			5,843,179 A	12/1998	Vanney et al.
			5,848,969 A	12/1998	Panescu et al.
			5,855,563 A	1/1999	Kaplan et al.
			5,855,601 A	1/1999	Bessler et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

5,855,603	A	1/1999	Reif	6,283,995	B1	9/2001	Moe et al.
5,860,992	A	1/1999	Daniel	6,287,339	B1	9/2001	Vazquez et al.
5,861,028	A	1/1999	Angell	6,290,674	B1	9/2001	Roue et al.
5,865,801	A	2/1999	Houser	6,299,638	B1	10/2001	Sauter
5,876,436	A	3/1999	Vanney et al.	6,309,417	B1	10/2001	Spence
5,879,371	A	3/1999	Gardiner et al.	6,312,447	B1	11/2001	Grimes
5,891,160	A	4/1999	Williamson, IV et al.	6,312,465	B1	11/2001	Griffin et al.
5,891,195	A	4/1999	Klostermeyer et al.	6,319,280	B1	11/2001	Schoon
5,895,420	A	4/1999	Mirsch, II et al.	6,319,281	B1	11/2001	Patel
5,902,308	A	5/1999	Murphy	6,322,588	B1	11/2001	Ogle et al.
5,908,450	A	6/1999	Gross et al.	6,328,727	B1	12/2001	Frazier et al.
5,908,452	A	6/1999	Bokros et al.	6,328,763	B1	12/2001	Love et al.
5,910,170	A	6/1999	Reimink et al.	6,338,740	B1	1/2002	Carpentier
5,919,147	A	7/1999	Jain	6,350,281	B1	2/2002	Rhee
5,921,934	A	7/1999	Teo	6,358,278	B1	3/2002	Brendzel et al.
5,921,935	A	7/1999	Hickey	6,358,556	B1	3/2002	Ding et al.
5,924,984	A	7/1999	Rao	6,371,983	B1	4/2002	Lane
5,931,969	A	8/1999	Carpentier et al.	6,391,053	B1	5/2002	Brendzel et al.
5,935,163	A	8/1999	Gabbay	6,395,025	B1	5/2002	Fordenbacher et al.
5,957,949	A	9/1999	Leonhardt et al.	6,402,780	B2	6/2002	Williamson, IV et al.
5,961,549	A	10/1999	Nguyen et al.	6,409,759	B1	6/2002	Peredo
5,961,550	A	10/1999	Carpentier et al.	6,413,275	B1	7/2002	Nguyen et al.
5,972,004	A	10/1999	Williamson, IV et al.	6,419,696	B1	7/2002	Ortiz et al.
5,972,024	A	10/1999	Northrup, III et al.	6,425,902	B1	7/2002	Love
5,976,183	A	11/1999	Ritz	6,425,916	B1	7/2002	Garrison et al.
5,984,949	A	11/1999	Levin	6,440,164	B1	8/2002	DiMatteo et al.
5,984,959	A	11/1999	Robertson et al.	6,447,524	B1	9/2002	Knodel
5,984,973	A	11/1999	Girard et al.	6,454,799	B1	9/2002	Schreck
6,007,577	A	12/1999	Vanney et al.	6,458,153	B1	10/2002	Bailey et al.
6,010,531	A	1/2000	Donlon et al.	6,461,382	B1	10/2002	Cao
6,042,607	A	3/2000	Williamson, IV et al.	6,468,305	B1	10/2002	Otte
6,045,576	A	4/2000	Starr et al.	6,503,272	B2	1/2003	Duerig et al.
6,059,827	A	5/2000	Fenton, Jr.	6,514,265	B2	2/2003	Ho et al.
6,066,160	A	5/2000	Colvin et al.	6,530,952	B2	3/2003	Vesely
6,068,657	A	5/2000	Lapeyre et al.	6,547,827	B2	4/2003	Carpentier et al.
6,074,041	A	6/2000	Imanaka et al.	6,551,332	B1	4/2003	Nguyen et al.
6,074,417	A	6/2000	Peredo	6,558,418	B2	5/2003	Carpentier et al.
6,074,418	A	6/2000	Buchanan et al.	6,569,196	B1	5/2003	Vesely
6,081,737	A	6/2000	Shah	6,582,462	B1	6/2003	Andersen et al.
6,083,179	A	7/2000	Oredsson	6,585,766	B1	7/2003	Huynh et al.
6,096,074	A	8/2000	Pedros	6,589,279	B1	7/2003	Anderson et al.
6,099,475	A	8/2000	Seward et al.	6,598,307	B2	7/2003	Love et al.
6,102,944	A	8/2000	Huynh	6,602,289	B1	8/2003	Colvin et al.
6,106,550	A	8/2000	Magovern et al.	6,607,541	B1	8/2003	Gardiner et al.
6,110,200	A	8/2000	Hinnenkamp	6,613,059	B2	9/2003	Ho et al.
6,113,632	A	9/2000	Reif	6,613,085	B1	9/2003	Anderson et al.
6,117,091	A	9/2000	Young et al.	6,641,593	B1	11/2003	Schaller et al.
6,126,007	A	10/2000	Kari et al.	6,652,578	B2	11/2003	Bailey et al.
6,129,758	A	10/2000	Love	6,676,671	B2	1/2004	Robertson et al.
6,139,575	A	10/2000	Shu et al.	6,678,962	B1	1/2004	Love et al.
6,143,024	A	11/2000	Campbell et al.	6,682,559	B2	1/2004	Myers et al.
6,143,025	A	11/2000	Stobie et al.	6,685,739	B2	2/2004	DiMatteo et al.
6,149,658	A	11/2000	Gardiner et al.	6,692,513	B2	2/2004	Streeter et al.
6,162,233	A	12/2000	Williamson, IV et al.	6,695,859	B1	2/2004	Golden et al.
6,165,183	A	12/2000	Kuehn et al.	6,709,457	B1	3/2004	Otte et al.
6,168,614	B1	1/2001	Anderson et al.	6,716,243	B1	4/2004	Colvin et al.
6,176,877	B1	1/2001	Buchanan et al.	6,716,244	B2	4/2004	Klaco
6,183,512	B1	2/2001	Howanec, Jr. et al.	6,716,789	B1	4/2004	Heineke et al.
6,197,042	B1 *	3/2001	Ginn et al. .... 606/213	6,719,790	B2	4/2004	Brendzel et al.
6,197,054	B1	3/2001	Hamblin, Jr. et al.	6,730,118	B2	5/2004	Spenser et al.
6,200,306	B1	3/2001	Klostermeyer	6,733,525	B2	5/2004	Yang et al.
6,203,553	B1	3/2001	Robertson	6,764,508	B1	7/2004	Roehe et al.
6,214,043	B1	4/2001	Krueger et al.	6,767,362	B2	7/2004	Schreck
6,217,610	B1	4/2001	Carpentier et al.	6,769,434	B2	8/2004	Liddicoat et al.
6,217,611	B1	4/2001	Klostermeyer	6,776,785	B1	8/2004	Yencho
6,231,561	B1	5/2001	Frazier et al.	6,786,924	B2	9/2004	Ryan et al.
6,231,602	B1	5/2001	Carpentier et al.	6,786,925	B1	9/2004	Schoon et al.
6,241,765	B1	6/2001	Griffin et al.	6,790,229	B1	9/2004	Berrekouw
6,245,102	B1	6/2001	Jayaraman	6,790,230	B2	9/2004	Beyersdorf et al.
6,245,105	B1	6/2001	Nguyen et al.	6,805,711	B2	10/2004	Quijano et al.
6,254,636	B1	7/2001	Peredo	6,830,585	B1	12/2004	Artot et al.
6,264,691	B1	7/2001	Gabbay	6,833,924	B2	12/2004	Love et al.
6,270,526	B1	8/2001	Cox	6,837,902	B2	1/2005	Nguyen et al.
6,270,527	B1	8/2001	Campbell et al.	6,846,324	B2	1/2005	Stobie
6,283,127	B1	9/2001	Sterman et al.	6,846,325	B2	1/2005	Liddicoat
				6,872,226	B2	3/2005	Cali et al.
				6,893,459	B1	5/2005	Macoviak
				6,893,460	B2	5/2005	Spenser et al.
				6,896,690	B1	5/2005	Lambrecht et al.

(56)

## References Cited

## U.S. PATENT DOCUMENTS

6,908,481 B2	6/2005	Cribier	2002/0188348 A1	12/2002	DiMatteo et al.
6,911,043 B2	6/2005	Myers et al.	2002/0198594 A1	12/2002	Schreck
6,913,607 B2	7/2005	Ainsworth et al.	2003/0014104 A1	1/2003	Cribier
6,918,917 B1	7/2005	Nguyen et al.	2003/0023300 A1	1/2003	Bailey et al.
6,921,407 B2	7/2005	Nguyen et al.	2003/0023302 A1	1/2003	Moe et al.
6,926,730 B1	8/2005	Nguyen et al.	2003/0023303 A1	1/2003	Palmaz et al.
6,929,653 B2	8/2005	Streeter	2003/0036791 A1	2/2003	Philipp et al.
6,939,365 B1	9/2005	Fogarty	2003/0036795 A1	2/2003	Andersen et al.
6,945,980 B2	9/2005	Nguyen et al.	2003/0040792 A1	2/2003	Gabbay
6,945,997 B2	9/2005	Huynh et al.	2003/0045902 A1	3/2003	Weadeock
6,960,221 B2	11/2005	Ho et al.	2003/0055495 A1	3/2003	Pease et al.
6,974,476 B2	12/2005	McGuckin et al.	2003/0109922 A1	6/2003	Peterson
7,011,681 B2	3/2006	Vesely	2003/0109924 A1	6/2003	Cribier
7,025,780 B2	4/2006	Gabbay	2003/0114913 A1	6/2003	Spenser et al.
7,037,333 B2	5/2006	Myers et al.	2003/0125793 A1	7/2003	Vesely
7,070,616 B2	7/2006	Majercak et al.	2003/0130729 A1	7/2003	Paniagua et al.
7,083,648 B2	8/2006	Yu	2003/0149477 A1	8/2003	Gabbay
7,097,659 B2	8/2006	Woolfson et al.	2003/0149478 A1	8/2003	Figulla et al.
7,101,396 B2	9/2006	Artof et al.	2003/0153974 A1	8/2003	Spenser et al.
7,137,184 B2	11/2006	Schreck	2003/0167089 A1	9/2003	Lane
7,141,064 B2	11/2006	Scott et al.	2003/0191481 A1	10/2003	Nguyen et al.
7,147,663 B1	12/2006	Berg et al.	2003/0199963 A1	10/2003	Tower et al.
7,153,324 B2	12/2006	Case et al.	2003/0199971 A1	10/2003	Tower et al.
7,172,625 B2	2/2007	Shu et al.	2003/0229394 A1	12/2003	Ogle et al.
7,175,659 B2	2/2007	Hill et al.	2003/0236568 A1	12/2003	Hojeibane et al.
7,182,769 B2 *	2/2007	Ainsworth et al.	2004/0015232 A1	1/2004	Shu
7,186,265 B2	3/2007	Sharkawy et al.	2004/0019374 A1	1/2004	Hojeibane et al.
7,195,641 B2	3/2007	Palmaz et al.	2004/0024452 A1	2/2004	Kruse et al.
7,201,761 B2	4/2007	Woolfson et al.	2004/0030381 A1	2/2004	Shu
7,201,771 B2	4/2007	Lane	2004/0034411 A1	2/2004	Quijano et al.
7,201,772 B2	4/2007	Schwammenthal et al.	2004/0039436 A1	2/2004	Spenser et al.
7,214,344 B2	5/2007	Carpentier et al.	2004/0044406 A1	3/2004	Woolfson
7,238,200 B2	7/2007	Lee et al.	2004/0050393 A1	3/2004	Golden et al.
7,252,682 B2	8/2007	Seguin	2004/0068276 A1	4/2004	Golden et al.
7,261,732 B2	8/2007	Justino	2004/0078074 A1	4/2004	Anderson et al.
7,300,463 B2	11/2007	Liddicoat	2004/0093075 A1	5/2004	Kuehne
RE40,377 E	6/2008	Williamson, IV et al.	2004/0102797 A1	5/2004	Golden et al.
7,393,360 B2	7/2008	Spenser et al.	2004/0106976 A1	6/2004	Bailey et al.
7,422,603 B2	9/2008	Lane	2004/0106990 A1	6/2004	Spence et al.
7,445,632 B2	11/2008	McGuckin et al.	2004/0122514 A1	6/2004	Fogarty
7,513,909 B2	4/2009	Lane et al.	2004/0122516 A1	6/2004	Fogarty
7,547,313 B2	6/2009	Gardiner et al.	2004/0122526 A1	6/2004	Imran
7,556,647 B2	7/2009	Drews et al.	2004/0167573 A1	8/2004	Williamson, IV et al.
7,578,843 B2	8/2009	Shu	2004/0167620 A1	8/2004	Ortiz et al.
7,597,711 B2	10/2009	Drews et al.	2004/0176839 A1	9/2004	Huynh et al.
7,708,775 B2	5/2010	Rowe et al.	2004/0186563 A1	9/2004	Lobbi
7,722,643 B2	5/2010	Ho et al.	2004/0186565 A1	9/2004	Schreck
7,744,611 B2	6/2010	Nguyen et al.	2004/0193261 A1	9/2004	Berrekouw
7,763,040 B2	7/2010	Schaller et al.	2004/0199176 A1	10/2004	Berrekouw
7,771,469 B2	8/2010	Liddicoat et al.	2004/0206363 A1	10/2004	McCarthy et al.
7,803,184 B2	9/2010	McGuckin et al.	2004/0210304 A1	10/2004	Seguin et al.
2001/0007956 A1	7/2001	Letac et al.	2004/0210305 A1	10/2004	Shu
2001/0018592 A1	8/2001	Schaller et al.	2004/0210307 A1	10/2004	Khairkhanan
2001/0021872 A1	9/2001	Bailey et al.	2004/0225355 A1	11/2004	Stevens
2001/0039435 A1	11/2001	Roue et al.	2004/0225356 A1	11/2004	Frater
2001/0039436 A1	11/2001	Frazier et al.	2004/0236411 A1	11/2004	Sarac et al.
2001/0041914 A1	11/2001	Frazier et al.	2004/0260389 A1	12/2004	Case et al.
2001/0041915 A1	11/2001	Roue et al.	2004/0260390 A1	12/2004	Sarac et al.
2001/0049492 A1	12/2001	Frazier et al.	2005/0010285 A1	1/2005	Lambrech et al.
2002/0026238 A1	2/2002	Lane et al.	2005/0027348 A1	2/2005	Case et al.
2002/0032481 A1	3/2002	Gabbay	2005/0033398 A1	2/2005	Seguin
2002/0055774 A1	5/2002	Liddicoat	2005/0043760 A1	2/2005	Fogarty
2002/0058994 A1	5/2002	Hill et al.	2005/0043790 A1	2/2005	Seguin
2002/0058995 A1	5/2002	Stevens	2005/0060029 A1	3/2005	Le et al.
2002/0077555 A1	6/2002	Schwartz	2005/0065594 A1	3/2005	DiMatteo et al.
2002/0077698 A1	6/2002	Peredo	2005/0065601 A1	3/2005	Lee et al.
2002/0091441 A1	7/2002	Guzik	2005/0065614 A1	3/2005	Stinson
2002/0116054 A1	8/2002	Lundell et al.	2005/0070924 A1	3/2005	Schaller et al.
2002/0123802 A1	9/2002	Snyders	2005/0075584 A1	4/2005	Cali
2002/0128684 A1	9/2002	Foerster	2005/0075659 A1	4/2005	Realyvasquez et al.
2002/0138138 A1	9/2002	Yang	2005/0075667 A1	4/2005	Ho et al.
2002/0151970 A1	10/2002	Garrison et al.	2005/0075713 A1	4/2005	Biancucci et al.
2002/0173842 A1	11/2002	Buchanan	2005/0075717 A1	4/2005	Nguyen et al.
2002/0177223 A1	11/2002	Ogle et al.	2005/0075718 A1	4/2005	Nguyen et al.
2002/0183834 A1	12/2002	Klaco	2005/0075719 A1	4/2005	Bergheim
			2005/0075720 A1	4/2005	Nguyen et al.
			2005/0075724 A1	4/2005	Svanidze et al.
			2005/0075730 A1	4/2005	Myers et al.
			2005/0080454 A1	4/2005	Drews

(56)

## References Cited

## U.S. PATENT DOCUMENTS

2005/0096738 A1 5/2005 Cali et al.  
 2005/0098547 A1 5/2005 Cali et al.  
 2005/0101975 A1 5/2005 Nguyen et al.  
 2005/0107871 A1\* 5/2005 Realyvasquez et al. .... 623/2.11  
 2005/0131429 A1 6/2005 Ho et al.  
 2005/0137682 A1 6/2005 Justino  
 2005/0137686 A1 6/2005 Salahieh et al.  
 2005/0137687 A1 6/2005 Salahieh et al.  
 2005/0137688 A1 6/2005 Salahieh et al.  
 2005/0137689 A1 6/2005 Salahieh et al.  
 2005/0137690 A1 6/2005 Salahieh et al.  
 2005/0137691 A1 6/2005 Salahieh et al.  
 2005/0137692 A1 6/2005 Haug et al.  
 2005/0137694 A1 6/2005 Haug et al.  
 2005/0137695 A1 6/2005 Salahieh et al.  
 2005/0137696 A1 6/2005 Salahieh et al.  
 2005/0137702 A1 6/2005 Haug et al.  
 2005/0150775 A1 7/2005 Zhang et al.  
 2005/0159811 A1 7/2005 Lane  
 2005/0165477 A1 7/2005 Anduiza et al.  
 2005/0165479 A1 7/2005 Drews et al.  
 2005/0182483 A1 8/2005 Osborne et al.  
 2005/0182486 A1 8/2005 Gabbay  
 2005/0192665 A1 9/2005 Spenser et al.  
 2005/0203616 A1 9/2005 Cribier  
 2005/0203617 A1 9/2005 Forster et al.  
 2005/0203618 A1 9/2005 Sharkawy et al.  
 2005/0216079 A1 9/2005 MaCoviak  
 2005/0222674 A1 10/2005 Paine  
 2005/0234546 A1 10/2005 Nugent et al.  
 2005/0240259 A1 10/2005 Siskin et al.  
 2005/0240263 A1 10/2005 Fogarty  
 2005/0251252 A1 11/2005 Stobie  
 2005/0261765 A1 11/2005 Liddicoat  
 2005/0283231 A1 12/2005 Haug et al.  
 2006/0004389 A1 1/2006 Nguyen et al.  
 2006/0025857 A1 2/2006 Bergheim et al.  
 2006/0052867 A1 3/2006 Revuelta et al.  
 2006/0058871 A1 3/2006 Zakay et al.  
 2006/0058872 A1 3/2006 Salahieh et al.  
 2006/0074484 A1 4/2006 Huber  
 2006/0085060 A1 4/2006 Campbell  
 2006/0095125 A1 5/2006 Chinn et al.  
 2006/0122634 A1 6/2006 Ino  
 2006/0122692 A1 6/2006 Gilad et al.  
 2006/0135964 A1 6/2006 Vesely  
 2006/0136052 A1 6/2006 Vesely  
 2006/0136054 A1 6/2006 Berg et al.  
 2006/0149360 A1 7/2006 Schwammenthal et al.  
 2006/0149367 A1 7/2006 Sieracki  
 2006/0154230 A1 7/2006 Cunanan  
 2006/0161249 A1 7/2006 Realyvasquez et al.  
 2006/0167543 A1 7/2006 Bailey et al.  
 2006/0195183 A1 8/2006 Navia et al.  
 2006/0195184 A1 8/2006 Lane  
 2006/0195185 A1 8/2006 Lane  
 2006/0195186 A1 8/2006 Drews  
 2006/0207031 A1 9/2006 Cunanan et al.  
 2006/0229708 A1 10/2006 Powell et al.  
 2006/0235508 A1 10/2006 Lane  
 2006/0241745 A1 10/2006 Solem  
 2006/0246888 A1 11/2006 Bender et al.  
 2006/0253191 A1 11/2006 Salahieh et al.  
 2006/0259134 A1 11/2006 Schwammenthal et al.  
 2006/0259135 A1 11/2006 Navia et al.  
 2006/0259136 A1 11/2006 Nguyen et al.  
 2006/0265056 A1 11/2006 Nguyen et al.  
 2006/0271172 A1 11/2006 Tehrani  
 2006/0271175 A1 11/2006 Woolfson et al.  
 2006/0276888 A1 12/2006 Lee  
 2006/0287717 A1 12/2006 Rowe et al.  
 2006/0287719 A1 12/2006 Rowe et al.  
 2007/0005129 A1 1/2007 Damm et al.  
 2007/0010835 A1 1/2007 Breton et al.  
 2007/0010876 A1 1/2007 Salahieh et al.

2007/0010877 A1 1/2007 Salahieh et al.  
 2007/0016285 A1 1/2007 Lane  
 2007/0016286 A1 1/2007 Herrmann et al.  
 2007/0016288 A1 1/2007 Gurskis  
 2007/0027461 A1 2/2007 Gardiner et al.  
 2007/0043435 A1 2/2007 Seguin et al.  
 2007/0078509 A1 4/2007 Lotfy  
 2007/0078510 A1 4/2007 Ryan  
 2007/0095698 A1 5/2007 Cambron  
 2007/0100440 A1 5/2007 Figulla et al.  
 2007/0106313 A1 5/2007 Golden et al.  
 2007/0129794 A1 6/2007 Realyvasquez  
 2007/0142848 A1 6/2007 Ainsworth et al.  
 2007/0142906 A1 6/2007 Figulla et al.  
 2007/0142907 A1 6/2007 Moaddeb et al.  
 2007/0150053 A1 6/2007 Gurskis  
 2007/0156233 A1 7/2007 Kapadia et al.  
 2007/0162103 A1 7/2007 Case et al.  
 2007/0162107 A1 7/2007 Haug et al.  
 2007/0162111 A1 7/2007 Fukamachi et al.  
 2007/0162113 A1 7/2007 Sharkawy et al.  
 2007/0179604 A1 8/2007 Lane  
 2007/0185565 A1 8/2007 Schwammenthal et al.  
 2007/0198097 A1 8/2007 Zegdi  
 2007/0203575 A1 8/2007 Forster et al.  
 2007/0203576 A1 8/2007 Lee et al.  
 2007/0213813 A1 9/2007 Von Segesser et al.  
 2007/0225801 A1 9/2007 Drews et al.  
 2007/0233237 A1 10/2007 Krivoruchko  
 2007/0239266 A1 10/2007 Birdsall  
 2007/0239269 A1 10/2007 Dolan et al.  
 2007/0239273 A1 10/2007 Allen  
 2007/0255398 A1 11/2007 Yang et al.  
 2007/0260305 A1 11/2007 Drews et al.  
 2007/0265701 A1 11/2007 Gurskis et al.  
 2007/0270944 A1 11/2007 Bergheim et al.  
 2007/0288089 A1 12/2007 Gurskis et al.  
 2008/0004696 A1 1/2008 Vesely  
 2008/0033543 A1 2/2008 Gurskis et al.  
 2008/0071361 A1 3/2008 Tuval et al.  
 2008/0071369 A1 3/2008 Tuval et al.  
 2008/0097595 A1 4/2008 Gabbay  
 2008/0119875 A1 5/2008 Ino et al.  
 2008/0281411 A1 11/2008 Berreklouw  
 2008/0319543 A1 12/2008 Lane  
 2009/0036903 A1 2/2009 Ino et al.  
 2009/0112233 A1 4/2009 Xiao  
 2009/0192599 A1 7/2009 Lane et al.  
 2009/0192602 A1 7/2009 Kuehn  
 2009/0192603 A1 7/2009 Ryan  
 2009/0192604 A1 7/2009 Gloss  
 2009/0192605 A1 7/2009 Gloss et al.  
 2009/0192606 A1 7/2009 Gloss et al.  
 2009/0210052 A1 8/2009 Forster et al.  
 2009/0264903 A1 10/2009 Lee et al.  
 2009/0319038 A1 12/2009 Gurskis et al.  
 2010/0030244 A1 2/2010 Woolfson et al.  
 2010/0044410 A1 2/2010 Argentine et al.  
 2010/0100174 A1 4/2010 Gurskis  
 2010/0249894 A1 9/2010 Oba et al.

## FOREIGN PATENT DOCUMENTS

EP 0 084 395 8/1986  
 EP 0 096 721 12/1987  
 EP 0 125 393 12/1987  
 EP 0 179 562 7/1989  
 EP 0 826 340 3/1998  
 EP 1057460 12/2000  
 EP 1 088 529 4/2001  
 EP 1171059 1/2002  
 EP 971 650 1/2005  
 EP 171 059 2/2005  
 GB 1093599 12/1967  
 GB 1477643 6/1977  
 GB 2011259 7/1979  
 GB 2 056 023 3/1981  
 GB 2 069 843 9/1981  
 GB 2254254 10/1992

(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS


GB	2 279 134	12/1994
SU	1116573	7/1985
WO	87/05489	9/1987
WO	89/00084	2/1989
WO	91/15167	10/1991
WO	92/01269	8/1992
WO	92/13502	8/1992
WO	92/19184	11/1992
WO	92/19185	11/1992
WO	95/17139	6/1995
WO	95/28899	11/1995
WO	96/40006	12/1996
WO	97/09933	3/1997
WO	97/09944	3/1997
WO	97/27799	8/1997
WO	97/28745	8/1997
WO	97/39688	10/1997
WO	97/41801	11/1997
WO	97/42871	11/1997
WO	98/06329	2/1998
WO	99/11201	3/1999
WO	99/15112	4/1999
WO	99/51169	10/1999
WO	00/32105	6/2000
WO	00/40176	7/2000
WO	00/44311	8/2000

WO	00/56250	9/2000
WO	00/59382	10/2000
WO	00/60995	10/2000
WO	00/64380	11/2000
WO	01/10310	2/2001
WO	01/10312	2/2001
WO	01/49217	7/2001
WO	01/58363	8/2001
WO	01/76510	10/2001
WO	01/82840	11/2001
WO	01/87190	11/2001
WO	03/053289	7/2003
WO	03/063740	8/2003
WO	2004/006810	1/2004
WO	2004/089246	10/2004
WO	2005/004753	1/2005
WO	2005/020842	3/2005
WO	2005/039452	5/2005
WO	2005/072655	8/2005
WO	2006/086135	8/2006
WO	2009/137517	11/2009


## OTHER PUBLICATIONS

Jansen, et al., "Detachable Shape-Memory Sewing Ring for Heart Valves," *Artif. Organs.*—vol. 16, No. 3, 1992, pp. 294-297, Helmholtz Institute for Biomedical Engineering, Technical University of Aachen, Aachen, Germany.


\* cited by examiner



**Fig. 1**



**Fig. 2**



**Fig. 3**




Fig. 4




Fig. 5



Fig. 6



Fig. 7




Fig. 8




Fig. 9








Fig. 10








Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30




Fig. 31




Fig. 32




Fig. 33




Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 38






Fig. 39






**Fig. 40**



**Fig. 41**



**Fig. 42**




Fig. 43




Fig. 44




Fig. 45




Fig. 46




Fig. 47

## ATTACHMENT DEVICE AND METHODS OF USING THE SAME

This application is a continuation of application Ser. No. 10/681,700, filed Oct. 8, 2003, now U.S. Pat. No. 7,556,647.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates generally to a device for attaching a first mass to a second mass and methods of making and using the same.

#### 2. Description of the Related Art

Prosthetic heart valves can replace defective human valves in patients. Prosthetic valves commonly include sewing rings, suture cuffs or rings that are attached to and extend around the outer circumference of the prosthetic valve orifice.

In a typical prosthetic valve implantation procedure, the aorta is incised and the defective valve is removed leaving the desired placement site that may include a fibrous tissue layer or annular tissue. Known heart valve replacement techniques include individually passing sutures through the fibrous tissue or desired placement site within the valve annulus to form an array of sutures. Free ends of the sutures are extended out of the thoracic cavity and laid, spaced apart, on the patient's body. The free ends of the sutures are then individually threaded through a flange of the sewing ring. Once all sutures have been run through the sewing ring (typically 12 to 18 sutures), all the sutures are pulled up taught and the prosthetic valve is slid or "parachuted" down into place adjacent the placement site tissue. The prosthetic valve is then secured in place by traditional knot tying with the sutures. This procedure is time consuming as doctors often use three to ten knots per suture.

The sewing ring is often made of a biocompatible fabric through which a needle and suture can pass. The prosthetic valves are typically attached to the sewing rings which are sutured to a biological mass that is left when the surgeon removes the existing valve from the patient's heart. The sutures are tied snugly, thereby securing the sewing ring to the biological mass and, in turn, the prosthetic valve to the heart.

During heart valve replacement procedures, the patient is on heart-lung bypass which reduces the patient's oxygen level and creates non-physiological blood flow dynamics. The longer a patient is on heart-lung bypass, the greater the risk for permanent health damage. Existing suturing techniques extend the duration of bypass and increase the health risks due to heart-lung bypass. Furthermore, the fixturing force created by suturing varies significantly from suture to suture, even for the same medical professional.

In addition, sutures and other attachment devices are used in a variety of medical applications where the use of the device of the present invention would provide an advantage in fixing a first mass to a second mass, where the first mass is a tissue or a device or prosthesis, and the second mass is a tissue or a device or prosthesis. These applications include anchoring a prosthesis such as a synthetic or autologous graft to surrounding tissue or another prosthesis, tissue repair such as in the closure of congenital defects such as septal heart defects, tissue or vessel anastomosis, fixation of tissue with or without a reinforcing mesh for hernia repair, orthopedic anchoring such as in bone fusing or tendon or muscle repair, ophthalmic indications, laparoscopic or endoscopic tissue repair or placement of prostheses, or use by robotic devices for procedures performed remotely.

For these indications and others, there is a need for a fixturing device to minimize the time spent fixturing certain

devices or conduits, such as a valve prosthesis and a second mass, a vessel to another vessel or anatomical structure, tissue to tissue, surrounding tissue to a second prosthesis, and the like as described above. Furthermore, there is a need for a device that compliments existing suturing or attachment devices and methods and reduces fixturing times. Also, there is a need for a fixturing device that can be easily removed. There also exist a need to provide a fixturing device that can provide a consistent fixturing force.

### BRIEF SUMMARY OF THE INVENTION

A device for connecting a first mass to a second mass is disclosed. The device has a base and a first leg. The base has a base axis, a first end and a second end. The first leg extends from the first end of the base. The device has a first configuration and a second configuration. When the base is rotated with respect to the base axis, the device is in the first configuration. The device can also have a second leg extending from the second end of the base.

Another device for connecting a first mass to a second mass is disclosed. The device has a base, a first leg and a second leg. The base has a base axis, a first end and a second end. The first leg has a first longitudinal axis and a first leg length. The first leg extends from the first end of the base. The second leg has a second longitudinal axis and a second leg length. The second leg extends from the second end of the base. The first leg length is substantially longer than the second leg length.

The device can have a first configuration and a second configuration. When the base is rotated with respect to the base axis, the device is in the first configuration.

Yet another device for connecting a first mass to a second mass is disclosed. The device has a base, a first leg and a second leg. The base is curved. The base has a base diameter, a first end and a second end. The first leg has a first longitudinal axis and a first leg length. The first leg extends from the first end of the base. The second leg has a second longitudinal axis and a second leg length. The second leg extends from the second end of the base. The device has a relaxed configuration. In the relaxed configuration the first leg crosses the second leg at a leg angle. The leg angle is less than 180 degrees.

The leg angle can be less than or equal to 90 degrees. The leg angle can be less than or equal to 60 degrees. The base diameter can be less than or equal to 0.13 inches. The base diameter can be greater than or equal to 0.08 inches.

A method of attaching a first mass to a second mass is disclosed. The method uses an attachment device having a base, a first leg, and a second leg. The base has a first end and a second end. The first leg extends from the first end of the base. The second leg extends from the second end of the base. The attachment device has a first configuration and a second configuration. The method includes holding the attachment device in the first configuration. The method also includes twisting the base of the attachment device to force the attachment device into the second configuration. Further, the method includes inserting the attachment device into the first mass and the second mass. The method also includes releasing the attachment device.

Twisting the base of the attachment device can occur before inserting the attachment device into the first mass. Inserting the attachment device, at least partially, into the first mass can occur before twisting the base of the attachment device.

Another method of attaching a first mass to a second mass is disclosed. The method includes forcibly holding an attachment device in a second configuration. The attachment device

has a first configuration and the second configuration. The method also includes inserting the attachment device into the first mass and the second mass. The method also includes releasing the attachment device into the first configuration.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front view of an embodiment of the attachment device.

FIG. 2 is a side view of an embodiment of the attachment device.

FIG. 3 is a bottom view of an embodiment of the attachment device.

FIGS. 4-10 illustrate embodiments of section A-A of the attachment device.

FIG. 11 is a front view of an embodiment of the attachment device.

FIGS. 12 and 13 are bottom views of various embodiments of the attachment device shown in FIG. 11.

FIGS. 14 and 15 are front views of various embodiments of the attachment device.

FIG. 16 is a front perspective view of an embodiment of the attachment device.

FIG. 17 is a top view of the embodiment of the attachment device shown in FIG. 16.

FIG. 18 is a side perspective view of an embodiment of the attachment device.

FIG. 19 is a side view of the attachment device shown in FIG. 18.

FIGS. 20 and 21 are front views of various embodiments of the attachment device.

FIG. 22 is a front perspective view of an embodiment of the attachment device.

FIG. 23 is a top view of the embodiment of the attachment device shown in FIG. 22.

FIG. 24 is a front view of an embodiment of the attachment device.

FIG. 25 illustrates an embodiment of a mandrel for manufacturing the attachment device.

FIGS. 26 and 27 illustrate methods of changing the attachment device from a first configuration to a second configuration.

FIGS. 28-30 are cross-sections illustrating an embodiment of a method of using the attachment device.

FIGS. 31-33 are cross-sections illustrating an embodiment of a method of using the attachment device with the pledget shown in full perspective for FIGS. 31 and 32.

FIGS. 34-36 are cross-sections illustrating an embodiment of a method of using the embodiment of the attachment device shown in FIG. 14.

FIGS. 37-39 are cross-sections illustrating an embodiment of a method of using the embodiment of the attachment device shown in FIGS. 18 and 19.

FIGS. 40-42 are cross-sections illustrating an embodiment of a method of using the attachment device.

FIG. 43 is a cross-section illustrating a method of using the flag.

FIG. 44 illustrates an embodiment of the tool for deploying the attachment device.

FIG. 45 illustrates the end of a tool for deploying the attachment device.

FIGS. 46 and 47 illustrate using the tip of an embodiment of the tool to deploy the attachment device.

#### DETAILED DESCRIPTION

FIGS. 1 through 3 illustrate an attachment device 2. The attachment device 2 can have a base 4, legs 6, and a tip 8 at the

end of each leg 6. (Phantom lines delineate the base 4, legs 6 and tips 8.) The base 4, legs 6 and tips 8 can be separate or integral elements. A flag 10 can be attached to, and extend from, the base 4. The base 4 and/or the legs 6 can be straight or curved.

The attachment device 2 can be made from a deformable or elastic material or a combination of materials having resulting deformable or elastic properties. The material can be, for example, stainless steel alloys, nickel titanium alloys (e.g., Nitinol), cobalt-chrome alloys (e.g., ELGILOY® from Elgin Specialty Metals, Elgin, Ill.; CONICHROME® from Carpenter Metals Corp., Wyomissing, Pa.), polymers such as polyester (e.g., DACRON® from E. I. Du Pont de Nemours and Company, Wilmington, Del.), polypropylene, polytetrafluoroethylene (PTFE), expanded PTFE (ePTFE), polyether ether ketone (PEEK), nylon, polyether-block co-polyamide polymers (e.g., PEBAX® from ATOFINA, Paris, France), aliphatic polyether polyurethanes (e.g., TECOFLEX® from Thermedics Polymer Products, Wilmington, Mass.), polyvinyl chloride (PVC), polyurethane, thermoplastic, fluorinated ethylene propylene (FEP), extruded collagen, silicone, echogenic, radioactive, radiopaque materials or combinations thereof. Examples of radiopaque materials are barium sulfate, titanium, stainless steel, nickel-titanium alloys, tantalum and gold.

Any or all elements of the attachment device 2 can be a matrix for cell ingrowth or used with a fabric, for example a covering (not shown) that acts as a matrix for cell ingrowth. The fabric can be, for example, polyester (e.g., DACRON® from E. I. du Pont de Nemours and Company, Wilmington, Del.), polypropylene, PTFE, ePTFE, nylon, extruded collagen, silicone or combinations thereof.

The attachment device 2 and/or the fabric can be filled and/or coated with an agent delivery matrix known to one having ordinary skill in the art and/or a therapeutic and/or diagnostic agent. These agents can include radioactive materials; radiopaque materials; cytogenic agents; cytotoxic agents; cytostatic agents; thrombogenic agents, for example polyurethane, cellulose acetate polymer mixed with bismuth trioxide, and ethylene vinyl alcohol; lubricious, hydrophilic materials; phosphor cholene; anti-inflammatory agents, for example non-steroidal anti-inflammatories (NSAIDs) such as cyclooxygenase-1 (COX-1) inhibitors (e.g., acetylsalicylic acid, for example ASPIRIN® from Bayer AG, Leverkusen, Germany; ibuprofen, for example ADVIL® from Wyeth, Collegeville, Pa.; indomethacin; mefenamic acid), COX-2 inhibitors (e.g., VIOXX® from Merck & Co., Inc., Whitehouse Station, N.J.; CELEBREX® from Pharmacia Corp., Peapack, N.J.; COX-1 inhibitors); immunosuppressive agents, for example Sirolimus (RAPAMUNE®, from Wyeth, Collegeville, Pa.), or matrix metalloproteinase (MMP) inhibitors (e.g., tetracycline and tetracycline derivatives) that act early within the pathways of an inflammatory response. Examples of other agents are provided in Walton et al, Inhibition of Prostaglandin E<sub>2</sub> Synthesis in Abdominal Aortic Aneurysms, *Circulation*, Jul. 6, 1999, 48-54; Tambiah et al, Provocation of Experimental Aortic Inflammation Mediators and Chlamydia Pneumoniae, *Brit. J. Surgery* 88 (7), 935-940; Franklin et al, Uptake of Tetracycline by Aortic Aneurysm Wall and Its Effect on Inflammation and Proteolysis, *Brit. J. Surgery* 86 (6), 771-775; Xu et al, Sp1 Increases Expression of Cyclooxygenase-2 in Hypoxic Vascular Endothelium, *J. Biological Chemistry* 275 (32) 24583-24589; and Pyo et al, Targeted Gene Disruption of Matrix Metalloproteinase-9 (Gelatinase B) Suppresses Development of Experimental

Abdominal Aortic Aneurysms, *J. Clinical Investigation* 105 (11), 1641-1649 which are all incorporated by reference in their entireties.

A base axis 12 can extend longitudinally through the transverse cross-sectional center of the base 4. As shown in FIG. 2, when viewed from the side, the base axis 12 can form a base plane angle 14 from about 0° to about 30°, for example about 10°. The base 4 can have a base inner radius 16 from about 0.25 mm (0.010 in.) to about 19.1 mm (0.750 in.), for example about 1.91 mm (0.075 in.). The proximal end of the base 4 can be formed into a table 17. The table 17 can be a flat surface that tapers to the base 4.

The base 4 and legs 6 can have a shaft diameter 18 from about 0.03 mm (0.001 in.) to about 6.35 mm (0.250 in.), for example, about 0.51 mm (0.020 in.). The base 4 and legs 6 can have the same or different shaft diameters 18. A base neutral radius 19 can be the base inner radius 16 and half the shaft diameter 18. As shown in FIG. 1, the legs 6 can intersect at a leg angle 20 in or near the plane of the attachment device 2 or in or near the approximate plane of the base 4. An approximate plane is a plane that can be used whether the base 4 does or does not fall on a flat plane. If the base 4 is a straight line or a point, the approximate plane of the base 4 can be calculated using the points of the legs 6 that are nearest the base 4 and out of line with the base 4. The leg angle 20 can be from about 180° to about 10°, more narrowly from about 90° to about 60°, for example about 45° or, for example, about 60°.

The length from an end of the base 4 to a longitudinal leg axis 24 can be a body length 22. The body length 22 can be from about 0.25 mm (0.010 in.) to about 12.7 mm (0.500 in.), for example about 2.913 mm (0.1147 in.). The length between the distal end of one tip 8 and the distal end of the opposite tip 8 can be a tip distance 26. The tip distance 26 can be from about 0.03 mm (0.001 in.) to about 25.4 mm (1.000 in.), more narrowly about 1.3 mm (0.050 in.) to about 3.18 mm (0.125 in.), for example about 2.3 mm (0.090 in.).

The tip 8 can have a tip length 28 from about 0.05 mm (0.002 in.) to about 12.7 mm (0.500 in.), for example about 1.0 mm (0.040 in.). The tip 8 can have a tip angle 30 from about 5° to about 90°, for example about 30°. The tips 8 can be straight, pointed ends, curve out of line (shown by alternative tips 8a and 8b, drawn in phantom lines in FIGS. 2 and 3) from the nearest end of the leg 6, or combinations thereof.

The tips 8 and/or legs 6 can have retention devices 29. The retention devices 29 can be barbs, spikes, hooks, threads, ribs, splines, a roughened surface, a sintered surface, a covered surface (e.g., with DACRON® from E. I. du Pont de Nemours and Company, Wilmington, Del.) or combinations thereof. A retention coating 31, for example a biodegradable coating or filler such as gel or gelatin or otherwise removable, can be on and/or around and/or near the retention devices 29. The retention coating 31 (shown in phantom lines) can be configured to render the retention device 29 substantially ineffective until a substantial amount of the retention coating 31 has been biodegraded or otherwise removed.

The legs 6 can have mechanical interfaces 33, for example, a slot, snap, protrusion, latch, catch or combinations thereof. The interfaces 33 can be aligned so the interface on one leg 6 meets the interface 33 on the other leg 6 at the point where the legs 6 cross. The interfaces 33 can removably attach to each other.

FIGS. 4 through 10 illustrate examples of cross-section A-A of the legs 6 and/or the base 4. The cross-section A-A of the legs 6 can be the same or different as the cross-sections of the base 4. The cross-sections of the base 4 and/or legs 6 can be constant or vary along their respective lengths. FIGS. 4 through 8, respectively, illustrate circular, rectangular (in-

cluding square), triangular, substantially flat, and star-shaped or irregular cross-sections A-A. FIG. 9 illustrates an oval cross-section A-A. A ratio of the shaft diameter 18 to the length of a minor axis 32 can be from about 1:1 to about 20:1, for example 10:1.

FIG. 10 illustrates a cavity 36 inside the cross-section A-A. The cavity 34 can be hollow or can be filled completely or partially. The cavity 34 can be filled with an agent delivery matrix known to one having ordinary skill in the art and/or a therapeutic and/or diagnostic agent and/or echogenic and/or radioactive and/or radiopaque materials, for example, the agents and/or materials listed supra. The type and amount of filling can vary along the length of the base 4 and/or legs 6. The ratio of the shaft diameter 18 to a cavity diameter 36 can be from about 1:1 to about 50:1, for example, about 2:1.

FIG. 11 illustrates an attachment device 2 that can have a leg 6 that can have a first leg segment 38 and a second leg segment 40. The first leg segment 38 can extend from the base 4. The second leg segment 40 can extend on a proximal end from the first leg segment 38. The tip 8 can extend from a distal end of the second leg segment 40. The second leg segment 40 can have a different radius of curvature than the first leg segment 38 and/or form an angle with respect to the first leg segment 40. FIG. 12 illustrates that the second leg segment 40 can form an angle (shown by arrows) with the approximate plane of the base 4. FIG. 13 illustrates that the first leg segment 38 can form an angle (shown by arrows) with the approximate plane of the base 4. The second leg segments 40 can be substantially parallel with the approximate plan of the base 4.

FIG. 14 illustrates an attachment device 2 that can have a first leg 6a that can be substantially longer than a second leg 6b. The ratio of a first leg-tip length 22a to a second leg-tip length 22b can be from about 1:1 to about 10:1, for example, about 3:1.

FIG. 15 illustrates an attachment device that can have a first leg radius 42 and a second leg radius 44. The ratio of the first leg radius 42 to the second leg radius 44 can be from about 1:1 to about 50:1, for example about 10:1.

FIGS. 16 and 17 illustrate an attachment device 2 that can have a "flat top." The approximate plane of the second leg 6b can form an angle, for example about 90°, with the approximate plane of the base 4. When in use, the flat top can further anchor the attachment device 2 against the first mass and/or second mass. FIGS. 18 and 19 illustrate an attachment device 2 that can have arms 6 that can wrap around the base axis 12.

FIG. 20 illustrates an attachment device 2 that can have arms 46 that can extend from the base 4 and/or the legs 6. When deployed, the arms 46 can squeeze tissue between the arms 46 and the legs 6 and/or base 4 for additional retention force. Anchors 48 can extend from the arms 46, for example at the distal ends of the arms 46. The anchors 48 can be, for example, hooks, barbs, spikes, staples or combinations thereof. The anchors 48 can extend directly from the base 4 and/or legs 6 with or without arms 46 separately attached to the base 4 and/or legs 6. FIG. 21 illustrates an attachment device 2 that can have a straight base 4 and can have the arms 46 extending from the base 4.

FIGS. 22 and 23 illustrate an attachment device that can have first, second and third legs 6a, 6b and 6c. The base 4 can be a platform, wireframe, or point attachment which can be spot-welded or brazed, tube crimped or otherwise mechanically connected. The planes of the legs 6a, 6b and 6c can intersect at substantially equal angles, about 120°, or unequal angles.

FIG. 24 illustrates an attachment device that can have a first loop 49 and a second loop 51. The first loop 49 can be formed

from the base 4 and a proximal portion of the first leg segments 38. The second loop 51 can be formed from a distal portion of the first leg segments 38 and a proximal portion of the second leg segments 40.

#### Methods of Making

FIG. 25 illustrates a mandrel 50 that can be used to form the attachment device 2, for example during heat treatment. The base 4 and/or legs 6 can be held on the mandrel 50 by a single cylinder 52, a formed path 54, a pressure plate 56, for example a washer under a screw or combinations thereof. Methods for forming shape memory alloys (e.g., Nitinol) are known to those having ordinary skill in the art. The tips 8 can be formed, for example, by grinding, electropolishing, or precision sharpening (e.g., polishing services from Point Technologies, Inc., Boulder, Colo.) to a satisfactory geometry, including a trocar point, beveled, tapered, pointed or flattened.

Other methods known to one having ordinary skill in the art can be used to manufacture the attachment device 2 and/or its elements. For example, manufacturing techniques include molding, machining, casting, forming (e.g., pressure forming), crimping, stamping, melting, screwing, gluing, welding, die cutting, laser cutting, electrical discharge machining (EDM), etching or combinations thereof.

Any elements, sub-assemblies, or the attachment device 2 as a whole after final assembly, can be coated by dip-coating or spray-coating methods known to one having ordinary skill in the art, utilizing materials such as PTFE (e.g., TEFLON® from E. I. du Pont de Nemours and Company, Wilmington, Del.), polyester (e.g., DACRON® from E. I. du Pont de Nemours and Company, Wilmington, Del.), gelatin, gel, other polymers or combinations thereof. One example of a method used to coat a medical device for vascular use is provided in U.S. Pat. No. 6,358,556 by Ding et al. and hereby incorporated by reference in its entirety. Time release coating methods known to one having ordinary skill in the art can also be used to delay the release of an agent in the coating. The coatings can be thrombogenic or anti-thrombogenic.

The attachment device 2, or any element thereof (e.g., the base 4) can be covered with a fabric, for example polyester (e.g., DACRON® from E. I. du Pont de Nemours and Company, Wilmington, Del.), polypropylene, PTFE (e.g., TEFLON® from E. I. du Pont de Nemours and Company, Wilmington, Del.), ePTFE, nylon, extruded collagen, gel, gelatin, silicone or combinations thereof. Methods of covering an implantable device with fabric are known to those having ordinary skill in the art, for example, sintering, spray coating, adhesion, loose covering, dipping or combinations thereof.

#### Methods of Using

The attachment device 2 can have a first configuration (e.g., the configuration shown in FIGS. 26 and 27) and a second configuration (e.g., the configuration shown in FIGS. 1 through 3). The attachment device 2 can have the second configuration when the attachment device is in a relaxed state, with no external forces applied (e.g., prior to insertion or use). The attachment device 2 can have the first configuration when external forces are applied, such as by a delivery tool prior to delivery. When external forces are removed from the attachment device 2, the attachment device 2 can revert from the first configuration to the second configuration.

The attachment device can substantially revert to the second configuration even when some permanent hysteresis deformation occurs and/or when a foreign object (e.g., a first and/or second mass) is obstructing the attachment device 2. When the attachment device 2 has the first configuration, one or both legs 6 can be rotated with respect to the base 4 (e.g., by

rotating the base 4 around the base axis 12, one or both legs 6 splay or separate as they are torqued by the twisting or rotating around of the base).

FIG. 26 illustrates a method of forcing the attachment device to have the first configuration. The attachment device 2 can be forced to have the first configuration by the application of a base torque, shown by arrows 58, applied about the base axis 12. The base torque can be directly applied to the base 4. The base torque indirectly becomes, or can be applied as, a leg torque, as shown by arrows 60a and 60b, to the legs 6a and/or 6b about the leg axes 24a and 24b. If approximately two times the base neutral radius 19 is less than the tip distance 26, the legs 6 will splay outward when entering the first mass 68. If approximately two times the base neutral radius 19 is greater than or equal to the tip distance 26, the legs 6 will splay inward or stay vertical when deploying into the first mass 68.

FIG. 27 illustrates a method of forcing the attachment device to have the first configuration. The attachment device 2 can be forced to have the first configuration by the application of a pivot torque, shown by arrows 62, applied about the area where the base 4 attaches to the legs 6, so that the legs 6 are forced to pivot radially outward from each other. The pivot torque can be applied by applying outward translational forces, as shown by arrows 64, to one or both legs 6. The pivot torque can be applied by applying translational forces to the base 4, as shown by arrows 66.

As illustrated in FIGS. 28 through 30, the attachment device 2 can be deployed to attach a first mass 68 to a second mass 70. The first mass 68 and/or the second mass 70 can be a prosthesis and/or a tissue, or both tissue or both prostheses. The prosthesis can be, for example, cardiac leads, markers, stents, grafts, stent-grafts, heart valves, annuloplasty rings, autografts, allografts, xenografts or any assemblies thereof or combination thereof. The tissue can be, for example, vessels, valves, organs (e.g., intestine, heart, skin, liver, kidney, urethra, bone mass, tendon, nerve, muscle), calcified soft tissue or any combination thereof.

Heart valve assemblies disclosed by Griffin et al. in U.S. Pat. No. 6,241,765, by Lane in U.S. Pat. No. 6,371,983 and by Ritz in U.S. Pat. No. 5,976,183, both of which are hereby incorporated in their entireties, can be placed with the use of the device of the present invention. Other heart valve assemblies that can be used include, for example, the Advantage Bileaflet heart valve, Parallel valve, Freestyle stentless aortic valve, Hancock Porcine heart valve, Hancock apical left ventricular connector model 174A, Hancock valved conduit models 100, 105, 150, Hall Medtronic heart valve, Hall Medtronic valved conduit, MOSAIC® heart valve and Intact porcine tissue valve (by Medtronic, Inc. Minneapolis, Minn.); Angelini Lamina-flo valve (by Cardio Carbon Company, Ltd., England); Bjork-Shiley single-disk, monostrut and caged-disk valves (Shiley, Inc., now-defunct, previously of CA); Wada-Cutter valve and Chitra Cooley-Cutter valve (by Cutter Biomedical Corp., San Diego, Calif.); Angioflex trileaflet polyurethane valve (by Abiomed, Inc., Danvers, Mass.); ATS AP Series heart valve and ATS Standard heart valve (by ATS Medical, Inc., Minneapolis, Minn.); ANNU-LOFLO® annuloplasty ring, ANNUFLEX® annuloplasty ring, CARBSEAL® valved conduit, ORBIS® Universal aortic and mitral valve, pediatric/small adult valve, R series valve, SUMIT® mitral valve, TOP HAT® aortic valve, OPTIFORM® mitral valve, MITROFLOW SYNERGY® PC stented aortic pericardial bioprosthesis and the SYNERGY® ST stented aortic and mitral porcine bioprosthesis (by Carbo-Medics, Inc., Austin, Tex.); ON-X® prosthetic heart valve (by MCRI®, LLC, Austin, Tex.); Starr-Edwards SILAS-

TIC® ball valve, Starr-Edwards 1000, Starr-Edwards 1200, Starr-Edwards 1260, Starr-Edwards 2400, Starr-Edwards 6300, Starr-Edwards 6500, Starr-Edwards 6520, Carpentier-Edwards porcine tissue valve, Carpentier-Edwards pericardial prosthesis, Carpentier-Edwards supra-annular valve, Carpentier-Edwards annuloplasty rings, Duromedics valve and PERIMOUNT® heart valve (by Edwards Lifesciences Corp., Irvine, Calif.); Cross-Jones Lenticular disc valve (by Pemco, Inc.); Tissuemed stented porcine valve (by Tissuemed, Ltd., Leeds, England); Tekna valve (by Baxter Healthcare, Corp., Deerfield, Ill.); Komp-01 mitral retainer ring (by Jyros Medical Ltd., London, England); SJM® Masters Series mechanical heart valve, SJM® Masters Series aortic valved graft prosthesis, ST. JUDE MEDICAL® mechanical heart valves, ST. JUDE MEDICAL® mechanical heart valve Hemodynamic Plus (HP) series, SJM REGENT® valve, TORONTO SPV® (Stentless Porcine Valve) valve, SJM BIOCOR® valve and SJM EPIC® valve (St. Jude Medical, Inc., St. Paul, Minn.); Sorin Bicarbon, Sorin Carbocast, Sorin Carboseal Conduit, Sorin Pericarbon and Sorin Pericarbon Stentless (by Snia S.p.A., Italy). The attachment devices of the present invention may be deployed to implant these various devices in the supra-annular position, or infrannular, depending on the geometry and preferred placement of a particular device. Similarly, it may be advantageous to use the attachment devices 2 of the present invention to secure a sewing ring, or first prosthesis by placing them horizontally or vertically within or around the annulus of such ring, prior to placing a second prosthesis including a valve structure, as provided in U.S. application Ser. No. 10/646,639 filed, 22 Aug. 2003, hereby incorporated by reference in its entirety.

FIG. 28 illustrates that the attachment device 2 can be held in the first configuration. The attachment device 2 can be fed through a pledget 71 before the attachment device 2 is forced into the first mass 68. The pledget 71 can be a piece of fabric, for example, a fabric listed supra. The pledget 71 can be loaded onto the attachment device 2 before use. FIG. 29 illustrates that the attachment device 2 can be forced, as shown by arrow 72, into and through the first mass 68 and part of the second mass 70. FIG. 30 illustrates that the attachment device 2 can be released from having the first configuration. The attachment device 2 can revert to having substantially the second configuration. A pinching force, shown by arrows, can be applied to the attachment device 2 to encourage additional reversion of the attachment device 2 to having the second configuration. The attachment device 2 shown in FIG. 24 can be deployed in the same manner as described supra, except that the attachment device 2 shown in FIG. 24 can be rotated sufficiently to straighten the first and second loops, before or during deployment.

The attachment device 2 can be removed and redeployed at any stage of deployment supra, for example, if the surgeon is unsatisfied with the position of the attachment device 2, or if the prosthesis need replacing or “redoing” at a point in the future. If the attachment device 2 has a retention device 29, when the retention coating 31 sufficiently biodegrades or is otherwise removed, the retention devices 29 will become exposed and can substantially prevent the removal of the attachment device 2 from the deployment site. Removal may still be achieved however, by apply sufficient force (by a tool or other device) to overcome the strength of the secondary retention element.

FIGS. 31 through 33 illustrate a method of deploying the attachment device 2 to attach a first mass 68 to a second mass 70. The pledget 71 can be fed over the attachment device 2 before use. The pledget 2 can be formed as a rectangular container with an access opening 73, for example a slit, hole,

or aperture, to allow access to the base 4 of the attachment device 2. The attachment device 2 can have the second configuration. The attachment device 2 can be forced, as shown by arrow, so the tips 8 engage the first mass 68. FIG. 32 illustrates that, with the tips 8 held by the first mass 68, a longitudinal torque, shown by arrows, applied to the attachment device 2 about a longitudinal axis 74 can then force the attachment device 2 into the first configuration. As illustrated by FIG. 33, the attachment device 2 can be forced, shown by arrow, through the first mass 68 and part of the second mass 70. The longitudinal torque (not shown in FIG. 33) can be removed during deployment or after the attachment device 2 is completely deployed into the first and second masses 68 and 70. The pledget 71 can be crushed during deployment.

FIGS. 34 through 36 illustrate a method of deploying the attachment device shown in FIG. 14. The first leg 6a can be forced, as shown by arrow, into and through the first mass 68 and part of the second mass 70. The first leg 6a can have a “paddle” (not shown). The paddle can be a flat oval or long rectangular cross-sectional shape on one leg. The paddle can increase resistive force with the first and/or second mass 68 and/or 70 when applying torque to the attachment device 2.

FIG. 35 illustrates that the attachment device 2 can be forced into the first configuration by applying a base torque, shown by arrows 58. The second leg 6b can then rotate outwardly from the attachment device 2, as shown by arrow 76.

FIG. 36 illustrates that the attachment device 2 can be forced, shown by arrow, through the first mass 68 and part of the second mass 70. The base torque (not shown in FIG. 36) can be removed during deployment or after the attachment device 2 is completely deployed into the first and second masses 68 and 70.

FIGS. 37 through 39 illustrate a method of deploying the attachment device 2 shown in FIGS. 18 and 19. FIG. 37 illustrates that the base 4 and the tips 8 can be placed in contact with or near the first mass 68. FIG. 38 illustrates that the arms 6 can be rotated, as shown by arrows, about the base axis 12. The arms 6 can be rotated to cause the arms 6 to be forced into the first mass 68. FIG. 39 illustrates that the arms 6 can be rotated, as shown by arrows, further about the base axis 12. The arms 6 can be forced into and through the second mass 70. The arms 6 can re-enter the first mass 68.

FIGS. 40 through 42 illustrate a method of deploying the attachment device 2 to attach a first mass 68 to a second mass 70. The first mass 68 and the second mass 70 can be two sections of the same object, such as when the attachment device 2 is used to close a wound. FIG. 40 illustrates that the attachment device 2 can be held in the first configuration. FIG. 41 illustrates that the attachment device 2 can be forced, as shown by arrow 72, so that the first leg 6a inserts into the first mass 68 and that the second leg 6b inserts into the second mass 70. FIG. 42 illustrates that the attachment device 2 can be released from having the first configuration. The attachment device 2 can revert to having substantially the second configuration, causing the legs 6a and 6b to rotate inward, shown by arrows 78, applying force, shown by arrows 80, to the first mass 68 and the second mass 70 such that the first and second masses 68 and 70 move toward each other.

The attachment device 2 can be removed from the second mass 70 and/or the first mass 68, when applicable, by reversing the steps of the deployment methods supra.

FIG. 43 illustrates that, during use, the attachment device 2 can be covered by new tissue growth 82. The flag 10 can extend outside of the new tissue growth 82 (as shown) or be located just below the surface but palpable. The flag 10 can act as a marker, palpable or visible by direct vision or imaging modalities known in the art (e.g., x-ray, magnetic resonance



imaging (MRI), ultrasound, computed tomography (CT), echocardiogram) for example to locate the attachment device 2 in case of removal of the attachment device 2. The flag 10 can be made of, for example, suture material (e.g., Nylon, polyglycolic acid, polyester such as DACRON® from E. I. du Pont de Nemours and Company, Wilmington, Del., metals such as those used in the other elements of the attachment device 2, other polymers or combinations thereof). The base 4 can also serve this function (e.g., of a marker) in some applications.

FIG. 44 illustrates a tool 84 for deploying the attachment device 2. The tool 84 can have a first lever 86 and a second lever 88. The first lever 86 can be rotatably attached to the second lever 88 at a pivot 90. The first and second levers 86 and 88 can have a handle 92 at each lever's first end and a pad 94 at each lever's second end. The pads 94 can be used to hold the attachment device 2. When a force is applied to the handles 92, shown by arrows 96, the force is transmitted, shown by arrows 98, to the pads 94.

A driver shaft 100 can have a driver handle 102 at a first end and grips 104 at a second end. The pivot 90 can have a longitudinal channel 106. The driver shaft 100 can pass through the longitudinal channel 106 and/or be rotatably mounted to a case (not shown) fixed to a lever 86 or 88. The grips 104 can be releasably attached to the attachment device 2. The attachment device 2 can be rotated about the longitudinal axis 2 by releasing the pads 94 and rotating, as shown by arrows 108, the driver handle.

FIG. 45 shows the end of a tool 84 for deploying the attachment device 2 before the attachment device 2 has been loaded into the tool 84. The tool 84 can have a top part 110 and a bottom part 112. The top part 110 can be removably attached to the bottom part, as shown by arrow 114.

The top part 110 and/or the bottom part 112 can have grooves 116 sized to fit the base 4 and a portion of one or more legs 6 when the attachment device 2 has the first configuration. The attachment device 2 can be forced to have the first configuration and be loaded into the tool 84, as shown by arrow 118. The top part 110 can be attached to the bottom part 112 with the attachment device 2 seated (not shown) in the grooves 116.

The attachment device 2 can be placed at a desired deployment site by the tool 84. The device 2 can be deployed from the tool 84 by removing the top part 110 from the bottom part 112, and removing the tool 84 from the deployment site.

FIG. 46 illustrates an end of a tool 84. The tool 84 can have a case 120 with an anvil 122 and leg ports 124. The case 120 can be slidably attached to a slide 126. The attachment device 2 can be loaded around the anvil 122. The legs 6 can protrude from the case 120 through the leg ports 124.

FIG. 47 illustrates a method of using the tool 84 of FIG. 46 to deploy the attachment device 2. The slide 126 can be forced, as shown by arrow 128, toward the anvil 122. The slide 126 can push the base 4 against the anvil 122, causing the legs 6 to rotate outward, as shown by arrows 76. The surface geometry of the anvil 122 and the slider 126 can match the surface geometry of the attachment device 2, when the attachment device is fully strained, as shown in FIG. 39. The attachment device 2 can then be inserted into the desired deployment site (not shown). When the attachment device 2 is in place, the attachment device 2 can be deployed from the tool 84, for example, by sliding the anvil 122 out of the way (perpendicular to the plane of FIG. 47) and forcing the attachment device 2 out the end of the tool 84 with the slide 126.

The ends of the tools 84 shown in FIGS. 45 through 47 can be pivoted to the remainder of the tool 84 by methods known to those having ordinary skill in the art. The pivotable end of

the tool 84 can improve access to deployment sites not as easily accessible by a non-articulating tool 84. The tool 84 can be non-articulatable. It would also be possible when access to the site of implantation allows, to employ a tool substantially similar to a needle driver tool known to those skilled in the art.

Additional disclosure is included in U.S. patent application Ser. Nos. 10/327,821 and 10/646,639, filed 20 Dec. 2002 and 22 Aug. 2003, respectively, which are hereby incorporated by reference in their entireties. It is apparent to one skilled in the art that various changes and modifications can be made to this disclosure, and equivalents employed, without departing from the spirit and scope of the invention. Elements shown with any embodiment are exemplary for the specific embodiment and can be used on other embodiments within this disclosure.

We claim:

1. A method for attaching a prosthesis to a tissue annulus using an attachment device comprising a base and a pair of legs extending from the base, the attachment device being elastically movable from a relaxed state wherein the legs cross one another and a delivery state wherein the legs extend substantially parallel with one another, the method comprising:

loading the attachment device into a tool with the attachment device in the relaxed state;

securing the prosthesis to the tissue annulus using the attachment device while applying a force using the tool to place the attachment device in the delivery state; and releasing the attachment device from the tool such that the attachment device returns towards the relaxed state such that the legs cross one another,

wherein the attachment device is delivered by:

a) holding the attachment device in the tool in the relaxed state;

b) applying a force with the tool to force the attachment device to the delivery state;

c) inserting the legs through the prosthesis into tissue with the attachment device in the delivery state; and

d) deploying the attachment device from the tool such that the attachment device returns towards the relaxed state.

2. The method of claim 1, wherein the tool comprises an anvil, and step a) comprises loading the attachment device around the anvil in the relaxed state.

3. The method of claim 1, wherein the tool comprises a slide and an anvil for causing the legs of the attachment device to rotate outward to the delivery state during step b).

4. The method of claim 3, wherein step d) comprises sliding the anvil out of the way and forcing the attachment device out the end of the tool with the slide.

5. The method of claim 1, wherein the tool retains the attachment device in the delivery state while the attachment device is inserted through the prosthesis into tissue, whereupon the attachment device is deployed from the tool.

6. A method for attaching an annular prosthesis to a tissue annulus using a plurality of attachment devices, each attachment device comprising a base and a pair of legs extending from the base, the attachment device being elastically movable from a relaxed state wherein the legs cross one another and a delivery state wherein the legs extend substantially parallel with one another, the method comprising:

loading an attachment device into a tool with the attachment device in the relaxed state;

securing the annular prosthesis to the tissue annulus using the attachment device while applying a force using the tool to place the attachment device in the delivery state;

## 13

releasing the attachment device from the tool such that the attachment device returns towards the relaxed state such that the legs cross one another; and

inserting a plurality of additional attachment devices through the prosthesis and into the tissue annulus to further secure the annular prosthesis,

wherein each attachment device is delivered by:

- a) holding the attachment device in the tool in the relaxed state;
- b) applying a force with the tool to force the attachment device to the delivery state;
- c) inserting the legs through the annular prosthesis into tissue with the attachment device in the delivery state; and
- d) deploying the attachment device from the tool such that the attachment device returns towards the relaxed state.

7. The method of claim 6, wherein the annular prosthesis comprises one of a stent, graft, stent-graft, heart valve, annuloplasty ring, autograft, allograft, and a xenograft.

8. The method of claim 6, wherein the annular prosthesis comprises a sewing ring, and wherein the annular prosthesis is attached to the tissue annulus by inserting the attachment devices through the sewing ring.

9. The method of claim 6, wherein the tool comprises an anvil, and step a) comprises loading the attachment device around the anvil in the relaxed state.

10. The method of claim 6, wherein the tool comprises a slide and an anvil for causing the legs of the attachment device to rotate outward to the delivery state during step b).

11. The method of claim 10, wherein step d) comprises sliding the anvil out of the way and forcing the attachment device out the end of the tool with the slide.

12. The method of claim 6, wherein the tool retains the attachment device in the delivery state while the attachment

## 14

device is inserted through the annular prosthesis into tissue, whereupon the attachment device is deployed from the tool.

13. A method for attaching a heart valve prosthesis to a tissue annulus using attachment devices, each attachment device comprising a base and a pair of legs extending from the base, the attachment devices being elastically movable from a relaxed state wherein the legs cross one another and a delivery state wherein the legs extend substantially parallel with one another, the heart valve prosthesis comprising a first prosthesis comprising a sewing ring and a second prosthesis comprising a valve structure, the method comprising:

securing the first prosthesis to a tissue annulus by inserting the attachment devices through the sewing ring, a tool carrying the attachment devices in the relaxed state, the tool applying a force to place the attachment devices in the delivery state when the attachment devices are inserted through the sewing ring;

releasing the attachment devices from the tool such that the attachment devices return towards the relaxed state such that the legs cross one another; and

thereafter placing the second prosthesis,

wherein each attachment device is delivered and released by:

- a) holding the attachment device in the tool in the relaxed state;
- b) applying a force with the tool to force the attachment device to the delivery state;
- c) inserting the legs through the first prosthesis into tissue with the attachment device in the delivery state; and
- d) deploying the attachment device from the tool such that the attachment device returns towards the relaxed state.

\* \* \* \* \*

专利名称(译)	附件装置及其使用方法		
公开(公告)号	<a href="#">US8603161</a>	公开(公告)日	2013-12-10
申请号	US12/498195	申请日	2009-07-06
[标]申请(专利权)人(译)	ARBOR手术TECH		
申请(专利权)人(译)	ARBOR外科技术, INC.		
当前申请(专利权)人(译)	美敦力公司, INC.		
[标]发明人	DREWS MICHAEL J GURSKIS DONNELL W BACICH STEVEN R		
发明人	DREWS, MICHAEL J. GURSKIS, DONNELL W. BACICH, STEVEN R.		
IPC分类号	A61B17/10 A61B17/064 A61B17/068 A61B17/08 A61B17/122		
CPC分类号	A61B17/064 A61B17/0682 A61B17/083 A61F2/2427 A61B17/1227 A61B2017/0641 Y10S623/904		
其他公开文献	US20100010616A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

公开了用于附接第一质量和第二质量的装置及其制造和使用方法。该装置可由弹性、弹性或可变形材料制成。该装置可用于将心脏瓣膜环连接到生物环。该装置还可用于伤口闭合或各种其他手术，例如将假体固定到周围组织或其他假体，组织修复，例如关闭先天性缺陷，例如隔膜心脏缺损，组织或血管吻合，固定具有或不具有用于疝修复的增强网的组织，诸如骨融合或肌腱或肌肉修复中的矫形锚固，眼科适应症，腹腔镜或内窥镜组织修复或假体的放置，或机器人装置用于诸如上述执行的程序的组织远程。

