



US009277908B2

(12) **United States Patent**
Butler et al.

(10) **Patent No.:** **US 9,277,908 B2**
(45) **Date of Patent:** ***Mar. 8, 2016**

(54) **RETRACTOR**

(71) Applicant: **Atropos Limited**, County Wicklow (IE)

(72) Inventors: **John Butler**, County Mayo (IE); **Derek William Young**, County Dublin (IE); **Aoibheann Gill**, County Longford (IE); **Alan Reid**, Dublin (IE); **Frank Bonadio**, County Wicklow (IE)

(73) Assignee: **Atropos Limited**, Bray, County Wicklow (IE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/634,159**

(22) Filed: **Feb. 27, 2015**

(65) **Prior Publication Data**

US 2015/0272563 A1 Oct. 1, 2015

Related U.S. Application Data

(63) Continuation of application No. 13/205,517, filed on Aug. 8, 2011, now Pat. No. 8,986,202, which is a continuation of application No. 11/841,777, filed on Aug. 20, 2007, now Pat. No. 8,012,088, which is a

(Continued)

(30) **Foreign Application Priority Data**

Oct. 14, 1999	(IE)	990861
Dec. 16, 1999	(IE)	991053
Feb. 18, 2000	(EP)	00650010

(51) **Int. Cl.**

A61B 17/02 (2006.01)

A61B 1/32 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61B 17/0218** (2013.01); **A61B 1/32** (2013.01); **A61B 17/0206** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC .. A61B 1/32; A61B 17/0293; A61B 17/3423; A61B 17/3421; A61B 17/3431

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,157,202 A	10/1915	McLeland
1,598,284 A	8/1926	Kinney

(Continued)

FOREIGN PATENT DOCUMENTS

DE	37 39 532	12/1988
DE	37 37 121	5/1989

(Continued)

OTHER PUBLICATIONS

Kagaya, "Laparoscopic cholecystectomy via two ports, using the "Twin-Port" system", J. Hepatobiliary Pancreat Surg (2001) 8:76-80.


Primary Examiner — Anu Ramana

(74) *Attorney, Agent, or Firm* — Bookoff McAndrews, PLLC

(57) **ABSTRACT**

A retractor (101) for retracting the margins of a wound opening (103) comprises an inner anchoring O-ring (105) attached to a cylindrical sleeve (106) at a distal end and a reinforcing O-ring (109) attached to a proximal end of the sleeve (106). The sleeve (106) is led between an inner ring part (110) and a corresponding recess (116) in an outer ring part (111). The outer ring part (111) has anchor formations (120) over which the proximal end of the sleeve (106) is attached to anchor the sleeve (106). To retract the wound opening (103) the sleeve (106) is pulled while the guide rings (110, 111) are moved against the tissue surrounding the wound opening (103). This pulls the inner O-ring (105) against the inside of the tissue adjacent the wound opening (103), and retracts the wound opening (103). The sleeve (106) is manipulated locally for maximum retraction efficiency.

20 Claims, 24 Drawing Sheets



Related U.S. Application Data

continuation of application No. 10/374,523, filed on Feb. 27, 2003, now Pat. No. 7,445,597, which is a continuation of application No. 09/849,341, filed on May 7, 2001, now Pat. No. 6,582,364, which is a continuation of application No. 09/688,138, filed on Oct. 16, 2000, now Pat. No. 6,254,534.

(51) Int. Cl.

A61B 19/00 (2006.01)

A61B 17/34 (2006.01)

A61B 17/00 (2006.01)

(52) U.S. Cl.

CPC **A61B 17/0293** (2013.01); **A61B 17/3423** (2013.01); **A61B 19/26** (2013.01); **A61B 17/3421** (2013.01); **A61B 17/3431** (2013.01); **A61B 2017/00557** (2013.01); **A61B 2017/0225** (2013.01); **A61B 2017/3429** (2013.01); **A61B 2017/3488** (2013.01); **A61B 2017/3492** (2013.01)

(56)**References Cited****U.S. PATENT DOCUMENTS**

1,810,466 A	6/1931	Deutsch	4,228,792 A	10/1980	Rhys-Davies
2,219,564 A	10/1940	Reyniers	4,239,036 A	12/1980	Krieger
2,305,289 A	12/1942	Coburg	4,240,411 A	12/1980	Hosono
2,695,608 A	11/1954	Gibbon	4,253,201 A	3/1981	Ross et al.
2,835,253 A	5/1958	Borgeson	4,306,562 A	12/1981	Osborne
2,853,075 A	10/1958	Hoffman	4,321,915 A	3/1982	Leighton
3,039,468 A	6/1962	Price	4,331,138 A	5/1982	Jessen
3,111,943 A	11/1963	Orndorff	4,338,934 A	7/1982	Spademan
3,244,169 A	4/1966	Baxter	4,338,937 A	7/1982	Lehrman
3,253,594 A	5/1966	Matthews et al.	4,367,728 A	1/1983	Mutke
3,313,299 A	4/1967	Spademan	4,399,816 A	8/1983	Spangler
3,329,390 A	7/1967	Hulsey	4,411,659 A	10/1983	Jensen et al.
3,332,417 A	7/1967	Blanford et al.	4,421,296 A	12/1983	Stephens
3,347,226 A	10/1967	Harrower	4,424,833 A	1/1984	Spector
3,347,227 A	10/1967	Harrower	4,428,364 A	1/1984	Bartolo
3,397,692 A	8/1968	Creager, Jr. et al.	4,430,081 A	2/1984	Timmermans
3,402,710 A	9/1968	Paleschuck	4,434,791 A	3/1984	Darnell
3,447,533 A	6/1969	Spicer	4,436,519 A	3/1984	O'Neill
3,522,800 A	8/1970	Lesser	4,485,490 A	12/1984	Akers et al.
3,523,534 A	8/1970	Nolan	4,488,877 A	12/1984	Klein
3,570,475 A	3/1971	Weinstein	4,543,088 A	9/1985	Bootman et al.
3,592,198 A	7/1971	Evans	4,550,713 A	11/1985	Hyman
3,656,485 A	4/1972	Robertson	4,553,537 A	11/1985	Rosenberg
3,685,786 A	8/1972	Woodson	4,601,710 A	7/1986	Moll
3,717,151 A	2/1973	Collett	4,610,665 A	9/1986	Matsumoto
3,729,006 A	4/1973	Wilder et al.	4,626,245 A	12/1986	Weinstein
3,782,370 A	1/1974	McDonald	4,634,424 A	1/1987	O'Boyle
3,797,478 A	3/1974	Walsh et al.	4,649,904 A	3/1987	Krauter
3,807,393 A	4/1974	McDonald	4,654,030 A	3/1987	Moll et al.
3,828,764 A	8/1974	Jones	4,673,393 A	6/1987	Suzuki et al.
3,841,332 A	10/1974	Treacle	4,673,394 A	6/1987	Fenton
3,853,126 A	12/1974	Schulte	4,755,170 A	7/1988	Golden
3,853,127 A	12/1974	Spademan	4,776,843 A	10/1988	Martinez et al.
3,856,021 A	12/1974	Macintosh	4,777,943 A	10/1988	Chvapil
3,907,389 A	9/1975	Cox et al.	4,784,646 A	11/1988	Feingold
3,915,171 A	10/1975	Shermeta	4,798,594 A	1/1989	Hillstead
3,965,890 A	6/1976	Gauthier	4,809,679 A	3/1989	Shimonaka
3,996,623 A	12/1976	Kaster	4,863,438 A	9/1989	Gauderer
3,998,217 A	12/1976	Trumbull et al.	4,889,107 A	12/1989	Kaufman
4,000,739 A	1/1977	Stevens	4,895,565 A	1/1990	Hillstead
4,016,884 A	4/1977	Kwan-Gett	4,897,081 A	1/1990	Poirier
4,024,872 A	5/1977	Muldoon	4,903,710 A	2/1990	Jessamine et al.
4,030,500 A	6/1977	Ronnquist	4,950,222 A	8/1990	Scott et al.
4,083,370 A	4/1978	Taylor	4,950,223 A	8/1990	Silvanov
4,096,853 A	6/1978	Weigand	4,984,564 A	1/1991	Yuen
4,130,113 A	12/1978	Graham	4,991,593 A	2/1991	LeVahn
4,177,814 A	12/1979	Knepshild	4,998,538 A	3/1991	Charowsky et al.
4,188,945 A	2/1980	Wenander	5,002,557 A	3/1991	Hasson
4,217,664 A	8/1980	Faso	5,015,228 A	5/1991	Columbus et al.
			5,019,101 A	5/1991	Purkait
			5,026,366 A	6/1991	Leckrone
			5,041,095 A	8/1991	Littrell
			5,045,070 A	9/1991	Grodecki et al.
			D320,658 S	10/1991	Quigley et al.
			5,071,411 A	12/1991	Hillstead
			5,074,878 A	12/1991	Bark et al.
			5,082,005 A	1/1992	Kaldany
			5,086,763 A	2/1992	Hathman
			5,092,846 A	3/1992	Nishijima
			5,125,897 A	6/1992	Quinn et al.
			5,129,885 A	7/1992	Green et al.
			5,141,498 A	8/1992	Christian
			5,149,327 A	9/1992	Oshiyama
			5,156,617 A	10/1992	Reid
			5,158,553 A	10/1992	Berry et al.
			5,159,921 A	11/1992	Hoover
			5,161,773 A	11/1992	Tower
			5,167,636 A	12/1992	Clement
			5,178,162 A	1/1993	Bose
			5,188,595 A	2/1993	Jacobi
			5,192,301 A	3/1993	Kamiya et al.
			5,197,955 A	3/1993	Stephens et al.
			5,207,656 A	5/1993	Kranys
			5,209,737 A	5/1993	Richartt
			5,211,370 A	5/1993	Powers
			5,211,633 A	5/1993	Strouder
			5,213,114 A	5/1993	Bailey, Jr.
			5,234,455 A	8/1993	Mulhollan
			5,242,409 A	9/1993	Buelna

(56)

References Cited

U.S. PATENT DOCUMENTS

5,248,304	A	9/1993	Vigdorich et al.	5,749,882	A	5/1998	Hart et al.
5,261,883	A	11/1993	Hood et al.	5,755,660	A	5/1998	Tyagi
5,263,922	A	11/1993	Sova et al.	5,769,783	A	6/1998	Fowler
5,269,763	A	12/1993	Boehmer	5,769,794	A	6/1998	Conlan et al.
5,269,772	A	12/1993	Wilk	5,782,812	A	7/1998	Hart et al.
D343,236	S	1/1994	Quigley et al.	5,795,290	A	8/1998	Bridges
5,279,575	A	1/1994	Sugarbaker	5,803,919	A	9/1998	Hart et al.
D346,022	S	4/1994	Quigley et al.	5,803,921	A	9/1998	Bonadio
5,299,582	A	4/1994	Potts	5,807,350	A	9/1998	Diaz
5,300,036	A	4/1994	Mueller	5,810,721	A	9/1998	Mueller et al.
5,308,336	A	5/1994	Hart et al.	5,813,409	A	9/1998	Leahy et al.
5,309,896	A	5/1994	Moll et al.	5,814,026	A	9/1998	Yoon
5,316,541	A	5/1994	Fischer	5,817,062	A	10/1998	Flom
5,320,611	A	6/1994	Bonutti	5,820,555	A	10/1998	Mueller, Jr. et al.
5,330,437	A	7/1994	Durman	5,832,925	A	11/1998	Rothrum
5,330,497	A	7/1994	Freitas	5,848,992	A	12/1998	Hart et al.
5,334,143	A	8/1994	Carroll	5,853,395	A	12/1998	Crook et al.
5,336,192	A	8/1994	Palestrant	5,865,728	A	2/1999	Moll et al.
5,342,315	A	8/1994	Rowe et al.	5,871,474	A	2/1999	Hermann et al.
5,342,385	A	8/1994	Norelli et al.	5,882,344	A	3/1999	Strouder
5,350,364	A	9/1994	Stephens et al.	5,899,208	A	5/1999	Bonadio
5,364,345	A	11/1994	Lowery et al.	5,904,703	A	5/1999	Gilson
5,366,478	A	11/1994	Brinkerhoff et al.	5,906,577	A	5/1999	Beane et al.
5,368,545	A	11/1994	Schaller et al.	5,916,232	A	6/1999	Hart
5,383,861	A	1/1995	Hempel	5,947,922	A	9/1999	MacLeod
5,385,553	A	1/1995	Hart et al.	5,951,467	A	9/1999	Picha et al.
5,391,153	A	2/1995	Haber et al.	5,957,913	A	9/1999	de la Torre et al.
5,391,156	A	2/1995	Hildwein et al.	5,964,781	A	10/1999	Mollenauer et al.
5,395,367	A	3/1995	Wilk	5,993,485	A	11/1999	Beckers
5,403,264	A	4/1995	Wohlers	5,994,450	A	11/1999	Pearce
5,407,433	A	4/1995	Loomas	5,997,515	A	12/1999	de la Torre et al.
5,423,848	A	6/1995	Washizuka et al.	6,024,736	A	2/2000	de la Torre et al.
5,429,609	A	7/1995	Yoon	6,025,067	A	2/2000	Fay
5,431,676	A	7/1995	Durbal	6,033,426	A	3/2000	Kaji
5,443,452	A	8/1995	Hart et al.	6,033,428	A	3/2000	Sardella
5,456,284	A	10/1995	Ryan	6,036,685	A	3/2000	Mueller
5,476,475	A	12/1995	Gadberry	6,042,573	A	3/2000	Lucey
5,480,410	A	1/1996	Cuschieri et al.	6,048,309	A	4/2000	Flom et al.
5,496,280	A	3/1996	Vandenbroeck	6,059,816	A	5/2000	Moenning
5,503,112	A	4/1996	Luhman	6,077,288	A	6/2000	Shimomura et al.
5,514,109	A	5/1996	Mollenauer et al.	6,099,506	A	8/2000	Macoviak et al.
5,514,133	A	5/1996	Golub et al.	6,110,154	A	8/2000	Shimomura et al.
5,520,632	A	5/1996	Leveen	6,123,689	A	9/2000	To
5,522,791	A	6/1996	Leyva	6,142,935	A	11/2000	Flom et al.
5,522,824	A	6/1996	Ashby	6,142,936	A	11/2000	Beane et al.
5,524,644	A	6/1996	Crook	6,149,642	A	11/2000	Gerhart et al.
5,526,536	A	6/1996	Cartmill	6,150,608	A	11/2000	Wambeke
5,545,179	A	8/1996	Williamson, IV	6,159,182	A	12/2000	Davis
5,562,632	A	10/1996	Davila	6,162,172	A	12/2000	Cosgrove et al.
5,562,688	A	10/1996	Riza	6,162,196	A	12/2000	Hart et al.
5,577,993	A	11/1996	Zhu et al.	6,162,206	A	12/2000	Bindokas
5,582,577	A	12/1996	Lund et al.	6,163,949	A	12/2000	Neuenschwander
5,584,850	A	12/1996	Hart et al.	6,164,279	A	12/2000	Tweedle
5,601,579	A	2/1997	Semertzides	6,171,282	B1	1/2001	Ragsdale
5,620,415	A	4/1997	Lucey	6,183,486	B1	2/2001	Snow et al.
5,632,979	A	5/1997	Goldberg	6,238,373	B1	5/2001	de la Torre et al.
5,634,911	A	6/1997	Hermann et al.	6,254,533	B1	7/2001	Fadem et al.
5,634,936	A	6/1997	Linden	6,254,534	B1	7/2001	Butler et al.
5,634,937	A	6/1997	Mollenauer et al.	6,258,065	B1	7/2001	Dennis
5,636,645	A	6/1997	Ou	6,315,770	B1	11/2001	de la Torre et al.
5,640,977	A	6/1997	Leahy et al.	6,319,246	B1	11/2001	de la Torre et al.
5,649,550	A	7/1997	Crook	6,322,541	B2	11/2001	West
5,653,705	A	8/1997	de la Torre et al.	6,328,730	B1	12/2001	Harkrider, Jr.
5,657,963	A	8/1997	Hinchliffe	6,346,074	B1	2/2002	Roth
5,658,272	A	8/1997	Hasson	6,382,211	B1	5/2002	Crook
5,658,306	A	8/1997	Kieturakis	6,420,475	B1	7/2002	Chen
5,672,168	A	9/1997	de la Torre et al.	6,440,063	B1	8/2002	Beane
5,685,854	A	11/1997	Green	6,450,983	B1	9/2002	Rambo
5,707,703	A	1/1998	Rothrum et al.	6,454,783	B1	9/2002	Piskun
5,709,664	A	1/1998	Vandenbroeck	6,464,686	B1	10/2002	O'Hara et al.
5,720,730	A	2/1998	Blake, III	6,485,435	B1	11/2002	Bakal
5,738,628	A	4/1998	Sierocuk et al.	6,485,467	B1	11/2002	Crook et al.
5,741,234	A	4/1998	Aboul-Hosn	6,488,620	B1	12/2002	Segermark et al.
5,741,298	A	4/1998	MacLeod	6,533,734	B1	3/2003	Corley, III et al.
5,743,884	A	4/1998	Hasson et al.	6,551,270	B1	4/2003	Bimbo et al.
				6,554,793	B1	4/2003	Pauker
				6,569,119	B1	5/2003	Haberland et al.
				6,578,577	B2	6/2003	Bonadio et al.
				6,582,364	B2	6/2003	Butler et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,589,167	B1	7/2003	Shimonmura	2004/0068232	A1	4/2004	Hart et al.
6,589,211	B1	7/2003	MacLeod	2004/0073090	A1	4/2004	Butler
6,607,504	B2	8/2003	Haarala	2004/0092795	A1	5/2004	Bonadio et al.
6,613,952	B2	9/2003	Rambo	2004/0092796	A1	5/2004	Butler et al.
6,623,426	B2	9/2003	Bonadio et al.	2004/0093018	A1	5/2004	Johnson
6,706,050	B1	3/2004	Giannadakis	2004/0097793	A1	5/2004	Butler et al.
6,714,298	B2	3/2004	Ryer	2004/0106942	A1	6/2004	Taylor
6,723,044	B2	4/2004	Pulford	2004/0143158	A1	7/2004	Hart et al.
6,793,621	B2	9/2004	Butler et al.	2004/0154624	A1	8/2004	Bonadio et al.
6,796,940	B2	9/2004	Bonadio et al.	2004/0215063	A1	10/2004	Bonadio et al.
6,797,765	B2	9/2004	Pearce	2004/0230161	A1	11/2004	Zeiner
6,814,078	B2	11/2004	Crook	2004/0249248	A1	12/2004	Bonadio et al.
6,814,700	B1	11/2004	Mueller et al.	2004/0260244	A1	12/2004	Piechowicz et al.
6,840,951	B2	1/2005	de la Torre et al.	2005/0020884	A1	1/2005	Heart et al.
6,846,287	B2	1/2005	Bonadio et al.	2005/0033246	A1	2/2005	Ahlberg
6,860,463	B2	3/2005	Hartley	2005/0059865	A1	3/2005	Kahle
6,866,861	B1	3/2005	Luhman	2005/0065475	A1	3/2005	Hart et al.
6,884,253	B1	4/2005	McFarlane	2005/0065543	A1	3/2005	Kahle
6,902,541	B2	6/2005	McNally et al.	2005/0090713	A1	4/2005	Gozales
6,908,430	B2	6/2005	Caldwell	2005/0090716	A1	4/2005	Bonadio et al.
6,916,331	B2	7/2005	Mollenauer et al.	2005/0090717	A1	4/2005	Bonadio et al.
6,936,037	B2	8/2005	Bubb	2005/0131349	A1	6/2005	Albrecht
6,939,296	B2	9/2005	Ewers	2005/0137609	A1	6/2005	Guiraudon
6,945,932	B1	9/2005	Caldwell et al.	2005/0148823	A1	7/2005	Vaugh et al.
6,958,037	B2	10/2005	Ewers	2005/0155611	A1	7/2005	Vaugh et al.
6,979,324	B2	12/2005	Bybordi	2005/0159647	A1	7/2005	Hart et al.
7,008,377	B2	3/2006	Beane	2005/0192483	A1	9/2005	Bonadio et al.
7,052,454	B2	5/2006	Taylor	2005/0192598	A1	9/2005	Johnson
7,081,089	B2	7/2006	Bonadio et al.	2005/0197537	A1	9/2005	Bonadio et al.
7,083,626	B2	8/2006	Hart et al.	2005/0203346	A1	9/2005	Bonadio et al.
7,112,185	B2	9/2006	Hart et al.	2005/0209510	A1	9/2005	Bonadio et al.
7,118,528	B1	10/2006	Piskun	2005/0222582	A1	10/2005	Wenchell
7,153,319	B1	12/2006	Haberland et al.	2005/0240082	A1	10/2005	Bonadio et al.
7,195,590	B2	3/2007	Butler et al.	2005/0241647	A1	11/2005	Nguyen
7,297,106	B2	11/2007	Yamada et al.	2005/0267419	A1	12/2005	Smith
7,300,399	B2	11/2007	Bonadio et al.	2005/0277946	A1	12/2005	Greenhalgh
7,344,547	B2	3/2008	Piskun	2005/0288558	A1	12/2005	Ewers
7,445,597	B2	11/2008	Butler et al.	2005/0288634	A1	12/2005	O' Herron
7,537,564	B2	5/2009	Bonadio et al.	2006/0020164	A1	1/2006	Butler et al.
7,540,839	B2	6/2009	Butler et al.	2006/0020241	A1	1/2006	Piskun et al.
7,559,893	B2	7/2009	Bonadio et al.	2006/0030755	A1	2/2006	Ewers et al.
7,749,415	B2	7/2010	Brustad et al.	2006/0041270	A1	2/2006	Lenker
7,753,901	B2	7/2010	Piskun et al.	2006/0047284	A1	3/2006	Gresham
7,837,612	B2	11/2010	Gill et al.	2006/0047293	A1	3/2006	Haberland et al.
7,867,164	B2	1/2011	Butler et al.	2006/0106402	A1	5/2006	McLucas
7,909,760	B2	3/2011	Albrecht et al.	2006/0149137	A1	7/2006	Pingleton et al.
7,998,068	B2	8/2011	Bonadio et al.	2006/0149306	A1	7/2006	Hart et al.
8,012,088	B2	9/2011	Butler et al.	2006/0161050	A1	7/2006	Butler et al.
8,021,296	B2	9/2011	Bonadio et al.	2006/0241651	A1	10/2006	Wilk
8,157,817	B2	4/2012	Bonadio et al.	2006/0247498	A1	11/2006	Bonadio et al.
8,187,178	B2	5/2012	Bonadio et al.	2006/0247499	A1	11/2006	Butler et al.
8,317,691	B2	11/2012	Bonadio et al.	2006/0247500	A1	11/2006	Voegel et al.
8,375,955	B2	2/2013	Desai et al.	2006/0247516	A1	11/2006	Hess et al.
8,518,024	B2	8/2013	Williams et al.	2006/0258899	A1	11/2006	Gill et al.
8,657,740	B2	2/2014	Bonadio et al.	2006/0264706	A1	11/2006	Piskun
8,734,336	B2	5/2014	Bonadio et al.	2007/0004968	A1	1/2007	Bonadio et al.
2001/0037053	A1	11/2001	Bonadio et al.	2007/0049966	A1	3/2007	Bonadio et al.
2001/0039430	A1	11/2001	Dubrul et al.	2007/0093695	A1	4/2007	Bonadio et al.
2001/0047188	A1	11/2001	Bonadio et al.	2007/0118175	A1	5/2007	Butler et al.
2002/0002324	A1	1/2002	Mcmanus	2007/0185387	A1	8/2007	Albrecht et al.
2002/0010389	A1	1/2002	Butler et al.	2007/0203398	A1	8/2007	Bonadio et al.
2002/0038077	A1	3/2002	de la Torre et al.	2007/0255219	A1	11/2007	Vaugh et al.
2002/0072762	A1	6/2002	Bonadio et al.	2007/0299387	A1	12/2007	Williams et al.
2002/0111536	A1	8/2002	Cuschieri et al.	2008/0027476	A1	1/2008	Piskun
2003/0028179	A1	2/2003	Piskun	2008/0097162	A1	4/2008	Bonadio et al.
2003/0078478	A1	4/2003	Bonadio et al.	2008/0097163	A1	4/2008	Butler et al.
2003/0139756	A1	7/2003	Brustad	2008/0255519	A1	10/2008	Piskun et al.
2003/0187376	A1	10/2003	Rambo	2008/0281161	A1	11/2008	Albrecht et al.
2003/0192553	A1	10/2003	Rambo	2008/0281162	A1	11/2008	Albrecht et al.
2003/0225392	A1	12/2003	McMichael	2009/0012477	A1	1/2009	Norton et al.
2003/0236549	A1	12/2003	Bonadio et al.	2009/0036745	A1	2/2009	Bonadio et al.
2004/0015185	A1	1/2004	Ewers et al.	2009/0069837	A1	3/2009	Bonadio et al.
2004/0024363	A1	2/2004	Goldberg	2009/0093683	A1	4/2009	Richard et al.
2004/0049099	A1	3/2004	Ewers et al.	2009/0149714	A1	6/2009	Bonadio
2004/0049100	A1	3/2004	Butler	2009/0187079	A1	7/2009	Albrecht et al.
				2009/0292176	A1	11/2009	Bonadio et al.
				2009/0326330	A1	12/2009	Bonadio et al.
				2010/0057121	A1	3/2010	Piskun et al.
				2010/0063362	A1	3/2010	Bonadio et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0063364	A1	3/2010	Bonadio et al.
2010/0081880	A1	4/2010	Widenhouse et al.
2010/0081881	A1	4/2010	Murray et al.
2010/0113886	A1	5/2010	Piskun et al.
2010/0204548	A1	8/2010	Bonadio et al.
2010/0217087	A1	8/2010	Bonadio et al.
2010/0274091	A1	10/2010	Rothstein et al.
2010/0274093	A1	10/2010	Shelton, IV
2010/0280326	A1	11/2010	Hess et al.
2011/0270195	A1	11/2011	Piskun
2012/0022333	A1	1/2012	Main et al.
2013/0245373	A1	9/2013	Okoniewski

FOREIGN PATENT DOCUMENTS

DE	296 00 939	6/1998
EP	0113520	7/1984
EP	0142262	5/1985
EP	0537768	4/1993
EP	0950376	10/1999
EP	1118657	7/2001
EP	1312318	5/2003
FR	1456623	9/1966
GB	1151993	5/1969
GB	1355611	6/1974
GB	1372491	10/1974
GB	1379772	1/1975
GB	1400808	7/1975
GB	1407023	9/1975
GB	1496696	12/1977
GB	2071502	9/1981
GB	2255019	10/1992
GB	2275420	8/1994
JP	10-108868	4/1998
JP	11-290327	10/1999
JP	2001-61850	3/2001
JP	2002-28163	1/2002
JP	2004-509659	4/2004
JP	2004-195037	7/2004
RU	1342485	1/1997
WO	WO 86/06272	11/1986
WO	WO 92/11880	7/1992

WO	WO 92/21292	12/1992
WO	WO 93/05740	4/1993
WO	WO 95/05207	2/1995
WO	WO 95/07056	3/1995
WO	WO 95/22289	8/1995
WO	WO 95/24864	9/1995
WO	WO 95/27445	10/1995
WO	WO 95/27468	10/1995
WO	WO 96/36283	11/1996
WO	WO 97/32514	9/1997
WO	WO 97/32515	9/1997
WO	WO 98/35614	8/1998
WO	WO 98/48724	11/1998
WO	WO 99/03416	1/1999
WO	WO 99/25268	5/1999
WO	WO 99/29250	6/1999
WO	WO 00/32116	6/2000
WO	WO 00/32117	6/2000
WO	WO 00/32119	6/2000
WO	WO 00/32120	6/2000
WO	WO 00/35356	6/2000
WO	WO 00/54675	9/2000
WO	WO 00/54676	9/2000
WO	WO 00/54677	9/2000
WO	WO 01/08563	2/2001
WO	WO 01/08581	2/2001
WO	WO 01/26558	4/2001
WO	WO 01/91652	12/2001
WO	WO 01/91653	12/2001
WO	WO 02/17800 A2	3/2002
WO	WO 02/34108 A2	5/2002
WO	WO 03/026512 A1	4/2003
WO	WO 03/034908 A3	5/2003
WO	WO 03/061480 A1	7/2003
WO	WO 03/103548 A1	12/2003
WO	WO 2004/026153 A1	4/2004
WO	WO 2004/030547 A1	4/2004
WO	WO 2005/009257 A2	2/2005
WO	WO 2005/034766 A2	4/2005
WO	WO 2005/089661	9/2005
WO	WO 2006/040748 A1	4/2006
WO	WO 2006/059318	8/2006
WO	WO 2008/121294 A1	10/2008
WO	WO 2009/035663 A2	3/2009
WO	WO 2014/144233 A1	9/2014






Fig.1

*Fig. 2*






Fig. 4













Fig. 5



















*Fig. 16*






Fig. 18






Fig. 19








Fig. 25




Fig. 26









Fig. 27









RETRACTOR

This application is a Continuation of Application Ser. No. 13/205,517, filed Aug. 8, 2011, now U.S. Pat. No. 8,986,202, which is a Continuation of Application Ser. No. 11/841,777, filed Aug. 20, 2007, now U.S. Pat. No. 8,012,088, which is a Continuation of Application Ser. No. 10/374,523, filed Feb. 27, 2003, Now U.S. Patent No. 7,445,597, which is a Continuation of Application Ser. No. 09/849,341, filed May 7, 2001, now U.S. Pat. No. 6,582,364, which is a Continuation of Application Ser. No. 09/688,138, filed Oct. 16, 2000, now U.S. Pat. No. 6,254,534, all of which are incorporated herein by reference in their entireties.

INTRODUCTION

The invention relates to a retractor. In particular the invention relates to a retractor for retracting the margins of an incision or a natural bodily orifice to provide maximum exposure of an organ or body structures for examination and/or access for surgical procedures, while also providing protection for the exposed sides of the incised tissue.

Various retractors are known. However in general known retractors are difficult and cumbersome to use, and/or are relatively expensive. In addition known retractors are limited to use with a particular size of incision and a particular patient anatomy.

This invention is directed towards providing an improved wound retractor which will overcome at least some of these problems, and in addition provide a means of wound protection during a surgical procedure.

STATEMENTS OF INVENTION

According to the invention there is provided a surgical wound retractor comprising:

a distal anchoring member for insertion into a wound opening;

a connecting means having an inner wound engaging portion and an outer portion, the wound engaging portion being mounted to the distal anchoring member, the connecting means having an insertion configuration in which the inner wound engaging portion has a reduced radial dimension and a retracting configuration;

an external guide means for the outer portion of the connecting means;

the external guide means being movable relative to the connecting means to shorten the axial extent of the connecting means and thereby bias the wound engaging portion of the connecting member into the retracting configuration to retract the wound opening laterally; and external anchoring means for anchoring the connecting means to maintain retraction of the opening.

In one preferred embodiment of the invention at least the inner wound engaging portion of the connecting means comprises a sleeve for extending around the wound opening to protect the opening.

In one embodiment the outer portion of the connecting means comprises a sleeve extension of the inner wound engaging portion of the connecting means.

Preferably the connecting means comprises a generally cylindrical sleeve.

In a preferred embodiment the guide means comprises an annular ring means. The annular ring means preferably comprises inner and outer ring parts between which the connecting means is led. In a preferred embodiment the outer ring part includes the anchor means for anchoring the connecting

means. In one arrangement the anchor means comprises anchor formations on the outer ring to which the connecting means is attached on retraction of the opening.

Preferably the inner ring means defines a projection for location in a complementary recess of the outer ring with the connecting means located therebetween.

In one embodiment the inner ring is a relatively loose fit in the recess of the outer ring part.

Preferably at least portion of one of the ring parts is movable from a rest position in which the connecting member is substantially clamped between the ring parts to a release position in which at least portion of the connecting member is movable relative to the ring parts. Ideally only portion of the connecting member is movable relative to the ring parts in the release position.

In another embodiment the inner ring is a relatively tight fit in the outer ring part to grip the connecting member therebetween.

In one aspect of the invention the outer ring part comprises a plurality of interconnected segments which are independently movable to facilitate localised release of the connecting member for adjusting of the retraction force applied at the opening. The ring part or segment thereof is preferably manually manipulable between the clamped rest position and the release position.

In one embodiment of the invention the connecting means includes a proximal reinforcing means for engagement with the external anchoring means. Ideally the proximal reinforcing means is a proximal ring.

Preferably the distal anchoring means is of resilient material. Typically the distal anchoring means is an O-ring.

Preferably at least an outer surface of the guide means which engages with the connecting means is of a material with a low coefficient of friction such as polytetrafluoroethylene.

In a particularly preferred embodiment the retractor includes a platform for attachment of another device to the retractor.

In an especially preferred arrangement one of the ring parts defines a platform for attachment of another device to the retractor.

In another aspect the invention provides a method for retracting a wound opening using a surgical wound retractor comprising a distal anchoring member, a connecting means having a wound engaging portion mounted to the distal anchoring member and an outer portion, an external guide means for the outer portion of the connecting means and an external anchoring means; the method comprising the steps:

positioning the distal anchoring member to be retained inside a wound opening with the connecting means extending; outwardly therefrom through the opening;

moving the external guide means relative to the outer portion of the connecting means to shorten the axial extent of the connecting means and thereby bias the wound engaging portion into a retracting configuration to retract the wound opening; and

anchoring the connecting means to maintain retraction of the wound opening.

Preferably the method includes the steps of moving the external guide means relative to the outer portion of the connecting means to partially retract the wound opening, gripping the outer portion of the connecting means and pulling it relative to the guide means to fully retract the wound opening.

In one embodiment the method includes the steps of:

(a) gripping a local section of the outer portion of the connecting means while the remaining section of the outer portion of the connecting means is anchored,

3

- (b) pulling the local section to increase the retraction at a local area of the wound opening, and
- (c) anchoring the local section of the connecting means.

Ideally the method includes repeating steps (a) to (c) for other local sections of the outer portion of the connecting means.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more clearly understood from the following description thereof given by way of example only with reference to the accompanying drawings, in which:

FIG. 1 is an exploded view of a wound retractor according to the invention;

FIG. 2 is a perspective view of the retractor of FIG. 1 assembled;

FIG. 3 is a side cross sectional view of the assembled retractor of FIG. 2;

FIG. 4 is a perspective view of an unretracted wound opening;

FIG. 5 is a perspective view illustrating insertion of part of the retractor of FIG. 2 into the wound opening;

FIG. 6 is a side cross sectional view of the retractor of FIG. 2 after insertion;

FIG. 7 is a plan view of the retractor of FIG. 2 after insertion;

FIGS. 8(a) and 8(b) are side cross sectional views illustrating lateral retraction of the wound opening using the retractor of FIG. 2;

FIG. 9 is a side cross sectional view of the retractor of FIG. 2 after lateral retraction of the wound opening;

FIG. 10 is a plan view of the retractor of FIG. 2 after lateral retraction of the wound opening;

FIG. 11 is a plan view of a part of a guide means of the retractor of FIG. 2;

FIG. 12 is a side view of the part of FIG. 11;

FIG. 13 is a cross sectional view along the line A-A in FIG. 11;

FIG. 14 is a cross sectional view of part of another wound retractor according to the invention;

FIG. 15 is a cross sectional view of the retractor of FIG. 14, in use;

FIG. 16 is an exploded view of parts of another wound retractor according to the invention;

FIG. 17 is a perspective view of the wound retractor of FIG. 16 assembled;

FIGS. 18 and 19 are perspective cut-away views of the retractor of FIG. 17 in different positions;

FIG. 20 is a schematic plan view illustrating manipulation of a part of the retractor of FIGS. 17 to 19;

FIG. 21 is a side cross sectional view of the retractor part in the configuration of FIG. 20;

FIG. 22 is a schematic plan view of the retractor part in a release position;

FIG. 23 is a side cross sectional view of the retractor part in the configuration of FIG. 22;

FIG. 24 is a perspective view of a hand access device for use with a wound retractor according to the invention;

FIG. 25 is a side cross sectional view of the retractor of FIG. 2 with the hand access device of FIG. 24 in position;

FIG. 26 is a perspective view of a drape for use with a wound retractor according to the invention;

FIG. 27 is a side cross sectional view of the retractor of FIG. 2 with the drape of FIG. 26 in position;

FIG. 28(a) is a perspective view of a form retaining device in a pliable state for use with a wound retractor according to the invention;

4

FIG. 28(b) is a perspective view of the form retaining device of FIG. 28(a) in a stiff state;

FIG. 29 is a side cross sectional view of the retractor of FIG. 2 with the stiffened form retaining device of FIG. 28(b) in position;

FIG. 30 is an exploded view of the form retaining device of FIG. 28 and a clamp;

FIG. 31 is a side view of the form retaining device of FIG. 28 and the clamp of FIG. 31; and

FIG. 32 is a side cross sectional view of the retractor of FIG. 2 with the form retaining device of FIG. 28 and the clamp of FIG. 30 in position.

DETAILED DESCRIPTION

Referring to FIGS. 1 to 13 there is illustrated a wound retractor 101 according to the invention, which in the case illustrated is used to retract the margins of a wound such as an abdominal wound opening 103, as illustrated in FIG. 4.

The reactor 101 comprises a distal anchoring member, in this case in the form of a resilient inner O-ring 105, for insertion into the wound opening 103, and a connecting means, in this case in the form of an elastomeric sleeve 106 which is substantially cylindrical. The sleeve 106 has an inner wound engaging portion and an outer portion, and the wound engaging portion is attached to the inner O-ring 105. The sleeve has an insertion configuration in which the inner wound engaging portion has a reduced radial dimension and a retracting configuration to retract the wound opening 103 laterally.

An external guide means is provided for the outer portion of the sleeve 106, and in this case the guide means comprises an inner ring part 110 and an outer ring part 111 between which the sleeve 106 is led. The retractor 101 includes external anchoring means for anchoring the sleeve 106 to maintain retraction of the wound opening 103, and in this case the anchoring means is provided by a plurality of anchor formations 120 on the outer surface of the outer ring part 111 (FIG. 2), the formations 120 extending radially outwardly to define hooks.

The outer ring part 111 is of the same annular shape as the inner ring part 110 but has a larger diameter and a recess 116. The inner ring part 110 is of a relatively stiff material and mates with the outer ring part 111 in the recess 116 to slidably retain the sleeve 106 therebetween, as illustrated in FIG. 3. In this case the ring parts 110, 111 are a relatively loose fit to facilitate movement of the ring parts 110, 111 relative to the sleeve 106 to shorten the axial extent of the sleeve 106 and thereby bias the wound engaging portion into the retracting configuration to retract the wound opening 103 laterally.

The ring parts 110, 111 are of a material with a low coefficient of friction such as Polytetrafluoroethylene (PTFE). PTFE is a tough, non-resilient material of moderate tensile strength and with excellent lubricity.

The retractor 101 also includes a proximal reinforcing means for engagement with the anchor formations 120, and in this case the reinforcing means is provided by a resilient outer O-ring 109 of a material which is flexible relative to the inner O-ring 105. The outer O-ring 109 is attached to the proximal end of the sleeve 106, the rings 105, 109 helping to maintain the open shape of the sleeve 106 at its extremities (FIG. 2).

In use the inner O-ring 105 and the sleeve 106 are squeezed into the insertion configuration for insertion of the inner O-ring 105 into the wound opening 103 (FIG. 5). The inner O-ring 105 is of a polymeric material which facilitates scrunching up of the inner O-ring 105 into a low-profile, elongate shape, as illustrated in FIG. 5, to facilitate ease of

use. On release of the inner O-ring **105**, the resilient O-ring **105** returns to its normal 0-shape overlapping an inner edge of the wound opening **103** to safely anchor the retractor **101** in the wound, as illustrated in FIG. 6. As may be seen from FIGS. 6 and 7, after insertion of the inner O-ring **105**, the wound opening **103** is substantially closed and the sleeve **106** is in a wrinkled compressed configuration.

The sleeve **106** is then pulled while pushing the ring parts **110**, **111** against the tissue surrounding the wound opening **103**, as illustrated in FIG. 8(a), to shorten the axial extent of the sleeve **106** and thereby bias the wound engaging portion into the retracting configuration to retract laterally the right-hand side (as viewed in FIG. 8(a)) of the wound opening **103**. The right-hand side of the outer O-ring **109** is hooked around the formations **120** to maintain the right-hand side of the wound opening **103** retracted (FIG. 8(b)). The left-hand side of the sleeve **106** is then pulled while pushing the ring parts **110**, **111** to retract laterally the left-hand side of the wound opening **103**, as illustrated in FIG. 8(b). The left-hand side of the outer O-ring **109** is then hooked around the formations **120** to maintain the entire wound opening **103** fully retracted, as illustrated in FIGS. 9 and 10.

The separate formations **120** and the configuration of the wound retractor **101** generally allow the sleeve **106** to be readily manipulated locally as illustrated in FIGS. 8(a) and 8(b) to provide an optimised retraction, force. Thus, the manipulation is not simply limited to a single vertical axis but can be carried out in several different directions by pulling of the sleeve **106**, and localised hooking of the outer O-ring **109** to the appropriate formation **120**. In this way the retractor can be tailored to a particular application.

The recess **116** against which the sleeve **106** is slidably retained by the inner ring part **110** is C-shaped with an extended upper lip **117**, as may be seen in FIG. 13. The upper lip **117** maintains the inner ring part **110** safely within the recess **116** regardless of the pulling direction or tensile pulling force exerted on the sleeve **106**. It is preferable to pull the sleeve **106** in a non-vertical direction and to perform localised hooking of the outer O-ring **109**, and the extended upper lip **117** encourages non-vertical pulling of the sleeve **106**.

The elastomeric sleeve **106** lines the side of the retracted wound opening **103**, as illustrated in FIG. 9, and thus acts both as a means of wound retraction and wound protection.

The surgical wound retractor is of simple construction, is easy to use and can be manufactured inexpensively to provide a disposable unit.

A single wound retractor according to the invention may be used for a wide range of incision sizes and to achieve a range of different localised retraction forces which are required to accommodate the incision, the patient anatomy and the surgical procedure to be performed. In the retractor of FIGS. 1 to 10 the sleeve **106** is a relatively tight fit between the outer and inner guide ring parts **110**, **111**. It is also possible to configure the outer and inner ring parts **110**, **111** so that the inner ring part **110** is a relatively looser fit in the outer part **111**. In this case the guide means comprises an outer ring part or other annular shape within which slides a second component. The second component is of the same annular shape as the outer ring part but with a lesser diameter and has an exterior compartmental recess designed so that the outer ring part fits loosely around the second component and both can easily slide relative to each other. The components fit loosely together so that an elastomeric sleeve can fit in the gap between them and slide therein. Such an arrangement is illustrated in FIGS. 14 and 15. On pulling of a local area of the sleeve **106** as indicated in FIG. 15 the inner ring part **110** moves to an appropriate side clamping the sleeve **106** at that

opposite side while allowing local manipulation of the gripped section of sleeve allowing the local retraction force at the gripped side to be optimised prior to anchoring of the sleeve at that side. This procedure may be repeated at other local regions of the sleeve **106**.

Referring to FIGS. 16 to 23 there is illustrated another wound retractor **150** according to the invention which is similar to the wound retractor **101** described with reference to FIGS. 1 to 13 and like parts are assigned the same reference numerals in FIGS. 16 to 23.

In this case the guide means comprises the inner ring part **110** and an outer PTFE ring part **151** configured so that the outer ring part **151** engages the inner ring part **110** at a plurality of discrete points circumferentially spaced around the outer ring part **151** to clamp the sleeve **106** between the inner and outer ring parts **110**, **151** at each discrete point. The outer ring part **151** comprises a plurality of interconnected segments **155** circumferentially spaced around the outer ring part **151** which press on the inner ring part **110** to clamp the sleeve **106** and are independently movable to facilitate localised release of the sleeve **106** for adjustment of the retraction force. Cut-out T-slots **156** are provided between the segments **155** and a main body **158** of the outer ring part **151**, and handles **160** project radially outwardly of the main body **158** of the outer ring part **151** intermediate the segments **155**.

In use, adjacent handles **160** are manually gripped as illustrated in FIG. 20 to apply a release force in the direction of arrows A which in turn pulls the local segment **155** in the direction of arrow B from a rest position damping the sleeve **106** (FIGS. 20 and 21) to a release position (FIGS. 22 and 23) in which the sleeve **106** is readily pulled and manipulated locally. By releasing the clamp between the inner ring part **110** and the segment **155** the elastomeric sleeve **106** is readily slid from one position to another. This arrangement is particularly advantageous to facilitate local manipulation of the retraction force.

In general, the wound retractor **150** according to the invention is employed by inserting the inner O-ring **105** into a wound opening **103** and pulling the sleeve **106** so that the inner O-ring **105** lies flat against the interior anatomical surface. The inner O-ring **105** anchors the retractor **150** in the wound and prevents the elastomeric sleeve **106** from slipping out of the wound opening **103**. The guide means clamp is then released by squeezing handles **160** and the ring parts **110**, **151** are slid down the elastomeric sleeve **106** until they come into contact with the exterior anatomical surface. Retraction is achieved by pulling the sleeve **106** to shorten the distance between the inner O-ring **105** and the ring parts **110**, **151** and thereby displace the elastomeric sleeve **106** laterally and with it the margins of the wound opening **103**. The elastomeric sleeve **106** is anchored to maintain retraction of the wound opening **103** by releasing the handles **160** of the outer ring part **151** to clamp the sleeve **106**.

The wound retractors according to the invention also provides a platform on which a wide range of devices may be mounted. In one case the platform is provided by an inner projection part of the inner ring part **110** on which a ring part **171** with a complementary recess **172** may be easily fitted somewhat in the manner of a snap-type engagement. Various devices may be provided with such a ring part **171**. For example, as illustrated in FIGS. 24 and 25 the device may be a hand access device **175** for use in laparoscopic surgery. Alternatively the device may be a drape **180** (FIGS. 26 and 27) or a form retaining device **185** which is manipulated to the form of, for example, an organ **187** to be held back and from

which air is then evacuated along an evacuation line **186** to retain the desired organ holding configuration (FIGS. **28** and **29**).

The platform may alternatively be provided by a clamp **200** as illustrated in FIGS. **30** to **32**. The clamp **200** comprises an upper jaw **201**, a lower jaw **202**, a clip **203** and an arm **204**.

The clamp **200** is assembled by screwing the clip **203** to the base of the lower jaw **202**, sliding the upper jaw **201** over the lower jaw **202** to engage the male projecting parts **208** within the corresponding female recesses **209** and extending the arm **204** through the open mouth **207** between the upper and lower jaws **201**, **202**. A plurality of teeth **205** are provided on the arm **204**, the teeth **205** being sized to project upwardly through a recess **206** in the upper jaw **201** when the arm **204** is within the open mouth **207**. The teeth **205**, as shown more clearly in FIG. **31**, are shaped such that the arm **204** may be pulled back through the open mouth **207** in a ratchet-type arrangement but cannot be pushed forward again. A suitable material for the clamp components **201**, **202**, **203**, **204** is spring steel.

Various devices may be attached to the free end of the arm **204**, such as the form retaining device **185**, as illustrated in FIG. **30**. In use the clip **203** is securely fixed to the wound retractor **101** by a snap-fit arrangement with the form retaining device **185** extending into the wound opening **103**, as illustrated in FIG. **31**. The form retaining device **185** is then ratcheted laterally across the wound opening **103** to retract, for example, an internal organ **220**. The ratchet configuration of the clamp **200** and the rigidity of the form retaining device **185** ensure that the internal organ **220** is securely maintained in a desired position.

It will be appreciated that any of the embodiments of the wound retractor according to the invention may be used as a platform on which to mount other devices for use in various surgical procedures. Such devices may include: a capping device to cover the incision site or orifice; a hand-access device to allow the surgical procedure to be converted from an open procedure into a hand-assisted laparoscopic procedure; an instrument port for the insertion of instruments; a trocar for use in laparoscopic surgery; an internal organ retractor to assist in the displacement of internal structures from the operative field; or an illuminating means to deliver illumination to an area shaded from the theatre lights. It will be clear to those skilled in the art that the enhancements are not limited to the brief list mentioned here.

The wound retractor may be constructed in other annular shapes. For example the distal and proximal rings attached to the elastomeric sleeve may be oval or elliptical instead of circular.

The retractor may be used to retract and protect the margins of a natural bodily orifice such as the anus or vagina, or can be used to retract and protect the edges of a man-made stoma such as is created for tracheostomy or following gastrointestinal surgery.

The invention is not limited to the embodiments hereinbefore described which may be varied in both construction and detail.

The invention claimed is:

1. A medical device, comprising:

a wound protector, including:

a proximal ring,
a distal ring, and

a sleeve extending between the proximal ring and the distal ring, wherein the distal ring and a distal portion of the sleeve are configured for insertion into an incision, and the proximal ring and a proximal portion of the sleeve are configured for positioning outside of the incision; and

a proximal assembly coupled to the proximal ring, the proximal assembly including:

an outer member coupled to the proximal ring,

an inner member, wherein at least part of the inner member is received by the outer member, and the inner member slidably engages the outer member, and

an access portion providing a passageway through the proximal assembly.

2. The medical device of claim 1, wherein the outer member has an inner circumferential portion, the inner member has an outer circumferential portion, and the inner circumferential portion slidably engages the outer circumferential portion.

3. The medical device of claim 1, wherein one of the inner member and the outer member includes a recess, and the other of the inner member and the outer member includes a portion that protrudes into the recess.

4. The medical device of claim 1, wherein the outer member is annular.

5. The medical device of claim 1, wherein the inner member is annular.

6. The medical device of claim 1, wherein the access portion includes a cylindrical port.

7. The medical device of claim 1, wherein the access portion extends proximally from a proximal surface of the inner member.

8. The medical device of claim 7, wherein a proximal end of the access portion includes a proximal opening.

9. The medical device of claim 8, wherein the access portion extends distally from a distal surface of the inner member.

10. The medical device of claim 9, wherein a distal end of the access portion includes a distal opening.

11. The medical device of claim 1, wherein a longitudinal axis of the access portion is coaxial with a longitudinal axis of the wound protector.

12. A medical device, comprising:

a wound protector, including:

a proximal ring,

a distal ring, and

a sleeve extending between the proximal ring and the distal ring, wherein the distal ring and a distal portion of the sleeve are configured for insertion into an incision, and the proximal ring and a proximal portion of the sleeve are configured for positioning outside of the incision; and

a proximal assembly coupled to the proximal ring, the proximal assembly including:

a base coupled to the proximal ring, the base having a proximal surface and a distal surface, and

an access portion configured to provide passage through the base, wherein the access portion extends proximally from the proximal surface of the base, the access portion has a proximal end with a proximal aperture, and the proximal aperture is spaced in a proximal direction from the proximal surface of the base.

13. The medical device of claim 12, wherein the access portion has a central passageway in fluid communication with the proximal aperture.

14. The medical device of claim 12, wherein the base is coupled to the proximal ring by an annular proximal receiver.

15. The medical device of claim 14, wherein the base includes one of a protrusion and a recess, the proximal receiver includes the other of the protrusion and the recess, and the protrusion is received by the recess.

9

16. The medical device of claim 15, wherein the protrusion and the recess are configured for snap-fit engagement.

17. The medical device of claim 12, wherein a longitudinal axis of the access portion is coaxial with a longitudinal axis of the wound protector.

18. A method of retracting and sealing an incision for laparoscopic procedures, comprising:

making an incision in a patient;

positioning a wound retractor system proximate the incision, the wound retractor system including:

a distal ring,

a proximal ring,

a sleeve extending between the distal ring and the proximal ring and fixedly coupled to both the proximal ring and the distal ring, and

a proximal receiver including a recess;

10

inserting the distal ring through the incision such that the sleeve extends through the incision and the proximal ring is located outside of the incision;

retracting the incision with the sleeve;

coupling a portion of the proximal ring to the recess of the proximal receiver so that the receiver restricts movement of the proximal ring and an actual length of the sleeve between the distal ring and the proximal receiver is shortened; and

coupling an access device to the proximal receiver.

19. The method of claim 18, wherein the coupling of the access device to the proximal receiver includes a coupling via a snap-fit engagement.

20. The method of claim 18, wherein retracting the incision includes inverting at least a portion of the sleeve prior to coupling the portion of the proximal ring to the recess of the proximal receiver.

* * * * *

专利名称(译)	牵开器		
公开(公告)号	US9277908	公开(公告)日	2016-03-08
申请号	US14/634159	申请日	2015-02-27
[标]申请(专利权)人(译)	阿特波斯有限公司		
申请(专利权)人(译)	阿特洛波斯有限公司		
当前申请(专利权)人(译)	阿特洛波斯有限公司		
[标]发明人	BUTLER JOHN YOUNG DEREK WILLIAM GILL AOIBHEANN REID ALAN BONADIO FRANK		
发明人	BUTLER, JOHN YOUNG, DEREK WILLIAM GILL, AOIBHEANN REID, ALAN BONADIO, FRANK		
IPC分类号	A61B17/02 A61B1/32 A61B17/34 A61B17/00		
CPC分类号	A61B17/0218 A61B1/32 A61B17/0206 A61B17/0293 A61B17/3423 A61B90/50 A61B17/3421 A61B17/3431 A61B2017/00557 A61B2017/0225 A61B2017/3429 A61B2017/3488 A61B2017/3492 A61B2017/00265 A61B2017/3419		
优先权	19990861 1999-10-14 IE 19991053 1999-12-16 IE 2000650010 2000-02-18 EP 11/841777 2011-09-06 US 10/374523 2008-11-04 US 09/849341 2003-06-24 US 09/688138 2001-07-03 US		
其他公开文献	US20150272563A1		
外部链接	Espacenet USPTO		

摘要(译)

用于缩回伤口开口边缘 (103) 的牵开器 (101) 包括附着于a的内锚定O形圈 (105) 远端的圆柱形套管 (106) 和连接到套管近端的加强O形环 (109) (106) 。套管 (106) 在内环部分 (110) 和外环部分 (116) 之间引导 (111 的) 。外环部分 (111) 具有锚定结构 (120) ，套管的近端 (106) 附着在锚固结构上以固定袖子 (106) 。为了缩回伤口 (103) ，拉动套管 (106) ，同时引导环 (110,111) 移动抵靠组织围绕伤口开口 (103) 。这将内部O形环 (105) 拉向与伤口开口相邻的组织内部 (103) ，并缩回伤口开口 (103) 。套筒 (106) 被局部操纵以获得最大的收缩效率。

