



US009700296B2

(12) **United States Patent**
Bonadio et al.

(10) **Patent No.:** **US 9,700,296 B2**
(45) **Date of Patent:** ***Jul. 11, 2017**

- (54) **WOUND RETRACTOR DEVICE**
- (71) Applicant: **Atropos Limited**, County Wicklow (IE)
- (72) Inventors: **Frank Bonadio**, County Wicklow (IE);
John Butler, County Mayo (IE);
Trevor Vaughn, County Offaly (IE);
Shane J. MacNally, County Wicklow (IE); **Alan Reid**, Dublin (IE)
- (73) Assignee: **Atropos Limited**, County Wicklow (IE)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/753,796**

(22) Filed: **Jun. 29, 2015**

(65) **Prior Publication Data**

US 2016/0022257 A1 Jan. 28, 2016

Related U.S. Application Data

- (63) Continuation of application No. 13/655,286, filed on Oct. 18, 2012, now Pat. No. 9,095,300, which is a
(Continued)

(30) **Foreign Application Priority Data**

Dec. 1, 1998	(IE)	980997
Feb. 15, 1999	(IE)	990111

(Continued)

- (51) **Int. Cl.**
A61B 1/32 (2006.01)
A61B 17/02 (2006.01)
(Continued)

- (52) **U.S. Cl.**
CPC **A61B 17/0293** (2013.01); **A61B 1/32** (2013.01); **A61B 17/3423** (2013.01);
(Continued)

- (58) **Field of Classification Search**
CPC A61B 17/3423; A61B 17/3431; A61B 17/0218; A61B 17/0469; A61B 17/0293
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,157,202 A	10/1915	McLeland
1,598,284 A	8/1926	Kinney

(Continued)

FOREIGN PATENT DOCUMENTS

DE	37 39 532	12/1988
DE	37 37 121	5/1989

(Continued)

OTHER PUBLICATIONS

Kagaya, "Laparoscopic cholecystectomy via two ports, using the "Twin-Port" system", J. Hepatobiliary Pancreat Surg (2001) 8:76-80.


Primary Examiner — Anu Ramana

(74) *Attorney, Agent, or Firm* — Bookoff McAndrews, PLLC

(57) **ABSTRACT**

A wound protector and retractor device **1** comprises a sleeve **2**, a distal member provided by a distal ring **3** of resilient material and a proximal member provided by a proximal ring **4**. The sleeve **2** is led around the ring **3** and is free to move axially relative to the distal ring **3** somewhat in the manner of a pulley. The proximal ring **4** is fixed to the sleeve **2**, in this case at the proximal inner end thereof. The sleeve **2** terminates in a handle or gripping portion which is reinforced by a gripping ring **15**. The sleeve extends from the proximal ring **4** and the distal ring **3** is contained between inner and outer layers **2a**, **2b** of the sleeve **2**. The resilient distal ring **3** is scrunched up and inserted through the incision **6**. The sleeve **2** is then pulled upwardly. On pulling of the sleeve **2** upwardly the outer layer **2b** is pulled up while the inner layer **2a** is drawn around the proximal ring **3**. This

(Continued)



results in shortening the axial extent between the proximal ring 4 and the distal ring 3, tensioning the sleeve and applying a retraction force to the margins of the incision 6. As the incision is being retracted the margins are also protected by the sleeve. On retraction, an access port is provided, for example for a surgeon to insert his hand and/or an instrument to perform a procedure. The device may be used as a retractor in open surgery or as a base for a valve/seal to allow it to be used in hand assisted laparoscopic surgery or for instrument access or hand access generally.

20 Claims, 52 Drawing Sheets

Related U.S. Application Data

continuation of application No. 12/426,438, filed on Apr. 20, 2009, now Pat. No. 8,317,691, which is a continuation of application No. 10/678,653, filed on Oct. 6, 2003, now Pat. No. 7,559,893, which is a continuation-in-part of application No. 10/133,979, filed on Apr. 29, 2002, now Pat. No. 6,846,287, which is a continuation of application No. 09/801,826, filed on Mar. 9, 2001, now abandoned, which is a continuation of application No. PCT/IE99/00122, filed on Dec. 1, 1999, said application No. 10/678,653 is a continuation-in-part of application No. 10/374,523, filed on Feb. 27, 2003, now Pat. No. 7,445,597, which is a continuation of application No. 09/849,341, filed on May 7, 2001, now Pat. No. 6,582,364, which is a continuation of application No. 09/688,138, filed on Oct. 16, 2000, now Pat. No. 6,254,534.

(60) Provisional application No. 60/415,780, filed on Oct. 4, 2002, provisional application No. 60/428,215, filed on Nov. 22, 2002, provisional application No. 60/490,909, filed on Jul. 30, 2003.

Foreign Application Priority Data

Oct. 14, 1999 (IE) 990861
 Dec. 16, 1999 (IE) 991053
 Feb. 18, 2000 (EP) 00650010

(51) **Int. Cl.**

A61B 17/34 (2006.01)
A61B 17/00 (2006.01)

(52) **U.S. Cl.**

CPC *A61B 17/3498* (2013.01); *A61B 17/3431* (2013.01); *A61B 2017/00557* (2013.01); *A61B 2017/0212* (2013.01); *A61B 2017/0225* (2013.01); *A61B 2017/3443* (2013.01); *A61B 2017/3482* (2013.01); *A61B 2017/3484* (2013.01); *A61B 2017/3492* (2013.01)

(58) **Field of Classification Search**

USPC 600/184, 201–208; 128/846, 849, 850, 128/852
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,810,466 A 6/1931 Deutsch
 2,219,564 A 10/1940 Reyniers
 2,305,289 A 12/1942 Coburg
 2,695,608 A 11/1954 Gibbon

2,835,253 A 5/1958 Borgeson
 2,853,075 A 10/1958 Hoffman
 3,039,468 A 6/1962 Price
 3,111,943 A 11/1963 Orndorff
 3,244,169 A 4/1966 Baxter
 3,253,594 A 5/1966 Matthews et al.
 3,313,299 A 4/1967 Spademan
 3,329,390 A 7/1967 Hulsey
 3,332,417 A 7/1967 Blanford et al.
 3,347,226 A 10/1967 Harrower
 3,347,227 A 10/1967 Harrower
 3,397,692 A 8/1968 Creager, Jr. et al.
 3,402,710 A 9/1968 Paleschuck
 3,447,533 A 6/1969 Spicer
 3,522,800 A 8/1970 Lesser
 3,523,534 A 8/1970 Nolan
 3,570,475 A 3/1971 Weinstein
 3,592,198 A 7/1971 Evans
 3,656,485 A 4/1972 Robertson
 3,685,786 A 8/1972 Woodson
 3,717,151 A 2/1973 Collett
 3,729,006 A 4/1973 Wilder et al.
 3,782,370 A 1/1974 McDonald
 3,797,478 A 3/1974 Walsh et al.
 3,807,393 A 4/1974 McDonald
 3,828,764 A 8/1974 Jones
 3,841,332 A 10/1974 Treacle
 3,853,126 A 12/1974 Schulte
 3,853,127 A 12/1974 Spademan
 3,856,021 A 12/1974 Macintosh
 3,907,389 A 9/1975 Cox et al.
 3,915,171 A 10/1975 Shermeta
 3,965,890 A 6/1976 Gauthier
 3,996,623 A 12/1976 Kaster
 3,998,217 A 12/1976 Trumbull et al.
 4,000,739 A 1/1977 Stevens
 4,016,884 A 4/1977 Kwan-Gett
 4,024,872 A 5/1977 Muldoon
 4,030,500 A 6/1977 Ronnquist
 4,083,370 A 4/1978 Taylor
 4,096,853 A 6/1978 Weigand
 4,112,932 A 9/1978 Chiulli
 4,130,113 A 12/1978 Graham
 4,177,814 A 12/1979 Knepshield
 4,188,945 A 2/1980 Wenander
 4,217,664 A 8/1980 Faso
 4,228,792 A 10/1980 Rhys-Davies
 4,239,036 A 12/1980 Krieger
 4,240,411 A 12/1980 Hosono
 4,253,201 A 3/1981 Ross et al.
 4,306,562 A 12/1981 Osborne
 4,321,915 A 3/1982 Leighton
 4,331,138 A 5/1982 Jessen
 4,338,934 A 7/1982 Spademan
 4,338,937 A 7/1982 Lehrman
 4,367,728 A 1/1983 Mutke
 4,399,816 A 8/1983 Spangler
 4,411,659 A 10/1983 Jensen et al.
 4,421,296 A 12/1983 Stephens
 4,424,833 A 1/1984 Spector
 4,428,364 A 1/1984 Bartolo
 4,430,081 A 2/1984 Timmermans
 4,434,791 A 3/1984 Darnell
 4,436,519 A 3/1984 O'Neill
 4,485,490 A 12/1984 Akers et al.
 4,488,877 A 12/1984 Klein
 4,543,088 A 9/1985 Bootman
 4,550,713 A 11/1985 Hyman
 4,553,537 A 11/1985 Rosenberg
 4,601,710 A 7/1986 Moll
 4,610,665 A 9/1986 Matsumoto
 4,626,245 A 12/1986 Weinstein
 4,634,424 A 1/1987 O'Boyle
 4,649,904 A 3/1987 Krauter
 4,654,030 A 3/1987 Moll et al.
 4,673,393 A 6/1987 Suzuki et al.
 4,673,394 A 6/1987 Fenton
 4,755,170 A 7/1988 Golden
 4,776,843 A 10/1988 Martinez et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

4,777,943 A	10/1988	Chvapil	5,403,264 A	4/1995	Wohlers et al.
4,784,646 A	11/1988	Feingold	5,407,433 A	4/1995	Loomas
4,798,594 A	1/1989	Hillstead	5,423,848 A	6/1995	Washizuka et al.
4,809,679 A	3/1989	Shimonaka	5,429,609 A	7/1995	Yoon
4,863,438 A	9/1989	Gauderer	5,431,676 A	7/1995	Dubrul
4,889,107 A	12/1989	Kaufman	5,443,452 A	8/1995	Hart et al.
4,895,565 A	1/1990	Hillstead	5,456,284 A	10/1995	Ryan
4,897,081 A	1/1990	Poirier	5,476,475 A	12/1995	Gadberry
4,903,710 A	2/1990	Jessamine et al.	5,480,410 A	1/1996	Cuschieri et al.
4,950,222 A	8/1990	Scott et al.	5,496,280 A	3/1996	Vandenbroek
4,950,223 A	8/1990	Silvanov	5,503,112 A	4/1996	Luhman
4,984,564 A	1/1991	Yuen	5,514,109 A	5/1996	Mollenauer et al.
4,991,593 A	2/1991	LeVahn	5,514,133 A	5/1996	Golub et al.
4,998,538 A	3/1991	Charowsky et al.	5,520,632 A	5/1996	Leveen
5,002,557 A	3/1991	Hasson	5,522,791 A	6/1996	Leyva
5,015,228 A	5/1991	Columbus et al.	5,522,824 A	6/1996	Ashby
5,019,101 A	5/1991	Purkait	5,524,644 A	6/1996	Crook
5,026,366 A	6/1991	Leckrone	5,526,536 A	6/1996	Cartmill
5,041,095 A	8/1991	Littrell	5,545,179 A	8/1996	Williamson, IV
5,045,070 A	9/1991	Grodecki et al.	5,562,632 A	10/1996	Davila
D320,658 S	10/1991	Quigley et al.	5,562,688 A	10/1996	Riza
5,071,411 A	12/1991	Hillstead	5,577,993 A	11/1996	Zhu et al.
5,074,878 A	12/1991	Bark et al.	5,582,577 A	12/1996	Lund et al.
5,082,005 A	1/1992	Kaldany	5,584,850 A	12/1996	Hart et al.
5,086,763 A	2/1992	Hathman	5,601,579 A	2/1997	Semertzides
5,092,846 A	3/1992	Nishijima	5,620,415 A	4/1997	Lucey
5,125,897 A	6/1992	Quinn et al.	5,632,979 A	5/1997	Goldberg
5,129,885 A	7/1992	Green et al.	5,634,911 A	6/1997	Hermann et al.
5,141,498 A	8/1992	Christian	5,634,936 A	6/1997	Linden
5,149,327 A	9/1992	Oshiyama	5,634,937 A	6/1997	Mollenauer et al.
5,156,617 A	10/1992	Reid	5,636,645 A	6/1997	Ou
5,158,553 A	10/1992	Berry et al.	5,640,977 A	6/1997	Leahy et al.
5,159,921 A	11/1992	Hoover	5,649,550 A	7/1997	Crook
5,161,773 A	11/1992	Tower	5,653,705 A	8/1997	de la Torre et al.
5,167,636 A	12/1992	Clement	5,657,963 A	8/1997	Hinchliffe
5,178,162 A	1/1993	Bose	5,658,272 A	8/1997	Hasson
5,188,595 A	2/1993	Jacobi	5,658,306 A	8/1997	Kieturakis
5,192,301 A	3/1993	Kamiya et al.	5,672,168 A	9/1997	de la Torre et al.
5,197,955 A	3/1993	Stephens et al.	5,685,854 A	11/1997	Green
5,207,656 A	5/1993	Kranys	5,707,703 A	1/1998	Rothrum et al.
5,209,737 A	5/1993	Ritchartt	5,709,664 A	1/1998	Vandenbroek
5,211,370 A	5/1993	Powers	5,720,730 A	2/1998	Blake, III
5,211,633 A	5/1993	Stouder	5,738,628 A	4/1998	Sierocuk et al.
5,213,114 A	5/1993	Bailey, Jr.	5,741,234 A	4/1998	Aboul-Hosn
5,234,455 A	8/1993	Mulhollan	5,741,298 A	4/1998	MacLeod
5,242,409 A	9/1993	Buelna	5,743,884 A	4/1998	Hasson et al.
5,248,304 A	9/1993	Vigdorchik et al.	5,749,882 A	5/1998	Hart et al.
5,261,883 A	11/1993	Hood et al.	5,755,660 A	5/1998	Tyagi
5,263,922 A	11/1993	Sova et al.	5,769,783 A	6/1998	Fowler
5,269,763 A	12/1993	Boehmer	5,769,794 A	6/1998	Conlan et al.
5,269,772 A	12/1993	Wilk	5,782,812 A	7/1998	Hart et al.
D343,236 S	1/1994	Quigley et al.	5,795,290 A	8/1998	Bridges
5,279,575 A	1/1994	Sugarbaker	5,803,919 A	9/1998	Hart et al.
D346,022 S	4/1994	Quigley et al.	5,803,921 A	9/1998	Bonadio
5,299,582 A	4/1994	Potts	5,807,350 A	9/1998	Diaz
5,300,036 A	4/1994	Mueller	5,810,721 A	9/1998	Mueller et al.
5,308,336 A	5/1994	Hart et al.	5,813,409 A	9/1998	Leahy et al.
5,309,896 A	5/1994	Moll et al.	5,814,026 A	9/1998	Yoon
5,316,541 A	5/1994	Fischer	5,817,062 A	10/1998	Flom
5,320,611 A	6/1994	Bonutti	5,820,555 A	10/1998	Mueller
5,330,437 A	7/1994	Durman	5,832,925 A	11/1998	Rothrum
5,330,497 A	7/1994	Freitas	5,848,992 A	12/1998	Hart et al.
5,334,143 A	8/1994	Carroll	5,853,395 A	12/1998	Crook et al.
5,336,192 A	8/1994	Palestrant	5,865,728 A	2/1999	Moll et al.
5,342,315 A	8/1994	Rowe et al.	5,871,474 A	2/1999	Hermann et al.
5,342,385 A	8/1994	Norelli et al.	5,882,344 A	3/1999	Stouder
5,350,364 A	9/1994	Stephens et al.	5,899,208 A	5/1999	Bonadio
5,364,345 A	11/1994	Lowery et al.	5,904,703 A	5/1999	Gilson
5,366,478 A	11/1994	Brinkerhoff et al.	5,906,577 A	5/1999	Beane et al.
5,368,545 A	11/1994	Schaller et al.	5,916,232 A	6/1999	Hart
5,383,861 A	1/1995	Hempel	5,947,922 A	9/1999	MacLeod
5,385,553 A	1/1995	Hart et al.	5,951,467 A	9/1999	Picha et al.
5,391,153 A	2/1995	Haber et al.	5,957,913 A	9/1999	de la Torre et al.
5,391,156 A	2/1995	Hildwein et al.	5,964,781 A	10/1999	Mollenauer et al.
5,395,367 A	3/1995	Wilk	5,993,485 A	11/1999	Beckers
			5,994,450 A	11/1999	Pearce
			5,997,515 A	12/1999	de la Torre et al.
			6,024,736 A	2/2000	de la Torre et al.
			6,025,067 A	2/2000	Fay

(56)

References Cited

U.S. PATENT DOCUMENTS

6,033,426	A	3/2000	Kaji	7,083,626	B2	8/2006	Hart et al.
6,033,428	A	3/2000	Sardella	7,112,185	B2	9/2006	Hart et al.
6,036,685	A	3/2000	Mueller	7,118,528	B1	10/2006	Piskun
6,042,573	A	3/2000	Lucey	7,153,319	B1	12/2006	Haberland et al.
6,048,309	A	4/2000	Flom et al.	7,195,590	B2	3/2007	Butler et al.
6,059,816	A	5/2000	Moenning	7,297,106	B2	11/2007	Yamada et al.
6,077,288	A	6/2000	Shimomura et al.	7,300,399	B2	11/2007	Bonadio et al.
6,099,506	A	8/2000	Macoviak et al.	7,344,547	B2	3/2008	Piskun
6,110,154	A	8/2000	Shimomura et al.	7,445,597	B2	11/2008	Butler et al.
6,123,689	A	9/2000	To	7,537,564	B2	5/2009	Bonadio et al.
6,142,935	A	11/2000	Flom et al.	7,540,839	B2	6/2009	Butler et al.
6,142,936	A	11/2000	Beane et al.	7,559,893	B2	7/2009	Bonadio et al.
6,149,642	A	11/2000	Gerhart et al.	7,749,415	B2	7/2010	Brustad et al.
6,150,608	A	11/2000	Wambeke	7,753,901	B2	7/2010	Piskun et al.
6,159,182	A	12/2000	Davis	7,837,612	B2	11/2010	Gill et al.
6,162,172	A	12/2000	Cosgrove et al.	7,867,164	B2	1/2011	Butler et al.
6,162,196	A	12/2000	Hart et al.	7,909,760	B2	3/2011	Albrecht et al.
6,162,206	A	12/2000	Bindokas	7,998,068	B2	8/2011	Bonadio et al.
6,163,949	A	12/2000	Neuenschwander	8,012,088	B2	9/2011	Butler et al.
6,164,279	A	12/2000	Tweedle	8,021,296	B2	9/2011	Bonadio et al.
6,171,282	B1	1/2001	Ragsdale	8,157,817	B2	4/2012	Bonadio et al.
6,183,486	B1	2/2001	Snow et al.	8,187,178	B2	5/2012	Bonadio et al.
6,238,373	B1	5/2001	de la Torre et al.	8,317,691	B2	11/2012	Bonadio et al.
6,254,533	B1	7/2001	Fadem et al.	8,343,047	B2	1/2013	Albrecht et al.
6,254,534	B1	7/2001	Butler et al.	8,375,955	B2	2/2013	Desai et al.
6,258,065	B1	7/2001	Dennis	8,485,970	B2	7/2013	Widenhouse et al.
6,315,770	B1	11/2001	de la Torre et al.	8,518,024	B2	8/2013	Williams et al.
6,319,246	B1	11/2001	de la Torre et al.	8,657,740	B2	2/2014	Bonadio et al.
6,322,541	B2	11/2001	West	8,734,336	B2	5/2014	Bonadio et al.
6,328,730	B1	12/2001	Harkrider, Jr.	8,740,785	B2	6/2014	Butler et al.
6,346,074	B1	2/2002	Roth	8,752,553	B2	6/2014	Bonadio et al.
6,382,211	B1	5/2002	Crook	8,876,708	B1	11/2014	Piskun et al.
6,420,475	B1	7/2002	Chen	8,888,693	B2	11/2014	Bonadio et al.
6,440,063	B1	8/2002	Beane	8,961,406	B2	2/2015	Ortiz et al.
6,450,983	B1	9/2002	Rambo	8,961,407	B2	2/2015	Piskun et al.
6,454,783	B1	9/2002	Piskun	8,986,202	B2	3/2015	Butler et al.
6,464,686	B1	10/2002	O'Hara et al.	9,078,695	B2	7/2015	Hess et al.
6,485,435	B1	11/2002	Bakal	9,095,300	B2	8/2015	Bonadio et al.
6,485,467	B1	11/2002	Crook et al.	9,131,835	B2	9/2015	Widenhouse et al.
6,488,620	B1	12/2002	Segermark et al.	9,271,753	B2	3/2016	Butler et al.
6,533,734	B1	3/2003	Corley, III et al.	9,277,908	B2	3/2016	Butler et al.
6,551,270	B1	4/2003	Bimbo et al.	2001/0037053	A1	11/2001	Bonadio et al.
6,554,793	B1	4/2003	Pauker	2001/0039430	A1	11/2001	Dubrul et al.
6,569,119	B1	5/2003	Haberland et al.	2001/0047188	A1	11/2001	Bonadio et al.
6,578,577	B2	6/2003	Bonadio et al.	2002/0002324	A1	1/2002	Mcmanus
6,582,364	B2	6/2003	Butler et al.	2002/0010389	A1	1/2002	Butler et al.
6,589,167	B1	7/2003	Shimomura	2002/0038077	A1	3/2002	de la Torre et al.
6,589,211	B1	7/2003	MacLeod	2002/0072762	A1	6/2002	Bonadio et al.
6,607,504	B2	8/2003	Haarala	2002/0111536	A1	8/2002	Cuschieri et al.
6,613,952	B2	9/2003	Rambo	2003/0028179	A1	2/2003	Piskun
6,623,426	B2	9/2003	Bonadio et al.	2003/0078478	A1	4/2003	Bonadio et al.
6,706,050	B1	3/2004	Giannadakis	2003/0139756	A1	7/2003	Brustad
6,714,298	B2	3/2004	Ryer	2003/0187376	A1	10/2003	Rambo
6,723,044	B2	4/2004	Pulford	2003/0192553	A1	10/2003	Rambo
6,793,621	B2	9/2004	Butler et al.	2003/0225392	A1	12/2003	McMichael
6,796,940	B2	9/2004	Bonadio et al.	2003/0236549	A1	12/2003	Bonadio et al.
6,797,765	B2	9/2004	Pearce	2004/0015185	A1	1/2004	Ewers et al.
6,814,078	B2	11/2004	Crook	2004/0024363	A1	2/2004	Goldberg
6,814,700	B1	11/2004	Mueller et al.	2004/0049099	A1	3/2004	Ewers et al.
6,840,951	B2	1/2005	de la Torre et al.	2004/0049100	A1	3/2004	Butler
6,846,287	B2	1/2005	Bonadio et al.	2004/0068232	A1	4/2004	Hart et al.
6,860,463	B2	3/2005	Hartley	2004/0073090	A1	4/2004	Butler
6,866,861	B1	3/2005	Luhman	2004/0092795	A1	5/2004	Bonadio et al.
6,884,253	B1	4/2005	McFarlane	2004/0092796	A1	5/2004	Butler et al.
6,902,541	B2	6/2005	McNally et al.	2004/0093018	A1	5/2004	Johnson
6,908,430	B2	6/2005	Caldwell	2004/0097793	A1	5/2004	Butler et al.
6,916,331	B2	7/2005	Mollenauer et al.	2004/0106942	A1	6/2004	Taylor
6,936,037	B2	8/2005	Bubb	2004/0143158	A1	7/2004	Hart et al.
6,939,296	B2	9/2005	Ewers	2004/0154624	A1	8/2004	Bonadio et al.
6,945,932	B1	9/2005	Caldwell et al.	2004/0215063	A1	10/2004	Bonadio et al.
6,958,037	B2	10/2005	Ewers	2004/0230161	A1	11/2004	Zeiner
6,979,324	B2	12/2005	Bybordi	2004/0249248	A1	12/2004	Bonadio et al.
7,008,377	B2	3/2006	Beane	2004/0260244	A1	12/2004	Piechowicz et al.
7,052,454	B2	5/2006	Taylor	2005/0020884	A1	1/2005	Heart et al.
7,081,089	B2	7/2006	Bonadio et al.	2005/0033246	A1	2/2005	Ahlberg
				2005/0059865	A1	3/2005	Kahle
				2005/0065475	A1	3/2005	Hart et al.
				2005/0065543	A1	3/2005	Kahle
				2005/0090713	A1	4/2005	Gonzales

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0090716 A1 4/2005 Bonadio et al.
 2005/0090717 A1 4/2005 Bonadio et al.
 2005/0131349 A1 6/2005 Albrecht
 2005/0137609 A1 6/2005 Guiraudon
 2005/0148823 A1 7/2005 Vaugh et al.
 2005/0155611 A1 7/2005 Vaugh et al.
 2005/0159647 A1 7/2005 Hart et al.
 2005/0192483 A1 9/2005 Bonadio et al.
 2005/0192598 A1 9/2005 Johnson
 2005/0197537 A1 9/2005 Bonadio et al.
 2005/0203346 A1 9/2005 Bonadio et al.
 2005/0209510 A1 9/2005 Bonadio et al.
 2005/0222582 A1 10/2005 Wenchell
 2005/0240082 A1 10/2005 Bonadio et al.
 2005/0241647 A1 11/2005 Nguyen
 2005/0267419 A1 12/2005 Smith
 2005/0277946 A1 12/2005 Greenhalgh
 2005/0288558 A1 12/2005 Ewers
 2005/0288634 A1 12/2005 O'Herron
 2006/0020164 A1 1/2006 Butler et al.
 2006/0020241 A1 1/2006 Piskun et al.
 2006/0030755 A1 2/2006 Ewers et al.
 2006/0041270 A1 2/2006 Lenker
 2006/0047284 A1 3/2006 Gresham
 2006/0047293 A1 3/2006 Haberland et al.
 2006/0106402 A1 5/2006 McLucas
 2006/0149137 A1 7/2006 Pingleton et al.
 2006/0149306 A1 7/2006 Hart et al.
 2006/0161050 A1 7/2006 Butler et al.
 2006/0241651 A1 10/2006 Wilk
 2006/0247498 A1 11/2006 Bonadio et al.
 2006/0247499 A1 11/2006 Butler et al.
 2006/0247500 A1 11/2006 Voegele et al.
 2006/0247516 A1 11/2006 Hess et al.
 2006/0258899 A1 11/2006 Gill et al.
 2006/0264706 A1 11/2006 Piskun
 2007/0004968 A1 1/2007 Bonadio et al.
 2007/0049966 A1 3/2007 Bonadio et al.
 2007/0093695 A1 4/2007 Bonadio et al.
 2007/0118175 A1 5/2007 Butler et al.
 2007/0185387 A1 8/2007 Albrecht et al.
 2007/0203398 A1 8/2007 Bonadio et al.
 2007/0255219 A1 11/2007 Vaugh et al.
 2007/0287889 A1 12/2007 Mohr
 2007/0299387 A1 12/2007 Williams et al.
 2008/0027476 A1 1/2008 Piskun
 2008/0097162 A1 4/2008 Bonadio et al.
 2008/0097163 A1 4/2008 Butler et al.
 2008/0255519 A1 10/2008 Piskun et al.
 2008/0281161 A1 11/2008 Albrecht et al.
 2008/0281162 A1 11/2008 Albrecht et al.
 2009/0012477 A1 1/2009 Norton et al.
 2009/0036745 A1 2/2009 Bonadio et al.
 2009/0069837 A1 3/2009 Bonadio et al.
 2009/0093683 A1 4/2009 Richard et al.
 2009/0149714 A1 6/2009 Bonadio
 2009/0187079 A1 7/2009 Albrecht et al.
 2009/0221966 A1 9/2009 Richard
 2009/0292176 A1 11/2009 Bonadio et al.
 2009/0326330 A1 12/2009 Bonadio et al.
 2010/0057121 A1 3/2010 Piskun et al.
 2010/0063362 A1 3/2010 Bonadio et al.
 2010/0063364 A1 3/2010 Bonadio et al.
 2010/0081880 A1 4/2010 Widenhouse et al.
 2010/0081881 A1 4/2010 Murray et al.
 2010/0113886 A1 5/2010 Piskun et al.
 2010/0204548 A1 8/2010 Bonadio et al.
 2010/0217087 A1 8/2010 Bonadio et al.
 2010/0261972 A1 10/2010 Widenhouse et al.
 2010/0274091 A1 10/2010 Rothstein et al.
 2010/0274093 A1 10/2010 Shelton, IV
 2010/0280326 A1 11/2010 Hess et al.
 2011/0011410 A1 1/2011 Desai et al.
 2011/0071359 A1 3/2011 Bonadio et al.
 2011/0092778 A1 4/2011 Butler et al.

2011/0270195 A1 11/2011 Piskun
 2012/0016394 A1 1/2012 Bonadio et al.
 2012/0022333 A1 1/2012 Main et al.
 2012/0029297 A1 2/2012 Bonadio et al.
 2012/0116172 A1 5/2012 Butler et al.
 2012/0123214 A1 5/2012 Bonadio et al.
 2013/0041231 A1 2/2013 Bonadio et al.
 2013/0060093 A1 3/2013 Bonadio et al.
 2013/0116509 A1 5/2013 Bonadio et al.
 2013/0245373 A1 9/2013 Okoniewski
 2014/0107425 A1 4/2014 Bonadio et al.
 2014/0303443 A1 10/2014 Bonadio et al.
 2014/0323809 A1 10/2014 Bonadio et al.
 2015/0148611 A1 5/2015 Bonadio et al.
 2015/0272563 A1 10/2015 Butler et al.
 2015/0335353 A1 11/2015 Widenhouse et al.
 2016/0022257 A1 1/2016 Bonadio et al.

FOREIGN PATENT DOCUMENTS

DE 296 00 939 6/1998
 EP 0113520 7/1984
 EP 0142262 5/1985
 EP 0537768 4/1993
 EP 0950376 10/1999
 EP 1118657 7/2001
 EP 1312318 5/2003
 EP 1593348 11/2005
 EP 2168511 3/2010
 FR 1456623 9/1966
 GB 1151993 5/1969
 GB 1355611 6/1974
 GB 1372491 10/1974
 GB 1379772 1/1975
 GB 1400808 7/1975
 GB 1407023 9/1975
 GB 1496696 12/1977
 GB 2071502 9/1981
 GB 2255019 10/1992
 GB 2275420 8/1994
 JP 10-108868 4/1998
 JP 11-290327 10/1999
 JP 2001-61850 3/2001
 JP 2002-28163 1/2002
 JP 2004-509659 4/2004
 JP 2004-195037 7/2004
 JP 2011-98138 5/2011
 SU 1342485 1/1997
 WO WO 86/06272 11/1986
 WO WO 92/11880 7/1992
 WO WO 92/21292 12/1992
 WO WO 93/05740 4/1993
 WO WO 95/05207 2/1995
 WO WO 95/07056 3/1995
 WO WO 95/22289 8/1995
 WO WO 95/24864 9/1995
 WO WO 95/27445 10/1995
 WO WO 95/27468 10/1995
 WO WO 96/36283 11/1996
 WO WO 97/32514 9/1997
 WO WO 97/32515 9/1997
 WO WO 98/35614 8/1998
 WO WO 98/48724 11/1998
 WO WO 99/03416 1/1999
 WO WO 99/25268 5/1999
 WO WO 99/29250 6/1999
 WO WO 00/32116 6/2000
 WO WO 00/32117 6/2000
 WO WO 00/32119 6/2000
 WO WO 00/32120 6/2000
 WO WO 00/35356 6/2000
 WO WO 00/54675 9/2000
 WO WO 00/54676 9/2000
 WO WO 00/54677 9/2000
 WO WO 01/08563 2/2001
 WO WO 01/08581 2/2001
 WO WO 01/26558 4/2001
 WO WO 01/91652 12/2001
 WO WO 01/91653 12/2001

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO 02/17800 A2	3/2002
WO	WO 02/34108 A2	5/2002
WO	WO 03/026512 A1	4/2003
WO	WO 03/034908 A3	5/2003
WO	WO 03/061480 A1	7/2003
WO	WO 03/103548 A1	12/2003
WO	WO 2004/026153 A1	4/2004
WO	WO 2004/030547 A1	4/2004
WO	WO 2005/009257 A2	2/2005
WO	WO 2005/034766 A2	4/2005
WO	WO 2005/089661	9/2005
WO	WO 2006/040748 A1	4/2006
WO	WO 2006/059318	8/2006
WO	WO 2008/121294 A1	10/2008
WO	WO 2009/035663 A2	3/2009
WO	WO 2014/144233 A1	9/2014




FIG. 1




FIG. 3




FIG. 4




FIG. 2




FIG. 5




FIG. 6




FIG. 8




FIG. 7




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 25




FIG. 23




FIG. 26




FIG. 24




FIG. 27




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41A




FIG. 41B




FIG. 41D




FIG. 41C




FIG. 43




FIG. 42




FIG. 44






FIG. 45






FIG. 49

FIG. 48





FIG. 50






FIG. 53






FIG. 52






FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 61

FIG. 60




FIG. 62




FIG. 64

FIG. 63




FIG. 65




FIG. 66




FIG. 68




FIG. 67




FIG. 70




FIG. 69




FIG. 72




FIG. 71

WOUND RETRACTOR DEVICE

This application is a Continuation of U.S. application Ser. No. 13/655,286, filed Oct. 18, 2012, which is a Continuation of U.S. application Ser. No. 12/426,438, filed Apr. 20, 2009, now U.S. Pat. No. 8,317,691, which is a Continuation of U.S. application Ser. No. 10/678,653, filed Oct. 6, 2003, now U.S. Pat. No. 7,559,893, which is a Continuation-In-Part of U.S. application Ser. No. 10/133,979, filed Apr. 29, 2002, now U.S. Pat. No. 6,846,287, which is a Continuation of U.S. application Ser. No. 09/801,826, filed Mar. 9, 2001, now abandoned, which is a Continuation of International Application No. PCT/IE99/0022, filed Dec. 1, 1999.

U.S. application Ser. No. 10/678,653 is also a Continuation-In-Part of U.S. application Ser. No. 10/374,523, filed Feb. 27, 2003, now U.S. Pat. No. 7,445,597, which is a Continuation of U.S. application Ser. No. 09/849,341, filed May 7, 2001, now U.S. Pat. No. 6,582,364, which is a Continuation of U.S. application Ser. No. 09/688,138, filed Oct. 16, 2000, now U.S. Pat. No. 6,254,534.

U.S. application Ser. No. 10/678,653 also claims benefits of priority of U.S. Provisional Application No. 60/415,780, filed Oct. 4, 2002, 60/428,215, filed Nov. 22, 2002, and U.S. Provisional Application No. 60/490,909, filed Jul. 30, 2003.

U.S. application Ser. No. 09/688,138 also claims the benefits of priority of European Application No. 00650010, filed Feb. 18, 2000, Application No. 991053, filed Dec. 16, 1999, in Ireland, Application No. 990861, filed Oct. 14, 1999, in Ireland.

International Application No. PCT/IE99/0022 also claims the benefits of priority of Application No. 990111, filed Feb. 15, 1999, in Ireland, and Application No. 980997, filed Dec. 1, 1998, in Ireland.

All of the above-listed applications are incorporated herein by reference in their entireties.

INTRODUCTION

The invention relates to a retractor. In particular the invention relates to a retractor for retracting the margins of an incision or a natural bodily orifice to provide maximum exposure of an organ or body structures for examination and/or access for surgical procedures, while also providing protection for the exposed sides of the incised tissue.

Various retractors are known. Some known retractors are difficult and cumbersome to use, and/or are relatively expensive. In addition, some known retractors are limited to use with a particular size of incision and a particular patient anatomy.

This invention is directed towards providing an improved wound retractor which will overcome at least some of these problems, and in addition provide a means of wound protection during a surgical procedure.

STATEMENTS OF INVENTION

According to the invention there is provided a wound protector and retractor device comprising:

- a longitudinal axis;
 - a distal member;
 - a proximal member; and
 - a sleeve extending at least between the distal member and the proximal member,
- the sleeve having a proximal gripping portion for pulling the sleeve upwardly to shorten an axial extent located between the distal member and the proximal member.

In the device, on release of the gripping portion the shortened axial extent between the distal member and the proximal member is substantially maintained without a requirement for an additional locking device.

In one embodiment the proximal gripping portion is provided at a proximal end portion of the sleeve. The gripping portion may be reinforced by a reinforcing arrangement such as a gripping ring. The gripping ring may be mounted to the sleeve.

In one embodiment the sleeve is fixed to the proximal member at a first end portion and is movable over the proximal member at a second end portion. The sleeve may be axially slidable over the proximal member at the second end portion.

In another embodiment the second end portion of the sleeve is slidingly received over a portion of the proximal member to allow relative movement between the sleeve and the proximal member to shorten the axial extent of the sleeve located between the distal member and the proximal member. The portion of the proximal member that slidingly receives the sleeve may include an outer portion of the proximal member. The second end portion of the sleeve may be biased against the proximal member.

In one embodiment the proximal member is located within the sleeve.

The proximal member may form a part of a securing arrangement configured to substantially fix the axial extent of the sleeve located between the distal member and the proximal member at a desired length.

The sleeve may extend from the proximal member, around the distal member, and has a return section outside of the proximal member, the return section providing the proximal gripping portion.

In one embodiment the distal member comprises a distal ring which may be an O-ring.

The distal ring may be formed of an elastomeric material.

In one embodiment the proximal member comprises a proximal ring which may be an O-ring.

The proximal ring may be relatively rigid with respect to the distal ring.

In one embodiment the sleeve is of a pliable material.

The wound protector and retractor device may comprise a guide member for a proximal portion of the sleeve.

The sleeve may extend between the guide member and the proximal member.

The guide member may comprise a receiver for the proximal member. For example, the guide member may have an inwardly facing recess defining a receiver for the proximal member. In one case the proximal member comprises a proximal ring and the recess has a shape which is complementary to that of the proximal ring, for example the recess may be substantially C-shaped in transverse cross section.

In another embodiment a lock may be provided for locking the guide member to the proximal member. The guide member may be engagable with the proximal member to provide the lock.

In some cases the guide member may be an interference fit with the proximal member.

In one embodiment, on retraction of an incision the sleeve defines an excess sleeve portion extending between the proximal member and the gripping portion.

The excess sleeve portion may be removed. Alternatively the excess sleeve portion is inserted through the retractor and in this case may define an organ retainer.

Alternatively the excess sleeve portion is configured to form a seal such as a forearm seal or an instrument seal.

The seal may comprise an iris valve.

In one embodiment the device comprises a guide member for a proximal portion of the sleeve and the excess sleeve material is mounted to the guide member. The excess sleeve material together with the guide member may define a chamber. The chamber may have an inflation port. In one case, on inflation, the chamber defines a seal for an object such as a surgeon's forearm or an instrument shaft.

In one embodiment the device comprises a first proximal mounting member and a second proximal mounting member between which at least portion of a sleeve extends. The first and second mounting members may be movable relative to one another.

The mounting members may be movable axially relative to one another and/or the mounting members are rotationally movable relative to one another.

In one arrangement the mounting members are movable relative to one another to configure at least portion of the proximal portion of the sleeve to form a seal. The mounting members may be movable to twist the sleeve to form an iris.

In one embodiment the device comprises a biasing member for biasing the seal into a desired configuration such as a closed configuration.

The biasing member may be a spring such as a coil spring.

In one embodiment the device further comprises a lock for locking the first and second mounting members together.

The second mounting member may be engagable with the first mounting member to provide the lock. The lock may be provided by snap fitting engagement between the mounting members. Alternatively one mounting member is an interference fit with the other mounting member to provide the lock.

In one case the sleeve which extends between the mounting members is a proximal portion of the retracting sleeve.

In another case the sleeve which extends between the mounting members is a connecting sleeve which is separate from the retracting sleeve.

The first mounting member may comprise a ring member.

The second mounting member may comprise a ring member.

In one embodiment the wound protector and retractor device further includes a valve.

The valve may be attached to the retractor device.

In one case the valve is attached to the proximal portion of the sleeve.

In another case a connector is provided between the device and the valve. The connector may comprise a connector sleeve. The connector sleeve may be of substantially fixed length.

In one embodiment a flexible joint is provided between the valve and the device.

In another embodiment a malleable joint is provided between the valve and the device. In this case the valve may be offset with respect to the longitudinal axis of the wound retractor.

In one embodiment the malleable joint is provided by a malleable connecting sleeve section. The malleable connecting sleeve section may be of corrugated configuration.

In one embodiment the valve is a lip seal.

Alternatively the valve is an iris seal.

The valve may be a forearm seal or an instrument seal.

In one embodiment the device comprises a release arrangement for releasing the device from a retracting configuration. The release arrangement may comprise a

pulling device. The pulling device may be coupled to the distal member. The pulling device may comprise a pull cord or a ribbon.

In another aspect the invention provides a wound protector and retractor device comprising:

a longitudinal axis;

a distal member;

a proximal member; and

a sleeve extending at least between the distal member and the proximal member,

the sleeve, on retraction of an incision, defining an excess sleeve portion extending proximally from the proximal member.

In one embodiment the excess sleeve portion is configured to form a seal such as a forearm seal or an instrument seal. The seal may comprise an iris valve.

In a further aspect the invention provides a wound protector and retractor device comprising:

a longitudinal axis;

a distal member;

a proximal member; and

a sleeve extending at least between the distal member and the proximal member,

the device further comprising a first proximal mounting member and a second proximal mounting member between which at least portion of a sleeve extends.

The first and second mounting members may be movable relative to one another. The mounting members may be movable axially relative to one another and/or the mounting members are rotationally movable relative to one another. In one case the mounting members are movable relative to one another to configure at least portion of the proximal portion of the sleeve to form a seal. The mounting members may be movable to twist the sleeve to form an iris. The device may comprise a biasing member for biasing the seal into a desired configuration such as a closed configuration.

In another aspect the invention provides a surgical device comprising a wound retractor, a valve and a connector between the wound protector and the valve, the wound retractor comprising:

a longitudinal axis;

a distal member;

a proximal member; and

a sleeve extending at least between the distal member and the proximal member.

The connector may comprise a connector sleeve which may be of substantially fixed length. The connector may comprise a flexible joint between the valve and the retractor. Alternatively the connector comprises a malleable joint between the valve and the retractor. The valve may be offset with respect to the longitudinal axis of the wound retractor. The malleable joint is provided by a malleable connecting sleeve section. The malleable connecting sleeve sections may be of corrugated configuration.

In another aspect the invention provides a method for retracting an incision comprising the steps of:

making an incision in a patient;

providing a wound retractor comprising a longitudinal axis, a distal member, a proximal member, and a sleeve extending at least between the distal member and the proximal member, the sleeve having a proximal gripping portion;

inserting the distal member through the incision such that the sleeve extends through the incision and the proximal member is located outside of the incision;

gripping the gripping portion of the sleeve and pulling the sleeve upwardly to shorten an axial extent of the sleeve located between the distal member and the proximal member.

In one embodiment, on release of the gripping portion the shortened axial extent of the sleeve between the distal member and the proximal member is substantially maintained.

The sleeve may be fixed to the proximal member at a first end portion and extending over the proximal member at a second end portion, and the method comprises moving the sleeve over the proximal member as the sleeve is pulled upwardly to shorten the axial extent of the sleeve located between the distal member and the proximal member. The method may comprise the step of moving the sleeve relative to the proximal member including sliding a portion of the sleeve against a radially outer portion of the proximal member.

In one embodiment a portion of the sleeve located between the distal member and the proximal member includes two material layers. The sleeve may be wrapped around the distal member to form the two material layers.

The method may comprise sealing the wound retractor, for example by attaching a seal to the wound retractor, by releaseably mounting a seal to the wound retractor. A seal may be mounted a proximal end of the wound retractor. A seal may be mounted to a proximal end of the sleeve.

In one case the retractor comprises a mounting member and the seal is attached to the mounting member.

In one embodiment the seal is attached to the proximal end of the wound retractor using a connector.

The connector may be a connecting sleeve. The connector may be at least partially of a flexible material. Alternatively the connector is at least partially of a malleable material and the method may comprise the step of manipulating the connector into a desired configuration. In one case the desired configuration is a configuration in which the seal is offset from the longitudinal axis of the wound retractor.

In one embodiment the method comprises pulling the sleeve upwardly to provide an excess sleeve portion extending proximally of the wound retractor. In one case the method comprises the step of cutting away the excess sleeve portion. In another case the method comprises the step of inserting the excess sleeve portion through the retractor. The excess sleeve material may be inserted through the retractor providing an organ retainer.

In another case the method comprises the step of manipulating the excess sleeve portion to provide a seal.

In one embodiment the retractor comprises a proximal mounting member and the excess sleeve portion is attached to the mounting member.

In another embodiment the excess sleeve portion forms, with the mounting member, a chamber. The chamber may have an inflation port and the method comprises inflating the chamber to provide a seal.

The seal may be a lip seal or an iris seal.

In one embodiment the wound retractor is sealed with a forearm seal.

In another embodiment the wound retractor is sealed with an instrument seal.

In one case the incision is of a size to receive an instrument, when retracted.

In another case the incision is of a size to receive a forearm, when retracted.

In a further case the incision is of a size to provide a site for open surgery, when retracted.

According to the invention there is provided a medical device comprising:

a retractor member comprising a distal portion for insertion through an incision made in a patient, and a proximal portion for extending from the incision and outside of the patient;

a distal member associated with the distal portion of the retractor member;

a proximal member associated with the proximal portion of the retractor member;

the retractor member being axially movable relative to the distal member to draw the proximal and distal members towards one another thereby shortening the axial extent of the retractor member between the proximal and distal members.

In one embodiment the retractor member comprises a sleeve member. The sleeve member preferably extends around the distal member.

In one embodiment the distal member is a ring member such as a resilient ring member, for example, an O-ring.

In one embodiment the proximal member is connected to the retractor member. The proximal member may be a ring member.

In one embodiment the sleeve member is of a pliable material.

In one arrangement the sleeve extends from the proximal member, around the distal member and has a return section outside of the proximal member.

The return section may have a handle member such as a ring member.

In one embodiment the device comprises a guide member. The retractor member may extend between the guide member and the proximal member.

The guide member may comprise a receiver for the proximal member.

The guide member may comprise a guide ring-receiving member.

The sleeve return section may be configured to provide an integral valve member. In this case the sleeve return section may be twisted to provide an iris valve.

In another embodiment the sleeve return section is mounted to the guide member.

The sleeve return section may be extended into the opening defined by the sleeve member.

The device may comprise a lock for locking the guide member to the proximal member. Typically the guide member is engagable with the proximal member to provide the lock.

The guide member may be an interference fit with the proximal member.

In one embodiment of the invention the device includes a valve, such as an iris-type valve.

In one embodiment the device comprises a biasing member for biasing the valve into a desired position such as the closed position.

In one arrangement the device comprises a guide member located proximally of the proximal member and a biasing means is provided between the proximal member and the guide member. The biasing means may comprise a spring such as a coil spring.

In one embodiment a sleeve member extends between the proximal member and the guide member and the biasing means is located around the sleeve. The sleeve member may be an extension of the retractor member.

In one embodiment the device comprises a release member for releasing the device from an incision. The release

member may comprise an elongate member such as a pull ribbon or string extending from a distal end of the device.

The release member may extend from the distal member.

In one embodiment the valve is located or locatable proximal of the proximal member. A pliable material may be provided between the valve and the proximal member. The pliable material may comprise a proximal extension of the retractor member.

In one embodiment the pliable material comprises a sleeve section.

In another embodiment the valve is a lip seal.

The invention also provides a method for retracting an incision comprising the steps of:—

providing a device comprising a retractor member having a distal portion and a proximal portion, a distal member associated with the distal portion and a proximal portion associated with the proximal portion;

inserting the distal member and the distal portion of the retractor member through an incision made in a patient; and

pulling the retractor member axially relative to the distal member to draw the proximal and distal members towards one another thereby shortening the axial extent of the retractor member between the proximal and distal members and retracting the incision.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more clearly understood from the following description of some embodiments thereof, given by way of example only, with reference to the accompanying drawings, in which:

FIG. 1 is a perspective view of a retractor according to the invention;

FIG. 2 is a cross sectional view of the device of FIG. 1; FIGS. 3 and 4 are perspective views illustrating the formation of the device of FIGS. 1 and 2;

FIGS. 5 and 6 are cross sectional views of FIGS. 3 and 4 respectively;

FIGS. 7 and 8 are perspective views illustrating the use of the device;

FIGS. 9 and 10 are cross sectional views illustrating the method of use of the device;

FIG. 11 is a cross sectional view of another device according to the invention in a configuration ready for use;

FIG. 12 is a perspective view of the device of FIG. 11 with a distal portion inserted through an incision;

FIG. 13 is a cross sectional view of the device of FIG. 11 with a distal portion inserted through an incision;

FIG. 14 is a cross sectional view of the device of FIG. 11 in use with an incision retracted;

FIG. 15 is a perspective view of the device in the configuration of FIG. 14;

FIG. 16 is a perspective view of the device in situ with an excess sleeve portion being removed;

FIG. 17 is a cross sectional view of the device in situ with an excess sleeve portion extending back into the incision;

FIG. 18 is a perspective view of the device in situ with an excess sleeve portion being twisted;

FIG. 19 is a perspective view similar to FIG. 18 with the excess sleeve portion further twisted to provide an iris valve;

FIG. 20 is a cross sectional view of another device according to the invention in situ;

FIG. 21 is a cross sectional view of the device of FIG. 20 with an excess sleeve portion mounted to a guide member;

FIG. 22 is a cross sectional view of the device of FIG. 21 with the excess sleeve portion inflated to provide an integral evert ing access port;

FIG. 23 is a perspective view of another retractor according to the invention incorporating a release device;

FIG. 24 is a cross sectional view of the retractor of FIG. 23;

FIG. 25 is a perspective view illustrating the formation of the device of FIG. 23;

FIG. 26 is a cross sectional view of the device in the configuration of FIG. 25;

FIG. 27 is a cross sectional view of the retractor of FIGS. 23 to 26, in use;

FIG. 28 is a cross sectional view of the retractor of FIGS. 23 to 27 illustrating the operation of a release device;

FIG. 29 is a perspective view of another device according to the invention in an insertion configuration;

FIG. 30 is a perspective view of the device of FIG. 29 in position in an incision;

FIG. 31 is another perspective view of the device of FIG. 30 in another configuration;

FIG. 32 is another view of the device of FIG. 31 with an outer portion severed and a valve being formed;

FIG. 33 is a view of the device of FIG. 32 with the valve closed;

FIG. 34 is a perspective view of another device similar to the device of FIGS. 29 to 33 with a valve closed;

FIG. 35 is a cross sectional view of the device of FIG. 34;

FIG. 36 is a perspective view of another device similar to the device of FIGS. 29 to 33 incorporating a biasing means in an inserted configuration;

FIG. 37 is another perspective view of the device of FIG. 36 in a retracting configuration;

FIG. 38 is a perspective view of the device of FIG. 37 in another configuration and excess sleeve being removed;

FIG. 39 is a perspective view of the device of FIG. 38 with a valve closed;

FIG. 40 is a perspective view of the device of FIG. 39 with a valve partially open;

FIGS. 41A and 41B are perspective views of the device of FIG. 39;

FIGS. 41C and 41D are perspective views of the device of FIG. 39 with an object inserted through the valve;

FIG. 42 is a perspective view of another device according to the invention;

FIG. 43 is a cross sectional view of the device of FIG. 42 in position in an incision;

FIG. 44 is a cross sectional view of the device of FIG. 43 with an object extending therethrough;

FIG. 45 is a cross sectional view similar to FIG. 44 with an object offset from a longitudinal axis of the device;

FIG. 46 is a cross sectional view of another device according to the invention on insertion into an incision;

FIG. 47 is a cross sectional view of the device of FIG. 46 with an incision retracted;

FIGS. 48 and 49 are cross sectional views of the device of FIG. 47 showing the formation of an iris valve;

FIG. 50 is a cross sectional view of another access port;

FIG. 51 is a cross sectional view of the port of FIG. 50 with an instrument in position;

FIGS. 52 to 55 are cross sectional views of another access port;

FIGS. 56 and 57 are cross sectional views of a further access port;

FIGS. 58 and 59 are cross sectional views of another access port;

FIGS. 60 to 62 are cross sectional views of a further access port;

FIGS. 63 to 66 are cross sectional views of another access port;

FIGS. 60 to 72 are cross sectional views of another access port of the invention.

DETAILED DESCRIPTION

Referring to the drawings, and initially to FIGS. 1 to 10 thereof there is illustrated a device 1 comprising a retractor member provided by a sleeve 2, a distal member provided by a distal ring 3 of resilient material such as an O-ring and a proximal member provided by a proximal ring 4 which may also be an O-ring.

The sleeve 2 is of any suitable material such as of pliable plastics film material and comprises a distal portion 5 for insertion through an incision 6, in this case made in a patient's abdomen 7, and a proximal portion 8 for extending from the incision 6 and outside of the patient.

In this case the distal ring 3 is not fixed to the sleeve 2 but rather the sleeve is led around the ring 3 and is free to move axially relative to the distal ring 3 somewhat in the manner of a pulley. The proximal ring 4 is fixed to the sleeve 2, in this case at the proximal inner end thereof. The sleeve 2 terminates in a handle or gripping portion which in this case is reinforced by a gripping ring 15.

To configure the retractor device according to the invention a sleeve 2 is first provided with the gripping ring 15 fixed at one end and the proximal ring 4 fixed at the other end. The distal ring 3 is then placed over the sleeve 2 as illustrated in FIGS. 4 and 6. The gripping ring 15 is then used to manipulate the sleeve 2 so that the sleeve 2 is folded back on itself into the configuration of FIGS. 1 and 2 in which the gripping ring 15 is uppermost. The sleeve extends from the proximal ring 4 and the distal ring 3 is contained between inner and outer layers 2a, 2b of the sleeve 2. The device is now ready for use.

The resilient distal ring 3 is scrunched up and inserted through the incision 6 with the distal end 5 of the sleeve 2 as illustrated in FIG. 4. The sleeve 2 is then pulled upwardly in the direction of the arrows A in FIGS. 8 to 10. On pulling of the sleeve 2 upwardly the outer layer 2b is pulled up while the inner layer 2a is drawn around the proximal ring 3. This results in shortening the axial extent between the proximal ring 4 and the distal ring 3, tensioning the sleeve and applying a retraction force to the margins of the incision 6. The system appears to be self locking because when tension is applied to the sleeve 2 and the pulling force is released the rings 3, 4 remain in position with a retraction force applied. Frictional engagement between the layers of the sleeve in this configuration may contribute to this self locking.

As the incision is being retracted the margins are also protected by the sleeve. On retraction, an access port is provided, for example for a surgeon to insert his hand and/or an instrument to perform a procedure. The device may be used as a retractor in open surgery or as a base for a valve/seal to allow it to be used in hand assisted laparoscopic surgery or for instrument or hand access generally.

Excess sleeve portion 20 outside the incision may, for example, be cut-away.

The retractor is suitable for a range of incision sizes and is easily manufactured. It is also relatively easy to manipulate, in use. It not only retracts but also protects the incision.

Referring now to FIGS. 11 to 19 there is illustrated another device 50 according to the invention which is similar to the device described above with reference to FIGS. 1 to 10 and like parts are assigned the same reference numerals. In this case the device comprises a guide member 51 for the proximal ring 4. The guide member 51 is in the form of an annular ring member with an inwardly facing

C-shaped groove 52 which is sized to accommodate the ring 4 as illustrated. The outer layer of the sleeve 2 is interposed between the ring 4 and the guide 51 to further control the pulling of the sleeve and thereby further controlling the application of the retraction force. The guide 51 also assists in stabilising the proximal ring 4. The use of the device 50 is illustrated in FIGS. 12 to 15 is similar to that described above.

Any suitable guide such as the ring 51 may be used to assist in retaining/stabilising the proximal ring 4 in a desired position during pulling up of the sleeve to retract the incision. The guide may be located proximal of the ring 4.

The guide member provides a monitoring member to which devices such as valves may be attached.

Referring to FIG. 16, it will be noted that in one case the excess sleeve portion 20 may be cut-away.

Referring to FIG. 17, in this case the excess sleeve portion is inverted 60 into the incision. In this configuration it may act as an organ retractor, or provide the surgeon with an open tunnel to work in.

Referring to FIGS. 18 and 19 in this case the excess sleeve portion is twisted to form an iris diaphragm valve 65.

In the embodiment illustrated in FIGS. 20 to 22 a device 70 according to the invention has an integral seal/valve 71. The device 70 is similar to that described above with reference to FIGS. 11 to 19 and like parts are assigned the same reference numerals. In this case the guide member 50 has an outer groove 75 to receive the gripping ring 15 as illustrated in FIG. 21. The excess sleeve portion 20 is folded out and down and the gripping ring 15 is engaged in the groove 75 to provide an air tight seal. In this configuration the excess sleeve may be inflated through an inflation port 76 to provide an integral access valve 71. The valve may be used to sealingly engage a hand, instrument or the like passing therethrough. The inflated sleeve portion defining the valve is evertable on passing an object therethrough.

Referring to FIGS. 23 to 28 there is illustrated another retractor 80 according to the invention which is similar to the retractors described above and like parts are assigned the same reference numerals. In this case the retractor 80 has a release mechanism which in this case is provided by a release cord or ribbon 81 which is coupled at one end 82 to the inner ring 3 and terminates in an outer free end 83 which may be grasped by a user. The ribbon 81, on assembly, is led through the gap between the proximal ring 4 and the outer guide member 51 so that it is positioned between the ring 4 and the guide member. The ribbon 81 facilitates release of the self locked sleeve in the in-use configuration sited in an incision. Pulling on the ribbon 81 pulls on the inner ring 3, allowing the ring 3 to be released from the inner wall of the incision to thereby release the device. The flexibility of the ring 3 facilitates this movement.

The advantage of this arrangement is that a user can readily release the device from its self locked retracting configuration.

Referring to FIGS. 29 to 33 there is illustrated another device 90 according to the invention in which parts similar to those of the devices described above are assigned the same reference numerals. In this case the device 90 has a lower guide ring 51 for the proximal ring 4 and an outer guide assembly provided by an upper guide ring 91 and a second proximal ring 92 between which the sleeve 2 is led. In all relevant embodiments the upper guide such as the ring 91 may provide a second mounting member located proximally of the first guide member such as the ring 51 which also provides a mounting member. The device is used to first retract an incision as described above. During this phase the

outer guide assembly is conveniently external of the guide member **51** and proximal ring **4**. Indeed, it may be completely detached from the sleeve **2** and subsequently coupled to the sleeve **2** at an appropriate stage such as when the incision is retracted as illustrated in FIG. **30**. The outer guide assembly is then moved downwardly towards the incision as illustrated in FIG. **31**. This may be achieved while pulling the sleeve **2** upwardly. When the guide assembly is adjacent to the guide member **51** excess sleeve length may be severed as illustrated in FIG. **32**. By twisting the guide assembly relative to the guide member **51** the sleeve **2** is twisted, closing down the lumen of the sleeve **2** and forming an iris type access valve **95** as illustrated in FIG. **33**. In this way a sealed access port is provided for hand and/or instrument access through the incision.

It will be appreciated that while reference has been made to an incision made by a surgeon the devices of the invention may be applied for retraction of any opening such as a body opening.

Referring to FIGS. **34** and **35** there is illustrated another retractor device **100** according to the invention which is similar to the device of FIGS. **29** to **33** and like parts are assigned the same reference numerals. In this case a releasable lock is provided to maintain the access valve **95** closed. For interlocking, in this instance the upper guide ring **91** is an interference fit with the lower guide ring **51**. Various other locking arrangements may be used such as a screw threaded or bayonet type engagement, magnets, clips and the like.

Referring to FIGS. **36** to **41D** there is illustrated another retractor device **110** according to the invention which is similar to the device of FIGS. **29** to **33** and like parts are assigned the same reference numerals. In this case the device incorporates a biasing means to bias an integral valve into a closed position. The biasing means is in this case provided by a coil spring **111** which is located around the sleeve between the guide rings **51**, **91**. In use, the device is used in a similar manner to the device of FIGS. **29** to **33** except that on movement of the upper guide ring **91** downwardly the spring **111** also moves downwardly towards the lower guide ring **51**, initially into the position illustrated in FIG. **38**. Excess sleeve material may be removed at this stage. The spring **111** is tensioned as the upper ring **91** is rotated while pushing the upper ring **91** downwardly. The sleeve material between the two rings **51**, **91** is twisted, forming an iris type valve **112** as illustrated in FIG. **39**. To open the valve **112** to pass an object such as an instrument, hand, arm or the like therethrough a downward force may be applied to push the upper ring **91** towards the lower ring **51** against the biasing of the spring. This configuration is illustrated in FIG. **40**. When the object is inserted the upper ring member **91** is released, allowing the valve to close around the object. The operation of the device **110** will be readily apparent from FIGS. **41A** to **41D**. In FIG. **41A** the valve **112** is illustrated in a closed resting configuration. FIG. **41B** shows the application of a downward force to open the valve **112**. An object such as an instrument **113** is shown inserted through the open valve **112** in FIG. **41C**. In FIG. **41D** the downward pressure on the upper ring **91** is released allowing the valve **112** to close around the object **113**.

Referring now to FIGS. **42** to **45** there is illustrated another device **120** according to the invention which has some aspects similar to the device of FIGS. **11** to **18** and like parts are assigned the same reference numerals. In this case the device has a lip seal **121**. The lip seal **121** is provided by a membrane with a central aperture **122** through which an object **123** such as an instrument is passed. The lip seal **121** is located on the sleeve **2** proximally of the guide ring **51**

such that a proximal flexible sleeve section **125** is provided. This sleeve section **125** is very useful in facilitating offset movements of the object **123** as illustrated in FIG. **45**. The sleeve section **125** accommodates movement of the object **123** whilst maintaining sealing engagement between the lip seal **121** and the object **123**. It will be appreciated that this feature, as with several other features described above may be utilised in association with other constructions of wound protector/retractors and access parts generally other than those illustrated in the drawings.

Referring to FIGS. **46** to **48** there is illustrated another device **130** according to the invention which has some features similar to those of FIGS. **11** to **15**, like parts being assigned the same reference numerals. In this case the sleeve has a proximal section external of the wound when the device is in the retracting configuration. This proximal sleeve section comprises a first portion **131** extending from the guide ring **51** and a second portion **132** extending from the first portion **131**. The second portion **132** is defined between two spaced-apart iris rings **134**, **135**. It will be noted that the iris rings **134**, **135** have engagement features such as projections and grooves for interengagement on assembly. The iris ring **134** also has an engagement element, in this case provided by a groove **137** for engagement on assembly with a corresponding engagement element of the guide ring **51** which in this case is provided by a projection **138**.

The device is fitted as described above to retract an incision, leaving the first and second sleeve portions **131**, **132** extending proximally. The first sleeve portion **131** is redundant and can be removed or scrunched up on assembly of the first iris ring **134** to the guide ring **138** as illustrated in FIG. **48**. The second or upper iris ring **135** is then rotated to twist the sleeve section **132** to form an iris-type seal as illustrated in FIG. **49**. The iris ring **135** is engaged with the iris ring **134** as illustrated to maintain the valve closed.

In some of the embodiments described above a valve **829** is mounted directly to a retractor base **811**. It is possible to provide a flexible coupling between the retractor **811** and the valve **829**. For example, as illustrated in FIGS. **93** and **94** such a flexible coupling is provided by a length of flexible sleeve **830** extending between the retractor **811** and the valve **829**. The flexible sleeve **830** may be formed by excess retractor sleeve material attached to the valve **829**.

In a further embodiment of the invention as illustrated in FIGS. **52** to **57** a valve **860** may be coupled to the retractor **811** in such a way as to facilitate a flexible joint therebetween. For example, a fixed length sleeve **862** may extend between an outer proximal ring **863** of the retractor **811** and the valve **860**. Excess sleeve material **864** from the retractor **811** may pass up through the valve **860**. The valve **860** may be pushed down and the excess sleeve pulled up to firmly lock the base retractor **811** in the incision. Excess sleeve material **864** may be cut-away and removed, if desired. The flexible sleeve **864** allows the instrument to tilt as illustrated in FIG. **57** without compromising the valve seal to the shaft of the instrument/object **814**.

As illustrated in FIGS. **58** and **59** a spring **867** may be provided between the valve **860** and the retractor proximal ring **863** for more controlled flexibility.

Referring now to FIGS. **60** to **62** another modular system is illustrated in which a valve **870** is releasably mounted to a retractor **811**. The retractor **811** may have a proximal ring **871** with a recess **872** to receive the valve **870**. An instrument shaft **814** can readily pass through the valve **870** and retractor **811**. At least a section **873** of the shaft **814** can be bent or steered almost immediately distal of the retractor.

Referring now to FIGS. 63 to 66 any suitable valve 880 may be coupled to a retractor 811 using excess sleeve material 881 from the retractor 811. The valve 880 may be pulled upwardly to deploy the base retractor 811. The excess sleeve material 881 provides a flexible neck which facilitates easy introduction of objects such as an instrument 883, even one having a bent shaft (FIG. 119). As illustrated in FIG. 120 such an arrangement also facilitates additional instrument reach by allowing the valve 880 to be moved closer to the base retractor 811.

Referring to FIGS. 67 to 72 there is illustrated another access port comprising a wound protector and retractor device 811 and a valve 900. The valve 900 is connected to an outer guide ring 901 of the retractor device 811 by a sleeve 902 which in this case is of malleable material of corrugated configuration somewhat in the manner of the bendable hinge portion of a bendable drinking straw. The sleeve 902 may be pre-shaped to be offset from the longitudinal axis of the retractor to facilitate ease of insertion of an instrument or the like. The corrugated sleeve 902 may be compressed as illustrated in FIG. 68 to provide a low profile to facilitate outlining any of excess retractor sleeve as illustrated in FIGS. 69 and 70. Thereafter, the corrugated sleeve 902 can be extended/elongated and is readily manipulated into a desired configuration. Because the sleeve 902 is malleable it will retain a desired bent shape, even when the abdomen is pressurised. Any excess retractor sleeve material 905 may be cut-away as illustrated or used as described above.

In this context the term "malleable" is used to denote an element which is capable of being manipulated into a desired position and/or orientation, and which retains this manipulated position and/or orientation under the typical stresses and strains applied when used for an intended purpose with a patient, for example during partial insertion of a laparoscopic instrument.

The access ports of the invention can be used in a number of ways. In one method the retractor is used as described above, the distal inner ring being inserted into an incision, the outer ring being slid to controllably radially expand the incision. The retractor may then be locked in position. If necessary, the outer ring can be moved further downwardly to create a larger incision.

In some arrangements an instrument may be bent manually outside the body and the bent instrument is delivered through the access port to readily access the operative site.

In a further embodiment an instrument is inserted into the access port and the surgeon uses the abdominal wall itself to bend the instrument and then insert the bent section further into the abdomen.

In all cases the sleeve may be gripped by gripping a valve or other element mounted thereto.

The access ports of the invention have at least some of the following advantages:

Controlled Radial Expansion

1. Greater access using smaller incision
2. Can vary incision size as need be (e.g. specimen removal during lap coli.)

Greater Sealing Capabilities

1. No gas leakage from the wound margins
2. Cannot be inadvertently pulled out of the incision
3. Will seal any incision and never require secondary sealing method (suture, Hasson port, etc.)

Eliminate Intra-Abdominal Profile

1. Gives back more working space in the abdomen (critical in pelvic surgery)

2. Perineal access for operations such as Radical Prostatectomy.

Protection of Wound from Infection and Cancer Seeding

1. Tight seal with no "chimney stack" effect
2. Upon removal all areas of potential contamination are isolated from the incision

Reduced Extra-Abdominal Profile

1. Will increase the effective working length of an instrument
2. Greater working area outside the abdomen

Increase the Freedom of Movement of Conventional Laparoscopic Instruments

The invention is not limited to the embodiments herein-before described, with reference to the accompanying drawings, which may be varied in construction and detail.

The invention claimed is:

1. A surgical device, comprising:

a wound retractor, including:

- a distal ring,
- a proximal ring, and
- a wound retracting sleeve extending at least between the distal ring and the proximal ring, wherein the wound retractor is for retracting a wound opening via shortening of an axial extent of the wound retracting sleeve that extends between the distal ring and the proximal ring; and

a sealing assembly coupled to the wound retractor, the sealing assembly including:

- an annular base supporting at least a portion of the proximal ring, the annular base having a periphery,
- a flexible covering coupled to the periphery of the annular base, and
- a valve member coupled to the flexible covering, wherein the flexible covering and the valve member form a seal across the annular base and the proximal ring, and the valve member includes:

- a body, and
- an accessway surrounded by the body, wherein the accessway is sized to receive an instrument, and wherein a surface of the body that defines the accessway sealingly engages the instrument.

2. The surgical device of claim 1, wherein the flexible covering includes an opening, and the valve member forms a seal across the opening.

3. The surgical device of claim 1, wherein the valve member is movable in a proximal-distal direction relative to the annular base.

4. The surgical device of claim 1, wherein at least a portion of the valve member is movable towards and away from the periphery of the annular base.

5. The surgical device of claim 1, wherein the valve member directly contacts a proximalmost end of the flexible covering, and the annular base directly contacts a distalmost end of the flexible covering.

6. The surgical device of claim 1, wherein the wound retractor includes a central longitudinal axis, the accessway includes a central longitudinal axis, and the flexible covering facilitates tilting of the central longitudinal axis of the accessway relative to the central longitudinal axis of the wound retractor.

7. The surgical device of claim 1, wherein the annular base receives the proximal ring.

8. A surgical device, comprising:

a wound retractor, including:

- a distal ring,
- a proximal ring, and

15

- a wound retracting sleeve extending at least between the distal ring and the proximal ring, wherein the wound retractor is for retracting a wound opening via shortening of an axial extent of the wound retracting sleeve that extends between the distal ring and the proximal ring; and
- a sealing assembly coupled to the wound retractor, the sealing assembly including:
 - a base, wherein at least a portion of the proximal ring and at least a portion of the wound retracting sleeve mount onto the annular base, with the portion of the wound retracting sleeve being held between the proximal ring and the base, and wherein the base includes a periphery,
 - a flexible covering coupled to the periphery of the base, and
 - a valve member coupled to the flexible covering, wherein the flexible covering and the valve member form a seal across the base and the proximal ring, and the valve member includes:
 - a body, and
 - an accessway surrounded by the body, wherein the accessway is sized to receive an instrument, and wherein a surface of the body that extends about the accessway sealingly engages the instrument.
- 9. The surgical device of claim 8, wherein the flexible covering is coupled to a proximalmost end of the periphery of the base.
- 10. The surgical device of claim 8, wherein the flexible covering includes an opening, and valve member forms a seal across the opening.
- 11. The surgical device of claim 8, wherein the valve member is pivotable relative to the base.
- 12. The surgical device of claim 8, wherein the valve member is movable in a proximal-distal direction relative to at least a portion of the flexible covering.
- 13. The surgical device of claim 8, wherein the valve member directly contacts a proximal portion of the flexible covering, and a distal portion of the flexible covering directly contacts the base.
- 14. A surgical device, comprising:
 - a wound retractor, including:
 - a distal ring,
 - a proximal ring, and
 - a wound retracting sleeve extending at least between the distal ring and the proximal ring, wherein the wound retractor is for retracting a wound opening via

16

- shortening of an axial extent of the wound retracting sleeve that extends between the distal ring and the proximal ring; and
- a sealing assembly coupled to the wound retractor, the sealing assembly including:
 - an annular base including a recess, wherein the proximal ring extends into the recess, and wherein the annular base has a periphery,
 - a flexible cover coupled to the periphery of the annular base and covering at least a portion of the annular base, wherein the flexible cover includes an opening formed therein, and
 - a valve member in the opening of the flexible cover, wherein the flexible cover and the valve member form a seal across the annular base and the proximal ring, and the valve member includes:
 - a body, and
 - an accessway surrounded by the body, wherein the accessway is sized to receive an instrument, and wherein a surface of the body that surrounds the accessway sealingly engages the instrument.
- 15. The surgical device of claim 14, wherein a distal portion of the flexible cover is coupled to a proximal portion of the periphery of the annular base.
- 16. The surgical device of claim 14, wherein the valve member forms a seal across the opening in the flexible cover.
- 17. The surgical device of claim 14, wherein the valve member is movable in proximal-distal direction relative to the annular base.
- 18. The surgical device of claim 14, wherein the annular base includes a central longitudinal axis, and at least a portion of the valve member is movable away from the central longitudinal axis.
- 19. The surgical device of claim 14, wherein the valve member directly contacts a proximal portion of the flexible cover, and a distal portion of the flexible cover directly contacts the annular base.
- 20. The surgical device of claim 14, wherein the annular base includes a central longitudinal axis, the accessway includes a central longitudinal axis, and the flexible cover facilitates tilting of the central longitudinal axis of the accessway relative to the central longitudinal axis of the annular base.

* * * * *

专利名称(译)	伤口牵开器装置		
公开(公告)号	US9700296	公开(公告)日	2017-07-11
申请号	US14/753796	申请日	2015-06-29
[标]申请(专利权)人(译)	阿特波斯有限公司		
申请(专利权)人(译)	阿特洛波斯有限公司		
当前申请(专利权)人(译)	阿特洛波斯有限公司		
[标]发明人	BONADIO FRANK BUTLER JOHN VAUGH TREVOR MACNALLY SHANE J REID ALAN		
发明人	BONADIO, FRANK BUTLER, JOHN VAUGH, TREVOR MACNALLY, SHANE J. REID, ALAN		
IPC分类号	A61B1/32 A61B17/34 A61B17/02 A61B17/00		
CPC分类号	A61B17/0293 A61B1/32 A61B17/3423 A61B17/3498 A61B17/3431 A61B2017/00557 A61B2017/0212 A61B2017/0225 A61B2017/3443 A61B2017/3482 A61B2017/3484 A61B2017/3492 A61B17/3439 A61B17/3462		
优先权	19980997 1998-12-01 IE 19990111 1999-02-15 IE 19990861 1999-10-14 IE 19991053 1999-12-16 IE 2000650010 2000-02-18 EP 60/415780 2002-10-04 US 60/428215 2002-11-22 US 60/490909 2003-07-30 US		
其他公开文献	US20160022257A1		
外部链接	Espacenet USPTO		

摘要(译)

伤口保护器和牵开器装置 1 包括套筒 2，由远端环 3 弹性材料提供的远端构件和提供的近端构件通过近端环 4。套筒 2 围绕环引导，并且以滑轮的方式稍微相对于远端环 3 自由地轴向移动。近端环 4 固定到套管 2 上，在这种情况下在其近端内端处。套筒 2 终止于手柄或抓握部分，该抓握部分由抓握环 15 增强。套筒从近端环 4 延伸，并且远端环 3 包含在内层和外层之间 2 a，2 b 套筒 2。弹性远端环 3 被碾碎并插入穿过切口 6。然后将套筒 2 向上拉。在向上拉套筒 2 时，外层 2 拉出，而内层 2 > a 围绕近端环 3 绘制。这导致近端环 4 和远端环之间的轴向范围缩短，张紧套管并向切口的边缘施加收缩力 6 的。当切口缩回时，边缘也受到套筒的保护。在缩回时，提供进入端口，例如用于外科医生插入他的手和/或器械以执行手术。该装置可用作开放手术中的牵开器或用作瓣膜/密封件的基座，以允许其用于手动腹腔镜手术或用于器械进入或手动进入通常。

