



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
01.08.2012 Bulletin 2012/31

(51) Int Cl.:
A61B 17/3207 (2006.01)

(21) Application number: **12165347.1**

(22) Date of filing: **22.04.2004**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LI LU MC NL PL PT RO SE SI SK TR

- **Patel, Himanshu**
San Jose
California 95125 (US)
- **Venegas, Gautama**
Pleasanton
California 94588 (US)

(30) Priority: **22.04.2003 US 421979**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
04760156.2 / 1 622 523

(74) Representative: **Gray, James et al**
Withers & Rogers LLP
4 More London Riverside
London
SE1 2AU (GB)

(71) Applicant: **Tyco Healthcare Group LP**
Mansfield, MA 02048 (US)

- (72) Inventors:
- **Simpson, John B.**
Woodside
California 94062 (US)
 - **Rosenthal, Michael**
Palo Alto
California 95125 (US)

Remarks:

This application was filed on 24-04-2012 as a divisional application to the application mentioned under INID code 62.

(54) **Methods and devices for cutting tissue**

(57) A method of removing material from a blood flow lumen generally includes providing a device (140) having a cutting element (104) and an opening, advancing the device through the blood flow lumen to a site where material is to be removed, forcing the opening toward a wall of the site where material is to be removed, and moving the cutting element and the opening so that material in the blood flow lumen is cut by the cutting element and directed into the opening for removal as the cutting element and opening are moved through the blood flow lumen. In some embodiments, the device may be deflected or bent to force the opening toward a wall to remove material. The cutting element may be rotatable and may have an axis that is movable, that is not parallel to the longitudinal axis of the device, or both. In some embodiments, the cutting element is movable between retracted and deployed positions for advancing the device to a site for treatment and for removing material, respectively.




FIG. 1

Description

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] The present application is a continuation-in-part of U.S. Patent Application No. 10/288,581, (Attorney Docket No. 018489-002540US), which is a continuation-in-part of U.S. Patent Application No. 10/027, 418, filed December 19, 2001, entitled "Debulking Catheter", which claims the benefit of Provisional Patent Application Serial No. 60/257,704, filed December 20,2000, entitled "Debulking Catheter". and Provisional Patent Application Serial No. 60/272,273 filed February 27,2001, entitled "Debulking Catheter", the complete disclosures of which are incorporated herein by reference.

[0002] The present application also claims the benefit of Provisional Application No. 60/381,632, filed on May 19,2002, entitled "Debulking Catheter", the complete disclosure of which is incorporated herein by reference.

[0003] The present application is also related to U.S. Patent Application Nos. 09/377, 884, filed August 19,1999, entitled "Apparatus and Methods for Material Capture and Removal" and 09/377,894, filed August 19,1999, entitled "Apparatus and Methods for Removing Material From a Body Lumen", the complete disclosures of which are incorporated by reference.

BACKGROUND OF THE INVENTION

[0004] The present invention relates generally to systems and methods for debulking body lumens. More particularly, the present invention relates to atherectomy catheters for excising atheroma and other materials from blood vessels and from stents.

[0005] Cardiovascular disease frequently arises from the accumulation of atheromatous material on the inner walls of vascular lumens, particularly arterial lumens of the coronary and other vasculature, resulting in a condition known as atherosclerosis. Atherosclerosis occurs naturally as a result of aging, but may also be aggravated by factors such as diet, hypertension, heredity, vascular injury, and the like. Atheromatous and other vascular deposits restrict blood flow and can cause ischemia which, in acute cases, can result in myocardial infarction. Atheromatous deposits can have widely varying properties, with some deposits being relatively soft and others being fibrous and/or calcified. In the latter case, the deposits are frequently referred to as plaque.

[0006] One conventional treatment for cardiovascular disease is the use of stents. Endoluminal stents are commonly used to treat obstructed or weakened body lumens, such as blood vessels and other vascular lumens. Once deployed in the blood vessel, the stent can remain in the body lumen where it will maintain the patency of the lumen and/or support the walls of the lumen which surround it. One factor impeding the success of stent technology in endoluminal treatments is the frequent occurrence of in-stent restenosis, characterized by prolifer-

ation and migration of smooth muscle cells within and/or adjacent to the implanted stent, causing reclosure or blockage of the body lumen.

[0007] Atherosclerosis and restenosis can be treated in a variety of ways, including drugs, bypass surgery, and a variety of catheter-based approaches which rely on intravascular debulking or removal of the atheromatous or other material occluding a blood vessel. Of particular interest to the present invention, a variety of methods for cutting or dislodging material and removing such material from the blood vessel have been proposed, generally being referred to as atherectomy procedures. Atherectomy catheters intended to excise material from the blood vessel lumen generally employ a rotatable and/or axially translatable cutting blade which can be advanced into or past the occlusive material in order to cut and separate such material from the blood vessel lumen. In particular, side-cutting atherectomy catheters generally employ a housing having an aperture on one side, a blade which is rotated or translated by the aperture, and a balloon to urge the aperture against the material to be removed.

[0008] Although atherectomy catheters have proven very successful in treating many types of atherosclerosis and in-stent restenosis, improved atherectomy catheters and methods are continuously being pursued. For example, many currently available side-cutting atherectomy catheters have difficulty in capturing occluding material in the cutting aperture. To facilitate material capture, the cutting aperture is frequently elongated to increase the area into which the material can penetrate. Such elongation typically requires an equivalent lengthening of the cutter housing. Since most cutter housings are rigid, such lengthening makes it more difficult to introduce the distal end of the catheter through tortuous regions of the vasculature.

[0009] Another shortcoming of many currently available atherectomy catheters is that they typically require a balloon positioned opposite the cutting window to urge the cutting window into contact with occluding material. Such balloons, however, unduly increase the size of the distal portion of the catheter. Even with the balloon, the amount of material that can be removed by conventional atherectomy catheters is limited by the size of the cutting window. Other disadvantages of some catheters include cutting elements with less than ideal hardness, inadequate storage space within the catheter for containing removed material, sub-optimal guide wire lumens, and/or the like.

[0010] For these reasons, it would be advantageous to have atherectomy catheters, and methods for their use, which could access small, tortuous regions of the vasculature and remove atheromatous and other occluding materials from within blood vessels and stents in a controlled fashion. In particular, it would be desirable to have atherectomy catheters and methods which could facilitate capturing and invagination of atheromatous materials. Ideally, such catheters and methods would be adaptable for use in a variety of body lumens, including

but not limited to coronary and other arteries. At least some of these objectives will be met by the present invention.

BRIEF SUMMARY OF THE INVENTION

[0011] The present invention provides catheters and methods for removing material from (or "debulking") a body lumen. Catheters of the present invention may be used in a variety of body lumens, including but not limited to intravascular lumens such as coronary arteries. Typically, debulking catheters are used to remove occlusive material, such as atherosclerotic plaque, from vascular lumens, but they may alternatively be used to remove other materials. Generally, debulking catheters include a proximal portion, a distal portion having an opening (or "window"), and a cutting element (or "tissue debulking assembly") which may be exposed through the opening to contact material in a body lumen. The catheter debulks a body lumen when it is moved while the cutting element is in contact with the material in the lumen.

[0012] In one aspect of the present invention, a method of removing material from a blood flow lumen comprises: providing a device having a cutting element and an opening; advancing the device through the blood flow lumen to a site where material is to be removed; forcing the opening toward a wall of the site where material is to be removed; and moving the cutting element and the opening after the forcing step so that material in the blood flow lumen is cut by the cutting element and directed into the opening for removal as the cutting element and opening are moved through the blood flow lumen. Optionally, the moving step may be carried out with the cutting element and the opening moving together in unison through the blood flow lumen.

[0013] In some embodiments, the forcing step is carried out by bending the device so that the opening is forced against the wall of the site. Also in some embodiments, the providing step is carried out with the cutting element being rotatable, with the moving step being carried out with the cutting element rotating when severing the material. When the cutting element is rotatable, the providing step may be carried out with the device having a longitudinal axis, and with the moving step being carried out with the cutting element rotating around an axis which is not parallel to the longitudinal axis of the device. In some embodiments, the providing step is carried out with the cutting element having an axis of rotation which is movable relative to a longitudinal axis of the device.

[0014] In some embodiments, the moving step is carried out with the cutting element cutting a continuous piece of material. Optionally, in such embodiments, the providing step may be carried out with the opening being on a side of the device; the forcing step may be carried out to force the side against the blood flow lumen; and the moving step may be carried out with the cutting element extending out of the opening, the cutting element directing the continuous piece of material into the open-

ing. In some embodiments, the moving step is carried out by moving the cutting element and window in a distal direction, with the cut material being stored in the device at a location distal to the cutting element. Also in some embodiments, the providing step is carried out with the cutting element being movable relative to the opening.

[0015] In still other embodiments, the providing step is carried out with the cutting element being movable between a deployed position and a retracted position, the cutting element extending out of the opening when in the deployed position and being contained within the opening when in the retracted position. In such embodiments, the advancing step is typically carried out with the cutting element in the retracted position and the moving step is carried out with the cutting element being in the deployed position. For example, the providing step may be carried out with the cutting element extending beyond the opening a distance of about 0.025 mm to about 0.64 mm. Generally, the providing step may be carried out with the opening being positioned along a side of the device.

[0016] In still another aspect of the present invention, a device for cutting tissue is provided which has an elongate body with an opening therein. A rotatable cutting element is coupled to a torque transmitting element which extends through the body. A visualization element is movable from a stored position to a working position which is at a radially outward position on the body.

[0017] In yet another aspect of the present invention, a device for cutting tissue is provided which has a movable cover coupled to the body. The cover is movable from a stored position, in which the rotatable cutting element is covered by the cover, to a working position, in which at least part of the rotatable cutting element is exposed. The cover may be linearly movable relative to the body so that the cover essentially translates without deforming.

[0018] In another aspect of the invention, a method of removing material from a vascular location is provided. The body may be deformed before advancing the cutting element and opening through the vascular region to cut and remove a continuous piece of material as describe herein. The deformable portion of the body may take any suitable shape such as S-shaped or helical providing the step of forcing the opening toward a wall of the site where material is to be removed. The deformable portion may be relatively long, such as at least 1cm or even at least 2 cm, to help stabilize the device.

[0019] In another aspect of the invention, a device for cutting tissue is provided which has two pivot points on opposite sides of the cutting element. The pivot points both help to move the cutting element into the cutting position and force the opening toward a wall. In particular the cutting or working position presents the cutting element at an orientation which may be advantageous when advancing the entire device through the vasculature as describe herein to cut and remove a continuous piece of material.

[0020] For a further understanding of the nature and

advantages of the invention, reference should be made to the following description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021]

Figure 1 is a perspective view of a debulking catheter of the present invention;

Figure 1A is a side view of a portion of a debulking catheter as in Figure 1, where the body has a rigid distal portion with a bend, according to one embodiment of the present invention;

Figure 2 is an exploded view of an exemplary distal portion of the debulking catheter of the present invention;

Figure 3A is an end view of the distal portion of the debulking catheter of Figure 1 in which the cutter is in a closed position in the catheter body;

Figure 3B is a sectional view along Line A-A of Figure 3A;

Figures 3C and 3D are views of the distal portion of a debulking catheter, where the distal portion has a locking shuttle mechanism;

Figure 4A is an end view of the distal portion of the debulking catheter of Figure 1 in which the cutter is in an open position outside of the cutting window ;

Figure 4B is a sectional view along Line A-A of Figure 4A;

Figures 4C and 4D are views of the distal portion of a debulking catheter, where the distal portion has a locking shuttle mechanism;

Figure 5A is an end view of the distal portion of the debulking catheter of Figure 1 in which the cutter is in a packing position within a tip of the catheter;

Figure 5B is a sectional view along Line A-A of Figure 5A ;

Figures 6 to 8 illustrate a monorail delivery system of the present invention;

Figure 9A is a perspective view of a cutter of the present invention;

Figure 9B is an end view of the cutter of Figure 9A;

Figure 9C is a sectional view of the cutter along Line A-A of the cutter of Figures 9A and 9B;

Figure 10A is a perspective view of a in-stent restenosis cutter of the present invention;

Figure 10B is an end view of the cutter of Figure 10A ;

Figure 10C is a sectional view of the cutter along Line B-B of the cutter of Figures 10A and 10B ;

Figure 11A is a perspective view of another in-stent restenosis cutter of the present invention;

Figure 11B is an end view of the cutter of Figure 11A ;

Figure 11C is a sectional view of the cutter along Line C-C of the cutter of Figures 11A and 11B ;

Figure 11D is a side view of another embodiment of a cutter, shown partially within a catheter body;

Figure 12 illustrates a proximal handle and cutter

driver of the present invention ;

Figure 13 illustrates a cutter driver with a handle cover removed;

Figures 14 to 16 illustrate three positions of the lever for controlling the cutter;

Figure 17 is a simplified flow chart illustrating a method of the present invention;

Figures 18 and 19 illustrate a method of the present invention;

Figure 20 schematically illustrates another method of the present invention

Figure 21 shows another device for cutting tissue with the device having a movable cover;

Figure 22 shows the device of Figure 21 with the cover in a stored position;

Figure 23 shows the device of Figure 21 with the cover in a working position which exposes part of the rotatable cutting element;

Figure 24 shows still another device for cutting tissue having two pivot points on opposite sides of the cutting element;

Figure 25 shows the device of Figure 24 after articulating the device at the pivot points to put the cutting element in a cutting position;

Figure 26A is a side view of the elongate body or shaft forming a helical shape.

Figure 26B is a perspective view looking at the distal end of the device;

Figure 27A shows a tube which forms part of the elongate body of Figure 26 in a straight configuration;

Figure 27B shows the tube of Figure 27A in a bent configuration ; and

Figure 28 illustrates a kit of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0022] The catheters and methods of the present invention are designed to debulk atheroma and other occlusive material from diseased body lumens, and in particular coronary arteries, de novo lesions, and in-stent restenosis lesions. The catheters and methods, however, are also suitable for treating stenoses of body lumens and other hyperplastic and neoplastic conditions in other body lumens, such as the ureter, the biliary duct, respiratory passages, the pancreatic duct, the lymphatic duct, and the like. Neoplastic cell growth will often occur as a result of a tumor surrounding and intruding into a body lumen. Debulking of such material can thus be beneficial to maintain patency of the body lumen. While the remaining discussion is directed at debulking and passing through atheromatous or thrombotic occlusive material in a coronary artery, it will be appreciated that the systems and methods of the present invention can be used to remove and/or pass through a variety of occlusive, stenotic, or hyperplastic material in a variety of body lumens.

[0023] Apparatus according to the present invention will generally comprise catheters having catheter bodies adapted for intraluminal introduction to the target body

lumen. The dimensions and other physical characteristics of the catheter bodies will vary significantly depending on the body lumen which is to be accessed. In the exemplary case of atherectomy catheters intended for intravascular introduction, the proximal portions of the catheter bodies will typically be very flexible and suitable for introduction over a guidewire to a target site within the vasculature. In particular, catheters can be intended for "over-the-wire" introduction when a guidewire channel extends fully through the catheter body or for "rapid exchange" introduction where the guidewire channel extends only through a distal portion of the catheter body. In other cases, it may be possible to provide a fixed or integral coil tip or guidewire tip on the distal portion of the catheter or even dispense with the guidewire entirely. For convenience of illustration, guidewires will not be shown in all embodiments, but it should be appreciated that they can be incorporated into any of these embodiments.

[0024] Catheter bodies intended for intravascular introduction will typically have a length in the range from 50 cm to 200 cm and an outer diameter in the range from 1 French to 12 French (0.33 mm: 1 French), usually from 3 French to 9 French. In the case of coronary catheters, the length is typically in the range from 125 cm to 200 cm, the diameter is preferably below 8 French, more preferably below 7 French, and most preferably in the range from 2 French to 7 French. Catheter bodies will typically be composed of an organic polymer which is fabricated by conventional extrusion techniques. Suitable polymers include polyvinylchloride, polyurethanes, polyesters, polytetrafluoroethylenes (PTFE), silicone rubbers, natural rubbers, and the like. Optionally, the catheter body may be reinforced with braid, helical wires, coils, axial filaments, or the like, in order to increase rotational strength, column strength, toughness, pushability, and the like. Suitable catheter bodies may be formed by extrusion, with one or more channels being provided when desired. The catheter diameter can be modified by heat expansion and shrinkage using conventional techniques. The resulting catheters will thus be suitable for introduction to the vascular system, often the coronary arteries, by conventional techniques.

[0025] The distal portion of the catheters of the present invention may have a wide variety of forms and structures. In many embodiments, a distal portion of the catheter is more rigid than a proximal portion, but in other embodiments the distal portion may be equally as flexible as the proximal portion. One aspect of the present invention provides catheters having a distal portion with a reduced rigid length. The reduced rigid length can allow the catheters to access and treat tortuous vessels and small diameter body lumens. In most embodiments a rigid distal portion or housing of the catheter body will have a diameter that generally matches the proximal portion of the catheter body, however, in other embodiments, the distal portion may be larger or smaller than the flexible portion of the catheter.

[0026] A rigid distal portion of a catheter body can be formed from materials which are rigid or which have very low flexibilities, such as metals, hard plastics, composite materials, NiTi, steel with a coating such as titanium nitride, tantalum, ME-92®, diamonds, or the like. Most usually, the distal end of the catheter body will be formed from stainless steel or platinum/iridium. The length of the rigid distal portion may vary widely, typically being in the range from 5 mm to 35 mm, more usually from 10 mm to 25 mm, and preferably between 6 mm and 8 mm. In contrast, conventional catheters typically have rigid lengths of approximately 16 mm.

[0027] The side opening windows of the present invention will typically have a length of approximately 2 mm. In other embodiments, however, the side opening cutting window can be larger or smaller, but should be large enough to allow the cutter to protrude a predetermined distance that is sufficient to debulk material from the body lumen.

[0028] The catheters of the present invention can include a flexible atraumatic distal tip coupled to the rigid distal portion of the catheter. For example, an integrated distal tip can increase the safety of the catheter by eliminating the joint between the distal tip and the catheter body. The integral tip can provide a smoother inner diameter for ease of tissue movement into a collection chamber in the tip. During manufacturing, the transition from the housing to the flexible distal tip can be finished with a polymer laminate over the material housing. No weld, crimp, or screw joint is usually required.

[0029] The atraumatic distal tip permits advancing the catheter distally through the blood vessel or other body lumen while reducing any damage caused to the body lumen by the catheter. Typically, the distal tip will have a guidewire channel to permit the catheter to be guided to the target lesion over a guidewire. In some exemplary configurations, the atraumatic distal tip comprises a coil. In some configurations the distal tip has a rounded, blunt distal end. The catheter body can be tubular and have a forward-facing circular aperture which communicates with the atraumatic tip. A collection chamber can be housed within the distal tip to store material removed from the body lumen. The combination of the rigid distal end and the flexible distal tip is approximately 30 mm.

[0030] A rotatable cutter or other tissue debulking assembly may be disposed in the distal portion of the catheter to sever material which is adjacent to or received within the cutting window. In an exemplary embodiment, the cutter is movably disposed in the distal portion of the catheter body and movable across a side opening window. A straight or serrated cutting blade or other element can be formed integrally along a distal or proximal edge of the cutting window to assist in severing material from the body lumen. In one particular embodiment, the cutter has a diameter of approximately 1.14 mm. It should be appreciated however, that the diameter of the cutter will depend primarily on the diameter of the distal portion of the catheter body.

[0031] In exemplary embodiments, activation of an input device can deflect a distal portion of the catheter relative to the proximal portion of the catheter. Angular deflection of the distal portion may serve one or more purposes in various embodiments. Generally, for example, deflection of the distal portion increases the effective "diameter" of the catheter and causes the debulking assembly to be urged against material in a lumen, such as atherosclerotic plaque. In other embodiments, deflection of the distal portion may act to expose a debulking assembly through a window for contacting material in a lumen. In some embodiments, for example, activation of the input device moves the debulking assembly over a ramp or cam so that a portion of the rigid distal portion and flexible tip are caused to drop out of the path of the debulking assembly so as to expose the debulking assembly through the window. In some embodiments, deflection may both urge a portion of the catheter into material in a lumen and expose a tissue debulking assembly.

[0032] Some embodiments further help to urge the debulking assembly into contact with target tissue by including a proximal portion of the catheter body having a rigid, shaped or deformable portion. For example, some embodiments include a proximal portion with a bend that urges the debulking assembly toward a side of the lumen to be debulked. In other embodiments, one side of the proximal portion is less rigid than the other side. Thus, when tension is placed on the catheter in a proximal direction (as when pulling the debulking assembly proximally for use), one side of the proximal portion collapses more than the other, causing the catheter body to bend and the debulking assembly to move toward a side of the lumen to be debulked. 100701 In exemplary embodiments, the debulking assembly comprises a rotatable cutter that is movable outside the window. By moving the cutter outside of the cutting window beyond an outer diameter of the distal portion of the catheter, the cutter is able to contact and sever material that does not invaginate the cutting window. In a specific configuration, the rotating cutter can be moved over the cam within the rigid, or distal, portion of the catheter body so that the cutting edge is moved out of the window. Moving the rotating cutter outside of the cutting window and advancing the entire catheter body distally, a large amount of occlusive material can be removed. Consequently, the amount of material that can be removed is not limited by the size of the cutting window.

[0033] As will be described in detail below, in some situations it is preferable to provide a serrated cutting edge, while in other situations it may be preferable to provide a smooth cutting edge. Optionally, the cutting edge of either or both the blades may be hardened, e.g., by application of a coating. A preferred coating material is a chromium based material, available from ME-92, Inc., which may be applied according to manufacturer's instructions. In some embodiments, the cutter includes a tungsten carbide cutting edge. Other rotatable and axially movable cutting blades are described in U.S. Patent Nos.

5,674,232; 5,242,460; 5,312,425; 5,431,673; and 4,771,774, the full disclosures of which are incorporated herein by reference. In some embodiments, a rotatable cutter includes a beveled edge for removal of material from a body lumen while preventing injury to the lumen. In still other embodiments, a tissue debulking assembly may include alternative or additional features for debulking a lumen. For example, the debulking assembly may include, but is not limited to, a radio frequency device, an abrasion device, a laser cutter and/or the like.

[0034] The catheters of the present invention may include a monorail delivery system to assist in positioning the cutter at the target site. For example, the tip of the catheter can include lumen (s) that are sized to receive a conventional guidewire (typically 0.014" diameter) or any other suitable guidewire (e.g., having diameters between 0.018" and 0.032") and the flexible proximal portion of the catheter body can include a short lumen (e.g., about 12 centimeters in length). Such a configuration moves the guidewire out of the rigid portion so as to not interfere with the debulking assembly.

[0035] In other embodiments, however, the guidewire lumen may be disposed within or outside the flexible proximal portion of the catheter body and run a longer or shorter length, and in fact may run the entire length of the flexible portion of the catheter body. The guidewire can be disposed within lumen on the flexible portion of the catheter body and exit the lumen at a point proximal to the rigid portion of the catheter. The guidewire can then enter a proximal opening in the tip lumen and exit a distal opening in the tip lumen. In some embodiments, the catheter has a distal guidewire lumen on its flexible distal tip and a proximal guidewire lumen on its flexible body. For example, in some embodiments the distal lumen may have a length of between about 2.0 cm and about 3.0 cm and the proximal lumen may have a length of between about 10 cm and about 14 cm. In yet further embodiments, a distal tip guidewire lumen may be configured to telescope within a proximal guidewire lumen, or vice versa. A telescoping guidewire lumen may enhance performance of the catheter by preventing a guidewire from being exposed within a body lumen.

[0036] The present invention may optionally employ any of a wide variety of conventional radiopaque markers, imaging devices, and/or transducers. In exemplary embodiments, the catheters of the present invention can include a radiopaque distal portion and/or radiopaque markers disposed on a distal portion of the catheter body, such as proximal and distal of the cutting window, on the cam or ramp, so as to allow the user to track the position of the cutter, or the like. The catheters of the present invention will also be particularly useful with ultrasonic transducers, such as an IVUS, of a type which may be deployed linearly within the catheter body or circumferentially on the debulking assembly. Linear deployment will allow viewing along a discrete length of the catheter axis, preferably adjacent to the cutting point, usually over a length in the range from 1 mm to 30 mm, preferably 2

mm to 10 mm. Circumferentially deployed phased arrays may subtend a viewing arc in the range from 5° to 360°, usually from 180° to 360°. For imaging transducers located on cutting blades within a housing or second cutting element, the field of imaging will generally be limited by the dimensions of the aperture. In some cases, however, it might be possible to fabricate all or a portion of the cutter blade/housing out of an ultrasonically translucent material. A more complete description of suitable imaging catheters are described more fully in U.S. Patent Application Serial No. 09/378,224, filed August 19, 1999, and entitled "Atherectomy Catheter with Aligned Imager", now U.S. Patent No., 6,299,622B1, the complete disclosure of which is incorporated herein by reference. In addition to ultrasonic array transducers, the imaging devices of the present invention may comprise optical coherence tomography devices, such as described in U.S. Patent No. 5,491,524, the full disclosure of which is incorporated herein by reference, as well as Huang et al. (1991) Science 254: 1178-1181; Brezinski et al. (1997) Heart 77: 397-403; and Brezinski et al (1996) Circulation 93: 1206-1213. In some instances, the present invention may also provide optical imaging using optical wave guides and the like.

[0037] Referring now to Figure 1, a catheter 20 constructed in accordance with principles of the present invention comprises a catheter body 22 having a proximal portion 24 and a distal portion 26. Proximal portion 24 can be coupled to distal portion 26 with a connection assembly 27 to allow pivoting or deflection of distal portion 26 relative to proximal portion 24. A proximal end of the catheter body 22 can have a handle 40 for manipulation by a user, a luer for connection to an aspiration or fluid delivery channel, or the like.

[0038] A debulking assembly, such as a cutter 28, abrasive member, or the like, is disposed within a lumen 30 of the catheter body 22. The cutter 28 is typically rotatable within the distal portion 26 about an axis that is parallel to the longitudinal axis of the distal portion 26 of catheter 20 and axially movable along the longitudinal axis. The cutter 28 can access target tissue through a side opening window 32 which is typically large enough to allow the cutter 28 to protrude through and move out of the window 32 a predetermined distance. The cutter is coupled to a cutter driver 34 through a coiled drive shaft 36. Actuation of a movable actuator or other input device 38 can activate the drive shaft 36 and cutter, move cutter 28 longitudinally over a cam so as to deflect the distal portion and move the cutter 28 out of cutting window 32. Camming of the cutter 28 can cause the distal portion 26 to pivot or deflect relative to the proximal portion 24 so as to deflect and urge the cutter into the tissue in the body lumen.

[0039] In some embodiments, the distal portion 26 of the catheter may be moved to an angled or offset configuration from the longitudinal axis of the proximal portion 24 of the catheter and the cutter 28. In some embodiments, the cutter 28 can also be deflected off of the axis

of the proximal and/or distal portion of the catheter. Moving the distal portion 26 to an angled/offset position may cause a portion of the catheter to urge against a target tissue, may expose the cutter 28 through the window 32 or both, in various embodiments.

[0040] In catheters 20 of the present invention, proximal portion 24 is typically relatively flexible and distal portion 26 is typically relatively rigid. Additionally, many embodiments include a flexible distal tip 42. The flexible proximal portion 24 of the catheter is typically a torque shaft and the distal portion 26 is typically a rigid tubing. The torque shaft 24 facilitates transportation of the catheter body 22 and cutter 28 to the diseased site. The proximal end of the torque shaft 24 is coupled to a proximal handle 40 and the distal end of the torque shaft is attached to the distal, rigid portion 26 of the catheter through the connection assembly 27. The drive shaft 36 is movably positioned within the torque shaft 24 so as to rotate and axially move within the torque shaft 24. The drive shaft 36 and torque shaft 24 are sized to allow relative movement of each shaft without interfering with the movement of the other shaft. The catheter body will have the pushability and torqueability such that torquing and pushing of the proximal end will translate motion to the distal portion 26 of the catheter body 22.

[0041] Referring now to Figure 1A, a catheter 20 as in Figure 1 may have a flexible proximal portion 24 which additionally includes urging means 25. As shown in Figure 1A, urging means 25 may comprise a rigid bent or curved shape towards the distal end of proximal portion 24, which may help urge the cutter 28 or other debulking apparatus toward a wall of a body lumen to enhance treatment. Such a rigid bend increases the working range of the catheter by allowing the cutter to be urged into a lumen wall across a wider diameter lumen.

[0042] In other embodiments, urging means 25 may take many other suitable forms. For example, a similar result to the rigid bend may be achieved by including a rigid distal portion that is not permanently bent but that is more rigid on one side than on the opposite side of catheter body 22. Thus, when proximal tension is applied to the proximal portion 24, as when proximal force is applied to the debulking apparatus to expose the cutter 28 through the window 32, the urging means 25 (i.e., the rigid distal portion of proximal portion 24) will cause the catheter body 22 to bend toward the less rigid side. The less rigid side will typically be the same side as the window 32, so that the window 32 and/or the cutter 28 will be urged against a wall of a body lumen by the bend. In still other embodiments, a shaped element may be introduced into catheter body to act as urging means 25. Any suitable urging means is contemplated.

[0043] Figure 2 illustrates an exploded view of a distal end of the catheter. In such embodiments, the catheter 10 includes a connection assembly 27, a rigid housing 26, a distal tip 42 that at least partially defines a collection chamber 53 for storing the severed atheromatous material, and a lumen that can receive the guidewire. The

distal tip 42 can have a distal opening 43 that is sized to allow an imaging guidewire or conventional guidewire (not shown) to be advanced distally through the tip. In some embodiments, the distal tip 42 may also include a distal guidewire lumen (not shown) for allowing passage of a guidewire. For example, some embodiments may include a distal guidewire lumen having a length of between about 1.0 cm and about 5.0 cm, and preferably between about 2.0 cm and about 3.0 cm. Such a distal guidewire lumen may be used alone or in conjunction with a proximal guidewire lumen located on another, more proximal, portion of the catheter 20.

[0044] In embodiments including a distal guidewire lumen and a proximal guidewire lumen, the distal lumen may be configured to partially telescope within a portion of the proximal guidewire lumen, or vice versa. Such telescoping lumens may be used in embodiments where the distal portion 26 of catheter body 22 is movable relative to the proximal portion 24. A telescoping lumen may enhance performance of the catheter 20 by allowing a guidewire to be maintained largely within a lumen and to not be exposed within the body lumen being treated. Telescoping lumens may have any suitable diameters and configurations to allow for sliding or otherwise fitting of one lumen within another.

[0045] A ramp or cam 44 can at least partially fit within the distal portion 26. As will be described in detail below, in many embodiments proximal movement of the cutter 28 over the ramp 44, causes the deflection of the distal housing 26 and guides cutter 28 out of cutting window 32. (In other embodiments, a ramp may be used to deflect the distal portion without extending the cutter out of the window.) Attached to the ramp 44 is a housing adaptor 46 that can connect one or more articulation member 48 to the distal tip to create an axis of rotation of the distal portion 26. The housing adaptor 46 and articulation member 48 allow the distal end of the catheter to pivot and bias against the body lumen. In the illustrated embodiment there are only one housing adaptor 46 and one articulation member 48, but it should be appreciated that the catheters of the present invention can include, two, three, or more joints (e.g., axis of rotation), if desired. Moreover, the axes of rotation can be parallel or non-parallel with each other.

[0046] The catheter can also include a shaft adaptor 50 and collar 52 to couple articulation member 48 to the torque shaft 22. Shaft adaptor 50 can connect the housing to the torque shaft and collar 52 can be placed over a proximal end of the shaft adaptor and crimped for a secure attachment. It should be appreciated by one of ordinary skill in the art that while one exemplary catheter of the present invention has the above components that other catheters of the present invention may not include more or fewer of the components described above. For example, some components can be made integral with other components and some components may be left out entirely. Thus, instead of having a separate ramp 44, the ramp may be integrated with the distal tip to direct

the cutter out of the cutting window.

[0047] As shown in Figures 3-5, the cutters 28 of the present invention will generally be movable between two or more positions. During advancement through the body lumen, the cutter will generally be in a neutral position (Figures 3A and 3B) in which the cutter 28 is distal of cutting window 32. In some embodiments, an imaging device (not shown) can be coupled to cutter 28 so as to image the body lumen through cutting window 32 when cutter 28 is in the neutral position. Once the catheter 20 has reached the target site, the cutter 28 can be moved to an open position (Figures 4A and 4B) in which the cutter 28 is moved to a proximal end of the cutting window 32 and will extend out of the cutting window 32 a distance L beyond an outer diameter D of the rigid portion 26. In most embodiments, in the open position, the cutter will have deflected the distal portion and the cutter's axis of rotation will generally be in line with connection assembly 27 but angled or offset from longitudinal axis of the distal portion of the catheter body.

[0048] Optionally, in some embodiments, cutter 28 can be moved to a packing position, in which the cutter is moved distally, past the neutral position, so as to pack the severed tissue into a distal collection chamber 53 (Figures 5A and 5B). It should be appreciated however, that while the exemplary embodiment moves the cutter to the above described positions, in other embodiments of the present invention the cutter can be positioned in other relative positions. For example, instead of having the neutral position distal of the cutting window, the neutral position may be proximal of the window, and the open position may be along the distal end of the cutting window, or the like.

[0049] Referring again to Figures 4A and 4B, the interaction of the components of the rigid distal portions 26 in one exemplary embodiment of the present invention will be further described. As shown in Figure 4B, the cutting window 32 is typically a cutout opening in the distal portion 26. While the size of the cutting window 32 can vary, the cutting window should be long enough to collect tissue and circumferentially wide enough to allow the cutter to move out of the cutting window during cutting, but sized and shaped to not expel emboli into the vasculature. Cams or ramp 44 (shown most clearly in Figure 4B) can be disposed in the distal portion of the catheter body to guide or otherwise pivot the cutter 28 out of the cutting window 32 as the cutter 28 is pulled proximally through tensioning of drive shaft 36.

[0050] A joint is located proximal to the cutting window 32 to provide a pivot point for camming of the distal portion 26 relative to the proximal portion 24. The bending at a flexible joint 49 is caused by the interaction of cams or ramps 44 with cutter 28 and the tensile force provided through drive shaft 36. In the exemplary configuration, the joint includes a housing adaptor 46 that is pivotally coupled to the distal rigid portion 26. As shown in Figures 4A and 4B, the resulting pivoting of the rigid distal portion 26 relative to the proximal portion causes a camming

effect which urges the distal housing against the body lumen wall without the use of urging means (e.g., a balloon) that is positioned opposite of the cutting window. Thus, the overall cross sectional size of the catheter bodies can be reduced to allow the catheter to access lesions in smaller body lumens. In exemplary embodiments, the distal housing can deflect off of the axis of the proximal portion of the catheter typically between 0 degrees and 30 degrees, usually between 5° degrees and 20° degrees, and most preferably between 5° degrees and 10° degrees. The angle of deflection relates directly to the urge. Urge, however, does not necessarily relate to force but more to the overall profile of the catheter. For example, the greater the angle of deflection, the larger the profile and the bigger the lumen that can be treated. The ranges were chosen to allow treatment of vessels ranging from less than 2 mm to greater than 3 mm within the limits of mechanical design of the components. It should be appreciated however, that the angles of deflection will vary depending on the size of the body lumen being treated, the size of the catheter, and the like.

[0051] In some embodiments, the deflection of the distal portion 26 of the catheter urges the cutter into position such that distal advancement of the entire catheter body can move the rotating cutter through the occlusive material. Because the cutter is moved a distance L_1 beyond the outer diameter of the distal portion of the catheter and outside of the cutting window, the user does not have to invaginate the tissue into the cutting window. In some embodiments, for example, the cutter can be moved between about 0.025 mm and about 1.016 mm, and preferably between about 0.025 mm and about 0.64 mm, beyond the outer dimension of the distal housing. It should be appreciated that the cutter excursion directly relates to the depth of cut. The higher the cutter moves out of the cutting window the deeper the cut. The ranges are chosen around efficacy without risk of perforation of the body lumen.

[0052] Some embodiments of the catheter include a shuttle mechanism or other similar mechanism for temporarily locking the catheter in a cutting position. Figures 3C and 3D illustrate such an embodiment in the neutral, non-cutting position. Such embodiments generally include a shuttle member 45 and a shuttle stop member 42. The shuttle stop member 42 is typically disposed at an angle, relative to a longitudinal axis through the catheter. Figures 4C and 4D show the same embodiment in the cutting position.

[0053] When the cutter 28 is moved into the cutting position in such embodiments, the shuttle member 45 falls into the shuttle stop member 42 and thus locks the debulking apparatus in a cutting position. To unlock the debulking apparatus, the cutter 28 may be advanced forward, distally, to release the shuttle member 45 from the shuttle stop member 42.

[0054] Some embodiments including a shuttle mechanism will also include two joints in catheter body 22. Thus, catheter body 22 will include a proximal portion 26,

a distal portion 24 and a middle portion. When shuttle mechanism is activated to expose cutter 28 through window 32, the middle portion may orient itself at an angle, relative to the proximal and distal portions, thus allowing cutter to be urged towards a side of a lumen. Such a two-jointed configuration may provide enhanced performance of the catheter 20 by providing enhanced contact of the cutter 28 with material to be debulked from a body lumen.

[0055] Pushing the entire catheter across a lesion removes all or a portion of the lesion from the body lumen. Severed tissue from the lesion is collected by directing it into a collection chamber 53 in the tip via the cutter 28. Once the catheter and cutter 28 have moved through the lesion, the cutter 28 can be advanced distally to a "part off position" in which the cutter is moved back into the cutting window 32 (Figure 3B). The tissue is collected as the severed pieces of tissue are directed into a collection chamber 53 via the distal movement of cutter 28 and catheter. The collection chamber 53 of the tip and distal portion 26 acts as a receptacle for the severed material, to prevent the severed occlusive material from entering the body lumen and possibly causing downstream occlusions. The cutter 28 can interact with the distal edge of the cutting window to part off the tissue and thereafter pack the severed tissue into collection chamber 53 (Figure 3B). In exemplary embodiments, the driver motor can be programmed to stop the rotation of the cutter at the part off position so that the cutter 28 can move to a third position (Figure 5B) and pack the material in the collection chamber in the tip without rotation. Typically, the collection chamber 53 will be large enough to allow multiple cuts to be collected before the device has to be removed from the body lumen. When the collection chamber is full, or at the user's discretion, the device can be removed, emptied and reinserted over the guidewire via a monorail system, as will be described below.

[0056] In various embodiments, enhancements to the collection chamber 53 may be included. For example, in some embodiments the collection chamber 53 may be configured to be partially or completely translucent or radiolucent and a portion of the catheter surrounding or adjacent to the window 32 will be radiopaque. This combination of radiolucent collection chamber 53 and radiopaque material adjacent window 32 will enhance the ability of a user to determine how full the collection chamber 53 is, because the fullness of the collection chamber will be directly related to the distance the cutter 28 can advance forward into the collection chamber 53. By facilitating the assessment of collection chamber filling, these embodiments will reduce the need for manually withdrawing the catheter to examine the collection chamber 53.

[0057] In some embodiments, the collection chamber 53 may connect to the rigid housing by means of interlocking components, which interlock with complementary components on the rigid housing. Such components may resemble a screw-in configuration, for example. Inter-

locking components will provide a stable connection between the collection chamber 53 and the rigid housing while not increasing the outer diameter of either the chamber 53 or the housing. Generally, collection chamber 53 may be given any suitable configuration, shape or size. For example, collection chamber 53 in Figures 6-8 has a helical configuration. Alternatively, collection chamber 53 may include a series of circular members, straight linear members, one solid cylindrical or cone-shaped member or the like.

[0058] Figures 6 through 8 illustrate one exemplary monorail delivery system to assist in positioning the cutter 28 at the target site. For example, tip 42 of the catheter can include a lumen 54 having a distal opening 43 and a proximal opening 55 that is sized to receive a guidewire, having a diameter of about 0.014 in., about 0.018 in., about 0.032 in. or any other suitable diameter.

[0059] As shown in Figure 8, the flexible proximal portion of the catheter body may also include a short lumen 56 (e.g., about 12 centimeters in length). In some embodiments, however, the guidewire lumen 56 may be disposed within or outside the flexible proximal portion of the catheter body and run a longer or shorter length, and in fact may run the entire length of the flexible portion 24 of the catheter body. In use, the guidewire can be disposed within lumen 56 on the flexible portion of the catheter body and exit the lumen at a point proximal to the rigid portion 26 of the catheter. The guidewire can then re-enter a proximal opening 55 in the tip lumen 54 and exit through distal opening 43 in the tip lumen. By moving the guidewire outside of the rigid portion 26 of the catheter body, the guidewire will be prevented from tangling with the cutter 28. Typically, tip lumen 54 will be disposed along a bottom surface of the tip and the lumen 56 will be disposed along a side of the proximal portion 22 of the catheter body so that the guidewire will be in a helical configuration. In various embodiments, the tip lumen 54 and the proximal lumen 56 can have any suitable combination of lengths. For example, in one embodiment the tip lumen 54 may have a length between about 1 cm and about 5 cm, more preferably between about 2 cm and about 3 cm, and the proximal lumen may have a length of between about 8 cm and about 20 cm, more preferably between about 10 cm and about 14 cm.

[0060] Referring now to Figures 22A and 22B, some catheters 120 of the present invention include a proximal guidewire lumen 126 coupled with the proximal portion of the catheter body 123, and a telescoping distal guidewire lumen 124 coupled with either the distal tip 122, part of the distal portion of the catheter body, or both. The telescoping lumen 124 will typically be attached to the tip 122 or a distal portion, but will also include an unattached portion 121, which will not be directly attached to any part of the catheter body. This unattached portion 121 (or "free floating lumen") protects a guidewire from contacting a body lumen in which the device is used and also allows the device to be moved more freely, without bending or kinking the guidewire. The telescoping

guidewire 124 extends within the proximal lumen 126 at the distal opening 127 of proximal lumen 126. Again, the telescoping feature allows for movement of the catheter body while preventing or reducing bending of the guidewire. For example, in some embodiments catheter 120 allows for deflection of distal tip 122 and the distal portion of the catheter 120 relative to the proximal portion 123, for example by movement about a pivot point 129. Telescoping distal lumen 124 and proximal lumen 126 allow for this movement by allowing distal lumen 124 to telescope within proximal lumen 126. At the same time, distal lumen 124 protects a guide wire from exposure to a body lumen and/or bodily fluids.

[0061] Any suitable configurations and sizes of distal lumen 124 and proximal lumen 126 are contemplated. For example, in one embodiment distal lumen 124 may telescope within proximal lumen 126 by a distance of approximately 1 cm. Furthermore, a telescoping lumen 124 may be longer than distal lumens in other embodiments. For example, telescoping lumen 124 may have a length of between about 2 cm and about 10 cm, and preferably between about 5 cm and about 8 cm. As is apparent from the drawing figures, the outer diameter of telescoping distal lumen 124 is configured to fit within the inner diameter of proximal lumen 126. Generally, any combination of sizes, lengths, diameters and shapes of distal lumen 124 and proximal lumen 126 may be used, to allow telescoping of one into another.

[0062] The catheters of the present invention can include radiopaque markers so as to allow the user to track the position of the catheter under fluoroscopy. For example, as already described, a point or area around or adjacent to the window may be made radiopaque. In other embodiments, the rigid distal portion 26 can be radiopaque and radiopaque markers can be disposed on the flexible shaft. Typically, the markers 59 will be disposed along the top, proximal to the cutting window, and on the bottom of the catheter to let the user know the position of the cutter and cutting window relative to the target site. If desired, the top and bottom markers can be different shaped so as to inform the user of the relative orientation of the catheter in the body lumen. Because the guidewire will form a helix in its transition from lumen 56 to tip lumen 54, the user will be able to view the top and bottom radiopaque markers 59 without interference from the guidewire. Some embodiments of the catheter can also include a radiopaque cutter stop 61 (Figure 3B) that is crimped to driveshaft 36 proximal of the cutter that moves with the cutter so as to let the user know when the cutter is in the open position.

[0063] Figures 9A through 1 D show some exemplary embodiments of the cutter 28 of the present invention. The distal portion 60 of the rotatable cutter 28 can include a serrated knife edge 62 or a smooth knife edge 64 and a curved or scooped distal surface 66. The distal portion 60 may have any suitable diameter or height. In some embodiments, for example, the diameter across the distal portion 60 may be between about 0.1 cm and about 0.2

cm. A proximal portion 68 of the cutter 28 can include a channel 70 that can be coupled to the drive shaft 36 that rotates the cutter. As shown in Figures 10A-10C, some embodiments of the cutters can include a bulge or bump 69 that is provided to interact with a stent so as to reduce the interaction of the cutting edge with the stent. In any of the foregoing embodiments, it may be advantageous to construct a serrated knife edge 62, a smooth knife edge 64, or a scooped distal surface 66 out of tungsten carbide.

[0064] Another embodiment of a cutter 28 suitable for use in the present invention is shown in side view within a catheter body distal portion 26 in Figure 1. In this embodiment, the cutter 28 has a beveled edge 64, made of tungsten carbide, stainless steel, titanium or any other suitable material. The beveled edge 64 is angled inward, toward the axis of rotation (or center) of the cutter 28, creating a "negative angle of attack" 65 for the cutter 28. Such a negative angle of attack may be advantageous in many settings, when one or more layers of material are desired to be debulked from a body lumen without damaging underlying layers of tissue. Occlusive material to be removed from a vessel typically has low compliance and the media of the vessel (ideally to be preserved) has higher compliance. A cutter 28 having a negative angle of attack may be employed to efficiently cut through material of low compliance, while not cutting through media of high compliance, by allowing the high-compliance to stretch over the beveled surface of cutter 28.

[0065] Figures 12 through 16 illustrate an exemplary cutter driver 34 of the present invention. As shown in Figure 12 and 13, cutter driver 34 can act as the handle for the user to manipulate the catheters 20 of the present invention as well as a power source.

[0066] Typically, the cutter drivers 34 of the present invention include a single input device, such as a lever 38 that controls the major operations of the catheter (e.g., axial movement to cause urging, rotation to cause cutting, and axial movement for packing). As shown in Figures 13 and 14, cutter driver 34 includes a power source 72 (e.g., batteries), a motor 74, a microswitch 76 for activating motor 74, and a connection assembly (not shown) for connecting the drive shaft 36 to the driver motor 74. In some embodiments, the drive motor can rotate drive shaft 36 between 1,000 rpm and 10,000 rpm or more, if desired.

[0067] Figures 14 through 16 illustrate one exemplary method of operating cutter driver 34. In use, the catheter will be delivered to the target site with cutter driver unattached and the cutter in the neutral position (Figure 3B). The cutter driver can be attached with the urge lever 38 in a neutral position (Figure 14), which indicates that the cutter is closed, but not in a packing position. The user can then move the catheter (and cutter driver unit, if desired) to position the distal portion 26 of the catheter adjacent the target tissue. As shown in Figure 15, to activate the rotation of the cutter, the urge lever 38 can be moved proximally from the neutral position to move the cutter

proximally and out of cutting window 32 (Figure 4B) and simultaneously depressing microswitch 76 to activate motor 74. At the end of the cutting procedure, as shown in Figure 16, the user can push urge lever 38 completely forward to a distal position to push the cutter into a packing position (Figure 5B). After the urge lever passes the middle of the travel, the microswitch 76 can be released so as to deactivate the cutter before reaching the packing position such that packing can occur without the cutter rotating. It should be appreciated, while the figures illustrate the use of an urge lever or thumb switch as an input device, the present invention can use other type of input devices, such as labeled buttons (e.g., close window, debulk tissue, and pack), or the like.

[0068] Advantageously, cutter driver 34 provides an automatic on/off control of the cutter 28 that is keyed to the position of the cutter. Such a configuration frees the user from the complicated task of remembering the sequence of operations to activate and deactivate the rotation and axial movement of the cutter.

[0069] While the cutter driver 34 is illustrated as a disposable battery powered unit, it should be appreciated that in other embodiments, the cutter driver can use other power sources to control the cutter driver. It should further be appreciated that other cutter drivers can be used with the present invention. While not preferred, it is possible to have separate controls to control the axial movement of the cutter and the rotation of the cutter.

[0070] Some exemplary methods of the present invention will now be described. One method of the present invention comprises delivering a catheter to a target site in the body lumen. A distal portion of the catheter can be deflected relative to a proximal portion of the catheter to expose a tissue debulking device in the catheter. The body lumen can be debulked with the exposed debulking device. Specifically, as shown schematically in Figure 17, one specific method comprises advancing a catheter to a target site (Step 100). A cutter can be rotated and moved out of the cutting window (Steps 102, 104). Preferably, a distal portion of the catheter can be pivoted or deflected so as to position the cutter adjacent the target material. Thereafter, the catheter and the rotating cutter can be moved through the body lumen to remove the target material from the body lumen (Step 106).

[0071] As shown in Figures 18 and 19, the catheter can be percutaneously advanced through a guide catheter or sheath and over a conventional or imaging guidewire using conventional interventional techniques. The debulking catheter 20 can be advanced over the guidewire and out of the guide catheter to the diseased area. As shown in Figure 18, the window 32 will typically be closed (with the cutter or other debulking device 28 in a first, distal position). As shown in Figure 19, catheter 20 will typically have at least one hinge or pivot connection to allow pivoting about one or more axes of rotation to enhance the delivery of the catheter into the tortuous anatomy without dislodging the guide catheter or other sheath. The cutter can be positioned proximal of the le-

sion. Optionally, a transducer, IVUS, or other imaging assembly can be used to verify the position of the debulking catheter.

[0072] Once the position of the catheter is confirmed, the cutter 28 will be retracted proximally and moved out of cutting window 32 to its second, exposed position. In some embodiments, movement of the cutter can deflect the distal portion of the catheter to increase the profile of the catheter at the target site. Movement of the cutter is typically caused by proximal movement of lever 38 and tensioning of drive shaft 36. Movement of the lever can be scaled to any desired ratio or a direct 1: 1 ratio of movement between the handle and cutter. When the cutter is moved proximally it contacts ramp or cam surfaces so as to guide the cutter up and at least partially out of the cutting window 32. Additionally, as shown by arrow 80, the distal portion of catheter body 26 rotates about the joint 49 to provide an urging force for the cutter (and catheter body) to move toward the diseased area.

[0073] Thereafter, as shown by arrow 82 the operator can move the entire catheter body 22 through the lesion to dissect the tissue. As the cutter 28 and catheter body 22 are advanced distally through the lesion, tissue that is trapped between the cutting edge 52 and the cutting window 32 is severed from the body lumen. To part off the tissue, the operator can stop pushing the device distally and the cutter can be advanced distally inside the cutting window by advancing the handle 38. During the distal movement of the cutter, the cutter 28 rides back over the ramps 44 and directs the cutter back inside of the cutting window 32. Such movement causes the distal portion 26 of the catheter to move in line with the cutter and proximal portion 24 (Figure 5B). When the cutter has moved to its distal position, the cutter parts off the severed tissue and urges the severed tissue inside of a collection chamber 53 in the distal tip 42. Optionally, after the cutter 28 has parted off the tissue, the lever 38 and thus the non-rotating cutter 38 can be advanced distally to pack the tissue into the collection chamber 53 (Figure 5B). Use of the cutter to pack the severed tissue will allow the operator multiple specimens to be collected prior to removing the catheter 20 from the body lumen. When it is determined that the collection chamber is full, the catheter can be removed from the body lumen and the collection chamber can be emptied.

[0074] In another method of the present invention, as shown in Figure 20, an input device is disposed in a first position to position a tissue removal element in a neutral position (Step 120). The input device is activated to rotate the tissue removal element and to axially move the tissue removal device to an active position (Step 122). The input device can then be activated again to move the tissue removal element to a packing position (Step 124). In an exemplary embodiment, the input device is a lever or thumb switch that can be moved to correspond to the movement of a cutting element on the catheter. Thus, as the lever is moved proximally, the cutter is rotated and moved proximally to an open position. When the lever is

moved to a distal position, the rotation of the cutter can be stopped and the cutter can be moved distally to pack severed tissue into a collection chamber.

[0075] Referring to Figures 21-24, still another device 102 for cutting and/or removing material is shown. The device 102 has a cutting element 104 which may be any suitable cutting element 104 such as those described herein. The device 102 has an elongate body 106 and a visualization element 114 coupled to the body 106. A cover or tip 108 is positioned at the distal end of the device 102. The cover 108 is movable from the stored position of Figures 21 and 22 to the working position of Figure 23 in which at least part of the cutting element 104 is exposed [0112] The cover 108 may be movable relative to the elongate body 106 in any suitable manner. For example, the cover 108 and body 106 may engage one another with a slot and pin engagement 107 so that the cover 108 translates linearly relative to the body 106. The cover 108 may be naturally biased or held in the stored position with the user actuating the device to move the cover 108 to the working position. For example, the cover 108 may be coupled to a lumen 110, such as a guidewire lumen, with the user tensioning, or even compressing, the lumen 110 and/or body 106 to move the cover 108 to the working position. The cover 108 has a longitudinal axis which may remain substantially parallel to the longitudinal axis of the elongate body 106. Furthermore, the cover 108 may be movable to a number of different positions which expose varying amounts of the cutting element 104 so that the depth of cut may be selected or varied by the user. The cover or tip 108 may have a recess or cavity 112 in which material to be removed is held as is described herein.

[0076] The visualization element 114 may be any suitable visualization element such as a fiberoptic and lens or an ultrasound element. The visualization element 114 may be movable or fixed relative to the body 106. The visualization element 114 is positioned on a radially outer, and preferably outermost, portion of the body 106 so that the element 114 may be pressed against or moved adjacent to the tissue of interest. This may provide advantages when using certain types of visualization elements 114 such as optical elements which may emit or receive energy which is partially absorbed by blood or other fluids present. Various examples of a suitable visualization element are described in U.S. Patent Nos. 6,191,862, 6,445,939, 6,134,003, 5,459,570 and 5,321,501 which are hereby incorporated by reference.

[0077] Referring to Figures 24 and 25, still another device 130 for cutting and/or removing material is shown wherein the same or similar reference numbers refer to the same or similar structure. The device 130 may be used to cut or remove material from a vascular location using any method described herein. The device 130 has the cutting element 104 which may be coupled to the torque transmitting element extending through the elongate body 106. A first pivot point 132 and a second pivot point 134 are positioned on opposite sides of the cutting

element 104. When moving to the working position of Figure 25, the cutting element 104 moves into engagement with the tissue to be cut or removed. The device 130 may also have the visualization element 114 positioned on the radially outermost part of the device 130. The visualization element may be moved from the stored position of Figure 24 to the working position of Figure 25. The device 130 has a tip 135 which has a recess or cavity 112 or other structure to receive material to be removed. The device 130 may be naturally biased toward the working or stored position with the other position being created by tensioning a pull wire 137 on one or the other side of the device 130.

[0078] Referring to Figures 26A and 26B, another device 140 is shown having an elongate body 142 which is deformable to a generally helical shape. The elongate body 142 is moved to the deformed or helical shape to help stabilize the device 140 within the vessel. Stabilization of the device 140 may be particularly helpful when moving the entire device 140 through the vessel when removing material as described herein. The helical shape of the body may help to stabilize the device, depending upon the particular shape of the vasculature, and may specifically help resist or reduce twisting of the device 140 within the vasculature as the device is advanced during cutting. The helical shape may be formed in any suitable manner. Referring to Figures 27A and 27B, for example, a tube 144 may be cut with a pattern which naturally forms the helical shape when a compressive force is applied to the tube 144. The tube 144 is contained in a sheath 146 which holds the tube 144 but permits the tube 144 to deform as necessary. As can be appreciated from Figures 26A and 26B, the helical shape may be somewhat subtle. Surface lines 145 have been added for clarity in visualizing the shape of the body 142. In one embodiment, the diameter of the body 142 is 1.0 to 2.5 mm while the diameter of the helical shape is about 2.0 to 7.5 mm. In still another aspect, the helical shape has less than 360 degrees of rotation over its length and preferably about 180 degrees. The deformed part of the elongate body 142, 152 may be relatively long. For example, the deformed part may be at least 1 cm and may even be at least 2 cm when measured in a relaxed or straightened configuration. Of course, the elongate body 142 which may also be deformed to a generally S-shape rather than helical shape.

[0079] The shaft or body of Figures 26A and 26B may be used with any of the devices or methods described herein. For example, the helical body 142 may be used with the device 102 of Figures 21-23. Initial compression of the tube 144 may cause the body 142 to assume the helical shape. Continued compression of the tube 144 displaces the tip or cover 108 to expose the cutting element. The entire device 102 may then be moved through the vessel to cut a continuous piece of material which is directed into the recess or cavity 112 in the cover 108. Thus, it can be appreciated that many combinations are within the scope of the present invention with any of the

working ends of the device being used with any of the shafts or elongate bodies.

[0080] Referring now to Figure 28, the present invention will further comprise kits including catheters 200, instructions for use 202, and packages 204. Catheters 200 will generally be as described above, and the instruction for use (IFU) 202 will set forth any of the methods described above. Package 204 may be any conventional medical device packaging, including pouches, trays, boxes, tubes, or the like. The instructions for use 202 will usually be printed on a separate piece of paper, but may also be printed in whole or in part on a portion of the packaging 204.

[0081] While all the above is a complete description of the preferred embodiments of the inventions, various alternatives, modifications, and equivalents may be used. For example, while preferred cutters are moved proximally to move the cutter out of the cutting window, alternative embodiments may move the cutter distally to move the cutter out of the cutting window. Additionally, while most embodiments employ a cutter that extends out beyond the outer diameter of the cutting window, it may be possible to incorporate a cutter that stays within the diameter catheter body. Additionally, in some embodiments, the debulking assembly may be exposed through the window without causing a deflection of the distal portion of the catheter. Moreover, instead of having a distal tip that is rotatable relative to the proximal portion of the catheter, the catheter can include a shape memory material such that the catheter forms a jog or a pre-bent shape when it reaches its target area.

[0082] Although the foregoing invention has been described in detail for purposes of clarity of understanding, it will be obvious that certain modifications may be practiced within the scope of the appended claims.

Claims

1. A device for cutting tissue (140), comprising:

an elongate body (142) having an opening therein, the elongate body (142) having a longitudinal axis, the elongate body (142) further having a portion which is selectively deformable from a relatively straight shape to a generally helical shape; and


a rotatable cutting element (104) having a torque transmitting element extending through the elongate body (142), the cutting element (104) being configured to move with respect to the elongate body (142) from a stored position, in which the rotatable cutting element (104) is covered by the elongate body, to a working position, in which at least part of the rotatable cutting element (104) is exposed from the elongate body (142).

2. The device (140) of claim 1 wherein the rotatable cutting element (140) is moved from the stored position to the working position upon deformation of the elongate body (142) from the relatively straight shape to the generally helical shape. 5
3. The device (140) of claim 1 or claim 2, further comprising: a visualization element movable from a stored position to a working position. 10
4. The device (140) of claim 3, wherein:

the visualization element moves to a position proximate to the opening of the elongate body (142) at a position radially outward relative to the opening when moving to the working position. 15
5. The device (140) of claim 3 or claim 4, wherein: 20

the visualization element emits energy selected from the group of ultrasound and infrared.
6. The device (140) of any preceding claim further including a tip having a tissue collection chamber, wherein tissue cut by the cutting element is directed into the collection chamber. 25
7. The device (140) of any preceding claim, wherein: the tip is disposed at the distal end of the elongate body. 30
8. The device (140) of any preceding claim, wherein the selectively deformable portion of the elongate body is at least 1 cm. 35
9. The device (140) of any preceding claim, wherein the selectively deformable portion of the elongate body (142) is at least 2 cm. 40
10. The device (140) of any preceding claim, wherein a diameter of the elongate body (142) is 1.0 to 2.5 mm and a diameter of the generally helical shape is about 2.0 to 7.5 mm. 45
11. The device (140) of any preceding claim, wherein the deformable portion is configured to deform from the relatively straight shape to the generally helical shape upon compression. 50

55







FIG. 1A






FIG. 3A




FIG. 3B




FIG. 3D




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 4C






FIG. 4D








FIG. 8




FIG. 9A




FIG. 9B










FIG. 9C








FIG. 11D




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26A




FIG. 26B




FIG. 27A




FIG. 27B




FIG. 28



EUROPEAN SEARCH REPORT

Application Number
EP 12 16 5347

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	WO 01/15609 A1 (FOX HOLLOW TECHNOLOGIES [US]) 8 March 2001 (2001-03-08) * page 5, line 31 - page 6, line 18 * * page 8, line 29 - page 9, line 13 * * page 9, line 32 - page 10, line 14 * * page 10, line 24 - page 11, line 12 * * page 15, lines 12-34 * * figures 1,2A-C,3A,3B,11A * -----	1,3-11	INV. A61B17/3207
X,D	US 2002/077642 A1 (PATEL HIMANSHU [US] ET AL) 20 June 2002 (2002-06-20) * paragraphs [0053], [0064] - [0069], [0072], [0073]; figures 1,3B,4B,5B,6 * -----	1,3-11	
			TECHNICAL FIELDS SEARCHED (IPC)
			A61B
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 11 June 2012	Examiner Maier, Christian
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

 1
EPO FORM 1503 03.02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 12 16 5347

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-06-2012

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 0115609 A1	08-03-2001	NONE	

US 2002077642 A1	20-06-2002	AT 499054 T	15-03-2011
		AU 3107402 A	01-07-2002
		EP 1345542 A2	24-09-2003
		EP 2353526 A1	10-08-2011
		JP 4080874 B2	23-04-2008
		JP 2004516073 A	03-06-2004
		US 2002077642 A1	20-06-2002
		WO 0249690 A2	27-06-2002

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 288581 A [0001]
- US 02741801 A [0001]
- US 60257704 B [0001]
- US 60272273 B [0001]
- US 60381632 B [0002]
- US 37788499 A [0003]
- US 09377894 B [0003]
- US 5674232 A [0033]
- US 5242460 A [0033]
- US 5312425 A [0033]
- US 5431673 A [0033]
- US 4771774 A [0033]
- US 37822499 A [0036]
- US 6299622 B1 [0036]
- US 5491524 A [0036]
- US 6191862 B [0076]
- US 6445939 B [0076]
- US 6134003 A [0076]
- US 5459570 A [0076]
- US 5321501 A [0076]

Non-patent literature cited in the description

- HUANG et al. *Science*, 1991, vol. 254, 1178-1181 [0036]
- BREZINSKI et al. *Heart*, 1997, vol. 77, 397-403 [0036]
- BREZINSKI et al. *Circulation*, 1996, vol. 93, 1206-1213 [0036]

专利名称(译)	用于切割组织的方法和装置		
公开(公告)号	EP2481364A1	公开(公告)日	2012-08-01
申请号	EP2012165347	申请日	2004-04-22
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	泰科医疗集团LP		
当前申请(专利权)人(译)	泰科医疗集团LP		
[标]发明人	SIMPSON JOHN B ROSENTHAL MICHAEL PATEL HIMANSHU VENEGAS GAUTAMA		
发明人	SIMPSON, JOHN B. ROSENTHAL, MICHAEL PATEL, HIMANSHU VENEGAS, GAUTAMA		
IPC分类号	A61B17/3207 A61B A61B17/00 A61B17/22 A61B17/28 A61B17/29 A61B17/32 A61B19/00		
CPC分类号	A61B17/320758 A61B17/320783 A61B2017/00685 A61B2017/2927 A61B2017/320032 A61B2017/320791 A61B2090/306 A61B2090/373 A61B2090/3782 A61B1/00087 A61B1/05 A61B1/3137 A61B5/0036 A61B5/0066 A61B5/0084 A61B5/02007 A61B5/4836 A61B2017/320064		
代理机构(译)	灰色, JAMES		
审查员(译)	MAIER, CHRISTIAN		
优先权	10/421979 2003-04-22 US		
其他公开文献	EP2481364B1		
外部链接	Espacenet		

摘要(译)

从血流腔移除材料的方法通常包括提供具有切割元件 (104) 和开口的装置 (140) , 使装置穿过血流腔前进到要移除材料的位置, 从而迫使开口朝向要移除材料的部位的壁, 并移动切割元件和开口, 使得切割元件切割血流腔中的材料, 并且当切割元件和开口移动时, 切割元件中的材料被引导到开口中以便移除通过血流腔。在一些实施例中, 装置可以被偏转或弯曲以迫使开口朝向墙壁以移除材料。切割元件可以是可旋转的并且可以具有可移动的轴, 该轴不平行于装置的纵向轴, 或两者。在一些实施例中, 切割元件可在缩回和展开位置之间移动, 以分别将装置推进到用于处理和移除材料的位置。




FIG. 1