



US 20150119916A1

(19) **United States**(12) **Patent Application Publication**
Dietz et al.(10) **Pub. No.: US 2015/0119916 A1**(43) **Pub. Date: Apr. 30, 2015**(54) **ULTRASONIC SURGICAL INSTRUMENTS
WITH MOVING CUTTING IMPLEMENT****Publication Classification**(71) Applicant: **Ethicon Endo-Surgery, Inc.**, Cincinnati,
OH (US)(72) Inventors: **Timothy G. Dietz**, Wayne, PA (US);
Gregory W. Johnson, Milford, OH
(US); **Sean P. Conlon**, Loveland, OH
(US); **Daniel J. Mumaw**, Sandton (ZA);
Jerome R. Morgan, Cincinnati, OH
(US); **William D. Dannaher**, Cincinnati,
OH (US); **Omar J. Vakharia**,
Cincinnati, OH (US); **Richard W.**
Timm, Cincinnati, OH (US); **Matthew**
C. Miller, Cincinnati, OH (US); **Galen**
C. Robertson, Apex, NC (US)(51) **Int. Cl.****A61B 17/32** (2006.01)**A61B 17/3207** (2006.01)**A61B 17/22** (2006.01)(52) **U.S. Cl.**CPC ... **A61B 17/320068** (2013.01); **A61B 17/22004**
(2013.01); **A61B 17/3207** (2013.01); **A61B**
17/320783 (2013.01); **A61B 2017/00778**
(2013.01)

(57)

ABSTRACT

In various embodiments, a surgical instrument for operation in an aqueous environment is provided. In at least one embodiment, the surgical instrument may include a hollow sheath and a blade disposed at least partially within the sheath. Coupled to the blade may be at least one ultrasonic transducer, which, in turn, may be coupled to a drive system. The drive system may be configured to deliver gross axial motions to the blade such that the blade translates with respect to the hollow sheath when the drive system is activated. Accordingly, tissue may be cut by the blade with gross axial movement of the blade and/or ultrasonic vibrational motion provided by the ultrasonic transducer(s). In alternative embodiments, the blade may be rotated axially instead of translated with respect to the hollow sheath.


(21) Appl. No.: **14/590,574**(22) Filed: **Jan. 6, 2015****Related U.S. Application Data**(62) Division of application No. 12/703,893, filed on Feb.
11, 2010, now Pat. No. 8,961,547.

Fig. 1




Fig. 1A




Fig. 1B




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6A








Fig. 6B








Fig. 11




Fig. 12A




Fig. 12B




Fig. 12C




Fig.13









Fig. 14













Fig. 22






Fig. 25









Fig. 26










Fig. 39




Fig. 38




Fig.40







Fig.41



ULTRASONIC SURGICAL INSTRUMENTS WITH MOVING CUTTING IMPLEMENT

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a divisional application claiming priority under 35 U.S.C. § 121 to U.S. patent application Ser. No. 12/703,893, entitled **ULTRASONIC SURGICAL INSTRUMENTS WITH MOVING CUTTING IMPLEMENT**, filed Feb. 11, 2010, now U.S. Patent Application Publication No. 2011/0196404, the entire disclosure of which is hereby incorporated by reference herein.

BACKGROUND

[0002] The present disclosure generally relates to ultrasonic surgical systems and, more particularly, to ultrasonic systems that allow surgeons to perform cutting and coagulation of tissue.

[0003] Over the years, a variety of different types of non-ultrasonically powered cutters and shaving devices for performing surgical procedures have been developed. Some of these devices employ a rotary cutting instrument and other devices employ a reciprocating cutting member. For example, shavers are widely used in arthroscopic surgery. Arthroscopic surgery involves performing surgery in the joint space. To perform the surgery, the joints are commonly filled with pressurized saline for distention and visualization.

[0004] The aforementioned devices generally consist of a power supply, a handpiece, and a single-use end effector. The end effector commonly has an inner and outer tube. The inner tube rotates relative to the outer tube and will cut tissue with its sharpened edges. The inner tube can rotate continuously or oscillate. In addition, such device may employ a suction channel that travels through the interior of the inner tube. For example, U.S. Pat. No. 4,850,354 to McGurk-Burleson, et al., discloses a non-ultrasonically powered surgical cutting instrument that comprises a rotary cutter for cutting material with a shearing action. It employs an inner cutting member which is rotatable within an outer tube.

[0005] U.S. Pat. No. 3,776,238 to Peyman et al. discloses an ophthalmic instrument in which tissue is cut by a chopping action set-up by the sharp end of an inner tube moving against the inner surface of the end of an outer tube. U.S. Pat. No. 5,226,910 to Kajiyama et al. discloses another surgical cutting instrument that has an inner member which moves relative to an outer member to cut tissue entering through an aperture in the outer member.

[0006] U.S. Pat. No. 4,922,902 to Wuchinich et al. discloses a method and apparatus for endoscopic removal of tissue utilizing an ultrasonic aspirator. The device uses an ultrasonic probe which disintegrates compliant tissue and aspirates it through a narrow orifice. U.S. Pat. No. 4,634,420 to Spinosa et al. discloses an apparatus and method for removing tissue from an animal and includes an elongated instrument having a needle or probe, which is vibrated at an ultrasonic frequency in the lateral direction. The ultrasonic movement of the needle breaks-up the tissue into fragments. Pieces of tissue can be removed from the area of treatment by aspiration through a conduit in the needle. U.S. Pat. No. 3,805,787 to Banko discloses yet another ultrasonic instrument that has a probe that is shielded to narrow the beam of ultrasonic energy radiated from the tip of the probe. In one embodiment the shield extends past the free-end of the probe

to prevent the probe from coming into contact with the tissue. U.S. Pat. No. 5,213,569 to Davis discloses a phaco-emulsification needle which focuses the ultrasonic energy. The focusing surfaces can be beveled, curved or faceted. U.S. Pat. No. 6,984,220 to Wuchinich and U.S. Patent Publication No. U.S. 2005/0177184 to Easley disclose ultrasonic tissue dissection systems that provide combined longitudinal and torsional motion through the use of longitudinal-torsional resonators. U.S. Patent Publication No. U.S. 2006/0030797 A1 to Zhou et al. discloses an orthopedic surgical device that has a driving motor for driving an ultrasound transducer and horn. An adapter is provided between the driving motor and transducer for supplying ultrasonic energy signals to the transducer.

[0007] While the use of ultrasonically powered surgical instruments provide several advantages over traditional mechanically powered saws, drills, and other instruments, temperature rise in bone and adjacent tissue due to frictional heating at the bone/tissue interface can still be a significant problem. Current arthroscopic surgical tools include punches, reciprocating shavers and radio frequency (RF) devices. Mechanical devices such as punches and shavers create minimal tissue damage, but can sometimes leave behind ragged cut lines, which are undesirable. RF devices can create smoother cut lines and also ablate large volumes of soft tissue; however, they tend to create more tissue damage than mechanical means. Thus, devices which could provide increased cutting precision while forming smooth cutting surfaces without creating excessive tissue damage would be desirable.

[0008] The foregoing discussion is intended only to illustrate the present field and should not be taken as a disavowal of claim scope.

SUMMARY

[0009] In various embodiments, a surgical instrument is provided. In at least one embodiment, the surgical instrument can comprise a hollow sheath, a blade disposed at least partially within the hollow sheath, at least one ultrasonic transducer operably coupled to the blade, and a drive system. In these embodiments, the drive system can communicate with the transducer to deliver axial motions to the blade such that the blade translates with respect to the hollow sheath when the drive system is activated.

[0010] In at least one embodiment, a surgical instrument is provided that can comprise a hollow sheath, a blade disposed at least partially within the hollow sheath, at least one ultrasonic transducer coupled to the blade, and a drive system. In these embodiments, the drive system can communicate with the transducer to deliver rotational motions to the blade such that the blade rotates with respect to the hollow sheath when the drive system is activated. Further, in these embodiments, the hollow sheath can include at least one opening therein and at least one tooth positioned in the opening. Moreover, in these embodiments, the tooth can be configured to grip tissue positioned within the opening.

[0011] In at least one embodiment, a surgical instrument is provided that can comprise a hollow sheath including at least one opening therein, a blade disposed at least partially within the hollow sheath, an ultrasonic transducer coupled to the blade, a tissue gripping member movably supported by the hollow shaft, and a drive system coupled to the tissue gripping member. In these embodiments, the drive system can be configured to deliver axial motions to the tissue gripping member

such that the tissue gripping member translates with respect to the hollow sheath when the drive system is activated.

BRIEF DESCRIPTION OF THE FIGURES

[0012] The novel features of the embodiments described herein are set forth with particularity in the appended claims. The embodiments, however, both as to organization and methods of operation may be better understood by reference to the following description, taken in conjunction with the accompanying drawings as follows.

[0013] FIG. 1 is a schematic view of a non-limiting embodiment of a surgical control system embodiment.

[0014] FIG. 1A is a perspective view of a non-limiting embodiment of a control system enclosure.

[0015] FIG. 1B is a perspective view of another non-limiting embodiment of a control system enclosure arrangement.

[0016] FIG. 2 is a partial cross-sectional view of a non-limiting embodiment of a handheld surgical instrument employing a linear drive system.

[0017] FIG. 3 is a top view of a distal portion of a non-limiting embodiment of a surgical instrument.

[0018] FIG. 4 is a side cross-sectional view of the distal portion of the surgical instrument of FIG. 3.

[0019] FIG. 5 is a side cross-section view of a distal portion of a non-limiting embodiment of a surgical instrument.

[0020] FIG. 6A is a front cross-sectional view of the distal portion of the surgical instrument of FIG. 5, taken along line 6A-6A.

[0021] FIG. 6B is another front cross-sectional view of the distal portion of the surgical instrument of FIG. 5, taken along line 6B-6B.

[0022] FIG. 7A is a side cross-section view of a distal portion of a non-limiting embodiment of a surgical instrument; a blade of the instrument is shown in a first axial position.

[0023] FIG. 7B is another side cross-sectional view of the distal portion of the surgical instrument of FIG. 7A; the blade is shown translated axially to a second axial position.

[0024] FIG. 8 is a top view of the distal portion of the surgical instrument of FIG. 7A.

[0025] FIG. 9 is a perspective view of a distal portion of a non-limiting embodiment of a surgical instrument.

[0026] FIG. 10A is a perspective view of a distal portion of a hollow sheath of the surgical instrument of FIG. 9.

[0027] FIG. 10B is a perspective view of a distal portion of a blade of the surgical instrument of FIG. 9.

[0028] FIG. 10C is a perspective view of a shearing plate of the surgical instrument of FIG. 9.

[0029] FIG. 11 is a side cross-sectional view of the distal portion of the surgical instrument of FIG. 9.

[0030] FIGS. 12A-12C are a series of side cross-sectional views of the distal portion of the surgical instrument of FIG. 9 showing the blade in different axial positions as the blade translates with respect to the hollow sheath.

[0031] FIG. 13 is a side view of a non-limiting embodiment of a linear drive system for use in a surgical instrument, such as the surgical instrument of FIG. 2.

[0032] FIG. 14 is a side view of a non-limiting embodiment of another linear drive system for use in a surgical instrument, such as the surgical instrument of FIG. 2.

[0033] FIG. 15 is a side view of a non-limiting embodiment of another linear drive system for use in a surgical instrument, such as the surgical instrument of FIG. 2.

[0034] FIG. 16 is a partial cross-sectional view of a non-limiting embodiment of a surgical instrument employing another linear drive system.

[0035] FIG. 17 is a perspective view of a distal portion of a non-limiting embodiment of a surgical instrument including a plurality of openings in a hollow sheath; tissue is shown being drawn into the openings.

[0036] FIG. 18 is a partial cutaway view of the distal portion of the surgical instrument of FIG. 17, showing a toothed blade.

[0037] FIG. 19 is a perspective view of a distal portion of another non-limiting embodiment of a surgical instrument including a plurality of openings in a hollow sheath.

[0038] FIGS. 20A-20B are side cross-sectional views of distal portions of toothed blades for use in a surgical instrument, such as the surgical instruments of FIGS. 17-19.

[0039] FIGS. 21A-21C are side cross-sectional views of individual teeth that may be used with a toothed blade.

[0040] FIG. 22 is a partial cross-sectional view of a non-limiting embodiment of a surgical instrument employing two suction lumens.

[0041] FIG. 23 is a perspective view of a distal portion of the surgical instrument of FIG. 22.

[0042] FIGS. 24A and 24B are side views of distal portions of blades for a surgical instrument, such as the surgical instrument of FIG. 22.

[0043] FIG. 25 is a partial cross-sectional view of a non-limiting embodiment of a surgical instrument employing a rotational drive system.

[0044] FIG. 26 is a perspective view of the surgical instrument of FIG. 25.

[0045] FIG. 27 is a side cross-sectional view of a distal portion of a non-limiting embodiment of a surgical instrument including teeth defined in an opening of a hollow sheath for gripping tissue.

[0046] FIGS. 28-29 are partial views of teeth that may be used in a surgical instrument, such as the surgical instrument of FIG. 27.

[0047] FIG. 30 is a side cross-section view of a nose piece and associated components of a surgical instrument, such as the surgical instrument of FIG. 27.

[0048] FIG. 31 is a side view of a distal portion of a non-limiting embodiment of a surgical instrument including a rotatable blade.

[0049] FIG. 32 is a cross-section view of the surgical instrument of FIG. 31, taken along line 32-32.

[0050] FIG. 33A is a cross-section view of the blade of the surgical instrument of FIG. 31, taken along line 33A-33A.

[0051] FIG. 33B is a cross-sectional view of the blade of the surgical instrument of FIG. 31, taken along line 33B-33B.

[0052] FIG. 34 is a cross-section view of another non-limiting embodiment of a blade for a surgical instrument, such as the surgical instrument of FIG. 31.

[0053] FIG. 35 is a side cross-sectional view of another non-limiting embodiment of a blade for a surgical instrument, such as the surgical instrument of FIG. 31.

[0054] FIG. 36 is a cross-sectional view of the blade of FIG. 35, taken along line 36-36.

[0055] FIG. 37 is a front cross-sectional view of a distal portion of a non-limiting embodiment of a surgical instrument including a mass balanced blade.

[0056] FIG. 38 is a top view of a distal portion of a non-limiting embodiment of a surgical instrument including a blade with a screw surface.

[0057] FIG. 39 is a top view of the distal portion of the blade of the surgical instrument of FIG. 38.

[0058] FIG. 40 is a partial cross-sectional view of a non-limiting embodiment of a surgical instrument including a movable tissue gripping member.

[0059] FIG. 41 is a cross-sectional view of a hollow sheath, cables, and a blade of the surgical instrument of FIG. 40, taken along line 41-41.

[0060] FIG. 42A is a perspective view of a distal portion of the surgical instrument of FIG. 40; the tissue gripping member is shown in an extended position.

[0061] FIG. 42B is a perspective view of the distal portion of the surgical instrument of FIG. 40; the tissue gripping member is shown in a retracted position.

[0062] FIG. 43 is a cross-section view of the hollow sheath, cables, and blade of the surgical instrument of FIG. 40, taken along line 43-43 in FIG. 42A.

DETAILED DESCRIPTION

[0063] The owner of the present application also owns the following U.S. Patent Applications that were filed on Feb. 11, 2010, and which are herein incorporated by reference in their respective entireties:

[0064] U.S. patent application Ser. No. 12/703,860, now U.S. Pat. No. 8,531,064, entitled ULTRASONICALLY POWERED SURGICAL INSTRUMENTS WITH ROTATING CUTTING IMPLEMENT;

[0065] U.S. patent application Ser. No. 12/703,864, now U.S. Pat. No. 8,323,302, entitled METHODS OF USING ULTRASONICALLY POWERED SURGICAL INSTRUMENTS WITH ROTATABLE CUTTING IMPLEMENTS;

[0066] U.S. patent application Ser. No. 12/703,866, now U.S. Patent Application Publication No. 2011-0196398 A1, entitled SEAL ARRANGEMENTS FOR ULTRASONICALLY POWERED SURGICAL INSTRUMENTS;

[0067] U.S. patent application Ser. No. 12/703,870, now U.S. Patent Application Publication No. 2011-0196399 A1, entitled ULTRASONIC SURGICAL INSTRUMENTS WITH ROTATABLE BLADE AND HOLLOW SHEATH ARRANGEMENTS;

[0068] U.S. patent application Ser. No. 12/703,875, now U.S. Pat. No. 8,469,981, entitled ROTATABLE CUTTING IMPLEMENT ARRANGEMENTS FOR ULTRASONIC SURGICAL INSTRUMENTS;

[0069] U.S. patent application Ser. No. 12/703,877, now U.S. Pat. No. 8,382,782, entitled ULTRASONIC SURGICAL INSTRUMENTS WITH PARTIALLY ROTATING BLADE AND FIXED PAD ARRANGEMENT;

[0070] U.S. patent application Ser. No. 12/703,879, now U.S. Pat. No. 8,486,096, entitled DUAL PURPOSE SURGICAL INSTRUMENT FOR CUTTING AND COAGULATING TISSUE;

[0071] U.S. patent application Ser. No. 12/703,885, now U.S. Pat. No. 8,579,928, entitled OUTER SHEATH AND BLADE ARRANGEMENTS FOR ULTRASONIC SURGICAL INSTRUMENTS; and

[0072] U.S. patent application Ser. No. 12/703,899, now U.S. Pat. No. 8,419,759, entitled ULTRASONIC SURGICAL INSTRUMENT WITH COMB-LIKE TISSUE TRIMMING DEVICE.

[0073] Certain embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these

embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting embodiments and that the scope of these embodiments is defined solely by the claims. The features illustrated or described in connection with one embodiment may be combined with the features of other embodiments. Further, where an ordering of steps in a process is indicated, such ordering may be rearranged or the steps may be carried out contemporaneously as desired unless illogical or the listed order is explicitly required. Such modifications and variations are intended to be included within the scope of the appended claims.

[0074] In the following description, like reference characters designate like or corresponding parts throughout the several views. Also in the following description, it is to be understood that terms such as “forward,” “rearward,” “front,” “back,” “right,” “left,” “over,” “under,” “top,” “bottom,” “upwardly,” “downwardly,” “proximally,” “distally,” and the like are words of convenience and are not to be construed as limiting terms. The description below is for the purpose of describing various embodiments and is not intended to limit the appended claims.

[0075] Various embodiments are directed to improved ultrasonic surgical systems and instruments configured for effecting tissue dissecting, cutting, and/or coagulation during surgical procedures as well as the cutting implements employed thereby. In one embodiment, an ultrasonic surgical instrument apparatus is configured for use in open surgical procedures, but has applications in other types of surgery, such as laparoscopic, endoscopic, and robotic-assisted procedures. Versatile use is facilitated by selective use of ultrasonic energy, the selective gross axial and/or rotational motion of the cutting/coagulation implement, and/or suction applied near and/or through the cutting/coagulation implement.

[0076] It will be appreciated that the terms “proximal” and “distal” are used herein with reference to a clinician gripping a handpiece assembly. Thus, an end effector is distal with respect to the more proximal handpiece assembly. It will be further appreciated that, for convenience and clarity, spatial terms such as “top” and “bottom” also are used herein with respect to the clinician gripping the handpiece assembly. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and absolute.

[0077] FIG. 1 illustrates in schematic form one non-limiting embodiment of a surgical system 10. The surgical system 10 may include an ultrasonic generator 12 and an ultrasonic surgical instrument assembly 100 that may include ultrasonic producing components. As will be discussed in further detail below, the ultrasonic generator 12 may be connected by a cable 14 to an ultrasonic transducer assembly 114 in a housing portion 102 of the surgical instrument assembly 100. The transducer assembly 114 may include one or more ultrasonic transducers capable of producing ultrasonic vibrations. Further, attached to the ultrasonic transducer assembly 114 may be a horn 124 for amplifying and/or focusing ultrasonic motions created by the transducer assembly 114. Coupled to the horn 124 may be a blade 200 disposed at least partially within a hollow sheath 230 extending from the housing portion 102. In one embodiment, the system 10 further includes a motor control system 20 that includes a power supply 22

that is coupled to a control module **24** by cable **23** to supply, for example, 24VDC thereto. The motor control module **24** may comprise a control module manufactured by National Instruments under Model No. NI cRIO-9073. However, other motor control modules may be employed. Any of a number of power supplies may be successfully employed for power supply **22**. The power supply **22** may be further coupled to a motor drive **26** by cable **25** to also supply 24VDC thereto. The motor drive **26** may comprise a motor drive manufactured by National Instruments. However, other motor drives may be successfully employed. Control module **24** may also be coupled to the motor drive **26** by cable **27** for supplying power thereto. A conventional foot pedal **30** or other control switch arrangement may be attached to the control module **24** by a cable **31**. As will be discussed in further detail below, the ultrasonic surgical instrument **100** may include a drive system that may include a motor **190** that has an encoder **194** associated therewith. The drive system may communicate with the transducer assembly **114**, via a rotational-to-linear motion converter **150** (described below), to deliver gross axial motions to the blade **200** such that the blade translates with respect to the hollow sheath when the drive system is activated. The motor **190** may comprise a motor manufactured by National Instruments under Model No. CTP12ELF10MAA00. However, other motors may be employed. The encoder **194** may comprise a linear encoder manufactured by US Digital under Model No. E2-500-197-I-D-D-B. However, other motors and encoders may be used. The encoder **194** may be coupled to the motor control module **24** by an encoder cable **32** and the motor **190** may be coupled to the motor drive **26** by cable **33**. The surgical system **10** may also include a computer **40** that may communicate by Ethernet cable **42** with the motor control module **24**.

[0078] As can also be seen in FIG. 1, in various embodiments, the motor control system **20** may be housed in an enclosure **21**. To facilitate easy portability of the system, various components may be attached to the motor control system **20** by removable cable connectors. For example, foot pedal switch **30** may be attached to a detachable cable connector **37** by cable **35** to facilitate quick attachment of the foot pedal to the control system **20**. A/C power may be supplied to the power supply **22** by a conventional plug/cable **50** that is attached to a detachable cable connector **54** that is attached to cable **52**. The computer **40** may have a cable **60** that is attached to detachable cable connector **62** that is coupled to cable **42**. The encoder **194** may have an encoder cable **70** that is attached to a detachable connector **72**. Likewise, the motor **190** may have a cable **74** that is attached to the detachable connector **72**. The detachable connector **72** may be attached to the control module **24** by cable **32** and the connector **72** may be attached to the motor drive **26** by cable **33**. Thus, cable connector **72** serves to couple the encoder **194** to the control module **24** and the motor **190** to the motor drive **26**. The cables **70** and **74** may be housed in a common sheath **76**.

[0079] In an alternative embodiment, the ultrasonic generator **12** and the control system **20** may be housed in the same enclosure **105**. See FIG. 1A. In yet another embodiment, the ultrasonic generator **12** may electrically communicate with the motor control system **20** by a jumper cable **107**. Such arrangement may share a data link as well as a common means for supplying power (cord **50**). See FIG. 1B.

[0080] In various embodiments, the ultrasonic generator **12** may include an ultrasonic generator module **13** and a signal generator module **15**. See FIG. 1. The ultrasonic generator

module **13** and/or the signal generator module **15** each may be integrated with the ultrasonic generator **12** or may be provided as separate circuit modules electrically coupled to the ultrasonic generator **12** (shown in phantom to illustrate this option). In one embodiment, the signal generator module **15** may be formed integrally with the ultrasonic generator module **13**. The ultrasonic generator **12** may comprise an input device **17** located on a front panel of the generator **12** console. The input device **17** may comprise any suitable device that generates signals suitable for programming the operation of the generator **12** in a known manner. Still with reference to FIG. 1, the cable **14** may comprise multiple electrical conductors, such as copper wires, for the application of electrical energy to positive (+) and negative (−) electrodes of an ultrasonic transducer assembly **114** as will be discussed in further detail below.

[0081] Various forms of ultrasonic generators, ultrasonic generator modules and signal generator modules are known. For example, such devices are disclosed in commonly owned U.S. patent application Ser. No. 12/503,770, now U.S. Pat. No. 8,461,744, entitled ROTATING TRANSDUCER MOUNT FOR ULTRASONIC SURGICAL INSTRUMENTS, filed Jul. 15, 2009, which is herein incorporated by reference in its entirety. Other such devices are disclosed in one or more of the following U.S. Patents, all of which are incorporated by reference herein: U.S. Pat. No. 6,480,796 (METHOD FOR IMPROVING THE START UP OF AN ULTRASONIC SYSTEM UNDER ZERO LOAD CONDITIONS); U.S. Pat. No. 6,537,291 (METHOD FOR DETECTING A LOOSE BLADE IN A HANDLE CONNECTED TO AN ULTRASONIC SURGICAL SYSTEM); U.S. Pat. No. 6,626,926 (METHOD FOR DRIVING AN ULTRASONIC SYSTEM TO IMPROVE ACQUISITION OF BLADE RESONANCE FREQUENCY AT STARTUP); U.S. Pat. No. 6,633,234 (METHOD FOR DETECTING BLADE BREAKAGE USING RATE AND/OR IMPEDANCE INFORMATION); U.S. Pat. No. 6,662,127 (METHOD FOR DETECTING PRESENCE OF A BLADE IN AN ULTRASONIC SYSTEM); U.S. Pat. No. 6,678,621 (OUTPUT DISPLACEMENT CONTROL USING PHASE MARGIN IN AN ULTRASONIC SURGICAL HANDLE); U.S. Pat. No. 6,679,899 (METHOD FOR DETECTING TRANSVERSE VIBRATIONS IN AN ULTRASONIC HANDLE); U.S. Pat. No. 6,908,472 (APPARATUS AND METHOD FOR ALTERING GENERATOR FUNCTIONS IN AN ULTRASONIC SURGICAL SYSTEM); U.S. Pat. No. 6,977,495 (DETECTION CIRCUITRY FOR SURGICAL HANDPIECE SYSTEM); U.S. Pat. No. 7,077,853 (METHOD FOR CALCULATING TRANSDUCER CAPACITANCE TO DETERMINE TRANSDUCER TEMPERATURE); U.S. Pat. No. 7,179,271 (METHOD FOR DRIVING AN ULTRASONIC SYSTEM TO IMPROVE ACQUISITION OF BLADE RESONANCE FREQUENCY AT STARTUP); and U.S. Pat. No. 7,273,483 (APPARATUS AND METHOD FOR ALERTING GENERATOR FUNCTION IN AN ULTRASONIC SURGICAL SYSTEM).

[0082] As can be seen in FIG. 2, an ultrasonic surgical instrument **100** may comprise a housing **102** that houses the motor **190**, the encoder **194**, the ultrasonic transducer assembly **114**, and the horn **124**. The transducer assembly **114** may be movably supported within the housing **102** by conventional linear bearings **104**, such as rollers. Extending from the horn **124** may be the blade **200**, which passes through the hollow sheath **230** to a window or opening **231** defined

therein. As shown in FIG. 2, a distal end 202 of the blade 200 may be seen through the opening 231 at a distal portion 250 of the surgical instrument 100. The housing 102 may be provided in two or more parts that are attached together by fasteners such as screws, snap features, etc. and/or by one or more adhesives and may be fabricated from, for example, polycarbonate, stainless steel, or other material. The motor 190 may be mounted to the housing 102 and may mechanically communicate with the ultrasonic transducer by way of a rotational-to-linear motion converter 150, which may comprise a rack member 153 and a pinion 154. Additional gears may be added between the pinion 154 and the rack member 153 to achieve desired gear reductions, if desired. Further, the rack member 153 may hold the encoder 194 and be attached to the transducer assembly 114. Accordingly, activation of the motor 190 may turn pinion 154, and thus drive rack 153, encoder 194, transducer assembly 114, horn 124, and blade 200 in a proximal direction “PD” or a distal direction “DD” parallel to or coaxial with the hollow sheath’s longitudinal axis A-A. The motor 190 may comprise, for example, a stepper motor manufactured by National Instruments under Model No. CTP12ELF10MAA00. However, other motors, such as brushless DC or other types, may be employed to effectuate, for example, “gross” axial motion of the blade 200 relative to the hollow sheath 230 on the order of 1 to 15 mm. The encoder 194 may convert the position and/or speed of the rack member 154 into electrical pulses that provide position, speed, and/or other control information to the control module 24. Further, the encoder 194 may include an in-line force sensor (not shown), such as a piezoelectric sensor, that may measure a load experienced by the blade’s distal end 202 and communicated to the rack member 153, such as the load provided by tissue when the surgical instrument is used in a surgical operation.

[0083] Referring still to FIG. 2, the ultrasonic transducer assembly 114 may include a housing 118 that supports piezoelectric ultrasonic transducers 115 for converting electrical energy to mechanical energy that results in longitudinal vibrational motion of the ends of the transducers 115. The ultrasonic transducers 115 may comprise a stack of ceramic piezoelectric elements with a motion null point located at some point along the stack. The ultrasonic transducers 115 may be mounted between a proximal end piece 116 and a distal end piece 117. In addition, the horn 124 may be mounted to the distal end piece 117 at the null point on one side and to the blade 200 on the other side. As a result, the blade 200 will vibrate in the longitudinal direction at an ultrasonic frequency rate with the ultrasonic transducer assembly 114. The ends of the ultrasonic transducer assembly 114 achieve maximum motion with a portion of the stack constituting a motionless node, when the ultrasonic transducer assembly 114 is driven at maximum current at the transducer’s resonant frequency. However, the current providing the maximum motion will vary with each instrument and is a value stored in the non-volatile memory of the instrument so the system can use it.

[0084] The parts of the surgical instrument 100 may be designed such that the combination will oscillate at the same resonant frequency. In particular, the elements may be tuned such that the resulting length of each such element is one-half wavelength or a multiple thereof. Longitudinal back and forth motion is amplified as the diameter closer to the blade 200 of the acoustical mounting horn 124 decreases. Thus, the horn 124 as well as the blade 200 may be shaped and dimensioned

so as to amplify blade motion and provide ultrasonic vibration in resonance with the rest of the acoustic system, which produces the maximum back and forth motion of the end of the acoustical mounting horn 124 close to the blade 200. A motion from 20 to 25 microns at the ultrasonic transducers 115 may be amplified by the horn 124 into blade movement of about 40 to 100 microns.

[0085] Referring briefly back to FIG. 1, when power is applied to the ultrasonic instrument 110 by operation of the foot pedal 30 or other switch arrangement, the control system 20 may, for example, cause the blade 200 to vibrate longitudinally at approximately 55.5 kHz, and the amount of longitudinal movement will vary proportionately with the amount of driving power (current) applied, as adjustably selected by the user. When relatively high cutting power is applied, the blade 200 may be designed to move longitudinally in the range of about 40 to 100 microns at the ultrasonic vibrational rate. Such ultrasonic vibration of the blade 200 will generate heat as the blade contacts tissue, i.e., the acceleration of the blade 200 through the tissue converts the mechanical energy of the moving blade 200 to thermal energy in a very narrow and localized area. This localized heat creates a narrow zone of coagulation, which will reduce or eliminate bleeding in small vessels, such as those less than one millimeter in diameter. The cutting efficiency of the blade 200, as well as the degree of hemostasis, will vary with the level of driving power applied, the cutting rate or force applied by the surgeon to the blade, the nature of the tissue type, and the vascularity of the tissue.

[0086] Referring again to FIG. 2, when power is applied to motor 190, motor 190, via pinion 154, applies a “gross axial motion” to the rack member 153 to cause the ultrasonic transducer assembly 114 and blade 200 to translate with respect to the hollow sheath 230. As used herein, the term “gross axial motion,” and the like, is to be distinguished from “ultrasonic motion,” and the like, that may be achieved by way of the ultrasonic transducer assembly. The term “gross axial motion” instead encompasses translational motion that is not solely generated by operation of the ultrasonic transducer assembly 114.

[0087] To provide the ultrasonic instrument 110 with power from the ultrasonic generator 12 (see FIG. 1), a multiple-segment jointed protector 110 may be employed. As can be seen in FIG. 2, conductors 151, 152 are coupled to the ultrasonic transducer assembly 114 and extend out of the instrument through the housing 102. Further, the protector 110 may be attached to the instrument housing 102 at one end and to the transducer assembly housing 118 at the other end. The conductors 151, 152 may pass through one or more holes in the transducer assembly housing. Accordingly, ultrasonic signals from the ultrasonic generator 12 are transferred to the ultrasonic transducers 115 through the conductors 151, 152. The protector 110 may prevent the conductors 151, 152 from being damaged or pinched by the mechanical components of the instrument 100 when the motor 190 is activated.

[0088] Referring still to FIG. 2, various embodiments also include a distal nosepiece 160 that may be removably attached to the distal end of the housing 102 by fasteners and/or adhesives (not shown). The nosepiece 160 may be fabricated from, for example, stainless steel, aluminum, or plastic. In various embodiments, the distal end 202 of the blade 200 extends through a hollow portion 210 of the nosepiece 160. The hollow sheath 230 may likewise extend through the hollow portion 210. The hollow portion 210 may

include an annular groove in which a proximal seal **212** may be held against the end of the hollow sheath **230** and against the blade **200**. The seal **212** may comprise, for example, a silicone O-ring, a brazing, or a press-fit seal, and serve to establish a substantially fluid-tight and/or airtight seal between the nosepiece **160**, blade **200**, and hollow sheath **230**.

[0089] Also in various embodiments, the hollow sheath **230** may be coaxially aligned with the blade **200** and be attached to the hollow portion **210** of the nosepiece **160** by, for example, welding, press-fitting, threading, adhering with glue or other adhesive(s), etc. As can be seen in FIG. 2, a suction port **240** may be attached to the nosepiece **160** to communicate with a proximal hole **232** in the hollow sheath **230**. A flexible tube **242** may be attached to the suction port **240** and communicate with a collection receptacle **243** that is coupled to a source of vacuum, generally depicted as **244**. Thus, the hollow sheath **230** forms a suction path extending around the blade **200** that begins at the distal portion **250** of the outer sheath **230**, such as at the opening **231**, and goes out through the hole **232** to the suction port **240**. Those of ordinary skill in the art will appreciate that alternate suction paths are also possible. Further, a distal seal **213**, similar to proximal seal **212**, may be held in the nosepiece **160** and may help further seal the hollow sheath **230** therein such that the suction path from the opening **231**, through the sheath **230**, out hole **232**, and through the port **240** is maintained with minimal or no ingress of air from outside the aforementioned path.

[0090] Various embodiments of the surgical system **10** (see FIG. 1) provide the ability to selectively apply ultrasonic axial motion to the blade **200** and gross axial motion to the blade **200** as well. If desired, the clinician may simply activate the ultrasonic transducer assembly **114** without activating the motor **190**. In such cases, the instrument **100** may be used in ultrasonic mode simply as an ultrasonic instrument. Frequency ranges for longitudinal ultrasonic motion may be on the order of, for example, 30-80 kHz. Similarly, the clinician may desire to activate the motor **190** without activating the ultrasonic transducer assembly **114**. Thus, gross axial motion will be applied to the blade **200** in the translational mode, without the application of longitudinal ultrasonic motion thereto. Gross axial speeds may be, for example, on the order of 0.25 in/s to 5 in/s. In other applications, the clinician may desire to use the instrument **100** in the ultrasonic and translational modes wherein the blade **200** will experience longitudinal ultrasonic motion from the transducer assembly **114** and gross axial motion from the motor **190**. Further, the blade **200** may translate back and forth within the hollow sheath **230** by reversing the output of the motor. By way of example, the motor **190** may first cause the blade **200** to move in the distal direction DD. The encoder **194** may then sense or calculate when the blade **200** has reached the distal end of the hollow sheath **230** and then provide feedback causing the motor **190** to reverse, thereby moving the blade **200** in the proximal direction PD until the encoder **194** again senses or calculates that the blade **200** has moved sufficiently in the proximal direction PD, and then the encoder **194** may again provide feedback causing the motor to reverse again. Various such gross translational oscillatory or reciprocating motions may thereby be achieved. Moreover, those of ordinary skill in the art will readily appreciate that various embodiments of the surgical system **10** may be affectively employed in connection with arthroscopic as well as other surgical applications.

[0091] The surgical instrument **100** may have various distal portions **250**. FIGS. 3 and 4 illustrate an example of a distal portion **450** of another non-limiting embodiment of a surgical instrument wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. In these embodiments, the surgical instrument includes a hollow sheath **430**, a blade **200** disposed at least partially within the hollow sheath **430**, an ultrasonic transducer (not shown, see transducers **115** in FIG. 2) operably coupled to the blade, and a drive system (also not shown, see motor **190** in FIG. 2) communicating with the transducer to deliver axial motions to the blade **200** such that the blade **200** translates, for example in the proximal and distal directions, PD and DD, respectively, with respect to the hollow sheath **430** when the drive system is activated. In such embodiments, the blade **200** may have a tube-like shape and may cut tissue when the same is drawn into and/or through the opening **431** of the hollow sheath **430** by suction there-through. Accordingly, tissue that is drawn into the sheath **430** may be cut by activating the ultrasonic transducers to create ultrasonic motion of the blade **200** and/or by activating the motor to cause the blade **200** to translate with gross axial motion with respect to the hollow sheath **430**. The distal end **202** of the blade **200** may be shaped to enhance cutting by having a sharp edge or a scalloped shape. The latter shape may assist in the cutting of tough tissues.

[0092] FIGS. 5-6B illustrate another example of a distal portion **550** of another non-limiting embodiment of a surgical instrument wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. FIG. 5 is a cross-sectional view taken along a longitudinal axis of the hollow sheath **530** and FIGS. 6A and 6B are cross-sectional views taken along their respective lines in FIG. 5. In these embodiments, a septum **260** may divide the interior of the hollow sheath **530** into a suction portion "A" and a blade portion "B." The suction portion A may communicate with a suction port (not shown, see port **240**, described above). Further, the septum **260** may be divided into a perforated portion **261** and a solid portion **262**, both of which may be integrally formed with the hollow sheath **530**. Alternatively, all of the septum **260** may be perforated. In any event, suction may be applied to the instrument such that, during a surgical operation, tissue is pulled toward suction portion A, by way of the perforated portion **261**. Such configurations may help properly position tissue through opening **531** such that the blade **200'** may be moved into and cut the tissue held therethrough. Further, referring to FIG. 5, a pad **226** may be fixed to the sheath **530** and/or to the septum **260** to provide a cutting surface against which the blade **200'** may cut tissue, when the blade **200'** is moved into contact therewith. Also, as can be seen in FIG. 6B, the blade **200'** may include a U-shape to reduce mass.

[0093] Referring still to FIGS. 5-6B, in at least one embodiment, tissue may be cut as follows. First, suction may be applied to the suction portion A of the hollow sheath **530** such that tissue is drawn into the opening **531**. Second, the ultrasonic transducers may cause the blade **200'** to vibrate ultrasonically. Third, the blade **200'** may be advanced in the distal direction DD such that the blade **200'** cuts the tissue by both gross axially movement and ultrasonic vibrational movement. Third, the blade **200'** may be retracted while suction is maintained, thereby capturing and/or drawing the severed tissue into the suction portion A of the hollow sheath **530**.

[0094] FIGS. 7A-8 illustrate another example of a distal portion 650 of another non-limiting embodiment of a surgical instrument wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. FIGS. 7A and 7B are longitudinal cross-sectional views of the instrument's distal portion 650, with the blade 200" in a first position in FIG. 7A and in a second position in FIG. 7B. FIG. 8 is a top view of the distal portion 650 showing a teardrop-shaped opening 631 in hollow sheath 630. In these embodiments, the blade 200" may further include a lumen 205 through which suction may also be applied. Accordingly, the blade 200" may include a distal aperture 206 and a proximal aperture 207 (see FIG. 2). As best seen in FIG. 2, the proximal aperture 207 may be positioned within the nosepiece 160 (see FIG. 2). In any event, referring back to FIGS. 7A-7B, suction may be applied through the lumen 205 such that tissue "T" may be drawn into the blade 200" via distal aperture 206 when the blade 200" is in the first axial position, see FIG. 7A. After the tissue is drawn into the blade 200" (see FIG. 7A), the tissue T may be pinched between the distal aperture 206 and a narrow portion 632 of the opening 631 by translating the blade 200" in the proximal direction to the second axial position, see FIG. 7B. Thereafter, the tissue may be cut by activating the ultrasonic transducer(s), as described above. The opening's narrow portion 632, combined with the pinching of the tissue therein, may help more easily sever tissue with the ultrasonic vibrational motion of the blade 200".

[0095] FIGS. 9-12C illustrate another example of a distal portion 750 of another non-limiting embodiment of a surgical instrument wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. In these embodiments, the hollow sheath 730 may further include a beveled shearing surface 735 against which the blade 200" may cut tissue at opening 731. The beveled shearing surface 735 may be similar to a single tooth in that it provides a sharpened edge against which tissue may be cut. FIG. 9 is a perspective view of the distal portion 750 of the surgical instrument. FIG. 10A is a perspective view of the distal portion of the hollow sheath, FIG. 10B is a perspective view of the distal portion of the blade 200", and FIG. 10C is a perspective view of a shearing plate 736. The shearing surface 735 may be integrally formed with or attached to the sheath 730. In at least one embodiment, the shearing surface 735 may be formed from a portion of a shearing plate 736. In such embodiments, the shearing plate may be held in place on the hollow sheath 200" via press pins, epoxy, snap features, etc. As seen in FIG. 10A, the hollow sheath 730 may include a recess 737 and protrusions 738 extending therefrom for receiving the plate 736. Further, as best seen in the cross-sectional view provided in FIG. 11, the blade 200" may further include a sharpened surface 209 that is complimentary to the beveled shearing surface 735. Also, proximal to the sharpened surface 209, sufficient clearance "C" may exist between the blade 200" and the inner surface of the hollow sheath 730 such that suction may communicate from the suction port (not shown, see port 240 in FIG. 2) to the opening 731. Further, the clearance C may be large enough to allow tissue to be drawn through the hollow sheath 730 between the blade 200" and the sheath 730.

[0096] Further, as noted above, the blade 200" may move axially past the opening 731. For example, FIGS. 12A-12C illustrate a series of side cross-sectional views of the distal portion 750 of the surgical instrument with the blade 200" in

different axial positions as the blade 200" translates with respect to the hollow sheath 730. FIG. 12A shows the blade 200" in a distal-most axial position, FIG. 12B shows the blade 200" in an interim position, and FIG. 12C shows the blade 200" in a proximal position. In at least one embodiment, the instrument may function as follows. First, as the blade moves axially past the opening 731, the blade 200" may receive ultrasonic motions from one or more ultrasonic transducers (see transducers 115 in FIG. 2), as described above. Further, before or as the blade is moving, suction may be applied to the hollow sheath 730. As the two shearing surfaces 735, 209 approach one another, they may cut tissue fibrils hanging in the opening 731. The severed tissue fragments may then be moved through the clearance space C between the blade 200" and the hollow sheath 730 and ultimately evacuated out of the instrument via the suction port, described above.

[0097] Referring briefly back to FIG. 2, while the drive system described above utilizes a rack-and-pinion arrangement as the instrument's rotational-to-linear motion converter 150, other converters may be employed. For example, referring now to FIG. 13, a converter 150' may include a slider-crank mechanism configured to transform the rotary drive from the electric motor 190' into linear motion. In such embodiments, the converter 150' may include a slide member 153' coupled to a first crank member 154' which, in turn, is coupled to a second crank member 155' that is attached to the motor's axle. As the motor causes the second crank member 155' to rotate in a clockwise "CW" or counter-clockwise "CCW" direction, the first crank member 154' causes the slide member 153' to slide in the proximal or distal direction, PD or DD, respectively. The slide member 153', which may be coupled to the ultrasonic transducer assembly (see assembly 114 in FIG. 2), may thereby effectuate the gross axial movement of the transducer assembly and thus the blade, as described above. Note that in this and other examples of rotational-to-linear converters described below, various components of the surgical instrument, such as the housing, are omitted for clarity. Additionally, the blade may grossly reciprocate with respect to the hollow sheath because the slide member 153' may move proximally and then distally as the motor 190' rotates the second crank member 155'.

[0098] By way of another example, a rotational-to-linear motion converter 150" may include a worm gear. Referring to FIG. 14, a motor 190" is shown with its axle 155" projecting toward transducer assembly 114. Coupled to the axle 155" may be a worm gear 154" that is threadably engaged with a threaded member 153". The threaded member 153" is subsequently coupled to the transducer assembly 114. Accordingly, activation of the motor 190" may cause the worm gear 154" to rotate about its axis, thereby driving the threaded assembly 153", and, thus, ultimately, the transducer assembly 114 and the blade (not shown), in a proximal or distal direction, PD or DD, respectively.

[0099] Another exemplary rotational-to-linear motion converter 150''' may include a lead screw. Referring to FIG. 15, a motor 190''' is shown with a lead screw 155''' serving as its axle. The lead screw 155''' may be threadably engaged with a nut 154''' that is attached to support members 153'''. Accordingly, activation of the motor 190''' may cause the lead screw 155''' to rotate 154''' about its axis, thereby driving the nut 154''', support members 153''', transducer assembly 114 (shown in phantom), and, ultimately, the blade, in a proximal or distal direction, PD or DD, respectively.

[0100] Further, while the above drive systems have utilized a motor, manual drive systems may be used. For example, referring to FIG. 16, another example of a non-limiting embodiment of a surgical instrument 100' is shown wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. In these embodiments, a trigger 191 may be pivotally coupled to the housing 102 by a pivot pin 192. The handle may further include a groove 195 in which a projection 193 of the transducer assembly 114 is received. Accordingly, moving the trigger 191 in a first rotational direction RD' may cause the transducer assembly 114 and the blade 200 to move in a distal direction DD. Moving the trigger in a second rotational direction RD'' may also cause the transducer assembly 114 and the blade 200 to move in a proximal direction PD. In use, a user may grasp the housing 102 and activate the trigger 191 with his or her thumb or finger(s).

[0101] In various embodiments, other opening configurations at a distal portion of the instrument, such as distal portion 250, see FIG. 2, may be employed. Focusing now on one non-limiting embodiment, FIGS. 17-18 illustrate another example of a distal portion 850 of another non-limiting embodiment of a surgical instrument wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. FIG. 17 is a perspective view of the distal portion 850 including a plurality of openings 831 in the hollow sheath 830. Tissue "T" is shown being drawn or drawn into the openings 831 by way of a suction port (not shown, see port 240 in FIG. 2) communicating with the hollow sheath 830. FIG. 18 is a partial cutaway view of the distal portion 850 of the surgical instrument. In these embodiments, the multiple openings 831 may be advantageous over one single opening for pulling the fibrous tissue T therethrough and into contact with blade 800 while stabilizing the tissue T for the blade 800 to cut. The openings 831 may be formed as perforations, or a grid of holes, in the hollow sheath 830. Alternatively, referring to FIG. 19, the openings 831' may be formed as slits in the sheath 830' of the distal portion 850'.

[0102] Additionally, in at least one embodiment, the blade 800 may only receive ultrasonic axial movement thereto, as discussed above. Accordingly, a drive system, also as discussed above (including, for instance a motor and/or trigger), may be unnecessary. However, in an alternative embodiment, the blade 800 may receive gross axial motions thereto and be operably coupled to a drive system for moving the blade in proximal or distal directions, PD or DD, respectively, see FIG. 18.

[0103] Further, a rasped or toothed blade may further enhance the cutting ability of the instrument. For example, referring to FIG. 18, the blade 800 may include teeth 801 projecting toward and positioned with respect to the openings 831 such that the teeth may contact tissue drawn into the openings 831. The teeth may further have varying profiles. Referring now to FIGS. 20A-21C, a variety of blade teeth profiles, 801', 801'', 801''', 801''', 801'''' are illustrated. The aforementioned teeth profiles may provide advantageous cutting ability to the blade, such as blades 800, 800', and/or 800''.

[0104] While some embodiments described above include one suction port, in various embodiments, other suction configurations may be employed. Focusing now on one non-limiting embodiment, FIGS. 22-23 illustrate another example of a surgical instrument 100'' wherein like numbers previously used to describe the various embodiments disclosed

above are used to designate like components. FIG. 22 is a partial cross-sectional view of part of the surgical instrument 100'' employing two suction lumens and two suction ports and FIG. 23 is a perspective view of the distal portion 950 of the surgical instrument 100''. Referring to FIG. 22, the surgical instrument may include a housing 102 containing the transducer assembly 114 coupled to the horn 124, among other things. As discussed above, the horn may subsequently be attached to the blade 900. Additionally, the nose piece 160' may include a first suction port 240 and a second suction port 241 which may be coupled to independent collection receptacles 243, 243' and/or vacuum sources 244, 244' by flexible tubing 242, 242'. The hollow sheath 930 may further include a septum 960 dividing the interior of the hollow sheath into a first lumen 963 and a second lumen 964. The septum 960 may extend to the proximal end of the hollow sheath and abut against proximal seal 212. The first suction port 240 may communicate with the first lumen 963 and the second port 241 may communicate with the second lumen 964. Referring to FIG. 23, the first and second lumens 963 and 964, respectively, can be seen extending to the hollow sheath's opening 931. Accordingly, applying suction to ports 240 and 241 (see FIG. 22) may create two suction paths, via the first and second lumens 963 and 964, that communicate with the opening 931 for applying suction thereto. The suction dynamics at the opening 931 may be further modified by applying different amounts of suction to the first port 240 and the second port 241.

[0105] A blade 900 may be disposed at least partially within the first suction lumen 963. Further, the distal end 902 of the blade 900 may extend through the opening 931. Further, a suction tube 965 may be added to the second lumen 964 to enhance the suction force applied at or near the opening 931. In any event, tissue may be drawn toward the first lumen 963 and/or the second lumen 964 when suction is applied to one or both of suction ports 240, 241. The dual suction lumens 963, 964 may provide enhanced contact and suction of tissue in a liquid environment, such as that experienced during arthroscopic surgery. The two lumens 963, 964 may provide a reliable device capable of pulling in fibrous tissue and evacuating debris therethrough.

[0106] Referring to FIG. 24A, which illustrates a side view of a distal portion of the blade 900, the blade 900 may be rasped or include teeth 901 near its distal end 902. The teeth 901 may help improve tissue ablation by adding an optimized surface for friction to occur in a liquid environment. Additionally, while the blade 900 may be coupled to an ultrasonic transducer, such as one or more contained in the ultrasonic transducer assembly 114 (see FIG. 22), so that the blade 900 may experience ultrasonic vibrational motion, the blade 900 may also be coupled to a drive system configured to apply gross axial motion thereto, as described above, thereby enhancing the cutting ability of the blade 900. Further, in at least one embodiment and referring to FIG. 23, the blade's distal end 902 may be retracted into the hollow sheath 930 by the drive system such that the blade does not unintentionally cut tissue until desired, at which point the blade may be extended back through the opening 931.

[0107] Alternatively, other blade configurations may be employed. For example, referring to FIG. 24B, a blade 900' may contain a flat surface 901' near its distal end 902'. In such embodiments, the surface itself may generate enough friction, when ultrasonic vibrational motion is applied thereto, to cut tissue.

[0108] While some of the embodiments described above have disclosed gross axial motion of a blade to provide various advantages, similar advantages may be obtained with a surgical instrument that instead utilizes gross rotational motion of a blade. Focusing now on one non-limiting embodiment, FIGS. 25-26 illustrate another surgical instrument 300 wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. In these embodiments, the surgical instrument 300 includes a housing 302 that houses a transducer assembly 314 that is attached to an ultrasonic horn 324. The ultrasonic horn 324 may be coupled to the proximal end of the blade 200, as discussed above. The ultrasonic horn 324 may be rotatably supported within the housing 302 by a distal bearing 336. A nosepiece 160 may be attached to the housing 302 by fasteners 161 in the manner described above.

[0109] In this embodiment, a drive system may be provided that communicates with the transducer assembly 314 to deliver rotational motions thereto such that the blade rotates with respect to the hollow sheath 230 when the drive system is activated. For example, the ultrasonic transducer assembly 314 may have magnets 316 embedded or otherwise attached thereto to form an integral motor rotor, generally designated as 320. A motor stator ring 330 is mounted within the housing 302 as shown. Conductors 332, 334 are attached to the motor stator ring 330 and pass through the common sheath 76 to be attached to the motor cable 33 in the control system 20 as described above. A hollow shaft 340 extends through the motor rotor 320 to form a passage for conductors 151, 152. Conductors 151, 152 are coupled to the ultrasonic transducer assembly 314 and an inner contact 2154. The inner contact 2154 is attached to a portion of the hollow shaft 340 that rotatably extends into a slip ring assembly 2150 that is also supported within the housing 302. The hollow shaft 340 is rotatably supported within the housing 302 by a proximal bearing 342. The slip ring assembly 2150 is fixed (i.e., non-rotatable) within the housing 302 and includes a fixed outer contact 2156 that is coupled to conductors 2157, 2158 that form a generator cable 14. When power is supplied to the motor stator 330, the rotor 320 and the integral ultrasonic transducer 314 are caused to rotate about axis A-A. Ultrasonic signals from the ultrasonic generator 12 are transferred to the inner contact 2154 by virtue of rotating contact or electrical communication between the inner contact 2154 and the outer contact 2156. Those signals are transmitted to the ultrasonic transducer assembly 314 by conductors 151, 152. A suction may be applied between the blade 200 and hollow sheath 230 through port 240. A collection receptacle 243 and source of suction 240 may be attached to the port 240 by tube 242. The distal end of the blade is exposed through a window in the distal end of the hollow sheath 230 at the distal portion 250 of the instrument to expose the blade to tissue as will be further discussed below.

[0110] Additional details regarding surgical instrument 300 and other embodiments of surgical instruments with rotating blades may be found in U.S. patent application Ser. No. 12/703,860, now U.S. Pat. No. 8,531,064, entitled ULTRASONIC SURGICAL INSTRUMENTS WITH ROTATING CUTTING IMPLEMENT, filed on Feb. 11, 2010, which is incorporated herein by reference in its entirety.

[0111] In at least one embodiment, the distal portion of a surgical instrument may be configured to grip tissue that is being cut. Focusing now on one non-limiting embodiment, FIG. 27 illustrates an example of the distal portion 1050 of the

surgical instrument wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. The hollow sheath 1030 may include an opening 1031 therein that is positioned such that tissue may be drawn therethrough and into contact with the blade 1000. The opening 1031 may further include one or more teeth 1032 that are configured to grip tissue positioned within the opening 1031. Additionally, the opening 1031 may project away from the blade 1000, or otherwise be shaped to increase the surface area of the opening to increase suction force at the opening 1031 when suction is applied to the instrument, as described above. Thus, tissue "T", which is shown being drawn toward the opening 1031, may be better held by the instrument when the blade 1000 is ultrasonically activated and/or grossly translated or rotated. Holding or gripping the tissue T when the blade is cutting may be advantageous to prevent the tissue T from bypassing a cutting edge 1006 of the blade 1000.

[0112] The teeth 1032 may be annular ribs as shown in FIG. 27. Alternatively, referring to FIGS. 28-29, which show various teeth options, the teeth 1032 may be hooks 1032', fish-scale like tabs 1032", or a roughened surface (not shown). FIG. 29 shows the tissue T being gripped by the tabs 1032".

[0113] Further, as noted above, the blade may grossly rotate or translate with respect to the hollow shaft, by way a drive system as described above. Also, in at least one embodiment, the blade may be hollow and define a lumen 1005 therein through which suction may be applied to draw tissue toward and into contact with the blade 1000. In at least one embodiment, the suction port 240 (see FIGS. 25-26) may communicate exclusively with the lumen 1005. In other words, the suction path may be limited to the lumen 1005 and not include the space between the hollow sheath 1030 and the blade 1000. In more detail, referring to FIG. 30, which illustrates an embodiment of nosepiece 160 and various related components, the hollow sheath 1030 is supported within a hollow nosepiece 160 that has a suction port 240 therein. A flexible tube 242 may be attached to the suction port 240 and communicate with a collection receptacle 243 that is coupled to a source of suction, generally depicted as 244. The hollow sheath 1030 may be supported within the nosepiece 160 by a proximal seal 1013 and a distal seal 1015 which are located on each side of the suction port 240 and which serve to establish fluid tight seals therebetween. The hollow sheath 1030 is provided with at least one proximal opening 1014 in registration with the suction port 240 between the proximal seal 1013 and the distal seal 1015. In addition, the blade 1000 is rotatably supported within the hollow sheath 1030 by at least a proximal blade seal 1025 and a distal blade seal 1027. At least one blade discharge port 1028 may be provided through the lumen 1005 of the blade 1000 between the proximal blade seal 1025 and the distal blade seal 1027 to discharge into the at least one proximal sheath opening 1014.

[0114] In various embodiments, in a rotary surgical instrument, such as surgical instrument 300 described above, it may be desirable to reduce the blade mass to optimize rotational cutting speed. Thus, in at least one non-limiting embodiment, focusing now on FIGS. 31-32, a blade 1100 may be paddle shaped. FIG. 31 is a side view of a distal portion 1150 of a surgical instrument including the rotatable blade 1100 and FIG. 32 is a cross-section view of the distal portion 1150, taken along line 32-32. A hollow sheath 1130 may include opening 1131, as discussed above. The blade 1100 may be disposed at least partially within the hollow sheath 1130 and

include a wide portion 1101 and a narrow portion 1102. The narrow portion 1102 may extend proximally and be coupled to the horn 324 (see FIG. 25). The wide portion 1102 of the blade 1100 may extend toward and/or into the opening 1131.

[0115] In at least one embodiment, referring to FIG. 32, the blade 1100 may include a concave surface or surfaces 1103 to further reduce rotational inertia as the blade 1100 rotates in a clockwise “CW” or counterclockwise “CCW” direction. Additionally, the concave surfaces 1103 may vary along the cross section of the blade 1100 to enhance the blade’s cutting ability. Referring now to FIGS. 33A and 33B, the cross-section of blade 1100 at lines 33A-33A and 33B-33B, respectively, can be seen. The distal portion of the concave surfaces 1103 (see FIG. 33A) may be thicker and taller than the proximal portion of the same (see FIG. 33B). Alternatively, referring to FIG. 34, the mass of a blade 1100' may be reduced by forming a hole 1105 along the longitudinal axis of the blade 1100'. In at least one embodiment, the hole 1105 may be milled into the blade 1100'.

[0116] In at least one embodiment, referring to FIGS. 35-36, the mass of a blade 1200 usable with hollow sheath 1130 described above, may be reduced by using a blade including a gap 1206 positioned such that it may align within the opening 1131 of the sheath 1130, see FIG. 31. Again, referring to FIG. 35, the blade 1200 may include a narrow portion 1202 and a wide portion 1201. The wide portion 1201 may further define the gap 1206 therein that may be positioned such that the gap 1206 is next to or coincident with the opening 1131, when the blade 1200 is used with sheath 1130, see FIG. 31. The length “D” of the wide portion 1201 may be such that the length D is at least as long as is the opening 1131, see FIG. 31. Again, as described above and referring to FIG. 36, the wide portion 1201 of the blade 1200 may include a concave surface 1203 to reduce blade mass. Alternatively, a blade may further reduce blade mass by incorporating a blade that is mass balanced such that it may have an elliptical center that is offset from the axis of rotation. For example, referring to FIG. 37, an axial or front cross-sectional view of a distal portion 1350 of a surgical instrument including a blade 1300 is shown positioned within the hollow sheath 1130, as described above. The blade 1300 may be configured to rotate about axis “A.” However, the concave surface 1303 may not be symmetric about that axis. For example, a first side 1307 of the blade 1300 may be wider than a second side 1308. In such embodiments, the elliptical center “B” may be offset from the rotational axis A. Accordingly, the blade may be made from a non-homogenous material such that distribution of mass about the rotational axis A is balanced and the blade may rotate at high speeds without damaging itself or the hollow sheath 1130.

[0117] Alternative rotational blade configurations are possible. For example, referring to FIGS. 38-39, a non-limiting embodiment is provided in which a blade 1400 may include a screw surface 1403 positioned next to an opening 731 in a hollow sheath 730. The sheath 730 may be similar to the sheath 730 seen in FIG. 9 and discussed above. For example, the sheath 730 may also include a shearing plate 736 with a beveled shearing surface 735 positioned in the opening 731, as discussed above. Also as noted above, the beveled shearing surface 735 may be similar to a single tooth in that it provides a sharpened edge against which tissue may be cut. In any event, the screw surface 1403 may function like an auger and

as the blade 1400 is rotated, the screw surface 1403 may pull tissue toward the shearing plate 736 to enhance the cutting of tissue.

[0118] In various embodiments, tissue may be gripped by a movable tissue gripping member to enhance the cutting thereof. Focusing now on one non-limiting embodiment, FIGS. 40-43 illustrate another surgical instrument 300' wherein like numbers previously used to describe the various embodiments disclosed above are used to designate like components. FIG. 40 is a partial cross-sectional view of the surgical instrument 300'. The surgical instrument 300' may be similar to surgical 300 described above and seen in FIG. 25, for example, except at least that it further includes a drive system including a trigger 391 pivotally coupled to the nosepiece 160 that is subsequently connected to and configured to cause a tissue gripping member 1550 to move with respect to a hollow sheath 1530 (see FIGS. 42A-42B). Additionally, as discussed above, the blade 1500 is configured to rotate at least partially within the hollow sheath 1530.

[0119] As noted above, the drive system may be configured to deliver axial motions to the tissue gripping member 1540 such that the tissue gripping member translates with respect to the hollow sheath 1530 when the drive system is activated. In more detail, focusing now on FIGS. 42A-42B, FIG. 42A is a perspective view of a distal portion 1550 of the surgical instrument 300' with the tissue gripping member 1540 shown in an extended position and FIG. 42B is a perspective view of the distal portion 1550 with the tissue gripping member 1540 shown in a retracted position. The hollow sheath 1530 may include a distal opening 1531 that opens towards the distal direction DD. Further, extending from the opening 1531 may be the tissue gripping member 1540. At least one and optionally two load-bearing cables 1551, 1552 may be coupled to the tissue gripping member 1540 and extend in the proximal direction PD therefrom. As used herein, a cable can include a solid core cable, a twisted wire cable, a chain, a band, a rope, etc., and any other load-bearing member. Inside the hollow sheath 1530, referring to FIG. 43, which shows a cross-sectional view of the hollow sheath 1530, cables 1551, 1552, and blade 1500, taken along line 43-43 in FIG. 42A, may be channels 1535, 1536 that are sized and configured to receive the cables 1551, 1552 therein. Although not shown, the channels may open at a distal opening (not shown) at or near the sheath’s opening 1531. Referring still to FIG. 43, the blade 1500 may include concave surfaces 1503 as discussed above for facilitating the cutting of tissue; alternatively the blade may include a screw surface also as described above. Focusing back on FIGS. 40 and 41, FIG. 41 shows a cross-sectional view of the hollow sheath 1550, cables 1551, 1552, and blade 1500, taken along line 41-41, which is at or near the proximal end of the sheath 1550. As can be seen in FIG. 41, within the nosepiece 160, the cables 1551, 1552 may pass out of the channels 1535, 1536 of the hollow sheath 1530 by way of holes 1537, 1538 defined therein. The cables may be coupled to a trigger 391 which is pivotally mounted to the nosepiece. Accordingly, movement of the trigger 391 by a user may cause the cables 1551, 1552 and, subsequently, the tissue gripping member 1540 to axially move or translate with respect to the hollow sheath 1530.

[0120] The surgical instrument 300' may be used as follows. First, a user may manipulate the trigger 391 to extend the tissue gripping member 1540, as seen in FIG. 42. Next, the user may place tissue between the hollow sheath 1530 and the gripping member 1540. Optionally, suction may be applied to

port 240 to assist in the positioning of the tissue. Then, the user may move the trigger 391 such that the gripping member 1540 retracts to a position like the one seen in FIG. 42B, thereby pulling tissue into the hollow sheath 1530 and into contact with the blade 1500. At the same time or after retracting the gripping member 1540, the user may activate the ultrasonic transducer assembly 314 such that ultrasonic vibrational motion is applied to the blade 1500. Optionally, power may also be supplied to the motor stator 330 such that the rotor 320, the integral ultrasonic transducer 314, and the blade 1500 are caused to rotate about axis A-A. The gripped tissue may therefore be cut by one or both of the ultrasonic vibrational motion and the gross rotational motion of the blade 1500. After cutting the tissue, the remnants may be suctioned out of the instrument 300' via port 240, as described above. The above exemplary steps may be repeated to cut additional tissue.

[0121] The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

[0122] Preferably, the various embodiments described herein will be processed before surgery. First, a new or used instrument is obtained and if necessary cleaned. The instrument can then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK® bag. The container and instrument are then placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, or high-energy electrons. The radiation kills bacteria on the instrument and in the container. The sterilized instrument can then be stored in the sterile container. The sealed container keeps the instrument sterile until it is opened in the medical facility. Sterilization can also be done by any number of ways known to those skilled in the art including beta or gamma radiation, ethylene oxide, and/or steam.

[0123] In various embodiments, an ultrasonic surgical instrument can be supplied to a surgeon with a waveguide and/or end effector already operably coupled with a transducer of the surgical instrument. In at least one such embodiment, the surgeon, or other clinician, can remove the ultrasonic surgical instrument from a sterilized package, plug the ultrasonic instrument into a generator, as outlined above, and use the ultrasonic instrument during a surgical procedure. Such a system can obviate the need for a surgeon, or other clinician, to assemble a waveguide and/or end effector to the ultrasonic surgical instrument. After the ultrasonic surgical instrument has been used, the surgeon, or other clinician, can place the ultrasonic instrument into a sealable package, wherein the package can be transported to a sterilization

facility. At the sterilization facility, the ultrasonic instrument can be disinfected, wherein any expended parts can be discarded and replaced while any reusable parts can be sterilized and used once again. Thereafter, the ultrasonic instrument can be reassembled, tested, placed into a sterile package, and/or sterilized after being placed into a package. Once sterilized, the reprocessed ultrasonic surgical instrument can be used once again.

[0124] Although various embodiments have been described herein, many modifications and variations to those embodiments may be implemented. For example, different types of end effectors may be employed. Also, where materials are disclosed for certain components, other materials may be used. The foregoing description and following claims are intended to cover all such modification and variations.

[0125] Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated material does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

1. A surgical instrument, comprising:
 - a hollow sheath including at least one opening therein and at least one tooth positioned in the opening, wherein the at least one tooth is configured to grip tissue positioned within the at least one opening;
 - a blade disposed at least partially within the hollow sheath;
 - at least one ultrasonic transducer coupled to the blade; and
 - a drive system communicating with the at least one transducer to deliver rotational motions to the blade such that the blade rotates with respect to the hollow sheath when the drive system is activated.
2. The surgical instrument of claim 1, wherein the blade comprises a concave surface positioned next to the at least one opening;
3. The surgical instrument of claim 2, wherein the blade includes an elliptical center that is offset from a rotational axis of the blade.
4. The surgical instrument of claim 1, wherein the at least one tooth comprises a beveled shearing surface.
5. The surgical instrument of claim 1, wherein the blade comprises a screw surface positioned next to the at least one opening.
6. The surgical instrument of claim 1, wherein the blade further includes a lumen defined therein.
7. The surgical instrument of claim 1, wherein the blade is paddle shaped.
8. A surgical instrument, comprising:
 - a sheath, comprising:
 - an opening; and
 - a tissue gripping feature positioned adjacent to the opening;

a rotatable assembly, comprising:

- a blade positioned at least partially within the sheath, wherein the blade comprises:
 - a distal cutting portion aligned with the opening in the sheath; and
 - a proximal attachment portion; and
- an ultrasonic transducer operably coupled to the proximal attachment portion of the blade; and
- a rotary motion generator configured to rotate the rotatable assembly relative to the sheath.

9. The surgical instrument of claim 8, wherein rotatable assembly is configured to rotate about an axis, wherein the sheath comprises a protruding portion protruding away from the axis, and wherein the opening is defined into the protruding portion

10. The surgical instrument of claim 8, wherein the blade comprises a lumen fluidly coupled to a suction port.

11. The surgical instrument of claim 8, wherein the blade comprises a non-uniform cross-sectional geometry.

12. The surgical instrument of claim 8, wherein the distal cutting portion comprises an auger.

13. The surgical instrument of claim 8, wherein the tissue gripping feature comprises a beveled surface.

14. The surgical instrument of claim 8, wherein the tissue gripping feature comprises an annular rib.

15. The surgical instrument of claim 8, wherein the tissue gripping feature comprises a roughened surface.

16. A surgical instrument, comprising:

- a sheath comprising an opening;
- an ultrasonic blade positioned at least partially within the sheath and at least partially aligned with the opening, wherein the ultrasonic blade is configured to vibrate along a longitudinal axis relative to the sheath and rotate about the longitudinal axis relative to the sheath;
- a first drive system comprising a rotatable ultrasonic transducer operably coupled to the ultrasonic blade, wherein the ultrasonic blade is configured to vibrate when the first drive system is activated; and
- a second drive system comprising a rotary motion generator operably coupled to the rotatable ultrasonic transducer, wherein the rotatable ultrasonic transducer and the ultrasonic blade are configured to rotate relative to the sheath when the second drive system is activated.

17. The surgical instrument of claim 16, wherein the sheath further comprises a tissue gripping feature adjacent to the opening.

18. The surgical instrument of claim 16, wherein the ultrasonic blade comprises a lumen in fluid communication with a suction port.

19. The surgical instrument of claim 16, wherein the ultrasonic blade comprises a non-uniform cross-sectional geometry.

20. The surgical instrument of claim 16, wherein the ultrasonic blade comprises a distal auger.

* * * * *

专利名称(译)	带移动切割工具的超声波手术器械		
公开(公告)号	US20150119916A1	公开(公告)日	2015-04-30
申请号	US14/590574	申请日	2015-01-06
[标]申请(专利权)人(译)	伊西康内外科公司		
申请(专利权)人(译)	爱惜康内镜手术，INC.		
当前申请(专利权)人(译)	爱惜康内镜手术，INC.		
[标]发明人	DIETZ TIMOTHY G JOHNSON GREGORY W CONLON SEAN P MUMAW DANIEL J MORGAN JEROME R DANNAHER WILLIAM D VAKHARIA OMAR J TIMM RICHARD W MILLER MATTHEW C ROBERTSON GALEN C		
发明人	DIETZ, TIMOTHY G. JOHNSON, GREGORY W. CONLON, SEAN P. MUMAW, DANIEL J. MORGAN, JEROME R. DANNAHER, WILLIAM D. VAKHARIA, OMAR J. TIMM, RICHARD W. MILLER, MATTHEW C. ROBERTSON, GALEN C.		
IPC分类号	A61B17/32 A61B17/3207 A61B17/22		
CPC分类号	A61B17/320068 A61B17/22004 A61B17/3207 A61B17/320092 A61B2017/00778 A61B2017/00296 A61B17/320783		
其他公开文献	US9962182		
外部链接	Espacenet USPTO		

摘要(译)

在各种实施例中，提供了一种用于在水性环境中操作的手术器械。在至少一个实施例中，外科器械可包括中空护套和至少部分地设置在护套内的刀片。耦合到叶片的可以是至少一个超声换能器，其又可以耦合到驱动系统。驱动系统可以配置成向刀片输送总轴向运动，使得当驱动系统被激活时刀片相对于中空护套平移。因此，刀片可以通过刀片的总轴向移动和/或由超声换能器提供的超声振动来切割组织。在替代实施例中，刀片可以轴向旋转而不是相对于中空护套平移。

