



US006773443B2

(12) **United States Patent**
Truwit et al.

(10) **Patent No.:** **US 6,773,443 B2**
 (45) **Date of Patent:** **Aug. 10, 2004**

(54) **METHOD AND APPARATUS FOR TAKING A BIOPSY**

(75) Inventors: **Charles L. Truwit**, Wayzata, MN (US);
Randal Nelson, Pine Springs, MN (US)

(73) Assignee: **Regents of the University of Minnesota**, Minneapolis, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/919,583**

(22) Filed: **Jul. 31, 2001**

(65) **Prior Publication Data**

US 2002/0077646 A1 Jun. 20, 2002

Related U.S. Application Data

(60) Provisional application No. 60/221,712, filed on Jul. 31, 2000.

(51) **Int. Cl.**⁷ **A61B 17/32**

(52) **U.S. Cl.** **606/169; 606/170; 600/567**

(58) **Field of Search** **606/170, 159, 606/169, 171; 600/564, 566, 567**

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,565,062 A * 2/1971 Kurts 606/169
 4,685,458 A * 8/1987 Leckrone 606/7
 4,886,061 A * 12/1989 Fischell et al. 606/159

5,085,662 A * 2/1992 Willard 606/159
 5,254,082 A * 10/1993 Takase 604/119
 5,527,331 A * 6/1996 Kresch et al. 604/22
 5,571,130 A * 11/1996 Simpson et al. 606/159
 5,674,235 A * 10/1997 Parisi 604/22
 5,792,166 A * 8/1998 Gordon et al. 606/167
 6,027,514 A * 2/2000 Stine et al. 606/159
 6,120,519 A * 9/2000 Weber et al. 606/170
 6,273,862 B1 * 8/2001 Privitera et al. 600/568

OTHER PUBLICATIONS

"Innovative Products Energy-Based Products", <http://www.ethiconendo.com/ultrasonic.jsp>, Ethicon Endo-Surgery, Inc. Johnson & Johnson Company, (Sep. 19, 2003), 5 pages.

* cited by examiner


Primary Examiner—Michael H. Thaler

(74) *Attorney, Agent, or Firm*—Schwegman, Lundberg, Woessner & Kluth, P.A.

(57) **ABSTRACT**

There is described method and apparatus for taking a biopsy wherein the apparatus is formed of a biocompatible cylindrical member with an outer wall and a hollow core, the cylindrical member having a longitudinal axis. An opening in the outer wall of the member is provided and a cutting device cuts tissue entering the opening as it travels along the opening. Cut tissue is treated with a coagulating agent or member so that the coagulation occurs concurrently or just after the tissue is cut wherein the coagulation occurs at a trailing edge of the opening as it travels.

6 Claims, 2 Drawing Sheets






Fig.1




Fig.2




Fig.3




Fig.4




Fig.5

1

METHOD AND APPARATUS FOR TAKING A BIOPSY

This application claims benefit of 60/221,712, filed Jul. 31, 2000.

TECHNICAL FIELD OF THE INVENTION

The present invention relates generally to the field of medicine, and more particularly to an endoscopy biopsy device and its use in medical procedures.

BACKGROUND

Intracranial endoscopy devices include both flexible and rigid endoscopes. These devices typically have at least one channel through which a biopsy device or grabbing forcep device can be delivered. As a result, the combination of a fiberoptic endoscopic channel with a second channel for biopsy device necessitates a minimum diameter. Because of this requirement, endoscopy devices are limited in their applications. Specifically, some neurosurgeons prefer not to introduce a larger caliber device through the brain parenchyma merely to gain access to the ventricular cavity.

In addition, surgeons are occasionally reluctant to biopsy intraventricular mass lesions without direct visualization because of the risk of hemorrhage. Parenchymal lesions, by virtue of their adjacent tissue, offer some support to provide a tamponading effect against hemorrhage following biopsy. Intraventricular lesions, on the other hand, provide no such structural support as a barrier to postbiopsy hemorrhage.

SUMMARY OF THE INVENTION

As described in more detail herein below, the present invention provides method and apparatus for taking a biopsy wherein the apparatus is formed of a biocompatible cylindrical member with an outer wall and a hollow core, the cylindrical member having a longitudinal axis. An opening in the outer wall of the member is provided wherein the opening travels in the direction of the longitudinal axis of the member. A cutting device cuts tissue entering the opening as it travels along the member wherein the cutting occurs in a leading edge of the opening as it travels. Cut tissue is treated with a coagulating agent or member so that the coagulation occurs just after the tissue is cut wherein the coagulation occurs at a trailing edge of the opening as it travels. The opening can be provided with a spiral shaped member having a spiral shaped opening which rotates about the axis of the cylindrical member to provide the moving opening.

BRIEF DESCRIPTION OF THE DRAWING

FIGS. 1–5 illustrate a biopsy device according to various example embodiments of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the invention reference is made to the accompanying drawings which form a part hereof, and in which is shown, by way of illustration, specific embodiments in which the invention may be practiced. In the drawings, like numerals describe substantially similar components throughout the several views. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention. Other embodiments may be utilized and structural, logical, and electrical changes may be made without departing from the scope of the present invention.

2

Referring now to FIG. 1, there is illustrated an example embodiment of method and apparatus for taking a biopsy. An introducer **10** is formed of a biocompatible cylindrical member **12** with an outer wall and a hollow core, the cylindrical member **12** having a longitudinal axis **14**. An opening **16** in the outer wall of the member is provided wherein the opening extends, in one example embodiment, in the direction of the longitudinal axis **14** of the member. A biopsy needle cutting device cuts tissue entering the opening **16** when it is positioned in a body being biopsied, for example but not by way of limitation, in a brain of a patient. In the example embodiment of FIG. 1, the biopsy needle is formed of a rod **30** with U-shaped end **32** that supports a cutting wire **34**. In one embodiment, end **32** bends away from the central axis of rod **30** such that cutting wire **34** is spaced away from the axis of rod **30** with respect to a plane perpendicular to rod **30**. In the case of this embodiment, the cutting wire **34** is similarly moved so as to pass under the opening **16** and cut tissue intruding into opening **16**, allowing the tissue to be retrieved by extraction of the introducer **10**.

In FIG. 3, another example embodiment of a needle is formed of a hollow tube **20** having an outside diameter just smaller than the inside diameter of the introducer **10**, with an opening or window **22** approximately the size of the opening **16**. A cutting wire **24** is positioned on one end of the opening **22**, bridging between points **26** and **28** of the end of tube **20**. As tube **20** travels inside introducer **10**, under control of an operator or automatic controls, with the cutting wire **24** traversing perpendicularly or at an angle to the opening **16**, tissue intruding into opening **16** is cut by wire **24** and is captured in tube **20** or introducer **10**, or both, either of which can be extracted from the body so that a biopsy sample can be retrieved. Tissue may be encouraged to intrude or enter into opening **16** by application of a vacuum to the introducer **10**.

In the example embodiment of FIG. 2, the cutting wire **24** is attached on either end to the cylindrical member **12**. In this embodiment, the member **12** is moved relative to a hollow tube **19** having an opening generally corresponding to opening **16**, and remaining stationary while the biopsy is taken as the cutting member **24** is moved on member **12**.

According to one example embodiment, the biopsy needles and introducer are made of nonconductive materials that are compatible with a magnetic resonance imaging (MRI) device. According to another sample embodiment, the cutting wires **24** and **34** are energized ultrasonically to provide for ultrasonic cutting and coagulation. The cutting wires thus first cut the sample, and then coagulate any blood or bleeding in the cut to prevent postbiopsy bleeding. In this embodiment, the wires **24** and **34** are attached on each end to respective wires that run along the biopsy needles back to an external device capable of producing the ultrasonic energy. According to yet another sample embodiment, the cutter may be formed of a wire or a formed cutting surface (for example a blade) of metal such as titanium or stainless steel or of a non-metal such as ceramic or silicon. According to yet another embodiment, the introducer **10** and biopsy needles are kept in rotational alignment using a keying system or device, so as to insure that the wire is in alignment with the biopsy window or opening **16**. In addition, according to yet another embodiment, the proximal end of the needle has a mark or some other form of indication that the wire has been drawn through the length of the window. Alternatively, the cutter may be set at the proximal end of the window or opening **16** and pushed longitudinally to cut the biopsy sample. In yet another alternative embodiment, the

3

biopsy needle is held stationary with respect to the body, and the introducer **10** is moved providing for relative movement of the cutting edge with respect to the opening **16**.

According to yet another embodiment, the wires **24** and **34** may be energized at a first cutting frequency in order to traverse the opening **16** and cut the tissue therein, and then, energized at a coagulating frequency and traversed across the opening **16** a second time in order to coagulate the tissue and prevent or reduce bleeding.

According to yet another example embodiment shown in FIG. **4**, the needle **60** includes a cutting edge **62** that is formed from or along the outside circumference of the wall **64** of needle **60**. This edge may be straight, or may have a crescent shape, or a combination of both, in one example embodiment. When needle **60** is rotated inside introducer **10**, cutting edge **62** traverses window **16** in a direction such that the blade begins at one corner of the opening and moves diagonally across the opening to the other corner. Cutting occurs beginning at one end **66** of window **16**, and continues in the direction of the end **68**, until the edge **62** has completed traversing the opening **16** in its entirety such that point **70** of the cutting edge reaches point **72** at the corner of opening **16**. This provides that the cutting of the tissue begins in one corner and progresses such that a greater frontal area of the tissue is cut as the blade continues to rotate. The blade thus moves in a direction that is both in part parallel to the longitudinal axis and transverse to the longitudinal axis of the introducer **10**.

In FIG. **5**, there is illustrated yet another example embodiment, identical to the embodiment of FIG. **4**, except for the inclusion of a coagulating member **80** which extends along the outside of wall **64** so as to come into contact with freshly cut tissue just after cutting edge **62** has completed its cut. In this embodiment, member **80** thus prevents the cut tissue from bleeding postbiopsy. According to one embodiment, member **80** may comprise a heated wire or a coagulating agent that is, for example, impregnated in an

4

absorbent material. In another embodiment, member **80** is the distal end of a fiberoptic member which is heated with optical energy supplied to member **80** through an optical fiber (or wire in the case of a heated wire) running out through the introducer **10** to an optical source outside the patient's body, generally indicated as member **82**.

What is claimed is:

1. Apparatus comprising:

a cylindrical introducer member with an outer wall and a hollow core, the cylindrical member having a longitudinal axis and an opening along a side; and

a hollow tube slidable in the hollow core with a hollow tube opening about the size of the opening and a cutting wire positioned on one end of the hollow tube opening.

2. Apparatus of claim **1** wherein the wire is to be energized at a first frequency to cut tissue during a first traverse of the opening and at a second frequency to coagulate the cut tissue during a second traverse of the opening.

3. The apparatus of claim **1**, further comprising an ultrasound energy source coupled to the cutting wire.

4. Apparatus comprising:

a cylindrical introducer member with an outer wall and a hollow core, the cylindrical member having a longitudinal axis and an opening along a side; and

a hollow tube slidable in the hollow core with a hollow tube opening about the size of the opening and a cutting wire positioned at an end of the hollow tube and forming an edge of the hollow tube opening.

5. Apparatus of claim **4** wherein the cutting wire is to be energized at a first frequency to cut tissue during a first traverse of the opening and at a second frequency to coagulate the tissue during a second traverse of the opening.

6. The apparatus of claim **4**, further comprising an ultrasound energy source coupled to the cutting wire.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,773,443 B2
DATED : August 10, 2004
INVENTOR(S) : Truwit et al.

Page 1 of 1


It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page,

Item [56], **References Cited**, U.S. PATENT DOCUMENTS, delete "Kurts" and insert -- Kuris --.

Signed and Sealed this

Thirty-first Day of January, 2006

A handwritten signature in black ink on a light gray dotted background. The signature reads "Jon W. Dudas" in a cursive, stylized script. The "J" is large and loops around the "on". The "W" and "D" are also stylized.

JON W. DUDAS

Director of the United States Patent and Trademark Office

专利名称(译)	用于进行活组织检查的方法和设备		
公开(公告)号	US6773443	公开(公告)日	2004-08-10
申请号	US09/919583	申请日	2001-07-31
[标]申请(专利权)人(译)	TRUWIT CHARLES 大号 NELSON RANDAL		
申请(专利权)人(译)	truwit查尔斯L. NELSON RANDAL		
当前申请(专利权)人(译)	明尼苏达大学校董会		
[标]发明人	TRUWIT CHARLES L NELSON RANDAL		
发明人	TRUWIT, CHARLES L. NELSON, RANDAL		
IPC分类号	A61B10/00 A61B17/22 A61B17/32 A61B18/14 A61B19/00 A61B10/04		
CPC分类号	A61B10/04 A61B17/320068 A61B17/320783 A61B18/14 A61B2017/00911 A61B2017/320069 A61B2017/32007		
优先权	60/221712 2000-07-31 US		
其他公开文献	US20020077646A1		
外部链接	Espacenet USPTO		

摘要(译)

描述了用于进行活组织检查的方法和设备，其中该设备由具有外壁和中空芯的生物相容性圆柱形构件形成，该圆柱形构件具有纵向轴线。提供构件外壁中的开口，并且切割装置在沿着开口行进时切割进入开口的组织。用凝结剂或构件处理切割的组织，使得在切割组织的同时或刚好发生凝固，其中凝固发生在开口行进时的开口的后缘处。

