




US 20140058380A1

(19) **United States**(12) **Patent Application Publication**
Arts et al.(10) **Pub. No.: US 2014/0058380 A1**(43) **Pub. Date: Feb. 27, 2014**(54) **CATHETER WITH REMOTELY EXTENDIBLE INSTRUMENTS**(71) Applicant: **Covidien LP**, Mansfield, MA (US)(72) Inventors: **Gene H. Arts**, Berthoud, CO (US);
Timothy J. Bahney, Portland, OR (US);
John D. Carlton, Las Vegas, NV (US);
Duane E. Kerr, Loveland, CO (US);
William H. Nau, Jr., Longmont, CO (US)(73) Assignee: **Covidien LP**, Mansfield, MA (US)(21) Appl. No.: **14/066,868**(22) Filed: **Oct. 30, 2013****Related U.S. Application Data**

(63) Continuation of application No. 13/670,253, filed on Nov. 6, 2012, now Pat. No. 8,597,291, which is a continuation of application No. 12/202,546, filed on Sep. 2, 2008, now Pat. No. 8,303,581.

Publication Classification(51) **Int. Cl.**
A61B 19/00 (2006.01)
A61B 10/04 (2006.01)**A61F 2/82** (2006.01)**A61B 18/20** (2006.01)**A61B 18/14** (2006.01)**A61M 1/00** (2006.01)**A61B 18/18** (2006.01)(52) **U.S. Cl.**CPC **A61B 19/20** (2013.01); **A61M 1/0058** (2013.01); **A61B 10/04** (2013.01); **A61B****18/1815** (2013.01); **A61B 18/20** (2013.01);**A61B 18/14** (2013.01); **A61F 2/82** (2013.01)USPC **606/33**; 606/130(57) **ABSTRACT**

A method for performing a surgical procedure within lungs of a patient. The method comprising the steps of providing a plurality of surgical instruments and providing a housing. Attaching a flexible, elongated shaft with distal and proximal ends to the housing. Engaging at least one working end to the distal end of the housing, the working end including a plurality of tubes disposed therein that define a corresponding plurality of working channels for housing a corresponding plurality of surgical instruments. Controlling an actuator to engage at least one of the corresponding plurality of surgical instruments, wherein rotation of the working end with respect to a longitudinal axis of the elongated shaft engages at least one of the plurality of surgical instrument with the actuator to deploy the at least one surgical instrument to the lung as needed during a surgical procedure.






FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5




FIG. 6

CATHETER WITH REMOTELY EXTENDIBLE INSTRUMENTS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation of U.S. patent application Ser. No. 13/670,253 filed on Nov. 6, 2012, which is a continuation of U.S. patent application Ser. No. 12/202,546 filed on Sep. 2, 2008, now U.S. Pat. No. 8,303,581, the entire contents of each being incorporated by reference herein.

TECHNICAL FIELD

[0002] The present disclosure relates to devices for use with catheters, endoscopes and other electrosurgical instruments for coagulating tissue. More particularly, the present disclosure relates to a catheter having a series of channels disposed therein for housing a variety of selectively extendible and deployable surgical instruments.

BACKGROUND OF RELATED ART

[0003] This present disclosure relates to instruments and methods for performing minimally invasive, laparoscopic or endoscopic surgical procedures. More particularly, the present disclosure relates to instruments and methods that are especially suitable for procedures that require or benefit from minimally invasive access to anatomical conduits, vessels or tissue for treating the same.

[0004] Over the last several years, minimally invasive or endoscopic surgical tools and methods have been developed for treating vessels and tissue that are less intrusive and less traumatic. For example, with one known technique, the surgeon makes a few small incisions in the abdomen and inserts one or more elongated surgical instruments, e.g., forceps, scissors, clip appliers, staplers, etc., into the incision and carefully manipulates the instruments while viewing the operating area through an endoscope or laparoscope. These techniques are often referred to as endoscopic, laparoscopic, minimally invasive, or video-assisted surgery. References to endoscopic surgery and endoscopes below is intended to encompass all these fields, and the exemplary operations described below with reference to endoscopes can also be accomplished with laparoscopes, gastroscopes, and any other imaging devices which may be conveniently used.

[0005] Typically, many of the above-described techniques require the surgeon to insert different instruments through the working lumen of the catheter to treat tissue, separate vessels or perform other surgical procedures. As can be appreciated, this simply adds to the overall complexity of the operation since it requires the repeated exchange of surgical instruments through the working lumen to perform the different tasks associated with a given surgical procedure.

SUMMARY

[0006] The present disclosure relates to an electrosurgical apparatus for performing a surgical procedure including a housing having an elongated shaft with proximal and distal ends. The shaft includes a plurality of tubes disposed therein that define a corresponding plurality of working channels configured to house a corresponding plurality of surgical instruments. An actuator is included and dimensioned for selective reciprocation within the shaft and configured to operably engage one or more of the corresponding plurality of

surgical instruments and deploy the surgical instrument to an operating cavity as needed during a surgical procedure. The actuator is configured to allow remote operation of the surgical instrument within the operating cavity.

[0007] In one embodiment, the plurality of surgical instruments are arranged in an array-like manner within the working channels of the shaft. In another embodiment, the plurality of surgical instruments is selected from a group consisting of: vessel sealers, coagulators, biopsy instruments, needles, probes, sensors, graspers, forceps, knives, scissors, sutures, balloon dissectors, stents, irrigators, suction devices, stabilizers, blunt dissectors, lasers, optical devices, implants and anchors.

[0008] In yet another embodiment, the actuator includes an actuating cable and/or an electrical cable operably connected thereto. One or more of the cables are utilized to engage, deploy and/or operate one or more of the plurality of surgical instruments.

[0009] The housing is adapted to connect to an electrosurgical generator, an irrigation source, a suction source and/or accessory equipment configured to operably connect to at least one of the plurality of surgical instruments. The electrosurgical generator, irrigation source, suction source and/or accessory equipment may be configured to include a controller disposed thereon for remotely controlling the actuator and/or a sensor disposed thereon for indexing the plurality of surgical instruments attached to the flexible shaft.

[0010] The present disclosure also relates to an electrosurgical apparatus for performing a surgical procedure having a housing with an elongated flexible shaft attached thereto with proximal and distal ends and a working end including a plurality of tubes disposed therein that define a corresponding plurality of working channels configured to house a corresponding plurality of surgical instruments. The working end is selectively engageable with the distal end of the elongated shaft. An actuator is included that is dimensioned for selective reciprocation within the shaft and configured to operably engage the corresponding plurality of surgical instruments and deploy one or more of the corresponding plurality of surgical instruments to an operating cavity as needed during a surgical procedure. A sensor may be disposed on the housing for indexing (from each of the working ends) the plurality of surgical instruments attached to the flexible shaft.

[0011] The present disclosure also relates to a method for performing a surgical procedure and includes the steps of: providing a housing and attaching a flexible, elongated shaft with distal and proximal ends to the housing; engaging one or more working ends (in series) to the distal end of the housing, the working end including a plurality of tubes disposed therein that define a corresponding plurality of working channels for housing a corresponding plurality of surgical instruments; and controlling an actuator to engage one or more of the corresponding plurality of surgical instruments and deploy the corresponding surgical instrument(s) to an operating cavity as needed for use during a surgical procedure.

[0012] The method may also include the steps of indexing the plurality of surgical instruments disposed in the working end(s); and providing feedback to the surgeon relating to the status and/or location ("stored", "deployed", "in use", "disposed" and/or "malfunction") of each of the plurality of surgical instruments.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 is a front, perspective view of electrosurgical instruments shown extending through working channels of a flexible shaft of a catheter in accordance with one embodiment of the present disclosure;

[0014] FIG. 2 is a schematically-illustrated, enlarged, side perspective view of one embodiment of the present disclosure showing a working end for use with the elongated shaft having selectively extendable instruments disposed therein;

[0015] FIG. 3 is a schematically-illustrated, internal view of the present disclosure showing various selectively extendable instruments disposed therein and a deployment tool;

[0016] FIGS. 4A-4C are schematically-illustrated, greatly enlarged, sequential views of a biopsy tool for use with the catheter of FIG. 1;

[0017] FIG. 5 is a schematically-illustrated, enlarged view showing an exchangeable instrument magazine for use with the catheter of FIG. 1; and

[0018] FIG. 6 is a schematically-illustrated, enlarged view showing a series of exchangeable magazines for use with the catheter of FIG. 1.

DETAILED DESCRIPTION

[0019] Referring now to FIG. 1, a multi-port catheter, generally identified by reference numeral 10 is shown. Catheter 10 includes a proximal end 13, a distal end 15 and an elongated shaft 12 disposed therebetween. In the drawings and in the description that follows, the term “proximal”, as is traditional, will refer to the end of the forceps that is closer to the user, while the term “distal” will refer to the end of the forceps that is further from the user.

[0020] The proximal end 13 of catheter is operably engaged to a housing 16 that, in turn, operably connects to an electrosurgical generator 50 and accessory equipment 60 via cables 55 and 65, respectively. Accessory equipment 60 is configured to support one or more of the various features associated with the surgical instruments attached to catheter 10 as explained in more detail below, e.g., suction, irrigation, gas supply, optical equipment, steering and actuating handles and/or act as an alternate energy source for supporting instruments with alternate energy capabilities, e.g., microwave, ultrasound laser, etc.

[0021] As shown in FIGS. 1-3, shaft 12 is generally elongated and flexible to facilitate negotiating various cavities and other internal structures of an operating cavity and includes a plurality of working channels 14a-14d defined in a general, array-like manner therein and that extend therethrough. The shaft 12 may be rigid in an alternative embodiment. Housing 16 may include a similar plurality of channels 16a and 16b defined therein that align in registration with one or more respective channels 14a-14d defined in shaft 12 to facilitate remotely controlling one or more surgical instruments. Alternatively, one or more deployment actuators or tools 320 may be utilized to control the various surgical instruments, as explained in detail below. Housing 16 may also include one or more instrument controllers 20 disposed thereon that are actuatable to control (activate, rotate, extend, operate, articulate, etc.) one or more surgical instruments or the deployment tool 320.

[0022] Turning now to FIG. 2 which shows one embodiment of the catheter 10 having four tubes 110a-110d disposed therein that define four channels 107a-107d for housing a corresponding number of surgical instruments, e.g., instru-

ments 125 and 135. More particularly, the distal end 15 of shaft 12 is configured to operatively engage one or more working ends 205 and 105 that are, in turn, configured to house one or more surgical instruments, e.g., surgical instruments 125 and 135, therein. As shown, working end 205 is configured to removeably engage distal end 15 or may be configured to be integrally associated therewith. Working end 205, in turn, includes a plurality of mechanical interfaces 203, 204, 206a and 206b that are dimensioned to operably engage a corresponding plurality of interfaces 103, 104, 106a and 106b disposed working end 105.

[0023] The mechanically engaging interfaces, namely, interfaces, 203, 204, 206a and 206b on end 205 and the mechanically engaging interfaces, 103, 104, 106a and 106b on end 105 are configured to assure accurate and consistent alignment of the internal working channels 110a-110d, mechanical actuators 115a, 115b and internal electrical connections 117. As such, the various electrical and mechanical connections of working end 105 are universal and allow selective replacement (or interchangeability) of different working ends onto working end 205 as needed. A surgeon can select a working end 105 containing specific surgical tools needed for a particular surgical procedure and engage the working end 105 onto end 205, thereby reducing the need to feed a new surgical instrument down the channel of the catheter 10 for each use. Alternatively, a surgeon may manually load working end 105 with specific instruments needed for a particular surgical procedure or order a custom set of instruments that is loaded by a manufacturer.

[0024] As explained in more detail below with respect to the operation of the catheter 10, the surgeon has the ability to rotate the working end 105 independently (or with shaft 12) to orient a new surgical instrument, e.g., instrument 125, for use inside a operating cavity as needed without compromising the integrity of the operating cavity and without having to replace instruments during a surgical procedure due to sterilization or mechanical issues. Moreover, each instrument, e.g., instrument 125, may be rotated into place and deployed (via controllers 20 and actuators 115a and 115b) either separately or in tandem as needed. Certain channels, e.g., channels 107b and 107d, may be left available in case a new or unanticipated instrument is needed during a given procedure.

[0025] For example, the working end 105 may include a vessel sealing device 125 and an electrosurgical pencil 135, which are each independently deployable, activatable and controllable via one or more controllers 20 disposed on the housing 16 or as part of the accessory equipment 60. Vessel sealer 125 is configured to allow a surgeon to selectively and remotely grasp, dissect, manipulate, seal and/or cut vessels and tissue. Electrosurgical pencil 135 allows a surgeon to remotely coagulate and cut vessels and tissue. When not in use, each instrument, e.g., sealer 125, is housed within a corresponding channel or pocket 110a disposed in working end 105. A remote actuator, e.g., actuator 115a, is activated to deploy the vessel sealer 125 from the distal end 103 of the working end 105.

[0026] Actuator 115a may be multifunctional and include one or more cables or other electrical connections that enable the surgeon to deploy, rotate, articulate, extend and otherwise operate the surgical instrument during use thereof. Similarly, electrical connections 117 may be multifunctional as well and allow the surgeon to activate various electrical components of

the surgical instrument as well as actuate various electrically-controlled operating components (motors, solenoids, gears, etc.).

[0027] Other instruments may be selected as part of a given working end **105** that perform different functions depending upon the particular surgery involved. Examples of instruments that may be utilized within the various working channels include vessel sealing instruments e.g., as described in commonly-owned U.S. Pat. No. 7,771,425, electrosurgical pencils, e.g., as described in commonly-owned U.S. Pat. No. 7,879,033 and ablation instruments, e.g., as described in commonly-owned U.S. Pat. No. 7,879,031. Other instruments and devices that may be utilized include: biopsy instruments, needles, probes, sensors, graspers, forceps, knives, scissors, sutures, stents, irrigators, balloon dissectors, suction devices, stabilizers, blunt dissectors, lasers, optical devices, implants, anchors, tissue ablaters, etc. These instruments may be housed within the articulating members of the end of the shaft **12**.

[0028] FIG. 3 shows another embodiment of a working end **305** for use with catheter **10** that includes two internally disposed channels **307a** and **307b** defined therein for use in deploying various surgical instruments **335a-335d**. Channels **307a** and **307b** are generally offset relative to one another and extend through the distal end **303** of working end **305**, thereby allowing independent and/or simultaneous deployment of surgical instruments **335a-335d** to the operating cavity. Working end **305** also includes a plurality of elongated cavities **310a-310d** disposed around the internal peripheral surface thereof that are dimensioned to house one or more instruments therein. Similar to the working ends **105** and **205** above, working end **305** may be configured to house various surgical instruments needed for a particular surgical procedure, thereby reducing the need to feed a new surgical instrument down the channels **307a**, **307b** of the catheter **10** for each use.

[0029] Working end **305** also includes a deployment tool **320** that operably connects to one or more controllers on the housing **16** that is configured to allow selective deployment and control of a particular surgical instrument into a respective working channel, e.g., **307a**, and into the operating cavity. More particularly, deployment tool **320** includes a shaft **318** that is selectively reciprocateable within the catheter **10** to allow a surgeon the ability to selectively engage a desired surgical instrument, e.g., instrument **335c**, from the surgical instrument's respective cavity **310c** and deploy the instrument **335c** into the operating cavity via a working channel **307a** or **307b**. The deployment tool **320** may include a universal coupling **315** disposed at a distal end thereof that is configured to engage a corresponding coupling **322a**, **322c** disposed on the surgical instrument **335a**, **335c**, respectively. The universal coupling **315** may be multifunctional and include one or more actuators, cables or electrical connections that enable the surgeon to engage, deploy, rotate, articulate, extend and otherwise operate the surgical instrument (or components thereof, e.g., various electrically-controlled operating components (motors, solenoids, gears, etc.)) during use.

[0030] In the particular embodiment shown in FIG. 3, the various tools include an electrosurgical pencil **335a**, a needle electrode **335b**, a biopsy tool **335c** and a deployable stent **335d**. Again, other instruments may also be housed within the various cavities of working end **305** including: probes, sensors, graspers, forceps, knives, scissors, sutures, irrigators,

suction devices, stabilizers, dissectors, lasers, optical devices, implants, anchors, tissue ablaters, etc.

[0031] The remote proximal end **13** of the catheter shaft **12**, the housing **16** or the accessory equipment **60** may include one or more sensors or indexing devices **17** that are configured to locate, orient or "index" the various surgical instruments disposed within working end **305** and, e.g., the cavity location and/or particular function of each instrument. For example, the housing **16** (or equipment **60**) may include a sensor or an indexing tool (or other visual indicator) **17** that corresponds to both instrument type and instrument location within the working end **305**. The surgeon may then manually engage a desired surgical instrument (or activate an automatic instrument engagement protocol) based on the indexing information displayed on the housing **16** (or equipment **60**). Moreover, it is contemplated that a second set of cavities (not shown) may be defined within the working end **305** for "used" instruments, sample specimens or additional working components (e.g., additional stents).

[0032] Sensors **17** may also be used to confirm engagement/disengagement of the proper instrument, mechanical failure, or various operating characteristics of the surgical instruments as needed during use, impedance matching, temperature monitoring, etc. Various tissue parameters may also be determined by the sensor(s) **17**, e.g., tissue impedance, tissue temperature, tissue moisture, etc.

[0033] FIGS. 4A-4C shows an example of a surgical instrument or tool **435** that may be selectively deployable from one or more of the hereindescribed working ends for use with catheter **10**. More particularly, and similar to the instruments described above, instrument **435** is a biopsy tool configured to fit within working channel **407** defined in tube **402**. A tool actuator **415** is reciprocateable within the working channel **407** and allows a surgeon to remotely operate the biopsy tool **435** as needed. For example, the biopsy instrument **435** is initially deployed by moving the actuator **415** distally past the end of working channel **407** which opens a pair of cup-like opposing jaws **436a** and **436b** of the biopsy tool **435** about a pivot **438** via a spring bias **427** disposed at the proximal end of the tool **435**. Once the opposing jaws **436a** and **436b** are opened, the biopsy tool **435** may be moved into position to engage specimen tissue **1000** as shown in FIG. 4A.

[0034] Once positioned, the surgeon pulls the actuating tool proximally (while maintaining shaft **12** in place), which forces the opposing jaws **436a** and **436b** to close about the tissue specimen **1000** as shown in FIG. 4B. The edges of the opposing jaw members **436a** and **436b** include sharpened edges that allow the jaw members **436a** and **436b** to cut and capture the tissue specimen **1000** between the jaw members **436a** and **436b**. Once the tissue **1000** is cut, the surgeon continues to pull the tool **435** proximally so that the tissue specimen **1000** may be safely stored between the opposing jaw members **436a** and **436b** within working channel **507** (See FIG. 4C).

[0035] FIG. 5 shows another embodiment of a working end **505** for use with catheter **10** that includes one or more internally disposed tubes **502a** and **502b** having channels **507a** and **508a** defined therein for use in deploying various surgical instruments, e.g., instrument **535** within channel **507a**. More particularly, working end **505** is selectively engageable with end **205** of catheter **10** in a similar manner described above with respect to FIG. 2. In the instance wherein the actuating and electrical cables need to be properly aligned to operate a

particular surgical instrument, it is necessary to ensure proper alignment of the working channels **507a** and **210a** of ends **505** and **205**, respectively.

[0036] For example, in order to ensure actuating cables **515** and **215** align for proper operation of instrument **535**, the proximal end **525a** of tube **502a** may be configured to align with the distal end **225a** of tube **202a**. One or more alignment interfaces **532** and **232** may be employed on ends **525a** and **225a**, respectively. The alignment interfaces **532** and **232** may also be employed to register the electrical cables **517** and **217** on each end **525a** and **225a**. Ideally, the mechanical interfaces **532a** and **232a** are universal connections or interfaces, thereby allowing interchangeability of various working ends of surgical instrumentation with differently configured or “loaded” configurations of surgical tools. The mechanical interfaces **532a** and **232a** may be threaded, snap-fit, tongue and groove or any other suitable type of mating connectable interfaces.

[0037] FIG. 6 shows another embodiment of a catheter **10** that includes a series of interchangeable working ends **605a-605c** that may be selectively engaged to end **205** of catheter **10**. Each interchangeable working end **605a-605c** includes a plurality of cavities **610a-610d**, **610a'-610d'** and **610a''-610d''** defined therein for housing various surgical instruments. One or more mechanical interfaces (similar to the mechanical interfaces **532** and **232** described above) may be employed to align and/or secure the plurality of working ends **605a-605c** to one another and/or to end **205**. A deployment tool **615** may be utilized to remotely engage, deploy and/or operate any one of the instruments, e.g., instruments **635a**, **635b**, within the operating cavity as needed. For example, in the particular arrangement shown in FIG. 6, as many as twelve instruments may be used within a surgical cavity without having to remove and insert instrumentation in a conventional manner. One or more actuating cables **615** and electrical connections **617** may be employed to permit remote engagement, deployment and operation of the various surgical instrumentation as needed.

[0038] The present disclosure also relates to a method for performing a surgical procedure and includes the steps of: providing a housing and attaching a flexible, elongated shaft with distal and proximal ends to the housing. The method also includes the additional steps of: engaging one or more working ends (in series) to the distal end of the housing, the working end including a plurality of tubes disposed therein that define a corresponding plurality of working channels for housing a corresponding plurality of surgical instruments, and controlling an actuator to engage one or more of the corresponding plurality of surgical instruments and deploy the corresponding surgical instrument to an operating cavity as needed for use during a surgical procedure.

[0039] The method may also include the steps of indexing the plurality of surgical instruments disposed in the working end(s), and providing feedback to the surgeon relating to the status and/or location of each of the plurality of surgical instruments. The feedback relating to the status and/or location of each of the plurality of surgical instruments may include indicia displayed on the housing such as: “stored”, “deployed”, “in use”, “disposed” and/or “malfunction”.

[0040] From the foregoing and with reference to the various figure drawings, those skilled in the art will appreciate that certain modifications can also be made to the present disclosure without departing from the scope of the present disclosure. For example and as mentioned above, the housing,

generator, suction/irrigation equipment and/or the accessory equipment may include a sensor or indexing mechanism or tool which orients and “indexes” the various surgical instruments, before, during or after use. The indexing tool may be configured to provide real-time feedback to the surgeon as to the status and location of each instrument. As a new instrument or magazine of instruments is added or interchanged, the indexing tool automatically (or manually) updates the display or index on the appropriate system component (e.g., housing, generator, suction/irrigation equipment and/or the accessory equipment) thereby providing accurate information to the surgeon.

[0041] Moreover, there have been described and illustrated herein several embodiments of a catheter with various working ends for treating tissue and performing other surgical procedures. While particular embodiments of the disclosure have been described, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of particular embodiments. Those skilled in the art will envision other modifications within the scope and spirit of the claims appended hereto.

1-12. (canceled)

13. An apparatus, comprising:

a housing;

an elongated shaft extending from the housing, the elongated shaft including a plurality of channels each of which including at least one actuator, the elongated shaft including at least one mechanical interface at a distal end thereof; and

at least one working end including at least one mechanical interface at a proximal end thereof and a plurality of channels each of which including at least one surgical instrument, the at least one working end engageable with the distal end of the elongated shaft to engage the at least one mechanical interface of the at least one working end with the at least one mechanical interface at the distal end of the elongated shaft for aligning the plurality of channels of the at least one working end with the plurality of channels of the elongated shaft to allow selective deployment of the at least one surgical instrument from the at least one working end.

14. The apparatus according to claim 13, wherein at least one of the plurality of channels of the elongated shaft houses at least one electrical connection configured to deploy the at least one surgical instrument from the at least one working end.

15. The apparatus according to claim 13, wherein the at least one surgical instrument included in each of the plurality of channels is individually selected from the group consisting of vessel sealers, coagulators, biopsy instruments, needles, probes, sensors, graspers, forceps, knives, scissors, sutures, stents, irrigators, balloon dissectors, suction devices, stabilizers, blunt dissectors, lasers, optical devices, implants, tissue ablaters and anchors.

16. The apparatus according to claim 13, wherein the housing is adapted to connect to at least of an energy source, an irrigation source, a suction source or accessory equipment configured to operably connect to the at least one surgical instrument.

17. The apparatus according to claim 16, wherein the energy source is selected from the group consisting of electrosurgical generators, ultrasound generators and microwave generators.

18. The apparatus according to claim 13, wherein the at least one surgical instrument included in each of the plurality of channels includes at least a biopsy tool and an electrosurgical probe.

19. The apparatus according to claim 18, wherein the electrosurgical probe connects to a microwave generator and enables the application of microwave energy to treat tissue.

20. The apparatus according to claim 13, wherein the elongated shaft is sized to traverse the passages of a lung.

21. The apparatus according to claim 13, wherein the at least one mechanical interface on the working end and the elongated shaft are one of threaded, tongue and groove fit, or snap-fit.

22. A method for performing a surgical procedure within a lung of a patient, comprising:

navigating a distal end of an elongated shaft of a surgical apparatus to target tissue within a lung of a patient;

engaging mechanical interfaces disposed on each of a working end of the surgical apparatus and the elongated shaft with one another for aligning a plurality of channels including a first surgical instrument of the working end with a plurality of channels including at least one actuator of the elongated shaft in a first configuration to allow selective deployment of the at least one surgical instrument from the working end;

actuating the at least one actuator to deploy the first surgical instrument from the working end;

disengaging the mechanical interfaces from one another and realigning the plurality of channels of the working end with the plurality of channels of the elongated shaft to a second configuration that is different from the first configuration; and

actuating the at least one actuator to deploy a second surgical instrument from the working end.

23. The method of claim 22, further including indexing the first and second surgical instruments and providing feedback

to a surgeon relating to at least one of the status and location of each of the first and second surgical instruments.

24. The method of claim 23, wherein providing feedback includes utilizing indicia displayed on a housing of the surgical apparatus, the indicia including at least one of "stored", "deployed", "in use", "disposed" and "malfunction".

25. The method of claim 22, further including arranging the first and second surgical instruments in an array-like manner within the plurality of channels of the working end.

26. The method of claim 22, wherein the first and second surgical instruments are selected from the group consisting of vessel sealers, coagulators, biopsy instruments, needles, probes, sensors, graspers, forceps, knives, scissors, sutures, stents, irrigators, balloon dissectors, suction devices, stabilizers, blunt dissectors, lasers, optical devices, implants, tissue ablaters and anchors.

27. The method of claim 22, further including connecting a housing of the surgical apparatus to at least one of an energy source, an irrigation source, a suction source or accessory equipment configured to operably connect to at least one of the first and second surgical instruments.

28. The method of claim 27, wherein connecting the housing of the surgical apparatus to the at least one energy source includes coupling a sensor to at least one of the housing of the surgical apparatus, electrosurgical generator, irrigation source, suction source or accessory equipment for indexing the at least one first and second surgical instruments.

29. The method of claim 27, wherein connecting the housing of the surgical apparatus to the at least one energy source includes utilizing a microwave source.

30. The method of claim 29, wherein utilizing the microwave source includes applying microwave energy to the target tissue within the lung of the patient.

31. The method of claim 22, including, when in the first configuration, the first surgical instrument is configured to one of grasp, manipulate, or seal the target tissue.

32. The method of claim 31, including, when in the second configuration, the second surgical instrument is configured to one of biopsy, dissect, or cut the target tissue.

* * * * *

专利名称(译)	具有远程可扩展仪器的导管		
公开(公告)号	US20140058380A1	公开(公告)日	2014-02-27
申请号	US14/066868	申请日	2013-10-30
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	COVIDIEN LP		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	ARTS GENE H BAHNEY TIMOTHY J CARLTON JOHN D KERR DUANE E NAU JR WILLIAM H		
发明人	ARTS, GENE H. BAHNEY, TIMOTHY J. CARLTON, JOHN D. KERR, DUANE E. NAU, JR., WILLIAM H.		
IPC分类号	A61B19/00 A61B10/04 A61F2/82 A61B18/20 A61B18/14 A61M1/00 A61B18/18		
CPC分类号	A61B19/20 A61M1/0058 A61B10/04 A61F2/82 A61B18/20 A61B18/14 A61B18/1815 A61B17/3421 A61B10/06 A61B17/00234 A61B17/0469 A61B17/29 A61B17/320016 A61B18/1206 A61B18/1442 A61B18/1445 A61B18/1477 A61B18/1492 A61B18/24 A61B90/10 A61B2017/00292 A61B2017/00362 A61B2017/00464 A61B2017/320044 A61B2017/320048 A61B2017/320064 A61B2017/3445 A61B2017/3449 A61B2018/00166 A61B2018/00589 A61B2018/00601 A61B2018/0063 A61B2018/00755 A61B2018/00791 A61B2018/00875 A61B2018/1425 A61B2018/1861 A61B2217/005 A61B2217/007 A61F2/95 A61M2025/004		
其他公开文献	US9375283		
外部链接	Espacenet USPTO		

摘要(译)

一种用于在患者的肺内执行外科手术的方法。该方法包括提供多个手术器械和提供壳体的步骤。将具有远端和近端的柔性细长轴附接到壳体。使至少一个工作端接合到壳体的远端，工作端包括设置在其中的多个管，这些管限定相应的多个工作通道，用于容纳相应的多个手术器械。控制致动器以接合相应的多个外科器械中的至少一个，其中工作端相对于细长轴的纵向轴线的旋转接合多个外科器械中的至少一个与致动器以至少展开在外科手术过程中根据需要将一个手术器械送到肺部。

