



US007083579B2

(12) **United States Patent**
Yokoi et al.

(10) **Patent No.:** **US 7,083,579 B2**
(45) **Date of Patent:** **Aug. 1, 2006**

(54) **ENCAPSULATED MEDICAL DEVICE AND METHOD OF EXAMINING, CURING, AND TREATING INTERNAL REGION OF BODY CAVITY USING ENCAPSULATED MEDICAL DEVICE**

(75) Inventors: **Takeshi Yokoi**, Hino (JP); **Hironobu Takizawa**, Hachioji (JP); **Hidetake Segawa**, Hachioji (JP); **Hideyuki Adachi**, Sagamihara (JP)

(73) Assignee: **Olympus Corporation**, Toyko (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 632 days.

(21) Appl. No.: **10/251,443**

(22) Filed: **Sep. 20, 2002**

(65) **Prior Publication Data**

US 2003/0060734 A1 Mar. 27, 2003

(30) **Foreign Application Priority Data**

Sep. 27, 2001 (JP) 2001-297703

(51) **Int. Cl.**

A61B 5/117 (2006.01)

A61B 5/103 (2006.01)

(52) **U.S. Cl.** **600/593**

(58) **Field of Classification Search** 600/549, 600/561, 593, 309, 437, 562; 604/28, 65; 607/92; 606/32; 128/903

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,028,687 A 6/1977 Hamaguchi et al.

FOREIGN PATENT DOCUMENTS

JP 7-111985 5/1995

JP 9-327447 12/1997

JP 2000-342522 12/2000

Primary Examiner—Max F. Hindenburg

Assistant Examiner—Brian Szmal

(74) *Attorney, Agent, or Firm*—Scully, Scott, Murphy & Presser, P.C.

(57) **ABSTRACT**

An encapsulated medical device includes a radio antenna through which the encapsulated medical device transmits or receives a radio wave to or from an extracorporeal device. The encapsulated medical device is passed through the lumen of a body cavity in order to examine, cure, or treat an internal region of the body cavity under the control of the extracorporeal device. A capsule body included in the encapsulated medical device has an extended portion formed at an upper end of one axis of a cross section of the capsule body cut at right angle to the longitudinal axis thereof. The capsule body has a linkage hole bored in the extended portion thereof to allow a fluid such as a gas or humor to flow into and backward parts of the lumen through the hole.

31 Claims, 19 Drawing Sheets




FIG. 1





FIG. 2

FIG.3B




FIG.3A




FIG.3C




FIG.4




FIG.5




FIG.6





FIG. 7

FIG.8C




FIG.8A




FIG.8B




FIG.9A




FIG.9B




FIG.10B




FIG.10A




FIG.11A





FIG.11B






FIG. 13B




FIG. 13A




FIG. 13C




FIG. 13D




FIG. 14

FIG.15




FIG. 16B




FIG. 16A







FIG.17**FIG.19****FIG.20**

FIG. 18




FIG.22B

FIG.22A




FIG.23B




FIG.23A




FIG.24A





FIG.24B



ENCAPSULATED MEDICAL DEVICE AND METHOD OF EXAMINING, CURING, AND TREATING INTERNAL REGION OF BODY CAVITY USING ENCAPSULATED MEDICAL DEVICE

This application claims the benefit of Japanese Application No. 2001-297703 filed in Japan on Sep. 27, 2001, the contents of which are incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to an encapsulated medical device, and a method of examining, curing, and treating an internal region of a body cavity using the encapsulated medical device.

2. Description of the Related Art

Conventionally, an endoscope is used to examine, cure, or treat an intended region by inserting an elongated inserting section thereof, which is coupled to an operation unit, into a body cavity. It is however hard to keep the endoscope inserted therein for a prolonged period of time.

For example, Japanese Unexamined Patent Application Publication No. 2000-342522, and Japanese Unexamined Patent Application Publications Nos. 7-111985 and 9-327447 which the present applicant filed previously have proposed peroral medical devices capable of examining, curing, or treating an internal region.

The Japanese Unexamined Patent Application Publication No. 2000-342522 has proposed a peroral endoscope. The peroral endoscope has a balloon, which is used to immobilize the endoscope at an intended region of the lumen of a body cavity, included in the front part of an inserting section thereof.

The Japanese Unexamined Patent Application Publication Nos. 7-111985 and 9-327447 propose encapsulated medical devices. The encapsulated medical devices have various sensor means and power supply means disposed on the surface of a capsule body.

However, in the peroral endoscope described in the Japanese Unexamined Patent Application Publication No. 2000-342522 has a drawback that the balloon comes into close contact with the internal surface of a body cavity to block the lumen of the body cavity. Consequently, the balloon comes to a standstill on the internal surface of the body cavity in a stenosed part thereof. Moreover, in the peroral endoscope, a hole or a groove, which allows a fluid such as a gas or humor to flow forwards or backwards in the lumen, is not formed between the balloon and an endoscope body, in the balloon itself, nor in a portion of the endoscope body other than the portion having the balloon. Therefore, when the peroral endoscope described in the Japanese Unexamined Patent Application Publication No. 2000-342522 comes to a standstill on the internal surface of the body cavity in the stenosed part thereof, a fluid such as a gas or humor cannot flow forwards or backwards in the lumen.

In contrast, the encapsulated medical devices described in the Japanese Unexamined Patent Application Publication Nos. 7-111985 and 9-327447 have a plurality of means including various sensor means and power supply means fixed on the periphery of a capsule body. The outer diameter of the capsule body is large when all over the periphery thereof is included. The capsule body therefore comes into close contact with the internal surface of a body cavity to block the lumen of the body cavity. Consequently, the

capsule body comes to a standstill on the internal surface of the body cavity in a stenosed part thereof.

In the encapsulated medical devices, concave parts of the periphery of the capsule body created by various sensor means and the power supply means are shallow. Therefore, when the capsule body comes to a standstill on the internal surface of the body cavity in a stenosed part thereof, the concave parts hardly allow a fluid such as a gas or humor to flow forwards or backwards in the lumen. The encapsulated medical devices have been developed without concern about the incident that the capsule body may come to a standstill in a stenosed part of a lumen. No description has been made of the incident that the capsule body may come to a standstill in a stenosed part of a lumen.

For example, in relation to the encapsulated medical device, alarm devices for livestock or especially for delivery including the one described in U.S. Pat. No. 4,028,687 have been proposed. The alarm device is inserted into the birth canal so that it will alarm at the time of delivery.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide an encapsulated medical device and a method of examining, curing, or treating an internal region of a body cavity using the encapsulated medical device. Herein, the encapsulated medical device allows a fluid such as a gas or humor to flow forwards or backwards in the lumen even when a capsule body comes to a standstill in a stenosed part of the body cavity. Nevertheless, the capsule body is highly general-purpose and the ease of swallowing of the encapsulated medical device does not deteriorate.

Another object of the present invention is to provide an encapsulated medical device capable of safely protecting the internal surface of a body cavity despite its coming into close contact with the internal surface thereof, and a method of examining, curing, or treating an internal region of a body cavity using the encapsulated medical device.

Still another object of the present invention is to provide an encapsulated medical device permitting a doctor or a co-medical to judge whether a disease, bleeding, or any other abnormality is found or to judge at what position or in what state a capsule is passing, and a method of examining, curing, or treating an internal region of a body cavity using the encapsulated medical device.

Still another object of the present invention is to provide an encapsulated medical device that when coming into close contact with the internal surface of, for example, the small intestine in a stenosed part thereof to block the lumen of the small intestine, allowing a fluid such as a gas or humor to flow into regions spreading ahead of and behind the stenosed part, and a method of examining, curing, or treating an internal region of a body cavity using the encapsulated medical device.

Still another object of the present invention is to provide an encapsulated medical device permitting diagnosis of whether an abnormality is found in the direction of the depth of a deep region in the lumen of, for example, the small intestine, and a method of examining, curing, or treating an internal region of a body cavity using the encapsulated medical device.

According to the present invention, an encapsulated medical device consists mainly of a capsule body and fluid passage forming means. The capsule body passes through the lumen of a body cavity so as to examine, cure, or treat an internal region of the body cavity. The fluid passage forming means is included in the capsule body. When the

capsule body passes through the lumen of a body cavity, if the capsule body comes into close contact with the internal surface of the body cavity to block the lumen of the body cavity, the fluid passage forming means forms a fluid passage which links the forward and backward parts of the lumen.

According to the method of examining, curing; or treating an internal region of a body cavity using an encapsulated medical device in accordance with the present invention, fluid passage forming means included in a capsule body, when the capsule body comes into close contact with the internal surface of a body cavity to block the lumen of the body cavity, forms a fluid passage that links the forward and backward parts of the lumen.

Other features of the present invention and the advantages thereof will be fully apparent from the description below.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the overall configuration of a medical system including a first embodiment of the present invention;

FIG. 2 is a circuit block diagram showing an encapsulated medical device in accordance with the first embodiment of the present invention;

FIG. 3A is a sectional view showing the components of the encapsulated medical device shown in FIG. 2;

FIG. 3B shows the appearance of the front part of the encapsulated medical device shown in FIG. 3A;

FIG. 3C shows the appearance of the back part of the encapsulated medical device shown in FIG. 3A;

FIG. 4 is a sectional view showing a scene where the encapsulated medical device shown in FIG. 3A to FIG. 3C is passing through the esophagus;

FIG. 5 is a sectional view showing a scene where the encapsulated medical device shown in FIG. 3A to FIG. 3C has come to a standstill in a stenosed part of the small intestine;

FIG. 6 is a sectional view of the encapsulated medical device shown in FIG. 5;

FIG. 7 is a schematic explanatory diagram showing a scene where the encapsulated medical device is being recovered using a string-like recovering tool;

FIG. 8A is a sectional view showing the components of an encapsulated medical device of a variant having a linkage groove formed in an extended portion thereof;

FIG. 8B shows the appearance of the front part of the encapsulated medical device shown in FIG. 8A;

FIG. 8C shows the appearance of the back part of the encapsulated medical device shown in FIG. 8A;

FIG. 9A is a sectional view showing the components of an encapsulated medical device of a variant whose center axis passing through the center of the minor axis of a cross section thereof cut at right angle to the longitudinal axis thereof is deviated from the optical axis of an observation unit included therein;

FIG. 9B shows the appearance of the front part of the encapsulated medical device shown in FIG. 9A;

FIG. 10A shows the appearance of an encapsulated medical device of a variant that has extended portions of a capsule body formed on both ends of one axis of the cross section of the capsule body;

FIG. 10B shows the appearance of the front part of the encapsulated medical device that is shown in FIG. 10A and that is passing through the esophagus;

FIG. 11A is an explanatory diagram showing an encapsulated medical device of a variant that has a linkage hole bored obliquely with respect to the longitudinal axis thereof;

FIG. 11B is an explanatory diagram showing an encapsulated medical device of a variant that has a linkage hole bored to be tortuous with respect to the longitudinal axis thereof;

FIG. 12A is an explanatory diagram showing the appearance of an encapsulated medical device of a variant that has a plurality of projections formed on the periphery of a capsule body;

FIG. 12B shows the appearance of the front part of the encapsulated medical device shown in FIG. 12A;

FIG. 13A is a sectional view showing the components of an encapsulated medical device in accordance with a second embodiment of the present invention;

FIG. 13B is an A—A sectional view of the encapsulated medical device shown in FIG. 13A;

FIG. 13C is a B—B sectional view of the encapsulated medical device shown in FIG. 13A;

FIG. 13D is a C—C sectional view of the encapsulated medical device shown in FIG. 13A;

FIG. 14 is a D—D sectional view of the encapsulated medical device shown in FIG. 13B;

FIG. 15 is a sectional view showing a scene where the encapsulated medical device shown in FIG. 13A to FIG. 14 has come to a standstill in a stenosed part of the small intestine;

FIG. 16A is a sectional view showing the components of an encapsulated medical device in accordance with a third embodiment of the present invention;

FIG. 16B is an E—E sectional view of the encapsulated medical device shown in FIG. 16A;

FIG. 17 is an explanatory diagram showing an encapsulated medical device of a variant that has a capsule body thereof covered with a transparent member that is an armor member;

FIG. 18 is an explanatory diagram showing a scene where the encapsulated medical device shown in FIG. 17 has come to a standstill in a stenosed part of the small intestine;

FIG. 19 is an explanatory diagram showing an encapsulated medical device of a variant that has a net-like mesh cover (mesh jacket) serving as an armor member freely detachably attached to a capsule body thereof;

FIG. 20 is an explanatory diagram showing a scene where the encapsulated medical device shown in FIG. 19 has come to a standstill in a stenosed part of the small intestine;

FIG. 21A is an explanatory diagram showing an encapsulated medical device of a variant that has an elastic rubber cover, which has a spiral groove formed therein and serves as an armor member, freely detachably attached to a capsule body thereof;

FIG. 21B is a perspective view showing the elastic rubber cover shown in FIG. 21A;

FIG. 22A is a sectional view showing an encapsulated medical device in accordance with a fourth embodiment of the present invention;

FIG. 22B is an F—F sectional view of the encapsulated medical device shown in FIG. 22A;

FIG. 23A shows the appearance of the encapsulated medical device that is shown in FIG. 22A and FIG. 22B and that has a balloon thereof expanded;

FIG. 23B is a G—G sectional view of the encapsulated medical device shown in FIG. 23A;

FIG. 24A is a sectional view showing an encapsulated medical device of a variant that has an armor member, which includes a balloon, freely detachably attached to the periphery of a capsule body; and

FIG. 24B is an H—H sectional view of the encapsulated medical device shown in FIG. 24A.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be described with reference to the drawings below.

First Embodiment

FIG. 1 to FIG. 12B are concerned with a first embodiment of the present invention. FIG. 1 shows the overall configuration of a medical system including the first embodiment of the present invention. FIG. 2 is a circuit block diagram showing the encapsulated medical device in accordance with the first embodiment of the present invention. FIG. 3A is a sectional view showing the components of the encapsulated medical device shown in FIG. 2. FIG. 3B shows the appearance of the front part of the encapsulated medical device shown in FIG. 3A. FIG. 3C shows the appearance of the back part of the encapsulated medical device shown in FIG. 3A. FIG. 4 is a sectional view showing a scene where the encapsulated medical device shown in FIG. 3A to FIG. 3C is passing through the esophagus. FIG. 5 is a sectional view showing a scene where the encapsulated medical device shown in FIG. 3A to FIG. 3C has come to a standstill in a stenosed part of the small intestine. FIG. 6 is a sectional view of the encapsulated medical device shown in FIG. 5. FIG. 7 is a schematic explanatory diagram showing a scene where the encapsulated medical device is being recovered using a string-like recovering tool. FIG. 8A is a sectional view showing the components of an encapsulated medical device of a variant that has a linkage groove formed in an extended portion thereof. FIG. 8B shows the appearance of the front part of the encapsulated medical device shown in FIG. 8A. FIG. 8C shows the appearance of the back part of the encapsulated medical device shown in FIG. 8A. FIG. 9A is a sectional view showing the components of an encapsulated medical device of a variant whose center axis passing through the center of the minor axis of a cross section thereof that is cut at right angle to the longitudinal axis thereof is deviated from the optical axis of an observation unit included therein. FIG. 9B shows the appearance of the front part of the encapsulated medical device shown in FIG. 9A. FIG. 10A shows the appearance of an encapsulated medical device of a variant that has extended portions of a capsule body formed on both ends of an axis of the cross section of the capsule body. FIG. 10B shows the appearance of the front part of the encapsulated medical device that is shown in FIG. 10A and that is passing through the esophagus. FIG. 11A is an explanatory diagram showing an encapsulated medical device of a variant that has a linkage hole formed obliquely with respect to the longitudinal axis of the device. FIG. 11B is an explanatory diagram showing an encapsulated medical device of a variant that has a linkage hole formed to be tortuous with respect to the longitudinal axis of the device. FIG. 12A is an explanatory diagram showing the appearance of an encapsulated medical device of a variant that has a plurality of projections formed on the periphery of a capsule body thereof. FIG. 12B shows the appearance of the front part of the encapsulated medical device shown in FIG. 12A.

As shown in FIG. 1, an encapsulated medical device 1 transmits or receives radio waves to or from an extracorporeal device 3 while passing through the lumen of a body cavity of a patient 2. The encapsulated medical device 1 can examine, cure, or treat an internal region under the control of the extracorporeal device 3. The encapsulated medical device 1 and extracorporeal device 3 constitute a medical system 4.

The medical system 4 is designed to examine the esophagus, duodenum, small intestine, or large intestine according to a method described below. For example, the method of a screening of the esophagus, duodenum, small intestine, or large intestine is performed such that the encapsulated medical device 1 is, like a medicine, swallowed together with water or the like after the completion of pretreatment for, for example, the large intestine (intestinal cleansing). If the medical system 4 is used to deal with the esophagus or the like, the encapsulated medical device 1 quickly passes through the esophagus. In this case, the esophagus is visualized at a rate of 10 frames per sec. If the medical system 4 is used to deal with the small intestine or the like, the encapsulated medical device 1 slowly passes through the small intestine. In this case, the small intestine is visualized at a rate of two frames per sec. The picked up images are subjected to required signal processing and digital compression, transferred to the extracorporeal device 3, and then recorded. Consequently, required information alone can be visualized in the form of a motion picture in order to facilitate diagnosis.

To begin with, the extracorporeal device 3 will be described.

The extracorporeal device 3 consists mainly of a personal computer 11, a keyboard 12, a monitor 13, and an extracorporeal antenna 14. The personal computer 11 has the function to control the encapsulated medical device 1. The keyboard 12 is connected to the personal computer 11 and used to enter commands or data. The monitor 13 is connected to the personal computer 11 and serves as a display means for displaying images or the like. The extracorporeal antenna 14 is connected to the personal computer 11, sends a control signal that is used to control the encapsulated medical device 1, and receives a signal sent from the encapsulated medical device 1.

The extracorporeal device 3 produces a control signal, which is used to control the encapsulated medical device 1, by pressing the key-entry on the keyboard 12 or by using a control program stored on a hard disk incorporated in the personal computer 11. In the extracorporeal device 3, the produced control signal is transferred to a transmission circuit incorporated in the personal computer 11, modulated using a carrier of a predetermined frequency, and transmitted in the form of a radio wave through the extracorporeal antenna 14.

The encapsulated medical device 1 receives the radio wave through a radio antenna 21 that will be described later, demodulates the control signal carried by the radio wave, and outputs the control signal to respective circuits.

Moreover, the extracorporeal device 3 receives through the extracorporeal antenna 14 information (data) signals such as a video signal which are sent from the encapsulated medical device 1 through the radio antenna 21. The information signal is then transferred to the monitor 13 to display the image.

Next, the components of the encapsulated medical device 1 in accordance with the present embodiment will be detailed in conjunction with FIG. 2 and FIG. 3A to FIG. 3C.

The encapsulated medical device of the present embodiment is designed exclusively for examination (observation) use.

The encapsulated medical device **1** consists mainly of the radio antenna **21**, a radio transmission/reception circuit **22**, an illuminator **23**, an observation unit **24**, a digital signal processing circuit **25**, a battery unit **26**, and a switch **27**. Radio waves are transmitted or received to or from the extracorporeal device **3** through the radio antenna **21**. The radio transmission/reception circuit **22** processes signals of a radio wave that is transmitted or received through the radio antenna **21**. The illuminator **23** is composed of light-emitting diodes (LEDs) that generate illumination light with which the lumen of a body cavity is illuminated. The observation unit **24** picks up an optical image of a body cavity illuminated with the illumination light emanating from the illuminator **23**. The digital signal processing circuit **25** digitally processes an image signal produced by the observation unit **24**. A battery **26a** that includes cells and delivers supply power is placed in the battery unit **26**. The switch **27** is turned on or off in order to put the supply power, which is delivered from the battery unit **26**, to an on-state or off-state level.

The radio transmission/reception circuit **22** selectively samples a carrier that is a radio wave received from the extracorporeal device **3** through the radio antenna **21**, detects the waveform of a control signal, and demodulates the control signal. The control signal is then transferred to respective circuits. Moreover, the radio transmission/reception circuit **22** modulates information (data) signals including a video signal and being sent from the circuits by using a carrier of a predetermined frequency, and transmits the carrier in the form of a radio wave through the radio antenna **21**.

The observation unit **24** includes an objective optical system **31**, an image pickup sensor **32**, and an image pickup drive circuit **33**. The objective optical system **31** forms an optical image. The image pickup sensor **32** includes a complementary metal oxide semiconductor (CMOS) and picks up the optical image formed by the objective optical system **31**. The image pickup drive circuit **33** drives the image pickup sensor **32**.

The digital signal processing circuit **25** includes a digital video signal processing circuit (hereinafter, a video signal processing circuit) **34** and a digital compression circuit (hereinafter, a compression circuit) **35**. The video signal processing circuit **34** processes an image signal produced by the image pickup sensor **32** and converts it into a digital video signal. The compression circuit **35** compresses the digital video signal produced by the video signal processing circuit **34**.

The battery unit **26** delivers supply power from the battery **26a** placed therein to the illuminator **23**, digital signal processing circuit **25**, and radio transmission/reception circuit **22** via the switch **27**. The supply power delivered from the battery **26a** is routed to the observation unit **24** via the digital signal processing circuit **25**.

Moreover, the encapsulated medical device **1** has a permanent magnet (hereinafter, simply, a magnet) **36** incorporated therein. The magnet is needed in order to recover the encapsulated medical device, which comes to a standstill in the lumen of a body cavity, using a string-like recovering tool that has a magnet included in the front part thereof and that will be described later (see FIG. 7).

As shown in FIG. 3A to FIG. 3C, the encapsulated medical device **1** includes a cylindrical capsule body **1A** that can be passed through the lumen of a body cavity in order to examine, cure, or treat an internal region of the body

cavity and that is sealed to be airtight using a transparent body armor member **41**. The encapsulated medical device **1** has built-in components, which include the aforesaid illuminator **23** and observation unit **24**, placed in the capsule body **1A**. To be more specific, the encapsulated medical device **1** has the objective optical system **31**, which is included in the observation unit **24**, placed in the center of the front part of the capsule body **1A**. Moreover, the encapsulated medical device **1** has the image pickup sensor **32** disposed at the position of the image plane of the objective optical system **31**.

The image pickup drive circuit **33** encircles the image pickup sensor **32**. The digital signal processing circuit **25** is disposed proximally to the image pickup drive circuit **33** and image pickup sensor **32**. The radio transmission/reception circuit **22** is disposed proximally to the digital signal processing circuit **25**.

The illuminators **23** are disposed at the periphery of the objective optical system **31**, and illuminates a point in front of the capsule body **1A** via the body armor member **41**. In the drawing, the illuminator **23** is composed of, for example, four LEDs.

The battery unit **26** is located behind the radio transmission/reception circuit **22**. The battery **26a** composed of, for example, three cells is stored in the battery unit **26**. If the switch **27** is pressed, the battery unit **26** delivers supply power via the switch **27**. The radio antenna **21** as well as the magnet **36** is disposed behind the battery unit **26**.

The encapsulated medical device **1** has the aforesaid built-in components held in the body armor member **41** while being reinforced and borne by a metallic ring reinforcement member that is not shown. The encapsulated medical device **1** is designed to have a size permitting the patient **2** to swallow the capsule body **1A** easily.

In the present embodiment, the capsule body **1A** has an extended portion **42**. The extended portion **42** is formed at one end of one axis of the cross section of the capsule body **1A** cut at right angle to the longitudinal axis thereof, such that the cross section of the capsule body **1A** is non-circular. Herein, provided that the capsule body **1A** does not have the extended portion **42**, the cross section of the capsule body **1A** is substantially circular. The capsule body **1A** not only has the extended portion **42** that serves as fluid passage forming means but also a linkage hole **43** that serves as a fluid passage that allows a fluid such as a gas or humor to flow forwards or backwards in a lumen. Consequently, when the capsule body **1A** comes into close contact with the internal surface of a body cavity to block the lumen of the body cavity, a fluid such as a gas or humor flows forwards or backwards in the lumen through the linkage hole **43**.

Next, actions to be performed in the encapsulated medical device **1** of the present embodiment will be described below.

As shown in FIG. 1, when the lumen of a body cavity of the patient **2**, for example, the lumen of a stomach **51** thereof must be observed for a prolonged period of time, an operator asks the patient **2** to swallow the encapsulated medical device **1**. Thus, the encapsulated medical device **1** passes through the lumen of the stomach **51**. At this time, immediately before the patient **2** swallows the encapsulated medical device **1**, the operator turns on the switch **27** of the encapsulated medical device **1**. Consequently, supply power is delivered from the battery **26a** in the battery unit **26** to the illuminator **23**, observation unit **24**, digital signal processing circuit **25**, and radio transmission/reception circuit **22** respectively.

The encapsulated medical device **1** passes through an oral cavity **52**, descends an esophagus **53**, and enters the stomach

51. At this time, as shown in FIG. 4, the major axis of the cross section of the esophagus 53 is approximately 16 mm long and the minor axis thereof is approximately 14 mm long. The encapsulated medical device 1 can therefore pass through the esophagus readily.

If the lumen of the stomach 51 must be observed, an operator makes key-entry at, for example, the keyboard 12 included in the extracorporeal device 3 so as to input an observation start command. Consequently, a control signal produced responsively to the key-entry is radiated in the form of a radio wave through the extracorporeal antenna 14 and thus transmitted from the extracorporeal device 3 to the encapsulated medical device 1.

The encapsulated medical device 1 detects an operation start signal in the signal received through the radio antenna 21. Consequently, the radio transmission/reception circuit 22, illuminator 23, observation unit 24, and digital signal processing circuit 25 are driven.

The illuminator 23 emits illumination light towards a field of view offered by the observation unit 24. An optical image of an illuminated region falling within the field of view is picked up by the image pickup sensor 32 included in the observation unit 24, and photoelectrically converted into an image signal. The picked-up image signal is converted into a digital video signal by the video signal processing circuit 34 included in the digital signal processing circuit 25, compressed by the compression circuit 35, and modulated by the radio transmission/reception circuit 22. The resultant signal is radiated in the form of a radio wave through the radio antenna 21.

The extracorporeal device 3 receives the radio wave through the extracorporeal antenna 14. The received radio wave is demodulated by a receiving circuit included in the personal computer 11 and converted into a digital signal by an A/D converter included in the personal computer 11. The resultant digital signal is stored in a memory and read at a predetermined rate. Consequently, the picked-up optical image is displayed in colors on the monitor 13. The operator views the image so as to observe the lumen of the stomach 5 of the patient 2. The optical image may be recorded in an image recording device that is not shown.

After the observation of the stomach 51 is completed, the encapsulated medical device 1 is inched outwards from the stomach 51, and taken out through the anus, which is not shown, by way of a duodenum 54, small intestine 55, and large intestine 56. Meanwhile, the encapsulated medical device 1 permits observation of the lumen of the alimentary canal.

At this time, the encapsulated medical device 1 may, as shown in FIG. 5, come to a standstill in a stenosed part 55a of the lumen of the small intestine 55. In this case, as shown in FIG. 6, the encapsulated medical device 1 comes into close contact with the internal surface of the small intestine in the stenosed part 55a of the small intestine 55 to block the lumen thereof.

In this case, the encapsulated medical device 1 must be, as shown in FIG. 7, recovered using a string-like recovering tool 60.

However, it takes much time to recover the encapsulated medical device 1 using the string-like recovering tool 60. Meanwhile, a conventional encapsulated medical device fails to allow a fluid 61 such as a gas or humor to flow forwards or backwards beyond the stenosed part 55a of the small intestine 55 in the lumen thereof.

In the encapsulated medical device 1 of the present embodiment, the linkage hole 43 is bored as a fluid passage in the extended portion 42. The fluid 61 such as a gas or

humor can therefore flow forwards or backwards beyond the stenosed part 55a of the small intestine 55 in the lumen thereof. The encapsulated medical device 11 is then recovered using the sting-like recovering tool 60.

Consequently, if the encapsulated medical device 1 of the present invention comes to a standstill in a deep region in the lumen of a body cavity such as the small intestine 55 for a prolonged period of time, the fluid 61 such as an intestinal gas or humor can flow forwards or backwards in the lumen. Nevertheless, the ease of swallowing does not deteriorate.

Moreover, an encapsulated medical device may have a linkage groove formed, as shown in FIG. 8A to FIG. 8C, in the extended portion 42 of the capsule body 1A on behalf of the linkage hole 43.

As shown in FIG. 8A to FIG. 8C, an encapsulated medical device 71 has a linkage groove 73 formed in an extended portion 72 of a capsule body 71A.

The extended portion 72 has chamfers 74 formed on the banks of the linkage groove 73. Consequently, even when the extended portion 72 comes into close contact with the internal surface of a body cavity, the extended portion 72 safely protects the internal surface.

Similarly to the encapsulated medical device 1, when the encapsulated medical device 71 comes into close contact with the internal surface of a body cavity to block the lumen of the body cavity, a fluid such as a gas or humor flows forwards or backwards in the lumen through the linkage groove 73. The other components are identical to those of the encapsulated medical device 1, and the description of the components will therefore be omitted.

Consequently, the encapsulated medical device 71 provides the same advantages as the aforesaid encapsulated medical device 1.

Moreover, an encapsulated medical device may be designed so that the center axis thereof passing the center of the minor axis of the cross section thereof cut at right angle to the longitudinal axis thereof will be, as shown in FIG. 9A and FIG. 9B, deviated from the optical axis of the observation unit 24.

As shown in FIG. 9A and FIG. 9B, an encapsulated medical device 81 is designed so that a center axis 82 of a capsule body 81A passing the center of the minor axis of the cross section thereof cut at right angle to the longitudinal axis thereof is deviated from the optical axis 83 of the observation unit 24.

Moreover, the encapsulated medical device 81 has linkage holes 43 bored in an extended portion 84 that is disposed on the side of the optical axis 83 of the observation unit 24 opposite to the center axis 82 passing the center of the cross section cut at right angle to the longer axis. As for the linkage holes 43, for example, three linkage holes are formed symmetrically to one another with respect to the major axis 85 of the cross section. The linkage holes 43 may be replaced with linkage grooves 73.

Consequently, the encapsulated medical device 81 can be designed to permit slightly oblique vision with the optical axis of the observation unit 24 tilted relative to the center axis 82 passing the center of the minor axis of the cross section of the device cut at right angle to the longitudinal axis direction thereof.

Moreover, an encapsulated medical device may include a capsule body that has, as shown in FIG. 10A and FIG. 10B, extended portions formed at both ends of one axis of the cross section thereof.

As shown in FIG. 10A and FIG. 10B, an encapsulated medical device 91 includes a capsule body 91A that has an upper extended portion 92 and a lower extended portion 93

formed at both ends of one axis of the cross section thereof. Consequently, the cross section of the capsule body cut at right angle to the longitudinal axis thereof is elliptic. FIG. 10B shows the encapsulated medical device **91** passing through the esophagus **53**. Since the cross section of the esophagus **53** is elliptic, the encapsulated medical device **91** can readily pass through the esophagus.

The encapsulated medical device **91** has the linkage groove **73** formed in the upper extended portion **92** and the linkage hole **43** formed in the lower extended portion **93**. The linkage groove **73** and linkage hole **43** are substantially symmetrically to each other with respect to the minor axis **94** of the cross section of the encapsulated medical device. Alternatively, the encapsulated medical device **91** may have the linkage hole **43** formed in the upper extended portion and the linkage groove **73** formed in the lower extended portion **93**. Otherwise, the linkage hole **43** or linkage groove **73** may be formed in each of the upper and lower extended portions **92** and **93**. The encapsulated medical device **91** may have a plurality of linkage grooves **73** or linkage holes **43** formed symmetrically to one another with respect to the major axis **95** of the cross section thereof at the ends of which the upper and lower extended portions **92** and **93** are formed.

Moreover, the encapsulated medical device **91** may have various types of sensors disposed on the periphery of the capsule body **91A** in such a manner that the sensing portions of the sensors are exposed to outside and the interior of the device is kept watertight.

The encapsulated medical device **91** has an optical sensor **96**, which detects the brightness of the interior of a living body, disposed on the periphery of the tip of the capsule body **91A**. The encapsulated medical device **91** includes a pH sensor **97** and a temperature sensor **98** disposed on the periphery of the back of the capsule body **91A**. The pH sensor **97** detects a chemical quantity (pH) of an intracavitary juice, and the temperature sensor **98** detects the temperature of each organ. Various types of sensors may include, in addition to the optical sensor **96**, pH sensor **97**, and temperature sensor **98**, a pressure sensor that detects the pressure applied from the internal surface of a lumen to the external surface of the capsule body **91A** during passage of the capsule body through the lumen, and a hemoglobin sensor that detects an amount of hemoglobin in each organ (whether each organ is bleeding).

Information (data) acquired by the sensing portion of each of the various types of sensors is temporarily stored in a memory, which is not shown, in the capsule body **91A**. Thereafter, the information (data) is modulated by the radio transmission/reception circuit **22** in the same manner as it is described in relation to the encapsulated medical device **1**, and radiated in the form of a radio wave through the radio antenna **21**. The radio wave is received by the extracorporeal device **3** through the extracorporeal antenna **14**, demodulated by a reception circuit included in the personal computer **11**, and temporarily stored as information (data) in the memory. Thereafter, the information (data) stored in the memory is compared with a reference value stored in advance in the memory by a central processing unit (CPU) included in the personal computer **11**. The result of comparison is displayed on the monitor **13**. Consequently, an operator such as a doctor or a co-medical can judge whether an abnormality such as a disease or bleeding is found or a position or state at or in which the capsule body passes.

In particular, the encapsulated medical device **91** permits judgment of an alimentary disease or physiological analysis thereof when designed to measure a pH or an amount of hemoglobin in the alimentary canal of a living body. The

encapsulated medical device **91** is therefore very useful. When a plurality of types of sensors are included as various types of sensors in the encapsulated medical device **91**, examinations can be achieved efficiently.

Moreover, an encapsulated medical device may be, as shown in FIG. 11A and FIG. 11B, designed so that the linkage hole **43** will intersect the longitudinal axis of the device but not be parallel with the longitudinal axis.

As shown in FIG. 11A, an encapsulated medical device **101** has the linkage hole **43** formed in a capsule body **101A** slightly obliquely with respect to the longitudinal axis **102** of the capsule body **101A** but not in parallel with the longitudinal axis **102**. Moreover, as shown in FIG. 11B, an encapsulated medical device **103** has the linkage hole **43** formed in a capsule body **103A** to be tortuous but not be parallel with the longitudinal axis **102**.

The encapsulated medical devices **101** and **103** shown in FIG. 11A and FIG. 11B each have a distal opening **43a** bored in the front part of the capsule body **101A** or **103A** and a back opening **43b** bored in the back part thereof. The distal opening **43a** and back opening **43b** serve as the entrances or exits of the linkage hole **43**.

Moreover, an encapsulated medical device may be, as shown in FIG. 12A and FIG. 12B, designed to have a plurality of projections formed on the periphery of a capsule body so as to form a fluid passage.

Specifically, as shown in FIG. 12A and FIG. 12B, an encapsulated medical device **110** has a plurality of projections **111** formed on the periphery of a capsule body **110A**. Consequently, when the encapsulated medical device **110** comes into close contact with the internal surface of the small intestine **55** in a stenosed part **55a** thereof to block the lumen of the small intestine, the fluid **61** such as a gas or humor can flow forwards or backwards beyond the stenosed part **55a** of the small intestine by way of concave parts **111a** formed among the plurality of projections **111**. Herein, reference numeral **112** denotes a projection type pressure sensor whose sensing portion is a projection. The pressure sensors **112** are used to detect pressures, whereby the fact that the encapsulated medical device **110** has blocked, for example, the lumen of the small intestine **55** is sensed.

Moreover, the encapsulated medical device **110** is designed to spray a medicine. Specifically, the encapsulated medical device **110** has a medicine spray opening **113a** bored in the front part thereof so that a medicine preserved in a medicine reservoir **113** in the capsule body **110A** can be sprayed.

Furthermore, the encapsulated medical device **110** is designed to sample a humor. Specifically, the encapsulated medical device **110** has a humor infusion opening **114a** bored in the back part thereof so that a humor can be sampled and infused into a humor reservoir **114** in the capsule body **110A**. Opening or closing the openings **113a** and **114a** is controlled by the extracorporeal device **3** over a communication link in the same manner as described in relation to the first embodiment. Consequently, the encapsulated medical device **110** can discharge the medicine from the medicine reservoir **113** and spray it through the medicine spray opening **113a** in an intended region. Moreover, a humor can be sampled and infused into the humor reservoir **114** through the humor infusion opening **114a**.

Incidentally, the encapsulated medical device **110** may be designed to be able to mix a medicine in the medicine reservoir **113** with a humor sampled through the humor infusion opening **114a**, discharge the mixture through the medicine spray opening **113a**, and thus spray the mixture.

13

According to the present embodiment, the present invention is implemented in an encapsulated medical device that has the radio antenna **21** through which data is transmitted or received to or from the extracorporeal device **3**, and that is passed through the lumen of a body cavity in order to examine, cure, or treat an internal region of the body cavity under the control of the extracorporeal device **3**. The present invention is not limited to this type of encapsulated medical device. The present invention may be implemented in an encapsulated medical device that does not have the radio antenna **21** and that is passed through the lumen of a body cavity and then recovered in order to obtain information (data) of the optical image and the like, outside the living body.

Second Embodiment

FIG. **13A** to FIG. **15** are concerned with a second embodiment of the present invention. FIG. **13A** is a sectional view showing the components of an encapsulated medical device in accordance with the second embodiment of the present invention. FIG. **13B** is an A—A sectional view of the encapsulated medical device shown in FIG. **13A**. FIG. **13C** is a B—B sectional view of the encapsulated medical device shown in FIG. **13A**. FIG. **13D** is a C—C sectional view of the encapsulated medical device shown in FIG. **13A**. FIG. **14** is a D—D sectional view of the encapsulated medical device shown in FIG. **13A**. FIG. **15** is a sectional view showing a scene where the encapsulated medical device shown in FIG. **13A** to FIG. **14** has come to a standstill in a stenosed part of the small intestine.

In the aforesaid first embodiment, the encapsulated medical device is formed with one capsule body. In the second embodiment, a capsule body is divided into a distal hard member and a back hard member. The distal hard member and back hard member are linked with a flexible string-like member. The other components are nearly identical to those of the first embodiment. The description of the components will be omitted, and the same reference numerals will be assigned to the components.

As shown in FIG. **13A** to FIG. **13C**, an encapsulated medical device **120** of the second embodiment has a capsule body thereof composed of a distal hard member **121** and a back hard member **122** that are linked by a flexible string-like member **123**.

The distal hard member **121** and back hard member **122** are, similarly to the capsule body of the encapsulated medical device of the first embodiment, shaped like cylinders and covered with a transparent body armor member **41** to be kept airtight. Each of the distal hard member **121** and back hard member **122** has an extended portion **124** formed at the upper end of one axis of the cross section thereof cut at right angle to the longitudinal axis thereof. The cross section of each of the distal hard member **121** and back hard member **122** is non-circular, though the cross section thereof without the extended portion **124** is substantially circular.

The distal hard member **121** has, similarly to the capsule body of the encapsulated medical device **1** of the first embodiment, the observation unit **24**, illuminator **23**, digital signal processing circuit **25**, and radio transmission/reception circuit **22** placed therein. The distal hard member **121** has the radio antenna **21** disposed in the center of the extended portion **124**.

As shown in FIG. **14**, the extended portion **124** of the distal hard member **121** has the linkage holes **43**, which serve as a fluid passage, formed across the radio antenna **21**. In contrast, the back hard member **122** has the battery unit

14

26 placed therein. The switch **27** to be turned on or off in order to put supply power, which is delivered from the battery unit **26**, to an on-state or off-state level is disposed in the center of the extended portion **124**. Moreover, the back hard member **122** has the magnet **36** placed in the back part thereof. In the extended portion **124** of the back hard member **122**, the linkage holes **43** serving as a fluid passage are formed across the switch **27**.

The string-like member **123** is formed with an armor watertight member such as a urethane tube. The string-like member **123** is structured so that electric cables **123a** led out from the battery unit **26** in the back hard member **122** can run through the string-like member **123** and supply power delivered from the battery unit **26** can be routed to the distal hard member **121**. Referring to FIG. **13D**, the number of electric cables **123a** is four so that the electric cables **123a** will lead to the observation unit **24**, illuminator **23**, digital signal processing circuit **25**, and radio transmission/reception circuit **22** respectively.

The encapsulated medical device **120** of the second embodiment having the foregoing components is, similarly to the encapsulated medical device **1** described as the first embodiment, swallowed by the patient **2** for use.

The encapsulated medical device **120** passes through the oral cavity **52**, descends the esophagus **53**, and enters the stomach **51**. The encapsulated medical device **120** then captures images in the lumen of the stomach **51** using the image pickup sensor **32**. The image data is radiated in the form of a radio wave through the radio antenna **21**. Consequently, the images are displayed on the monitor of the extracorporeal device **3**.

Thereafter, assume that the encapsulated medical device **120** comes to a standstill in the stenosed part **55a** of, for example, the small intestine **55** and comes into close contact with the internal surface of the small intestine to block the lumen of the small intestine.

Nevertheless, as far as the encapsulated medical device **120** of the second embodiment is concerned, the linkage holes **43** are bored as a fluid passage in the extended portions **12**. The fluid **61** such as a gas or humor can flow forwards or backwards beyond the stenosed part **55a** of the small intestine **55** in the lumen of the small intestine. Thereafter, the encapsulated medical device **120** is recovered using the string-like-recovering tool **60** in the same manner as it is described in relation to the first embodiment.

Consequently, the encapsulated medical device **120** of the present embodiment provides the same advantages as the one of the first embodiment. Furthermore, according to the present embodiment, an encapsulated medical device can be designed more compactly.

Third Embodiment

FIG. **16A** to FIG. **21B** are concerned with a third embodiment of the present invention. FIG. **16A** is a sectional view showing the components of an encapsulated medical device in accordance with the third embodiment of the present invention. FIG. **16B** is an E—E sectional view of the encapsulated medical device shown in FIG. **16A**. FIG. **17** is an explanatory diagram showing an encapsulated medical device of a variant that has a capsule body thereof covered with a transparent member that is an armor member. FIG. **18** is an explanatory diagram showing a scene where the encapsulated medical device shown in FIG. **17** has come to a standstill in a stenosed part of the small intestine. FIG. **19** is an explanatory diagram showing an encapsulated medical device of a variant that has a net-like mesh cover (mesh

jacket) freely detachably attached to a capsule body thereof. FIG. 20 is an explanatory diagram showing a scene where the encapsulated medical device shown in FIG. 19 has come to a standstill in a stenosed part of the small intestine. FIG. 21A is an explanatory diagram showing an encapsulated medical device of a variant that has an elastic rubber cover, which serves as an armor member and has a spiral groove formed therein, freely detachably attached to a capsule body thereof. FIG. 21B is a perspective view showing the elastic rubber cover shown in FIG. 21A.

In the first and second embodiments, the linkage hole 43 or linkage groove 73 that is a fluid passage is formed in an extended portion of a capsule body that serves as fluid passage forming means. In the third embodiment, a fluid passage can be formed in an armor member that is freely detachably attached to the periphery of a capsule body and that serves as fluid passage forming means. The other components are nearly identical to those of the first or second embodiment. The same reference numerals will be assigned to the components, and the description of the components will be omitted.

As shown in FIG. 16A and FIG. 16B, an encapsulated medical device 130 of the third embodiment has a capsule body, which accommodates nearly the same built-in components as those described in relation to the first embodiment, as a distal hard member 131. The distal hard member 131 and a back hard member 132 are linked using a string-like member 123.

The distal hard member 131 does not have, unlike the capsule body described as a component of the first embodiment, the extended portion 42. Instead, the distal hard member 131 has notches 133 that are located at the top and bottom of a substantially circular cross section of the distal hard member 131, and the right and left sides of the cross section. A hard tubular member 134 that is an armor member is freely detachably attached to the periphery of the distal hard member 131, whereby the linkage holes 43 are formed between the internal surface of the hard tubular member 134 serving as fluid passage forming means and the notches 133.

On the other hand, the back hard member 132 has, similarly to the distal hard member 131, a tubular member 134, which serves as a fluid passage forming member, freely detachably attached to the periphery thereof in which the notches 133 are formed. Thus, the linkage holes 43 are formed.

Moreover, the back hard member 132 faces in a direction opposite to a direction in which the distal hard member 131 faces, thus permitting observation of the backward part of the lumen of a body cavity which lies in a direction opposite to a direction of advancement. A back-side illuminator 23b, a back-side observation unit 24b, a back-side digital signal processing circuit 25b, and a back-side radio transmission/reception circuit 22b are placed in the back hard member 132. Supply power is delivered from the battery unit 26 included in the distal hard member to the back hard member 132 by way of the string-like member 123.

In the back hard member 132, the back-side radio transmission/reception circuit 22b detects a signal, which is received by the distal hard member 131 through the radio antenna 21, by way of the string-like member 123. Responsively to the detection of the signal, the back-side illuminator 23b, back-side observation unit 24b, and back-side digital signal processing circuit 25b are driven.

In the back hard member 132, the back-side radio transmission/reception circuit 22b modulates video data which the back-side observation unit 24 produces by picking up an optical image. Consequently, the video data is transferred to

the distal hard member 131 by way of the string-like member 123 and radiated in the form of a radio wave through the radio antenna 21. Incidentally, the distal and back hard members 131 and 132 included in the encapsulated medical device 130 may be realized with a sole unit similarly to the capsule body included in the first embodiment.

Consequently, the encapsulated medical device 130 of the third embodiment provides the same advantages as the second embodiment. In addition, a view of a backward region can be produced.

Moreover, an encapsulated medical device may have a capsule body thereof covered with, as shown in FIG. 17, a transparent member that is an armor member.

Specifically, an encapsulated medical device 140 has, as shown in FIG. 17, a capsule body 140A thereof covered with a transparent plastic armor member 141.

The armor member 141 encloses the periphery of the capsule body 140A with a gap between them. A plurality of through-holes 142 that open into the gap and serve as linkage holes are bored in each of the distal and back parts of the capsule body 140A. Consequently, the encapsulated medical device 140 allows the fluid 61 such as a gas or humor to flow into the gap through the through-holes 142 and then flow out of the distal or back part thereof through the through-holes 142. The components of the capsule body 140A are identical to those of the distal hard member 131 described in conjunction with FIG. 16A and FIG. 16B. The description of the components will therefore be omitted.

When the encapsulated medical device 140 having the foregoing components blocks the lumen of, for example, the small intestine 55 in the stenosed part 55a thereof, the fluid 61 such a humor can pass the stenosed part 55a to flow forwards or backwards.

Moreover, an encapsulated medical device may be, as shown in FIG. 19, designed to have a net-like mesh cover (mesh jacket), which serves as an armor member, freely detachably attached to a capsule body thereof.

Specifically, as shown in FIG. 19, an encapsulated medical device 150 has a mesh cover (mesh jacket) 151 freely detachably attached to a capsule body 150A. Consequently, the encapsulated medical device 150 allows the fluid 61 such as a gas or humor to flow into the distal and back ends thereof through the small holes in the mesh cover 151 that serve as linkage holes.

At least a portion of the capsule body 150A falling within a range of observation offered by the observation unit 24 included in the capsule body 150A is covered with a transparent plastic cover 152 but not with the mesh cover 151.

When the encapsulated medical device 150 having the foregoing components comes into, as shown in FIG. 20, close contact with the internal surface of the small intestine 55 in the stenosed part 55a thereof to block the lumen thereof, the encapsulated medical device 150 allows the fluid 61 such as a humor to pass the stenosed part 55a so as to flow forwards or backwards.

Moreover, an encapsulated medical device may be, as shown in FIG. 21A and FIG. 21B, designed to have an elastic rubber cover, which has a spiral groove formed therein and serves as an armor member, freely detachably attached to a capsule body. Specifically, as shown in FIG. 21A and FIG. 21B, an encapsulated medical device 160 has an elastic rubber cover 161, which has a spiral groove 161a formed as a linkage groove therein, freely detachably attached to a capsule body 160A. Consequently, the encapsulated medical device 160 allows the fluid 61 such as a gas

or humor to flow out of the distal or back part thereof through the spiral groove **161a** formed in the elastic rubber cover **161**.

Moreover, the encapsulated medical device **160** has a treatment appliance storage **162** included in the capsule body **160A** so as to enable cure or treatment. A treatment appliance opening **162a** is bored in the front part of the treatment appliance storage **162**. The treatment appliance opening **162a** is filled up with a soluble membrane made of gelatin that is digested with a gastric juice or a fatty acid membrane that is digested with an intestinal juice. When the encapsulated medical device **160** reaches a region near an intended region, the treatment appliance opening **162a** opens.

The front part of a treatment appliance **163** contained in the treatment appliance storage **162** can freely project or sink through the treatment appliance opening **162a**. Therefore, an intended region in the lumen of a body cavity can be cured or treated. The movement of the treatment appliance **163** is controlled by the extracorporeal device **3** over a communication link as described in relation to the first embodiment. In practice, the movement of the treatment appliance **163** may be controlled using a joystick that is not shown and that is connected to the personal computer **11**.

In FIG. **21A**, the treatment appliance **163** is an injection needle through which a hemostyptic can be injected. In this case, after a bleeding region is identified using a blood sensor that is not shown or the observation unit **24**, the encapsulated medical device **160** instructs the movement of the treatment appliance **163** such as the hemostyptic injection needle stored in the capsule body **160A** while being controlled by the extracorporeal device **3** over a communication link. Consequently, ethanol or any other powder that is a hemostyptic is sprayed to the bleeding region in order to arrest the bleeding.

Moreover, the encapsulated medical device **160** has an ultrasonic unit **164** included in the capsule body so that an ultrasonic examination can be performed.

The ultrasonic unit **164** consists of an ultrasonic probe that transmits or receives ultrasonic waves, and an ultrasound control circuit that controls or drives the ultrasonic probe, though the ultrasonic probe and ultrasound control circuit are not shown.

The encapsulated-medical device **160** has the ultrasonic probe kept watertight so that an acoustic lens that is not shown will be embedded in the external surface of the back part of the capsule body **160A**. An ultrasonic tomographic image of a plane that extends 360° around the back part of the capsule body **160A** can be produced.

In the encapsulated medical device **160**, the data of the produced ultrasonic tomographic image is modulated by the radio transmission/reception circuit **22** in the same manner as view image data is modulated as described in relation to the first embodiment, and then radiated in the form of a radio wave through the radio antenna **21**. Consequently, the encapsulated medical device **160** enables diagnosis of whether an abnormality is present in a direction of the depth of a deep region in a body cavity such as the small intestine **55**. If the encapsulated medical device **160** is designed to have both the observation unit **24** and the ultrasonic unit **164**, both the internal surface of a body cavity and a deep region in the body cavity can be assessed simultaneously.

Fourth Embodiment

FIG. **22A** to FIG. **24B** are concerned with a fourth embodiment of the present invention. FIG. **22A** is a sectional

view showing the structure of an encapsulated medical device in accordance with the fourth embodiment of the present invention. FIG. **22B** is an F—F sectional view of the encapsulated medical device shown in FIG. **22A**. FIG. **23A** shows the appearance of the encapsulated medical device shown in FIG. **22A** and FIG. **22B** with a balloon thereof expanded. FIG. **23B** is a G—G sectional view of the encapsulated medical device shown in FIG. **23A**. FIG. **24A** is a sectional view of an encapsulated medical device of a variant that has an armor member with a balloon freely detachably attached to the periphery of a capsule body. FIG. **24B** is an H—H sectional view of the encapsulated medical device shown in FIG. **24A**.

In the fourth embodiment, a capsule body has a balloon as an armor member. The other components are nearly identical to those of the third embodiment. The description of the identical components will be omitted, and the same reference numerals will be assigned to the identical components.

As shown in FIG. **22A** and FIG. **22B**, an encapsulated medical device **170** of the fourth embodiment has a capsule body **170A**, which is nearly identical to the one included in the third embodiment, mounted in the front part of a flexible tube **172** that has a balloon **171** serving as an armor member. At this time, the capsule body **170A** can be freely dismounted from the flexible tube **172**.

The flexible tube **172** includes a balloon tube **173** that supplies or discharges a gas or a liquid **171a** for expansion to or from the balloon **171**, and an aeration/suction tube **174** for aerating the lumen of a body cavity or sucking air therefrom. The capsule body **170A** is mounted in the flexible tube **172** composed of the balloon tube **173** and aeration/suction tube **174** with the front part thereof exposed in such a manner that a field of view offered by the observation unit **24** will not be obstructed by the flexible tube **172**. The flexible tube **172** has the balloon tube **173** and aeration/suction tube **174** thereof bundled with a bundling member **175** such as a bundling band or tape.

The encapsulated medical device **170** has a gap **176**, through which a fluid such as a gas or humor flows, formed as a fluid passage between the capsule body **170A** and aeration/suction tube **174**.

The encapsulated medical device **170** of the fourth embodiment having the foregoing components has the flexible tube **172**, in which the capsule body **170A** is mounted, inserted into a body cavity. As shown in FIG. **23A** and FIG. **23B**, the balloon **171** is expanded in an intended region in the lumen of a body cavity so that the front part of the encapsulated medical device **170** will be immobilized in the intended region in order to examine, cure, or treat the region.

At this time, the front part of the flexible tube **172** comes into close contact with the internal surface of the body cavity to block the lumen thereof. Owing to the gap **176** formed between the capsule body **170A** and aeration/suction tube **174**, a fluid such as a gas or humor can pass.

Consequently, the encapsulated medical device **170** of the fourth embodiment provides the same advantages as the first to third embodiments.

Moreover, as shown in FIG. **24A** and FIG. **24B**, an encapsulated medical device **180** has an armor member **182**, which includes a balloon **181**, freely detachably attached to the periphery of a capsule body **180A** that is the same as the one included in the first embodiment. A patient swallows the encapsulated medical device **180**.

In this case, when the balloon **181** is expanded, a fluid passage is formed between the capsule body **180A** and the internal surface of the balloon **181** owing to the linkage hole or groove formed in the extended portion of the capsule

body **180A**. In FIG. **24B**, the capsule body **180A** has the linkage groove **73** formed in the extended portion **72** thereof.

The capsule body **180A** has the observation unit **24** and illuminator **23** incorporated in the distal and back parts thereof. The balloon **181** has an infusion port **182b**, through which an expansion gas or liquid **181a** is infused thereinto, bored therein.

The balloon **181** has the expansion gas or liquid **181a** infused through the infusion port **182b** thereof using a treatment appliance such as an injection needle inserted into a treatment appliance passage channel running through an endoscope that is not shown.

Consequently, the encapsulated medical device **180** can be more compact than the encapsulated medical device **170** and constructed more easily.

According to the present invention, it is apparent that a wide range of different embodiment can be constructed based on the invention without a departure from the spirit and scope of the invention. The present invention will be limited to the appended claims but not restricted to any specific embodiment.

What is claimed is:

1. An encapsulated medical device comprising:
a capsule body capable of passing through the lumen of a body cavity to permit examination or treatment; and fluid passage forming means, included in said capsule body, for when said capsule body passes through the lumen of a body cavity, if said capsule body comes into close contact with the internal surface of the body cavity to block the lumen thereof, forming a fluid passage that links the forward and backward parts of the lumen of the body cavity.
2. The encapsulated medical device according to claim 1, wherein said fluid passage forming means is formed directly in said capsule body or in an armor member that is freely detachably attached to the periphery of said capsule body.
3. The encapsulated medical device according to claim 1, wherein: said fluid passage forming means is realized with an extended portion of said capsule body, of which cross section cut at right angle to the longitudinal axis thereof is non-circular, formed at an end of one axis of the cross section of said capsule body;
provided that said capsule body does not have the extended portion, the cross section of said capsule body is substantially circular; and
said fluid passage forming means forms a fluid passage.
4. The encapsulated medical device according to claim 1, wherein a plurality of fluid passages are formed in one direction with respect to the longitudinal axis of said capsule body.
5. The encapsulated medical device according to claim 1, wherein said capsule body includes at least observing means.
6. The encapsulated medical device according to claim 1, wherein a plurality of fluid passages are formed substantially symmetrically to one another with respect to the longitudinal axis of said capsule body.
7. The encapsulated medical device according to claim 1, wherein said capsule body has a plurality of hard members linked by a flexible string-like member.
8. The encapsulated medical device according to claim 1, wherein said capsule body has a switch, which is used to control a battery that supplies power and to control power supply from the battery, incorporated therein.
9. The encapsulated medical device according to claim 1, wherein said capsule body includes at least one medical-

purpose examining means such as arm optical sensor, a pH sensor, a temperature sensor, a pressure sensor, or an ultrasonic probe.

10. The encapsulated medical device according to claim 1, wherein said capsule body includes at least one opening means for a treating or examining means, such as, a medicine administration port or a humor infusion port.

11. The encapsulated medical device according to claim 1, wherein said capsule body includes at least one treating means such as an injection needle.

12. The encapsulated medical device according to claim 1, wherein said fluid passage is realized with a spiral groove.

13. The encapsulated medical device according to claim 1, wherein said capsule body has at least a magnet incorporated therein.

14. The encapsulated medical device according to claim 1, wherein said capsule body has at least observing means and a magnet incorporated therein, and said fluid passage is realized with a spiral groove.

15. The encapsulated medical device according to claim 2, wherein said fluid passage is realized with a linkage hole formed between said capsule body and said armor member or in said armor member.

16. The encapsulated medical device according to claim 2, wherein said fluid passage is realized with a linkage groove formed in said armor member.

17. The encapsulated medical device according to claim 2, wherein a plurality of projections are formed on said armor member, and said fluid passage is realized with a plurality of concave parts formed among said plurality of projections.

18. The encapsulated medical device according to claim 2, wherein said armor member is realized with a hard tubular member, and said fluid passage is formed with the internal surface of said tubular member and notches formed in the periphery of said capsule body.

19. The encapsulated medical device according to claim 2, wherein said armor member is a transparent member formed to enclose the entire periphery of said capsule body, and said fluid passage is formed in said transparent member or between the internal surface of said transparent member and the periphery of said capsule body.

20. The encapsulated medical device according to claim 2, wherein said armor member is a mesh cover attached to the periphery of said capsule body, and the small holes of the mesh of the mesh cover realize said fluid passage.

21. The encapsulated medical device according to claim 2, wherein said armor member is a sack-like elastic balloon capable of expanding outwards beyond the periphery of said capsule body, and said fluid passage is formed between the internal surface of the elastic balloon and the periphery of said capsule body.

22. The encapsulated medical device according to claim 2, wherein said fluid passage is realized with a linkage hole or linkage groove formed in said capsule body.

23. The encapsulated medical device according to claim 2, wherein a plurality of projections are formed on said capsule body, and said fluid passage is realized with a plurality of concave parts formed among said plurality of projections.

24. The encapsulated medical device according to claim 2, wherein said fluid passage is realized with a spiral groove formed in said armor member.

25. The encapsulated medical device according to claim 2, wherein said armor member is an elastic member.

26. The encapsulated medical device according to claim 5, wherein:

21

said capsule body has the center axis thereof, which passes the center of the minor axis of a cross section thereof cut at right angle to the longitudinal axis thereof, deviated from the optical axis of said observing means; and

said fluid passage is formed in a space extending on the opposite side of the center axis, which passes the center of the minor axis of the cross section cut at right angle to the longitudinal axis, relative to the optical axis of said observing means.

27. The encapsulated medical device according to claim **5**, wherein said capsule body includes a plurality of observing means that permits observation in different directions.

28. The encapsulated medical device according to claim **20**, wherein said mesh cover does not cover at least a portion falling within a range of observation offered by said observing means.

29. A method of examining or treating an internal region of a body cavity using an encapsulated medical device that

22

includes a capsule body and fluid passage forming means for forming a fluid passage that links the forward and backward parts of the lumen of the body cavity when said capsule body comes into close contact with the internal surface of the body cavity to block the lumen thereof.

30. A method of examining or treating an internal region of a body cavity using an encapsulated medical device, wherein said encapsulated medical device includes a capsule body and fluid passage forming means that forms a fluid passage which links the forward and backward parts of the lumen of the body cavity when said capsule body comes into close contact with the internal surface of the body cavity to block the lumen thereof.

31. The method according to claim **30**, wherein the lumen of a body cavity is the lumen of the small or large intestine.

* * * * *

专利名称(译)	封装的医疗装置以及使用封装的医疗装置检查，固化和处理体腔内部区域的方法		
公开(公告)号	US7083579	公开(公告)日	2006-08-01
申请号	US10/251443	申请日	2002-09-20
[标]申请(专利权)人(译)	奥林巴斯株式会社		
申请(专利权)人(译)	奥林巴斯光学有限公司.		
当前申请(专利权)人(译)	OLYMPUS CORPORATION		
[标]发明人	YOKOI TAKESHI TAKIZAWA HIRONOBU SEGAWA HIDETAKE ADACHI HIDEYUKI		
发明人	YOKOI, TAKESHI TAKIZAWA, HIRONOBU SEGAWA, HIDETAKE ADACHI, HIDEYUKI		
IPC分类号	A61B5/117 A61B5/103 A61B5/07 A61B1/00 A61B5/06 A61B5/1455 A61B8/12 A61B17/00 A61M37/00		
CPC分类号	A61B1/00156 A61B1/00158 A61B5/06 A61B1/041 A61B5/7232 A61B5/42		
优先权	2001297703 2001-09-27 JP		
其他公开文献	US20030060734A1		
外部链接	Espacenet USPTO		

摘要(译)

封装的医疗设备包括无线电天线，封装的医疗设备通过该无线电天线向体外设备发送无线电波或从体外设备接收无线电波。封装的医疗装置穿过体腔的内腔，以便在体外装置的控制下检查，治愈或治疗体腔的内部区域。封装在封装的医疗装置中的胶囊体具有延伸部分，该延伸部分形成在胶囊主体的横截面的一个轴线的上端，该横截面与其纵向轴线成直角。胶囊体具有在其延伸部分中钻出的连接孔，以允许诸如气体或幽默的流体通过该孔流入管腔的前后部分。

