




US 20040122458A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2004/0122458 A1**
(43) **Pub. Date: Jun. 24, 2004**(54) **PERCUTANEOUS DEVICE AND METHOD
FOR HARVESTING TUBULAR BODY
MEMBERS**(60) Provisional application No. 60/395,248, filed on Jul.
11, 2002.**Publication Classification**(76) Inventors: **John C. Opie**, Scottsdale, AZ (US);
Stephen J. Joyce, Phoenix, AZ (US)(51) **Int. Cl.⁷** **A61D 1/02**
(52) **U.S. Cl.** **606/159**Correspondence Address:
SQUIRE, SANDERS & DEMPSEY L.L.P.
Two Renaissance Square
40 North Central Avenue, Suite 2700
Phoenix, AZ 85004-4440 (US)(21) Appl. No.: **10/618,456**(22) Filed: **Jul. 11, 2003****Related U.S. Application Data**(63) Continuation-in-part of application No. 10/444,776,
filed on May 23, 2003.(57) **ABSTRACT**

A percutaneous harvesting device for the harvesting of tubular body members from a body is disclosed. The percutaneous harvesting device includes an endovascular guide for sufficiently straightening the tubular vessel to be removed and a perivascular cutting tool that is inserted over the endovascular guide. The cutting tool is advanced along the length of the tubular body member to be removed and it cuts body tissue (wherein the tubular body member is positioned inside the body tissue) as it is advanced. The body tissue is thus dissected from the body and can then be extracted percutaneously and rapidly from the body by pulling the endovascular guide, and the tubular body member and surrounding body tissue, from the body.









FIG. 1






FIG. 4




FIG. 5a











FIG. 5b










FIG. 9




FIG. 10




FIG. 11




FIG. 12

PERCUTANEOUS DEVICE AND METHOD FOR HARVESTING TUBULAR BODY MEMBERS

CROSS REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of provisional application 60/395,248, filed on Jul. 11, 2002 and entitled "Percutaneous Vein Harvesting Device and Method of Use" and is a continuation-in-part of U.S. patent application Ser. No. 10/444,776 entitled "Guide Wire Torque Device" filed on May 24, 2003.

FIELD OF THE INVENTION

[0002] The present invention relates to methods and devices for removing tubular body members, particularly blood vessels, from the body of a human or animal.

BACKGROUND OF THE INVENTION

[0003] Various tubular structures in the body ("tubular body members") are sometimes removed, either for use somewhere else in the body or simply because removal is desired or necessary. As used herein, the terms "harvest," "dissect" and "remove," when used in connection with the removal of a tubular body member from the body, are synonymous. Tubular body members include blood vessels, such as arteries and veins, tendons, bile ducts and other structures. For example, the long saphenous vein (LSV) located in subcutaneous fatty tissue in an anteromedial compartment of the lower leg and thigh is sometimes removed for use in (1) arterial bypass surgery, including coronary artery bypass, and peripheral arterial surgery bypasses, and (2) preparing an arteriovenous (AV) loop for dialysis. The length of the harvested LSV may vary from 20 cm to 100 cm.

[0004] Traditionally, the LSV has been removed by making a long incision along the leg from about the ankle to the groin, or by making a series of multiple, bridged incisions. Tissue (primarily fat) including the LSV is dissected from the leg through the incision(s) and the LSV is then dissected from the surrounding tissue. While this procedure usually yields a usable LSV, the incision(s) is painful, is reported to suffer wound healing failures rates of up to 40% not infrequently mandating rehospitization and considerable expense and discomfort, is a possible source of infection, takes a long time to heal, and leaves a long, noticeable scar. Further, the harvested vein must be extensively handled in order to remove the surrounding tissue. That can result in damage to the LSV and possible early failure after the LSV is used as a graft.

[0005] In an attempt to solve the problems caused by removal of the LSV via a long incision or multiple incisions in the leg, various endoscopic techniques have been developed. These techniques involve the insertion of an endoscopic camera into the leg near the LSV at the knee area. The area around the camera may be inflated with a gas such as carbon dioxide using a gas-release nozzle positioned in an endoscopic dissection tool inserted along with the endoscopic camera—the gas is usually injected through a separate device requiring a separate incision. The endoscopic dissection tool is used to dissect the fatty tissue around the LSV and vein branches by gently using the pointed tip of the endoscopic dissection tool, the carbon dioxide gas flow and

additional endoscopic dissection tools. After separating the LSV and vein branches from the fatty tissue, the dissection tools are withdrawn and an endoscopic clipper is used to clip the various branches. Once that is completed a cutting tool (typically cauterizing scissors) is inserted through the endoscope. The cutting tool is manipulated to divide and cauterize the clipped branches of the vein. As used herein, the term "divide" when used in relation to a tubular body member means to cut entirely through the tubular body member.

[0006] After the LSV is dissected and the branches are clipped and divided as described above, incisions to expose the vein are made through the skin at the distal and proximal ends of the leg. The vein is ligated in continuity and then divided with a pair of scissors. The dissected LSV is then pulled out of the body.

[0007] While these endoscopic procedures reduce scarring, pain, wound-related complications and risk of infection as compared to the previously described open incision method, the endoscopic technique is both difficult to learn and to use. An endoscopic procedure can also damage the vein due to over manipulation and potential mishandling of the endoscopic tools. Additionally, endoscopic equipment used in these procedures is expensive to buy and use.

SUMMARY OF THE INVENTION

[0008] A method according to the invention improves upon the prior art methods for removing a tubular body member from the body and generally comprises the steps of (1) creating openings in the body through which the tubular body member can be accessed at a proximal end and a distal end, (2) sufficiently straightening the tubular body member to utilize a cutting tool according to the invention, (3) using a cutting tool to dissect a section of body tissue (wherein the tubular body member is inside the dissected section) between the proximal end and the distal end, and (4) removing the dissected section of tissue including the tubular body member from the body. Once the body tissue is removed from the body, the tubular body member is dissected from the body tissue using any suitable method.

[0009] One device according to the invention is a percutaneous harvesting device (PHD) for the harvesting of tubular body members from a body. The PHD includes (1) an endovascular component (EVC) for passing inside of the tubular body member to be removed, and (2) a perivascular cutting tool (PVT) that is inserted over the EVC and is used to cut a length of body tissue that includes the tubular body member.

[0010] In one preferred embodiment, the EVC comprises a guide wire and an endovascular guide (EVG) surrounding the guide wire. The EVG is preferably a catheter made from a soft material (preferably plastic) suitable for passing through the selected tubular body member without damage to the intimal surface of the tubular body member. The EVG may have a tapered end, or nose, to assist in introducing it into the tubular body member and may include one or more structures, such as grooves or rings, for securing the tubular body member to the EVG. Alternatively, the tubular body member can be secured to a specially designed, nozzle nosed, torque device with an external structure (such as an annular ridge or chevron) on the torque device, preferably positioned at the base of the nozzle. The nozzle is designed to fit partially inside the lumen of the tubular body member

and to retain the tubular body member, preferably by a suture at the external structure for ligating the tubular body member to the torque device. The torque device is then tightened onto the guide wire at the proximal end and the distal end, thus the tubular body member is firmly fixed to the guide wire via the torque device.

[0011] The PVT is preferably cylindrical and has a diameter (or width) greater than the diameter of the tubular body member. The PVT surrounds the tubular body member and cuts through the body tissue surrounding the tubular body member thus dissecting from the body an essentially cylindrical section of body tissue (mostly fat in the case of the LSV) with the tubular body member inside the body tissue. If the tubular body member is a blood vessel, the blade cuts the branches of the blood vessel, thus isolating the blood vessel and enabling it to be removed without tearing. The dissected section of body tissue is removed from the body and the tubular body member is separated from the surrounding tissue in the dissected section.

[0012] In one preferred embodiment, the PVT includes a cutting head and a body section. The cutting head preferably has an annular leading edge that forms an annular cutting blade.

[0013] The body section of the PVT is preferably a plastic tube having an attachment structure (preferably threads) at one end for attaching to the cutting head. Optionally, the body section includes an outer surface (or exterior) having a helical thread or other device on the outer surface to assist in the movement of the cutting tool through the body.

[0014] The PVT optionally is used in conjunction with a handle that can attach to an end of the body section of the PVT. The handle, and hence the PVT, is preferably turned by a user, such as a surgeon, to advance the PVT through a body to dissect the tubular body member. The handle may be an elongated shaft with one end that is connected to the body section of the PVT. Optionally, a handgrip can be attached to the handle for easier operation. Optionally, the PVT can be fitted with a power source, such as a battery pack and appropriate drive equipment to rotate or vibrate the PVT thus assisting in the dissection of the tubular body member with less resistance.

[0015] Thus, a PHD according to various aspects of the invention provides a less invasive and quicker way of removing tubular vessels such as the long saphenous vein (LSV) from a body.

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] Aspects of the present invention will be appreciated with reference to the description of the invention when made with reference to the accompanying drawings and wherein:

[0017] FIG. 1 is a side view of a preferred embodiment of a perivascular harvesting device;

[0018] FIG. 2 is a cross-sectional, side view of an embodiment of an endovascular component of the percutaneous harvesting device of FIG. 1;

[0019] FIG. 3 is a cross-sectional, side view of an alternate embodiment of an endovascular component;

[0020] FIG. 3a is an end view of an alternate embodiment of an endovascular component;

[0021] FIG. 4 is a cross sectional view of a perivascular cutting tool;

[0022] FIGS. 5a-5b are views of an embodiment of a cutting head for use with a perivascular cutting tool;

[0023] FIG. 6a is a side view of an alternative embodiment of a perivascular cutting tool;

[0024] FIG. 6b is a cross-sectional, side view of the perivascular cutting tool shown in FIG. 6a;

[0025] FIGS. 7a-7b are views of an alternative cutting head for use with the perivascular cutting tool of FIGS. 6a-6b;

[0026] FIGS. 8a-8c are views of a connector for use with the cutting head of FIGS. 6a-6b and 7a-7b;

[0027] FIG. 9 is a view of a cutting tool according to the invention that includes an optional handle and an optional hand grip;

[0028] FIG. 10 is a view of a percutaneous harvesting device according to the invention in use;

[0029] FIG. 11 is a flow diagram of a method using a device according to the invention.

[0030] FIG. 12 is a view of an alternate embodiment of a perivascular cutting tool, which has an automatic advancement device.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0031] In the following descriptions, the present invention is frequently discussed using the example of the removal of a blood vessel, such as the LSV, from the body. However, the devices and methods of the invention can be used to harvest any tubular body member from a body for any purpose.

[0032] Turning now to the drawing figures where the purpose is to describe preferred embodiments of the invention and not to limit same, a preferred embodiment of one device of the invention is percutaneous harvesting device (PHD) 100, illustrated in FIG. 1. PHD 100 is used percutaneously for dissecting a tubular body structure, such as a blood vessel, by cutting through a length of body tissue that includes the tubular body member, thus freeing the body tissue including the tubular body member from the body.

[0033] PHD 100 includes an endovascular component (EVC) 102 for insertion into the blood vessel to be removed, and a perivascular cutting tool (PCT) 104 for traveling subcutaneously and coaxially outside of and along the length of the blood vessel in which EVC 102 has been inserted. Cutting tool 104 is for cutting tissue surrounding the blood vessel.

[0034] EVC 102 may be any structure or structures suitable for sufficiently straightening the blood vessel so that the blood vessel can be dissected from the body using a PVT according to the invention. Referring to FIG. 2, in one embodiment EVC 102 comprises a guide wire 202 and an outer tube, or endovascular guide (EVG), 204 surrounding guide wire 202, although it is possible that the EVC could be a single tubular member threaded through the vein. In the preferred method of using EVC 102, guide wire 202 is first inserted into the blood vessel and EVG 204 is then inserted over guide wire 202 and threaded through the blood vessel.

[0035] Guide wire **202** is any suitable medical guide wire that can be used in a procedure according to the invention, and guide wire **202** preferably has a hydrophilic coating and a straight floppy tip **214** to help provide maneuverability through the blood vessel. U.S. Provisional Application 60/475,666 to Opie and Joyce, filed on Jun. 3, 2003 and entitled "Improved Medical Guide Wires" discusses exemplary guide wires and is herein incorporated in its entirety by reference. Suitable guide wires include those having a diameter between 0.010"-0.038" and having about a 2-5 cm long floppy tip. The guide wire is long enough to pass through and extend outside of each divided end of the blood vessel and is preferably about 40% longer than the section of blood vessel to be removed. If used to remove an LSV, the guide wire is usually about 230 -260 cm in length.

[0036] EVG **204** is preferably a flexible tubular plastic catheter and includes a central lumen **210** through which guide wire **202** is positioned when EVC **102** is positioned in the vein. EVG **204** optionally includes a tapered nose **206** that allows for easier introduction of EVG **204** into a blood vessel and easier passage through the blood vessel, and any structure suitable for this purpose may be used. Tapered nose **206** preferably is between about 3 and 4.5 cm in length and tapers to a tip **206A** that is about 1.5 mm in diameter. EVG **204** can be soft enough to allow a suture to be secured to the EVG **204** in order to secure an end of a blood vessel thereto to facilitate removal. Alternatively the suture can be applied to a guide wire torque device to secure the blood vessel as described herein. A guide wire torque device (or simply "wire torque device" or "torque device") is a device that mechanically grips and secures a guide wire. Suitable wire torque devices are disclosed in copending application Ser. No. 10/444,776 filed on May 24, 2003 and entitled "Guide Wire Torque Device" by Opie and Joyce, the disclosure of which is herein incorporated in its entirety by reference.

[0037] Typically, EVG **204** is 10% to 20% longer than the section of blood vessel to be removed because both ends of EVG **102** need to be exposed outside of the respective divided ends of the blood vessel. The outside diameter of the EVG depends on the size of the blood vessel because the EVG must be of a suitable size to pass through the blood vessel without damaging it. In a preferred embodiment, the EVG has a diameter of 3-4 mm.

[0038] In one embodiment, a series of grooves **212** are formed around the circumference of each end of EVC **102**. Grooves **212** are for securing the blood vessel to EVC **102**, preferably at each end of EVC **102** and preferably through the use of suture ligatures. In this embodiment the grooves are preferably about 0.5 mm deep and are spaced about 1.0 centimeter apart.

[0039] In another embodiment, grooves **212** (shown in FIG. 2) may be replaced by a series of rings **302** (shown in FIG. 2). In this embodiment, rings **302** are about 2.0 mm wide and are spaced about 1.0 cm apart. The blood vessel to be removed can be attached to rings **302** via sutures or clips. In addition to grooves **212** and rings **302**, any other structure that allows a blood vessel to be attached to EVC **102** may be used, or EVC **102** may not include any such structure. Any such structures for attaching a blood vessel to EVC **102**, if used, can be positioned at any suitable location on the EVC. In two known embodiments such structures are located on the EVG about 25-40 cm from each end of an EVG 80-150

cm in length, and 65-80 cm from each end of an EVG 230 cm in length. Alternatively, these structures may be replaced by structures on torque devices positioned at either end of the EVG, wherein the tubular body member can be secured to the structure on each torque device.

[0040] Presently, the most preferred embodiment of EVC **102** includes a guide wire with a hydrophilic coating and a single floppy tip and an EVG made of PVC or similar, suitable plastic, approximately 4 mm in diameter and having a central lumen of about 1-1.3 mm in diameter, wherein the EVG is threaded over the guide wire.

[0041] An alternate EVC **340** is shown in FIG. 3A. EVC **340** comprises an inner core **350** covered by an exterior covering **360**. Inner core **350** provides both strength and flexibility to EVC **340**, and is preferably made from a flexible or semi-flexible polymer plastic. However, any material that provides for a firm but semi-flexible inner core can be used. In one embodiment, the inner core is 2-3 mm in diameter. Any diameter can be used, however, as long as EVC **340** is properly sized to be threaded through the blood vessel to be removed.

[0042] The preferred embodiment of exterior covering **360** is deformable and deforms in response to pressure from a suture or clip (such as a C-clip) in order to secure an end of a blood vessel to EVC **340** without significant slippage. The exterior covering can be made from foamed plastic, silastic or silicone rubber, although any suitable bio-compatible material can be used. In one embodiment, exterior covering **360** is 0.5 to 1.0 mm thick, although other thickness can be used with the maximum thickness controlled by the overall thickness of EVC **340**, which needs to be properly sized to fit inside a blood vessel and is typically 3-4 mm in diameter if used in the removal of the LSV.

[0043] Exterior covering **360** may be co-extensive with inner core **350** or it may cover only part of an area of the inner core **350**. In one embodiment the exterior covering **360** may cover from 25 to 40 cm from one end of inner core **350** for a shorter EVC **340**, or 65-80 cm from one end of inner core **350** for a longer EVC **340**. EVC **340** may also include a nose or cone having dimensions the same as or similar to those of previously described structure **206**.

[0044] The PHD further includes a perivascular cutting tool (PVT) **104**. PVT **104** includes a body section **402** coupled to a cutting head **404**. As used herein, unless otherwise stated, "coupled" means attached in any manner suitable for the PVT to be used in the manner described herein.

[0045] Body section **402** is any suitable structure for use in a method according to the invention and is preferably a hollow tubular structure having a first end **401**, a second end **403**, a passage **406** extending therethrough and an optional driving helix **408** positioned on annular wall **410**. Body section **402** is preferably an extruded, semi-flexible polycarbonate (such as General Electric Lexan 12) piece flexible enough to be suitable for the particular application in which it is to be used. Body section **402** supports cutting head **404** and preferably helps to substantially center the cutting head **404** around the blood vessel being removed during the cutting procedure. Body section **402**, in one embodiment, has an exterior diameter of 15 mm and an internal diameter of 10 mm and is approximately 100 cm in length, and in this

embodiment wall **410** is preferably about 3 mm thick. Body section **402** may have different dimensions, however, the dimensions depending upon such factors as the application for which the PVT will be used and the amount of surrounding tissue to be removed with the blood vessel. The outer surface of wall **410** is preferably coated with a low-friction material, such as TEFLON, to reduce friction during use, or may be coated with a hydrophilic coating such as polyurethane.

[0046] Driving helix **408** is optional and is preferably a 2 mm high, clockwise, helical thread positioned on (i.e., formed in or attached to) the outer surface of wall **410** of body section **402**. Helix **408** assists in advancing PVT **104** through the body, and any structure positioned on wall **410** suitable for performing this function may be used, assuming such a structure is used at all. For example, other sizes and types of threads may be used, or a series of longitudinally-extending grooves may be positioned on in the outer surface of wall **410**, and the grooves may be slightly twisted to provide gripping ability.

[0047] As PVT **104** is turned, driving helix **408** grips the body tissue through which it is passing and helps to advance PVT **104** forward, and/or helps to prevent PVT **104** from slipping backward during a procedure. In one embodiment, driving helix **408** is dimensioned such that for every 360° rotation of body portion **402**, PVT **104** would advance 3.0 centimeters if there were no slippage, with a preferred range of 2-3 cm of advancement for every 360° rotation of body portion **402**.

[0048] Cutting head **404** is designed to cut the body tissue surrounding the blood vessel and to cut blood vessel branches, thus dissecting the body tissue from the body so that the body tissue including the blood vessel can be removed. Cutting head **404** is preferably metal (most preferably carbon steel or stainless steel). Referring to FIGS. **5a** and **5b**, cutting head **404** has, in one embodiment, a generally wedge-shaped front **501** (as seen in side view), approximately in the shape of a truncated cone. The shape of front **501** assists in the movement of PVT **104** inside the body by pushing tissue outward from PVT **104** as cutting head **404** advances. While cutting head **404** with front **501** is illustrated, cutting head **404** can be any suitable shape for use on the PVT.

[0049] Cutting head **404** includes an attachment end **504**. Attachment end **504**, in one embodiment, has threads **506** that threadingly engage first end **401** of body portion **402**, although cutting head **404** can be connected to body section **402** by any method or structure that provides a secure connection. Preferably, cutting head **404** is removable from body section **402**, so that it may be disposed of (if desired), while body section **402** can be sterilized and reused (if desired).

[0050] Cutting head **404** includes a leading edge forming an annular blade **508**. Alternatively, the cutting blade may not be annular or on the leading edge, although this is preferred. With annular blade **508** at the leading edge of PVT **104** the force required to advance PVT **104** through the body tissue is less than the force that would be required if the blade was behind the leading edge. Further, the annular blade provides 360 degrees of cutting surface, which also reduces the amount of force that must be applied to advance the PVT relative a cutting surface of less than 360°. Annular

blade **508** is, in one embodiment, non-serrated, although a serrated annular blade can also be used.

[0051] Cutting head **404** also includes, in one embodiment, and with reference to the cross-sectional view of FIG. **5b**, an internal funnel-shaped section **510** coupled to internal cylindrical section **512**. Internal funnel-shaped section **510** compresses tissue dissected by the cutting blade. In this respect, as PVT **104** advances, the dissected tissue is forced into section **510** by the forward movement of PVT **104**. In section **510** the body tissue is compressed from a first diameter essentially equal to diameter **511**, down to a second diameter essentially equal to diameter **513**. The compression of the body tissue helps keep the PVT **104** essentially centered around the blood vessel to be removed, which helps to prevent the blood vessel from being cut by cutting blade **508**.

[0052] In one embodiment first diameter **511**, i.e., the diameter of annular blade **508**, is 15 mm and second diameter **513**, i.e., the diameter of the internal cylindrical section **512**, is 10 mm. The length of internal funnel section **510** is, in one embodiment 10 mm, and is preferably in the range of 5 to 15 mm.

[0053] In another embodiment, and with reference to FIGS. **6a** and **6b**, an articulated PVT **600** is shown. Articulated PVT **600** has an articulated (i.e., jointed) cutting head **602** that is able to move and pivot independent from body portion **402** and any structure suitable for allowing cutting head **602** to pivot may be used. The articulation allows for easier movement of the articulated PVT **600** around structures such as the knee. In one embodiment, articulated cutting head **602** can pivot up to 15 degrees, although any suitable pivoting range may be utilized. Unless otherwise stated, the preferred size, shape, materials and configuration of cutting head **602** are the same as previously described for cutting head **404**. Articulated PVT **600** also includes a body section **402** (previously described) and an articulated connection section **601**. Articulated cutting head **602** is coupled to connection section **601**, as best seen in FIG. **6b**.

[0054] Referring to FIGS. **7a-7b**, articulated cutting head **602** includes a blade portion **702** having a leading edge forming an annular cutting blade **704** and a coupling section **706**. Coupling section **706** includes an annular rim **708** and a channel **710** formed in rim **708**. Similar to cutting head **404**, articulated cutting head **602** includes an internal funnel section **712** coupled to an internal cylindrical section **714**. Internal funnel section **712** compresses tissue dissected by annular cutting blade **704**. The advancement of articulated PVT **600** forces tissue to the cylindrical section **714**. The compression of the body tissue helps keep articulated PVT **600** essentially centered around the blood vessel to be removed in order to assist in preventing the blood vessel from being cut by cutting blade **704**.

[0055] Referring to FIGS. **8a-8c**, preferred connection section **601** comprises two parts, a first connection section **802** and a second connection section **804**. Each connection section **802** and **804** has threads **806** and when connection sections **802** and **804** are joined, threads **806** form an essentially continuous thread that can be used to threadingly connect section **601** to body portion **402**. Connection sections **802** and **804**, when joined, form a cup **808** between connection sections **802** and **804**.

[0056] Cup **808** includes a lip **810** that engages and retains annular rim **708** of articulated cutting head **602** and enables

cutting head **602** to pivot. Each lip **810** includes a stud **812**. When cup section **808** is coupled to coupling section **706**, each stud **812** is aligned with and positioned inside of a channel section **710**. In one embodiment there are two channel sections **710**, each of which has a stud **812** positioned therein when cutting head **602** is coupled to connecting section **601**. This prevents the articulated cutting head **602** from rotating continuously about a center axis, while still allowing the articulated cutting head **602** to pivot freely. If the cutting head **602** were allowed to continuously rotate, then the twisting motion that may be used to advance articulated PVT **600** inside the body could be translated into merely a spinning of articulated cutting head **602**.

[0057] Once the articulated cutting head **602** is coupled to the articulated connection section **601**, articulated cutting head **602** and articulated connection section **601** together act like a ball and socket joint wherein section **706** is analogous to the ball and cup section **808** is analogous to the socket. The articulation assists in the advancement of PVT **104** through the body. For example, articulated cutting head **602** allows PCT **600** to more easily maneuver around structures in the body, such as the knee joint.

[0058] Moving PVT **104** or **600** through the subcutaneous body tissue requires a certain amount of torque and/or pressure to force a PVT through the body tissue surrounding the blood vessel. To assist in advancing a PVT, an optional torque handle (or simply "handle") **902** can be attached to PCT **104** or **600** opposite the cutting head. Torque handle **902** is designed to fit into an adult human hand and is preferably a rod or tube made from extruded plastic (Lexan 12, high density polyethylene, acetal, Nylon, ABS are all plastics that could be used) and includes a connector **904** to connect to the PVT **104** and a shaft **906**. In one embodiment connector **904** comprises threads on the rod or tube that threadingly connect to the PVT. Optionally a handgrip **908** can be attached to or formed in handle **902** to further assist in operation of the PVT.

[0059] A surgeon or other medical worker would first attach torque handle **902** to the PVT **104** or **600**. This is done using connector **904**, which connects to the end of PVT **104** or **600** opposite the cutting head, preferably by a threaded connection. Once connected and the PVT is inserted into the body, the surgeon twists and pushes the shaft **906**. This causes the PVT to rotate and move forward. Cutting head **404** or **602** cuts the body tissue and the blood vessel and surrounding tissue is pressed through the body portion **402** as the PVT is advanced. Driving helix **408**, if used, helps move the PVT forward and prevents the PVT from backing out of the body. To remove the PVT, the user would either advance it entirely out of the body or turn it in the opposite direction while pulling on the torque handle **902** to back it out of the body. Handgrip **908** can also be used to help in twisting the torque handle **902**. Torque handle **902** and handgrip **908** can be made from a plastic such as polycarbonate, although any strong rigid material can be used.

[0060] Referring now to FIG. 10, EVC **102** is shown positioned in a blood vessel **1002** to be removed. When EVC **102** is inserted into vessel **1002**, blood vessel **1002** collapses around the endovascular guide **102** as the blood in blood vessel **1002** is pushed outward through branches **1004**. As seen in FIG. 10, blood vessel **1002** can be secured to EVC **102** using a suture **1006** to secure to a structure **212** formed

on EVG **204** or to the torque device as previously discussed. Alternatively, blood vessel **1002** may be secured to a wire torque device at one end or both ends. Typically, both ends of the blood vessel **1002** to be removed are secured to EVC **102** or to respective torque devices to help straighten blood vessel **1002** to be removed.

[0061] After endovascular guide **102** is inserted through blood vessel **1002**, PVT **104** is passed along endovascular guide **102** such that endovascular guide **102** and blood vessel **1002** it is inserted into is inside PVT **104**. As PVT **104** moves along endovascular guide **102** branches **1004** are severed by annular blade **508**, which is on the leading edge of PVT **104**. The diameter of annular blade **508** determines the length of branches **1004** left on removed blood vessel **1002**. Cut blood vessel **102** and surrounding tissue passes to body section **402**.

[0062] Referring to FIGS. 10 and 11, a preferred harvesting method shall be described. In this preferred harvesting (or removal) procedure, a PHD having either PVT **104** or PVT **600** may be utilized to remove an LSV. First, the LSV is accessed and divided at a proximal end (step **1102**) and a distal end (step **1104**). Next, a guide wire **202** is fed through the LSV and is exposed outside of the body at the proximal end and the distal end. EVG **204** is then advanced over guide wire **202** and into the LSV from the proximal end to the distal end and is exposed at each end (Steps **1105** and **1106**).

[0063] To secure the guide wire a wire torque device (the wire torque devices are not shown) is preferably placed on the guide wire at the proximal end outside of the LSV and another guide wire torque device is placed on the guide wire at the distal end outside of the LSV. The LSV is secured at both the proximal end and the distal end to either the EVG or a wire torque device, and the EVG is secured to a wire torque device at the proximal end and to a wire torque device at the distal end. (Step **1108**).

[0064] The guide wire, catheter and LSV are then pulled straight by applying force to the distal end and the proximal end of each, preferably by pulling on the wire torque devices. As used throughout this application with respect to straightening a tubular body member, the word "straight" means sufficiently straight to utilize a cutting tool according to the invention, and is not limited to a perfectly straight configuration.

[0065] Once the LSV is sufficiently straightened to remove it using a PVT as described herein, a PVT is utilized to dissect body tissue including the LSV from the body. The PVT is positioned so that the guide wire and EVG are inside the PVT and the LSV is preferably approximately axially-aligned with the cavity of the cutting head. (Step **1110**). Ideally, the passage of the PVT is coaxially aligned with the LSV, although the alignment need not be coaxial, the LSV must simply be positioned so that it is not cut by the cutting blade.

[0066] The PVT is then advanced along the accessed length of the tubular body member, cutting through the body tissue surrounding the LSV and the LSV branches, thereby separating the body tissue and LSV from the body. (Step **1112**). Once separated, the tissue including the LSV is removed from the body, which may be accomplished by simply by withdrawing the EVG with the LSV and surrounding tissue out of one of the incisions. (Step **1114**). After

being removed, the LSV is dissected from the surrounding body tissue and the vein can be flushed and the branches tied off. (Step 1116).

[0067] A drain, optionally positioned in the PVT, can be placed into the wound created by the PVT. The PVT is then removed leaving the drain in the leg precisely where the body tissue had been. (Step 1118). The drain would then be in place to remove blood and clots from the wound. Exemplary drains are disclosed in U.S. Provisional Application 60/476,663 filed on Jun. 5, 2003 and entitled "Improved Surgical Drains," to Opie and Joyce, the disclosure of which is herein incorporated in its entirety by reference.

[0068] In an alternative embodiment, manual operation of the PVT is replaced or augmented by an electromechanical operation using an automated device. For example, and with reference to FIG. 12, the perivascular cutting tool 104 is coupled to an automatic advancement device 1202. Automatic advancement device 1202 applies a twisting motion, vibration or other suitable force to the PVT to assist in advancing the PVT through the body and may be any device suitable for this purpose. In one embodiment, automatic advancement device 1202 comprises a low speed, high torque motor 1204 that couples to either the PVT or to a torque handle. Motor 1204 would use gears 1206, belts or any other method of connecting a motor to a shaft to transfer driving force to the PVT. Preferably, automatic advancement device 1202 comprises a variable speed motor to vary the torque an/or force applied to the PVT to control the speed of the PVT. In one embodiment, automatic advancement device 1202 includes an opening 1208 for the passage of an endovascular guide wire.

[0069] In addition to, or as an alternative to, twisting PVT 104 or 600, automatic advancement device 1202 may also vibrate or otherwise manipulate PVT 104 or 600 to assist in moving it through the body. Such a movement could be provided, for example, by an ultrasonic vibrator.

[0070] Having now described preferred embodiments of the invention; modifications and variations that do not depart from the spirit of the present invention may be made. The invention is thus not limited to the preferred embodiments, but is instead set forth in the following claims and legal equivalents thereof.

What is claimed is:

1. A device for removing a tubular body member from a body, the device comprising a cutting tool that includes:

- (a) a cutting head having (i) a leading edge comprising an annular cutting blade, and (ii) an attachment section; and
- (b) a body section having a proximal end, a distal end and an inner passage extending therethrough, the distal end operable to couple to the attachment section of the cutting head.

2. The device of claim 1 wherein the cutting head further includes an inner cavity, the inner cavity being funnel-shaped and having a first inner diameter at the leading edge and a second inner diameter, the second inner diameter being smaller than the first inner diameter, the inner cavity compressing body tissue during operation of the cutting tool to assist in keeping the tubular body member from being cut by the annular cutting blade.

3. The device of claim 1 wherein the attachment section of the cutting head is threaded and the distal end of the body section is threaded, the cutting head attachable to the body section by threading it onto the distal end.

4. The device of claim 1 wherein the body section is tubular.

5. The device of claim 1 wherein the body section has an exterior surface and the exterior surface is coated with a hydrophilic coating.

6. The device of claim 1 wherein the body section has an exterior surface and the exterior surface is coated with a low-friction coating.

7. The device of claim 1 wherein the body section further comprises an exterior surface, and a structure positioned on the exterior surface to assist in the movement of the cutting tool through body tissue

8. The device of claim 1 wherein the structure on the exterior surface is a helical thread.

9. The device of claim 1 further comprising an endovascular component for being positioned in the tubular body member.

10. The device of claim 9 wherein the endovascular component comprises a flexible tube and a medical guide wire.

11. The device of claim 9 wherein the endovascular component includes one or more structures to which the tubular body member can be attached.

12. The device of claim 1 wherein the cutting head pivots when attached to the body section.

13. The device of claim 1 wherein the cutting head is comprised of steel.

14. The device of claim 1 wherein the body section is comprised of polycarbonate.

15. The device of claim 1 further comprising an automatic advancement device to assist in the movement of the device for removing a tubular body member through the body.

16. The device of claim 15 wherein the automatic advancement device comprises an ultrasonic vibrator or electric motor.

17. The device of claim 1 that further comprises a handle attached to the proximal end of the body section.

18. The device of claim 17 wherein the handle comprises a cylindrical tube.

19. The device of claim 17 that further comprises a hand grip attached to the handle.

20. An apparatus for harvesting a tubular body member, the apparatus comprising:

- (a) an endovascular component having a diameter smaller than the diameter of the tubular body member, the endovascular component capable of being inserted into the tubular body member;
- (b) a cutting tool comprising:
 - (i) a tubular body section;
 - (ii) a cutting head attached to the tubular body section, the cutting head having a leading edge comprising an annular cutting blade; and
 - (iii) an opening extending through the cutting tool;

wherein the opening is sized to allow the tubular body member and some body tissue surrounding the tubular body member to fit inside.

21. The apparatus of claim 20 wherein the endovascular component includes an inner section and an outer section.

22. The apparatus of claim 21 wherein the inner section comprises a medical guide wire.

23. The apparatus of claim 20 that further comprises a torque handle coupled to the tubular body section, the torque handle used to turn the apparatus to assist in moving it through the body.

24. The apparatus of claim 20 further comprising an automatic advancement device to assist in the movement of the apparatus through the body.

25. A device for removing a tubular body member from a body, the device having a leading edge comprising an annular cutting blade.

26. The device of claim 25 that further includes an inner cavity extending therethrough, the inner cavity including a funnel-shaped section having a first inner diameter juxtaposed the leading edge and a second inner diameter, the second inner diameter smaller than the first inner diameter.

27. The device of claim 25 that further includes an exterior surface and a helical thread on the exterior surface.

28. A method for removing a tubular body member from a body, the method comprising the steps of:

making a first incision;

accessing and dividing a first end of the tubular body member near the first incision;

making a second incision;

accessing and dividing a second end of the tubular body member near the second incision;

inserting an endovascular component into the first end of the tubular body member;

moving the endovascular component through the tubular body member and out the second end so that the endovascular component has a proximal end exposed at the first end of the tubular body structure and a distal end exposed at the second end of the tubular body structure;

securing the proximal end of the endovascular component and the distal end of the endovascular component and

straightening the tubular body member by applying force to each end of the endovascular component;

positioning a cutting tool having a leading edge comprising an annular cutting blade and an inner cavity extending therethrough so that the endovascular component is inside the inner cavity;

advancing the cutting tool from the first end to the second end, the cutting tool cutting through and dissecting body tissue as it moves, wherein the tubular body portion is positioned within the dissected body tissue; and

removing the dissected body tissue including the tubular body member.

29. The method of claim 28 wherein the cutting tool is advanced from the first end to the second end by utilizing a twisting or vibrating motion.

30. The method of claim 28 wherein the cutting tool is advanced by utilizing a motor that causes the cutting tool to twist or vibrate.

31. A cutter head used with a cutting tool for removing a tubular body member from a body, the cutter head comprising:

(a) a leading edge comprising an annular cutting blade;

(b) an inner cavity extending therethrough, the inner cavity comprising a funnel-shaped section having a first diameter juxtaposed the leading edge and a second diameter, the second diameter being smaller than the first diameter; and

(c) an attachment structure for attaching to a body section.

32. A cutting tool for removing a tubular body member from a body, the cutting tool comprising:

(a) a cutter head; and

(b) a body section connectable to the cutter head, the body section having an exterior surface and a structure positioned on the exterior surface, the structure to assist in advancing the cutting tool through body tissue.

33. The cutting tool of claim 32 wherein the structure is a helical thread.

* * * * *

专利名称(译)	用于收获管状体构件的经皮装置和方法		
公开(公告)号	US20040122458A1	公开(公告)日	2004-06-24
申请号	US10/618456	申请日	2003-07-11
[标]申请(专利权)人(译)	OPIE约翰·C· JOYCE STEPHEN J		
申请(专利权)人(译)	OPIE JOHN C. JOYCE 斯蒂芬·		
当前申请(专利权)人(译)	斯科茨代尔医疗器械, INC.		
[标]发明人	OPIE JOHN C JOYCE STEPHEN J		
发明人	OPIE, JOHN C. JOYCE, STEPHEN J.		
IPC分类号	A61B17/00 A61B17/32 G07F17/34 A61D1/02		
CPC分类号	A61B17/00008 A61B17/32053 A61B17/320016		
优先权	60/395248 2002-07-11 US		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种用于从身体收获管状体构件的经皮收获装置。经皮收获装置包括用于充分矫直待移除的管状血管的血管内导向装置和插入血管内导向装置上的血管周围切割工具。切割工具沿管状主体构件的长度前进以被移除, 并且当切割工具前进时, 切割工具切割身体组织(其中管状主体构件定位在身体组织内)。因此, 身体组织从身体解剖, 然后通过从身体拉动血管内导向器和管状身体构件和周围的身体组织, 然后从身体经皮和快速提取。

