




US 20080234744A1

(19) **United States**(12) **Patent Application Publication**  
**Zylber et al.**(10) **Pub. No.: US 2008/0234744 A1**(43) **Pub. Date: Sep. 25, 2008**(54) **SPINAL STABILIZATION SYSTEM WITH  
RIGID AND FLEXIBLE ELEMENTS****Publication Classification**(76) **Inventors:** **Emmanuel Zylber**, Marseille (FR);  
**Thomas Egli**, Volketswil (CH);  
**Rosemary Thompson**, Seen (CH);  
**Markus Froehlich**, Balterswil  
(CH); **Giuseppe Cicerchia**,  
Winterthur (CH); **Jack A. Dant**, St.  
Paul, MN (US); **Thomas O. Viker**,  
Arden Hills, MN (US); **Kevin R.  
Ley**, Elk River, MN (US)(51) **Int. Cl.**  
**A61B 17/70** (2006.01)  
**A61B 17/58** (2006.01)  
**A61B 17/04** (2006.01)(52) **U.S. CL. .... 606/264; 606/246; 606/254; 606/305**(57) **ABSTRACT**

A spinal stabilization system generally comprises first and second anchor members configured to be secured to first and second vertebrae within a patient's body, a flexible element secured to the first anchor member, and a rigid element secured to the second anchor member. An end portion of the rigid element is coupled to an end portion of the flexible so that the system is able to provide both rigid and dynamic stabilization. The coupling is maintained even if the flexible element relaxes after a period of time within the patient's body.

Correspondence Address:

**CROMPTON, SEAGER & TUFTE, LLC**  
**1221 NICOLLET AVENUE, SUITE 800**  
**MINNEAPOLIS, MN 55403-2420 (US)**(21) **Appl. No.: 11/688,961**(22) **Filed: Mar. 21, 2007**




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 6A




FIG. 7







FIG. 8



## SPINAL STABILIZATION SYSTEM WITH RIGID AND FLEXIBLE ELEMENTS

### FIELD OF THE INVENTION

[0001] This invention relates to spinal stabilization systems, and more particularly to such systems including both a rigid element and a flexible element.

### BACKGROUND

[0002] The spinal column is a highly complex system of bones and connective tissues that provides support for the body and protects the delicate spinal cord. The spinal column includes a series of vertebrae stacked one on top of the other, each vertebral body including an inner or central portion of relatively weak cancellous bone and an outer portion of relatively strong cortical bone. The vertebrae in the cervical, thoracic, and lumbar regions of the spine are separated by intervertebral discs, which serve as cushions between adjacent vertebrae to dampen compressive forces experienced by the spine. A vertebral canal containing the spinal cord is formed by the intervertebral foramen of the vertebrae. In spite of the complexities, the spine is a highly flexible structure, capable of a high degree of curvature and twist in nearly every direction. For example, the kinematics of the spine normally includes flexion, extension, rotation, and lateral bending.

[0003] There are many types of conditions that can lead to significant pain and affect movement of the spine, including spinal disorders such as scoliosis (abnormal lateral curvature of the spine), kyphosis (abnormal forward curvature of the spine, usually in the thoracic spine), excess lordosis (abnormal backward curvature of the spine, usually in the lumbar spine), and spondylolisthesis (forward displacement of one vertebra over another, usually in a lumbar or cervical spine), as well as conditions caused by abnormalities, disease, or trauma, such as ruptured or slipped discs, degenerative disc disease, fractured vertebra, and the like. In addition to causing pain, these conditions may also threaten the critical elements of the nervous system housed within the spinal canal.

[0004] One of the most common methods for treating these conditions is to immobilize a portion of the spine to allow treatment. Traditionally, immobilization has been accomplished by rigid stabilization. For example, in a conventional spinal fusion procedure, a surgeon restores the alignment of the spine or the disc space between vertebrae by installing a rigid fixation rod between pedicle screws secured to adjacent vertebrae. Bone graft is placed between the vertebrae, and the fixation rod cooperates with the screws to immobilize the two vertebrae relative to each other so that the bone graft may fuse with the vertebrae.

[0005] Dynamic stabilization has also been used in spinal treatment procedures. Dynamic stabilization does not result in complete immobilization, but instead permits enhanced mobility of the spine while also providing sufficient stabilization to effect treatment. One example of a dynamic stabilization system is the Dynesys® system available from Zimmer, Inc. of Warsaw, Ind. Such dynamic stabilization systems typically include a flexible spacer positioned between pedicle screws installed in adjacent vertebrae of the spine. Once the spacer is positioned between the pedicle screws, a flexible cord is threaded through a channel in the spacer. The flexible cord is also secured to the pedicle screws by a housing and set

screw, thereby retaining the spacer between the pedicle screws while cooperating with the spacer to permit mobility of the spine.

[0006] In some instances, it is desirable to immobilize a portion of the spine using a rigid stabilization system without significantly limiting the mobility or increasing the stress on nearby areas of the spine. Although combining the rigid stabilization system with a dynamic stabilization system would help achieve this objective, there are several challenges associated with doing so. Specifically, there are several challenges associated with combining a flexible element, such as a braided polymer cord, with a rigid element, such as a rigid fixation rod, in a single construct. The cord and rod are ideally connected or coupled to each other before or during a surgical procedure. But the stiffness of the flexible element is often designed to decrease after placement into a patient's body and as treatment occurs to provide increased range of motion. Therefore, a spinal stabilization system in which the rigid element remains sufficiently coupled to the flexible element after this "relaxation" is highly desirable.

### SUMMARY OF THE INVENTION

[0007] This invention provides a system or construct incorporating both a rigid element and flexible element to stabilize a portion of the spine. The system generally includes first and second anchor members, which may be pedicle screw assemblies, configured to be secured to first and second vertebrae within a patient's body. The rigid element is secured to the first anchor member, while the flexible element is secured to the second anchor member. Respective end portions of the rigid and flexible elements are coupled to each other in a manner that securely retains their connection, even after the system has been positioned within the patient's body for an extended period of time.

[0008] In some embodiments, the end portion of the flexible element is received over the end portion of the rigid element. For example, the flexible element may be a cord constructed from polymer fibers braided over the end portion of the rigid element. To further facilitate retaining the cord on the rigid element, the fibers may be ultrasonically cut and/or ultrasonically welded to an enlarged ball tip of the rigid element. Such an arrangement increases the amount of surface area in contact between the cord and the rigid element and makes it difficult to pull the cord off the rigid element. A compression-fit collar may also be received over the end portion of the cord so that the fibers are gripped between the ball tip of the rigid element and the collar.

[0009] In other embodiments, the end portion of the rigid element includes an axial bore that receives the end portion of the flexible element. The axial bore extends at least partially into the rigid element from an end surface and is shaped to retain an end portion of the flexible element therein. For example, the end portion of the flexible element may include an enlarged section having a first diameter and the axial bore may include a restricted or tapered portion having a second diameter less than the first diameter. The enlarged section of the flexible element may be formed by positioning an insert or plug into the end portion of the flexible element. The restricted portion of the axial bore may be incorporated into the shape of the bore at the time of manufacture or may be formed by swaging a portion of the rigid element.

[0010] If desired, the end portion of the rigid element with the axial bore may be received in a housing of a vertebral anchor, such as a pedicle screw assembly. One or more open-

ings extend through an outer surface of the rigid element and into the axial bore. A pin is press-fit into the opening by means of a hand press or by tightening a set screw that secures the rigid element within the housing of the pedicle screw assembly. Because the pin extends into the axial bore, it applies a compression force to the end portion of the flexible element received by the bore. This compression force retains the end portion of the flexible element within the bore.

[0011] By virtue of the foregoing, a spinal stabilization system that effectively incorporates aspects of both rigid and dynamic stabilization is provided. The different manners of coupling the rigid element to the flexible element are each designed so that the coupling is maintained even after relaxation of the flexible element over time.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate exemplary embodiments of the invention and, together with a general description of the invention given above, and the detailed description given below, serve to explain the principles of the invention.

[0013] FIG. 1 is a partial side elevational view showing a spinal stabilization system including both a rigid element and a flexible element secured within a patient's body;

[0014] FIG. 2 is a schematic view showing how the rigid and flexible elements of FIG. 1 may be coupled together according to one embodiment of the invention;

[0015] FIG. 3 is a side elevational view, partially in cross-section, showing how the rigid and flexible elements of FIG. 1 may be coupled together according to another embodiment of the invention;

[0016] FIG. 4 is a side elevational view, partially in cross-section, showing how the rigid and flexible elements of FIG. 1 may be coupled together according to another embodiment of the invention;

[0017] FIG. 5 is cross-sectional view showing how the rigid and flexible elements of FIG. 1 may be coupled together according to another embodiment of the invention;

[0018] FIG. 6 is a cross-sectional view showing how the rigid and flexible elements of FIG. 1 may be coupled together according to another embodiment of the invention;

[0019] FIG. 6A is a perspective view of a portion of the rigid element shown in FIG. 6;

[0020] FIG. 7 is a perspective view showing a portion of the flexible element of FIG. 1 according to another embodiment of the invention;

[0021] FIG. 8 is a cross-sectional perspective view showing how the flexible element of FIG. 6 may be coupled to the rigid element of FIG. 1;

[0022] FIG. 9 is a cross-sectional side view showing the rigid and flexible elements of FIG. 1 according to another embodiment of the invention;

[0023] FIG. 10 is a perspective view showing how the rigid and flexible elements of FIG. 9 may be coupled together; and

[0024] FIG. 11 is a partial side elevational view, partially in cross-section, showing how the rigid and flexible elements of FIG. 1 may be coupled together according to another embodiment of the invention.

#### DETAILED DESCRIPTION

[0025] FIG. 1 shows one embodiment of a spinal stabilization system or construct 10 according to the invention within a

patient's body. The stabilization system 10 includes first, second, and third anchor members 12, 14, 16 secured to respective first, second, and third vertebrae 18, 20, 22 within the patient's body. The anchor members 12, 14, 16 may be any type of anchor such as a screw or hook designed to cooperate with a rigid element 24 or a flexible element 26 to stabilize a portion of the spine. For example, in the embodiment shown in FIG. 1, the anchor members 12, 14, 16 are pedicle screw assemblies each having a screw body 30, a housing or retainer 32 coupled to the screw body 30, and a set screw 34. Each housing 32 receives the rigid element 24 or the flexible element 26, which are secured to the associated housing 32 by one of the set screws 34. One example of this type of pedicle screw arrangement is the Optima® Spinal Stabilization System available from Zimmer, Inc. of Warsaw, Ind.

[0026] The rigid element 24 and the flexible element 26 each extend between two or more of the pedicle screw assemblies. The rigid element 24 may be a metal rod, such as those commonly used in rigid spinal fixation procedures, while the flexible element 26 may be a cord, such as those commonly used in dynamic stabilization procedures. For example, the flexible element 26 may be constructed from braided polyethylene-terephthalate (PET) fibers or other braided polymer fibers. A flexible spacer 36 is received over the flexible element 26 to provide additional support during movement of the spine in some embodiments.

[0027] As shown in FIG. 1, the rigid element 24 is coupled to the flexible element 26 between the first and second anchor members 12, 14. Such an arrangement enables the overall system or construct 10 to combine the features of both rigid stabilization and dynamic stabilization. In particular, the rigid element 24 enables the system 10 to rigidly immobilize a desired area of the spine to promote fusion or other treatment in a desired area, while the flexible element 26 provides additional stabilization without significantly increasing the stress on nearby vertebrae or compromising mobility. The rigid and flexible elements 24, 26 may be coupled to each other in a variety of different manners, examples of which will be described below with reference to FIGS. 2-11.

[0028] For example, FIGS. 2 and 3 illustrate embodiments in which an end portion 50 of a braided cord 52 is received over an end portion 54 of a rigid fixation rod 56. The end portion 50 of the cord 52 is retained on the end portion 54 of the rod 56, which may be achieved by braiding or weaving the fibers of the cord 52 over the end portion 54. Once this step is complete, the region where the cord 52 overlaps the rod 56 is heat treated in a manner that promotes intimate chemical and physical bonding of the cord 52 to the rod 56. For example, the cord 52 may be ultrasonically welded to the rod 56. Such an arrangement results in the cord 52 being coupled to the rod 56 prior to implantation without placing meaningful stresses on the cord 52 and without the system 10 requiring additional components.

[0029] Additionally, as shown in FIG. 3, in some embodiments the end portion 54 of the fixation rod 56 may further include an enlarged ball tip 58. Once the cord 52 is braided over the ball tip 58, the end portion 50 of the cord 52 is cut at location on the rod 56 spaced from the ball tip 58 (i.e., where the cord 52 has a smaller diameter than that of the ball tip) by ultrasonic cutting. The ultrasonic cutting and/or welding results in the fiber ends joining together so that the end portion 50 includes a permanent diameter smaller than the ball tip 58, thereby preventing the cord 52 from fraying and further retaining it on the end portion 54 of the fixation rod 56. The



relatively large amount of contact area between the cord 52 and the rod 56 helps distribute any pre or post-operative loads on the cord 52, which in turn minimizes the effects of changes in those loads resulting from post-operative relaxation of the cord 52 or other conditions.

[0030] If desired, a collar 60 may also be compression-fitted around the end portion 50 of the cord 52 to further retain the cord 52 on the fixation rod 56. When tension is applied to the cord 52, the collar 60 cooperates with the ball tip 58 to provide a gripping force. The collar 60 includes a polished end surface 62 configured to confront the spacer 36 (FIG. 1), with the end surface 62 optionally defined by a radially extending flange 64. Those skilled in the art will appreciate that the collar 60 may also be designed to interact with one of the pedicle screw assemblies.

[0031] Rather than being received over the end portion of the rigid element 24, the flexible element 26 may be received and retained within a portion of the rigid element 24. For example, FIG. 4 illustrates an embodiment in which an end portion 70 of a fixation rod 72 includes an axial bore 74 extending from an end surface 76. An end portion 78 of a flexible cord 80 is received in the axial bore 74. To retain the cord 80 in the bore 74, the end portion 70 of the fixation rod 72 is swaged (i.e., cold-worked) about its circumference at one or more locations designated by 82. The 360 degree swages 82 place the cord 80 into high, radially-symmetric compression so that it cannot be easily pulled out of the axial bore 74. The swages 82 also provide the end portion 70 of the fixation rod 72 with a rib-like appearance.

[0032] FIG. 5 also illustrates an embodiment of the spinal stabilization system 10 in which a fixation rod 90 is swaged to retain an end portion 92 of a flexible cord 94 within an axial bore 96. Specifically, the fixation rod 90 terminates in an end surface 98 defined by a radially extending flange 100. The end surface 98 may be configured to confront a spacer 36 (FIG. 1) and further includes flange 102 extending distally therefrom around the opening of the axial bore 96. After the end portion 92 of the cord 94 is inserted into the axial bore 96, the distal flange 102 is swaged in a radially inward direction to define a restricted portion 104 of the axial bore 96. The restricted portion 104 has a diameter less than that of the end portion 92 of the cord 94 so that the cord 94 is retained in the axial bore 96.

[0033] For this purpose, the end portion 92 of the cord 94 may include an insert or plug 106 to define an enlarged diameter section 108. The insert 106 may be constructed from metal or any other biocompatible material and is surrounded and retained by the end portion 92 of the cord 94. For example, after weaving fibers of the cord 94 around the insert 106 or positioning the insert 106 in a predefined space within the end portion 92, the cord 94 may be ultrasonically heated while being compressed around the insert 106 in a mold (not shown). This ultrasonic forming process promotes bonding of the cord fibers to the insert 106 and provides the cord 94 with a shape that retains the insert 106 in the end portion 92. Thus, when the end portion 92 of the cord 94 is received in the axial bore 96 and the distal flange 102 is swaged inwardly to define the restricted portion 104, pulling on the cord 94 results in the cord fibers being “wedged” between the insert 106 and the restricted portion 104. This resistance to pull-out remains effective even after warming and relaxation of the cord 94 within a patient’s body.

[0034] An embodiment that operates upon similar principles is shown in FIGS. 6 and 6A. In this embodiment, an end

portion 112 of a flexible cord 114 is provided with an insert 116 in the same manner as the previous embodiment to define an enlarged diameter section 118. A fixation rod 120 having an enlarged end portion 122 includes an axial bore 124 extending from an end surface 126. The axial bore 124 receives the end portion 112 of the cord 114, but includes a restricted portion 128 having a smaller diameter than that of the enlarged section 118. If desired, an interior surface 130 of the axial bore 124 may be tapered to help define the restricted portion 128 and to define a shape that more closely resembles that of the cord end portion 112.

[0035] In this arrangement, the cord 114 cannot be end-loaded into the axial bore 124 through an opening 132 on the end surface 126 of the fixation rod 120. Instead, the end portion 112 of the cord 114 is inserted through a slot 134 on the end portion 122 of the rod 120. The slot 134 extends into the axial bore 124 and includes an enlarged opening 136 to accommodate the enlarged section 118 of the cord 114, as shown in FIG. 6A. Applying tension to the cord 114 after the end portion 112 is received in the axial bore 124 creates a wedge-like effect due to the interference between insert 116 and the restricted portion 128. In other words, as with the embodiment shown in FIG. 5, the fibers of the cord 114 are “wedged” between the insert 116 and the restricted portion 128 to retain the cord 114 within the axial bore 124. The more tension that is placed on the cord 114, the stronger it is gripped between the insert 116 and the restricted portion 128.

[0036] The cord 114 may be inserted through the slot 134 and into the axial bore 124 prior to or even during an operation because of the pre-formed shape of the fixation rod 120. For example, during a surgical procedure, the rod 120 may first be secured to a top-loading pedicle screw 30 (FIG. 1) using the housing 32 and set screw 34. After inserting the end portion 112 of the cord 114 through the slot 134 and into the axial bore 124, the cord 114 may then be secured to a different pedicle screw assembly to stabilize the entire construct 10. Because the cord 114 is not put under any stress prior to insertion into the patient’s body, concerns about stress relaxation during storage are avoided. Additionally, if further surgical procedures are later required to effect treatment, the cord 114 may be easily replaced without requiring removal of the fixation rod 120. This is particularly advantageous when seeking to modify the amount of dynamic stabilization provided by the entire construct 10 by replacing the original cord 114 with a different one.

[0037] FIGS. 7 and 8 illustrate another embodiment in which a cord 140 may be coupled to a rigid element 142 between the first and second anchor members 12, 14 (FIG. 1). In this embodiment, the cord 140 is provided with a pre-formed shape. For example, the cord 140 may be constructed from polymer fibers and may be ultrasonically heated while being compressed in a mold. This ultrasonic forming process in one embodiment results in an end portion 144 of the cord 140 having a reduced diameter and first and second recesses 146, 148.

[0038] The rigid element 142 includes an end portion 150 with an outer surface 152 and an end surface 154. The end surface 154 is defined by a radially extending flange 156 and configured to confront the spacer 36 (FIG. 1). An axial bore 158 extends into the end portion 150 from the end surface 154, and the outer surface 152 includes first and second openings or holes 160, 162 extending into the axial bore 158. The axial bore 158 receives the end portion 144 of the cord 140, with the first and second openings 160, 162 aligned with

the respective first and second recesses **146, 148**. To retain the cord **140** within the axial bore **158**, first and second fasteners **164, 166** are inserted through the respective first and second openings **160, 162** until they are received in the respective first and second recesses **146, 148**. Because the first and second recesses **146, 148** are permanently formed in the end portion **144** of the cord **140**, relaxation of the cord **140** has minimal or no affect on the engagement between the first and second recesses **146, 148** and the first and second fasteners **164, 166**.

[0039] The fasteners **164, 166** shown in FIG. 8 are pins that are press-fit into the first and second openings **160, 162**. It will be appreciated, however, that a wide variety of other types of fasteners (screws, rings, clips, etc.) may be secured within the first and/or second openings **160, 162** to retain the end portion **144** of the cord **140** within the axial bore **158**. It will also be appreciated that only one fastener may be used to retain the cord **140** and that the axial bore **158** of the rigid element **142** may be shaped with features adapted to cooperate with the preformed shaped of the cord **140**. For example, rather than including the second opening **162**, the rigid element **142** may be machined to define a protrusion (not shown) in the axial bore **158** at the same location. The protrusion would cooperate with the second recess **148** to retain the end portion **144** of the cord **140** in the axial bore **158**. The end portion **144** of the cord **140** and axial bore **158** of the rigid element **142** may therefore be shaped in a variety of different manners to achieve this type of relationship.

[0040] FIGS. 9-11 illustrate embodiments of the system **10** shown in FIG. 1 in which the rigid member **24** is shaped to cooperate with one of the pedicle screw assemblies **12, 14, 16** to retain the flexible element **26** within a portion thereof. The housings **32** and set screws **34** shown in FIG. 1 have a different configuration in the embodiments shown in FIGS. 9-11 and will be indicated with prime marks (') in the description below.

[0041] To this end, FIGS. 9 and 10 illustrate a rigid element **172** having an end portion **174** received in the housing **32'** of a pedicle screw assembly. The end portion **174** includes an end surface **176** configured to confront a spacer **36** (FIG. 1), an axial bore **178** extending from the end surface **176**, an outer surface **180**, and first and second openings **182, 184** on the outer surface **180** extending into the axial bore **178**. The first opening **182** has a relatively small diameter and receives a needle member **186**, while the second opening **184** has a larger diameter and receives a pin **188**. An interference fit may be provided between the needle member **186** and the first opening **182** and the pin **188** and the second opening **184**.

[0042] A flexible element **190**, such as a cord constructed from braided polymer fibers, includes an end portion **192** received in the axial bore **178**. The flexible element **190** is initially secured within the axial bore **178** by inserting the needle member **186** through the first opening **182**. The manufacturer typically accomplishes this step so that the construct is pre-assembled with the flexible element **190** coupled to the rigid element **172** prior to delivery to the customer. The needle member **186** engages the cord **190** proximate an end **194**, which serves little function in terms of ultimately providing stabilization once in a patient's body.

[0043] The pin **188** may also be partially inserted into the second opening **184** by the manufacturer, but is not advanced far enough to place any appreciable stresses on the cord **190**. Instead, the final pressing of the pin **188** is accomplished prior to use with a hand press (not shown) or other similar tool. The

pin **188** is ideally advanced through the second opening **184** until a top surface **196** of the pin **188** becomes substantially flush with the outer surface **180** of the rigid element **172**. Such an arrangement prevents the pin **188** from interfering with the operation of the set screw **34'**, which secures the rigid element **172** to the housing **32'** of the pedicle screw assembly.

[0044] The pin **188** compresses the flexible element **190** within the axial bore **178** to retain the flexible element **190** therein. A protrusion **198**, such as a bump or rib, may be provided in the axial bore **178** opposite the second opening **184** so that the flexible element **190** is gripped between the pin **188** and the protrusion **198**. The pin **188** applies sufficient force to securely retain the cord **190** even after relaxation once inserted into a patient's body. Although only a press-fit pin is shown, any type of fastener capable of applying forces to the cord **190** may be used instead.

[0045] FIG. 11 shows a similar embodiment having a pin **210** for retaining an end portion **212** of a flexible element **214** within an axial bore **216** of a rigid element **218**. As with the previous embodiment, the axial bore **216** is positioned within an end portion **220** of the rigid element **218** received in the housing **32'** of a pedicle screw assembly and has an end surface **222** configured to confront the spacer **36** (FIG. 1). An opening **224** on an outer surface **226** of the end portion **220** extends into the axial bore **216** and is aligned with the set screw **34'** received in the housing **32'**. The set screw **34'** normally engages internal threads **230** to secure the end portion **220** of the rigid element in a socket defined by the housing **32'**. To accommodate for the pin **210**, the housing **32'** further includes first and second tabs **234, 236** extending upwardly. Each of the first and second tabs **234, 236** includes internal threads **238** as well.

[0046] In use, the end portion **212** of the flexible element **214** is inserted into the axial bore **216**. The pin **210** is then inserted into the opening **224** and the set screw **34'** is advanced along the internal threads **238** of the first and second tabs **234, 236** until it contacts a top surface **240** of the pin **210**. To secure the flexible element **214** within the axial bore **216**, the set screw **34'** is further advanced to engage the internal threads **230** of the housing **32'** and to push the pin **210** into the opening **224**. The set screw **34'** is advanced until the top surface **240** of the pin **210** is substantially flush with the outer surface **226** of the rigid element **218**. In this position, the pin **210** applies a sufficient compression force to retain the end portion **212** of the flexible element **214** within the axial bore. One or more protrusions **242** or the like may be provided within the axial bore **216** to help grip the flexible element **214**, much like the previous embodiment.

[0047] Thus, the flexible element **214** may be secured to the rigid element **218** without any additional tools. The same tool normally used to secure the set screw **34'** is used to advance the pin **210** into the axial bore **216**. Although the pin **210** and set screw **34'** are shown as separate components, they may alternatively be integrally formed as a single component. The first and second tabs **234, 236** may also be configured to be removed from the housing **32'** after the set screw **34'** is completely advanced. In particular, the first and second tabs **234, 236** serve to distribute the force applied to the housing **32'** while tightening the set screw **34'** with a screwdriver or other tool. The tabs **234, 236** may be frangibly connected or otherwise separable from the housing **32'** of the pedicle screw assembly. Once the set screw **34'** is advanced so that it only

engages the internal threads 230 of the housing 32', the first and second tabs 234, 236 may be broken off from the housing 32' and removed.

[0048] While the invention has been illustrated by the description of one or more embodiments thereof, and while the embodiments have been described in considerable detail, they are not intended to restrict or in any way limit the scope of the appended claims to such detail. Additional advantages and modifications will readily appear to those skilled in the art. For example, although the rigid element is primarily described above as a metal rod, those skilled in the art will appreciate that "rigid" is a relative term. To this end, the rigid element may be a metal cable and the flexible element may be a polymer cord. The cable and cord may be coupled using the techniques described above or may simply be spliced together.

[0049] Therefore, the invention in its broader aspects is not limited to the specific details, representative apparatus and methods, and illustrative examples shown and described. Accordingly, departures may be made from such details without departing from the scope or spirit of the general inventive concept.

What is claimed is:

1. A spinal stabilization system, comprising:  
first and second anchor members configured to be secured to first and second vertebrae, respectively, within a patient's body;  
a flexible element secured to the first anchor member and having an end portion; and  
a rigid element secured to the second anchor member and having an end portion;  
wherein the end portion of one of the flexible element and the rigid element receives and couples to the end portion of the other one of the flexible element and the rigid element between the first and second anchor members.
2. The spinal stabilization system of claim 1 wherein the flexible element is a cord constructed from braided fibers, the fibers surrounding the end portion of the rigid element.
3. The spinal stabilization system of claim 2 wherein the end portion of the rigid element includes an enlarged tip.
4. The spinal stabilization system of claim 3 wherein the end portion of the flexible element is ultrasonically welded to the rigid element.
5. The spinal stabilization system of claim 2, further comprising:  
a collar received over the end portion of the flexible element to retain the flexible element over the end portion of the rigid element.
6. The spinal stabilization system of claim 5, further comprising:  
a spacer received over the flexible element, the collar having a first end surface confronting the spacer.
7. The spinal stabilization system of claim 6, wherein the collar has a second end surface confronting the second anchor member.
8. The spinal stabilization system of claim 1 wherein the rigid element includes an axial bore extending into the end portion thereof, the end portion of the flexible element being received in the axial bore.
9. The spinal stabilization system of claim 8 wherein the rigid element is a metal rod swaged about at least a portion of the circumference of the end portion thereof to radially compress the flexible element in the axial bore.

10. The spinal stabilization system of claim 9 wherein the end portion of the rigid element is swaged at two spaced apart locations.

11. The spinal stabilization system of claim 8 wherein the end portion of the flexible element has a first diameter, the axial bore including a restricted portion having a second diameter less than the first diameter to retain the end portion of the flexible element therein.

12. The spinal stabilization system of claim 11 wherein the end portion of the flexible element includes an insert to define an enlarged section having the first diameter.

13. The spinal stabilization system of claim 12, wherein the rigid element further includes a slot extending into the axial bore, the slot being shaped to receive the end portion of the flexible element so that the flexible element is inserted into the axial bore.

14. The spinal stabilization system of claim 12 wherein the restricted portion is at least partially defined by a tapered interior surface of the axial bore.

15. The spinal stabilization system of claim 12 wherein the insert is constructed from a rigid biocompatible material.

16. The spinal stabilization system of claim 15 wherein the insert is constructed from metal.

17. The spinal stabilization system of claim 12 wherein the flexible element is a cord constructed from braided fibers, the fibers surrounding the insert at the end portion of the flexible element.

18. The spinal stabilization system of claim 17 wherein the fibers around the insert are ultrasonically heated and compressed to secure the insert within the end portion of the flexible element.

19. The spinal stabilization system of claim 11 wherein the end portion of the rigid element terminates in an end surface, the end surface having a flange extending distally therefrom, the restriction being formed by swaging the flange in a radially inward direction.

20. The spinal stabilization system of claim 8, wherein the end portion of the rigid element includes an outer surface surrounding the axial bore and an opening on the outer surface extending into the axial bore, the system further comprising:

a fastener secured in the opening and extending into the axial bore to retain the flexible element therein.

21. The spinal stabilization system of claim 20 wherein the fastener is a pin secured within the opening by an interference fit.

22. The spinal stabilization system of claim 20 wherein the flexible element includes a recess shaped to cooperate with the fastener when the fastener is secured in the opening on the outer surface of the rigid element.

23. The spinal stabilization system of claim 22 wherein the recess is formed by ultrasonically heating the flexible element while the flexible element is compressed into a desired shape.

24. The spinal stabilization system of claim 8, further comprising:

a spacer received over the flexible element; and

a flange extending radially from the rigid element to define an end surface confronting the spacer.

25. The spinal stabilization system of claim 1 wherein the flexible element is a cord constructed from braided polymer fibers.

26. The spinal stabilization system of claim 1 wherein the rigid element is a metal rod.

**27.** The spinal stabilization system of claim **1** wherein the first and second anchor members are respective first and second pedicle screw assemblies.

**28.** A spinal stabilization system, comprising:

first and second anchor members configured to be secured to first and second vertebrae, respectively, within a patient's body;

a flexible element secured to the first anchor member and having an end portion; and

a rigid element secured to the second anchor member and having an end portion;

wherein the end portion of the rigid element includes an axial bore to receive the end portion of the flexible element, the axial bore retaining the end portion of the flexible element therein to couple the rigid and flexible elements between the first and second anchor members.

**29.** The spinal stabilization system of claim **28** wherein the rigid element is a metal rod swaged to retain the end portion of the flexible element in the axial bore.

**30.** The spinal stabilization system of claim **29** wherein the end portion of the rigid element is swaged about at least a portion of the circumference thereof at two spaced apart locations.

**31.** The spinal stabilization system of claim **29** wherein the end portion of the rigid element includes an end surface having a flange extending distally therefrom, the flange being swaged in a radially inward direction.

**32.** The spinal stabilization system of claim **28** wherein the end portion of the flexible element includes an insert to define an enlarged section.

**33.** The spinal stabilization system of claim **32** wherein the flexible element is a cord constructed from braided fibers, the fibers surrounding the insert at the end portion of the flexible element.

**34.** The spinal stabilization system of claim **33** wherein the fibers around the insert are ultrasonically heated and compressed to secure the insert within the end portion of the cord.

**35.** The spinal stabilization system of claim **32**, the rigid element further comprising:

a slot extending into the axial bore, the slot receiving the end portion of the flexible element when the flexible element is inserted into the axial bore.

**36.** The spinal stabilization system of claim **28**, further comprising:

a spacer received over the cord;

wherein the rigid element includes an end having a flange radially extending therefrom, the flange defining an end surface confronting the spacer.

**37.** A spinal stabilization system, comprising:

first and second anchor members configured to be secured to first and second vertebrae, respectively, within a patient's body;

a flexible element secured to the first anchor member and having an end portion; and

a rigid element secured to the second anchor member and having an end portion;

wherein the end portion of the flexible element is received over the end portion of the rigid element and retained thereon to couple the flexible element to the rigid element.

**38.** The spinal stabilization system of claim **37** wherein the flexible element is a cord constructed from braided fibers, the fibers surrounding the end portion of the rigid element.

**39.** The spinal stabilization system of claim **38** wherein the end portion of the rigid element includes an enlarged tip and the end portion of the flexible element is adapted to be ultrasonically cut at a location spaced from the enlarged tip.

**40.** The spinal stabilization system of claim **39**, further comprising:

a collar received over the end portion of the flexible element and adapted to provide a compression force to retain the flexible element on the end portion of the rigid element.

**41.** The spinal stabilization system of claim **40**, further comprising:

a spacer received over the cord, the collar having a first end surface confronting the spacer.

**42.** A spinal stabilization system, comprising:

first and second anchor members configured to be secured to first and second vertebrae, respectively, within a patient's body;

a flexible element secured to the first anchor member and having an end portion;

a rigid element secured to the second anchor member and having an end portion with an end surface, an axial bore extending from the end surface, an outer surface, and a first opening on the outer surface extending into the axial bore, the axial bore receiving the end portion of the flexible element; and

a first fastener extending through the first opening and into the axial bore to retain the flexible element therein, thereby coupling the rigid and flexible elements between the first and second anchor members.

**43.** The spinal stabilization system of claim **42** wherein the first fastener is a pin secured within the first opening by an interference fit.

**44.** The spinal stabilization system of claim **42** wherein the flexible element includes a recess shaped to cooperate with the first fastener when the first fastener is inserted through the first opening and into the axial bore.

**45.** The spinal stabilization system of claim **44** wherein the flexible element is a cord constructed from braided polymer fibers, the recess being formed by ultrasonically heating the flexible element while the flexible element is compressed into a desired shape.

**46.** The spinal stabilization system of claim **42** wherein the end portion of the rigid element further includes a second opening on the outer surface extending into the axial bore, the system further comprising:

a second fastener extending through the second opening and into the axial bore to retain the flexible element therein.

**47.** A spinal stabilization system, comprising:

first and second anchor members configured to be secured to first and second vertebrae, respectively, within a patient's body;

a flexible element secured to the first anchor member and having an end portion;

a rigid element secured to the second anchor member and having an end portion with an end surface, an axial bore extending from the end surface, an outer surface, and first and second openings on the outer surface extending into the axial bore, the axial bore receiving the end portion of the flexible element;

a needle member inserted through the first opening to retain the end portion of the flexible element within the axial bore; and

a fastener extending through the second opening to further retain the flexible element in the axial bore, the fastener having a top surface spaced apart from the outer surface of the rigid element in an initial position and substantially flush with the outer surface in an installed position.

**48.** The spinal stabilization system of claim **47** wherein the second anchor member further comprises:

a pedicle screw body; a housing receiving the end portion of the rigid element and defining a socket having internal threads; and

a set screw threadably engaging the socket to retain the fastener in the installed position.

**49.** The spinal stabilization system of claim **47**, further comprising:

a hand press adapted to advance the fastener from the initial position to the installed position.

**50.** The spinal stabilization system of claim **47** wherein the fastener is a pin secured within the opening on the outer surface of the rigid element by an interference fit.

**51.** The spinal stabilization system of claim **47** wherein the rigid element further includes a protrusion within the axial bore at a location substantially aligned with the second opening.

**52.** The spinal stabilization system of claim **47** wherein the flexible element is a cord constructed from braided polymer fibers.

**53.** The spinal stabilization system of claim **47** wherein the rigid element is a metal rod.

**54.** A spinal stabilization system, comprising:

first and second anchor members configured to be secured to first and second vertebrae within a patient's body, respectively, the second anchor member including a

pedicle screw body, a housing having opposed first and second tabs extending upwardly therefrom, and a set screw, the first and second tabs and the housing each having internal threads;

a flexible element secured to the first anchor member and having an end portion;

a rigid element secured to the second anchor member and having an end portion with an end surface, an axial bore extending from the end surface, an outer surface, and an opening on the outer surface extending into the axial bore, the axial bore receiving the end portion of the flexible element; and

a fastener extending through the opening in the outer surface of the rigid element to retain the flexible element in the axial bore;

wherein the set screw engages the internal threads of the first and second tabs and the housing and drives the fastener into the axial bore.

**55.** The spinal stabilization system of claim **54** wherein the first and second tabs are separable from the housing.

**56.** The spinal stabilization system of claim **54** wherein the faster and the set screw are integrally formed.

**57.** The spinal stabilization system of claim **54** wherein the rigid element further includes a protrusion within the axial bore at a location substantially aligned with the second opening.

**58.** The spinal stabilization system of claim **54** wherein the flexible element is a cord formed from braided polymer fibers.

**59.** The spinal stabilization system of claim **54** wherein the rigid element is a metal rod.

\* \* \* \* \*

专利名称(译)	脊柱稳定系统，具有刚性和柔性元件		
公开(公告)号	<a href="#">US20080234744A1</a>	公开(公告)日	2008-09-25
申请号	US11/688961	申请日	2007-03-21
[标]申请(专利权)人(译)	ZYLBER EMMANUEL EGLI THOMAS THOMPSON ROSEMARY FROEHLICH MARKUS 奇切尔基亚GIUSEPPE DANT插孔的 VIKER THOMASØ LEY凯文 - [R		
申请(专利权)人(译)	ZYLBER EMMANUEL EGLI THOMAS THOMPSON ROSEMARY FROEHLICH MARKUS 奇切尔基亚GIUSEPPE DANT插孔的 VIKER THOMASØ LEY凯文 - [R		
当前申请(专利权)人(译)	ZYLBER EMMANUEL EGLI THOMAS THOMPSON ROSEMARY FROEHLICH MARKUS 奇切尔基亚GIUSEPPE DANT插孔的 VIKER THOMASØ LEY凯文 - [R		
[标]发明人	ZYLBER EMMANUEL EGLI THOMAS THOMPSON ROSEMARY FROEHLICH MARKUS CICERCHIA GIUSEPPE DANT JACK A VIKER THOMAS O LEY KEVIN R		
发明人	ZYLBER, EMMANUEL EGLI, THOMAS THOMPSON, ROSEMARY FROEHLICH, MARKUS CICERCHIA, GIUSEPPE DANT, JACK A. VIKER, THOMAS O. LEY, KEVIN R.		
IPC分类号	A61B17/70 A61B17/58 A61B17/04		
CPC分类号	A61B17/7005 A61B17/7008 A61B17/705 A61B17/7031 A61B17/7022 A61B17/7004 A61B17/7019 A61B17/7032 A61B17/7034		

## 摘要(译)

脊柱稳定系统通常包括第一和第二锚固构件，其构造成固定到患者体内的第一和第二椎骨，固定到第一锚固构件的柔性元件，以及固定到第二锚固构件的刚性元件。刚性元件的端部连接到柔性元件的端部，使得系统能够提供刚性和动态稳定性。即使柔性元件在患者体内一段时间后松弛，也能保持耦合。

