





US 20120283761A1

(19) **United States**(12) **Patent Application Publication**  
**Rosenthal et al.**(10) **Pub. No.: US 2012/0283761 A1**(43) **Pub. Date: Nov. 8, 2012**(54) **METHODS AND DEVICES FOR CUTTING  
TISSUE AT A VASCULAR LOCATION**continuation-in-part of application No. 10/421,980,  
filed on Apr. 22, 2003, now abandoned.(75) Inventors: **Mike Rosenthal**, San Carlos, CA  
(US); **Himanshu Patel**, San Jose,  
CA (US)**Publication Classification**(51) **Int. Cl.**  
**A61B 17/22** (2006.01)(73) Assignee: **TYCO HEALTHCARE GROUP  
LP**, MANSFIELD, MA (US)(52) **U.S. Cl.** ..... **606/159**(21) Appl. No.: **13/551,123**(57) **ABSTRACT**(22) Filed: **Jul. 17, 2012**

A tissue cutting device includes a sizing element which detects the diameter of the vessel in which the cutting device is positioned. The sizing element is coupled to the cutting element so that the amount of the cutting element that is exposed varies in response to movement of the sizing element.

**Related U.S. Application Data**(63) Continuation of application No. 11/437,849, filed on  
May 18, 2006, now Pat. No. 8,246,640, which is a






FIG. 2




FIG. 3




FIG. 4












FIG. 5










FIG. 14




FIG. 15






FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23

## METHODS AND DEVICES FOR CUTTING TISSUE AT A VASCULAR LOCATION

### CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. application Ser. No. 11/437,849, filed May 18, 2006, which is a continuation-in-part of U.S. application Ser. No. 10/421,980, filed Apr. 22, 2003, the contents of each of which are hereby incorporated by reference herein.

### BACKGROUND OF THE INVENTION

[0002] The present invention is directed to devices and methods for cutting tissue. In a specific application, the present invention is directed to devices and methods for re-entering the true lumen from a subintimal space such as a dissection plane or so-called "false lumen."

[0003] Guidewires and other interventional devices are used to treat vessels and organs using endovascular approaches. A guidewire is typically guided through blood vessels to the treatment site and the device is then advanced over the guidewire. For example, angioplasty and stenting are generally accomplished by first introducing a guidewire to the desired site and then advancing the angioplasty or stent catheter over the guidewire.

[0004] When attempting to advance a guidewire or other interventional device through a highly stenosed region or chronic total occlusion (CTO), the guidewire or device may inadvertently enter into the wall of the vessel to create a sub-intimal space. Once in a subintimal space, it can be difficult to re-enter the vessel true lumen. Devices for reentering a vessel true lumen from a subintimal location are described in WO 02/45598 which is hereby incorporated by reference.

### BRIEF SUMMARY OF THE INVENTION

[0005] Various aspects of the invention are directed to methods and devices for re-entering a lumen during an endovascular procedure. In one embodiment, the device has a cutter, an opening, and an energy emitter coupled to the cutter. The device is advanced into the subintimal space and energy is then emitted from the energy emitter to locate the true lumen. In one aspect, the energy emitter and cutting element are moved together which exposes the cutting element to cut an access path into the true lumen. In another aspect of the present invention, the device may have a bendable tip which is bent while cutting tissue to create the access path or may be bent to direct the device or a guidewire through the access path.

[0006] In another aspect of the present invention, the device has a rotatable cutting element which may be moved from a stored position to a cutting position which exposes over 180 degrees, and even 220 or even 270 degrees of the cutting element relative to the axis of rotation. In another aspect of the invention, the cutter may be gradually exposed as necessary. In still another aspect of the present invention, the body of device may be wider along a portion of the device to urge tissue toward the cutting element. The opening is relatively large and may be open at the distal end and may expose at least part of the cutter at all positions distal to the opening. The open end of the device permits the tissue to naturally move toward the cutter due to the generally open nature of the distal end.

[0007] In still another aspect of the present invention, a system for accessing a subintimal space includes a catheter through which the tissue cutting device is advanced. The catheter may be coupled to a fluid source to inject contrast or the like and may also be coupled to a pressure monitor for monitoring pressure to determine when the access path has been created as described in greater detail below.

[0008] In a still further aspect of the invention, a method of entering a true lumen from a false lumen during an endovascular procedure is provided. A guidewire is positioned in the subintimal space. A reentry device is then advanced over the guidewire to the target location in the subintimal space. The access path is then created using the reentry device to cut the access path. The same guidewire is then directed through the access path. The reentry device may have two different openings with the first being used during advancement of the reentry device and a second opening through which the guidewire extends when being directed through the access path. The first opening may be configured to direct the guidewire substantially longitudinal while the second opening directs the guidewire at an angle relative to the longitudinal axis.

[0009] The present invention is also directed to a device for cutting tissue which automatically adjusts the position of the tissue cutting element in response to changes in vessel size. The device has a sizer coupled to the body which moves in response changes in vessel size. The sizer is coupled to the tissue cutting element so that the tissue cutting element changes position relative to the body when the vessel size changes. When the vessel size decreases, the tissue cutting element is moved to expose more of the cutting element. When the vessel size increases, the cutting element is moved to expose less of the cutting element. The term vessel size as used herein is used to generally describe a lateral dimension of the vessel.

[0010] These and other aspects of the invention will become apparent from the following description, drawings and claims.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] FIG. 1 shows a view of the system of the present invention.

[0012] FIG. 2 shows a guidewire positioned proximate to a total occlusion.

[0013] FIG. 3 shows a subintimal space created adjacent a true lumen by the guidewire.

[0014] FIG. 4 shows a reentry device of the present invention advanced over the guidewire to the subintimal space.

[0015] FIG. 5 shows a guidewire positioned in the true lumen.

[0016] FIG. 6 shows the reentry device with the cutting element in a stored position.

[0017] FIG. 7 shows the reentry device with the cutting element in a cutting position.

[0018] FIG. 8 is a side view of the reentry device of FIG. 7.

[0019] FIG. 9 shows another reentry device with the cutting element in a stored position.

[0020] FIG. 10 shows the reentry device of FIG. 9 with the cutting element in a cutting position and the distal portion bent.

[0021] FIG. 11 shows the reentry device of FIGS. 9 and 10 with the cutting element advanced to another cutting position which exposes even more of the cutting element and also bends the distal tip further.

[0022] FIG. 12 shows another reentry device which has a bendable distal portion.

[0023] FIG. 13 shows the reentry device of FIG. 12 with the distal portion bent.

[0024] FIG. 14 shows still another reentry device with a cutting element which may be tilted.

[0025] FIG. 15 shows the reentry device of FIG. 14 with the cutting element tilted to expose more of the cutting element and to move the cutting element through the opening in the body of the device.

[0026] FIG. 16 shows the reentry device of FIG. 6 having a junction leading to two separate guidewire outlets with the guidewire positioned in the first outlet during advancement of the device over the guidewire.

[0027] FIG. 17 shows the reentry device of FIG. 16 with the guidewire extending through the second outlet for directing the guidewire into the true lumen.

[0028] FIG. 18 shows a catheter having a lumen for receiving a guidewire and another lumen which receives the reentry device.

[0029] FIG. 19 shows another catheter having a single lumen through which the guidewire and reentry device pass.

[0030] FIG. 20 shows an external view of another device for cutting tissue having a sizer.

[0031] FIG. 21 shows another external view of the device of FIG. 20.

[0032] FIG. 22 is a cross-sectional view of the device of FIGS. 20 and 21.

[0033] FIG. 23 is a cross-sectional view of the device of FIGS. 20 and 21 with the sizer moved inward.

#### DETAILED DESCRIPTION OF THE INVENTION

[0034] Referring to FIGS. 1-8, a system 2 and device 4 for reentering a true lumen from a subintimal space, dissection plane or so-called false lumen is shown. The device 4 includes a cutting element 6 coupled to a torque transmitting element 8, such as a wire 10, which rotates the cutting element 6. The device 4 has an opening 12 at a distal end 14 with the cutting element 6 movable between a stored position (FIG. 6) and a cutting position (FIGS. 7 and 8) which exposes the cutting element 6. The cutting element 6 may be any suitable cutting element 6 such as the cutting element 6 described in patents incorporated by reference above. The cutting element 6 has a circular cutting edge which has a diameter of about 1 mm although any suitable size may be used depending upon the particular application. The cutting element 6 may also be any other type of cutter such as a laser, ultrasound, RF or other type of cutter without departing from various aspects of the present invention.

[0035] The device 4 has a flexible body 16 to navigate through blood vessels or other body lumens to a target location. The body 16 may be made of any suitable material as is known in the art such as Pebax. The torque transmitting element 8 extends through a lumen 18 in the body 16. The body 16 may have more lumens for various reasons such as introduction of fluids, such as contrast, or for delivery of another device 4 such as a guidewire or interventional device. The torque transmitting element 8 is coupled to a driver 20 which rotates the torque transmitting element 8 at a variable or fixed speed.

[0036] The device 4 may also have an energy emitting element 22, such as an ultrasound element 25, which emits (and may receive) energy to determine the location of the true lumen as explained below. The energy emitting element 22 is

coupled to the cutting element 6 so that the energy emitting element 22 and cutting element 6 are rotated together. The cutting element 6 is in the stored position when locating the true lumen so that the cutting element 6 is not exposed and will not cut or damage tissue. The energy emitting element 22 is positioned adjacent a window 24 which may be a side opening 26 or may simply be a portion of the sidewall which transmits a sufficient amount of the energy therethrough. Any suitable energy emitting element 22 may be used such as the ultrasound emitting element available from Boston Scientific and is marketed under the name Atlantis™. The cutting element 6 may be mounted to a collar which is then mounted to an ultrasound element holder 28 or the cutting element 6 may be integrally formed with the ultrasound element holder 28.

[0037] The device 4 has an atraumatic tip 34 which is relatively flexible to prevent damaging tissue. The tip 34 may be a separate piece laminated or glued to the body 16. The tip 34 is preferably made out of a relatively soft, flexible material, such as teflon, and may be used for blunt dissection as necessary. A reinforcing element 36 is encapsulated in the tip 34 to help the tip 34 maintain its general shape. The tip 34 may also have one or more guidewire lumens 38 or any of the guidewire features described herein.

[0038] The opening 12 in the distal portion may be designed to expose over 180 degrees of the cutting element 6 and may even expose 220 degrees or even 270 degrees of the cutting element 6 as defined by the axis of rotation. This provides advantages over WO 02/45598 which does not expose much of the cutting element 6 and requires invagination of the tissue within the opening to cut tissue. In another aspect of the invention, the cutting element 6 may be gradually exposed. For example, the cutting element 6 may be gradually exposed from 180-220 degrees or even 200-270 degrees. As explained below, this feature provides the user with the ability to change the amount of cutter 6 that is exposed depending upon the tissue thickness between the subintimal location and true lumen. The term opening 12 and amount of exposure of the cutting element 6 are defined by the outer bounds of the opening 12 and the axis of rotation. Referring to FIGS. 7 and 8, the cutting element 6 is exposed relative to the outer bounds of the opening 12 due to the relatively open distal end.

[0039] Referring to FIGS. 9-11, another device 4A for reentering a true lumen from a subintimal location is shown wherein the same or similar reference numbers refer to the same or similar structure. The device 4A also has an opening 12A at the distal end to expose the cutting element 6A. FIG. 9 shows the cutting element 6A in a stored position, FIG. 10 shows the cutting element 6A in a first cutting position and FIG. 11 shows the cutting element 6A in a second cutting position which further exposes the element 6A. The device 4A also has the window 24 through which the energy emitting element 22, such as the ultrasound element, may emit energy when the cutting element 6A is in the stored position.

[0040] A distal portion 40 of the body can bend or articulate to further expose the cutting element 6A and to move the cutting element 6A toward true lumen. The body has slots 42 formed therein to increase the flexibility of the distal portion 40. The cutting element 6A has a surface 44 which engages a lip 46 on the body. As the cutting element 6A is advanced, the interaction between the surface 44 and lip 46 causes the distal portion 40 to deflect. Bending the distal portion 40 can be helpful in moving the cutting element 6A toward the tissue and may also expose more of the cutting element 6A. As also

explained below, the tip **40** may also be bent to direct the device **4A** itself or a guidewire into the true lumen. The cutting element **6A** may also be gradually exposed as the cutting element **6A** moves distally and may be gradually exposed in the same manner described above.

[0041] Referring to FIGS. **12** and **13**, another reentry device **4B** is shown which has a distal portion or tip **60** which bends or articulates. The tip **60** may be articulated and actuated in any suitable manner. For example, the tip **60** may be bent upon longitudinal movement of the cutting element **6** (as shown above) or a separate actuator, such as a pull wire **62**, may be used. As can be appreciated from FIG. **13**, the tip **60** is bent or articulated to move the cutting element **6** toward the true lumen and to expose more of the cutting element **6**. The device **4B** may also be bent to direct the device **4B** itself or another device or guidewire through the guidewire lumen **38** to the access path into the true lumen as described further below.

[0042] Referring to FIGS. **14** and **15**, still another device **4C** for cutting tissue is shown wherein the same or similar numbers refer to the same or similar structure. The device **4C** includes a cutting element **6C**, an energy emitting element **22C** and a torque transmitter **8C** for rotating the elements. The device **4C** has an opening **64** along one side. The cutting element **6C** is contained within the opening **64** in the stored position of FIG. **14** and extends out of the opening **64** in the cutting position of FIG. **15**. The cutting element **6C** is moved out of the window **24** using an actuator **68**, such as a wire **70**, which tilts a bearing **72** supporting the shaft of the rotatable cutting element **6C**. Of course, any other suitable structure may be used to move the cutting element **6C** outside the opening **64** such as those described in U.S. Pat. No. 6,447,525 which is hereby incorporated by reference. Furthermore, the cutting element **6C** may be moved out of the opening **64** by bending the distal portion or tip as described herein.

[0043] Use of the devices **4**, **4A-C** is now described with reference to the device **4** although it is understood that any of the devices **4**, **4A-C** may be used. As mentioned above, the device **4** may be used to perform any suitable procedure to cut from one location to another in the body such as a procedure to reenter a true lumen. The device **4** is initially advanced to a position within a subintimal space **SS**. As described above, the subintimal space **SS** may be inadvertently created during an endovascular procedure with a guidewire **GW** or other device creating the subintimal space **SS** as shown in FIGS. **2** and **3**. The device **4** may be introduced over the same guidewire **GW** or device which created the subintimal space **SS** as shown in FIGS. **4** and **5**. Of course, the device **4** may also be advanced over the guidewire **GW** to a position proximate to the subintimal space **SS** after which the device **4** is then advanced by itself into the subintimal space **SS**.

[0044] After the device **4** is positioned at the appropriate location in the subintimal space **SS**, the energy emitting element **22** is used to determine the location of the true lumen. When using the ultrasound element **28**, for example, the ultrasound element **28** is rotated while emitting ultrasound energy and the energy emitted through the window **24** and reflected back through the window **24** is processed as is known in the art. The entire device **4** is rotated within the subintimal space **SS** to orient the window **24** until the true lumen is located. The angular orientation of the device **4** is then maintained so that the opening **12** and window **24** are directed toward the true lumen.

[0045] The cutting element **6** is then moved to the cutting position to expose the cutting element **6**. The cutting element **6** may be rotated with the driver **20** during this time so that cutting is initiated as the cutting element **6** is exposed. In another aspect of the invention, the entire device **4** itself may be moved through the subintimal space to cut tissue. This provides advantages over the method of WO 02/45598 which requires invagination of tissue through a window to attempt a cut at one location. If the tissue does not invaginate sufficiently into the window, such as when the tissue is too thick, the device of WO 02/45598 will not be able to cut completely through the tissue to create the access path to the true lumen. The user must then move the device and again attempt to invaginate enough tissue to cut an access path. The present invention provides the ability to move the entire device **4** through the subintimal space to create the access path rather than attempting a cut at a single discrete location as in WO 02/45598. Of course, the device **4** may also be used by moving only the cutting element **6** rather than the entire device **4** without departing from the invention.

[0046] The cutting element **6** may also be exposed to varying degrees, as described above, until enough of the cutting element **6** is exposed to cut through to the true lumen. For example, the user may choose to expose half of the cutting element **6** and attempt to create an access path to the true lumen. If an access path is not created, the user may then choose to expose more of the cutting element **6** and again attempt to create an access path. This procedure can be repeated until the access path is formed to the true lumen. The device **4A**, **4B** may also have a distal tip or portion **40**, **60** which bends to move the cutting element **6** toward the tissue and/or expose more of the cutting element **6** during cutting.

[0047] After successfully creating the access path into the true lumen, the device **4** itself or part thereof may be directed toward or through the access path. Referring to FIG. **9-13**, for example, the distal portion or tip **40**, **60** may be bent to help direct the device **4A**, **4B** itself or the guidewire **GW** through the access path.

[0048] Referring to FIGS. **16** and **17**, another device **4D**, similar to device **4**, is shown which has a guidewire lumen **74** having a junction **76** so the guidewire can be directed through either a first lumen **77** having a first outlet **78** or a second lumen **79** having a second outlet **80**. The first outlet **78** directs the guidewire substantially longitudinally for advancing the device **4D** over the guidewire to the target area in a conventional manner. The second outlet **80** directs the guidewire at an angle relative to the longitudinal axis, such as 30-75 degrees, to direct the guidewire through the access path into the true lumen.

[0049] The junction **76** may include a feature which directs the guidewire into the second outlet **80**. Referring to FIG. **17**, for example, the junction **76** may include a flap or stop **82** which closes and prevents or inhibits the guidewire from passing through the first outlet **78** after the guidewire has been withdrawn proximal to the junction **76**. When the guidewire is advanced again as shown in FIG. **17**, the guidewire passes through the second outlet **80** due to the stop **82**. The device **4** and/or guidewire **GW** are then manipulated to direct the guidewire **GW** through the access path. Although the stop **82** may be provided, the junction **76** may also simply be a relatively open junction **76** with the user manipulating and rotating the guidewire **GW** to direct the guidewire **GW** through the

desired outlet **78, 80**. The device is rotated about 180 degrees after creating the access path to direct the GW through outlet **80** and into the true lumen.

**[0050]** Referring to FIGS. **18** and **19**, the system **2** may also include a sheath or catheter **90** which is advanced proximal to the treatment site. The sheath **90** may help provide better control of the guidewire GW and devices **4** of the present invention during manipulation in the subintimal space. The sheath **90** may also be used to deliver contrast solution to the treatment site from a source of contrast **97** (see FIG. **1**) or may be coupled to a pressure sensor **94**. The pressure sensor **94** may be part of the contrast delivery system **97** or may be a separate component. Delivery of contrast and/or pressure monitoring may be used to determine when the access path has been created.

**[0051]** The sheath **90** may include only one lumen **92** with fluid delivery and pressure sensing being accomplished in the annular space between the device and sheath as shown in FIG. **19**. The sheath **90** may also have first and second lumens **96, 98** for separate delivery of the device **4** and guidewire GW. As mentioned above, the devices **4** of the present invention may be advanced over the same guidewire or device that created the subintimal space or may be advanced over another guidewire or even through the sheath **90** by itself.

**[0052]** After accessing the true lumen, another interventional device may be introduced into the true lumen for the intended therapy or procedure. For example, a stent catheter, angioplasty catheter, or atherectomy device may be used to treat the occlusion. The present invention has been described for reentering a true lumen from a subintimal space but, of course, may be used for other purposes to gain access from one space to another anywhere within the body.

**[0053]** Referring to FIGS. **20-23**, another device **100** for cutting tissue is shown wherein the same or similar reference numbers refer to the same or similar structure. The device **100** includes an elongate body **116** and a cutting element **106** coupled to a drive element **108** which is rotated to drive the cutting element **106**. The drive element **108** extends through a lumen **118** in the body **116** and is driven by a driver (not shown) at the proximal end. The cutting element **106** may be any suitable cutting element **106** including those described in the applications incorporated herein. The cutting element **106** has an essentially circular cutting surface **107** along the leading edge of the cutting element **106**.

**[0054]** The body **116** has an opening **112** therein and the tissue cutter **106** is movable from the stored position of FIGS. **20** and **22** to the cutting position of FIG. **23**. When moved to the cutting position of FIG. **23**, part of the tissue cutting element **106** becomes exposed relative to opening **112**. The opening **112** may be a side opening as shown in FIGS. **20-23** or may be a distal opening as shown in other devices described herein such as the devices of FIGS. **1-19**. The tissue cutting element **106** moves relative to the body **116** so that a cutting height **117** of the tissue cutting element **106** changes as the position of the cutting element changes relative to the body **116**. The cutting height **117** is defined by a maximum distance from the cutting surface **107** to an outer surface **109** of the body **116**.

**[0055]** The device **100** has a sizer **119** coupled to the body **116** which automatically adjusts the cutting height **117** based on vessel size. The sizer **119** is naturally biased to an outer position of FIG. **22** by a spring **122** which defines a maximum width of the device along the sizer **119**. The sizer **119** is moved inward from the position of FIG. **22** when contact with

the vessel wall overcomes the force biasing the sizer **119** outward. In simplistic terms, the sizer **119** is essentially moved inward by the vessel wall when the vessel size is smaller than the width of the device **100**. Thus, the sizer **119** moves between the positions of FIGS. **22** and **23** as the diameter of the vessel varies within a given range. When the vessel diameter is larger than the diameter of the device **100**, the tissue cutting element **106** will remain in the stored position of FIG. **22**. Stated another way, the sizer **119** is coupled to the tissue cutting element **106** so that an outward force is applied to the tissue cutting element **106** when the sizer **119** moves inward. The outward force on the tissue cutting element **106** being directed away from the body **116**.

**[0056]** The sizer **119** is coupled to the tissue cutting element **106** so that the amount of exposure of the cutting element, such as the cutter height **117**, changes when the vessel diameter changes. In the embodiment of FIG. **16**, the exposure of the tissue cutting element **106** is increased when the vessel diameter decreases so that a deeper cut is made in smaller vessels. A deeper cut may be desired when removing tissue in smaller vessels to increase the flow of blood through the vessel. The user may still move the tissue cutting element **106** to the cutting position of FIG. **23** by pulling on the drive element **108** so that a contact surface **123** on the sizer **119** engages a ramp **126** on an inner wall **128** of the body **116** to move the cutting element **106** to the position of FIG. **23**.

**[0057]** The tissue cutting device **100** may be used to cut tissue for any purpose. Furthermore, the device **100** has been described in connection with cutting tissue in blood vessels but may be used for any other purpose in the vasculature. The tissue may be cut and left within the body or may be removed in any suitable manner. For example, the device **100** may include a tissue collection chamber **130** coupled to the body **116** distal to the cutting element **106**. The tissue cutting element **106** cuts tissue and directs the tissue into the collection chamber **130**. The tissue cut by the tissue cutting element **106** is parted off from the surrounding tissue by moving the cutting element **106** back to the stored position.

**[0058]** The present invention has been described in connection with the preferred embodiments, however, it is understood that numerous alternatives and modifications can be made within the scope of the present invention as defined by the claims.

What is claimed is:

1. A device for re-entering a lumen during an endovascular procedure when in a subintimal space, comprising:

- an elongate body having first and second lumens, a distal end of the first lumen opening from the body at a first opening, a distal end of the second lumen opening from the body at a second opening, the second lumen being sized to receive a guidewire;
  - a window in the body between the first lumen and an exterior of the body, the window being spaced from the first opening;
  - a rotating cutter extending within the first lumen used for cutting tissue; and
  - an energy emitter which emits energy through the window to locate a lumen when in a subintimal space adjacent to the lumen;
- the cutter being movable to a cutting position which exposes part of the cutter through the first opening so that the cutter may create a path from the subintimal space to the lumen.



2. The device of claim 1, wherein:

the energy emitter is coupled to the cutter, the cutter and energy emitter being coupled to a torque transmitting element which rotates the cutter and the energy emitter together.

3. The device of claim 1, wherein:

the cutting element may be gradually exposed so that the amount of exposure may be varied in the cutting position.

4. The device of claim 1, wherein:

the cutting element is exposed over 180 degrees relative to an axis of rotation when in the cutting position.

5. The device of claim 1, wherein:

the cutting element is exposed over 270 degrees relative to the axis of rotation when in the cutting position.

6. The device of claim 1, wherein:

the elongate body has a distal portion which bends when the elongate body is moved to cut tissue with the cutter.

7. The device for re-entering a lumen during an endovascular procedure of claim 1, wherein:

the energy emitter is an ultrasound emitting element.

8. The device of claim 1, wherein:

the elongate body is wider along a portion adjacent to the cutting element to urge tissue toward the cutting element.

9. The device of claim 1, wherein:

the elongate body is moved within the subintimal space to move the cutter when the cutter creates the path back into the lumen.

10. The device of claim 1 wherein:

the window comprises a third opening in a sidewall of the elongate body.

11. The device of claim 1 wherein:

the first opening is at a distal end of the elongate body.

12. The device of claim 1 wherein:

the first opening is distal of the window.

\* \* \* \* \*

专利名称(译)	用于在血管位置切割组织的方法和装置		
公开(公告)号	<a href="#">US20120283761A1</a>	公开(公告)日	2012-11-08
申请号	US13/551123	申请日	2012-07-17
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	泰科医疗集团LP		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	ROSENTHAL MIKE PATEL HIMANSHU		
发明人	ROSENTHAL, MIKE PATEL, HIMANSHU		
IPC分类号	A61B17/22 A61B		
CPC分类号	A61B17/3207 A61B2017/22077 A61B2017/22095 A61B2017/320791 A61B2017/00292 A61B2017/00296 A61B2017/320766 A61B2017/0034 A61B2017/00778 A61B2017/22039 A61B2017/2927 A61B2017/320052 A61B2017/00309 A61B17/320758 A61B17/00234 A61B17/22 A61B17/320783		
其他公开文献	US8961546		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

组织切割装置包括定尺寸元件，该定尺寸元件检测切割装置所在的容器的直径。尺寸调整元件连接到切割元件，使得暴露的切割元件的量响应于尺寸调整元件的移动而变化。

