



US 20170360370A1

(19) **United States**

(12) **Patent Application Publication**  
**BURKETT**

(10) **Pub. No.: US 2017/0360370 A1**

(43) **Pub. Date: Dec. 21, 2017**

(54) **INTRAVASCULAR DEVICES, SYSTEMS, AND METHODS**

*A61B 5/0215* (2006.01)

*A61B 8/12* (2006.01)

*A61M 25/00* (2006.01)

(71) Applicant: **VOLCANO CORPORATION, SAN DIEGO, CA (US)**

(52) **U.S. Cl.**

CPC ..... *A61B 5/6851* (2013.01); *A61M 25/09*

(2013.01); *A61M 2025/09083* (2013.01);

*A61M 2025/0002* (2013.01); *Y10T 29/49826*

(2015.01); *A61B 8/12* (2013.01); *A61B 5/0215*

(2013.01); *A61M 2025/09175* (2013.01)

(72) Inventor: **DAVID H. BURKETT, PANAMA CITY BEACH, FL (US)**

(21) Appl. No.: **15/693,894**

(22) Filed: **Sep. 1, 2017**

(57) **ABSTRACT**

**Related U.S. Application Data**

(63) Continuation of application No. 15/167,568, filed on May 27, 2016, now Pat. No. 9,750,458, which is a continuation of application No. 13/931,052, filed on Jun. 28, 2013, now Pat. No. 9,351,687.

(60) Provisional application No. 61/665,697, filed on Jun. 28, 2012.


Intravascular devices, systems, and methods are disclosed. In some embodiments, the intravascular devices include at least one electronic, optical, or electro-optical component positioned within a distal portion of the device and one or more connectors positioned at a distal portion of the device. In some instances, the connectors are flexible coils, such as a ribbon coil, formed of a conductive material. In some particular instances, the conductive coil is embedded within a polymer tubing. Further, in some embodiments the electronic, optical, or electro-optical component is positioned within a flexible element at the distal portion of the device. In some instances the flexible element is a coil. Methods of making and/or assembling such intravascular devices/systems are also provided.

**Publication Classification**

(51) **Int. Cl.**

*A61B 5/00* (2006.01)

*A61M 25/09* (2006.01)






Fig. 1




Fig. 3




Fig. 2




Fig. 5




Fig. 4




Fig. 6




Fig. 9




Fig. 10




Fig. 7




Fig. 8




Fig. 11




Fig. 12



Fig. 13




Fig. 14




Fig. 15




Fig. 16

## INTRAVASCULAR DEVICES, SYSTEMS, AND METHODS

### CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation of U.S. application Ser. No. 15/167,568, filed May 27, 2016, now U.S. Pat. No. 9,750,458, which is a continuation of U.S. application Ser. No. 13/931,052, filed Jun. 28, 2013, now U.S. Pat. No. 9,351,687, which claims priority to and the benefit of U.S. Provisional Patent Application No. 61/665,697, filed Jun. 28, 2012, which are hereby incorporated by reference herein in their entireties.

### TECHNICAL FIELD

[0002] The present disclosure relates to intravascular devices, systems, and methods. In some embodiments, the intravascular devices are guidewires that include one or more electronic, optical, or electro-optical components.

### BACKGROUND

[0003] Heart disease is very serious and often requires emergency operations to save lives. A main cause of heart disease is the accumulation of plaque inside the blood vessels, which eventually occludes the blood vessels. Common treatment options available to open up the occluded vessel include balloon angioplasty, rotational atherectomy, and intravascular stents. Traditionally, surgeons have relied on X-ray fluoroscopic images that are planar images showing the external shape of the silhouette of the lumen of blood vessels to guide treatment. Unfortunately, with X-ray fluoroscopic images, there is a great deal of uncertainty about the exact extent and orientation of the stenosis responsible for the occlusion, making it difficult to find the exact location of the stenosis. In addition, though it is known that restenosis can occur at the same place, it is difficult to check the condition inside the vessels after surgery with X-ray.

[0004] A currently accepted technique for assessing the severity of a stenosis in a blood vessel, including ischemia causing lesions, is fractional flow reserve (FFR). FFR is a calculation of the ratio of a distal pressure measurement (taken on the distal side of the stenosis) relative to a proximal pressure measurement (taken on the proximal side of the stenosis). FFR provides an index of stenosis severity that allows determination as to whether the blockage limits blood flow within the vessel to an extent that treatment is required. The normal value of FFR in a healthy vessel is 1.00, while values less than about 0.80 are generally deemed significant and require treatment.

[0005] Often intravascular catheters and guidewires are utilized to measure the pressure within the blood vessel, visualize the inner lumen of the blood vessel, and/or otherwise obtain data related to the blood vessel. To date, guidewires containing pressure sensors, imaging elements, and/or other electronic, optical, or electro-optical components have suffered from reduced performance characteristics compared to standard guidewires that do not contain such components. For example, the handling performance of previous guidewires containing electronic components have been hampered, in some instances, by the limited space available for the core wire after accounting for the space needed for the conductors or communication lines of the electronic component(s), the stiffness of the rigid housing

containing the electronic component(s), and/or other limitations associated with providing the functionality of the electronic components in the limited space available within a guidewire. Further, due to its small diameter, in many instances the proximal connector portion of the guidewire (i.e., the connector(s) that facilitate communication between the electronic component(s) of the guidewire and an associated controller or processor) is fragile and prone to kinking, which can destroy the functionality of the guidewire. For this reason, surgeons are reluctant to remove the proximal connector from the guidewire during a procedure for fear of breaking the guidewire when reattaching the proximal connector. Having the guidewire coupled to the proximal connector further limits the maneuverability and handling of the guidewire.

[0006] Accordingly, there remains a need for improved intravascular devices, systems, and methods that include one or more electronic, optical, or electro-optical components.

### SUMMARY

[0007] Embodiments of the present disclosure are directed to intravascular devices, systems, and methods.

[0008] In one embodiment, a guidewire is provided. The guidewire comprises a first flexible element; a second flexible element coupled to the first flexible element in a position proximal to the first flexible element; a third flexible element coupled to the second flexible element in a position proximal to the second flexible element; a distal core extending within the first flexible element; a mounting structure positioned within the second flexible element and fixedly secured to the distal core, the mounting structure configured to have at least one component selected from the group of components consisting of an electronic component, an optical component, and an electro-optical component mounted thereto; at least one electronic, optical, or electro-optical component mounted to the mounting structure; a core fixedly attached to the mounting structure and extending proximally from the mounting structure through the second and third flexible elements; and at least one conductor having a proximal section and a distal section, wherein the distal section of the at least one conductor is coupled to the at least one electronic component and the proximal section of the at least one conductor is coupled to at least one connector; wherein the first, second, and third flexible elements have an outer diameter of 0.018" or less.

[0009] In some instances, the second flexible element comprises a ribbon coil. In that regard, the ribbon coil is embedded in a polymer tubing in some embodiments. The polymer tubing may have a thickness between about 0.0005" and about 0.003". In some embodiments, the core includes a first section that is fixedly attached to the mounting structure and a second section extending proximally from the first section, wherein the first section is formed of a first material and the second section is formed of a second material different than the first material. In some instances, the core further includes a third section extending proximally from the second section, wherein the third section is formed of a third material different than the second material. The third material is the same as the first material in some implementations. In some particular embodiments, the first material is a shape memory alloy, the second material is stainless steel, and the third material is a shape memory alloy.

[0010] In some embodiments, the at least one connector comprises a coil. In that regard, a wire forming the coil has a rectangular cross-sectional profile, a circular cross-sectional profile, a semi-circular cross-sectional profile with a rounded portion of the semi-circular cross-sectional profile extending outwardly, a semi-circular cross-sectional profile with a rounded portion of the semi-circular cross-sectional profile extending inwardly, and/or other suitable cross-sectional profile in some instances. In some embodiments, a section of the core positioned within the coil is formed of shape memory alloy, such as NiTiCo or Nitinol. In some instances, the proximal section of the at least one conductor is soldered to an inner portion of the coil. Sometimes, the coil is at least partially embedded within a polymer tubing. In some embodiments, an insulating layer is positioned between the coil and a proximal portion of the core.

[0011] In another embodiment, a method of assembling a guidewire is provided. The method includes providing a polymer tubing having a conductive coil embedded therein; removing a first portion of the polymer tubing to expose a first portion of the conductive coil; electrically coupling a proximal portion of a first conductor to the first portion of the conductive coil, wherein a distal portion of the first conductor is coupled to at least one component selected from the group of components consisting of an electronic component, an optical component, and an electro-optical component. In some instances, electrically coupling the proximal portion of the first conductor to the first portion of the conductive coil comprises soldering the first portion of the first conductor to the first portion of the conductive coil. In some embodiments, removing the first portion of the polymer tubing comprises laser ablating the polymer. In that regard, the polymer is ablated such that the first portion of the conductive coil extends between about 0.0001" and about 0.0005" above the polymer in some instances.

[0012] In some implementations, the method further includes removing a second portion of the polymer tubing to expose a second portion of the conductive coil; and electrically coupling a proximal portion of a second conductor to the second portion of the conductive coil, wherein a distal portion of the second conductor is coupled to at least one component selected from the group of components consisting of an electronic component, an optical component, and an electro-optical component. In that regard, the method may also include electrically isolating the first portion of the conductive coil from the second portion of the conductive coil. In some instances, electrically isolating the first portion of the conductive coil from the second portion of the conductive coil comprises forming an opening in a sidewall of the polymer tubing that severs a portion of the conductive coil positioned between the first and second portions of the conductive coil. The method may also include removing a third portion of the polymer tubing to expose a third portion of the conductive coil; electrically coupling a proximal portion of a third conductor to the third portion of the conductive coil, wherein a distal portion of the third conductor is coupled to at least one component selected from the group of components consisting of an electronic component, an optical component, and an electro-optical component; and electrically isolating each of the first, second, and third portions of the conductive coil from the other of the first, second, and third portions of the conductive coil. In that regard, electrically isolating each of the first, second, and third portions of the conductive coil from the other of the

first, second, and third portions of the conductive coil comprises forming openings in a sidewall of the polymer tubing to sever portions of the conductive coil positioned between each of the first, second, and third portions of the conductive coil in some instances. Further, the method may also include coupling the polymer tubing to a proximal portion of an intravascular device.

[0013] Additional aspects, features, and advantages of the present disclosure will become apparent from the following detailed description.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0014] Illustrative embodiments of the present disclosure will be described with reference to the accompanying drawings, of which:

[0015] FIG. 1 is a diagrammatic, schematic side view of an intravascular device according to an embodiment of the present disclosure.

[0016] FIG. 2 is a diagrammatic cross-sectional longitudinal view of an intravascular device according to an embodiment of the present disclosure.

[0017] FIG. 3 is a diagrammatic cross-sectional longitudinal view of an intravascular device similar to that of FIG. 2, but illustrating another embodiment of the present disclosure.

[0018] FIG. 4 is a diagrammatic cross-sectional longitudinal view of an intravascular device similar to that of FIGS. 2 and 3, but illustrating another embodiment of the present disclosure.

[0019] FIG. 5 is a diagrammatic cross-sectional longitudinal view of an intravascular device similar to that of FIGS. 2-4, but illustrating another embodiment of the present disclosure.

[0020] FIG. 6 is diagrammatic cross-sectional side view of an intravascular device according to an embodiment of the present disclosure.

[0021] FIG. 7 is a diagrammatic cross-sectional side view of a proximal connector portion of an intravascular device according to an embodiment of the present disclosure.

[0022] FIG. 8 is a diagrammatic cross-sectional side view of a proximal connector portion of an intravascular device similar to that of FIG. 7, but illustrating another embodiment of the present disclosure.

[0023] FIG. 9 is a diagrammatic cross-sectional side view of a proximal connector portion of an intravascular device similar to that of FIGS. 7 and 8, but illustrating another embodiment of the present disclosure.

[0024] FIG. 10 is a diagrammatic cross-sectional side view of a proximal connector portion of an intravascular device similar to that of FIGS. 7-9, but illustrating another embodiment of the present disclosure.

[0025] FIG. 11 is a diagrammatic cross-sectional close-up side view of a section of the proximal connector portion of an intravascular device of FIG. 7.

[0026] FIG. 12 is a diagrammatic side view of an element for forming a proximal connector portion of an intravascular device according to an embodiment of the present disclosure.

[0027] FIG. 13 is a diagrammatic side view of a proximal connector portion formed from the element of FIG. 12 according to an embodiment of the present disclosure.

[0028] FIG. 14 is a diagrammatic close-up side view of a conductor portion of the proximal connector portion of FIG. 13.

**[0029]** FIG. 15 is a diagrammatic close-up side view of an insulator portion of the proximal connector portion of FIG. 13.

**[0030]** FIG. 16 is a diagrammatic close-up, partial phantom perspective view of an insulator portion of the proximal connector portion of FIG. 13.

#### DETAILED DESCRIPTION

**[0031]** For the purposes of promoting an understanding of the principles of the present disclosure, reference will now be made to the embodiments illustrated in the drawings, and specific language will be used to describe the same. It is nevertheless understood that no limitation to the scope of the disclosure is intended. Any alterations and further modifications to the described devices, systems, and methods, and any further application of the principles of the present disclosure are fully contemplated and included within the present disclosure as would normally occur to one skilled in the art to which the disclosure relates. In particular, it is fully contemplated that the features, components, and/or steps described with respect to one embodiment may be combined with the features, components, and/or steps described with respect to other embodiments of the present disclosure. For the sake of brevity, however, the numerous iterations of these combinations will not be described separately.

**[0032]** As used herein, “flexible elongate member” or “elongate flexible member” includes at least any thin, long, flexible structure that can be inserted into the vasculature of a patient. While the illustrated embodiments of the “flexible elongate members” of the present disclosure have a cylindrical profile with a circular cross-sectional profile that defines an outer diameter of the flexible elongate member, in other instances all or a portion of the flexible elongate members may have other geometric cross-sectional profiles (e.g., oval, rectangular, square, elliptical, etc.) or non-geometric cross-sectional profiles. Flexible elongate members include, for example, guidewires and catheters. In that regard, catheters may or may not include a lumen extending along its length for receiving and/or guiding other instruments. If the catheter includes a lumen, the lumen may be centered or offset with respect to the cross-sectional profile of the device.

**[0033]** In most embodiments, the flexible elongate members of the present disclosure include one or more electronic, optical, or electro-optical components. For example, without limitation, a flexible elongate member may include one or more of the following types of components: a pressure sensor, a temperature sensor, an imaging element, an optical fiber, an ultrasound transducer, a reflector, a mirror, a prism, an ablation element, an RF electrode, a conductor, and/or combinations thereof. Generally, these components are configured to obtain data related to a vessel or other portion of the anatomy in which the flexible elongate member is disposed. Often the components are also configured to communicate the data to an external device for processing and/or display. In some aspects, embodiments of the present disclosure include imaging devices for imaging within the lumen of a vessel, including both medical and non-medical applications. However, some embodiments of the present disclosure are particularly suited for use in the context of human vasculature. Imaging of the intravascular space, particularly the interior walls of human vasculature can be accomplished by a number of different techniques, including ultrasound (often referred to as intravascular ultrasound

(“IVUS”) and intracardiac echocardiography (“ICE”)) and optical coherence tomography (“OCT”). In other instances, infrared, thermal, or other imaging modalities are utilized.

**[0034]** The electronic, optical, and/or electro-optical components of the present disclosure are often disposed within a distal portion of the flexible elongate member. As used herein, “distal portion” of the flexible elongate member includes any portion of the flexible elongate member from the mid-point to the distal tip. As flexible elongate members can be solid, some embodiments of the present disclosure will include a housing portion at the distal portion for receiving the electronic components. Such housing portions can be tubular structures attached to the distal portion of the elongate member. Some flexible elongate members are tubular and have one or more lumens in which the electronic components can be positioned within the distal portion.

**[0035]** The electronic, optical, and/or electro-optical components and the associated communication lines are sized and shaped to allow for the diameter of the flexible elongate member to be very small. For example, the outside diameter of the elongate member, such as a guidewire or catheter, containing one or more electronic, optical, and/or electro-optical components as described herein are between about 0.0007" (0.0178 mm) and about 0.118" (3.0 mm), with some particular embodiments having outer diameters of approximately 0.014" (0.3556 mm) and approximately 0.018" (0.4572 mm)). As such, the flexible elongate members incorporating the electronic, optical, and/or electro-optical component(s) of the present application are suitable for use in a wide variety of lumens within a human patient besides those that are part or immediately surround the heart, including veins and arteries of the extremities, renal arteries, blood vessels in and around the brain, and other lumens.

**[0036]** “Connected” and variations thereof as used herein includes direct connections, such as being glued or otherwise fastened directly to, on, within, etc. another element, as well as indirect connections where one or more elements are disposed between the connected elements.

**[0037]** “Secured” and variations thereof as used herein includes methods by which an element is directly secured to another element, such as being glued or otherwise fastened directly to, on, within, etc. another element, as well as indirect techniques of securing two elements together where one or more elements are disposed between the secured elements.

**[0038]** Referring now to FIG. 1, shown therein is a portion of an intravascular device 100 according to an embodiment of the present disclosure. In that regard, the intravascular device 100 includes a flexible elongate member 102 having a distal portion 104 adjacent a distal end 105 and a proximal portion 106 adjacent a proximal end 107. A component 108 is positioned within the distal portion 104 of the flexible elongate member 102 proximal of the distal tip 105. Generally, the component 108 is representative of one or more electronic, optical, or electro-optical components. In that regard, the component 108 is a pressure sensor, a temperature sensor, an imaging element, an optical fiber, an ultrasound transducer, a reflector, a mirror, a prism, an ablation element, an RF electrode, a conductor, and/or combinations thereof. The specific type of component or combination of components can be selected based on an intended use of the intravascular device. In some instances, the component 108 is positioned less than 10 cm, less than 5, or less than 3 cm from the distal tip 105. In some instances, the component

**108** is positioned within a housing of the flexible elongate member **102**. In that regard, the housing is a separate component secured to the flexible elongate member **102** in some instances. In other instances, the housing is integrally formed as a part of the flexible elongate member **102**.

[0039] The intravascular device **100** also includes a connector **110** adjacent the proximal portion **106** of the device. In that regard, the connector **110** is spaced from the proximal end **107** of the flexible elongate member **102** by a distance **112**. Generally, the distance **112** is between 0% and 50% of the total length of the flexible elongate member **102**. While the total length of the flexible elongate member can be any length, in some embodiments the total length is between about 1300 mm and about 4000 mm, with some specific embodiments have a length of 1400 mm, 1900 mm, and 3000 mm. Accordingly, in some instances the connector **110** is positioned at the proximal end **107**. In other instances, the connector **110** is spaced from the proximal end **107**. For example, in some instances the connector **110** is spaced from the proximal end **107** between about 0 mm and about 1400 mm. In some specific embodiments, the connector **110** is spaced from the proximal end by a distance of 0 mm, 300 mm, and 1400 mm.

[0040] The connector **110** is configured to facilitate communication between the intravascular device **100** and another device. More specifically, in some embodiments the connector **110** is configured to facilitate communication of data obtained by the component **108** to another device, such as a computing device or processor. Accordingly, in some embodiments the connector **110** is an electrical connector. In such instances, the connector **110** provides an electrical connection to one or more electrical conductors that extend along the length of the flexible elongate member **102** and are electrically coupled to the component **108**. Some specific embodiments of electrical connectors in accordance with the present disclosure are discussed below in the context of FIGS. 5-11. In other embodiments, the connector **110** is an optical connector. In such instances, the connector **110** provides an optical connection to one or more optical communication pathways (e.g., fiber optic cable) that extend along the length of the flexible elongate member **102** and are optically coupled to the component **108**. Further, in some embodiments the connector **110** provides both electrical and optical connections to both electrical conductor(s) and optical communication pathway(s) coupled to the component **108**. In that regard, it should again be noted that component **108** is comprised of a plurality of elements in some instances. In some instances, the connector **110** is configured to provide a physical connection to another device, either directly or indirectly. In other instances, the connector **110** is configured to facilitate wireless communication between the intravascular device **100** and another device. Generally, any current or future developed wireless protocol(s) may be utilized. In yet other instances, the connector **110** facilitates both physical and wireless connection to another device.

[0041] As noted above, in some instances the connector **110** provides a connection between the component **108** of the intravascular device **100** and an external device. Accordingly, in some embodiments one or more electrical conductors, one or more optical pathways, and/or combinations thereof extend along the length of the flexible elongate member **102** between the connector **110** and the component **108** to facilitate communication between the connector **110** and the component **108**. Generally, any number of electrical

conductors, optical pathways, and/or combinations thereof can extend along the length of the flexible elongate member **102** between the connector **110** and the component **108**. In some instances, between one and ten electrical conductors and/or optical pathways extend along the length of the flexible elongate member **102** between the connector **110** and the component **108**. For the sake of clarity and simplicity, the embodiments of the present disclosure described below include three electrical conductors. However, it is understood that the total number of communication pathways and/or the number of electrical conductors and/or optical pathways is different in other embodiments. More specifically, the number of communication pathways and the number of electrical conductors and optical pathways extending along the length of the flexible elongate member **102** is determined by the desired functionality of the component **108** and the corresponding elements that define component **108** to provide such functionality.

[0042] Referring now to FIGS. 2-5, shown therein are various cross-sectional profiles of intravascular devices of the present disclosure that illustrate techniques for extending communication pathways (e.g., electrical conductors and/or optical fibers) along the length of the device. In that regard, one of the major issues associated with existing functional guidewires is poor mechanical performance as compared to frontline guidewires. This performance loss is due in a large part to the typical design of the guidewires that severely limits the space available for the core or core wire due to the need to run the communication lines along the length of the device. As noted above, for the sake of clarity and simplicity, the embodiments of FIGS. 2-5 include three electrical conductors. More specifically, the embodiments of FIGS. 2-5 include three electrical conductors arranged as a trifilar. Existing trifilars are typically formed by three individual copper wires each wrapped with a color coded insulation material. A final overcoat is put over all three wires to connect them together as a single trifilar component.

[0043] Referring more specifically to FIG. 2, shown therein is a cross-sectional longitudinal view of an intravascular device **120** according to an embodiment of the present disclosure. The intravascular device **120** includes a main body **121** having an outer wall **122** defining an outer boundary of the intravascular device **120** and an inner wall **123** defining a lumen for receiving additional components of the intravascular device **120** that will be discussed in greater detail below. In the illustrated embodiment the main body **121** has a circular cross-sectional profile with an outer diameter **124**. Diameter **124** is between about 0.0007" (0.0178 mm) and about 0.118" (3.0 mm) in some embodiments, with some particular embodiments having an outer diameter of approximately 0.014" (0.3556 mm) or approximately 0.018" (0.4572 mm). In some embodiments, the main body **121** has a constant profile along all or a majority of its length. For example, where the main body **121** has a circular cross-sectional profile, as shown in FIG. 2, the various portions of the main body maintain a constant outer diameter along all or a majority of the length of the intravascular device **120**. In some embodiments, at the least the portions of the main body **121** that are intended to be disposed within the patient have a constant profile (or at least tapered/gradual transitions between portions with different outer profiles) to avoid potential injury to the patient while moving the intravascular device **120** through the patient. Further, it is recognized that the composition of the main

body **121** changes along the length of the intravascular device in some instances. For example, in some embodiments the main body **121** transitions between one or more of a hypotube, a coil, a balloon, a polymer sleeve, and/or other structures and combinations thereof. The main body **121** maintains a constant profile across the transitions in some instances. In some instances, the main body **121** includes a polymer tubing with a conductive coil embedded therein as discussed with respect to FIGS. **12-16** below.

**[0044]** The intravascular device **120** also includes a trifilar **125** disposed within the lumen of the main body **121** defined by the inner wall **123**. In that regard, the trifilar **125** consists of three electrical conductors or wires **126**, **127**, and **128**, which may be formed of any suitable conductive material including without limitation copper, copper alloys, silver, silver alloys, aluminum, and/or combinations thereof. Each of the wires **126**, **127**, and **128** is wrapped with an insulating layer **129**, **130**, and **131**, respectively. Any suitable insulating layer may be utilized, including without limitation polyimide, polyurethane, nylon, polyethylene, polypropylene, silicone rubber, fluoropolymers, and/or combinations thereof. In some embodiments, the insulating layers **129**, **130**, and **131** are color coded or otherwise include markings or identifiers to facilitate identification of the corresponding conductor **126**, **127**, and **128**. An overcoat layer **132** is formed over the three conductors **126**, **127**, and **128** and insulating layers **129**, **130**, and **131** to connect the conductors together as a single trifilar component **125**. Layer **132** is formed of an insulating material in some instances. For example, in some embodiments layer **132** is formed of one or more of polyurethane, polyethylene, polypropylene, silicone rubber, and/or combinations thereof. As shown, the trifilar **125** is positioned within the lumen **133** of the main body **121**. In some instances, lumen **133** is open space. In other instances, the lumen **133** is partially or completely filled with a material. For example, in some instances a portion of the lumen **133** is filled with an adhesive, such as polyurethanes, cyanoacrylates, acrylates, silicone, and/or combinations thereof, that is utilized to secure components of the intravascular device **120** together. Accordingly, in some instances, the material filling lumen **133** also surrounds a layer **134** and core wire **136**. In that regard, the layer **134** is formed of polyethylene terephthalate (PET) in some instances and may extend along all, a portion, or none of the length of the core wire **136** (i.e., layer **134** is omitted in some instances). In some embodiments, the layer **134** has a thickness between about 0.0001" (0.0025 mm) and about 0.0005" (0.0127 mm). In some embodiments, the layer **134** is intermittently used along the length of the core **136** as an insulator at certain joints and/or to hold the trifilar **125** to the core **136**.

**[0045]** As shown, the inner wall **123** of the main body **121** defines a lumen having a diameter **137**. The diameter **137** is dependent upon the outer diameter **124** of the main body **121** and the thickness of the main body between the outer wall **122** and the inner wall **123**. As noted above, diameter **124** is between about 0.0007" (0.0178 mm) and about 0.118" (3.0 mm) in some embodiments, with some particular embodiments having an outer diameter of approximately 0.014" (0.3556 mm) or approximately 0.018" (0.4572 mm). Further, the thickness of the main body **121** between the outer and inner surfaces **122** and **123** is between about 0.0005" or 0.0127 mm and about 0.003" or 0.0762 mm. In some specific embodiments, the thickness is about 0.0254 mm,

about 0.047 mm, or about 0.0508 mm. Based on the inner diameter **137**, the size and orientation of the trifilar **125**, and the thickness of layer **134**, the core **136** has a maximum diameter **138**.

**[0046]** In some instances, the arrangement of components shown in FIG. **2** limits the maximum outer diameter **138** of the core **136** to about 46% of the outer diameter **124** of the main body **121**. For example, for a 0.014" outer diameter imaging device, the core diameter **138** is limited to about 0.0065". While this core diameter size is an improvement over previous devices that had a core diameter of about 0.0055" for a 0.014" outer diameter imaging device, which is equivalent to about 39% of the outer diameter, the present disclosure provides additional embodiments below that facilitate further increases in the diameter of the core wire. In that regard, it should be noted that the present inventors have found that increases in the core diameter as small as 0.0005" provide significant improvement to the handling performance characteristics to the imaging device **120**. Some specific examples of arrangement that facilitate further increases in core diameter will now be described. For sake of clarity, these embodiments will be described in the context of an imaging device having a 0.014" outer diameter. However, it is understood that similar approaches may be utilized to increase the core diameters for imaging devices having smaller or larger outer diameters. In addition to and/or as an alternative to increasing the core diameters, the additional space provided by the embodiments of the present disclosure can be utilized to increase the number of components (e.g., including conductors and/or electronic components) positioned adjacent the distal portion of the device.

**[0047]** Referring now to FIG. **3**, shown therein is a cross-sectional longitudinal view of an intravascular device **140** according to another embodiment of the present disclosure. The intravascular device **140** includes some features similar to those described above with respect to imaging device **120** and, therefore, the same reference numerals have been utilized to refer to similar components. The intravascular device **140** includes a main body **121** having an outer wall **122** defining an outer boundary of the intravascular device **120** and an inner wall **123** defining a lumen for receiving additional components of the intravascular device **140** that will be discussed in greater detail below. In the illustrated embodiment the main body **121** has a circular cross-sectional profile with an outer diameter **124**. Diameter **124** is between about 0.0007" (0.0178 mm) and about 0.118" (3.0 mm) in some embodiments, with some particular embodiments having an outer diameter of approximately 0.014" (0.3556 mm) or approximately 0.018" (0.4572 mm). In some embodiments, the main body **121** has a constant profile along all or a majority of its length. For example, where the main body **121** has a circular cross-sectional profile, as shown in FIG. **3**, the various portions of the main body maintain a constant outer diameter along all or a majority of the length of the intravascular device **140**. In some embodiments, at the least the portions of the main body **121** that are intended to be disposed within the patient have a constant profile (or at least tapered/gradual transitions between portions with different outer profiles) to avoid potential injury to the patient while moving the intravascular device **140** through the patient. Further, it is recognized that the composition of the main body **121** changes along the length of the intravascular device in some instances. For example, in some embodiments the main body **121** transitions between

one or more of a hypotube, a coil, a balloon, a polymer sleeve, and/or other structures and combinations thereof. The main body **121** maintains a constant profile across the transitions in some instances. In some instances, the main body **121** includes a polymer tubing with a conductive coil embedded therein as discussed with respect to FIGS. **12-16** below.

[0048] The intravascular device **140** also includes a trifilar **125** disposed within the lumen of the main body **121** defined by the inner wall **123**. In that regard, the trifilar **125** consists of three electrical conductors or wires **126**, **127**, and **128**, which may be formed of any suitable conductive material including without limitation copper, copper alloys, silver, silver alloys, aluminum, and/or combinations thereof. Each of the wires **126**, **127**, and **128** is wrapped with an insulating layer **129**, **130**, and **131**, respectively. Any suitable insulating layer may be utilized, including without limitation polyimide, polyurethane, nylon, polyethylene, polypropylene, silicone rubber, fluoropolymers, and/or combinations thereof. In some embodiments, the insulating layers **129**, **130**, and **131** are color coded or otherwise include markings or identifiers to facilitate identification of the corresponding conductor **126**, **127**, and **128**. An overcoat layer **132** is formed over the three conductors **126**, **127**, and **128** and insulating layers **129**, **130**, and **131** to connect the conductors together as a single trifilar component **125**. Layer **132** is formed of an insulating material in some instances. For example, in some embodiments layer **132** is formed of one or more of polyurethane, polyethylene, polypropylene, silicone rubber, and/or combinations thereof. As shown, unlike the embodiment of FIG. **2** where the conductors **126**, **127**, and **128** were aligned such that a central longitudinal axis of each of the conductors **126**, **127**, and **128** would be in a common plane, in the embodiment of FIG. **3** the conductors **126**, **127**, and **128** are arranged in an arcuate, curved, and/or offset orientation such that the trifilar generally follows the curvature of the inner wall **123**. In the illustrated embodiment of FIG. **3**, central longitudinal axes of conductors **126** and **128** are positioned in a common plane, but the central longitudinal axis of conductor **127** is offset (upwards as viewed in FIG. **3**) towards the outer boundary of the main body **121**.

[0049] As shown, the trifilar **125** is positioned within the lumen **133** of the main body **121**. In some instances, lumen **133** is open space. In other instances, the lumen **133** is partially or completely filled with a material. For example, in some instances a portion of the lumen **133** is filled with an adhesive, such as polyurethanes, cyanoacrylates, acrylates, silicone, and/or combinations thereof, that is utilized to secure components of the intravascular device **120** together. Accordingly, in some instances, the material filling lumen **133** also surrounds a layer **134** and core wire **136**. In that regard, the layer **134** is formed of polyethylene terephthalate (PET) in some instances and may extend along all, a portion, or none of the length of the core wire **136** (i.e., layer **134** is omitted in some instances). In some embodiments, the layer **134** has a thickness between about 0.0001" (0.0025 mm) and about 0.0005" (0.0127 mm). In some embodiments, the layer **134** is intermittently used along the length of the core **136** as an insulator at certain joints and/or to hold the trifilar **125** to the core **136**.

[0050] As shown, the inner wall **123** of the main body **121** defines a lumen having a diameter **137**. The diameter **137** is dependent upon the outer diameter **124** of the main body **121**

and the thickness of the main body between the outer wall **122** and the inner wall **123**. As noted above, diameter **124** is between about 0.0007" (0.0178 mm) and about 0.118" (3.0 mm) in some embodiments, with some particular embodiments having an outer diameter of approximately 0.014" (0.3556 mm) or approximately 0.018" (0.4572 mm)). Further, the thickness of the main body **121** between the outer and inner surfaces **122** and **123** is between about 0.0005" or 0.0127 mm and about 0.003" or 0.0762 mm. In some specific embodiments, the thickness is about 0.0254 mm, about 0.047 mm, or about 0.0508 mm. Based on the inner diameter **137**, the size and orientation of the trifilar **125**, and the thickness of layer **134**, the core **142** has a maximum diameter **144**.

[0051] This arrangement of components shown in FIG. **3** increases the maximum outer diameter **144** of the core **142** relative to the maximum outer diameter **138** of the core **136** of imaging device **120** of FIG. **2** from about 46% to about 50% of the outer diameter **124** of the main body **121**. For example, for a 0.014" outer diameter imaging device, the core diameter **144** is increased to about 0.0070".

[0052] Referring now to FIG. **4**, shown therein is a cross-sectional longitudinal view of an intravascular device **150** according to another embodiment of the present disclosure. The intravascular device **150** includes some features similar to those described above with respect to imaging devices **120** and **140** and, therefore, the same reference numerals have been utilized to refer to similar components. The intravascular device **150** includes a main body **121** having an outer wall **122** defining an outer boundary of the intravascular device **120** and an inner wall **123** defining a lumen for receiving additional components of the intravascular device **150** that will be discussed in greater detail below. In the illustrated embodiment the main body **121** has a circular cross-sectional profile with an outer diameter **124**. Diameter **124** is between about 0.0007" (0.0178 mm) and about 0.118" (3.0 mm) in some embodiments, with some particular embodiments having an outer diameter of approximately 0.014" (0.3556 mm) or approximately 0.018" (0.4572 mm)). In some embodiments, the main body **121** has a constant profile along all or a majority of its length. For example, where the main body **121** has a circular cross-sectional profile, as shown in FIG. **4**, the various portions of the main body maintain a constant outer diameter along all or a majority of the length of the intravascular device **150**. In some embodiments, at the least the portions of the main body **121** that are intended to be disposed within the patient have a constant profile (or at least tapered/gradual transitions between portions with different outer profiles) to avoid potential injury to the patient while moving the intravascular device **150** through the patient. Further, it is recognized that the composition of the main body **121** changes along the length of the intravascular device in some instances. For example, in some embodiments the main body **121** transitions between one or more of a hypotube, a coil, a balloon, a polymer sleeve, and/or other structures and combinations thereof. The main body **121** maintains a constant profile across the transitions in some instances. In some instances, the main body **121** includes a polymer tubing with a conductive coil embedded therein as discussed with respect to FIGS. **12-16** below.

[0053] The intravascular device **150** also includes a trifilar **152** disposed within the lumen of the main body **121** defined by the inner wall **123**. In that regard, the trifilar **152** consists

of three electrical conductors or wires **153**, **154**, and **155**, which may be formed of any suitable conductive material including without limitation copper, copper alloys, silver, silver alloys, aluminum, and/or combinations thereof. Each of the conductors **153**, **154**, and **155** is wrapped with an insulating layer **156**, **157**, and **158**, respectively. Any suitable insulating layer may be utilized, including without limitation polyimide, polyurethane, nylon, polyethylene, polypropylene, silicone rubber, fluoropolymers, and/or combinations thereof. In some embodiments, the insulating layers **156**, **157**, and **158** are color coded or otherwise include markings or identifiers to facilitate identification of the corresponding conductor **153**, **154**, and **155**. In some embodiments, the insulating layers **156**, **157**, and **158** form a continuous integrated insulating structure that couples the conductors **153**, **154**, and **155** together. In other instances, the insulating layers **156**, **157**, and **158** are separately formed over the respective conductors **153**, **154**, and **155** and an overcoat layer is formed over the three conductors **153**, **154**, and **155** and insulating layers **156**, **157**, and **158** to connect the conductors together as a single trifilar component **152**.

[0054] As shown, similar to the conductors **126**, **127**, and **128** of FIG. 3, the conductors **153**, **154**, and **155** are arranged in an arcuate, curved, and/or offset orientation such that the trifilar generally follows the curvature of the inner wall **123**. In the illustrated embodiment of FIG. 4, central longitudinal axes of conductors **153** and **155** are positioned in a common plane, but the central longitudinal axis of conductor **154** is offset (upwards as viewed in FIG. 4) towards the outer boundary of the main body **121**. However, unlike the conductors **126**, **127**, and **128** of FIG. 3 that have a circular cross-sectional profile, the conductors **153**, **154**, and **155** of FIG. 4 have a flattened configuration. In particular, each of the conductors **153**, **154**, and **155** has a generally rectangular cross sectional profile within rounded edges. In some instances, each of the conductors has a cross-sectional width **160** between about 0.0178 mm and about 0.0762 mm. Further, in some instances, each of the conductors has a cross-sectional thickness **162** between about 0.00508 mm and about 0.0254 mm. Further still, in some instances each of the insulating layers **156**, **157**, and **158** has a thickness between about 0.00508 mm and about 0.0127 mm such that the total thickness **164** of the trifilar **152** is between about 0.01016 mm and about 0.0381 mm. In some instances, the flattened trifilar is formed by using a specific gauge wire (e.g., 48 gauge or 0.0012" copper wire) with specific build thickness of insulation (e.g., triple build) that results in overall thickness of trifilar of between about 0.0018" and about 0.002". The trifilar structure is then roller flattened to a specific desired thickness, such as the ranges discussed above, which results in the thicknesses of both the insulation and the copper wire being reduced.

[0055] As shown, the trifilar **152** is positioned within the lumen **133** of the main body **121**. In some instances, lumen **133** is open space. In other instances, the lumen **133** is partially or completely filled with a material. For example, in some instances a portion of the lumen **133** is filled with an adhesive, such as polyurethanes, cyanoacrylates, acrylates, silicone, and/or combinations thereof, that is utilized to secure components of the intravascular device **150** together. Accordingly, in some instances, the material filling lumen **133** also surrounds core wire **166**. In that regard, FIG. 4 shows a cross-section where the layer **134** discussed with respect to FIGS. 2 and 3 has been omitted. Based on the

inner diameter **137**, the size and orientation of the trifilar **152**, and the omission of the layer surrounding the core **166**, the core **166** has a maximum diameter **168**. This arrangement of components shown in FIG. 4 increases the maximum outer diameter **168** of the core **166** relative to the maximum outer diameter **138** of the core **136** of imaging device **120** of FIG. 2 from about 46% to about 61% of the outer diameter **124** of the main body **121**. For example, for a 0.014" outer diameter imaging device, the core diameter **168** is increased to about 0.0085".

[0056] Referring now to FIG. 5, shown therein is a cross-sectional longitudinal view of an intravascular device **170** according to another embodiment of the present disclosure. The intravascular device **170** includes some features similar to those described above with respect to imaging devices **120**, **140**, and **150** and, therefore, the same reference numerals have been utilized to refer to similar components. The intravascular device **170** includes a main body **121** having an outer wall **122** defining an outer boundary of the intravascular device **120** and an inner wall **123** defining a lumen for receiving additional components of the intravascular device **170** that will be discussed in greater detail below. In the illustrated embodiment the main body **121** has a circular cross-sectional profile with an outer diameter **124**. Diameter **124** is between about 0.0007" (0.0178 mm) and about 0.118" (3.0 mm) in some embodiments, with some particular embodiments having an outer diameter of approximately 0.014" (0.3556 mm) or approximately 0.018" (0.4572 mm)). In some embodiments, the main body **121** has a constant profile along all or a majority of its length. For example, where the main body **121** has a circular cross-sectional profile, as shown in FIG. 5, the various portions of the main body maintain a constant outer diameter along all or a majority of the length of the intravascular device **170**. In some embodiments, at the least the portions of the main body **121** that are intended to be disposed within the patient have a constant profile (or at least tapered/gradual transitions between portions with different outer profiles) to avoid potential injury to the patient while moving the intravascular device **170** through the patient. Further, it is recognized that the composition of the main body **121** changes along the length of the intravascular device in some instances. For example, in some embodiments the main body **121** transitions between one or more of a hypotube, a coil, a balloon, a polymer sleeve, and/or other structures and combinations thereof. The main body **121** maintains a constant profile across the transitions in some instances. In some instances, the main body **121** includes a polymer tubing with a conductive coil embedded therein as discussed with respect to FIGS. 12-16 below.

[0057] The intravascular device **170** also includes a trifilar **152** disposed within the lumen of the main body **121** defined by the inner wall **123**. In that regard, the trifilar **152** consists of three electrical conductors or wires **153**, **154**, and **155**, which may be formed of any suitable conductive material including without limitation copper, copper alloys, silver, silver alloys, aluminum, and/or combinations thereof. Each of the conductors **153**, **154**, and **155** is wrapped with an insulating layer **156**, **157**, and **158**, respectively. Any suitable insulating layer may be utilized, including without limitation polyimide, polyurethane, nylon, polyethylene, polypropylene, silicone rubber, fluoropolymers, and/or combinations thereof. In some embodiments, the insulating layers **156**, **157**, and **158** are color coded or otherwise

include markings or identifiers to facilitate identification of the corresponding conductor **153**, **154**, and **155**. In some embodiments, the insulating layers **156**, **157**, and **158** form a continuous integrated insulating structure that couples the conductors **153**, **154**, and **155** together. In other instances, the insulating layers **156**, **157**, and **158** are separately formed over the respective conductors **153**, **154**, and **155** and an overcoat layer is formed over the three conductors **153**, **154**, and **155** and insulating layers **156**, **157**, and **158** to connect the conductors together as a single trifilar component **152**.

[0058] As shown, the conductors **153**, **154**, and **155** are arranged in an arcuate, curved, and/or offset orientation such that the trifilar **152** generally follows the curvature of the inner wall **123**. In the illustrated embodiment of FIG. 5, central longitudinal axes of conductors **153** and **155** are positioned in a common plane, but the central longitudinal axis of conductor **154** is offset (upwards as viewed in FIG. 4) towards the outer boundary of the main body **121**. Each of the conductors **153**, **154**, and **155** has a generally rectangular cross sectional profile within rounded edges. In some instances, each of the conductors has a cross-sectional width **160** between about 0.0178 mm and about 0.0762 mm. Further, in some instances, each of the conductors has a cross-sectional thickness **162** between about 0.00508 mm and about 0.0254 mm. Further still, in some instances each of the insulating layers **156**, **157**, and **158** has a thickness between about 0.00508 mm and about 0.0127 mm such that the total thickness **164** of the trifilar **152** is between about 0.01016 mm and about 0.0381 mm. In some instances, the flattened trifilar is formed by using a specific gauge wire (e.g., 48 gauge or 0.0012" copper wire) with specific build thickness of insulation (e.g., triple build) that results in overall thickness of trifilar of between about 0.0018" and about 0.002". The trifilar structure is then roller flattened to a specific desired thickness, such as the ranges discussed above, which results in the thicknesses of both the insulation and the copper wire being reduced.

[0059] As shown, the trifilar **152** is positioned within the lumen **133** of the main body **121**. In some instances, lumen **133** is open space. In other instances, the lumen **133** is partially or completely filled with a material. For example, in some instances a portion of the lumen **133** is filled with an adhesive, such as polyurethanes, cyanoacrylates, acrylates, silicone, and/or combinations thereof, that is utilized to secure components of the intravascular device **170** together. Accordingly, in some instances, the material filling lumen **133** also surrounds a layer **134** and core wire **172**. In that regard, the layer **134** is formed of polyethylene terephthalate (PET) in some instances and may extend along all, a portion, or none of the length of the core wire **136** (i.e., layer **134** is omitted in some instances). In some embodiments, the layer **134** has a thickness between about 0.0001" (0.0025 mm) and about 0.0005" (0.0127 mm). In some embodiments, the layer **134** is intermittently used along the length of the core **172** as an insulator at certain joints and/or to hold the trifilar **152** to the core **172**. Based on the inner diameter **137**, the size and orientation of the trifilar **152**, and the layer **134** surrounding the core **172**, the core **172** has a maximum diameter **174**. This arrangement of components shown in FIG. 5 increases the maximum outer diameter **174** of the core **172** relative to the maximum outer diameter **138** of the core **136** of imaging device **120** of FIG. 2 from about 46% to about 57% of the outer diameter **124** of the main

body **121**. For example, for a 0.014" outer diameter imaging device, the core diameter **168** is increased to about 0.0080".

[0060] Referring now to FIG. 6, shown therein is a cross-sectional side view of an intravascular device **200** according to an embodiment of the present disclosure. As shown, the intravascular device **200** includes a proximal portion **202**, a middle portion **204**, and a distal portion **206**. Generally, the proximal portion **202** is configured to be positioned outside of a patient, while the distal portion **206** and a majority of the middle portion **204** are configured to be inserted into the patient, including within human vasculature. In that regard, the middle and distal portion **204** have an outer diameter between about 0.0007" (0.0178 mm) and about 0.118" (3.0 mm) in some embodiments, with some particular embodiments having an outer diameter of approximately 0.014" (0.3556 mm) or approximately 0.018" (0.4572 mm)). In the illustrated embodiment of FIG. 6, the intravascular device **200** has an outer diameter of 0.014" (0.3556 mm).

[0061] As shown, the distal portion **206** of the intravascular device **200** has a distal tip **207** defined by an element **208**. In the illustrated embodiment, the distal tip **207** has a rounded profile. In some instances, the element **208** is radiopaque such that the distal tip **207** is identifiable under x-ray, fluoroscopy, and/or other imaging modalities when positioned within a patient. In some particular instances, the element **208** is solder secured to a flexible element **210** and/or a flattened tip core **212**. In that regard, in some instances the flexible element **210** is a coil spring. The flattened tip core **212** extends distally from a distal core **214**. As shown, the distal core **214** tapers to a narrow profile as it extends distally towards the distal tip **207**. In some instances, the distal core **214** is formed of a stainless steel that has been ground down have the desired tapered profile. In some particular instances, the distal core **214** is formed of high tensile strength 304V stainless steel. In an alternative embodiment, the distal core **214** is formed by wrapping a stainless steel shaping ribbon around a nitinol core. Solder points **216** secure the distal core **214** to a mounting structure **218**. The mounting structure **218** is configured to receive and securely hold a component **220**. In that regard, the component **220** is one or more of an electronic component, an optical component, and/or electro-optical component. For example, without limitation, the component **220** may be one or more of the following types of components: a pressure sensor, a temperature sensor, an imaging element, an optical fiber, an ultrasound transducer, a reflector, a mirror, a prism, an ablation element, an RF electrode, a conductor, and/or combinations thereof.

[0062] The mounting structure **218** is fixedly secured within the distal portion **206** of the intravascular device **200** by an adhesive or solder **222**. In that regard, the mounting structure **218** is disposed within the flexible element **210** and/or a flexible element **224**. In some instances, the flexible element **224** is ribbon coil covered with a polymer coating. For example, in one embodiment the flexible element **224** is a stainless steel ribbon wire coil coated with polyethylene terephthalate (PET). In another embodiment, the flexible element is a polyimide tubing that has a ribbon wire coil embedded therein. For example, in some instances a polyimide or Pebax tubing with embedded coil similar to that discussed below with respect to FIGS. 12-16 is utilized for flexible element **224**. In some particular embodiments, the ribbon wire coil is embedded to an inner diameter of the polyimide tubing. The adhesive **222** is utilized to secure the

mounting structure **218** to the flexible element **210** and/or the flexible element **224**. Accordingly, in some instances the adhesive is urethane acrylate, cyanoacrylate, silicone, epoxy, and/or combinations thereof. The mounting structure **218** is also secured to a core **226** that extends proximally from the mounting structure towards the middle portion **204** of the intravascular device **200**. In that regard, a distal portion **228** of the core **226** tapers as it extends distally towards mounting structure **218**. A distal end of the distal portion **228** of the core **226** is fixedly secured to the mounting structure **218**. In some instances, the distal end of the core **226** is soldered to the mounting structure. As shown, adhesive **230** surrounds at least a portion of the distal portion **228** of the core **226**. In some instances, the adhesive **230** is the adhesive **222** used to secure the mounting structure **218** to the flexible element **210** and/or flexible element **224**. In other instances, adhesive **230** is a different type of adhesive than adhesive **222**. In one particular embodiment, adhesive or solder **222** is particularly suited to secure the mounting structure to flexible element **210**, while adhesive **230** is particularly suited to secure the mounting structure to flexible element **224**.

[0063] A communication cable **232** extends along the length of the intravascular device **200** from the proximal portion **202** to the distal portion **206**. In that regard, the distal end of the communication cable **232** is coupled to the component **220** at junction **234**. The type of communication cable utilized is dependent on the type of electronic, optical, and/or electro-optical components that make up the component **220**. In that regard, the communication cable **232** may include one or more of an electrical conductor, an optical fiber, and/or combinations thereof. Appropriate connections are utilized at the junction **234** based on the type of communication lines included within communication cable **232**. For example, electrical connections are soldered in some instances, while optical connections pass through an optical connector in some instances. In some embodiments, the communication cable **232** is a trifilar structure as described above with respect to FIGS. 2-5. Further, it is understood that all and/or portions of each of the proximal, middle, and/or distal portions **202**, **204**, **206** of the intravascular device **200** may have cross-sectional profiles as shown in FIGS. 2-5. In one particular embodiment, the component **220** is a pressure sensor and at least the middle portion **204** of the intravascular device **200** has the cross-sectional profile of either FIG. 4 or FIG. 5.

[0064] Further, in some embodiments, the proximal portion **202** and/or the distal portion **206** incorporate spiral ribbon tubing as discussed with respect to FIGS. 12-16 below. In some instances, the use of such spiral ribbon tubing allows a further increase in the available lumen space within the device. For example, in some instances use of a spiral ribbon tubing having a wall thickness between about 0.001" and about 0.002" facilitates the use of a core wire having an outer diameter of at least 0.0095" within a 0.014" outer diameter guidewire using a trifilar with circular cross-sectional conductor profiles (see, e.g., FIGS. 2 and 3). The size of the core wire can be further increased to at least 0.010" by using a trifilar with the flattened oblong cross-section conductor profiles (see, e.g., FIGS. 4 and 5). The availability to use a core wire having an increased diameter allows the use of materials having a lower modulus of elasticity than a standard stainless steel core wire (e.g., superelastic materials such as Nitinol or NiTiCo are utilized

in some instances) without adversely affecting the handling performance or structural integrity of the guidewire and, in many instances, provides improvement to the handling performance of the guidewire, especially when a superelastic material with an increased core diameter (e.g., a core diameter of 0.0075" or greater) is utilized within the distal portion **206**.

[0065] The distal portion **206** of the intravascular device **200** also optionally includes at least one imaging marker **236**. In that regard, the imaging marker **236** is configured to be identifiable using an external imaging modality, such as x-ray, fluoroscopy, angiograph, CT scan, MRI, or otherwise, when the distal portion **206** of the intravascular device **200** is positioned within a patient. In the illustrated embodiment, the imaging marker **236** is a radiopaque coil positioned around the tapered distal portion **228** of the core **226**. Visualization of the imaging marker **236** during a procedure can give the medical personnel an indication of the size of a lesion or region of interest within the patient. To that end, the imaging marker **236** can have a known length (e.g., 0.5 cm or 1.0 cm) and/or be spaced from the element **208** by a known distance (e.g., 3.0 cm) such that visualization of the imaging marker **236** and/or the element **208** along with the anatomical structure allows a user to estimate the size or length of a region of interest of the anatomical structure. It is understood that a plurality of imaging markers **236** are utilized in some instances. In that regard, in some instances the imaging markers **236** are spaced a known distance from one another to further facilitate measuring the size or length of the region of interest.

[0066] In some instances, a proximal portion of the core **226** is secured to a core **238** that extends through the middle portion **204** of the intravascular device. In that regard, the transition between the core **226** and the core **238** may occur within the distal portion **206**, within the middle portion **204**, and/or at the transition between the distal portion **206** and the middle portion **204**. For example, in the illustrated embodiment the transition between core **226** and core **238** occurs in the vicinity of a transition between the flexible element **224** and a flexible element **240**. The flexible element **240** in the illustrated embodiment is a hypotube. In some particular instances, the flexible element is a stainless steel hypotube. Further, in the illustrated embodiment a portion of the flexible element **240** is covered with a coating **242**. In that regard, the coating **242** is a hydrophobic coating in some instances. In some embodiments, the coating **242** is a polytetrafluoroethylene (PTFE) coating.

[0067] The proximal portion of core **226** is fixedly secured to the distal portion of core **238**. In that regard, any suitable technique for securing the cores **226**, **238** to one another may be used. In some embodiments, at least one of the cores **226**, **238** includes a plunge grind or other structural modification that is utilized to couple the cores together. In some instances, the cores **226**, **238** are soldered together. In some instances, an adhesive is utilized to secure the cores **226**, **238** together. In some embodiments, combinations of structural interfaces, soldering, and/or adhesives are utilized to secure the cores **226**, **238** together. In other instances, the core **226** is not fixedly secured to core **238**. For example, in some instances, the core **226** and the core **246** are fixedly secured to the hypotube **240** and the core **238** is positioned between the cores **226** and **246**, which maintains the position of the core **238** between cores **226** and **246**.

[0068] In some embodiments, the core 238 is formed of a different material than the core 226. For example, in some instances the core 226 is formed of nitinol and the core 238 is formed of stainless steel. In other instances, the core 238 and the core 226 are formed of the same material. In some instances the core 238 has a different profile than the core 226, such as a larger or smaller diameter and/or a non-circular cross-sectional profile. For example, in some instances the core 238 has a D-shaped cross-sectional profile. In that regard, a D-shaped cross-sectional profile has some advantages in the context of an intravascular device 200 that includes one or more electronic, optical, or electro-optical component in that it provides a natural space to run any necessary communication cables while providing increased strength than a full diameter core.

[0069] In some instances, a proximal portion of the core 238 is secured to a core 246 that extends through at least a portion of the proximal portion 202 of the intravascular device 200. In that regard, the transition between the core 238 and the core 246 may occur within the proximal portion 202, within the middle portion 204, and/or at the transition between the proximal portion 202 and the middle portion 204. For example, in the illustrated embodiment the transition between core 238 and core 246 is positioned distal of a plurality of conducting bands 248. In that regard, in some instances the conductive bands 248 are portions of a hypotube. In other instances, the conductive bands are coils, such as those discussed in the context of FIGS. 7-16 below. Proximal portions of the communication cable 232 are coupled to the conductive bands 248. In that regard, in some instances each of the conductive bands is associated with a corresponding communication line of the communication cable 232. For example, in embodiments where the communication cable 232 consists of a trifilar, each of the three conductive bands 248 illustrated in FIG. 6 are connected to one of the conductors of the trifilar, for example by soldering each of the conductive bands to the respective conductor. Where the communication cable 232 includes optical communication line(s), the proximal portion 202 of the intravascular device 200 includes an optical connector in addition to or instead of one or more of the conductive bands 248. An insulating layer or sleeve 250 separates the conductive bands 248 from the core 246. In some instances, the insulating layer 250 is formed of polyimide.

[0070] As noted above, the proximal portion of core 238 is fixedly secured to the distal portion of core 246. In that regard, any suitable technique for securing the cores 238, 246 to one another may be used. In some embodiments, at least one of the cores includes a structural feature that is utilized to couple the cores together. In the illustrated embodiment, the core 238 includes an extension 252 that extends around a distal portion of the core 246. In some instances, the cores 238, 246 are soldered together. In some instances, an adhesive is utilized to secure the cores 238, 246 together. In some embodiments, combinations of structural interfaces, soldering, and/or adhesives are utilized to secure the cores 238, 246 together. In other instances, the core 226 is not fixedly secured to core 238. For example, in some instances and as noted above, the core 226 and the core 246 are fixedly secured to the hypotube 240 and the core 238 is positioned between the cores 226 and 246, which maintains the position of the core 238 between cores 226 and 246. In some embodiments, the core 246 is formed of a different material than the core 238. For example, in some instances

the core 246 is formed of Nitinol and/or NiTiCo (nickel-titanium-cobalt alloy) and the core 238 is formed of stainless steel. In that regard, by utilizing a nitinol core within the conductive bands 248 instead of a stainless steel the likelihood of kinking is greatly reduced because of the increased flexibility of the nitinol core compared to a stainless steel core. In other instances, the core 238 and the core 246 are formed of the same material. In some instances the core 238 has a different profile than the core 246, such as a larger or smaller diameter and/or a non-circular cross-sectional profile.

[0071] Referring now to FIGS. 7-11, shown therein are various embodiments of proximal connectors according to the present disclosure. In particular, the embodiments of FIGS. 7-11 include flexible coil conductive bands that help to prevent kinking that can cause damage to the communication pathways of an intravascular device, such as communication cable 232 of intravascular device 200, by increasing the flexibility of the connecting portions of the intravascular device. The flexible coil conductive bands of the present disclosure also provide opportunities for reducing manufacturing costs and increasing the available space within the proximal portion of the device. For example, referring more specifically to FIG. 7, shown therein is a portion 260 of an intravascular device according to an embodiment of the present disclosure. As shown, the portion 260 includes electrical connectors 262, 264, and 266. In the illustrated embodiment of FIG. 7, each of the electrical connectors 262, 264, and 266 are formed of a wire coil, where the wire forming the coil has a circular cross-sectional profile. The wire is wound to have an outer diameter based on the desired outer diameter of the intravascular device. In that regard, the outer diameter of the coil may be equal to, slightly larger than, or slightly smaller than the desired outer diameter of the intravascular device. For example, in one embodiment of a 0.014" intravascular device, the coil has an outer diameter of 0.0142".

[0072] The electrical connectors 262, 264, and 266 are formed of a conductive material such as gold, an 80/20 platinum/iridium alloy, other platinum-iridium alloys, platinum-tungsten alloys, gold plated materials (e.g., stainless steel), other suitable conductive materials, and/or combinations thereof. In some embodiments, the electrical connectors 262, 264, and 266 include a stainless steel core with at least the outer surfaces plated with gold, copper, or other material having increased conductivity compared to stainless steel. An insulating portion 268 separates connector 262 from connector 264 and an insulating portion 270 separates connector 264 from connector 266. The electrical connectors 262, 264, and 266 and insulating portions 268 and 270 surround a central portion 272. In that regard, in some instances central portion 272 contains a core wire, communication cable(s), and/or other components of the intravascular device. In some specific embodiments, the central portion 272 includes at least a core wire and a trifilar. In that regard, each of the electrical connectors 262, 264, and 266 is connected to one of the conductors of the trifilar, for example, by soldering the conductor to the respective connector. In some embodiments, at least one of the electrical connectors 262, 264, and/or 266 does not have any insulating material positioned between it and the core. In that regard, in some such instances the electrical conductor(s) is soldered or otherwise secure to the core without any insulation material in between the element and the core. In one

particular embodiment, the most proximal connector is secured to the core without any insulating material. Further, the connector secured to the core is a ground contact in some instances.

[0073] Referring now to FIG. 8, shown therein is a portion 280 of an intravascular device according to another embodiment of the present disclosure. As shown, the portion 280 includes electrical connectors 282, 284, and 286. In the illustrated embodiment of FIG. 8, each of the electrical connectors 282, 284, and 286 are formed of a wire coil, where the wire forming the coil has a rectangular cross-sectional profile. In some applications, the rectangular cross-sectional profile improves functionality of the connectors compared to the circular cross-sectional profile of FIG. 7 due to the more constant outer surface of the resulting connectors. Further, in some instances, the wire or ribbon forming the coil has a thickness of 0.001" or less. With a thickness of 0.001" or less, a significant increase in space within the coils is provided, which can be used to implement a core with larger diameter and/or other make assembling the proximal portion of the intravascular device easier. Further, in some instances the wire or ribbon forming the coil has a width of 0.005" or less. The wire or ribbon forming the coil is wound to have an outer diameter based on the desired outer diameter of the intravascular device. In that regard, the outer diameter of the coil may be equal to, slightly larger than, or slightly smaller than the desired outer diameter of the intravascular device. For example, in one embodiment of a 0.014" intravascular device, the coil has an outer diameter of 0.0142".

[0074] The electrical connectors 282, 284, and 286 are formed of a conductive material such as gold, an 80/20 platinum/iridium alloy, other platinum-iridium alloys, platinum-tungsten alloys, gold plated materials (e.g., stainless steel), other suitable conductive materials, and/or combinations thereof. In some embodiments, the electrical connectors 282, 284, and 286 include a stainless steel core with at least the outer surfaces plated with gold, copper, or other material having increased conductivity compared to stainless steel. An insulating portion 288 separates connector 282 from connector 284 and an insulating portion 290 separates connector 284 from connector 286. The electrical connectors 282, 284, and 286 and insulating portions 288 and 290 surround a central portion 292. In that regard, in some instances central portion 292 contains a core wire, communication cable(s), and/or other components of the intravascular device. In some specific embodiments, the central portion 292 includes at least a core wire and a trifilar. In that regard, each of the electrical connectors 282, 284, and 286 is connected to one of the conductors of the trifilar, for example, by soldering the conductor to the respective connector.

[0075] Referring now to FIG. 9, shown therein is a portion 300 of an intravascular device according to another embodiment of the present disclosure. As shown, the portion 300 includes electrical connectors 302, 304, and 306. In the illustrated embodiment of FIG. 9, each of the electrical connectors 302, 304, and 306 are formed of a wire coil, where the wire forming the coil has a semi-circular cross-sectional profile with the rounded portion of the profile forming the outer surface of the coil. The wire is wound to have an outer diameter based on the desired outer diameter of the intravascular device. In that regard, the outer diameter of the coil may be equal to, slightly larger than, or slightly

smaller than the desired outer diameter of the intravascular device. For example, in one embodiment of a 0.014" intravascular device, the coil has an outer diameter of 0.0142".

[0076] The electrical connectors 302, 304, and 306 are formed of a conductive material such as gold, an 80/20 platinum/iridium alloy, other platinum-iridium alloys, platinum-tungsten alloys, gold plated materials (e.g., stainless steel), other suitable conductive materials, and/or combinations thereof. In some embodiments, the electrical connectors 302, 304, and 306 include a stainless steel core with at least the outer surfaces plated with gold, copper, or other material having increased conductivity compared to stainless steel. An insulating portion 308 separates connector 302 from connector 304 and an insulating portion 310 separates connector 304 from connector 306. The electrical connectors 302, 304, and 306 and insulating portions 308 and 310 surround a central portion 312. In that regard, in some instances central portion 312 contains a core wire, communication cable(s), and/or other components of the intravascular device. In some specific embodiments, the central portion 312 includes at least a core wire and a trifilar. In that regard, each of the electrical connectors 302, 304, and 306 is connected to one of the conductors of the trifilar, for example, by soldering the conductor to the respective connector.

[0077] Referring now to FIG. 10, shown therein is a portion 320 of an intravascular device according to another embodiment of the present disclosure. As shown, the portion 320 includes electrical connectors 322, 324, and 326. In the illustrated embodiment of FIG. 10, each of the electrical connectors 322, 324, and 326 are formed of a wire coil, where the wire forming the coil has a semi-circular cross-sectional profile with the flat portion of the profile forming the outer surface of the coil. In some applications, the using the flat portion as the outer surface of the coil improves functionality of the connectors compared to the using the rounded portion of the profile as the outer surface (as shown in FIG. 9) due to the more constant outer surface of the resulting connectors. The wire is wound to have an outer diameter based on the desired outer diameter of the intravascular device. In that regard, the outer diameter of the coil may be equal to, slightly larger than, or slightly smaller than the desired outer diameter of the intravascular device. For example, in one embodiment of a 0.014" intravascular device, the coil has an outer diameter of 0.0142".

[0078] The electrical connectors 302, 304, and 306 are formed of a conductive material such as gold, an 80/20 platinum/iridium alloy, other platinum-iridium alloys, platinum-tungsten alloys, gold plated materials (e.g., stainless steel), other suitable conductive materials, and/or combinations thereof. In some embodiments, the electrical connectors 322, 324, and 326 include a stainless steel core with at least the outer surfaces plated with gold, copper, or other material having increased conductivity compared to stainless steel. An insulating portion 328 separates connector 322 from connector 324 and an insulating portion 330 separates connector 324 from connector 326. The electrical connectors 322, 324, and 326 and insulating portions 328 and 330 surround a central portion 332. In that regard, in some instances central portion 332 contains a core wire, communication cable(s), and/or other components of the intravascular device. In some specific embodiments, the central portion 332 includes at least a core wire and a trifilar. In that regard, each of the electrical connectors 322, 324, and 326

is connected to one of the conductors of the trifilar, for example, by soldering the conductor to the respective connector.

[0079] Referring now to FIG. 11, shown therein is a diagrammatic cross-sectional close-up side view of a section of a proximal connector portion 340 of an intravascular device according to an embodiment of the present disclosure. In particular, FIG. 11 illustrates additional details of how a coil connector, such as those shown in FIGS. 7-10, may be incorporated into an intravascular device. In that regard, in the illustrated embodiment of FIG. 11, a coil 342 formed of a wire coil, where the wire forming the coil has a circular cross-sectional profile. The wire is wound to have an outer diameter based on the desired outer diameter of the intravascular device. In that regard, the outer diameter of the coil may be equal to, slightly larger than, or slightly smaller than the desired outer diameter of the intravascular device. For example, in one embodiment of a 0.014" intravascular device, the coil has an outer diameter of 0.0142". Further, the wire is wound such that there is sufficient spacing between adjacent windings of the coil 342 to facilitate soldering of a conductor positioned within the coil 342 to the coil. For example, as shown winding 344 and winding 346 as separated by space 348. Space 348 is between about 0.001" and about 0.0015" in some instances. Further, a conductor 350 is electrically coupled to the coil 342 at solder joint 352. In that regard, it is understood that multiple solder joints may be utilized in some instances. Insulating portions 356 and 358 separate the coil 342 from any adjacent coils. Further, an insulating layer 360 separates the coil 342, conductor 350, and solder joint 352 from a core 360, which is formed of a conductive material in some instances. In some instances, the insulating portions 356 and 358 and the insulating layer 360 are integrally formed. In other instances, the insulating portions 356 and 358 and the insulating layer 360 are formed separately.

[0080] In one particular embodiment, a shrink wrap is placed around the outer portion of the coil 342 (and any adjacent coils) and an insulating material is injected into the intravascular device and within the shrink wrap. The insulating material fills the space within the intravascular device around the insulating layer 360 and core 362. The close fit of the shrink wrap around the outer surface of the coil 342 prevents the insulating material from covering the outer conductive surface of the coil. Instead, the insulating material fills the spaces around the coil 342, thereby defining insulating portions 356 and 358, and any space between the coil 342 and the insulating layer 360, thereby forming insulating layer 364. In some instances, the insulating material is injected within the shrink wrap after the conductor 350 has been soldered to the coil 342. While the foregoing has been described with respect to the single coil 342 illustrated in FIG. 11, it is understood that the same arrangements and techniques for assembly may be utilized for two or more conductor coils of an intravascular device.

[0081] Referring now to FIGS. 12-16, shown therein are features related to forming a proximal connector portion of an intravascular device according to an embodiment of the present disclosure. Referring initially to FIG. 12, shown therein is tubing 400. In that regard, tubing 400 is a polymer tubing that includes a conductive coil embedded therein. The polymer used to form tubing 400 is polyimide in some instances, but may be another suitable insulating material in other instances. The conductive coil can be formed of any

suitable conductive material, including gold, an 80/20 platinum/iridium alloy, other platinum-iridium alloys, platinum-tungsten alloys, gold plated materials (e.g., stainless steel), other suitable conductive materials, and/or combinations thereof. In some embodiments, tubing 400 is a polyimide tubing with an embedded spiral ribbon coil formed of a platinum-iridium compound. In one such embodiment, the platinum-iridium compound has a ratio of platinum to iridium of approximately 80/20. As will be discussed in greater detail below, by exposing one or more portions of the embedded coil and electrically isolating the exposed portions from one another one or more conductive connectors can be defined in the tubing 400.

[0082] For example, as shown in FIG. 13, three conductive connectors 402, 404, and 406 have been formed by removing the surrounding polymer to expose the underlying coil. In that regard, the polymer is removed by laser ablation and/or chemical etching. As shown in FIG. 14, the polymer is removed such that the exposed portion of the coil 408 extends above the remaining polymer 410. In some instances, the polymer is removed such that the exposed coils 408 extend between about 0.0001" and about 0.0005" above the polymer. In one particular embodiment, the polymer is removed such that the exposed coils 408 extend approximately 0.0002" above the polymer. In other instances, the polymer is removed such that the exposed portion of the coil 408 and the remaining polymer 410 are substantially aligned with one another.

[0083] Referring again to FIG. 13, in addition to exposing the connectors 402, 404, and 406, it is necessary to electrically isolate the connectors from one another. In that regard, the connectors 402, 404, and 406 are portions of the same coil embedded in tubing 400. Accordingly, it is necessary to separate the connectors 402, 404, and 406 from one another if they are to act as separate connectors. In that regard, isolation region 412 is positioned between connectors 402 and 404, while isolation region 414 is positioned between connectors 404 and 406. One technique for electrically isolating the connectors is illustrated by the detailed views of isolation region 412 provided in FIGS. 15 and 16. As shown in FIGS. 15 and 16, the isolation region 412 includes an opening 416 through a sidewall of the tubing 400. In that regard, in the illustrated embodiment the opening 416 is generally pill shaped, having elongated straight sides and rounded ends. In that regard, the opening 416 has a height 418 that is generally between about 25% and about 60% of a diameter 420 of the tubing 400. In one particular embodiment, the tubing 400 has an outer diameter of 0.014" and the opening 416 has a height 418 of 0.0070". In the illustrated embodiment, opening 416 also has a length 422 associated with the straight sides and an overall length 424 that includes the rounded end portions. Generally, the length 422 is between about 5% and about 90% of a total length 426 of the isolation region 412, while the length 424 is between about 10% and about 95% of the total length of the isolation region. In that regard, the size of the opening is dependent upon ensuring that at least one full coil wind has been separated so that there is definitive coil isolation. Accordingly, in some instances the opening has a minimum length of 2.5 times the coil pitch. For example, if the coil pitch is 0.005, then the opening length would be ~0.0125", thus guaranteeing that at least 1 full coil wind was separated.

[0084] As shown in FIG. 16, by creating the opening 416 in the side wall portions of the imbedded coil are also

removed. In that regard, the opening 416 is created by laser cutting. In the illustrated embodiment, two windings of the coil have been cut. In other embodiments, one or more than two windings of the coil are cut within the isolation region 412. As a result of cutting two windings, three winding portions are created, namely coil portion 428 that is positioned within isolation portion 412, coil portion 430 that extends to the exposed portion that forms connector 402, and coil portion 432 that extends to the exposed portion that forms connector 404. In this manner, the coil portions 430 and 432 are electrically isolated from each other such that they can serve as separate electrical connectors for an intravascular device.

[0085] Persons skilled in the art will also recognize that the apparatus, systems, and methods described above can be modified in various ways. Accordingly, persons of ordinary skill in the art will appreciate that the embodiments encompassed by the present disclosure are not limited to the particular exemplary embodiments described above. In that regard, although illustrative embodiments have been shown and described, a wide range of modification, change, and substitution is contemplated in the foregoing disclosure. It is understood that such variations may be made to the foregoing without departing from the scope of the present disclosure. Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the present disclosure.

What is claimed is:

1. An intravascular device, comprising:
  - a flexible elongate member configured to be positioned within a vessel of a patient and comprising a proximal portion and a distal portion;
  - a sensing component disposed at the distal portion of the flexible elongate member;
  - at least one connector disposed at the proximal portion of the flexible elongate member; and
  - at least one conductor comprising a proximal section and a distal section, wherein the distal section of the at least one conductor is coupled to the sensing component and the proximal section of the at least one conductor is coupled to the at least one connector,
 wherein the at least one connector comprises a flexible conductive coil.
2. The intravascular device of claim 1, wherein a wire forming the flexible conductive coil has a rectangular cross-sectional profile.
3. The intravascular device of claim 1, wherein a wire forming the flexible conductive coil has a circular cross-sectional profile.

4. The intravascular device of claim 1, wherein a wire forming the flexible conductive coil has a semi-circular cross-sectional profile with a rounded portion of the semi-circular cross-sectional profile extending outwardly.

5. The intravascular device of claim 1, wherein a wire forming the flexible conductive coil has a semi-circular cross-sectional profile with a rounded portion of the semi-circular cross-sectional profile extending inwardly.

6. The intravascular device of claim 1, wherein the proximal section of the at least one conductor is soldered to an inner portion of the flexible conductive coil.

7. The intravascular device of claim 1, wherein the flexible conductive coil is at least partially embedded within a first polymer component.

8. The intravascular device of claim 1, wherein the at least one connector comprises a plurality of connectors.

9. The intravascular device of claim 8, wherein the plurality of connectors comprises electrically isolated portions of the flexible conductive coil.

10. The intravascular device of claim 9, wherein the flexible conductive coil comprises a cut winding electrically isolating individual connectors of the plurality of connectors.

11. The intravascular device of claim 1, wherein the sensing component is at least one of a pressure sensor, a temperature sensor, an imaging component, an optical fiber, or an ultrasound transducer.

12. The intravascular device of claim 1, wherein the sensing component is at least one of an electronic component, an optical component, or an electro-optical component.

13. The intravascular device of claim 1, wherein the sensing component is in communication with a computing device via the at least one conductor and the at least one connector.

14. The intravascular device of claim 1, wherein the at least one connector facilitates wireless communication between a computing device and the sensing component.

15. The intravascular device of claim 1, wherein the at least one conductor comprises a plurality of conductors.

16. The intravascular device of claim 1, wherein the at least one conductor has a non-circular cross-sectional profile.

17. The intravascular device of claim 1, wherein the at least one conductor has a rounded, rectangular cross-sectional profile.

\* \* \* \* \*

|                |   |         |            |
|----------------|---|---------|------------|
| 专利名称(译)        | 血管内装置，系统和方法   |         |            |
| 公开(公告)号        | <a href="#">US20170360370A1</a>   | 公开(公告)日 | 2017-12-21 |
| 申请号            | US15/693894   | 申请日     | 2017-09-01 |
| [标]申请(专利权)人(译) | 火山公司  |         |            |
| 申请(专利权)人(译)    | 火山CORPORATION   |         |            |
| 当前申请(专利权)人(译)  | 火山CORPORATION   |         |            |
| [标]发明人         | BURKETT DAVID H   |         |            |
| 发明人            | BURKETT, DAVID H.   |         |            |
| IPC分类号         | A61B5/00 A61M25/09 A61B5/0215 A61B8/12 A61M25/00  |         |            |
| CPC分类号         | A61M2025/0002 A61M2025/09175 A61B8/12 Y10T29/49826 A61M25/09 A61M2025/09083 A61B5/6851 A61B5/0215 |         |            |
| 优先权            | 61/665697 2012-06-28 US   |         |            |
| 其他公开文献         | US10602982  |         |            |
| 外部链接           | <a href="#">Espacenet</a> <a href="#">USPTO</a>   |         |            |

摘要(译)

公开了血管内装置，系统和方法。在一些实施例中，血管内装置包括位于装置的远侧部分内的至少一个电子，光学或电光组件以及位于该装置的远侧部分的一个或多个连接器。在某些情况下，连接器是柔性线圈，例如带状线圈，由导电材料形成。在一些特定情况下，导电线圈嵌入聚合物管中。此外，在一些实施例中，电子，光学或电光组件定位在设备的远端部分处的柔性元件内。在某些情况下，柔性元件是线圈。还提供了制造和/或组装这种血管内装置/系统的方法。

