



US008328803B2

(12) **United States Patent**  
**Regadas**

(10) **Patent No.:** **US 8,328,803 B2**  
(45) **Date of Patent:** **Dec. 11, 2012**

(54) **POLYP REMOVAL DEVICE AND METHOD OF USE**

(75) Inventor: **F. Sérgio P. Regadas**, Fortaleza-Ceara (BR)

(73) Assignee: **Covidien LP**, Mansfield, MA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 771 days.

2,532,043 A	11/1950	Wallace
3,149,633 A	9/1964	Zingale
3,752,159 A	8/1973	Wappler
3,856,015 A	12/1974	Iglesias
4,011,872 A	3/1977	Komiya
4,024,869 A	5/1977	Bonnet
4,060,087 A	11/1977	Hiltebrandt et al.
4,068,667 A	1/1978	Iglesias
4,116,198 A	9/1978	Roos
4,134,406 A	1/1979	Iglesias
4,202,338 A	5/1980	Bitrolf

(Continued)

(21) Appl. No.: **12/363,086**

(22) Filed: **Jan. 30, 2009**

(65) **Prior Publication Data**

US 2010/0036375 A1 Feb. 11, 2010

**Related U.S. Application Data**

(60) Provisional application No. 61/063,158, filed on Jan. 31, 2008.

(51) **Int. Cl.**  
**A61B 18/18** (2006.01)  
**A61B 17/24** (2006.01)

(52) **U.S. Cl.** ..... **606/47; 606/113**

(58) **Field of Classification Search** ..... 606/39, 606/113, 48, 49–52, 110, 127, 128, 47, 111  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

749,689 A	1/1904	Houghton
1,952,617 A	3/1934	Wappler
1,963,636 A	6/1934	Wappler
1,987,015 A	7/1934	Wappler
2,002,559 A	5/1935	Wappler
2,008,525 A	7/1935	Wappler
2,054,149 A	9/1936	Charles
2,442,966 A	6/1948	Wallace

**FOREIGN PATENT DOCUMENTS**

DE 2415263 10/1975  
(Continued)

**OTHER PUBLICATIONS**

International Search Report and Written Opinion of the International Searching Authority mailed Jun. 16, 2009 issued by the European Patent Office in counterpart International Application No. PCT/US2009/032690 filed Jan. 30, 2009.

(Continued)


*Primary Examiner* — Nicholas Lucchesi

*Assistant Examiner* — Weng Lee

(57) **ABSTRACT**

A device and system for removing tissue such as polyps is provided and includes a tubular member having proximal and distal ends, a snare portion operably extending from within the distal end of the tubular member and including first and second electrodes configured to treat tissue therebetween, the snare portion further including a cutting member for severing the treated tissue. The tissue removal device may further include a handle portion operatively extending from within the proximal end of the tubular member. The handle portion may be configured for operable engagement by a user and the cutting member may extend between distal ends of the first and second electrodes.

**15 Claims, 4 Drawing Sheets**



## U.S. PATENT DOCUMENTS

4,294,254 A 10/1981 Chamness  
 4,311,143 A 1/1982 Komiya  
 4,493,320 A 1/1985 Treat  
 4,503,855 A 3/1985 Maslanka  
 4,718,419 A 1/1988 Okada  
 4,905,691 A \* 3/1990 Rydell ..... 606/47  
 5,026,371 A 6/1991 Rydell et al.  
 5,066,295 A 11/1991 Kozak et al.  
 5,078,716 A 1/1992 Doll  
 5,192,280 A 3/1993 Parins  
 5,197,964 A 3/1993 Parins  
 5,207,686 A 5/1993 Dolgin  
 5,290,284 A 3/1994 Adair  
 5,318,564 A 6/1994 Eggers  
 5,417,697 A 5/1995 Wilk et al.  
 5,460,629 A 10/1995 Shlain et al.  
 5,462,553 A 10/1995 Dolgin  
 5,817,093 A \* 10/1998 Williamson et al. .... 606/50  
 5,971,994 A 10/1999 Fritzsche  
 6,015,415 A 1/2000 Avellanet  
 6,050,995 A \* 4/2000 Durgin ..... 606/47  
 6,071,283 A 6/2000 Nardella et al.  
 6,152,922 A 11/2000 Ouchi  
 6,235,026 B1 5/2001 Smith  
 6,517,539 B1 2/2003 Smith et al.  
 6,730,097 B2 5/2004 Dennis  
 6,743,228 B2 6/2004 Lee et al.  
 6,773,432 B1 8/2004 Clayman  
 6,827,717 B2 12/2004 Brommersma et al.  
 6,852,108 B2 2/2005 Barry et al.  
 6,852,111 B1 2/2005 Lieber  
 6,860,848 B2 3/2005 Wosnitza et al.  
 6,972,017 B2 12/2005 Smith et al.  
 7,008,420 B2 3/2006 Okada  
 7,037,307 B2 5/2006 Dennis  
 7,104,990 B2 9/2006 Jenkins et al.  
 2001/0009985 A1 7/2001 Durgin et al.  
 2002/0072739 A1 6/2002 Lee et al.  
 2002/0151889 A1 10/2002 Swanson et al.  
 2002/0165540 A1 11/2002 Bales et al.  
 2003/0009166 A1 1/2003 Moutafis et al.  
 2003/0040744 A1 2/2003 Latterell et al.  
 2003/0109870 A1 6/2003 Lee et al.  
 2003/0114850 A1 6/2003 McClurken et al.  
 2003/0125731 A1 7/2003 Smith et al.  
 2003/0144661 A1 7/2003 Brommersma et al.  
 2003/0153909 A1 8/2003 Levinson  
 2003/0176859 A1 9/2003 Levinson  
 2003/0181906 A1 9/2003 Boebel et al.  
 2003/0204188 A1 10/2003 Morrison et al.  
 2003/0212389 A1 11/2003 Durgin et al.  
 2003/0216731 A1 11/2003 Dennis  
 2004/0064139 A1 4/2004 Yossepowitch  
 2004/0106920 A1 6/2004 Jenkins et al.  
 2004/0153059 A1 8/2004 Okada  
 2004/0199159 A1 10/2004 Lee et al.  
 2004/0220564 A1 11/2004 Ho et al.  
 2005/0070889 A1 3/2005 Nobis et al.  
 2005/0085808 A1 4/2005 Nakao  
 2005/0096650 A1 5/2005 Ouchi  
 2005/0119652 A1 6/2005 Vetter et al.  
 2005/0131402 A1 6/2005 Ciarrocca et al.  
 2005/0131403 A1 6/2005 Chang  
 2005/0137591 A1 6/2005 Barry et al.  
 2005/0171531 A1 8/2005 Eliachar et al.  
 2005/0171532 A1 8/2005 Ciarrocca  
 2005/0209590 A1 9/2005 Terakura  
 2005/0222568 A1 10/2005 O'Sullivan  
 2005/0251134 A1 11/2005 Woloszko  
 2005/0283150 A1 12/2005 Moutafis et al.  
 2006/0009759 A1 1/2006 Christian et al.  
 2006/0030846 A1 2/2006 Buehlmann et al.  
 2006/0036234 A1 2/2006 Durgin et al.  
 2006/0052774 A1 3/2006 Garrison et al.  
 2006/0178670 A1 8/2006 Woloszko et al.  
 2007/0198011 A1 8/2007 Sugita  
 2008/0221587 A1 \* 9/2008 Schwartz ..... 606/113

## FOREIGN PATENT DOCUMENTS

DE 25 14 501 A1 10/1976  
 DE 2514501 10/1976  
 DE 2627679 1/1977  
 DE 3423356 6/1986  
 DE 3612646 4/1987  
 DE 8712328 3/1988  
 DE 4303882 8/1994  
 DE 4403252 8/1995  
 DE 19515914 7/1996  
 DE 29616210 1/1997  
 DE 19608716 4/1997  
 DE 19751106 5/1998  
 DE 19751108 5/1999  
 DE 10045375 10/2002  
 DE 19738457 1/2009  
 EP 0 467 501 A 1/1992  
 EP 1159926 12/2001  
 GB 1 490 585 A 11/1977  
 JP 61-501068 9/1984  
 JP 65-502328 3/1992  
 JP 5-5106 1/1993  
 JP 5-40112 2/1993  
 JP 06343644 12/1994  
 JP 07265328 10/1995  
 JP 08056955 3/1996  
 JP 08252263 10/1996  
 JP 09010223 1/1997  
 JP 11-070124 5/1998  
 JP 2000-102545 9/1998  
 JP 11244298 9/1999  
 JP 2000-342599 12/2000  
 JP 2000-350732 12/2000  
 JP 2001-008944 1/2001  
 JP 2001-029356 2/2001  
 JP 2001-128990 5/2001  
 SU 401367 11/1974  
 WO WO 93/21845 A 11/1993  
 WO WO 00/36986 6/2000  
 WO WO 01/54604 8/2001  
 WO WO 2005/110264 11/2005

## OTHER PUBLICATIONS

U.S. Appl. No. 12/176,679, filed Jul. 21, 2008.  
 U.S. Appl. No. 12/192,170, filed Aug. 15, 2008.  
 U.S. Appl. No. 12/192,189, filed Aug. 15, 2008.  
 U.S. Appl. No. 12/192,243, filed Aug. 15, 2008.  
 U.S. Appl. No. 12/195,624, filed Aug. 21, 2008.  
 U.S. Appl. No. 12/200,154, filed Aug. 28, 2008.  
 U.S. Appl. No. 12/200,246, filed Aug. 28, 2008.  
 U.S. Appl. No. 12/200,396, filed Aug. 28, 2008.  
 U.S. Appl. No. 12/200,526, filed Aug. 28, 2008.  
 U.S. Appl. No. 12/204,976, filed Sep. 5, 2008.  
 U.S. Appl. No. 12/210,598, filed Sep. 15, 2008.  
 U.S. Appl. No. 12/211,205, filed Sep. 16, 2008.  
 U.S. Appl. No. 12/233,157, filed Sep. 18, 2008.  
 U.S. Appl. No. 12/236,666, filed Sep. 24, 2008.  
 U.S. Appl. No. 12/237,515, filed Sep. 25, 2008.  
 U.S. Appl. No. 12/237,556, filed Sep. 25, 2008.  
 U.S. Appl. No. 12/237,582, filed Sep. 25, 2008.  
 U.S. Appl. No. 12/244,873, filed Oct. 3, 2008.  
 U.S. Appl. No. 12/246,553, filed Oct. 7, 2008.  
 U.S. Appl. No. 12/248,104, filed Oct. 9, 2008.  
 U.S. Appl. No. 12/248,115, filed Oct. 9, 2008.  
 U.S. Appl. No. 12/254,123, filed Oct. 20, 2008.  
 U.S. Appl. No. 12/331,643, filed Dec. 10, 2008.  
 U.S. Appl. No. 12/336,970, filed Dec. 17, 2008.  
 U.S. Appl. No. 12/352,942, filed Jan. 13, 2009.  
 U.S. Appl. No. 12/353,466, filed Jan. 14, 2009.  
 U.S. Appl. No. 12/353,470, filed Jan. 14, 2009.  
 U.S. Appl. No. 12/353,474, filed Jan. 14, 2009.  
 U.S. Appl. No. 12/363,086, filed Jan. 30, 2009.  
 U.S. Appl. No. 12/410,195, filed Mar. 24, 2009.  
 U.S. Appl. No. 12/411,542, filed Mar. 26, 2009.  
 U.S. Appl. No. 12/419,729, filed Apr. 7, 2009.

- U.S. Appl. No. 12/429,533, filed Apr. 24, 2009.  
 U.S. Appl. No. 12/434,382, filed May 1, 2009.  
 U.S. Appl. No. 12/503,256, filed Jul. 15, 2009.  
 U.S. Appl. No. 12/508,052, filed Jul. 23, 2009.  
 U.S. Appl. No. 12/535,869, filed Aug. 5, 2009.  
 U.S. Appl. No. 12/543,831, filed Aug. 19, 2009.  
 U.S. Appl. No. 12/543,969, filed Aug. 19, 2009.  
 U.S. Appl. No. 12/548,031, filed Aug. 26, 2009.  
 U.S. Appl. No. 12/548,534, filed Aug. 27, 2009.  
 U.S. Appl. No. 12/548,566, filed Aug. 27, 2009.  
 U.S. Appl. No. 12/551,944, filed Sep. 1, 2009.  
 U.S. Appl. No. 12/553,509, filed Sep. 3, 2009.  
 U.S. Appl. No. 12/556,025, filed Sep. 9, 2009.  
 U.S. Appl. No. 12/556,407, filed Sep. 9, 2009.  
 U.S. Appl. No. 12/556,427, filed Sep. 9, 2009.  
 U.S. Appl. No. 12/556,796, filed Sep. 10, 2009.  
 U.S. Appl. No. 12/562,281, filed Sep. 18, 2009.  
 U.S. Appl. No. 12/565,281, filed Sep. 23, 2009.  
 U.S. Appl. No. 12/568,199, filed Sep. 28, 2009.  
 U.S. Appl. No. 12/568,282, filed Sep. 28, 2009.  
 U.S. Appl. No. 12/569,395, filed Sep. 29, 2009.  
 U.S. Appl. No. 12/569,710, filed Sep. 29, 2009.  
 U.S. Appl. No. 12/574,001, filed Oct. 6, 2009.  
 U.S. Appl. No. 12/574,292, filed Oct. 6, 2009.  
 U.S. Appl. No. 12/576,380, filed Oct. 9, 2009.  
 U.S. Appl. No. 12/607,191, filed Oct. 28, 2009.  
 Michael Choti, "Abdominoperineal Resection with the LigaSure Vessel Sealing System and LigaSure Atlas 20 cm Open Instrument"; *Innovations That Work*, Jun. 2003.  
 Chung et al., "Clinical Experience of Sutureless Closed Hemorrhoidectomy with LigaSure" *Diseases of the Colon & Rectum* vol. 46, No. 1 Jan. 2003.  
 Carbonell et al., "Comparison of the Gyrus PlasmaKinetic Sealer and the Valleylab LigaSure Device in the Hemostasis of Small, Medium, and Large-Sized Arteries" *Carolinas Laparoscopic and Advanced Surgery Program*, Carolinas Medical Center, Charlotte, NC; Date: Aug. 2003.  
 Peterson et al. "Comparison of Healing Process Following Ligation with Sutures and Bipolar Vessel Sealing" *Surgical Technology International* (2001).  
 "Electrosurgery: A Historical Overview" *Innovations in Electrosurgery*; Sales/Product Literature; Dec. 31, 2000.  
 Johnson et al. "Evaluation of a Bipolar Electrothermal Vessel Sealing Device in Hemorrhoidectomy" *Sales/Product Literature*; Jan. 2004.  
 E. David Crawford "Evaluation of a New Vessel Sealing Device in Urologic Cancer Surgery" *Sales/Product Literature* 2000.  
 Johnson et al. "Evaluation of the LigaSure Vessel Sealing System in Hemorrhoidectomy" *American College of Surgeons (ACS) Clinica Congress Poster* (2000).  
 Muller et al., "Extended Left Hemicolectomy Using the LigaSure Vessel Sealing System" *Innovations That Work*, Sep. 1999.  
 Kennedy et al. "High-burst-strength, feedback-controlled bipolar vessel sealing" *Surgical Endoscopy* (1998) 12: 876-878.  
 Carus et al., "Initial Experience With the LigaSure Vessel Sealing System in Abdominal Surgery" *Innovations That Work*, Jun. 2002.  
 Heniford et al. "Initial Research and Clinical Results with an Electrothermal Bipolar Vessel Sealer" Oct. 1999.  
 Heniford et al. "Initial Results with an Electrothermal Bipolar Vessel Sealer" *Surgical Endoscopy* (2000) 15:799-801.  
 Herman et al., "Laparoscopic Intestinal Resection With the LigaSure Vessel Sealing System: A Case Report"; *Innovations That Work*, Feb. 2002.  
 Koyle et al., "Laparoscopic Palomo Varicocele Ligation in Children and Adolescents" *Pediatric Endosurgery & Innovative Techniques*, vol. 6, No. 1, 2002.  
 W. Scott Helton, "LigaSure Vessel Sealing System: Revolutionary Hemostasis Product for General Surgery"; *Sales/Product Literature* 1999.  
 LigaSure Vessel Sealing System, the Seal of Confidence in General, Gynecologic, Urologic, and Laparoscopic Surgery; *Sales/Product Literature*; Apr. 2002.  
 Joseph Ortenberg "LigaSure System Used in Laparoscopic 1st and 2nd Stage Orchiopexy" *Innovations That Work*, Nov. 2002.  
 Sigel et al. "The Mechanism of Blood Vessel Closure by High Frequency Electrocoagulation" *Surgery Gynecology & Obstetrics*, Oct. 1965 pp. 823-831.  
 Sampayan et al., "Multilayer Ultra-High Gradient Insulator Technology" *Discharges and Electrical Insulation in Vacuum*, 1998. Netherlands Aug. 17-21, 1998; vol. 2, pp. 740-743.  
 Paul G. Horgan, "A Novel Technique for Parenchymal Division During Hepatectomy" *The American Journal of Surgery*, vol. 181, No. 3, Apr. 2001 pp. 236-237.  
 Olsson et al. "Radical Cystectomy in Females" *Current Surgical Techniques in Urology*, vol. 14, Issue 3, 2001.  
 Palazzo et al. "Randomized clinical trial of Ligasure versus open haemorrhoidectomy" *British Journal of Surgery* 2002, 89, 154-157.  
 Levy et al. "Randomized Trial of Suture Versus Electrosurgical Bipolar Vessel Sealing in Vaginal Hysterectomy" *Obstetrics & Gynecology*, vol. 102, No. 1, Jul. 2003.  
 "Reducing Needlestick Injuries in the Operating Room" *Sales/Product Literature* 2001.  
 Bergdahl et al. "Studies on Coagulation and the Development of an Automatic Computerized Bipolar Coagulator" *J.Neurosurg.*, vol. 75, Jul. 1991, pp. 148-151.  
 Strasberg et al. "A Phase I Study of the LigaSure Vessel Sealing System in Hepatic Surgery" *Section of HPB Surge, Washington University School of Medicine, St. Louis MO*, Presented at AHPBA, Feb. 2001.  
 Sayfan et al. "Sutureless Closed Hemorrhoidectomy: A New Technique" *Annals of Surgery* vol. 234 No. 1 Jul. 2001; pp. 21-24.  
 Levy et al., "Update on Hysterectomy—New Technologies and Techniques" *OBG Management*, Feb. 2003.  
 Dulemba et al. "Use of a Bipolar Electrothermal Vessel Sealer in Laparoscopically Assisted Vaginal Hysterectomy" *Sales/Product Literature*; Jan. 2004.  
 Strasberg et al., "Use of a Bipolar Vessel-Sealing Device for Parenchymal Transection During Liver Surgery" *Journal of Gastrointestinal Surgery*, vol. 6, No. 4, Jul./Aug. 2002 pp. 569-574.  
 Sengupta et al., "Use of a Computer-Controlled Bipolar Diathermy System in Radical Prostatectomies and Other Open Urological Surgery" *ANZ Journal of Surgery* (2001) 71.9 pp. 538-540.  
 Rothenberg et al. "Use of the LigaSure Vessel Sealing System in Minimally Invasive Surgery in Children" *Int'l Pediatric Endosurgery Group (IPEG)* 2000.  
 Crawford et al. "Use of the LigaSure Vessel Sealing System in Urologic Cancer Surgery" *Grand Rounds in Urology* 1999 vol. 1 Issue 4 pp. 10-17.  
 Craig Johnson, "Use of the LigaSure Vessel Sealing System in Bloodless Hemorrhoidectomy" *Innovations That Work*, Mar. 2000.  
 Levy et al. "Use of a New Energy-based Vessel Ligation Device During Vaginal Hysterectomy" *Int'l Federation of Gynecology and Obstetrics (FIGO) World Congress* 1999.  
 Barbara Levy, "Use of a New Vessel Ligation Device During Vaginal Hysterectomy" *FIGO* 2000, Washington, D.C.  
 E. David Crawford "Use of a Novel Vessel Sealing Technology in Management of the Dorsal Venous Complex" *Sales/Product Literature* 2000.  
 Jarrett et al., "Use of the LigaSure Vessel Sealing System for Perihilar Vessels in Laparoscopic Nephrectomy" *Sales/Product Literature* 2000.  
 Crouch et al. "A Velocity-Dependent Model for Needle Insertion in Soft Tissue" *MICCAI* 2005; LNCS 3750 pp. 624-632, Dated: 2005.  
 McLellan et al. "Vessel Sealing for Hemostasis During Pelvic Surgery" *Int'l Federation of Gynecology and Obstetrics FIGO World Congress* 2000, Washington, D.C.  
 McLellan et al. "Vessel Sealing for Hemostasis During Gynecologic Surgery" *Sales/Product Literature* 1999.  
 Int'l Search Report EP 98944778.4 dated Oct. 31, 2000.  
 Int'l Search Report EP 98957771 dated Aug. 9, 2001.  
 Int'l Search Report EP 98958575.7 dated Sep. 20, 2002.  
 Int'l Search Report EP 04013772.1 dated Apr. 1, 2005.  
 Int'l Search Report EP 04027314.6 dated Mar. 10, 2005.  
 Int'l Search Report EP 04027479.7 dated Mar. 8, 2005.  
 Int'l Search Report EP 04027705.5 dated Feb. 3, 2005.  
 Int'l Search Report EP 04752343.6 dated Jul. 20, 2007.  
 Int'l Search Report EP 05002671.5 dated Dec. 22, 2008.

Int'l Search Report EP 05002674.9 dated Jan. 16, 2009.  
Int'l Search Report EP 05013463.4 dated Oct. 7, 2005.  
Int'l Search Report EP 05013895.7 dated Oct. 21, 2005.  
Int'l Search Report EP 05016399.7 dated Jan. 13, 2006.  
Int'l Search Report EP 05017281.6 dated Nov. 24, 2005.  
Int'l Search Report EP 05019130.3 dated Oct. 27, 2005.  
Int'l Search Report EP 05019429.9 dated May 6, 2008.  
Int'l Search Report EP 05020665.5 dated Feb. 27, 2006.  
Int'l Search Report EP 05020666.3 dated Feb. 27, 2006.  
Int'l Search Report EP 05021197.8 dated Feb. 20, 2006.  
Int'l Search Report EP 05021779.3 dated Feb. 2, 2006.  
Int'l Search Report EP 05021780.1 dated Feb. 23, 2006.  
Int'l Search Report EP 05021937.7 dated Jan. 23, 2006.  
Int'l Search Report—extended—EP 05021937.7 dated Mar. 15, 2006.  
Int'l Search Report EP 05023017.6 dated Feb. 24, 2006.  
Int'l Search Report EP 06002279.5 dated Mar. 30, 2006.  
Int'l Search Report EP 06005185.1 dated May 10, 2006.  
Int'l Search Report EP 06006716.2 dated Aug. 4, 2006.  
Int'l Search Report EP 06008515.6 dated Jan. 8, 2009.  
Int'l Search Report EP 06008779.8 dated Jul. 13, 2006.  
Int'l Search Report EP 06014461.5 dated Oct. 31, 2006.  
Int'l Search Report EP 06020574.7 dated Oct. 2, 2007.  
Int'l Search Report EP 06020583.8 dated Feb. 7, 2007.  
Int'l Search Report EP 06020584.6 dated Feb. 1, 2007.  
Int'l Search Report EP 06020756.0 dated Feb. 16, 2007.  
Int'l Search Report EP 06 024122.1 dated Apr. 16, 2007.  
Int'l Search Report EP 06024123.9 dated Mar. 6, 2007.  
Int'l Search Report EP 07 001480.8 dated Apr. 19, 2007.  
Int'l Search Report EP 07 001488.1 dated Jun. 5, 2007.  
Int'l Search Report EP 07 009026.1 dated Oct. 8, 2007.  
Int'l Search Report Extended—EP 07 009029.5 dated Jul. 20, 2007.  
Int'l Search Report EP 07 009321.6 dated Aug. 28, 2007.  
Int'l Search Report EP 07 010672.9 dated Oct. 16, 2007.  
Int'l Search Report EP 07 013779.9 dated Oct. 26, 2007.  
Int'l Search Report EP 07 014016 dated Jan. 28, 2008.  
Int'l Search Report EP 07 015191.5 dated Jan. 23, 2008.

Int'l Search Report EP 07 015601.3 dated Jan. 4, 2008.  
Int'l Search Report EP 07 020283.3 dated Feb. 5, 2008.  
Int'l Search Report EP 07 021646.0 dated Mar. 20, 2008.  
Int'l Search Report EP 07 021646.0 dated Jul. 9, 2008.  
Int'l Search Report EP 07 021647.8 dated May 2, 2008.  
Int'l Search Report EP 08 002692.5 dated Dec. 12, 2008.  
Int'l Search Report EP 08 004655.0 dated Jun. 24, 2008.  
Int'l Search Report EP 08 006732.5 dated Jul. 29, 2008.  
Int'l Search Report EP 08 006917.2 dated Jul. 3, 2008.  
Int'l Search Report EP 08 016539.2 dated Jan. 8, 2009.  
Int'l Search Report EP 09 003813.4 dated Aug. 3, 2009.  
Int'l Search Report EP 09 004491.8 dated Sep. 9, 2009.  
Int'l Search Report EP 09 005575.7 dated Sep. 9, 2009.  
Int'l Search Report EP 09 152267.2 dated Jun. 15, 2009.  
Int'l Search Report EP 09 152898.4 dated Jun. 10, 2009.  
Int'l Search Report EP 09 154850.3 dated Jul. 20, 2009.  
Int'l Search Report EP 09 160476.9 dated Aug. 4, 2009.  
Int'l Search Report EP 09 164903.8 dated Aug. 21, 2009.  
Int'l Search Report PCT/US98/18640 dated Jan. 29, 1999.  
Int'l Search Report PCT/US98/23950 dated Jan. 14, 1999.  
Int'l Search Report PCT/US98/24281 dated Feb. 22, 1999.  
Int'l Search Report PCT/US99/24869 dated Feb. 3, 2000.  
Int'l Search Report PCT/US01/11218 dated Aug. 14, 2001.  
Int'l Search Report PCT/US01/11224 dated Nov. 13, 2001.  
Int'l Search Report PCT/US01/11340 dated Aug. 16, 2001.  
Int'l Search Report PCT/US01/11420 dated Oct. 16, 2001.  
Int'l Search Report PCT/US02/01890 dated Jul. 25, 2002.  
Int'l Search Report PCT/US02/11100 dated Jul. 16, 2002.  
Int'l Search Report PCT/US03/28534 dated Dec. 19, 2003.  
Int'l Search Report PCT/US04/03436 dated Mar. 3, 2005.  
Int'l Search Report PCT/US04/13273 dated Dec. 15, 2004.  
Int'l Search Report PCT/US04/15311 dated Jan. 12, 2005.  
Int'l Search Report PCT/US07/021438 dated Apr. 1, 2008.  
Int'l Search Report PCT/US07/021440 dated Apr. 8, 2008.  
Int'l Search Report PCT/US08/61498 dated Sep. 22, 2008.  
Int'l Search Report PCT/US09/032690 dated Jun. 16, 2009.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8

**FIG. 9****FIG. 10**



## POLYP REMOVAL DEVICE AND METHOD OF USE

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of priority to U.S. Provisional Patent Application Ser. No. 61/063,158, titled "Endoscopic flexible loop for gastrointestinal polypectomy and mucosal resection using LigaSure™ sealing technology", by Wexner et al., filed Jan. 31, 2008, which is incorporated by reference herein.

### BACKGROUND

#### 1. Technical Field

The present disclosure relates to devices and methods for the removal of internal tissue and, more particularly, to snare-type devices including a pair of electrodes for treating tissue prior to excision.

#### 2. Background of Related Art

A polyp is an abnormal growth of tissue projecting from a mucous membrane. A polyp that is attached to the surface of the mucous membrane by a narrow elongated stalk is said to be pedunculated. If no stalk is present, the polyp is said to be sessile. Polyps are commonly found in the colon, stomach, nose, urinary bladder and uterus. Polyps may also form elsewhere in the body where mucous membranes exist, for example, the cervix and small intestine.

The surgical procedure for removing a polyp is generally referred to as a "polypectomy". Polypectomies are generally endoscopic or laparoscopic procedures performed through the oral or anal cavities. When the location of the polyp permits, the polypectomy may be performed as an open procedure. Conventional polypectomies are completed using various apparatus and techniques known in the art.

As noted above, there are two forms of polyps, sessile and pedunculated. The stalkless or sessile polyps are generally removed using electrical forceps. For example, the excess tissue projecting from the mucous membrane is cauterized and torn from the tissue wall. Pedunculated polyps, or those with stalks, tend to be larger with a greater blood supply. The size and shape of pedunculated polyps typically do not lend themselves to being removed using traditional forceps. Unlike sessile polyps, polyps with a stalk cannot simply be grasped in the jaw members of an electrosurgical forceps and be torn from the tissue wall. Instead, the polypectomy is performed using a surgical snare device.

Conventional snare devices are configured with a snare for looping over the distal end of a hanging polyp and tightening securely around the stalk of the polyp. By constricting the snare, and selectively applying energy to the snare, the device may cauterize or seal the polyp at the stalk as the polyp is severed from the tissue wall. Conventional snare devices may be configured for monopolar or bipolar use. Excising a polyp using a conventional snare device typically involves cutting or otherwise separating the polyp from the tissue wall as the snare device is activated and constricted about the stalk of the polyp. In this manner, the polyp is cauterized as the snare passes through the tissue.

### SUMMARY

Disclosed is a device configured for removing polyps. In one embodiment, the polyp removal device includes a tubular member having proximal and distal ends, a snare portion operably extending from within the distal end of the tubular

member and including first and second electrodes configured to seal tissue therebetween, the snare portion further including a cutting member for severing the sealed tissue. The polyp removal device may further include a handle portion operatively extending from within the proximal end of the tubular member. The handle portion may be configured for operable engagement by a user. The cutting member may extend between distal ends of the first and second electrodes.

The polyp removal device may be configured to grasp the stalk of a polyp between the first and second electrodes. The first and second electrodes may be hingedly attached to the cutting member. The snare portion may be configured to be retracted within the tubular member. The snare portion may be retracted within the tubular member upon retraction of the handle portion relative to the base portion.

A system including the polyp removal device may further include an electrosurgical generator. The electrodes may be electrically connected to the electrosurgical generator. The distal end of the tubular member may include a spacer member for preventing the first and second electrodes from contacting one another. Alternatively, at least one of the first and second electrodes may include a spacer mounted thereon for preventing contact between the first and second electrodes.

Also provided is a polyp removal device including a tubular member having proximal and distal ends, a handle portion operatively extending from the proximal end of the tubular member, and a snare portion slidably supported within the lumen of the tubular member and operably extending from the distal end of the tubular member, the snare portion including first and second electrodes operably mounted thereto for sealing tissue therebetween, wherein at least one of the first and second electrodes includes at least one spacer mounted thereon for preventing contact between the first and second electrodes. The snare portion of the polyp removal device may be retractable with the tubular member.

Additionally provided is a method of removing a polyp. The method includes the steps of providing a polyp removal device including, a tubular member having proximal and distal ends, a snare portion slidably supported within the lumen of the tubular member and operably extending from the distal end of the tubular member, the snare portion including first and second electrodes operably mounted thereto for sealing tissue therebetween, wherein at least one of the first and second electrodes includes at least one spacer mounted thereon for preventing contact between the first and second electrodes, extending the snare portion relative to the tubular member, looping the snare portion about a portion of a polyp, retracting the snare portion relative to the tubular member to capture the portion of the polyp between the first and second electrodes, and activating the first and second electrodes.

The method may further include the steps of partially advancing the snare portion relative to the tubular member, retracting the tubular member and the snare portion relative to the polyp and severing the polyp from surrounding tissue.

### BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the present disclosure and, together with the detailed description of the embodiments given below, serve to explain the principles of the disclosure.

FIG. 1 is a partial cross-sectional, top plan view of a polyp removal device according to an embodiment of the present disclosure, shown in a first or extended position;

FIG. 2 is a partial cross-sectional top plan view of the polyp removal device of FIG. 1, shown in a partially retracted position;

FIG. 3 is a partial cross-sectional top plan view of the polyp removal device of FIG. 1, shown in a retracted position;

FIG. 4 is a cross-section end view of the polyp removal device of FIGS. 1-3 taken along line 4-4 of FIG. 3;

FIG. 5 is a partial cross-section top plan view of an alternative embodiment of a polyp removal device according to the present disclosure in a completely retracted position;

FIG. 6 is a partial top plan view of the distal end of the polyp removal device of FIGS. 1-4, in a first or extending position about a polyp;

FIG. 7 is a partial top plan view of the distal end of the polyp removal device of FIG. 6, in a retracted position about a polyp; and

FIG. 8 is a partial top plan view of the distal end of the polyp removal device of FIGS. 6 and 7, in a partially advanced position about a polyp;

FIG. 9 is a partial top plan view of the distal end of the polyp removal device of FIGS. 6-8, as the stalk of the polyp is being severed; and

FIG. 10 is a partial top plan view of another illustrative embodiment of a polyp removal device of the present disclosure, in a retracted position about a polyp.

#### DETAILED DESCRIPTION OF EMBODIMENTS

The foregoing summary, as well as the following detailed description will be better understood when read in conjunction with the appended figures. For the purpose of illustrating the present disclosure, various embodiments are shown. It is understood, however, that the present disclosure is not limited to the precise arrangement and instrumentalities shown.

As shown in the drawings and described throughout the following description, as is traditional when referring to relative positioning on an object, the term "proximal" refers to the end of the apparatus that is closer to the user and the term "distal" refers to the end of the apparatus that is further from the user.

Referring to FIGS. 1-4, an embodiment of the presently disclosed polyp removal device is shown therein and is generally designated as polyp removal device 100. Polyp removal device 100 includes an elongated tubular member 110, a handle portion 120 extending proximally from tubular member 110, and a snare portion or assembly 130 operably engaged with handle portion 120 and extending distally from within elongated tube 110. Polyp removal device 100 may be any suitable length and size for accessing various locations throughout the body. Device 100 may be configured for removal of suitable types of polyps of any size, or may be configured for general mucosal resection or removal of any suitable tissue mass. Preferably, polyp removal device 100 is configured for endoscopic, laparoscopic or transluminal insertion.

Referring initially to FIGS. 1-3, elongated tubular member 110 includes proximal and distal ends 110a, 110b. Proximal end 110a of tubular member 110 is operably coupled to handle portion 120. As will be described in further detail below, handle portion 120 may be integrally formed with tubular member 110. Alternatively, handle portion 120 may be releasably secured to tubular member 110, or may instead be securely affixed to tubular member 110. Tubular member 110 may be flexible, semi-rigid, or rigid and may be constructed of metal, alloy, plastic, polymers, or any other suit-

able material. Distal end 110b of tubular member 110 is configured to slidably receive a proximal end of snare portion 130.

Although the following description of the polyp removal device 100 will be described in the form of a snare-type device, the aspects of the present disclosure may be modified for use with alternative handle configurations, including a pistol grip style device, mechanically and/or remotely actuated handles, other suitable types of devices or handle arrangements. As one example, polyp removal device 100 may be incorporated as a pistol grip style laparoscopic device like some of the LigaSure™ tissue fusion devices sold by Valleylab of Boulder, Colo.

Still referring to FIGS. 1-3, handle portion 120 of polyp removal device 100 includes a base 122 coupled to proximal end 110a of tubular member 110, a connector shaft 124 extending through base 122, and a handle 126 operably coupled to a proximal end 124a of connector shaft 124. In one embodiment, base 122 of handle portion 120 may be securely affixed to proximal end 110a of tubular member 110 using adhesive, bonding, mechanical fasteners, welding or other suitable methods. Alternatively, base 122 may be releasably connected to tubular member 110 using mechanical fasteners, threaded engagement, friction fitting, bayonet connections, or the like. In this manner, snare portion 130 may be removed and replaced through proximal end 110a of tubular member 110. Base 122 of handle portion 120 may instead be integrally formed with proximal end 110a of tubular member 110. Handle 126 is configured for operable engagement by a user. Handle 126 may be knurled or may include a coating for facilitating engagement by a user.

Base 122 of handle portion 120 is further configured for operable engagement with a generator 10. Base 122 defines a connection port 122a for receiving an electrical cord 10a extending from generator 10. Electrical cord 10a extends from connection port 122a through base 122 and is operably coupled to first and second electrodes 134, 136 of snare portion 130. Electrical cord 10a may be directly coupled to first and second electrodes 134, 136. Alternatively, electrical cord 10a may couple with a coupling member 123 mounted to shaft 124. In this manner, coupling member 123 electrically couples generator 10 with first and second electrodes 134, 136 along shaft 124. Generator 10 may include any suitable generator configured to selectively provide energy to electrodes 134, 136. For example, radiofrequency energy, either monopolar or bipolar may be provided to electrodes 134, 136. In other embodiments, ultrasonic, microwave, or laser energy may be provided. Depending on the energy modality utilized, snare 130 and/or electrodes 134, 136 may have to be reconfigured in order to handle the different types of energy.

In an embodiment where radiofrequency energy is utilized, to increase safety, bipolar radiofrequency energy is preferred because the energy will travel between first and second electrodes 134, 136 instead of between the snare 130 and some remote return pad. In one particular embodiment, generator 10 takes the form of a battery-powered generator that is integral with, or releasably coupled to, polyp removal device 100. In this example, electrical cord 10a is not needed. Generator 10 may also be configured to monitor the electrical properties of the tissue maintained between first and second electrodes 134, 136 and signal to the clinician when conditions have been met that are suitable for sealing of tissue.

Still referring to FIGS. 1-3, connector shaft 124 includes an elongated tubular shaft including proximal and distal ends 124a, 124b. Proximal end 124a is configured for operable engagement with handle 126. Handle 126 may be securely affixed, releasably coupled, or integrally formed with proxi-

mal end **124a** of connector shaft **124**. Handle portion **120** may further include a stop member **128** positioned about connector shaft **124** between base **122** and handle **126**. Stop member **128** prevents complete retraction of connector shaft **124** past base **122**. Proximal end **124a** may be configured to securely retain stop member **128**, or instead, may include grooves or indents **128a** for selectively positioning stop member **128** thereabout. In this manner, adjustment of stop member **128** reduces or increases the amount of extension of snare portion **130**. Alternatively, stop member **128** may be configured to selectively engage distal end **124a** of connector shaft **124** through the incorporation of a mechanical fastener or the like (not shown). Distal end **124b** of connector shaft **124** is operably coupled to snare portion **130**. Distal end **124b** may be permanently coupled, releasably coupled or integrally formed with snare portion **130**.

Snare portion **130** includes a snare **132** formed of a loop of rigid or semi-rigid wire or flexible band. Snare **132** may be constructed of metal, polymer or other suitable material. In the illustrated embodiment, snare **132** is non-conductive; however, snare **132** may be conductive or partially conductive. Coupled to snare **132** in any suitable manner near a distal end **130b** of snare portion **130** are first and second electrodes **134**, **136**. As discussed above, first and second electrodes **134**, **136** are electrically coupled to generator **10** to receive electrosurgical energy therefrom. First and second electrodes **134**, **136**, which may be of any suitable construction, each include at least a tissue contacting surface **134c**, **136c**. In some embodiments, first and second electrodes **134**, **136** are each formed from a tissue contacting surface **134c**, **136c** and an insulative body portion. Tissue contacting surfaces **134c**, **136c** may include any configuration suitable for treating tissue, including hatching, grooves and detents (not shown). In one embodiment, generator **10**, first and second electrodes **134**, **136**, and tissue contacting surfaces **134c**, **136c**, are all configured for sealing tissue.

Positioned between first and second electrodes **134**, **136** is a connection member **133**. Distal ends **134b**, **136b** of first and second electrodes **134**, **136**, respectively, are coupled to connection member **133**. First and second electrodes **134**, **136** and connection member **133** are configured such that in a first or extended position, proximal ends **134a**, **136a** of first and second electrodes **134**, **136**, respectively, are substantially spaced from one another. As will be discussed in further detail below, this configuration opens snare **132** to facilitate the looping of snare **132** over a polyp "P" (FIG. 6) and the positioning of first and second electrodes **134**, **136** about stalk "S" of polyp "P".

First and second electrodes **134**, **136** and connection member **133** are further configured such that as proximal end **130a** of snare portion **130** is retracted within distal end **110b** of tubular member **110**, proximal ends **134a**, **136a** of first and second electrodes **134**, **136**, respectively, are approximated towards each other, in the direction of arrows "A" (FIG. 1). In this manner, first and second electrodes **134**, **136** and connection member **133** act like a jaw assembly, thereby compressing stalk "S" of polyp "P" between first and second electrodes **134**, **136**. To prevent first and second electrodes **134**, **136** from contacting one another, distal end **110b** of tubular member **110** may include a spacer member **138** through which snare **132** may extend. Spacer member **138** spans distal end **110b** of tubular member **110** and includes a pair of apertures **138a** through which snare **132** is received. Apertures **138a** are spaced such that upon retraction of proximal end **130a** of snare portion **130** within tubular member **110**, proximal end **134a**, **136a** of first and second electrodes **134**, **136** are approximated towards one another. Apertures **138a** are fur-

ther configured to prevent first and second electrodes **134**, **136** contacting one another. Release of proximal end **130a** of snare portion **130** from within distal end **110b** of tubular member **100** permits proximal ends **134a**, **136a** of first and second electrodes **134**, **136** to approximate away from one another and eventual return to their initial position.

In an alternative embodiment, one or both of first and second electrodes **134**, **136** may include one or more spacers **134d**, **136d** (FIG. 5) formed on respective proximal ends **134a**, **136a**. Spacers **134d**, **136d** are configured to prevent contact between first and second electrodes **134**, **136**.

Connection member **133** extends between first and second electrodes **134**, **136** and is configured to maintain distal ends **134b**, **136b** of first and second electrodes **134**, **136**, in a spaced relationship throughout the tissue excising procedure. As described above, in a first or extended position, proximal ends **134a**, **136a** of first and second electrodes **134**, **136** are maintained in a substantially spaced apart relationship. This configuration facilitates positioning of snare **132**, and first and second electrodes **134**, **136** in particular, about stalk "S" of a polyp "P" (FIG. 6). Distal ends **134b**, **136b** of first and second electrodes **134**, **136** are coupled to connection member **133** in a manner that permits pivoting, hinging, or flexing of first and second electrodes **134**, **136** relative to connection member **133** as snare **132** is constricted about stalk "S" of polyp "P". First and second electrodes **134**, **136** and/or connection member **133** may be formed of flexible material, or may instead include a hinge mechanism or any other suitable configuration capable of permitting first and second electrodes **134**, **136** to pivot, hinge, or flex relative to connection member **133**. In the event that proximal ends **134a**, **136a** of first and second electrodes **134**, **136** are approximated away from one another by the configuration of connection member **133**, snare **132** may provide the spring force to maintain proximal ends **134a**, **136a** substantially spaced apart when polyp removal device **100** is in a first or extended position.

Connection member **133** further includes at least a first sharpened surface **133a**. First sharpened surface **133a** is formed between distal ends **134b**, **136b** of first and second electrodes **134**, **136** and may be configured to sever stalk "S" of polyp "P" after proper sealing of the tissue. In addition, or alternatively, the outer surface of connection member **133** may be sharpened to facilitate excising of polyp "P".

Referring now to FIGS. 1-3 and 6-8, one embodiment of the operation of polyp removal device **100** will be described. Initially, distal end **110b** of tubular member **110** is inserted into a patient. As discussed above, introduction of polyp removal device **100** may be accomplished through an endoscopic or laparoscopic port, or may be inserted transluminally through the mouth or anus. To facilitate insertion of tubular member **110** into the body, in one embodiment (FIG. 5), snare portion **130a** is completely retracted within tubular member **110**.

Once distal end **110b** of tubular member **110** is positioned near a polyp "P" to be removed, snare portion **130** is extended distally by advancing handle **126** of handle portion **120** relative to base **122**. The spring-like configuration between first and second electrodes **134**, **136** and connection member **133** results in proximal ends **134a**, **136a** of first and second electrodes **134**, **136** approximating away from each other as handle **126** is advanced and proximal end **130a** of snare portion **130** is released from tubular member **110**. The separating of proximal ends **134a**, **136a** of first and second electrodes **134**, **136** opens snare **132** and facilitates positioning of snare **132** about stalk "S" of polyp "P". Once snare **132** positioned such that stalk "S" is received between first and second electrodes **134**, **136**, handle **126** may be retracted or, in

the alternative, tubular member 110 may be advanced to constrict snare 132 about stalk "S". As proximal end 130a of snare portion 130 is received within distal end 110b of tubular member 110 through spacer member 138, proximal ends 134a, 136a of first and second electrodes 134, 136 are approximated towards one another, thereby capturing stalk "S" of polyp "P" therebetween. Other methods of approximating first and second electrodes 134, 136 towards one another are contemplated by the present invention. For example, another instrument separate from polyp removal device 100 may be utilized.

Continued retraction of snare portion 130 within tubular member 110 causes first and second electrodes 134, 136 to compress stalk "S" of polyp "P". Once the clinician is satisfied stalk "S" is sufficiently received between first and second electrodes 134, 136, generator 10 may be activated to treat the tissue between first and second electrodes 134, 136. Alternatively, and as discussed above, generator 10 may include a system for monitoring the electrical properties of the tissue between first and second electrodes 134, 136. Once a predetermined condition has been satisfied, preferably, a condition suitable to promote tissue sealing, generator 10 signals to the clinician that the tissue is ready to be sealed, at which point, generator 10 may automatically provide electrosurgical energy to tissue contacting surfaces 134c, 136c, or the clinician may activate generator 10 to provide the energy to seal the tissue. Electrosurgical energy is provided to tissue contacting surfaces 134c, 136c until the tissue of stalk "S" is properly sealed. Electrosurgical energy may be provided at a range of frequencies, over a variable duration, and may be continuous or intermittent, depending of the type of tissue being treated and the thickness of the tissue. Furthermore, the monitoring function may include for a signal to denote that the sealing is finished and that severing of the polyp "P" may take place.

In some embodiments, in order to effectively seal larger vessels (or tissue) two predominant mechanical parameters should be accurately controlled—the pressure applied to the vessel (tissue) and the gap distance between the electrodes—both of which are affected by the thickness of the sealed vessel. More particularly, accurate application of pressure may be important to oppose the walls of the vessel; to reduce the tissue impedance to a low enough value that allows enough electrosurgical energy through the tissue; to overcome the forces of expansion during tissue heating; and to contribute to the end tissue thickness, which is an indication of a good seal. It has been determined that a typical fused vessel wall is preferably between 0.001 and 0.006 inches. Below this range, the seal may shred or tear and above this range the lumens may not be properly or effectively sealed.

With respect to smaller vessels, the pressure applied to the tissue tends to become less relevant, whereas the gap distance between the electrically conductive surfaces becomes more significant for effective sealing. In other words, the chances of the two electrically conductive surfaces touching during activation increases as vessels become smaller.

As mentioned above, at least one electrode, e.g., 134, may include a stop member 134d that limits the movement of the two opposing electrodes 134, 136 relative to one another. Stop member 134d may extend from the tissue contacting surface 134c a predetermined distance according to the specific material properties (e.g., compressive strength, thermal expansion, etc.) to yield a consistent and accurate gap distance "G" during sealing (FIG. 5). In one embodiment, the gap distance between opposing tissue contacting surfaces 134c, 136c during sealing ranges from about 0.001 inches to about 0.006 inches and, preferably, between about 0.002 and

about 0.003 inches. The non-conductive stop members 134d, 136d may be molded onto electrodes 134, 136 (e.g., overmolding, injection molding, etc.), stamped onto electrodes 134, 136 or deposited (e.g., deposition) onto electrodes 134, 136. For example, one technique involves thermally spraying a ceramic material onto the surface of the electrodes 134, 136 to form the stop members 134d, 136d, respectively. Several thermal spraying techniques are contemplated that involve depositing a broad range of heat resistant and insulative materials on various surfaces to create stop members 134d, 136d for controlling the gap distance between electrically conductive surfaces 134c, 136c.

It has also been found that the pressure range for assuring a consistent and effective seal may be between about 3 kg/cm<sup>2</sup> to about 16 kg/cm<sup>2</sup> and, preferably, within a working range of 7 kg/cm<sup>2</sup> to 13 kg/cm<sup>2</sup>. Manufacturing an instrument that is capable of providing a closure pressure within this working range has been shown, in some embodiments, to be effective for sealing arteries, tissues and other vascular bundles.

As can be appreciated, controlling the compressive force between with first and second electrodes 134, 136 as snare portion 130 is retracted may facilitate and assure consistent, uniform and accurate closure pressure about the tissue within the desired working pressure range of about 3 kg/cm<sup>2</sup> to about 16 kg/cm<sup>2</sup> and, preferably, about 7 kg/cm<sup>2</sup> to about 13 kg/cm<sup>2</sup>. By controlling the intensity, frequency and duration of the electrosurgical energy applied to the tissue, the user can either cauterize, coagulate/desiccate, seal and/or simply reduce or slow bleeding.

In one embodiment, by controlling the force applied to handle 126, the resulting tension in snare portion 130 may be adjusted, which, in turn, regulates the overall pressure between electrodes 134, 136 to within the above-identified desired sealing range. A sensor 125 may be employed to accomplish this purpose and may be mechanically coupled to handle portion 120 and/or snare portion 130. A visual or audible indicator (not shown) may be operably coupled to handle portion 120, snare portion 130 and/or sensor 125 to provide visual, audible or tactile feed back to the user to assure that the clamping pressure is within the desired range prior to activation of the instrument.

Alternatively, handle portion 120 may incorporate a spring mechanism 125a configured to prevent excessive force being applied to snare portion 130, thereby preventing overcompression of the tissue between first and second electrodes 134, 136. Spring mechanism 125a may include a compression spring (not shown) that deforms once the force applied to handle 126 exceeds the force necessary to accomplish effective sealing between first and second electrodes 134, 136. In an alternative embodiment, snare portion 130 may instead be advanced and retracted through the rotation of handle 126. In this manner, handle portion 120 may include a torque mechanism, e.g., torque wrench or the like, (not shown) which is precisely set to measure the torque (rotational force) applied to snare portion 130 so the closure pressure between electrodes 134, 136 will fall within the desired pressure range.

Once the tissue of stalk "S" is sealed, handle 126 is partially advanced to extend a length of snare portion 130 from tubular member 110, thereby approximating proximal ends 134a, 136a of first and second electrodes, respectively, away from each other and exposing sealed stalk "S" to first sharpened surface 133a of connection member 133. While maintaining snare portion 130 relative to tubular member 110, tubular member 110 is retracted relative to polyp "P", thereby causing the engagement of stalk "S" with first sharpened

surface 133a of connection member 133. Continued retraction of tubular member 110 causes the complete severing of stalk "S" (see FIG. 9).

When using polyp removal device 110, the likelihood of excessive bleeding is greatly reduced because the tissue is completely sealed prior to being cut. Using polyp removal device 110 further reduces the likelihood of creating an open wound that is susceptible to infection. In addition, the utilization of bipolar energy to seal a polyp or other tissue is safer than monopolar, e.g., because of less thermal and energy spread, thereby reducing the likelihood of perforations.

With reference now to FIG. 10, an alternative embodiment of the present disclosure is shown generally as polyp removal device 200. Polyp removal device 200 is substantially similar to polyp removal device 100 and will, therefore, only be described as relates to the differences therebetween. Snare portion 230 includes first and second electrodes 234, 236 and a connection member 233. Extending between first and second electrodes 234, 236 and connection member 233 are extension members 235, 237, respectively. Extension member 235, 237 permit first and second electrodes 234, 236 to be spaced further apart from one another in a second or sealing condition. In this manner, polyp removal device 200 may be used to excise larger polyps having a larger stalk.

Various changes in form, detail and operation of the polyp removal devices of the present disclosure may be made without departing from the spirit and scope of the present disclosure.

What is claimed is:

1. A tissue removal system comprising:  
a tubular member having proximal and distal ends;  
a snare portion operably extending from the distal end of the tubular member and including first and second electrodes configured to treat tissue therebetween, the snare portion further including a cutting member having a sharpened surface positioned between the first and second electrodes for severing the treated tissue.
2. The tissue removal system of claim 1, further comprising a handle portion operatively coupled to the proximal end of the tubular member.
3. The tissue removal system of claim 2, wherein the handle portion is configured for operable engagement by a user.
4. The tissue removal system of claim 1, wherein the cutting member is configured to only cut when pulled in a proximal direction.
5. The tissue removal system of claim 1, wherein the tissue is a polyp and the first and second electrodes are configured to grasp a stalk of a polyp.

6. The tissue removal system of claim 2, wherein the first and second electrodes are hingedly attached to the cutting member.

7. The tissue removal system of claim 1, wherein the snare portion is configured to be retracted within the tubular member.

8. The tissue removal system of claim 1, wherein the first and second electrodes are each formed from a tissue contacting surface and an insulative body portion.

9. The tissue removal system of claim 1, further including an electrosurgical generator.

10. The tissue removal system of claim 9, wherein the first and second electrodes are electrically coupled to the electrosurgical generator and the generator is configured to deliver energy to the first and second electrodes in a bipolar manner.

11. The tissue removal system of claim 1, wherein the distal end of the tubular member includes a spacer member for preventing the first and second electrodes from contacting one another.

12. The tissue removal system of claim 1, wherein at least one of the first and second electrodes includes a spacer member mounted thereon for preventing contact between the first and second electrodes.

13. A tissue removal system comprising:  
a generator configured to generate and deliver energy to a tissue removal device, the tissue removal device comprising:  
a tubular member having proximal and distal ends;  
a handle portion operatively extending from the proximal end of the tubular member; and  
a snare portion slidably supported within the tubular member and configured to extend from the distal end of the tubular member, the snare portion including first and second electrodes operably mounted thereto for receiving energy from the generator for treating tissue therebetween;  
a cutting member having a sharpened surface positioned between the first and second electrodes and configured to sever the treated tissue; and  
wherein at least one of the first and second electrodes includes at least one spacer mounted thereon for preventing contact between the first and second electrodes.
14. The tissue removal device of claim 13, wherein the snare portion is formed from a non-conductive material.
15. The tissue removal system of claim 13, wherein the energy is selected from the group consisting of radiofrequency, ultrasonic, microwave, and laser.

\* \* \* \* \*

专利名称(译)	息肉清除装置和使用方法		
公开(公告)号	<a href="#">US8328803</a>	公开(公告)日	2012-12-11
申请号	US12/363086	申请日	2009-01-30
[标]申请(专利权)人(译)	柯惠有限合伙公司		
申请(专利权)人(译)	泰科医疗集团LP		
当前申请(专利权)人(译)	COVIDIEN LP		
[标]发明人	REGADAS F SERGIO P		
发明人	REGADAS, F. SERGIO P.		
IPC分类号	A61B18/18 A61B17/24		
CPC分类号	A61B17/32056 A61B18/14 A61B17/221 A61B17/32 A61B18/18 A61B2018/141 A61B2018/00345 A61B2018/00404 A61B2018/00482 A61B2018/00619 A61B2018/1407 A61B18/20		
助理审查员(译)	李，翁		
优先权	61/063158 2008-01-31 US		
其他公开文献	US20100036375A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

#### 摘要(译)

提供了一种用于移除组织（例如息肉）的装置和系统，其包括具有近端和远端的管状构件，从管状构件的远端内可操作地延伸的圈套部分，并包括构造在其间处理组织的第一和第二电极，圈套部分还包括用于切断处理过的组织的切割构件。组织去除装置还可包括手柄部分，其可操作地从管状构件的近端内延伸。手柄部分可以配置成可由使用者操作，并且切割构件可以在第一和第二电极的远端之间延伸。

