



US008840625B2

(12) **United States Patent**
Adams et al.

(10) **Patent No.:** **US 8,840,625 B2**
(45) **Date of Patent:** **Sep. 23, 2014**

(54) **SYSTEMS FOR PERFORMING
GYNECOLOGICAL PROCEDURES WITH
CLOSED VISUALIZATION LUMEN**

(75) Inventors: **Ronald D. Adams**, Holliston, MA (US);
William H. Gruber, Southborough, MA
(US); **Kevin G. Connors**, Wellesley, MA
(US); **Geoffrey B. Pardo**, Cambridge,
MA (US); **James Daniel Cole**, Wayland,
MA (US); **J. Christopher Flaherty**,
Topsfield, MA (US)

(73) Assignee: **Hologic, Inc.**, Bedford, MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 72 days.

(21) Appl. No.: **11/852,121**

(22) Filed: **Sep. 7, 2007**

(65) **Prior Publication Data**

US 2008/0097468 A1 Apr. 24, 2008

Related U.S. Application Data

(60) Provisional application No. 60/852,842, filed on Oct.
18, 2006.

(51) **Int. Cl.**

A61B 17/42 (2006.01)
A61B 17/12 (2006.01)
A61B 19/00 (2006.01)
A61B 18/22 (2006.01)
A61B 17/32 (2006.01)
A61B 17/00 (2006.01)
A61B 18/02 (2006.01)
A61B 17/02 (2006.01)
A61B 18/14 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/42** (2013.01); **A61B 2019/5217**
(2013.01); **A61B 19/24** (2013.01); **A61B 18/22**
(2013.01); **A61B 2017/320024** (2013.01); **A61B**
17/12099 (2013.01); **A61B 2017/00867**
(2013.01); **A61B 17/12045** (2013.01); **A61B**
18/02 (2013.01); **A61B 17/12136** (2013.01);
A61B 2017/4216 (2013.01); **A61B 17/0218**

(2013.01); **A61B 2217/007** (2013.01); **A61B**
18/1485 (2013.01); **A61B 2217/005** (2013.01);
A61B 2017/4233 (2013.01); **A61B 2017/320028**
(2013.01); **A61B 2017/00026** (2013.01); **A61B**
17/32002 (2013.01); **A61B 2019/5276**
(2013.01); **A61B 2017/4225** (2013.01)
USPC **606/119**; 606/193; 604/22; 604/514;
604/515; 604/517

(58) **Field of Classification Search**

USPC 606/119, 193; 604/22, 514, 515, 517
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,849,002 A 8/1958 Oddo et al.
3,561,429 A 2/1971 Jewett

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0010650 5/1980
EP 0044877 2/1982

(Continued)

OTHER PUBLICATIONS

U.S. Publication No. 2008-0245371 A1, including its prosecution
history, and the Office Actions.

(Continued)

Primary Examiner — Victor Nguyen


Assistant Examiner — Kevin Everage

(74) *Attorney, Agent, or Firm* — Vista IP Law Group LLP

(57) **ABSTRACT**

Systems, methods, apparatus and devices for performing
improved gynecologic and urologic procedures are disclosed.
An access sheath is provided with at least one lumen, and a
lens attached thereto. The various embodiments enable pro-
cedures to be performed outside the hospital setting, such as
in a doctor's office or clinic.

20 Claims, 17 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,188,952 A *	2/1980	Loschilov et al.	606/79	5,899,915 A	5/1999	Saadat	
4,198,981 A	4/1980	Sinnreich		5,902,251 A	5/1999	vanHooydonk	
4,203,444 A	5/1980	Bonnell et al.		5,904,649 A	5/1999	Andrese	
4,246,902 A	1/1981	Martinez		5,904,680 A	5/1999	Kordis et al.	
4,261,360 A	4/1981	Perez		5,911,739 A	6/1999	Kordis et al.	
4,598,698 A	7/1986	Siegmund		5,916,198 A	6/1999	Dillow	
4,598,710 A	7/1986	Kleinberg et al.		5,954,714 A	9/1999	Saadat et al.	
4,650,462 A	3/1987	DeSatnick et al.		5,954,715 A	9/1999	Harrington et al.	
4,673,393 A	6/1987	Suzuki et al.		5,961,444 A	10/1999	Thompson	
4,700,694 A	10/1987	Shishido		5,961,532 A	10/1999	Finley et al.	
4,729,763 A	3/1988	Henrie		5,964,755 A	10/1999	Edwards	
4,848,323 A	7/1989	Marijnissen et al.		5,964,777 A	10/1999	Drucker	
4,895,565 A	1/1990	Hillstead		5,972,000 A	10/1999	Beyar et al.	
4,949,718 A	8/1990	Neuwirth et al.		6,002,968 A	12/1999	Edwards	
4,998,527 A	3/1991	Meyer		6,032,673 A	3/2000	Savage et al.	
5,078,725 A	1/1992	Enderle et al.		6,039,748 A	3/2000	Savage et al.	
5,104,377 A	4/1992	Levine		6,042,590 A	3/2000	Sporri et al.	
5,108,414 A	4/1992	Enderle et al.		6,068,626 A	5/2000	Harrington et al.	
5,125,903 A	6/1992	McLaughlin et al.		6,080,129 A	6/2000	Blaisdell	
5,163,433 A	11/1992	Kagawa et al.		6,086,544 A	7/2000	Hibner et al.	
5,163,949 A	11/1992	Bonutti		6,117,070 A	9/2000	Akiba	
5,183,031 A	2/1993	Rossoff		6,126,635 A	10/2000	Simpson et al.	
5,195,541 A	3/1993	Obenchain		6,139,570 A	10/2000	Saadat et al.	
5,201,756 A	4/1993	Horzowski et al.		6,149,632 A	11/2000	Landuyt	
5,222,971 A	6/1993	Willard et al.		6,159,209 A	12/2000	Hakky	
5,246,016 A	9/1993	Lieber et al.		6,190,357 B1	2/2001	Ferrari et al.	
5,259,836 A	11/1993	Thurmond et al.		6,216,043 B1	4/2001	Swanson et al.	
5,269,798 A	12/1993	Winkler		6,216,044 B1	4/2001	Kordis	
5,275,609 A	1/1994	Pingleton et al.		6,221,007 B1	4/2001	Green	
5,304,115 A	4/1994	Pflueger et al.		6,293,952 B1 *	9/2001	Brosens et al.	606/119
5,320,091 A	6/1994	Grossi et al.		6,319,272 B1	11/2001	Brenneman et al.	
5,334,183 A	8/1994	Wuchinich		6,328,686 B1	12/2001	Kovac	
5,361,752 A	11/1994	Moll et al.		6,378,524 B1	4/2002	Jones	
5,377,668 A	1/1995	Ehmsen et al.		6,387,110 B1	5/2002	Drucker et al.	
5,392,765 A	2/1995	Muller		6,395,012 B1	5/2002	Yoon et al.	
5,402,772 A	4/1995	Moll et al.		6,428,498 B2	8/2002	Uflacker	
5,423,844 A	6/1995	Miller		6,428,539 B1	8/2002	Baxter et al.	
5,443,470 A	8/1995	Stern et al.		6,432,116 B1	8/2002	Callister et al.	
5,450,843 A	9/1995	Moll et al.		6,440,061 B1	8/2002	Wenner et al.	
5,458,112 A	10/1995	Weaver		6,458,076 B1	10/2002	Pruitt	
5,484,401 A	1/1996	Rodriguez et al.		6,471,644 B1	10/2002	Sidor, Jr.	
5,503,626 A	4/1996	Goldrath		6,494,909 B2	12/2002	Greenhalgh	
5,505,730 A	4/1996	Edwards		6,537,207 B1 *	3/2003	Rice et al.	600/121
5,514,091 A	5/1996	Yoon		6,547,784 B1	4/2003	Thompson et al.	
5,522,790 A	6/1996	Moll et al.		6,565,557 B1	5/2003	Sporri et al.	
5,540,658 A	7/1996	Evans et al.		6,605,037 B1	8/2003	Moll et al.	
5,575,788 A	11/1996	Baker et al.		6,607,545 B2	8/2003	Kammerer et al.	
5,601,583 A	2/1997	Donahue et al.		6,612,977 B2	9/2003	Staskin et al.	
5,602,449 A	2/1997	Krause et al.		6,626,940 B2	9/2003	Crowley	
5,618,296 A	4/1997	Sorensen et al.		6,638,235 B2	10/2003	Miller et al.	
5,624,395 A	4/1997	Mikhail et al.		6,673,101 B1	1/2004	Fitzgerald et al.	
5,624,399 A	4/1997	Ackerman		6,682,477 B2	1/2004	Boebel et al.	
5,656,013 A	8/1997	Yoon		6,709,667 B1	3/2004	Lowe et al.	
5,695,511 A	12/1997	Cano et al.		6,742,236 B1	6/2004	Dion et al.	
5,697,940 A	12/1997	Chu et al.		6,763,833 B1	7/2004	Khara et al.	
5,709,664 A	1/1998	Vandenbroek et al.		6,802,825 B2	10/2004	Ackerman et al.	
5,725,525 A	3/1998	Kordis		6,805,131 B2	10/2004	Kordis	
5,730,725 A	3/1998	Yoon		6,812,204 B1	11/2004	McHale et al.	
5,738,629 A	4/1998	Moll et al.		6,821,274 B2	11/2004	McHale et al.	
5,741,287 A	4/1998	Alden et al.		6,827,703 B1	12/2004	Ackerman	
5,743,850 A	4/1998	Moll et al.		6,858,024 B1	2/2005	Berg et al.	
5,743,851 A	4/1998	Moll et al.		6,896,682 B1	5/2005	McClellan et al.	
5,749,845 A	5/1998	Hildebrand et al.		6,951,569 B2	10/2005	Nohilly et al.	
5,749,889 A	5/1998	Bacich et al.		6,960,203 B2	11/2005	Xiao et al.	
5,755,731 A	5/1998	Grinberg		6,979,332 B2	12/2005	Adams	
5,782,800 A	7/1998	Yoon		6,997,925 B2	2/2006	Maguire et al.	
5,800,493 A	9/1998	Stevens et al.		7,037,321 B2	5/2006	Sachdeva et al.	
5,807,401 A	9/1998	Grieshaber et al.		7,070,559 B2	7/2006	Adams et al.	
5,823,945 A	10/1998	Moll et al.		7,105,003 B2	9/2006	Hildebrandt	
5,843,046 A	12/1998	Motisi et al.		7,150,713 B2	12/2006	Shener et al.	
5,855,549 A	1/1999	Newman		7,189,206 B2	3/2007	Quick et al.	
5,857,585 A	1/1999	Tolkoff et al.		7,226,459 B2	6/2007	Cesarini et al.	
5,865,728 A	2/1999	Moll et al.		7,226,460 B2	6/2007	Gibson et al.	
5,873,815 A	2/1999	Kerin et al.		7,249,602 B1	7/2007	Emanuel	
5,891,134 A	4/1999	Goble et al.		7,458,940 B2	12/2008	Miller	
				7,462,187 B2	12/2008	Johnston et al.	
				7,468,060 B2	12/2008	Utlely et al.	
				7,481,817 B2	1/2009	Sauer	
				7,491,212 B2	2/2009	Sikora et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

7,497,833	B2	3/2009	Miller	
7,510,563	B2	3/2009	Cesarini et al.	
7,588,545	B2	9/2009	Cohen et al.	
7,611,474	B2	11/2009	Hibner et al.	
7,666,200	B2	2/2010	Heisler	
7,749,254	B2	7/2010	Sobelman et al.	
7,753,857	B2	7/2010	Hibner	
7,763,033	B2	7/2010	Gruber et al.	
7,785,250	B2	8/2010	Nakao	
7,806,835	B2	10/2010	Hibner et al.	
7,938,804	B2	5/2011	Fischvogt	
2001/0008575	A1	7/2001	Rho et al.	
2001/0029371	A1	10/2001	Kordis	
2001/0041900	A1	11/2001	Callister et al.	
2001/0047183	A1	11/2001	Privitera et al.	
2001/0056222	A1	12/2001	Rudischhauser et al.	
2002/0010457	A1	1/2002	Duchon et al.	
2002/0013601	A1	1/2002	Nobles et al.	
2002/0020417	A1	2/2002	Nikolchev	
2002/0068934	A1	6/2002	Edwards et al.	
2002/0082634	A1	6/2002	Kammerer et al.	
2003/0050639	A1	3/2003	Yachia et al.	
2003/0083684	A1	5/2003	Cesarini et al.	
2003/0114875	A1	6/2003	Sjostrom	
2003/0153940	A1	8/2003	Nohilly et al.	
2004/0002702	A1	1/2004	Xiao et al.	
2004/0002703	A1	1/2004	Xiao et al.	
2004/0049211	A1	3/2004	Tremulis et al.	
2004/0116955	A1	6/2004	Foltz et al.	
2004/0127932	A1	7/2004	Shah	
2004/0204682	A1	10/2004	Smith	
2004/0225187	A1	11/2004	Kamrava et al.	
2004/0255957	A1	12/2004	Caffèrta	
2004/0267157	A1	12/2004	Miller et al.	
2005/0027245	A1	2/2005	Sachdeva et al.	
2005/0045183	A1	3/2005	Callister et al.	
2005/0080318	A1	4/2005	Squicciarini	
2005/0090849	A1	4/2005	Adams	
2005/0107663	A1	5/2005	Saadat et al.	
2005/0113715	A1	5/2005	Schwindt et al.	
2005/0113836	A1	5/2005	Lozier et al.	
2005/0113857	A1	5/2005	Nohilly et al.	
2005/0177168	A1	8/2005	Brunnett et al.	
2005/0182397	A1	8/2005	Ryan	
2005/0222598	A1 *	10/2005	Ho et al.	606/171
2005/0222663	A1 *	10/2005	Simpson et al.	623/1.11
2005/0234437	A1 *	10/2005	Baxter et al.	606/15
2005/0240206	A1	10/2005	Sjostrom	
2005/0245960	A1	11/2005	Grundeman	
2005/0250933	A1	11/2005	Binz et al.	
2005/0250993	A1	11/2005	Jaeger	
2005/0267408	A1	12/2005	Grandt et al.	
2005/0277970	A1	12/2005	Norman et al.	
2005/0277975	A1	12/2005	Saadat et al.	
2005/0288551	A1	12/2005	Callister et al.	
2006/0004436	A1	1/2006	Amarant et al.	
2006/0009798	A1	1/2006	Callister et al.	
2006/0036138	A1	2/2006	Heller et al.	
2006/0047185	A1	3/2006	Shener et al.	
2006/0064074	A1	3/2006	Mallaby	
2006/0089658	A1	4/2006	Harrington	
2006/0189972	A1	8/2006	Grossman	
2006/0200042	A1	9/2006	Weikel, Jr. et al.	
2006/0206136	A1	9/2006	Sachdeva et al.	
2006/0212055	A1	9/2006	Karabey et al.	
2006/0229647	A1	10/2006	Spitz et al.	
2006/0241344	A1 *	10/2006	Wilk	600/114
2006/0241586	A1	10/2006	Wilk	
2006/0241630	A1	10/2006	Brunnett et al.	
2006/0293560	A1	12/2006	Nguyen et al.	
2007/0010845	A1	1/2007	Gong et al.	
2007/0161957	A1	7/2007	Guenther et al.	
2007/0225744	A1	9/2007	Nobles et al.	
2007/0227544	A1	10/2007	Swann et al.	
2007/0232859	A1	10/2007	Secrest et al.	

2008/0015621	A1	1/2008	Emanuel
2008/0051758	A1	2/2008	Rioux et al.
2008/0058588	A1	3/2008	Emanuel
2008/0058595	A1	3/2008	Snoke et al.
2008/0065125	A1	3/2008	Olson
2008/0147012	A1	6/2008	Rome
2008/0183192	A1	7/2008	Saal et al.
2008/0234715	A1	9/2008	Pesce et al.
2008/0245371	A1	10/2008	Gruber et al.
2008/0249366	A1	10/2008	Gruber et al.
2008/0249553	A1	10/2008	Gruber et al.
2008/0262302	A1	10/2008	Azarbarzin et al.
2008/0281224	A1	11/2008	Johnson
2008/0319342	A1	12/2008	Shabaz et al.
2009/0005739	A1	1/2009	Hart et al.
2009/0048485	A1	2/2009	Heisler
2009/0054728	A1	2/2009	Trusty
2009/0118699	A1	5/2009	Uitley et al.
2009/0137927	A1	5/2009	Miller
2009/0177217	A1	7/2009	Keller
2009/0198149	A1	8/2009	Privitera et al.
2009/0270895	A1	10/2009	Churchill et al.
2009/0270896	A1	10/2009	Sullivan et al.
2009/0270897	A1	10/2009	Adams et al.
2009/0270898	A1	10/2009	Chin et al.
2010/0063360	A1	3/2010	Harrington et al.
2010/0152533	A1	6/2010	Mark
2010/0152758	A1	6/2010	Mark et al.
2010/0152761	A1	6/2010	Mark
2010/0160818	A1	6/2010	Haberstich et al.
2010/0179480	A1	7/2010	Sugiki et al.
2010/0185153	A1	7/2010	Sugiki et al.
2010/0198242	A1	8/2010	Heisler
2010/0274194	A1	10/2010	Sobelman et al.
2010/0312053	A1	12/2010	Larsen
2011/0034943	A1	2/2011	Churchill et al.
2011/0077674	A1	3/2011	Sullivan et al.

FOREIGN PATENT DOCUMENTS

EP	0141589	5/1985
EP	0366292	5/1990
EP	0449663	10/1991
EP	0531710	10/1991
EP	0539125	4/1993
EP	782427	2/1996
EP	853468	5/1996
EP	0812573	12/1997
EP	1259180	9/2001
EP	1635695	1/2005
FR	2701401	8/1994
WO	WO 94/07445	4/1994
WO	WO 94/11052	5/1994
WO	WO 95/10326	4/1995
WO	WO 95/32011	11/1995
WO	WO 96/15741	5/1996
WO	WO 98/18520	5/1998
WO	WO 98/29068	7/1998
WO	WO 98/51244	11/1998
WO	WO 99/60960	12/1999
WO	WO 00/00100	1/2000
WO	WO 00/12832	3/2000
WO	WO 00/66031	11/2000
WO	WO 01/08575	2/2001
WO	WO03/037194	5/2003
WO	WO 2005/009504	2/2005
WO	WO 2005/048862	6/2005
WO	WO 2005/074844	8/2005
WO	WO 2005/104966	11/2005
WO	WO 2009/111717	9/2009
WO	WO 2010/127171	11/2010
WO	WO 2010/127174	11/2010

OTHER PUBLICATIONS

U.S. Publication No. 2008-0249553 A1, including its prosecution history, and the Office Actions.

U.S. Publication No. 2008-0249366 A1, including its prosecution history, and the Office Actions.

(56)

References Cited

OTHER PUBLICATIONS

International Search Report and Written Opinion Received in PCT/US07/83982 Dated May 20, 2008.
 International Search Report and Written Opinion Received in PCT/US08/59493 Dated Apr. 4, 2008.
 International Search Report and Written Opinion Received in PCT/US07/83833 Dated Jun. 5, 2008.
 International Search Report and Written Opinion Received in PCT/US08/59504 Dated Sep. 4, 2008.
 International Search Report and Written Opinion Received in PCT/US08/59503 Dated Sep. 5, 2008.
 U.S. Appl. No. 11/852,151, including its prosecution history, and the Office Actions, Gruber, et al.
 U.S. Appl. No. 11/936,003, including its prosecution history, and the Office Actions, Gruber, et al.
 U.S. Appl. No. 11/951,853, including its prosecution history, and the Office Actions, Gruber, et al.
 U.S. Appl. No. 11/852,116, including its prosecution history, and the Office Actions, Gruber, et al.
 U.S. Appl. No. 11/852,142, including its prosecution history, and the Office Actions, Gruber, et al.
 U.S. Appl. No. 11/852,200, including its prosecution history, and the Office Actions, Gruber, et al.
 U.S. Appl. No. 11/923,357, including its prosecution history, and the Office Actions, Gruber, et al.
 U.S. Appl. No. 11/923,482, including its prosecution history, and the Office Actions, Gruber, et al.
 International Search Report Received and Written Opinion in PCT/US07/79449 Dated January 28, 2008.
 U.S. Appl. No. 12/432,691, including its prosecution history, and the Office Actions, Adams, et al.
 U.S. Appl. No. 12/432,702, including its prosecution history, and the Office Actions, Chin, et al.
 U.S. Appl. No. 12/432,686, including its prosecution history, and the Office Actions, Sullivan, et al.

U.S. Appl. No. 12/432,675, including its prosecution history, and the Office Actions, Churchill, et al.

U.S. Appl. No. 12/432,647, including its prosecution history, and the Office Actions, Litscher, et al.

"When mechanical dilation is necessary, a few prerequisites can make a difference", OBG Management, Apr. 2009, vol. 4, p. 29-33.

U.S. Appl. No. 12/917,351, including its prosecution history, and the Office Actions, Feb. 10, 2011, Churchill, et al.

U.S. Appl. No. 12/956,974, including its prosecution history, and the Office Actions, May 19, 2011, Adams, et al.

U.S. Appl. No. 12/972,233, including its prosecution history, and the Office Actions, Mar. 31, 2011, Sullivan, et al.

U.S. Appl. No. 12/565,620, including its prosecution history, and the Office Actions, Apr. 8, 2010, Adams, et al.

U.S. Appl. No. 12/842,775, including its prosecution history, and the Office Actions, Mar. 3, 2011, Gruber, et al.

U.S. Publication No. 2009-0270897 A1, including its prosecution history, and the Office Actions.

U.S. Publication No. 2009-0270896 A1, including its prosecution history, and the Office Actions.

U.S. Publication No. 2009-0270898 A1, including its prosecution history, and the Office Actions.

International Search Report and Written Opinion dated Jan. 11, 2011, in PCT Application No. PCT/US10/56416 in 14 pages.



International Search Report and Written Opinion dated Jul. 6, 2010, PCT Application No. PCT/US2010/033047 in 13 pages.


International Search Report and Written Opinion dated Jun. 29, 2010, PCT Application No. PCT/US2010/033050 in 7 pages.

Mark H. Emanuel, "The Intra Uterine Morcellator: A New Hysteroscopic Operating Technique to Remove Intrauterine Polyps and Myomas," Journal of Minimally Invasive Gynecology, vol. 12, p. 62-66 (2005).

"When mechanical dilation is necessary, a few prerequisites can make a difference", OBG Management, Apr. 2009, vol. 21, No. 4, p. 29-33.

* cited by examiner








FIG. 2A





FIG. 2B




FIG. 2C




FIG. 3A




FIG. 4




FIG. 5




FIG. 5A





FIG. 6






FIG. 7A






FIG. 7C








FIG. 9




FIG. 9A





FIG. 9B








FIG. 11




FIG. 12






FIG. 12A



*FIG. 13*

SYSTEMS FOR PERFORMING GYNECOLOGICAL PROCEDURES WITH CLOSED VISUALIZATION LUMEN

PRIORITY INFORMATION

This application claims priority under 35 U.S.C. §119 to U.S. Provisional Patent Application Ser. No. 60/852,842, filed Oct. 18, 2006, the disclosure of which is incorporated in its entirety herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to systems, methods, apparatus and devices for performing one or more gynecologic and urologic procedures. More particularly, devices and combinations of devices provide simplified use and enhanced safety to support performance of various diagnostic and therapeutic procedures in the doctor's office setting.

2. Description of the Related Art

Currently available gynecologic products are difficult to use and often have limited use and functionality. Treatment of gynecologic disorders and ailments is most often performed in a hospital and bears a large cost due to the setting and the support personnel required. Treatment options and modalities are also limited, such that the patient may not be offered the best option for her particular condition.

There is therefore a need for improved gynecologic systems, methods and devices that simplify use, offer improved functionality and enhanced safety.

SUMMARY OF THE INVENTION

There is provided in accordance with one aspect of the present invention, an intrauterine access and procedure system with direct visualization. The system comprises an elongate tubular sheath, having a proximal end, a distal end and at least one lumen extending therethrough. The sheath is adapted for transcervical access to the uterus.

A visualization element is adapted to extend through the sheath, for visualizing a site within the uterus. A tissue removal element is adapted to extend through the sheath, for removing tissue from the site. At least one fluid port is provided, for permitting introduction of fluid through the sheath and into the uterus. A lens is mounted to the sheath, to permit visualization of the site.

The outside diameter of the sheath is generally less than about 9 mm, often less than about 7 mm, and preferably less than about 6 mm. The visualization element may comprise a lens, or an ultrasound transducer. The sheath may comprise at least one radiopaque marker.

The tissue removal element may comprise a tissue cutter, such as an oscillating cutter or a rotating cutter. The tissue removal element may alternatively comprise an acoustic generator, a tissue morcellator, or an ablation element.

The system may additionally comprise a pull wire, for deflecting the distal end of the sheath. The system may additionally comprise an inflatable balloon, a tissue penetrating assembly, a stabilization device, a drug delivery assembly or a volume occupying device.

The system may additionally comprise a tissue distension element, such as an expandable basket.

Further features and advantages of the present invention will become apparent to those of skill in the art in view of the

detailed description of preferred embodiments which follows, when considered together with the attached drawings and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate various embodiments of the present invention, and, together with the description, serve to explain the principles of the invention. In the drawings:

FIG. 1 illustrates a perspective view of an exemplary embodiment of an introducer consistent with the present invention;

FIG. 1A illustrates a side sectional view of another exemplary embodiment of an introducer consistent with the present invention, wherein the introducer includes a pre-dilating balloon and is shown being deployed in the cervix of a patient;

FIG. 1B illustrates a side sectional view of another exemplary embodiment of an introducer consistent with the present invention, wherein the introducer includes a drug delivery element and a strain gauge and is shown deployed in the cervix of a patient;

FIG. 2 illustrates a side sectional view of an exemplary embodiment of a system of the present invention, wherein an introducer includes a radiopaque ring and is shown deployed in the cervix, and a tissue removal device with a side-saddle camera has been advanced through the introducer and into the uterus of a patient;

FIG. 2A illustrates a side sectional view of the distal end of a tissue removal device consistent with the present invention, wherein the device includes an oscillating cutter;

FIG. 2B illustrates a side sectional view of the distal end of another tissue removal device consistent with the present invention, wherein the device includes a rotating cutter;

FIG. 2C illustrates a side sectional view of the distal end of a tissue removal device and side-saddle camera, consistent with the present invention;

FIG. 3 illustrates a side sectional view of another exemplary embodiment of a system consistent with the present invention, wherein an introducer is shown deployed in the cervix of a patient, and a subsonic treatment device has been advanced through the introducer and into the uterus;

FIG. 3A illustrates a side view of the distal end of the subsonic treatment device of FIG. 3;

FIG. 4 illustrates a side view of another exemplary embodiment of an introducer consistent with the present invention, wherein the introducer includes a removable needle assembly and an inflatable balloon near its distal end;

FIG. 5 illustrates a side sectional view of another exemplary embodiment of a system consistent with the present invention, wherein an introducer is shown deployed through the vaginal wall of a patient and a treatment device has been advanced through the introducer to a location outside the uterus and proximate a fibroid in the uterine wall;

FIG. 5A illustrates a side sectional view of another exemplary embodiment of a system consistent with the present invention, wherein an introducer is shown deployed through the vaginal wall of a patient, a treatment device including a magnet in its distal portion has been advanced through the introducer to a location outside the uterus and a stabilizing magnetic device has been advanced into the uterus proximate a fibroid;

FIG. 6 illustrates a side sectional view of an exemplary method consistent with the present invention, wherein a first treatment device has been advanced through the cervix and a

3

fallopian tube and is accessing the outside of a fallopian tube, and a second treatment device has been advanced through the cervix and a fallopian tube and is accessing the outside of the uterus proximate a fibroid;

FIG. 7 illustrates a side sectional view of an exemplary drug delivery device consistent with the present invention, wherein the device is deployed in the cervix of the patient and integral needles are deployed into the cervical wall;

FIG. 7A illustrates a side sectional view of the drug delivery device of FIG. 7, wherein the needles are in the retracted position;

FIG. 7B illustrates a side sectional view of the drug delivery device of FIG. 7, wherein the needles are in an deployed position;

FIG. 7C illustrates a side sectional view of another exemplary drug delivery device consistent with the present invention, wherein the device includes a vacuum source and suction ports for attracting tissue toward a drug delivery element;

FIG. 8 illustrates a side sectional view of another exemplary drug delivery device consistent with the present invention, wherein the device is deployed in the cervix of the patient and integral exit holes allow fluid to pass into the cervical wall;

FIG. 8A illustrates a side view of the distal end of the drug delivery device of FIG. 8, wherein the device is deployed over an occluding guidewire;

FIG. 8B illustrates a side view of the proximal end of the drug delivery device of FIG. 8A.

FIG. 9 illustrates a side sectional view of another exemplary drug delivery device consistent with the present invention, wherein the device is deployed in the cervix of the patient, an integral balloon has been inflated and integral exit holes in the balloon allow fluid to pass into the cervical wall;

FIG. 9A illustrates a side view of the distal end of the drug delivery device of FIG. 9, wherein the device is deployed over a guidewire and the balloon is inflated;

FIG. 9B illustrates a side view of the proximal end of the drug delivery device of FIG. 9A.

FIG. 10 illustrates a side sectional view of an exemplary scaffolding device consistent with the present invention, wherein the device has been deployed in the uterus of a patient;

FIG. 10A illustrates a side sectional view of the scaffolding device of FIG. 10, wherein a control shaft has been near fully extended and a scaffold is partially deployed;

FIG. 10B illustrates a perspective view of an exemplary scaffolding device consistent with the present invention, wherein the scaffolding assembly comprises two resiliently biased arms;

FIG. 10C illustrates a perspective view of an exemplary scaffolding device consistent with the present invention, wherein the scaffolding assembly includes three resiliently biased arms;

FIG. 10D illustrates a side sectional view of the scaffolding device of FIG. 10B, wherein the scaffolding device has been inserted through an introducer of the present invention and has its distal portion in the uterus of a patient;

FIG. 11 illustrates a side sectional view of an exemplary visualization apparatus consistent with the present invention, wherein a camera device, a first light source and a second light source have been advanced into the uterus of a patient;

FIG. 12 illustrates a side sectional view of another exemplary system consistent with the present invention, wherein a uterine volume occupying device and a treatment device have each been advanced into the uterus of a patient;

FIG. 12A illustrates a side view of an exemplary wire shaping device consistent with the present invention;

4

FIG. 13 illustrates a flow chart of an exemplary method of dilation, consistent with the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

To facilitate an understanding of the invention, a number of terms are defined immediately herebelow.

As used herein, the term “trans-vaginal-wall” refers to devices or procedures which enter the vaginal opening, travel down the vaginal canal, and exit through the vaginal wall proximal to the cervix.

As used herein, the term “trans-cervical” refers to devices or procedures which enter the vaginal opening, travel down the vaginal canal, pass through the cervical canal and enter the uterus.

As used herein, the term “trans-uterine” refers to devices or procedures which pass through the wall of the uterus.

As used herein, the term “drug” refers to all drugs and other agents that may be included in the systems, methods apparatus and devices of the present invention; either by including the drug into a coating or an integral reservoir of a component; or by provided to the patient through other means such as via a lumen and exit port which is in fluid communication with a supply of the drug such as an infusion pump or syringe. Drugs shall include not only pharmaceutical compounds such as anesthetics, anti-thrombotics, thrombotics, anti-bacterial drugs and chemotherapeutics, but also other agents such as ionic solutions, hormones, genes, vitamins, clotting agents, naturally occurring substances such as extracts from plants, and any other compound or agent applicable to the procedures contained herein.

As used herein, “patient” refers to any animal, such as a mammal and preferably a human. Specific examples of “patients” included but are not limited to: individuals requiring medical assistance and healthy individuals.

Systems, methods, apparatus and devices consistent with the invention provide improved diagnostic and therapeutic gynecologic and urologic procedures and outcomes. The simplified, safer use provided allows these procedures to be performed in locations such as a doctor’s office or health clinic, eliminating the high costs associated with a hospital setting. Specific devices of the present invention reduce the pain encountered by the patient during and after the associated diagnostic or therapeutic procedure. The devices and apparatus provide to the clinician operator precision in both manipulation and device actions, and often allow reversibility of one or more steps of the procedure without undesirable consequence. Inadvertent tissue trauma is avoided with blunting of tips and other tissue-contacting surfaces. Simplified mechanisms, miniaturized geometries and improved methods reduce procedure times and trauma, and also the associated infection risk and blood loss. Intravasation, the entry of foreign matter in a blood vessel, is also reduced.

An introducer is provided which can be placed into the patient to provide a stable, working platform to support simplified introduction of one or more diagnostic, treatment or other devices. The introducer includes an elongate shaft with one or two or more internal lumens. The proximal end of the shaft may include one or more access ports, such as fluid access ports and device entry ports, as well as one or more controls such as buttons, knobs or levers used to manipulate the introducer or activate a mechanical or electronic module of the introducer. The introducer preferably accepts devices comprising elongate shafts, sequentially or simultaneously. The introducer system also permits the administration and/or removals of fluid from the patient, such as fluid administered

to the uterus, while also providing fluid stasis or maintaining stasis to a maximum pressure at which fluid can be automatically evacuated. The introducer system also permits the administration of one or more drugs, such as anesthetic drugs or clotting agents. The introducer system may be introduced through the cervix and into the uterus, through the vaginal wall to a location outside the uterus (trans-vaginal-wall), or through another entry path to a specific anatomical location within the patient.

Systems are provided that enable and/or perform diagnostic, therapeutic or combined diagnostic and therapeutic gynecologic and urologic procedures. The systems preferably include one or more of the introducer, a treatment device, a tissue removal device, a subsonic treatment device, a drug delivery device, a dilating device, a vaginal-wall-crossing device, a scaffolding device, a volume occupying device, a stabilizing device, a visualization apparatus and a navigation apparatus, all of the present invention, and other devices applicable to gynecological procedures. The systems of the present invention are simple to use, and provide reduced risks while enhancing outcomes.

Treatment Devices are provided which allow a clinician to perform, individually or in combination with additional devices, one or more gynecologic and urologic procedures. The treatment devices provided include but are not limited to: devices which remove, denature or otherwise treat undesired tissue; devices which modify the structure of a vessel such as a fallopian tube or blood vessel occlusion device; drug delivery devices; and other therapeutic or diagnostic devices. The treatment devices preferably include an elongate shaft, and the shaft may include one or more internal lumens. The proximal end of the shaft may include one or more access ports, such as fluid access ports and device entry ports. A handle may be included on the proximal end, the handle including one or more controls such as buttons, knobs or levers used to manipulate the elongate shaft or activate a mechanical or electronic module of the device. The treatment devices of the present invention may additionally or alternatively perform a diagnostic function. These treatment devices may provide multiple functions, such as diagnostic or treatment functions including applying a tamponade force to bleeding tissue or distending tissue such as uterine wall tissue.

Treatment devices include tissue removal devices which can be inserted through the introducer of the present invention and be subsequently operated to remove tissue. Tissue removal devices are often arranged with vacuum assemblies which provide a vacuum proximate a tissue removal element and evacuate the tissue to be removed to a site outside of the patient's body.

Treatment devices include subsonic treatment devices which also can be inserted through the introducer of the present invention and subsequently deliver subsonic energy to disrupt or otherwise modify tissue such as a fibroid.

Treatment devices include drug delivery devices which can be placed into the patient and controllably deliver a drug to a specific area of tissue or space, such as the vaginal wall, cervix, uterus, uterine wall or fallopian tube as well as a specific fibroid, polyp, tumor or other tissue mass. These drug delivery devices may provide additional functions, such as diagnostic or treatment functions including applying a tamponade force to bleeding tissue or distending tissue such as uterine wall tissue.

Dilating devices are provided which can be used to dilate the cervix, a penetration tract in the vaginal wall, or other tissue. The dilating devices preferably include an elongate shaft, and the shaft may include one or more internal lumens. The proximal end of the shaft may include one or more access

ports, such as fluid access ports and device entry ports. A handle may be included on the proximal end, the handle including one or more controls such as buttons, knobs or levers used to manipulate the elongate shaft or activate a mechanical or electronic module of the device. Specific embodiments include "smart" dilation systems and methods which measure one or more parameters (e.g. device parameters such as strain or pressure or patient parameters such as EKG, EEG, blood pressure or respiration). One or more algorithms are applied to the measured parameters and used to control one or more dilation parameters such as rate, force and magnitude. These dilation devices may be integrated into another device, such as an introducer, a treatment device, or other device of the present invention. These dilation devices may provide additional or alternative functions, such as diagnostic or treatment functions including applying a tamponade force to bleeding tissue, distending tissue such as uterine wall tissue, or delivering a drug to tissue. The dilating devices of the present invention are typically configured to dilate to a diameter less than 9 mm, preferably between 5 and 8 mm, and more preferably between 2 and 5 mm. The dilating devices of the present invention are typically dilated to a pressure not to exceed 300 psi (e.g. balloon dilation pressure), and preferably less than 150 psi.

Vaginal-wall-crossing devices are provided that permit safe introduction of one or more devices, such as the introducer of the present invention, from inside the vaginal canal, through the vaginal wall to various anatomical locations including but not limited to: the outer wall of the uterus; the outer wall of the fallopian tubes; the ovaries; intra-abdominal locations; other locations and combinations thereof. The crossing devices preferably include an elongate shaft, and the shaft may include one or more internal lumens. The proximal end of the shaft may include one or more access ports, such as fluid access ports and device entry ports. A handle may be included on the proximal end, the handle including one or more controls such as buttons, knobs or levers used to manipulate the elongate shaft or activate a mechanical or electronic module of the device. In a preferred embodiment, a guidewire is first placed through the vaginal wall, and one or more devices are placed over-the-wire. These crossing devices may provide additional or alternative functions, such as diagnostic or treatment functions including delivering a drug to tissue.

Distension devices are provided which can be introduced into a space, such as the uterus, and apply a force to tissue. The distension devices include without limitation, for example, scaffolding devices or the like. The distension devices are preferably inserted through the introducer of the present invention. The distension devices preferably include an elongate shaft, and the shaft may include one or more internal lumens. The proximal end of the shaft may include one or more access ports, such as fluid access ports and device entry ports. A handle may be included on the proximal end, the handle including one or more controls such as buttons, knobs or levers used to manipulate the elongate shaft or activate a mechanical or electronic module of the device. These distension devices may provide additional or alternative functions, such as diagnostic or treatment functions including applying a tamponade force to bleeding tissue or delivering a drug to tissue. These distension devices are preferably inserted into the uterus of a patient such that the scaffolding assembly preferably distends the uterine cavity to a volume equivalent to that which would be attained via a liquid distension media at a pressure of at least 40 mm of HG but not greater than 100 mm HG and preferably approximating 70 mm Hg.

Volume Occupying devices are provided which can be introduced into a space, such as the uterus, and occupy space within the uterus. The volume occupying devices are preferably inserted through the introducer of the present invention. The volume occupying devices preferably include an elongate shaft, and the shaft may include one or more internal lumens. The proximal end of the shaft may include one or more access ports, such as fluid access ports and device entry ports. A handle may be included on the proximal end, the handle including one or more controls such as buttons, knobs or levers used to manipulate the elongate shaft or activate a mechanical or electronic module of the device. These volume occupying devices provide the function of taking up space in a cavity, such as taking up space in the uterus to reduce the amount of fluid delivered to the uterus in a diagnostic or therapeutic procedure. These volume occupying devices may provide additional or alternative functions, such as diagnostic or treatment functions including applying a tamponade force to bleeding tissue, distending tissue such as uterine wall tissue, or delivering a drug to tissue.

Stabilizing devices are provided which are used to stabilize one or more separate devices, such as a treatment device of the present invention. Stabilizing devices may include magnets which attract a corresponding magnet integral to the separate device such as to position a treatment device proximate to tissue to be treated. The stabilizing devices preferably include an elongate shaft, and the shaft may include one or more internal lumens. The proximal end of the shaft may include one or more access ports, such as fluid access ports and device entry ports. A handle may be included on the proximal end, the handle including one or more controls such as buttons, knobs or levers used to manipulate the elongate shaft or activate a mechanical or electronic module of the device such as an electromagnet located in the distal portion of the shaft. These stabilizing devices may provide additional or alternative functions, such as diagnostic or treatment functions including applying a tamponade force to bleeding tissue, distending tissue such as uterine wall tissue, or delivering a drug to tissue.

Visualization apparatus are provided which provide enhanced imaging of target anatomical locations within the patient. The apparatus include one or more of: miniaturized cameras; infrared cameras; deployable light sources; stabilizing mechanisms; image stabilizing modules and processing; and improved and cost-reduced displays (e.g. a laptop screen display). The visualization apparatus preferably include one or more devices comprising an elongate shaft, and the shaft may include one or more internal lumens. The proximal end of the shaft may include one or more access ports, such as fluid access ports and device entry ports. A handle may be included on the proximal end, the handle including one or more controls such as buttons, knobs or levers used to manipulate the elongate shaft or activate a mechanical or electronic module of the device. These visualization apparatus may provide additional or alternative functions, such as diagnostic or treatment functions including applying a tamponade force to bleeding tissue, distending tissue such as uterine wall tissue, or delivering a drug to tissue.

Navigating apparatus are provided which enable a clinician to navigate one or more diagnostic or therapeutic devices to perform a gynecologic procedure. The navigation apparatus preferably include one or more of: an electromagnetic (EM) beacon and/or receiver; a light emitter and/or detector; and a magnetic source and/or a detector. The navigation apparatus preferably include one or more devices comprising an elongate shaft, and the shaft may include one or more internal lumens. The proximal end of the shaft may include one or

more access ports, such as fluid access ports and device entry ports. A handle may be included on the proximal end, the handle including one or more controls such as buttons, knobs or levers used to manipulate the elongate shaft or activate a mechanical or electronic module of the device. These navigation apparatus may provide additional or alternative functions, such as diagnostic or treatment functions including applying a tamponade force to bleeding tissue, distending tissue such as uterine wall tissue, or delivering a drug to tissue.

Shape-modifying wires are provided which are slidably received by one or more lumens of a device of the present invention, such as a morcellating or other treatment device used to access and treat a fibroid. Shapes on the one or more shaping wires can bias the elongate shaft of the device, such as at a distal portion, to a pre-determined shape. In a preferred embodiment, multiple shaping wires with varied shapes are provided to accommodate different procedures and/or access to different anatomical locations.

Numerous devices of the present invention include an elongate shaft, similar in construction to shafts used in laparoscopic and percutaneous devices. The shafts may be manufactured in a "lay up" process including multiple layers of similar or dissimilar materials, such as layers of flexible biocompatible material separated by a braided material such as metal wire or plastic filament. The construction is chosen to provide adequate column strength and torqueability to access the desired anatomical locations and perform the desired actions. Each shaft preferably has a blunt or otherwise atraumatic distal tip. The shafts may include one or more lumens, such as a lumen configured to slidably receive an elongate device such as a treatment catheter or guidewire, a lumen configured to allow fluid delivery and/or fluid sampling or removal; an inflation lumen configured to allow inflation of a balloon; a mechanical linkage lumen configured to slidably receive a cable such as to transmit force through the shaft (e.g. from a lever on a handle on the proximal end of the shaft); a lumen configured to slidably receive a shaping wire of the present invention; other lumens and combinations thereof.

The elongate shafts of the present invention may include a reinforced section such as a section located at the portion of the shaft that, when inserted into the body, is in proximity to the cervix. The reinforced section can provide the function of preventing collapse of an internal lumen of the shaft (enhanced radial strength) as well as prevent undesired perforation out of the shaft and into tissue such as cervical tissue. The reinforced section may comprise the braiding process described hereabove, and may be provided along a majority of length of the shaft, or a small portion. The shaft may include variable stiffness along its length, and may allow the stiffness to be adjusted, such as through the insertion of a stiffening wire, or by pressurizing an internal (blind) lumen of the shaft. The shaft may include along its length one or more clinician inflatable balloons, such as compliant or non-compliant nylon or PET balloons configured to dilate, deflect the device or neighboring tissue; deliver a drug; or perform another function. The elongate shafts of the present invention are typically less than 9 mm in diameter, and preferably between 5 to 8 mm in diameter, and more preferably between 2 and 5 mm in diameter.

The elongate shafts of the present invention may include clinician controlled deflection means, preferably one or more pull wires attached at their proximal end to a control in a handle on the proximal end of the shaft, and attached on their distal end to a portion of the shaft, such as a distal portion of the shaft. Advancement and retraction of the pull wire causes a portion of the shaft to deflect, such as to bring a treatment element of the present invention in proximity to tissue to be

treated. The shafts may further include one or more internal conduits, such as wires or optical fibers which do not need to be advanced or retracted. These conduits may be embedded in the wall of the shaft, fixed to an internal lumen, or sandwiched between layers present in a layered construction. Wires can be used to transmit electrical signals or energy, in either direction in the shaft. Fiber optic cables can be used to transmit light energy (e.g. laser energy) or signals (e.g. images from a lens), in either direction in the shaft. In the preferred embodiment, the shafts of the present invention include a handle on their proximal end, and the handle includes one or more controls to activate one or more portions of the device. In another preferred embodiment, a "kill-switch" control is included to allow the clinician to quickly stop an ongoing action.

The shafts and other components of the devices of the present invention are constructed of biocompatible materials. The devices may be configured for one-time use or be resterilizable. The materials include medical grade metals, plastics and other materials. Shaped memory metals such as Nitinol and shaped memory polymers may be used to provide controllable material properties or meet specific elasticity and/or resiliency requirements. The shafts and other components may include one or more coatings, such as coatings selected from the group consisting of: anti-infective drugs, anti-thrombogenic drugs; clotting agents; chemotherapeutics; anesthetics such as lidocaine; other drugs; and combinations thereof. Alternatively, the shafts and other components may include drug delivery means, such as drug reservoirs (e.g. connected to a supply of drug internal or external to the device) or drug depots (e.g. containing a supply of drug). One or more markers may be integral to a component of the device, such as a marker selected from the group consisting of: visible and non-visible markers; radiopaque markers; magnetic markers; ultrasonically reflective markers; and combinations thereof.

A functional element may be mounted to the shafts or other components of the devices of the present invention. These functional elements may include a sensor or transducer and/or another functional element such as a camera or marker as described hereabove. Applicable sensors include but are not limited to: electrodes such as electrical mapping electrodes; temperature sensors; pressure sensors; strain gauges; accelerometers; force sensing resistors; position sensors such as linear or rotary encoders; magnetic sensors such as hall effect transistors; optical sensors such as phototransistors; physiologic sensors such as EKG; EEG; respiration; blood sensors such as a blood gas sensors such as an O₂ saturation sensors; glucose sensors; blood pressure sensors; pH sensors; other physiologic sensors; and combinations thereof. Applicable transducers include but are not limited to: magnets; electrodes such as radiofrequency electrodes; heat generators; cryogenic generators; force or space-occupying generators such as an expandable balloon or solenoid; drug delivery elements such as iontophoretic elements; sound transducers such as acoustic transducers, ultrasound transducers and subsonic transducers; radiation sources; light sources such as visible or infrared light sources configured to provide a beacon for navigation and ultraviolet light sources configured to treat infection or kill bacteria; visualization elements such as cameras, lenses, fiber optics and ultrasound crystals; other functional elements; and combinations thereof. Functional elements may further include elements to cause dissection of tissue, such as blunt dissection projections and fluid jets.

The systems, methods, apparatus and devices of the present invention are applicable to patients with one or more of the following conditions:

presence of fibroids, polyps, tumors, blood clots or other undesired tissue (e.g. fibroids attached to the wall of the uterus, in the uterine wall or on the outside of the uterus); endometriosis and other abnormal bleeding; uterine prolapse; ectopic pregnancy; fertility issues (e.g. inability to conceive or desire to avoid pregnancy); cancer such as carcinoma of the cervix or uterus; infection; pain; and other disorders.

The systems, methods, apparatus and devices of the present invention are applicable to performing one or more therapeutic or diagnostic gynecologic and urologic procedures. These procedures may be performed inside or outside the uterus. Applicable primary procedures include but are not limited to:

fibroid, poly, tumor, blood clot, biopsy and other tissue removal, treatment or denaturing (e.g. removal, treatment or denaturing via mechanical means such as cutting, morcellating, lysing, excising or scraping; ablation such as radiofrequency, laser or cryogenic ablation; and/or removal of blood supply such as via associated vascular occlusion);

fertility procedures (e.g. in-vivo fertilization; tubal opening; egg harvesting and sperm delivery);

sterilization procedures (e.g. fallopian tube occlusion such as internal or external occlusion of the fallopian tube; procedures which detect and/or confirm fallopian tube occlusion; and fallopian tube removal or partial removal);

endometrial ablation or resection (e.g. providing a tamponade force; delivering a clotting or other agent; delivering a fluid such as a fluid at an elevated temperature; providing ablation energy such as radiofrequency; ultrasonic, laser or cryogenic energy);

vascular modification (e.g. procedures that change blood flow such as flow reducing or increasing procedures including vascular stenting and occlusion)

intra-abdominal procedures (e.g. oophorectomy; tubal ligation; tubal resection; endometrial ablation; subserosal fibroid removal and ovarian cyst removal) and

drug delivery (e.g. delivery of anesthetics; clotting agents; chemotherapeutics; occlusive agents, bulking agents and other agents).

In the performance of one or more gynecologic and urologic procedures, such as one or more of the procedures listed above, the systems, methods, apparatus and devices of the present invention may be used to perform one or more additional procedures, including but not limited to:

mechanical or gel distension of organs (e.g. bladder, lung, stomach, bowel, esophagus, oral cavity, rectum, nasal sinus, Eustachian tubes, heart, gall bladder, artery, vein, ducts)

administering of anesthetics (e.g. lidocaine injections proximate the cervix, vaginal wall or other tissue; and injections to otherwise reduce pain associated with cervical dilation; fallopian tube manipulation and vaginal wall penetration)

administering of a muscle relaxant, cervical pre-dilation and softening (e.g. a procedure performed a day or more in advance of a subsequent gynecological procedure) dilation (e.g. cervical dilation and dilation of a penetration tract through the vaginal wall)

tissue dissection (e.g. blunt dissection; liquid-jet (e.g. saline) dissection; and energy assisted dissection; and dissection utilizing Tumescence solution comprising an

11

anesthetic such as lidocaine and a vasoconstrictor such as epinephrine in order to dissect along normal facial planes and reduce nerve damage)
 vaginal wall and other conduit or organ penetration (e.g. penetration comprising an penetrating needle and guidewire passed through the needle)
 vessel occlusion or constriction (e.g. occlusion or constriction of a blood vessel such as the uterine artery; a fallopian tube; or the urethra)
 implant delivery (e.g. an occlusive device such as occlusive intra-luminal material or a vessel clip; a drug delivery implant such as a drug-loaded gel or foam; a radioactive seed; or suture)
 radiation treatment (e.g. temporary or permanent implantation of a radioactive seed or other source of radiation such as a liquid radionuclide)
 delivery of energy (e.g. electromagnetic energy such as radiofrequency energy; chemical energy; heat or cooling energy; mechanical energy such as vibrational energy; sound energy such as subsonic, acoustic and ultrasound energies; radiation; and combinations thereof)
 visualization of internal anatomy (e.g. via an endoscope or a camera or lens integral to a device shaft) and
 guidance of one or more devices (e.g. via a visible beacon such as a light emitted from the uterus, fallopian tubes or other anatomical location or via an electromagnetic beacon such as an antenna receiving a high frequency signal).

The systems, methods, apparatus and devices of the present invention may provide and/or utilize various means and routes of access to an internal location within the patient. Routes of access include but are not limited to:

trans-cervical (defined above);
 trans-vaginal-wall (defined above);
 trans-uterine (defined above);
 trans-vesicle;
 trans-urethral;
 laparoscopic, and other routes.

The devices and apparatus of the present invention may comprise an elongate shaft that includes one or more lumens such as to slidably receive one or more separate devices also comprising an elongate shaft. The device lumens may be configured to support over-the-wire insertion over a standard guidewire, or alternatively a side-car mounted near the distal end of the shaft may be provided to support monorail (also known as rapid exchange) insertion. The device lumens, such as the introducer of the present invention, may be sized and be otherwise configured to slidably receive one or more devices including but not limited to:

treatment device, tissue removal device, subsonic treatment device, drug delivery device, scaffolding device, volume occupying device, stabilizing device, visualization apparatus and navigation apparatus, a shape-modifying wire; all of the present invention;

ablation device;

ligating, lysing and/or excising device;

tissue removing device (e.g. a morcellator; scraper; cutter; or grabber);

tissue cutting device (e.g. an advancable blade cutting device);

tissue dissector (e.g. a blunt dissector; a fluid-jet dissector; or an energy delivery dissector);

suture and knot tying device;

snaring device (e.g. a device used to snare a guidewire or blood clot);

12

visualization device (e.g. a hysteroscope or other endoscope);

navigation device;

drug delivery device (e.g. a iontophoresis catheter); and
 vaginal crossing device (e.g. a needle based device which places a guidewire from inside the vaginal canal and through the vaginal wall).

The device lumens may be sized and include access elements such as luer fittings to attach to drug delivery devices such as syringes and infusion pumps. The device elongate shaft may be sized and otherwise configured to be passed through one or more devices including but not limited to:

dilators (e.g. sequential dilators or balloon dilators), and sheaths and introducers

Reference will now be made in detail to the present embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

Referring now to FIG. 1, a preferred embodiment of an introducer consistent with an embodiment of the present invention is illustrated. As shown in FIG. 1, introducer 100a includes an elongate, hollow shaft, sheath 110, which is configured to have distal end 111 (preferably with an atraumatic leading edge) be inserted into the body of a patient, such as through the cervix and into the uterus, to provide a working channel to introduce tools through a lumen of sheath 110 and into the uterus. In an alternative embodiment, distal end 111 of sheath 110 is placed into the vaginal opening of a patient, and manipulated to penetrate through the vaginal wall (such as by advancing over a pre-existing guidewire penetrating the vaginal wall), such as to provide a working channel to introduce tools through a lumen of sheath 110 to a location outside the uterus. Sheath 110 may be configured to slidably receive two or more devices, independently or simultaneously. In an alternative embodiment, sheath 110 includes multiple lumens along its length, each lumen configured to slidably receive a separate device. Sheath 110 may remain in place throughout the subsequent procedure, or for a portion of the procedural steps. Sheath 110 may be repositioned during the procedure, such as to advance or withdraw sheath 110.

Sheath 110 is manufactured from medical-grade plastics, metals and other biocompatible material such as a sheath including a Teflon outer layer. One or more portions of sheath 110 may be radiopaque, such as by inclusion of a barium sulfate in plastic material or inclusion of one or more metal portions which provide sufficient radiopacity. In a preferred embodiment, distal end 111 includes a radiopaque marker. Sheath 110 is preferably of a braided construction as has been described hereabove, and includes a reinforced portion, reinforcement 115 (e.g. consisting of a metal or plastic braided patch or embedded tube as has been described hereabove) near its distal end, configured to maintain the patency of one or more lumens within sheath 110 when external pressure is exerted (e.g. cervical or vaginal wall pressure) on that portion of sheath 110. Alternatively or additionally, reinforcement 115 may be configured to prevent a device inserted into sheath 110 from inadvertently puncturing out the side of sheath 110, such as to prevent a puncture that would damage cervical or other patient tissue unexpectedly. On the proximal end of sheath 110 is device insertion port 120, which provides access to an internal lumen of sheath 110 and has been configured to maintain fluid stasis with or without a device inserted through it. Port 120 preferably has an "X" cut opening through one or more diaphragms that maintain that fluid seal. The thicknesses of the diaphragms and the materials chosen preferably maintain pressure up to a predetermined level (e.g. 50 mm

Hg) after which fluid is automatically evacuated to prevent damage to the patient's internal tissue.

Mechanically attached and in fluid communication with device insertion port 120 are input valve 121 and output valve 122, each of which includes a standard luer connector for attachment to standard fluid infusion lines. Input valve 121 and output valve 122 may include simple one-way valves or more sophisticated valves that open (in either direction or both) at pre-determined pressures. In combination with port 120, fluid infusion and fluid evacuation means (not shown but preferably gravity driven or pump driven fluid movement means), can be attached to port 121 and port 122 and control the level of fluid introduced into the patient via introducer 100a. In a preferred embodiment, sheath 110 is a single lumen and the fluid is introduced through that lumen. In an alternative embodiment, sheath 110 includes multiple lumens and fluid can be delivered or evacuated through one or more lumens, simultaneously or independently. In the various gynecological procedures described herein, a volume of liquid and level of liquid pressure are used to visualize the internal space and/or provide space to manipulate one or more devices. In an alternative embodiment, a gel or gas is delivered into the patient.

Introducer 100a may include a handle, not shown, on its proximal end. The handle may include one or more controls, as has been described hereabove. Sheath 110 may include one or more valves within one or more lumens of sheath 110, such as a valve near the distal end 111. Introducer 100a may include a balloon along sheath 110, such as a balloon configured to dilate tissue such as the cervix or the vaginal wall. In an alternative embodiment, multiple balloons are employed, such as a balloon on a balloon configuration. Each balloon integrated into sheath 110 may have an integrally mounted functional element, as has been described hereabove but preferably a pressure or force sensor used to provide information to the clinician or a system component regarding dilation conditions (reference FIG. 13 herebelow). Sheath 110 may include one or more functional elements along its length, such as a vibrational transducer configured to assist in dilation. Sheath 110 may include a lumen for insertion of a shaped wire, such as a wire configured to resiliently bias sheath 110 and/or a wire configured to place a "straightening" bias on the cervical canal during introducer insertion, once inserted or both. In another alternative embodiment, sheath 110 includes an expandable cage structure, not shown but protruding from distal end 111. The expandable cage structure may have a fluted geometry such as a geometry configured to follow the contour of the uterus when introducer 100a is inserted through the cervix.

Introducer 100 of FIG. 1 and the numerous embodiments of the introducers described throughout this application, are sized to accommodate the one or more devices placed through sheath 110, while remaining as small as possible to reduce tissue trauma and pain to the patient, especially when sheath 110 is placed through the cervix of a patient. In a first embodiment, sheath 110 of Introducer 100 is typically less than 9 mm in diameter and preferably less than 8 mm diameter. In another embodiment, sheath 110 is less than 7 mm in diameter. In another embodiment, sheath 110 is less than 6 mm in diameter. In another embodiment, sheath 110 is less than 5 mm in diameter. In another embodiment, sheath 110 is less than 4 mm in diameter. In another embodiment, sheath 110 is less than 3 mm in diameter. In another embodiment, sheath 110 is less than 2 mm in diameter. Sheath 110 is configured in size and rigidity to prevent painful and potentially destructive dilation of the cervix.

Referring now to FIG. 1A, another preferred embodiment of an introducer consistent with the present invention is illustrated. Introducer 100b has a dual balloon construction and includes sheath 110, of similar construction to sheath 110 of FIG. 1. Introducer 100b is shown over a guidewire 131, such as an 0.038" standard interventional guidewire, which has been advanced through vagina V, through cervix C and into uterus U. An inflatable balloon introducer assembly 150 includes balloon 151 and shaft 155 and is shown having been advanced into the cervix C of a patient and balloon 151 inflated (inflation lumen and inflation port not shown). Inflation of balloon 151 is used to pre-dilate cervix C such that sheath 110 can be advanced into cervix C. Inflation balloon 151 is preferably less than 9 mm in diameter when fully inflated, and more preferably between 2 and 8 mm in diameter. Shaft 155, which is slidably received by sheath 110, may be pulled back prior to advancement of sheath 110, or balloon 151 may be left in place, although preferably partially deflated prior to advancement. In an alternative embodiment, balloon assembly 150 including shaft 155 and balloon 151 may be configured to be completely removed from sheath 110 such as after sheath 110 is placed to its desired location in the patient's body. After advancement of sheath 110, further dilation of the cervix may be accomplished by subsequent inflation of balloon 151, and/or via inflation of a balloon integral to sheath 110, balloon 116 (inflation lumen and inflation port also not shown). Inflation of either balloon 151 or balloon 116, or both, may be used to anchor sheath 110 in place.

On the proximal end of sheath 110 is device insertion port 120, which provides access to an internal lumen of sheath 110 and is in fluid communication with fluid transfer port 123 configured to introduce and/or remove fluid or other media through sheath 110 and into the patient as has been described hereabove. Port 120 includes a rotating collar 124, which can be rotated to permit devices to pass through port 120 as well as seal around those devices, such as via a diaphragm which seals around inserted devices similar to a Tuohy Borst valve configuration. Port 120 further provides fluid stasis when no device is inserted through it.

Guidewire 131 may be replaced with a different guidewire, such as with a guidewire with different stiffness or lubricious properties. Guidewire 131 may remain in place for a majority of the procedure, or may be removed early on.

Referring now to FIG. 1B, another preferred embodiment of an introducer consistent with the present invention is illustrated. Introducer 100c includes sheath 110 with distal end 111, device insertion port 120 with rotating collar 124 and fluid transfer port 123, all of similar construction to similar components of introducer 100a of FIG. 1 and introducer 100b of FIG. 2. Introducer 100c has been placed over guidewire 141 and advanced such that its distal portion resides within cervix C and its distal end is within uterus U of a patient.

Introducer 100c includes a force measuring element, strain gauge 113, which is used to monitor forces exerted on sheath 110 (and the corresponding resultant forces exerted on the neighboring tissue). Wires, not shown but attached to strain gauge 113 and traveling proximally through sheath 110, attach to an electronic module, also not shown, and provide pressure or other force information to the clinician or a system component which processes the information.

Introducer 100c further includes drug delivery element 114, such as a drug delivery mechanism. Drug delivery element 114 may be a simple drug coating, or may be a depot that stores a drug such as an anesthetic and delivers the drug via osmosis, iontophoresis or other drug delivery mechanism. In a preferred embodiment, drug delivery element 114 is a pressure releasable sack, such as a sack with a duck bill valve, and

when sufficient pressure is applied to the sac, such as via the cervix, a drug, such as lidocaine, is delivered. In another preferred embodiment, drug delivery element **114** includes multiple pressure-driven sacks, such as multiple sacks in different locations and/or multiple sacks with different delivery pressure properties.

Introducer **100c** further includes a visualization apparatus, visualization element **112** preferably a forward looking visualization tool such as forward looking ultrasound, or a lens that provides an image to a camera, not shown, but preferably a camera system that receives an image from a fiber optic in optical communication with the lens. A display, not shown but preferably integrated into a laptop computer via a USB or video connection, provides the camera image to the clinician and/or patient.

Referring now to FIG. 2, a preferred embodiment of a system **10** consistent with the present invention is illustrated. System **10** includes introducer **100d** and tissue removal device **200** which includes an integral visualization apparatus, camera **255** mounted to side-saddle catheter **250**. Introducer **100d** includes sheath **110**, device insertion port **120** and fluid transfer port **123**, all of similar construction to similar components of introducers **100a**, **100b** and **100c** hereinabove. Introducer **100d** has been placed and advanced such that its distal portion resides within cervix **C** and its distal end provides access within uterus **U** of a patient. Sheath **110** includes a marker, radiopaque ring **117** which can be used by the clinician to determine and/or confirm with fluoroscopy the diameter (e.g. the inside diameter) of sheath **110** at the location of ring **117**, such as to confirm or rule out the condition where the cervix may be undesirably compressing sheath **110**. In an alternative embodiment, ring **117** is an ultrasonically reflective marker enabling the condition to determine the associated diameter by using ultrasound, such as via an ultrasound device commonly located in a gynecologist office.

Tissue removal device **200**, a morcellating device, has been advanced through port **120**, through a lumen of sheath **110**, and into the uterus **U** of a patient. Tissue removal device **200** includes an elongate shaft, tube **201**, which includes on its distal end **203** a cutout, window **202**. A cutting element **210** is present within window **202** such that as the distal end of tube **201** is manipulated near tissue, cutting element **210** will cut that tissue. Vacuum means, not shown put in fluid communication with a lumen of tube **201** and window **202**, evacuate the pulverized, cut or otherwise detached particles to a location outside of the patient. In a preferred embodiment, vacuum and evacuation means are integral to a handle of device **200**. In another preferred embodiment, vacuum and evacuation means are connected to a port which is integral to a handle of device **200**. Cutting element **210**, of one or more configurations such as the configurations described below in reference to FIGS. 2A and 2B, is preferably attached to a speed control mechanism, not shown. The speed control mechanism is simplified for use by including one or more feedback means (e.g. electromotive feedback, rotation or other speed feedback, vibrational feedback, physiologic feedback such as EKG or blood pressure, or other feedback), wherein the feedback means can be used to automatically control the speed, greatly simplifying use for the clinician. In a preferred embodiment, the clinician available feedback is limited to a small number of finite settings, such as less than 10 settings. In another preferred embodiment, a kill-switch is included on a handle of the device, which is readily accessible to the clinician and upon activation removes power and/or applies a breaking function to instantaneously stop the cutting motion.

Referring additionally to FIG. 2C, also included in the system **10** of FIG. 2 is a side-saddle catheter **250** which includes sleeve **252** (e.g. a Teflon sleeve) which slidably surrounds tube **201**. Advancement and retraction of an elongate shaft, shaft **251** causes a visualization apparatus, camera **255** to be correspondingly advanced and retracted relative to tube **201**. The image received from camera **255**, such as an image displayed on a laptop computer display as has been described hereinabove, is used by the clinician to position the window **202** of tissue removal device **200** near one or more fibroids, such as fibroid **F1** located within the wall of uterus **U** and fibroid **F2** attached to the wall of uterus **U**. Camera **255** may utilize CCD and/or MEMS mirror control technology to produce and/or transfer an image. In a preferred embodiment, camera **255** includes one or more motion sensing elements, such as miniaturized accelerometers or gyros which can be fed back to an image processing system, not shown but preferably external to the patient, such that the image provided to the clinician does not move as the camera is moved. Alternatively or additionally, side saddle catheter **250** includes one or more functional elements, not shown but preferably selected from the list of functional elements provided hereinabove. The functional element may be fluid delivery port, such as a port configured to deliver saline or other clear fluid to clear the pathway of the camera view or to clean off a contaminated lens.

Referring now to FIG. 2A, a preferred embodiment of the cutting element **210** of FIG. 2 is shown. The distal end of tube **201** and window **202** is shown with an oscillating cutter **211** attached to an elongate control linkage, shaft **221**, which is attached at its proximal end to a reciprocating motor assembly, not shown, but preferably a simplified, precision speed controlled assembly as has been described hereinabove. In a preferred embodiment, the speed assembly utilizes feedback, also as has been described hereinabove. Referring now to FIG. 2B, another preferred embodiment of the cutting element of FIG. 2 is shown. The distal end of tube **201** and window **202** is shown with a spinning or rotational cutter **212** attached to an elongate control linkage, shaft **221**, which is attached at its proximal end to a rotational motor assembly, not shown, but preferably a simplified, precision speed controlled assembly as has been described hereinabove. In a preferred embodiment, the speed assembly utilizes feedback, also as has been described hereinabove.

System **10** of FIG. 2 is configured such that the outer diameter of sheath **110** of introducer **100d** is minimized. Inserted devices such as tissue removal device **200** (including camera **256**) and other inserted devices are also minimized in the cross sectional profiles of their distal portions, such that the inner diameter (and thus the outer diameter) of sheath **110** can be reduced. In a first embodiment, sheath **110** of Introducer **100** is typically less than 9 mm in diameter and preferably less than 8 mm diameter. In another embodiment, sheath **110** is less than 7 mm in diameter. In another embodiment, sheath **110** is less than 6 mm in diameter. In another embodiment, sheath **110** is less than 5 mm in diameter. In another embodiment, sheath **110** is less than 4 mm in diameter. In another embodiment, sheath **110** is less than 3 mm in diameter. In another embodiment, sheath **110** is less than 2 mm in diameter. Sheath **110** is configured in size and rigidity to prevent painful and potentially destructive dilation of the cervix.

Referring now to FIG. 3, another preferred embodiment of a system **10** consistent with the present invention is illustrated. System **10** includes introducer **100** and subsonic treatment device **300**. Introducer **100** includes sheath **110**, device insertion port **120** and fluid transfer port **123**, all of similar

construction to similar components of introducers **100a**, **100b**, **100c** and **100d** hereabove. Introducer **100d** has been placed and advanced such that its distal portion resides within cervix C and its distal end provides access within uterus U of a patient. A treatment catheter of the present invention, acoustic generator device **300** has been inserted through port **120**, down a lumen of sheath **110** and into the uterus of the patient.

Referring additionally to FIG. 3A, acoustic generator device **300** includes acoustic transducer **310** which comprises housing **302**, preferably a metal can with a lumen **304**, and a sound crystal **303**, configured to deliver subsonic sound waves. System **10** preferably includes specialized fluid medium, which is injected into uterus U via port **123** and sheath **110**. The fluid medium is configured to adequately conduct the emitted sound waves and provide an impedance mismatch between it and the targeted tissue (e.g. endometrium), such that large amounts of energy (sufficient to destroy or otherwise denature the tissue cells) is transferred to the tissue when the subsonic waves arrive at the interface.

Referring now to FIG. 4, another preferred embodiment of an introducer consistent with the present invention is illustrated. Introducer **100e** is configured to puncture through tissue, such as the vaginal wall to perform a trans-vaginal-wall procedure. Introducer **100e** includes sheath **110** with balloon **116** and distal end **111**, device insertion port **120** and fluid transfer port **123**, all of similar construction to similar components of introducer **100a**, **100b**, **100c** and **100d** hereabove.

Balloon **116**, which can be configured to perform one or more functions such as to dilate tissue, to anchor sheath **110** in place and to maintain one or more lumens of sheath **110** in an open state under high loading conditions. Balloon **116** is in fluid communication with inflation lumen **152** and injection port **153** such that a syringe or endoflator attached to the luer of port **153** can be used to inflate balloon **116**. Balloon **116** includes a miniaturized, integral pressure sensor **154**, which is preferably attached to one or more wires, not shown but traveling proximally and attaching to an electronic module which processes the received signal and provides pressure information to the clinician and/or utilizes the information in one or more ways such as to reduce patient pain such as via the "smart" dilation system and method described in detail in reference to FIG. 13 herebelow. Additional balloons and/or pressure sensors may be integrated into sheath **110**.

Pull wire **171** is fixedly attached at its distal end to a distal portion of sheath **110**, and it is operably attached at its proximal end to knob **172**, such that rotation of knob **172** causes sheath **110** to deflect. As shown in FIG. 4, rotation of knob **172** that causes pull wire **172** to retract causes the distal end of sheath **110** to deflect to the left and rotation of knob **172** that causes pull wire **172** to advance causes sheath **110** to deflect to the right. In an alternative embodiment, additional one or more pull wires are included to allow a clinician to deflect sheath **110** in multiple directions at multiple points along the length of sheath **110**. Deflection of sheath **110** allows for directional orientation, positioning and advancement of the one or more treatment or other devices that can be inserted into sheath **110** via port **120** (inserted devices not shown).

Introducer **100e** includes a tissue penetrating assembly comprising needle **161**, an elongate hollow needle preferably constructed of stainless steel or Nitinol, which has fixedly attached on its proximal end, knob **162**. Needle **161** resides within a lumen of sheath **110**, and is in place when introducer **100e** is advanced through tissue. Needle **161** has an internal lumen sized to slidably receive guidewire **131**. Guidewire **131** can be placed through needle **161** after needle **161** has been advanced through tissue (guidewire loaded from proximal

end of needle **161**). Alternatively, guidewire **131** can be placed to a target location, such as through the vaginal wall of a patient via another needle device, and then passed through needle **161** (guidewire loaded from distal end of needle **161**). In a preferred embodiment, needle **161** can be used to deliver anesthetic to tissue prior to needle **161** and/or sheath **110** advancement.

Introducer **110e** may have one or more functional elements, such as a functional element described hereabove and integrated into sheath **110**. In a preferred embodiment, a functional element comprising a visualization apparatus or a portion of a visualization apparatus, such as a camera lens and fiber optic or an ultrasound crystal and associated wiring are contained within sheath **110**. Advancement of sheath **110e**, such as through the vaginal wall to a location neighboring the outside of a patient's uterus, may require dissection of tissue. In a preferred embodiment, introducer **100e** includes a functional element such as a blunt dissector, a fluid jet, or other dissection element. In another preferred embodiment, a blunt dissection device, such as a blunt tipped probe, electrocautery probe, or fluid-jet probe, is advanced through a lumen of sheath **110** prior to and/or during advancement of sheath **110** through tissue. Once inserted into the body of the patient, the distal portion of sheath **110** may need to be tracked, such as it is advanced through the vaginal wall at the preferred location of the anterior or posterior culdesac of the vagina, to a location outside the uterus. Tracking means, such as visualization systems and navigation systems of the present invention, may be used such as by incorporating one or more visualization or navigation elements in introducer **100e** and/or by using separate devices to navigate and/or visualize. In a preferred embodiment, a visible light source is placed in a fallopian tube and a camera integral to introducer **100e** or a device inserted through sheath **110** is used to locate the visible light source and access the associated fallopian tube. In another preferred embodiment, an electromagnetic transmitting antenna is placed in a fallopian tube and a receiving antenna is integral to introducer **100e** or a device inserted through sheath **110** and is used to locate the transmitting source and access the associated fallopian tube.

Referring now to FIG. 5, another preferred embodiment of a system **10** consistent with the present invention is illustrated. System **10** includes introducer **100f** and treatment catheter **500a** which includes visualization element **520** and orientation apparatus **521**. Introducer **100f** includes sheath **110**, device insertion port **120** and fluid transfer port **123**, all of similar construction to similar components of introducers **100a**, **100b**, **100c**, **100d** and **100e** hereabove. Introducer **100f** has been advanced through the vaginal opening into the vagina V of a patient, to a distal location of the vaginal canal, proximate the cervix C. Sheath **110** has exited through the vaginal wall, as was described hereabove in reference to FIG. 4. A treatment or diagnostic device, as have been described in detail hereabove, treatment catheter **500a**, has been advanced through a lumen of sheath **110**, and further advanced, such as with manipulation via pull wires integral to introducer **100f** and/or treatment catheter **500a**, neither pull wires shown, such that the distal end of treatment catheter **500a** is proximate a fibroid F located in the wall of uterus U.

Treatment catheter **500a** includes shaft **501**, which includes near its distal end treatment element **510**, such as a morcellating assembly, a subsonic generator, an excisor, a cutter, an ablation element, or other tissue removal or denaturing element as has been described in detail hereabove. Also located near the distal end of shaft **501** is visualization element **520** which is preferably a camera lens connected to a fiber optic cable and configured to produce an image on

display **525** of laptop **526** via a cable, wire bundle **527**. Alternatively, visualization element **520** is an ultrasound crystal or crystals such as a rotating crystal or phased array of crystals, configured to produce an image on display **525** of laptop **526** via cable **527**. Visualization element **520** further includes orientation apparatus **521**, a nanoscale mechanism, such as a MEMS gyroscope, accelerometer or series of mercury switches, that is configured to provide movement information to an image processing unit such that the image provided to the clinician does not move as the visualization element moves. The image processing unit may be integral to laptop **526** and/or another component of system **10**.

Shaft **501**, which extends beyond the proximal end of introducer **100f** and exits port **120**, preferably includes on its proximal end a handle with one or more clinician controls (e.g. on-off buttons, pull wire rotational knobs, etc) and/or connections such as electrical connections to laptop computer **526**, or mechanical connections such as to motor assemblies which provide motion to visualization element **520** (e.g. to a rotating ultrasound crystal) or treatment element **510** (e.g. to a spinning or reciprocating cutting blade).

Anesthetics, such as lidocaine, may be administered periprocedurally (prior to, during and post procedure), via a separate device, or via one or more functional elements of introducer **100f**. Numerous gynecological procedures are applicable to the system **10** and method of FIG. **5**, including but not limited to: intra-uterine procedures (re-entering uterus thus avoiding cervical crossing); uterine wall procedures (e.g. the fibroid **F** treatment shown); fallopian tube procedures (e.g. tubal ligation); ovary procedures (e.g. egg harvesting); cancer treatment procedures; pain treatment procedures; other tissue treatment or removal procedures, and intra-abdominal procedures. As described in reference to FIG. **4**, one or more blunt dissection procedures may be performed in the placement of introducer **100f** and/or the advancement of one or more devices (e.g. treatment catheter **500a**) through sheath **110** and to the target procedure location. Also as described in FIG. **4**, one or more navigation or visualization procedures or devices may be used to navigate introducer **100f** and/or treatment catheter **500a**.

In an alternative embodiment, an additional device is inserted through port **120** and sheath **110**, either sequentially or simultaneously with treatment catheter **500a**. The additional device may perform one or more functions such as that of a treatment device, navigation device, stabilizing device, visualization device or other device as has been described as performing a function related to the intended gynecologic and urologic procedures described throughout this application. In another alternative embodiment, treatment catheter **500a** includes a second treatment element, of similar or dissimilar functionality to treatment element **510**.

Referring now to FIG. **5A**, another preferred embodiment of a system **10** consistent with the present invention is illustrated. System **10** includes introducer **100g**, treatment catheter **500b** and stabilizing device **550**. Introducer **100g** includes sheath **110**, device insertion port **120** and fluid transfer port **123**, all of similar construction to similar components of introducers **100a**, **100b**, **100c**, **100d**, **100e** and **100f** hereabove. Introducer **100g** has been advanced through the vaginal opening into the vagina **V** of a patient, to a distal location of the vaginal canal, proximate the cervix **C**. Sheath **110** has exited through the vaginal wall, as was described hereabove in reference to FIG. **4**. Sheath **110** includes drug delivery element **114**, located along sheath **110** at a location proximate the intended vaginal wall crossing, such that one or more drugs, preferably an anesthetic such as lidocaine, can be delivered to reduce pain. Drug delivery element **114** may

deliver a drug via simple infusion means such as osmosis or a weak-bonded coating transitioning into solution, or more sophisticated means such as pressure-regulated delivery or iontophoresis as has been described in detail hereabove.

A treatment or diagnostic device, as have been described in detail hereabove, treatment catheter **500b**, has been advanced through a lumen of sheath **110**, and further advanced, such as with manipulation via pull wires integral to introducer **100f** and/or treatment catheter **500b**, neither pull wires shown, such that the distal end of treatment catheter **500b** is proximate a fibroid **F** located in the wall of uterus **U**. Treatment catheter **500b** includes shaft **501**, which includes near its distal end treatment element **510**, such as a morcellating assembly, a subsonic generator, an excisor, a cutter, an ablation element, or other tissue removal or denaturing element as has been described in detail hereabove. Also located near the distal end of shaft **501** is magnet **502**, such as a rare earth magnet or clinician activatable electromagnet configured to allow the distal portion of shaft **501** of catheter **502** to be manipulated by one or more clinician-controllable magnetic fields. System **10** further includes stabilizing device **550**, inserted into the uterus through the vagina **V** and cervix **C** of the patient (outside of introducer **100g**). At the distal end of shaft **551** of stabilizing device **550** is a second magnet, magnet **552**, preferably a rare earth magnet or clinician activatable electromagnet similar or dissimilar (such as a difference in size and/or magnetic field strength) to magnet **502** of treatment catheter **500b**. Manipulation of the distal ends of either or both stabilizing device **550** or treatment catheter **500b** such that magnet **552** is in relative proximity to magnet **502** will enable the magnetic force to pull the two magnets and associated distal ends together. In a preferred embodiment, either or both magnet **552** and magnet **502** are electromagnets such that one or both magnetic fields can be deactivated for initial manipulation(s), and activated to achieve final position, such as at a location where treatment element **510** is in close proximity to uterine fibroid **F**, as shown in FIG. **5A**. In a preferred embodiment, the magnetically guided system **10** of FIG. **5a** can perform one or more procedures without the need for a camera or other visualization apparatus. In an alternative embodiment, a camera or other visualization apparatus is used, such as with a visualization element incorporated into sheath **100g**, treatment catheter **500b** or stabilizing device **550**.

Shaft **501**, which extends beyond the proximal end of introducer **100g** and exits port **120**, and shaft **551** both preferably include on their proximal end a handle with one or more clinician controls (e.g. on-off buttons, pull wire rotational knobs, etc) and/or connections such as electrical connections to a laptop computer (not shown but similar to laptop computer **526** of FIG. **5**), or mechanical connections such as to motor assemblies which provide motion to treatment element **510** (e.g. to a spinning or reciprocating cutting blade) or to manipulate one or more internal pull wires such as to create a robotically manipulated system.

Referring now to FIG. **6**, a preferred embodiment of a trans-fallopian method for performing a gynecologic procedure is illustrated. A first treatment device **500c** is inserted through the vaginal canal of the vagina **V**, through the cervix **C**, through the uterus **U** and through a fallopian tube **FT1** to a location outside the fallopian tube **FT1**. First treatment device **500c** includes an elongate shaft, shaft **501c** which includes on its distal end occluding assembly **510c**, shown as a snaring assembly but alternatively an occluding clip placement assembly or an occlusive drug delivery assembly. Shaft **501c** preferably includes one or more pull wires, for manipulation, and alternatively or additionally may be advancable over a

previously placed guidewire. Shaft **501c** preferably includes a handle on its proximal end, not shown but preferably including one or more controls such as pull wire controls and a control to synch up the snare of treatment element **510c**. Treatment element **510c** is shown having snared a portion of fallopian tube **FT1** such as to occlude fallopian tube **FT1** in a sterilization procedure.

A second treatment device **500d** is inserted through the vaginal canal of the vagina **V**, through the cervix **C**, through the uterus **U** and through a fallopian tube **FT2** to a location outside the fallopian tube **FT2** and proximate subserosal fibroid **F**. In an alternative embodiment, the introducer of the present invention is placed into the cervix **C**, and first treatment device **500c** and/or second treatment device **500d** are passed into the uterus **U** via the introducer. In another alternative embodiment, one or more of the previous devices resides outside of the introducer, such as to stabilize that device in the uterus. Second treatment device **500d** includes an elongate shaft, shaft **501d** which includes on its distal end treatment element **510d**, a fibroid treating element such as a morcellator, an ablative element, a lysing or excising element, or another device used to remove or denature fibroid tissue. Shaft **501d** preferably includes one or more pull wires, for manipulation, and alternatively or additionally may be advanceable over a previously placed guidewire. Shaft **501d** preferably includes a handle on its proximal end, not shown but preferably including one or more controls such as pull wire controls and a control to activate fibroid treating element **510d**.

Treatment catheter **500c** and/or treatment catheter **500d** may include one or more functional elements as has been described in detail hereabove. Preferably, a navigation and/or visualization element is employed to introduce the ends of the devices, especially to the target location once exiting the fallopian tube. Preferably treatment catheter **500c** and/or treatment catheter **500d** include one or more visualization markers, such as visible and non-visible markers; radiopaque markers; magnetic markers; ultrasonically reflective markers; and combinations thereof. Similar to the trans-vaginal-wall methods of FIGS. **5** and **5A**, the trans-fallopian tube approach of FIG. **6** may be used to perform numerous procedures including but not limited to: uterine wall procedures (e.g. the fibroid **F** treatment shown); fallopian tube procedures (e.g. the tubal ligation shown); ovary procedures (e.g. egg harvesting); cancer treatment procedures; pain treatment procedures; other tissue treatment or removal procedures, and intra-abdominal procedures.

Referring now to FIG. **7**, a preferred embodiment of a drug delivery device of the present invention is illustrated. Drug delivery device **400** is shown having been inserted into through the vagina **V** and into the cervix **C** of a patient. Device **400** includes an elongate shaft **401** with, near its distal end, drug delivery assembly **410**. Drug delivery assembly **410** includes needles **411** (e.g. Nitinol or stainless steel needles), shown deployed into the cervix **C** such as to deliver a drug to the cervix. Applicable drugs include anesthetics such as lidocaine, muscle relaxing drugs, and other drugs. Shaft **401** may include one or more lumens, such as a fluid delivery lumen to deliver a drug to needles **411** and a guidewire lumen for preferably advancing shaft **401** into the cervix **C** over a guidewire.

Referring now to FIG. **7A**, the distal end of shaft **401** is shown. Shaft **401** surrounds inner shaft **406**, which can be controllable advanced and retracted by the clinician such as via one or more controls on a proximal handle of drug delivery device **400**, handle and controls not shown. Needles **411** are undeployed, contained within the wall of shaft **401** with

their distal tips oriented toward and proximate to exit holes **412**. Referring now to FIG. **7B**, inner shaft **406** has been retracted, causing needles **411** to deploy, passing through exit holes **412**. Such retraction would cause needles **411** to penetrate into neighboring tissue, such as cervical tissue when shaft **401** is placed in the cervix when inner shaft **406** is retracted. In order to support the intended motion, needles **411** may be flexible or may be connected to a flexible hinge.

Referring now to FIG. **7D**, a preferred embodiment of a drug delivery device of the present invention is illustrated. Drug delivery device **400c** is shown having been inserted into through the vagina **V** and into the cervix **C** of a patient. Device **400c** includes an elongate shaft **401** with, near its distal end, drug delivery assembly **410d**. Shaft **401** includes occluding rings **416** on either end of drug delivery assembly **410c**. Occluding rings **416** and drug delivery assembly **410c** have been positioned in the cervix **C** such that drug delivered through one or more exit holes **412** of drug delivery assembly **410c** will contact cervical tissue. Applicable drugs include anesthetics such as lidocaine, muscle relaxing drugs, and other drugs.

Occluding rings **416** are sized to form a seal in the cervix, such as to allow elevated pressure delivery of drugs and/or to provide a vacuum seal in the area surrounding drug delivery element **410c**. In an alternative embodiment, shaft **401** includes a single occluding ring **201**, such as at a location of the proximal occlusion ring shown. In another alternative embodiment, occluding rings **201** may have a controllable diameter, such as rings comprising an inflatable balloon, balloon inflation lumen and inflation port not shown.

Drug delivery element **410c** further includes one or more suction ports **414**. Suction ports **414** and occluding rings **416** are configured such that when a vacuum is applied to suction ports **414**, the cervical (or other neighboring) tissue is pulled toward the exit holes **412** of drug delivery element **410c**, such that the efficacy of drug delivered through exit holes **412** is enhanced. Exit holes **412** and suction ports **414** are connected to independent hollow conduits that travel from drug delivery element **410c** to port **420** on the proximal end of drug delivery device **400c**. Port **420** fluidly connects to drug reservoir **430**, which in turn is pressurized by pressure reservoir **440** (such as a CO₂ pressure source) such that fluid can flow through shaft **401** to exit holes **412**. Port **420** is also fluidly connected to vacuum generator **450** such that suction can be transferred through shaft **401** (in a separate conduit than is connected to drug reservoir **430**) to suction ports **414**.

In an alternative embodiment, drug delivery element further includes an iontophoretic element, not shown but configured to enhance drug delivery into the tissue surrounding drug delivery element **410c**. In another alternative embodiment, shaft **401** includes a lumen to support over-the-wire delivery.

Referring now to FIG. **8**, another preferred embodiment of a drug delivery device of the present invention is illustrated. Drug delivery device **400a** is shown having been inserted into through the vagina **V** and into the cervix **C** of a patient. Device **400a** includes an elongate shaft **401** which includes drug delivery assembly **410a** near its distal end. Drug delivery assembly **410a** includes exit holes needles **413**, sized and configured to deliver a drug to the cervix. Applicable drugs include anesthetics such as lidocaine, muscle relaxing drugs, and other drugs. Shaft **401** may include one or more lumens, such as a fluid delivery lumen to deliver a drug to exit holes **413** and a guidewire lumen for preferably advancing shaft **401** into the cervix **C** over a guidewire.

Referring now to FIG. **8A**, the distal end of shaft **401** is shown. Shaft **401** surrounds an occluding guidewire **402**.

Shaft **401** can be controllably advanced and retracted by the clinician over guidewire **402**. Proximal to exit holes **413** is marker **404**, preferably a radiopaque or ultrasonically reflective marker used to position the exit holes **413** in the cervix C. Referring now to FIG. 8B, the proximal end of inner shaft **406** is shown wherein guidewire **402** exits the proximal end of the device. Infusion port **403** provides fluid access to the exit holes **413** such that drugs can be delivered via a syringe, infusion pump, or gravity feed system.

Referring now to FIG. 9, another preferred embodiment of a drug delivery device of the present invention is illustrated. Drug delivery device **400b** is shown having been inserted into through the vagina V and into the cervix C of a patient. Device **400a** includes an elongate shaft **401** with, near its distal end, drug delivery assembly **410b** comprising a balloon with multiple exit holes which are sized and configured to deliver a drug to the cervix. Applicable drugs include anesthetics such as lidocaine, muscle relaxing drugs, and other drugs. Shaft **401** may include one or more lumens, such as a fluid delivery lumen to deliver a drug to exit holes **413** and a guidewire lumen for preferably advancing shaft **401** into the cervix C over a guidewire.

Referring now to FIG. 9A, the distal end of shaft **401** is shown having been inserted over guidewire **402**. Shaft **401** can be controllably advanced and retracted by the clinician over guidewire **402**. Drug delivery assembly **410b** includes an inflatable balloon **415**, preferably a dual balloon construction with exit holes **413** in the outer balloon. Referring now to FIG. 9B, the proximal end of inner shaft **406** is shown wherein guidewire **402** exits the proximal end of the device. Infusion port **403** provides fluid access to the exit holes **413** such that drugs can be delivered via a syringe, infusion pump, or gravity feed system. Inflation port **406** provides inflation access to balloon **415**, such as to an inner balloon portion of balloon **415**. In an alternative embodiment, an enhanced drug delivery element is integral to balloon **415**, such as an iontophoretic element for precision controlled drug delivery. In another alternative or additional embodiment, balloon **415** is inflated to dilate or partially dilate the cervix C of the patient.

Referring now to FIG. 10, a preferred embodiment of a scaffolding device of the present invention is illustrated. Scaffolding device **600**, and the other distension devices of the present invention, are preferably inserted into the uterus of a patient such that the scaffolding assembly preferably distends the uterine cavity to a volume equivalent to that which would be attained via a liquid distension media at a pressure of at least 40 mm of HG but not greater than 100 mm HG and preferably approximating 70 mm Hg. Scaffolding device **600** is shown having been inserted into through the vagina V, through the Cervix C and into the uterus U of a patient. In an alternative embodiment, the introducer of the present invention is placed into the cervix C, and scaffolding device **600** is passed into the uterus U via the introducer. Scaffolding device **600** includes elongate shaft **601**. Extending beyond the distal tip **602** of shaft **601** is deployable basket **611**. Basket **611**, shown in its fully expanded state, is preferably a resiliently biased foldable weave of filaments made of Nitinol. Manipulation of shaft **601** (e.g. via pull-wires not shown) and/or basket **611** can be performed by the clinician to exert forces against one or more portions of the uterine wall UW such as to distend or scaffold the uterine wall, to apply tamponade to a bleed, and combinations thereof. Basket **611** can be arranged in numerous shapes, such as to mimic the shape of the uterus or a portion of the uterus. The weaved filaments may be sized (e.g. diameter, length or width) to effectively cover a small proportional area (e.g. large "windows" between filaments)

or they may be configured to cover a large proportion of the area (e.g. with a large profile and/or a covering).

Basket **611** may include a covering, on the inside or the outside of the resiliently biased structure, and the covering may be a partial covering. In a preferred embodiment, a clinician places a tamponade force on a bleeding tissue location with a covered portion of basket **611**. In another preferred embodiment, a clinician reduces the amount of fluid used in a procedure by inserting a scaffolding device **600** that includes a covering of basket **611** (i.e. the basket occupies space in the uterus and/or limits fluid transfer from the portion of the uterine wall in contact with the balloon). Basket **611** and any associated coverings may be coated, impregnated or otherwise include one or more drugs, such as clotting agents and anesthetics. In a preferred embodiment, the drug may be "released" by the clinician on demand, such as by an integral iontophoretic delivery element (e.g. integral to basket **611**), or by applying a force to an integral pressure activated drug depot (e.g. integral to basket **611**). Basket **611** and any associated coverings may be coated or treated with one or more compounds to change a property such as lubricity and radiopacity. Avoiding or reducing the need for distension with fluid subsequently reduces the risk factors (e.g. intravasation) associated with that fluid delivery.

Referring now to FIG. 10A, a cross section of the distal portion of scaffolding device **600** is shown with basket **611** in a near-fully deployed state. Basket **611** is fixedly attached to control shaft **612** which is slidably received by outer shaft **601** via lumen **603**. The proximal end of shaft **601** is preferably attached to a handle, not shown, which includes one or more controls, also not shown but preferably including a control knob or lever that can precisely advance and retract control shaft **612**. Retraction of control shaft **612** causes basket **611** to withdraw into the lumen **603** of shaft **601** and transition to a radially compact state. Subsequent advancement of control shaft **612** causes bases **611** to exit lumen **603** and resiliently expand into the deployed state shown in FIG. 10. In an alternative embodiment, basket **611** includes mechanical expansion means to assist in radial expansion, such mechanical expansion means including an inflatable balloon inside or outside of basket **611**, advancable push rods which exert radial forces upon different portions of basket **611** and/or other mechanical means. In this alternative embodiment, basket **611** may or may not be resiliently biased.

In a preferred embodiment, basket **611** can be expanded in the uterus (or other body cavity), and a procedure such as a tissue removal or denaturing procedure be performed "through" the weave of basket **611**. Numerous one or more treatment or other devices, can be used by the clinician while scaffolding device **600** is in place in the uterus. In particular, tissue treatment devices (e.g. morcellators; radiofrequency, laser and cryogenic ablaters; and subsonic treatment devices) and drug delivery devices can perform their intended function, such as to treat tissue present in between the filaments (tissue in "window" of basket **611**). In another preferred embodiment, scaffolding device **600** is used to treat uterine prolapse. In yet another preferred embodiment, a separate balloon catheter is inserted within balloon **611**, such as to occupy space and/or apply additional force to the uterine wall. In yet another alternative embodiment, one or more portions of basket **611** can be energized (e.g. deliver RF energy to tissue) in order to treat tissue, which may avoid the need for a second device.

Referring now to FIG. 10B, another preferred embodiment of a scaffolding device of the present invention is illustrated. Located on the distal end of elongate shaft **601** is a deployable scaffolding assembly **610a**. Scaffolding assembly **610a** is

configured to scaffold open a body cavity such as the uterus, while also providing an operating space to perform one or more procedures such as tissue removal. Scaffolding assembly **610a** may be arranged in one or more shapes, such as to conform to specific body areas such as the contour of uterine wall. Scaffolding assembly **610a** comprises two resiliently biased arms, first arm **621** and second arm **622**. These arms, preferably constructed of Nitinol, are configured to be radially compressed when drawn into the distal end of a tube, such as the lumen of the introducer of the present invention (see FIG. **10D**). Shaft **601** preferably includes one or more lumens, such as a lumen to slidably receive a guidewire for over-the-wire delivery. In an alternative embodiment, first arm **621** and/or second arm **622** include light source means, such as light provided through a window optically connected to a fiber optic cable, light provided by one or more LEDs and/or light provided via a chemoluminescent solution.

Referring now to FIG. **10C**, another preferred embodiment of a scaffolding device of the present invention is illustrated. Located on the distal end of elongate shaft **601** is a deployable scaffolding assembly **610b**. Scaffolding assembly **610b** (similar to **610a**) is configured to scaffold open a body cavity such as the uterus, while also providing an operating space to perform one or more procedures such as tissue removal. Scaffolding assembly **610b** may be arranged in one or more shapes, such as to conform to specific body areas such as the contour of uterine wall. Scaffolding assembly **610b** comprises three resiliently biased arms, first arm **621**, second arm **622** and third arm **623**. In an alternative embodiment, four or more arms may be included. These arms, preferably constructed of Nitinol, are configured to be radially compressed when drawn into the distal end of a tube, such as the lumen of the introducer of the present invention (see FIG. **10D**). Shaft **601** preferably includes one or more lumens, such as a lumen to slidably receive a guidewire for over-the-wire delivery. In an alternative embodiment, first arm **621**, second arm **622** and/or third arm **623** include light source means, such as light provided through a window optically connected to a fiber optic cable, light provided by one or more LEDs and/or light provided via a chemoluminescent solution.

Referring now to FIG. **10D**, a preferred embodiment of a system **10** consistent with the present invention is illustrated. System **10** includes introducer **100**, scaffolding device **600a** and treatment device **500**. Introducer **100d** includes sheath **110**, device insertion port **120** and fluid transfer port **123**, all of similar construction to similar components of introducers **100a**, **100b** and **100c**, **100d**, **100e**, **100f** and **100g** hereabove. Introducer **100** has been placed and advanced such that its distal portion resides within cervix C and its distal end provides access within uterus U of a patient.

Scaffolding device **600a**, of similar construction to the scaffolding device of FIG. **10B**, has been advanced through a lumen of introducer **100** such that the distal end of shaft **601** and scaffold assembly **610a** (fully expanded) reside within the uterus U such that a scaffolding force is applied to the uterine wall along a plane relatively perpendicular to the cross section shown in FIG. **10D**. First arm **621** and second arm **622** have been positioned at locations away from uterine fibroid F as shown in FIG. **10D**. Treatment device **500** has been coaxially advanced through a lumen of shaft **601** of scaffolding device **600a** such that the distal portion of shaft **501** resides within uterus U. At the distal end of shaft **501** is treatment element **510**, such as a morcellator or other tissue treatment element. Via deflection means, not shown but preferably a pull-wire internal to shaft **501**, treatment element **510** has been brought in close proximity to fibroid F, also as shown in FIG. **10D**.

In an alternative embodiment, treatment catheter **500**, scaffolding device **600a** and/or introducer **100** include a visualization apparatus such as a camera to visualize inside uterus U, such as when clear fluid is introduced into uterus U via port **123**. Light may be provided, as has been described in detail hereabove, from a functional element integral to the distal portions of treatment catheter **500** (e.g. proximate a camera which is proximate treatment element **510**), scaffolding device **600a** (e.g. in one or more of arms **621** and **622**) and/or introducer **100** (e.g. a forward beam light source) such as to improve the image provided to the clinician via the integral camera. In one embodiment, the camera is an infrared camera and heated and/or cooled solutions are utilized to increase the contrast in the infrared image (tissue temperature differences) and reduce or eliminate the need for an external light source.

In the performance of one or more gynecologic and urologic procedures, such as a tissue removal or other treatment procedure, scaffolding device **600a** and treatment device **500** are repositioned, such as to scaffold a different part of the uterus or to access a different portion of tissue, respectively. In a preferred embodiment, a second scaffolding device is inserted through introducer **100**, simultaneous with or at a different time than scaffolding device **600a** resides within introducer **100**. In another preferred embodiment, a second treatment device is inserted through introducer **100**, simultaneous with or at a different time than treatment device **500** resides within introducer **100**.

Referring now to FIG. **11**, a preferred embodiment of a visualization apparatus of the present invention is illustrated. Camera device **700** consists of shaft **701**, preferably an elongate shaft with a deflectable tip, which includes camera assembly **702** in its distal end portion. Camera assembly **702**, which preferably includes a sealed lens or window on its outer portion, includes one or more configurations as has been described hereabove, including one or more components or assemblies selected from the group consisting of: lenses including filtering lenses, wide angle lenses, gradient lenses and focusing lenses; mirrors; image sensors such as a CCD module; MEMS gyroscopes (such as to detect and accommodate for motion); MEMS mirrors; light sources such as LEDs; strain gauges (such as to detect and accommodate for motion); accelerometers (such as to detect and accommodate for motion); fiber optic cable for image transfer; other optical or image processing components and combinations thereof. Camera assembly **702** may be arranged as an endoscope, and/or may involve different technologies such as MEMS actuators, CCD modules and motion detectors which are configured to provide a stable image to a clinician despite camera movement. In an alternative embodiment, an output port, not shown, is located proximate to camera assembly **702** such that saline or other biocompatible liquid media in fluid communication with the output port can be flushed by camera assembly **702** such as to clear debris and improve image quality. Camera device **700** provides an image to a display, not shown but preferably a laptop screen as has been described in reference to FIG. **5**, such as through an electrical and/or optical connection on a handle of camera device **700**.

The visualization apparatus of FIG. **11** further includes a first light source **710** which is independent (e.g. independently maneuverable) from camera device **700**. First light source **710** includes shaft **711**, preferably an elongate shaft with a deflectable tip, which includes light emitting element **712** at its distal end. Light emitting element **712** is a tubular structure which can be shaped, via pull wire technology described above and/or via plastic deformation (e.g. plastically deformable wire included within light emitting element **712**) such as to wrap around the uterus as shown in FIG. **11**.

Light emitting element **712** is preferably a self-contained light source, such as an array of light emitting diodes that are surrounded by a window such as a diffracting or light-scattering lens. In an alternative embodiment, light emitting element **712** does not include a light source, but rather consists of a viewing window in optical communication with one or more fiber optic cables which in turn connect to a light source, the light source being integral to first light source **710** (such as in a handle of the device) or external and optically connected to first light source **710**. Light emitting element **712**, or a separate light source that supplies light emitting element **712**, is connected to a source of electrical power such as a battery (e.g. a battery in a handle of the device). In an alternative embodiment, light emitting element **712** emits light from a chemoluminescent solution (e.g. a chemoluminescent solution that is mixed on demand by the clinician, such as by one or more controls on the handle of the device). This light generating solution, as in found in commercially available "lightsticks", may be contained (sealed compartment) within light emitting element **720**, or be optically connected to element **720** via a fiber optic cable. In an alternative embodiment, the chemoluminescent solution is introduced into light emitting element **720** via an infusion lumen. In another alternative embodiment, both a chemoluminescent solution and another source of light (e.g. LED light) are provided by light emitting element **720**.

The visualization apparatus of FIG. **11** further includes a second light source **720** which is also independent (e.g. independently maneuverable) from camera device **700**. Second light source **720** includes shaft **721**, preferably an elongate shaft with a deflectable tip, which includes light emitting element **722** at its distal end. Light emitting element **722** is a balloon structure which can be inflated and deflated by the clinician, shown in the inflated or partially inflated state in FIG. **11**. Light emitting element **722** is preferably a self-contained light source, such as a vessel into which chemoluminescent solution is delivered, as has been described hereabove. Alternatively, one or more light emitting diodes that are surrounded by a covering (the balloon) which is configured as a diffracting or light-scattering lens. In an alternative embodiment, light emitting element **722** does not include a light source, but rather consists of a viewing window (the balloon) in optical communication with one or more fiber optic cables which in turn connect to a light source, the light source being integral to second light source **720** (such as in a handle of the device) or external and optically connected to second light source **720**. Light emitting element **722**, or a separate light source that supplies light emitting element **722**, may be connected to a source of electrical power such as a battery. In the preferred embodiment, light emitting element **722** emits light from a chemoluminescent solution (e.g. a chemoluminescent solution that is mixed on demand by the clinician and injected into the balloon of light emitting element **722**, such as by one or more controls on the handle of the device) and does not require the source of electrical power. In an alternative embodiment, both a chemoluminescent solution and another source of light (e.g. LED light) are provided by light emitting element **722**.

Camera device **700**, first light source **710** and second light source **720** have had their distal ends placed through the cervix C and into the uterus U of a patient. In an alternative embodiment, the introducer of the present invention is placed into the cervix C, and camera device **700**, first light source **710** and/or second light source **720** are passed into the uterus U via the introducer. In another alternative embodiment, one or more of the previous devices resides outside of the introducer, such as to stabilize that device in the uterus. Each

device preferably includes a handle on their proximal end, not shown but preferably including one or more controls including but not limited to: knobs or levers to manipulate one or more pull wires configured to manipulate the distal portions of the associated device; a control to zoom in or zoom out an image; a control to focus an image; a control to stabilize an image; a control to energize a light source; a control to change the light intensity of a light source (e.g. via change to energy supplied); a control to deliver a drug; a control to change the speed of a tissue removal assembly; a "Kill-switch" control to stop motion of a component immediately; other controls and combinations thereof.

In addition to the above controls, each handle may include one or more ports, such as ports selected from the group consisting of: a valved port such as a cracking pressure valved port, a two-way valved port and a duckbill valved port; a Tuohy-Borst valve; a fluid stasis valve; a device insertion port such as a port configured to accept a treatment device of the present invention; an infusion lumen access port such as an infusion lumen in fluid communication with a drug reservoir, exit port or other component of a drug delivery element; a balloon inflation lumen access port; other ports and combinations thereof. In a preferred embodiment, camera device **700**, first light source **710** and/or second light source **720** include one or more integral functional elements such as a drug delivery element or other functional element as have been described hereabove. In a preferred embodiment, the functional element is an integral inflatable balloon, not shown but preferably in a distal portion of the device and configured to: occupy space in the uterus, deflect the distal end of the associated device by applying a force to the uterine wall; apply tamponade force to the uterine wall, or distend the uterus.

The distal portions of camera device **700**, first light source **710** and second light source **720** may be manipulated in the uterus U such as to perform a secondary function including but not limited to: applying a tamponade force to a portion of the uterine wall (e.g. a perforation or bleed); to distend the uterus; and combinations thereof. The distal portions of camera device **700**, first light source **710** and second light source **720** have an "effective" outer diameter (e.g. the ID of an appropriate sheath **110** of the present invention) less than 9 mm, preferably between 5 and 8 mm, and more preferably less than 6 mm.

Referring now to FIG. **12**, a preferred embodiment of a volume occupying device of the present invention is illustrated. Volume occupying device **800** consists of shaft **801**, preferably an elongate shaft with a deflectable tip, which includes volume occupying balloon **802** in its distal end portion. Inflation of balloon **802** is accomplished by administering fluid such as saline from an inflation port, not shown but preferably on a handle on the proximal end of device **800**. Balloon **802** may be a compliant balloon such as expands to variable volumes based on the fluid pressure, or a non-compliant balloon configured to expand to a fixed volume, relatively independent of fluid pressure. Balloon **802** is preferable includes nylon and/or PET materials. Balloon **802** is configured to assume a shape when inflated that approximated the shape of the uterus or a portion of the space of the uterus, as shown in FIG. **12**. Inflation of balloon **802** is performed to accomplish one or more of the following functions: distend uterus U; effectively "cover" a portion of tissue surface area of uterus U such that fluids internal to uterus U will not be absorbed by or otherwise pass through that covered portion of tissue; apply a tamponade force to a portion of the uterine wall (e.g. a bleed or puncture site); occupy space of the uterus to reduce injected fluid volume; and other functions. In a preferred embodiment, device **800** performs at least two func-

tions listed immediately hereabove. In another preferred embodiment, device 800 performs the function of distending tissue (e.g. the uterine wall) as well as limiting the transfer of fluids into or through that tissue.

Also shown in FIG. 12 is treatment catheter 500, including an elongate shaft 501 and a treatment element 510 near the distal end of shaft 501. Treatment catheter 500, for example a tissue removal or denaturing device or a drug delivery device, is being advanced such as to a location to the right and above balloon 802 of volume occupying device 800. Advantages of placement of volume occupying device 800 include the functions in the paragraph above, as well as creating a small "work area" for the clinician to navigate with treatment catheter 500.

In an alternative embodiment, the introducer of the present invention is placed into the cervix C, and volume occupying device 800 and/or treatment catheter 400 are passed into the uterus U via the introducer. In another alternative embodiment, one or more of the previous devices resides outside of the introducer, such as to stabilize that device in the uterus.

Referring additionally to FIG. 12A, a shaping wire 560 including shape 561 near its distal end is shown. Shaping wire 560, preferably a heat-set shaped Nitinol wire, is configured to be inserted into a lumen of a device, such as a lumen of volume occupying device 800 or treatment catheter 500, lumens not shown. Clinician insertion of shaping wire 560 causes the distal portion of the device in which wire 560 is inserted, to change shape in a pre-determined manner. This shape-changing function allows the clinician to position one or more components of the devices (e.g. balloon 802 or treatment element 510), at a specific location within uterus U. In a preferred embodiment, shaping wire 560 is configured to be inserted into a lumen of one or more of the introducers, treatment catheters, distension devices, volume occupying devices, visualization apparatus, navigating apparatus or other devices of the present invention such as to modify the shape of a distal portion of the device.

Referring now to FIG. 13, a preferred method and associated system of the present invention is disclosed. Numerous procedural steps listed below in reference to FIG. 13 have been described in detail throughout this specification. For brevity, the details of each step will not be repeated below but should be considered within the scope of the method and system of FIG. 13 as has been described hereabove.

Step 10 involves placing one or more devices to dilate the cervix of a patient. Prior to, during and/or shortly after the dilation of Step 10, Step 11 may be performed which is the measurement of one or more patient parameters, such as patient physiologic parameters. Patient physiologic parameters include but are not limited to: force exerted by or on tissue such as force exerted by or on the cervix as measured by a transducer integral to a cervical dilator; EKG; EEG; blood and blood gas parameters such as cell counts and O₂ saturation levels; glucose parameters; pH; blood pressure; respiration; and combinations thereof.

Subsequent to Step 10, Step 20 involves the dilation of the patient's cervix. The dilation is performed per a set of dilation parameters, such parameters including but not limited to: pressure of dilation such as balloon pressure; amount of dilation per unit time; pressure increase per unit time; rate of change of dilation per unit time; rate of change of pressure increase per unit time; duty cycle of discontinuous dilation (e.g. on and off times if dilation performed in discrete time segments); frequency of discontinuous dilation; other dilation parameters and combinations thereof.

Simultaneous with the performance of the dilation of Step 20, Step 30 is performed in which one or more patient parameters, as have been listed above in reference to Step 11, are

taken. Step 40 is performed, in which the one or more parameters are analyzed and the results of the analysis is compared to a threshold. If a threshold is exceeded, that information is fed to the parameter modifying algorithm of Step 50, which in turn modifies one or more of the dilation of parameters of Step 20 (such as to decrease dilation pressure or stop dilation entirely). If the threshold is not exceeded, that information is fed back to the dilation control of Step 20 and no change is made.

For example, if one of the patient parameters collected in Step 30 is blood pressure, which may be an acceptable surrogate for pain level, when a previously determined blood pressure threshold is reached, dilation is reduced or stopped. The parameter analysis may be more sophisticated that comparing the physiologic measurement to a direct threshold, other analysis made additionally or alternatively be performed such as to look at rate of change of the parameter, or to analyze two or more parameters in combination: such as two or more of EKG, blood pressure and respiration.

In a preferred embodiment, a system is provided to automatically perform the parameter analysis of Step 40 and automatically modify the dilation parameters of Steps 50 and 20. In an alternative embodiment, the clinician may perform one or more steps, or perform a portion of one or more steps manually. In another preferred embodiment, one or more thresholds involved with the analysis are programmable by the clinician. In another preferred embodiment, the mathematical formulas of the analysis are programmable by the clinician.

The dilation performed in Step 20 may be accomplished with continuous application of pressure or discontinuously in discrete time segments. These discrete dilation time segments may be fractions of seconds, multiple seconds or even minutes. In a preferred embodiment, the analysis of the physiologic measurement is performed between dilation time segments, such that the subsequent dilation time segment is potentially modified (Step 50) due to the analysis performed in the previous "off" or no-dilation period.

The "smart" dilation system and method of FIG. 13 is preferably accomplished using an introducer of the present invention, such as introducer 100c of FIG. 1B which includes strain gauge 113 (output of strain gauge 113 is the measured physiologic parameter); or introducer 100e of FIG. 4 which includes pressure sensor 154 integral to dilating balloon 116 (output of sensor 154 is the measured physiologic parameter). Other devices of the present invention may include a functional element such as a pressure or other force sensor which provides an output signal that includes the physiologic data analyzed in Step 40.

In an alternative embodiment, the "smart" dilation system and method of FIG. 13 may deliver a drug based on the physiologic data analysis of Step 40, in addition to or alternative to modifying the dilation parameters in Step 50. In a preferred embodiment, a threshold for one analysis (based on one or more physiologic data) causes a drug to be delivered, and the threshold for a second analysis (based on similar or dissimilar physiologic data analysis used in the first analysis) causes a dilation parameter to be changed (including cessation of dilation).

It should be understood that numerous other configurations of the systems, devices and methods described herein could be employed without departing from the spirit or scope of this application. While the procedures described above have been described in terms of gynecological procedures, other applicable procedures can be incorporated without departing from the spirit and scope of the invention, particularly procedures applicable to both male and female patients.

The scaffolds and volume occupying element of the present invention comprise shapes and sizes that preferably allow both visualization (such as via an internal camera) and treatment (the performance of the intended clinical procedures, such as a tissue treatment procedure). Preferred shapes of these devices include but are not limited to: spherical; conical; trapezoidal; hemispherical; scallop-shaped; and combinations of the above such as a scaffolding device with a spherical portion and a conical portion. The size of the volume occupying elements of the present invention should be more than 5% of the volume of the cavity into which it is inserted (e.g. the uterus) and up to 100% of that space (e.g. to allow maximum viewing and working area without damaging tissue such as uterine wall or neighboring tissue).

The devices of the present invention may be provided in kits, such as kits that offer various size and shape scaffolding and volume occupying devices.

Each device (e.g. treatment device) could be used in various areas—not just Uterus

Each device (e.g. treatment device) could be used in various procedure types such as: percutaneous, laparoscopic, MIS, open surgery

Other embodiments of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. It is intended that the specification and examples be considered as exemplary only, with a true scope and spirit of the invention being indicated by the following claims. In addition, where this application has listed the steps of a method or procedure in a specific order, it may be possible, or even expedient in certain circumstances, to change the order in which some steps are performed, and it is intended that the particular steps of the method or procedure claim set forth herebelow not be construed as being order-specific unless such order specificity is expressly stated in the claim.

What is claimed is:

1. An intrauterine access and procedure system, comprising:

an elongate, tubular sheath having a proximal end, a distal end and at least one lumen extending therethrough, the sheath adapted for transcervical access to a uterus;

a tissue removal device adapted to extend through the sheath lumen for removing tissue from the site, the tissue removal device having a closed distal end and a window spaced proximally from the closed distal end and a cutting element operable to cut tissue received in the window; and

a visualization apparatus adapted to extend through the sheath for visualizing a site within the uterus, the visualization apparatus including a sleeve, the sleeve slidably surrounding the tissue removal device.

2. The intrauterine access and procedure system as in claim 1, wherein the tissue removal device comprises an ablation element.

3. The intrauterine access and procedure system as in claim 1, further comprising a stabilization device.

4. The intrauterine access and procedure system as in claim 1, further comprising a drug delivery assembly.

5. The intrauterine access and procedure system as in claim 1, wherein an outside diameter of the sheath is less than about 7 mm.

6. The intrauterine access and procedure system as in claim 1, wherein the visualization apparatus comprises a fiber optic device.

7. The intrauterine access and procedure system as in claim 1, wherein the visualization apparatus comprises an ultrasound transducer.

8. The intrauterine access and procedure system as in claim 1, wherein the sheath comprises at least one radiopaque marker.

9. The intrauterine access and procedure system as in claim 1, wherein the tissue removal device comprises a tissue cutter.

10. The intrauterine access and procedure system as in claim 1, wherein the tissue removal device comprises a tissue morcellator.

11. The intrauterine access and procedure system as in claim 1, further comprising a pull wire for deflecting the distal end of the sheath.

12. The intrauterine access and procedure system as in claim 1, further comprising an inflatable balloon carried by the sheath.

13. The intrauterine access and procedure system as in claim 1, further comprising a mechanical distension element.

14. The intrauterine access and procedure system as in claim 1, further comprising a volume occupying device.

15. The intrauterine access and procedure system as in claim 1, further comprising a tissue penetrating assembly.

16. The intrauterine access and procedure system as in claim 1, wherein the sheath is a metal hysteroscope.

17. The intrauterine access and procedure system as in claim 1, wherein the visualization apparatus includes a shaft for advancing and retracting the visualization apparatus relative to the sheath.

18. The intrauterine access and procedure system as in claim 1, wherein the visualization apparatus includes a camera.

19. The intrauterine access and procedure system as in claim 18, wherein the camera includes one of a CCD or MEMS.

20. The intrauterine access and procedure system as in claim 18, wherein the camera includes a motion sensing element.

* * * * *

专利名称(译)	用于执行具有闭合可视化腔的妇科手术的系统		
公开(公告)号	US8840625	公开(公告)日	2014-09-23
申请号	US11/852121	申请日	2007-09-07
[标]申请(专利权)人(译)	ADAMS RONALD D GRUBER 威廉姆·H· CONNORS KEVIN 慕 PARDO GEOFFREY 乙 COLE JAMES DANIEL FLAHERTY J CHRISTOPHER		
申请(专利权)人(译)	ADAMS RONALD D GRUBER 威廉姆·H· CONNORS KEVIN 慕 PARDO GEOFFREY 乙 COLE JAMES DANIEL FLAHERTY J CHRISTOPHER		
当前申请(专利权)人(译)	HOLOGIC INC.		
[标]发明人	ADAMS RONALD D GRUBER WILLIAM H CONNORS KEVIN G PARDO GEOFFREY B COLE JAMES DANIEL FLAHERTY J CHRISTOPHER		
发明人	ADAMS, RONALD D. GRUBER, WILLIAM H. CONNORS, KEVIN G. PARDO, GEOFFREY B. COLE, JAMES DANIEL FLAHERTY, J. CHRISTOPHER		
IPC分类号	A61B17/42 A61B17/00 A61B17/02 A61B17/12 A61B17/32 A61B18/02 A61B18/14 A61B18/22 A61B19/00		
CPC分类号	A61B17/42 A61B17/12099 A61B17/12045 A61B17/12136 A61B17/32002 A61B2217/005 A61B2017/4233 A61B2019/5217 A61B19/24 A61B18/22 A61B2017/320024 A61B2017/00867 A61B18/02 A61B2017/4216 A61B17/0218 A61B2217/007 A61B18/1485 A61B2017/320028 A61B2017/00026 A61B2019/5276 A61B2017/4225 A61B18/20 A61B90/02 A61B2090/3614 A61B2090/378 A61N5/1016		
审查员(译)	NGUYEN , VICTOR		
优先权	60/852842 2006-10-18 US		
其他公开文献	US20080097468A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了用于执行改进的妇科和泌尿手术的系统，方法，设备和装置。进入护套设置有至少一个内腔和附接到其上的透镜。各种实施例使得程序能够在医院环境之外执行，例如在医生的办公室或诊所中。

